

# Criteria-based visualization design for hazard maps

Max Schneider<sup>1</sup>, Fabrice Cotton<sup>1,2</sup>, and Pia-Johanna Schweizer<sup>3</sup>

<sup>1</sup>German Research Centre for Geosciences, Potsdam, Germany

<sup>2</sup>University of Potsdam, Germany

<sup>3</sup>Research Institute for Sustainability - Helmholtz Centre Potsdam, Potsdam, Germany

**Correspondence:** Max Schneider (mschneider@usgs.gov)

**Abstract.** Probabilistic seismic hazard estimates are a key ingredient of earthquake risk mitigation strategies and are often communicated through seismic hazard maps. Though the literature suggests that visual design properties are key for effective communication using such maps, guidelines on how to optimally design hazard map are missing from the literature. Current maps use color palettes and data classification schemes which have ~~well-reported~~ well-documented limitations that may inadvertently miscommunicate seismic hazard. We surveyed the literature on color and classification schemes to identify design criteria that have empirical support for communicating hazard information. These criteria were then applied to redesign the seismic hazard map for Germany. We isolated several communication goals for this map, including essential properties about moderate-hazard seismic regions and a critical hazard threshold related to the German seismic building codes. We elucidate our redesign process and the selection of new colors and classification schemes that satisfy the evidence-based criteria. In a mixed-methods survey, we evaluate the original and redesigned seismic hazard maps, finding that the redesign satisfies all the communication goals, and improves users' awareness about the spatial spread of seismic hazard, relative to the original. We consider practical implications for the design of hazard maps across the natural hazards.

## 1 Introduction

### 1.1 Probabilistic seismic hazard analysis and maps

Earthquakes are social problems because they cause ground shaking that can destroy buildings and injure or kill people. Ground shaking due to earthquakes is referred to as seismic hazard and physical models can assess the amount of ground shaking that can be expected at any given location in a seismic region. These models are functions of parameters that describe both how frequently various earthquakes occur in the region, and the full range of ground shaking that each earthquake may ~~result~~ in cause.

In a modern probabilistic seismic hazard assessment (PSHA) aiming to capture epistemic uncertainties, parameters for these models are varied systematically to create a hazard ensemble over many model runs. The probabilistic distribution of seismic hazard values across a region is highly skewed right, owing to the low probability of high shaking; this is because larger-magnitude earthquakes (which generate higher levels of shaking) have a correspondingly lower probability of occurring. In moderate-seismicity regions, the majority of the region ~~may have hazard areas~~ has hazard that is mapped as low, with few

25 zones of higher hazard and fewer zones still of ~~extreme~~the largest possible hazard. These unlikely but ~~extreme~~highest hazard levels have a strong impact on the expected losses, in particular in urban areas. Still, damaging shaking from earthquakes may also occur (of course, with a low probability) where hazard is mapped as low.

Probabilistic hazard assessments commonly show the horizontal ground acceleration (peak ground acceleration, PGA) which is exceeded, “on average”, every 475 years (e.g., Baker et al. (2021)). This so-called “475-year return period” means that, due to the assumption that earthquakes follow a Poisson distribution, this acceleration has a 10% probability of being exceeded in 50 years. Because earthquakes are generally clustered into certain zones in a region (e.g., around fault lines), hazard varies over space and PSHA ensembles are produced over fine-scale grids across a region. The resulting seismic hazard maps depict the spatial variation of a summary, e.g., the mean, of the ensemble of hazard outcomes. These hazard maps are used by a variety of user groups, from political or economic decision-makers assessing a seismic region’s land use to civil engineers and officials responsible for creating seismic-resistant buildings. Urban seismic risk is of particular importance, as ~~highly-developed~~highly-developed urban areas have greater exposure to earthquake damages.


### 1.1.1 ~~German seismic hazard map~~

## 1.2 German seismic hazard map

In our study, we consider seismic hazard mapping for the country of Germany. The seismicity of Germany is elevated in certain regions of the country, when compared to other parts of central Europe, particularly in the southwest and along the Rhine River. In general, the seismicity is indeed low in relation to the plate-boundary regions of the Mediterranean (Grünthal et al., 2018). Still, “no part can be regarded as aseismic” (Tyagunov et al., 2006), i.e. damaging seismic events can be expected, in principle, everywhere, over a long time window. The national German seismic hazard map is shown in Fig. 1 (reproduced from Fig. 28 (middle) in Grünthal et al. (2018)). This shows the mean PGA value that has a 10% probability exceedance in 50 years, with the mean taken over 4040 model runs in the probabilistic ensemble. The PSHA described herein was accomplished on behalf of the Deutsches Institut für Bautechnik (German Institute for Civil Engineering) and was launched by the respective national committee on standardization of the Deutsches Institut für Normung (German Institute for Standardization).

The map in Fig. 1 was produced following consultations with users of PSHA products (Grünthal, 2021) but, as discussed in the subsequent sections, this map has some disadvantages. It uses a rainbow color palette, which is known to be suboptimal for visual perception, with reported psychological associations that are not appropriate for seismic hazard, and less accessible to users with color vision deficiency. The legend associates these colors with hazard levels in a way that neither groups together hazard levels that are closer together, nor spotlights ~~key hazard thresholds~~meaningful hazard values. The legend further extends to a much higher value than what is shown in this map, likely because the same legend is used to map other (higher) parts of the PSHA ensemble (see Sect. 2.2). In this paper, we solely consider single-map representations of hazard and what the research evidence supports to ~~improve design~~such maps.

Visualization of seismic hazard can be challenging due to its spatial variation and highly skewed distributions, but these issues are ubiquitous across earthquake data (Schneider et al., 2022; Bostrom et al., 2008). As a starting point for our framework



**Figure 1.** National seismic hazard map for Germany, reproduced from Fig. 28 (middle) in Grünthal et al. (2018). It shows the peak ground acceleration (PGA, in  $\frac{m}{s^2}$ ) expected at each location for a return period of 475 years, taking the mean over the probabilistic ensemble.

for hazard map design, we specified what the viewer should ideally understand after reading the German seismic hazard map. We argue that these properties are fundamental to the understanding of how seismic hazard changes across a region, for the largest variety of users. The communication goals for the map include the following four properties about the seismic hazard phenomenon:

- G1 Probabilistic seismic hazard (shaking) is not spotty but rather, changes continuously in space because of the progressive decay of seismic waves generated by earthquakes and the fact that earthquakes may occur over large areas outside well-known faults.
- 65 G2 Earthquakes and associated damaging shaking may occur even in areas where no earthquakes have historically been observed and ~~therefore where seismic shaking is rare and~~ where (probabilistic) seismic hazard is mapped as low. As such, there is no zero-hazard area on the map.
- G3 The highest end of the hazard distribution has a large impact on expected losses and ~~extreme hazard thus differs the~~ highest hazards thus differ from the preceding levels of high hazard.
- 70 G4 Spatial patterns of hazard may be more important (e.g., for situational awareness) than the specific magnitude of the hazard.

### 1.3 Visual communication for hazard maps

Beyond identifying communication goals, mapping seismic hazard requires many practical choices on how to best represent the hazard values on a map. Though the amount of literature on the visual communication of seismic hazard is far smaller than on the models thereof, previous scholars have investigated how to best map seismic hazard.

Gaspar-Escribano and Iturrioz (2011) provide a series of general guidelines they call “experience-based” regarding which hazard parameters to map and how to select colors and graphical elements for seismic hazard maps. These issues are also highlighted in Fyfe and Molnar (2020), who investigate candidate seismic hazard maps for the Vancouver, Canada metro area with a stakeholder workshop and survey. The authors identify three key factors for effective visual communication: (1) choosing the right colors and graphical properties; (2) choosing appropriate hazard metrics and classifying them into discrete intervals for the map; and (3) using accessible data formats. Similar work on flood and volcano hazard communication has designed hazard maps and evaluated them with focus groups and interviews (Hagemeyer-Klose and Wagner, 2009; Meyer et al., 2012; Haynes et al., 2007).

Complementary to these studies, Marti et al. (2019) use a large-sample online survey to study users’ preferences and ability to read information off maps ~~presenting that present~~ different seismic hazard information for Switzerland. They find that maps showing hazard via maximum expected earthquake magnitudes or intensities are less successful than traditional hazard maps showing, e.g., PGA. They conclude that this is because those alternate maps fail to follow best practices related to color and data classification, but do not explain precisely what would improve them. Thompson et al. (2015) use both semi-structured interviews and a survey with stakeholders to test different designs for volcanic hazard maps in New Zealand. They find that

90 participants both prefer and have higher map-reading accuracy with maps where data is classified into discrete intervals, and that changing the color palette can change the hazard level perceived for a given location, as also found for tornado hazard maps by Miran et al. (2017).

A common finding across previous research is the importance of colors and data classification in how hazard maps are used and interpreted. But authors omit specifics of how and why to make particular design choices, typically citing so-called  
95 “best practices” used in their hazard maps without evidence (Hagemeyer-Klose and Wagner, 2009; Meyer et al., 2012; Fyfe and Molnar, 2020; Marti et al., 2019). Indeed, Thompson et al. (2015) summarize the state-of-the-art for hazard map design: “fundamental choices for color scheme ... and data classification are largely driven by subjective preference.” The problem is that suboptimal choices for either aspect may lead to distortions in how hazard is understood, especially by non-scientific users (Evans, 1977; Ware et al., 2018; Dasgupta et al., 2018). There is a research gap in identifying the key criteria that should guide  
100 these essential decisions in designing a hazard map.

#### 1.4 Criteria-based hazard mapping

A vast body of literature exists on color palettes and data classification schemes, both generally for general uses and specifically for natural hazards. Theoretical work has provided frameworks for considering both map elements. For example, color models can parametrize all colors into distinct-distinct dimensions, which can help isolate which aspects of color may be most critical  
105 for a hazard map. Similarly, scholars in cartography have proposed various methods of classifying data to produce discrete maps, to theoretically optimize how data is grouped for maps.

Research in these fields have has further studied what empirical effects different design decisions have on how well users can read and use the corresponding visualizations-maps (Bostrom et al., 2008; Kinkeldey et al., 2017). In controlled experiments, users perform tasks that elucidate whether or not a design choice can produce maps that are not merely properly read, but  
110 also properly understood. Such empirical evaluations can estimate the effects that a given design choice has on map-reading and perception. We use this literature to isolate which criteria can facilitate effective colors and data classification for seismic hazard maps.

We then apply these criteria to redesign the German seismic hazard map in Fig. 1. Since several candidate maps are consistent with the color and classification criteria, we decide between them using the four target properties of hazard we seek  
115 to communicate (see Sect. 1.1.1.2). We thus heed the call of previous authors to design maps that satisfy clearly-specified clearly-specified communication goals (Dransch et al., 2010; Thompson et al., 2017). We then rigorously evaluate our redesigned map against the baseline map to investigate how well users can read and understand seismic hazard from the two maps. In detailing our design and evaluation process, we attempt to provide a blueprint for future hazard map designers.

#### 1.5 Research aims and contributions

120 This work seeks to fill the research gap in systematizing how to select colors ,classification-schemes-,and-other-key-features and classification schemes for hazard maps. We collect evidence-based practices from the color, visualization and cartographical literatures, identifying criteria that are supported by empirical experiments. Our proposed method for hazard mapping

is centered around not only following research-backed design criteria, but also in meeting communication targets about the hazard phenomenon.

125 We showcase this method with a case study for the German seismic hazard map. We redesign the original hazard map, following the specified criteria and making design choices to highlight the key properties of seismic shaking we wish to communicate. We then evaluate the redesigned map with a controlled mixed-methods survey, using questions for not only map-reading but also hazard perception, which should be a primary objective of visual communication ~~Dransch et al. (2010); MacPherson-Krutsky et al. (2010)~~ [\(Dransch et al., 2010; MacPherson-Krutsky et al., 2020\)](#). The perception questions in our evaluation survey are directly linked  
130 to the key properties we wish to communicate.

The research questions we seek to address are as follows:

1. How can the design of seismic hazard maps be improved to both follow evidence-based practices and to aid the visual communication of key points about seismic hazard?
2. How well can a hazard map, redesigned for better visual communication, be read and interpreted by a technical audience?  
135 How does this compare to the previous (baseline) map?

## 2 Methods for selecting colors and classification schemes

### 2.1 Color: Literature review and best practices

Color is a critical visualization variable because “it is considered pre-attentive, meaning that information is extracted by the eye intuitively and rapidly” (Sherman-Morris et al., 2015). It is also an expressive and associative variable, with different colors  
140 producing different connotations (Itten, 1961). As such, care must be taken to select color palettes in hazard maps. There are well-evidenced criteria for selecting optimal colors for a palette and avoiding those colors that can lead to misinterpretations or unintended perceptions. For each criterion, we review the empirical literature that shows how ignoring it may endanger user understanding of data visualizations, including hazard maps.

To introduce key color issues, we use a color model, which expresses every possible color with a set of distinct variables  
145 (usually three). In the Hue-Saturation-Lightness (HSL) model, any color can be specified using values for Hue (0-360, representing the color’s position on the color wheel), Saturation (0-100, where increasing values correspond to more intense and deep versions of the color) and Lightness (0-100, where increasing values correspond to lighter versions of the color, with 0 yielding pure black and 100 pure white). Many other color models exist that separate the color’s luminance from the color’s hue and its intensity, e.g., the Hue-Saturation-Brightness model and the CIE-LUV model (Zhou and Hansen, 2015). Although  
150 more sophisticated color models have certain benefits (e.g., the CIE-LUV model transforms the color space such that lightness increases in non-linear ways, which is closer to how the human eye perceives it), we use the simpler HSL model throughout this paper, as it is sufficient to describe the key color criteria we propose for hazard maps.

In ~~an important study proposing~~ a typology for color palettes, Bujack et al. (2017) posit that the perceptual order of the colors is a fundamental requirement when colors are to be compared ~~,echoing many~~ [\(as in hazard maps\), echoing](#) earlier

155 authors (e.g., Tajima (1983); Trumbo (1981)). Colors may be ordered by their value on variables within the color model (for example, hue, lightness and saturation); it is desired for a palette's perceptual order based on any color variable to be the same as its order based on data value. It has been shown [in user experiments](#) that changes in color lightness are the primary driver of human perception of color differences, with hue being a secondary driver (Spence et al., 1999; Kindlmann et al., 2002). ~~Many~~ [Previous](#) authors (e.g., Thyng et al. (2016); Light and Bartlein (2004)) have argued that a monotonic increase in the lightness  
160 of the colors is required for a perceptually-ordered color palette. Empirical experiments have found that unordered palettes in maps can lead to inaccurate map-reading (Dasgupta et al., 2018) and more difficulty in selecting between real map features (Rogowitz et al., 1999).

Another key aspect of a successful color palette is perceptual uniformity, in which unit increases in data value correspond to unit increases in the perception of change between colors, consistently across the entire color palette ([Bujack et al., 2017](#); [Crameri et al., 2020](#)).  
165 . To achieve such a uniform perception of color differences throughout a map, authors have argued for not simply monotonic but linear progressions in color lightness across the entire palette (Robertson and O'Callaghan, 1986; Tajima, 1983). A palette that is not perceptually uniform can lead to perceptual distortions, with small data differences in one end of the palette being perceived differently than corresponding data differences at the other end (see Fig. 4 of Crameri et al. (2020)). Such a non-uniform reading of ~~the colors data~~ was found in Ware et al. (2018); ~~where;~~ [in an experiment](#), participants had to detect background patterns in maps with [color-different color palettes](#). [When using](#) palettes ~~that either had linear progressions in lightness (perceptually uniform) or not. The authors found that in palettes~~ where lightness changed non-linearly ([not perceptually uniform](#)), participants detected ~~the these~~ patterns worse for colors in the center of the palette, ~~and especially when using.~~ [The problem was worse for](#) the rainbow color palette, ~~which is known to not be perceptually uniform (see Sect. 3.3).~~

A third critical dimension spotlighted by numerous authors is color discriminability (Bujack et al., 2017; Rheingans,  
175 2000). For users to correctly interpret a color map, colors indicating important differences in data value should be [separable distinguishable](#) from one another, both in the map and its legend (Trumbo, 1981). Definitions for color discriminability have been proposed based on perceptual difference (i.e., difference in lightness or other color variables) (Maxwell, 2000; MacAdam, 1942) or how colors are identified by color names (Gramazio et al., 2016). Discriminable palettes have been associated with unit increases in both the hue and lightness profiles of a color palette (Trumbo, 1981). ~~In a user experiment,~~ Gramazio et al.  
180 (2016) found that palettes with optimized discriminability were superior to default palettes from oft-used software, as they often led participants [in their experiment](#) to more accurately identify which half of a map contained a reference color; participants also consistently preferred the palettes optimized for discriminability.

Colors should also be chosen that have psychological associations that befit the phenomenon being mapped. A body of empirical literature suggests that colors have consistent associations across individuals, which may be culture-specific (Wang  
185 et al., 2014). Typically, these studies ask participants to link a list of emotions or experiences with a set of colors. In many Western cultures, blue is "often associated with openness, peace, and tranquility" (Mehta and Zhu, 2009) and blue and green have been found to have "the qualities of being comfortable and soothing" (Clarke and Costall, 2008). On the other hand, red hues have been found to be associated with dangers and risks within Western cultures, while yellows are associated with caution and warning (Griffith and Leonard, 1997), which has been found to persist across [both](#) Western and Asian cultures (Or

190 and Wang, 2014; Chan et al., 2003). In a user experiment, Lin et al. (2013) found quicker responses on a chart-reading task when charts were colored using “semantically-resonant” colors that respected common [Western](#) associations rather than colors that did not, especially when the data being presented was more “colorable”, i.e., had a larger degree of color associations.

Finally, colors should be chosen based on principles of accessibility and inclusion, including for those audience members with color vision deficiency (CVD), or the inability to differentiate between certain colors. About 8% of males of European  
195 Caucasian ancestry suffer from some CVD; in other populations, the prevalence is lower but still non-trivial (Birch, 2012). The most common forms of CVD are deuteranomaly and protanomaly (red-green [colorblindnessblindness](#)) in which reds and greens of equal lightness are both seen as an identical shade of dark yellow (see Fig. S1 in the Supplement). People with this CVD can misread maps using the wrong color palettes. In Olson and Brewer (1997), participants with red-green blindness could read off colors and features in maps significantly better when using color palettes that were CVD-friendly (monotonically  
200 varying in lightness and avoiding red/green combinations) vs. -unfriendly (varying in hues and lightness with red and green together).

### 2.1.1 Criteria for selecting color palettes

The literature on which color aspects are critical for effective visual communication has not been lost on other geoscientific communities. Stauffer et al. (2015) discuss color concepts for heat maps common in meteorology, pinpointing the importance  
205 of differences in lightness across the palette and appropriate color conventions. Thyng et al. (2016) provides color guidelines and palettes for oceanography, spotlighting perceptual uniformity, cultural implications, and colorblind-friendliness as key criteria. Horton et al. (2020) proposes a “perception-informed color palette” for heat maps for avalanche science, optimizing it to be accessible for various CVDs. Expanding on this literature, we propose the following five critical criteria for consideration when choosing colors for hazard maps. While we do not claim these criteria are either sufficient or minimal for hazard map  
210 design, they align with lists and typologies published elsewhere; see e.g., Thyng et al. (2016); Bujack et al. (2017); Schloss et al. (2018).

- C1 **Perceptual order**: colors in the color scale should follow a natural, intuitive progression.~
- C2 **Perceptual uniformity**: the perception of difference between adjacent color levels should be uniform across each adjacent pair of colors.~
- 215 C3 **Discriminability**: colors in the color palette should be distinct and immediately discernible by most users, in both the map and legend.~
- C4 **Appropriate associations**: color associations should be relevant to the data being mapped, based on culturally-specific associations reported in the literature.~
- C5 **Accessibility**: colors should be readable and discriminable across the population, e.g., for users with CVD.~



## 220 2.2 Classification schemes: literature review and best practices

The seismic hazard values plotted on any hazard map take a continuous distribution. In order to map them using a discrete color palette, we need to select a classification scheme, or a procedure for classifying the continuous distribution into a set of distinct intervals that get assigned to a color. There are numerous approaches for this problem and we review the statistical and cartographic solutions in the literature.

225 Earlier work in cartography has largely advocated for mapping continuous variables with a discrete set of colors, rather than a continuous color palette spanning the data range. Many authors have argued that it is more difficult for users to accurately discriminate colors and read values off continuous maps (Dobson, 1973; Kennedy, 1994), though this has been debated in the literature (Tobler, 1973; Muller, 1979). Still, discrete maps are ubiquitous for depicting natural hazards, especially for public communication (Quinan and Meyer, 2015). The utility of discrete maps has been studied with perception tasks in user  
230 experiments. In Padilla et al. (2016), participants saw elevation maps using either continuous or discrete classification schemes and were more error-prone with the continuous map compared to the discrete maps, particularly for tasks requiring a steepness judgment. Marti et al. (2019) also found that participants had complaints about the continuous color scale the authors used in their seismic hazard maps and suggested that a discrete map would be more effective, as was echoed by Fyfe and Molnar (2020).

235 Classification schemes can thus lead to better reading and interpretation of hazard maps. The first step for many classification schemes is to consider the number of categories, and thus colors, that will be used in the map. Some authors have suggested that between five and seven categories can be well-distinguished, with their meanings remembered (MacDonald, 1999; Miller, 1956), based on principles of level-of-detail management and cartographic generalization (Çöltekin et al., 2017). Still, the effects of the number of categories in discrete maps on, e.g., hazard or risk perception has yet to be empirically studied. We  
240 thus posit that the optimal number of categories is determined by the distribution and patterns of the data being mapped, as well as other map-specific features. Because it is difficult for map users to discern too many an overabundance of categories, as described above, it is critical that discrete maps use only so many categories as can completely convey the important patterns in the data.

The map designer must also select between numerous available classification methods. The most basic approaches evenly  
245 split the data distribution into either equal intervals or equal quantiles (that is, equal probability mass). While such approaches may have the advantage of appearing conceptually straightforward, they ignore the characteristics of the data being plotted, e.g., skewness, multimodality or spatial clustering. In particular, these schemes group together data into classes based on an arguably arbitrary criterion (equal class width resp. equal number of data points for the equal intervals resp. quantile-based schemes). This may distort the map, depicting patterns that do not exist in the data, rather than highlighting those that do  
250 (Evans, 1977).

Authors have proposed other solutions that split a dataset into classes based on more rigorous quantitative criteria, such that values assigned to a class are more alike than those between separate classes. The most common classification approach used today was proposed independently in the statistical (Fisher, 1958) and geographical literature (Jenks, 1967), and has become

widely adopted. Given a fixed number of classes, the Fisher scheme attempts to find the split of the data that minimizes the variance of points within each class. The resulting breaks (also referred to as natural breaks and common across geographic information systems) have (1) optimally grouped data points together and (2) split data points apart that are sufficiently dissimilar. Other classification approaches attempt to, e.g., fit statistical parameters onto the dataset or prioritize spatial contiguity in the resulting map; see typologies of classification methodology in Evans (1977) and Armstrong et al. (2003). Techniques also exist for right-skewed data, such as the Head-Tails scheme (Jiang, 2013), where the dataset is first split at its mean into its “head” and its “tail”, which contains the data’s long skew. The tail is again split at its mean and this procedure continues iteratively, until some stopping point is reached (see examples in Jiang (2013) and Jiang et al. (2013)); the split points from each step of the procedure (mean of that step’s tail) comprise the class breaks.


The algorithmic classification schemes discussed above do not consider whether some data values may carry particular meaning, as they depend solely on the distribution rather than the context of the data. However, authors have discussed forming class breaks around meaningful values, e.g., using 50 percent as a class break when mapping voting results between two parties to symbolize the winning party, regardless of the ~~distributions~~ distribution of voting results (Brewer and Pickle, 2002). Evans (1977) advocates that such “class limits will be used in the few instances where they are available.” Though no literature exists to compare such pre-selected meaningful class breaks against algorithmic alternatives, we posit that including breaks known to carry particular meaning can be beneficial to hazard communication.

### 2.2.1 Criteria for selecting classification schemes


Some previous studies in the natural hazards have compared different schemes ~~based on different kinds of~~ by studying their misclassification errors (e.g., Cantarino et al. (2019) compares Fisher, Head-Tails and several other schemes for landslide susceptibility maps). To our knowledge, there is no previous literature on how classification schemes affect risk or hazard perception in users, neither for natural hazards nor other topics. This research gap means that, unlike colors, factors beyond experimental evidence must be used to select between classification schemes. Based on the literature surveyed, we propose the following three criteria as critical for selecting a classification scheme for hazard maps.

- L1 **Likeness:** the classes in the classification scheme should contain all data that are alike, based on a quantitative measure, and should break apart data that are not alike.
- L2 **Sufficiency and completeness:** there should be enough (but not too many) scale breaks in order to be able to immediately see the primary patterns in the data.
- L3 **Signification:** scale breaks should ideally signify meaningful values or changes in the distribution, rather than arbitrarily selected values.

## (a) Baseline map



## (b) Redesigned map



**Figure 2.** Classification schemes (left) and color palettes (right) for the baseline German seismic hazard map (a; see Fig. 1) and the redesigned version (b; see Fig. 4), following the criteria described in Sect. 2. Lightness and hue profiles indicate the extent to which the color palettes follow [the several criteria given in Sect. 2.1.](#)

### 3 Application to German seismic hazard

In this section, we apply the criteria and concepts introduced in [the previous three sections Sect. 2.1 and 2.2](#) to redesign the  
285 German seismic hazard map presented in Fig. 1.

#### 3.1 Hazard analysis and issues for Germany

Seismic hazard in Germany is spread across several regions, particularly the Hohenzollerngraben region (near Albstadt), the Rhine valley (near Aachen), and in contours surrounding these regions across central-western and southwestern Germany. There is also an elevated hazard zone in eastern Germany, east of Chemnitz. Basics of the tectonic and structural geological  
290 rationale behind the development of the PSHA model are provided in Grünthal et al. (2018). Seismic building standards for Germany are required for ordinary structures ([but only where seismic hazard is sufficiently high, i.e., not those, above a PGA threshold of  \$0.4 \frac{m}{s^2}\$](#)  (for essential infrastructure, e.g., dams or nuclear power plants, [for which stricter standards apply](#)) [but only where seismic hazard is sufficiently high, i. e above a PGA threshold of  \$0.4 \frac{m}{s^2}\$](#) . This value thus became a critical threshold in our hazard map redesign (see section 3.2). Although it stems from a specialist user group, we posit it will be useful for all users  
295 to distinguish “non-significant” hazard ( $PGA < 0.4 \frac{m}{s^2}$ ) from the rest of the hazard distribution.

### 3.2 Choosing the classification scheme


We first chose a classification scheme to represent the continuous distribution of mean PGA in a discrete map. The baseline classification scheme (see Fig. 1) covers a larger range than the values plotted in the map, likely because the legend is intended to cover a wider span of the PSHA ensemble than just its mean (see Fig. 25 in Grünthal et al. (2018) that uses the same legend to represent a larger range of values). It is furthermore the legend used for an interactive web portal [showing-which-shows](#) extreme percentiles from the German seismic hazard assessment (GFZ). As we are solely interested in a static single-map representation of seismic hazard (i.e., one that may be used in news media or reports for decision-makers), we limit our scale to only those values in the mean PGA map.

The baseline map uses a modified equal-interval scheme with round decimals, where the interval increases with increasing PGA. While this may seem a straightforward approach, the breaks chosen do not meet the criteria listed in Sect. 2.2. In particular, they do not carve out similar hazard levels into separate classes using the underlying data (criterion L1); they are moreover chosen based on other data not shown in this plot (lower and upper percentiles of the PGA distribution), rather than the data being mapped (mean PGA, see Sect. 1.1). The baseline scheme also has 16 categories, which is far above the literature-backed rule of thumb detailed in Sect. 2.2. Failing to consider sufficiency (criterion L2) in favor of including extra detail comes with the additional need to assign the excess of classes to colors, many of which are difficult to distinguish from one another (color criterion C3). Finally, these breaks fail to communicate meaningful hazard values (criterion L3) as they are arbitrarily chosen round intervals, which are unrelated to the key thresholds of seismic hazard in Germany.

We developed a new classification scheme that meets our three pre-specified criteria for classification. We first split the distribution of hazard values into “lower” and “higher” classes based on the critical value of  $0.4 \frac{m}{s^2}$ , the hazard level at which seismic building standards must be applied in Germany. The hazard values below  $0.4 \frac{m}{s^2}$  (the “lower” part) were split into three classes and the values above  $0.4 \frac{m}{s^2}$  (the “higher” part) were split into five classes, for a total of eight classes. In each part, we used the Fisher classification scheme (satisfying criterion L1), as implemented in the `classIntervals` function in the `classint` package in R (Bivand et al., 2020). Our classification thus communicates a critical value that splits seismic hazard for Germany, satisfying criterion L3. Unlike in the baseline map, the redesigned classification scheme was capped at the maximal value for the mean PGA data being mapped (criterion L1).

We also experimented with several other classification schemes. We first considered different numbers of classes, and created maps with 5-9 total classes, split in several ways between the “lower” and “higher” parts of the distribution. We settled on the split shown in Fig. 2, as this was the smallest number of classes in each part that sufficiently represented the spatial patterns of hazard across Germany (criterion L2). This also aligns with property [4-G4](#) of our communication goals regarding keeping spatial patterns salient (see Sect. [1.1.1.2](#)).

Since seismic hazard follows a long-tailed distribution, we also considered the Head-Tails scheme on the “higher” part, stopping the algorithm at the step when its tail did not contain at least 40% of the full set (see Fig. S2 in the Supplement). This broke the high-hazard values into eight classes. Only southwestern Germany had a noticeable difference in the depiction of hazard, as this is where the [most-extreme-highest](#) hazard is located. Fig. 3 shows that the Head-Tails scheme used [many](#)



**Figure 3.** A closeup of southwestern Germany for the seismic hazard maps made using the Fisher class breaks (a; see Fig. 4 for the full map) and the Head-Tails class breaks (b; see Fig. S2 in the Supplement for the full map).

330 four more classes to depict this steep increase in hazard, relative to the Fisher scheme. As one of our communication goals is to avoid hazard appearing concentrated in space (properties 1 and 2-G1 and G2 of our communication goals), we opted against the Head-Tails scheme. We also experimented with a-quantile-an equal-quantile classification scheme (see Fig. S3 in the Supplement) as this was preferred by a single empirical study we found [Brewer and Pickle, 2002] but opted against this as it flattened the distinction-between-high-and-extreme-hazard-visual distinction between hazard values at the top of the  
 335 distribution, violating property 3-G3.

### 3.3 Choosing the color palette

We attempted to improve on the rainbow color palette, which is commonly used for seismic hazard (Fig. S4 in the Supplement shows several other published seismic hazard maps, all employing a similar color palette). Despite the ubiquity of the rainbow palette (Borland and Taylor, 2007; Westaway, 2022), scholars have long described why it is in fact “unscientific” (Cramer et al., 2020), particularly for hazard maps. The hue and lightness profiles of Fig. 1’s rainbow palette are given in Fig. 2 and this  
 340 sheds light on why it fails to meet the five criteria isolated in Sect. 2.1:

- Neither the lightness nor hue profiles are monotonic, meaning that it is not perceptually ordered (criteria C1).
- The lightness profile is non-linear, meaning that it is not perceptually uniform (criteria C2).
- Many of the colors, especially at the upper end of the scale, are non-discriminable, possibly because they have-such  
 345 cover a limited range of hues (criteria C3).
- The palette uses blue and green shades that are commonly connoted with peaceful, tranquil and soothing associations in Western cultures, which are not appropriate for a hazard map (criteria C4).

- The palette combines reds and greens, making it not CVD-accessible ([criterion C5](#)).

The rainbow palette's lightness profile (see Fig. 2) leads to further problems, as pinpointed by other authors. When used in maps, this palette can cause the appearance of "false gradients introduced by a non-monotonic lightness profile, which accelerates at a different rate than the data it represents" (Thyng et al., 2016). The result is that map subregions may appear to be of nearly identical color and then sharply transition to another color. This can falsely be interpreted by viewers as a real gradient in the data, which "actively misleads the viewer by introducing artifacts to the visualization" (Borland and Taylor, 2007).

To address these issues, we selected a new color palette following the five criteria given in Sect. 2.1. We began with a Yellow-Orange-Red color scheme with eight colors (Yl-Or-Rd-8) from RColorBrewer, an evidence-based palette tool (Harrower and Brewer, 2003). This color palette is known to be accessible to people with the most common forms of CVD, as it does not combine red and green (criterion C5). Yl-Or-Rd-8 also has a monotonic progression of both lightness and hue, thus allowing a single intuitive perceptual order (criterion C1); it can also be modified to optimize discriminability (criterion C3) and for linear jumps in lightness and hue, creating perceptual uniformity (criterion C2). Furthermore, Yl-Or-Rd-8 has clear cultural connotations in Western cultures that begin with caution and preparation (yellows) and rise to danger and risk (reds) (criterion C4). This palette has furthermore been supported to depict different degrees of hazard by literature reviews (Bostrom et al., 2008), focus groups (Fyfe and Molnar, 2020), user experiments (Miran et al., 2017; Thompson et al., 2015) and guidelines for science communication (Doore et al., 1993; Haynes et al., 2007).

We chose three shades of yellow for the first three colors (see Fig. 2). Lightness and hue progressed in even jumps from the lightest shade of yellow that was visible on a white background (as in the legend) to the darkest shade of yellow produced by the Yl-Or-Rd-8 color scheme. This was to associate the first three scale breaks with caution, as these correspond to the "lower" part of the distribution. For the next five colors (the "higher" part of the distribution), we made exactly even jumps in both lightness and hue (criterion C2) between the final yellow color and a dark red color produced by the Yl-Or-Rd-8 scheme. We found that this led to several shades of red that were difficult to differentiate and we manually adjusted the color lightness and saturation until the colors were judged to be discriminable (criterion C3), while maintaining the same color order in both hue and lightness (criterion C1). We then modified the final color's hue to diverge slightly from the Yl-Or-Rd-8 palette, in order to highlight how the extreme-highest end of the hazard distribution differs from the high hazard preceding it (property 3-G3 of our communication goals, see Sect. 1.1.1.2). We chose a shade of dark brown that preserves perceptual order, uniformity and discriminability of the overall color scheme, while maintaining relevant color connotations and colorblind-friendliness.

### 3.4 Choosing the legend and annotations

Finally, we also experimented with different legend types and map annotations, which also have a (limited) base of empirical literature. The baseline map positioned its legend under the map, possibly because it was part of a set of three maps. In our redesign, we follow traditional cartographic style and position the legend on the right side of the map, which Edler et al. (2020)

380 has shown can lead to faster processing of the map. We follow Li and Qin (2014) in aligning the position of the color patches and labels and having a larger spacing between the label and its color patch than between color patches.

We further added several layers of annotation to the redesigned hazard map. We marked key cities in Germany, either with a land area above 65 km<sup>2</sup>, or that were in important hazard zones. We marked each city with a polygon showing its boundaries rather than a single point positioned at its geographical center. This followed internal evaluation (see Sect. 4 and Supplement 385 S6) and spotlights how urban seismic hazard can span multiple hazard levels in many German cities. We added labels for each city, printed in black where the background color was sufficiently light, and white where the background color was too dark (Albstadt), following recommendations from Brychtova and Çöltekin (2016). We considered labeling contours corresponding to important hazard values but ultimately omitted these (see Supplement S6).

#### 4 Evaluating redesigned seismic hazard maps


390 We tested the redesigned German seismic hazard map in a two-phase evaluation. We first created multiple prototypes that differed on certain features (e.g., the classification scheme or how cities were marked on the maps) and solicited structured feedback from seismic hazard experts. This is described in Supplement S6. The expert feedback helped us finalize a single redesigned map (see Fig. 4) which, in the second phase, we compared to the baseline map with a controlled user survey focusing on the users' awareness of the four seismic hazard properties and one critical threshold.

##### 395 4.1 Participants and design

For the user survey, we recruited early career researchers in the natural and engineering sciences from universities in Germany where the authors are affiliated. The participants had some expertise in geosciences or engineering but not necessarily in seismic hazard, which is similar to many of the technical users of hazard maps. We developed the survey in the survey platform Qualtrics and then invited these researchers to evaluation workshops, in which they completed the survey and we then presented 400 the research behind the [redesignredesigned map](#). Invited researchers were also able to take the online survey at a later time during a fixed period. 43 individuals began the survey and five did not complete questions for both maps, meaning they were excluded from analysis. Another participant did not provide responses to the open-ended and demographics questions, but was still included in the other analyses. The final sample included 38 participants (42.1% female, median age of 30).

We pre-registered the survey and analysis plan in the Open Science Framework 405 ([https://osf.io/puerc/?view\\_only=2b747decfbfb4093a9e925e5fe09cd48](https://osf.io/puerc/?view_only=2b747decfbfb4093a9e925e5fe09cd48), last access: 10 October 2022). The study was approved by the Institute for Advanced Sustainability Studies (IASS) ethics ombudsperson following the IASS procedure for ethics approval.

Participants began by reading a basic explanation of PSHA and what seismic hazard maps show. They were asked to use only the given map to answer the question, rather than any other maps or background knowledge. After providing informed 410 consent, they answered map-reading and hazard perception questions first with one map and then with the other (within-participants design), with the map order randomly assigned. We developed two equivalent versions of each map-reading and



**Figure 4.** Redesigned German seismic hazard map fulfilling evidence-based criteria for color (see Sect. 2.1) and data classification (see Sect. 2.2).



hazard perception question, and the question version was also assigned randomly ~~so~~ and such that no question would be repeated on both maps.

Map-reading questions asked participants to read off the maximum hazard level for a given city. Participants answered three  
415 of these questions for each map, and their responses were scored for accuracy. Hazard perception questions were designed  
around the four hazard properties (see Sect. ~~1.1~~ 1.2). For each property, we posed a statement about a city or pair of cities on  
the map and asked for the participant's level of agreement, on a seven-point scale with the following labels: "Strongly disagree",  
"Disagree", "Slightly disagree", "Neither agree nor disagree", "Slightly agree", "Agree", "Strongly agree". Cities were chosen  
such that agreement with the statement indicated an awareness of that hazard property. For example, for property ~~1~~ G1 (seismic  
420 hazard is not spotty, it changes continuously over space), participants marked their agreement with the statement: "Damaging  
shaking may be expected in Düsseldorf, according to the map" (Düsseldorf is in a zone of moderate hazard, contouring off a  
high-hazard zone near Aachen and thus, could expect damaging shaking). The full set of evaluation questions is provided in  
Supplement S7.


We also asked for participants' perception on whether particular cities needed seismic-resistant design for ordinary buildings.  
425 The aim was to see whether our redesign could sufficiently communicate the critical threshold of  $0.4 \frac{m}{s^2}$  without needing to  
provide this explicitly. We asked about two sets of cities: those we expected to be simple (at extreme ends of the scale) or  
difficult (in the middle of the scale).

~~Since there are no "correct answers" to~~ While these perception questions ~~, we have no "correct answers," we associated~~  
awareness of the hazard property with agreement with the statement. We then simply analyzed the within-participant differ-  
430 ences in response between the two maps to see if either map improved hazard awareness. Our inferential analysis for both  
map-reading and hazard perception compared these map differences (within-participant) to zero, using the Wilcoxon signed  
rank test, a non-parametric extension of the paired-samples *t*-test. Given the discrete nature of this data, we used the Pratt  
correction for ties [Pratt, 1959]. We set the significance threshold to 5% and accounted for multiple testing with the Bonferroni  
correction.

435 After completing the map-reading and hazard perception questions for both maps, the participants answered three open-  
response questions. We asked for ~~feedback on their~~ participants' preference between the two maps and reasoning behind this,  
what they would change about either map to make it more useful and which evaluation questions they found difficult. We used  
a systematic and intersubjectively verifiable approach to qualitatively analyze participant responses. After individually reading  
through all responses, we identified a set of distinct themes that could characterize the content in each response. We allowed  
440 each response to be categorized by one or more themes and studied the frequency and meaning of the theme categories. Finally,  
we asked for participants' demographics (age, gender, nationality) and academic background (university, discipline of study)  
to explore potential relationships between these and map effects.

## 4.2 Evaluation results

The first set of questions targeted how accurately participants could read values off the two maps. The majority of participants  
445 could accurately read most cities off both maps (see Fig. S5 in the Supplement), with participants averaging 71.9% correct with



**Figure 5.** Participant responses for hazard perception questions, under each map. Questions related to each hazard property (see Sect. 4.1.1.2) and the seismic building code threshold. Agreement responses (colored with greens) indicate awareness of the hazard principle/threshold. See Supplement S7 for the set of hazard perception questions.

the baseline and 77.2% with the redesigned maps. The maps were statistically indistinguishable in how accurately participants read them ( $p=0.4835$ ).

We then estimated how each map affected perception of the hazard properties, see Fig. 5. The first property was that seismic hazard is not spotty but rather changes continuously in space. There was greater agreement with the statements **asked for** 450 **related to** this property for the redesigned map (81.6% “in agreement”, or selecting one of the three “agree” options), than for the baseline map (36.8% in agreement). The 95% confidence interval (CI) for the difference in response between the redesigned and baseline map was entirely positive, meaning that the redesigned map significantly improved awareness of this hazard property ( $p=0.000019$ ). The second property was about seismic hazard being possible even in areas where hazard is not mapped as high. We again found that participants agreed with the corresponding statements more for the redesigned map 455 (89.5% in agreement), than for the baseline map (60.5% in agreement). The 95% CI for the participant-specific difference between maps was always positive, so participants showed significantly ( $p=0.0013$ ) more awareness of this property using the redesigned map.

The differences between the maps were smaller regarding perception of the other hazard properties. Both maps facilitated understanding of the third property (**extreme-highest** hazard differs from high hazard), with the vast majority responding 460 “Agree” or “Strongly agree” across both maps. The 95% CI for this difference contained zero, meaning the difference was

not statistically significant ( $p=0.014$ ), when accounting for multiple testing. Both maps also equivalently conveyed the fourth property (spatial patterns of hazard are more meaningful than the hazard values), meaning that the difference in response for these questions was not statistically significant ( $p=0.53$ ).

We also asked several questions about whether certain cities were perceived to need seismic building codes due to their hazard level. The difference between maps was negligible for cities where this question was more straightforward (Albstadt and Leipzig, both at extreme ends of the scale). Both maps led participants to correctly perceive that Albstadt requires building codes and Leipzig does not (78.9% of participants in agreement for the baseline map and 81.6% for the redesigned map), so the 95% CI for this map difference crossed zero ( $p=0.76$ ). For cities where this distinction was less clear (Freiburg, which requires building codes; Frankfurt, which does not), there was a slight difference between maps. The redesigned map led participants to more often make interpretations consistent with the actual building code (65.8% consistent with the building code), compared to the baseline map (34.2% consistent), though the within-participant difference was marginally insignificant ( ~~$p=0.046$~~ ) when accounting for multiple testing ( $p=0.046$ ), with its 95% CI containing zero.

	Theme	Baseline	Redesign
	Color features (discriminability, perceptual uniformity, etc.)	50.00	37.04
	Communication of hazard and risk (e.g., critical hazard values)	3.85	18.52
	Communication of high <del>/extreme</del> hazard levels	0.00	11.11
	Color associations/conventions	23.08	7.41
	Issues with data classification	7.69	11.11
	Issues with upper end of data scale	11.54	7.41
	Other	3.85	7.41
	Total	100	100

**Table 1.** Themes referred to by participants when describing their preference between the baseline and redesigned maps and the proportion of ~~responses that mentioned each times the~~ theme was mentioned across responses.

We then qualitatively analyzed feedback questions, seeking to identify the recurring themes across responses. The first feedback question asked participants for their preferred map and the reasons why. While 52.6% of the participants preferred the redesign map, 31.6% preferred the baseline and 15.8% did not indicate a single preference. Despite different preferences, color features (discriminability, perceptual uniformity, etc.) were most commonly mentioned by both groups (see Table 1). For example, a participant who preferred the baseline map found it “easier to discriminate between different colors than different tones of red” and a different participant who preferred the redesigned map said “it more clearly implies a continuous increase in danger”. Participants who preferred the redesign also reported a greater range of reasons, e.g., commonly addressing either critical or ~~high/extreme~~ particularly high hazard levels. For example, one participant found that with the redesign, “it is easier to identify where the most exposed areas are located.”

Responses to the other feedback questions were more similar between participants that preferred one map over the other. Regarding which aspects of the map could be improved, participants commonly brought up classification breaks needing to

be meaningful or interpretable; for example, a participant asked “which PGA could really affects constructions [sic] or be of potential threat to anyone/anything?”. Participants also mentioned that the double legend labels were difficult to interpret. There was an even spread in issues participants reported having with the survey, though Nearly half of the participants (47.4% of participants reported-) reported having no issue with the survey, and the issues that were reported were evenly spread across participants. Problems that were mentioned by multiple participants included not understanding thresholds corresponding to the building code questions and-or-or the wording in some questions, such as what “damaging shaking” means.

	Baseline	Both	Redesign
Female ( $n = 16$ )	37.50	6.25	56.25
Male ( $n = 20$ )	25.00	25.00	50.00
Younger (Age < 30, $n = 17$ )	35.00	25.00	40.00
Older (Age $\geq$ 30, $n = 20$ )	29.41	5.88	64.71
German ( $n = 9$ )	22.22	22.22	55.56
Non-German ( $n = 27$ )	37.04	14.81	48.15
University of Potsdam ( $n = 19$ )	26.32	26.32	47.37
Not at University of Potsdam ( $n = 19$ )	36.84	5.26	57.89
Geosciences students ( $n = 12$ )	50.00	16.67	33.33
Engineering students ( $n = 21$ )	23.81	14.29	61.90
All ( $n = 38$ )	31.58	15.79	52.63

**Table 2.** Preferences between the baseline and redesigned maps, split by subgroups on the person-specific variables. Some participants responded that they liked both maps, without a clear preference between them. Note: two participants did not specify their gender and five participants did not identify as a geoscience or engineering student.

We found that demographic and academic characteristics largely did not influence any of the reported map effects. Due to the small sample size, we examined these characteristics as binary variables, splitting participants by gender (male or female), age (younger or older than the median age of 30 years), modal nationality (German or non-German), modal university (attending University of Potsdam or not) and the two modal academic disciplines (geosciences or engineering). Map-reading accuracy and tendency to agree with the hazard perception questions were not qualitatively different in any of these groups, though sample sizes were too small to detect small differences. There was a slight difference in map preference between some subgroups (see Table 2) in particular for academic discipline, where geoscientists tended to prefer the baseline map and engineers the redesigned map.

## 5 Discussions and conclusions

### 5.1 Systematizing the design of hazard maps

500 Previous work on risk communication for seismic hazard maps has largely focused on collecting user feedback on different map designs, while citing non-specific “best practices” in describing how design choices were made. We sought to disentangle what graphical criteria actually constitute ~~these~~ best practices in map design, particularly focusing on color palettes and data classification, which have been prioritized by previous authors (~~Marti et al., 2019; Fyfe and Molnar, 2020; Thompson et al., 2017~~) (Marti et al., 2019; Fyfe and Molnar, 2020; Thompson et al., 2015). The aim was not to provide a recipe for how to design hazard maps, but rather a criteria-based framework around which to make design decisions. We surveyed the color and visualization literature, using the Hue-Saturation-Lightness color model to elucidate three central criteria (perceptual order, perceptual uniformity, and discriminative power) found to be key to correct map interpretation, based on decades of empirical experiments. We also found a body of empirical literature supporting choosing colors with psychological associations relevant to the map ~~topic~~ interpretation as well as those that are colorblind-accessible.

510 We then surveyed the cartographical literature to identify ~~different~~ data classification methods that could be relevant for hazard maps. Traditional approaches such as equal-interval or quantile classification can obscure or even distort the true features of the data being mapped. We reviewed ~~classic~~ classical and modern approaches designed to find class breaks that fit the data. We also ~~discussed the research behind~~ identified the research that advocates for using a sufficient but not excessive number of class breaks and making them meaningful when possible. As empirical evaluations to compare classification schemes are  
515 scant, we propose three general criteria that have support from the literature.

We implemented these criteria to select a new color palette and classification scheme for the German seismic hazard map. The classification scheme was split at the PGA of  $0.4 \frac{m}{s^2}$ , the critical threshold at which Germany requires seismic building codes for ordinary buildings. The lower part of the distribution was split into three classes and the higher part was split into five classes, using the Fisher classification scheme, which well-represented the key features of the data, grouping data into classes  
520 that were quantitatively similar. The map used a ~~carefully designed~~ carefully designed and colorblind-friendly yellow-orange-red-brown color palette. The lower part of the scale used shades of yellow associated with caution, whereas the higher part used red colors associated with risk and danger, to appropriately convey the meaning of each part of the scale. Colors were optimized to be perceptually uniform and discriminable, with a single intuitive and identical ordering by both lightness and hue.

### 525 5.2 Assessing the redesigned German seismic hazard map

We tested the two German seismic hazard maps on a sample of early career researchers using a survey with map-reading and hazard perception questions. Participants could read both maps equally well, contrary to the suggestions of Gaspar-Escribano and Iturrioz (2011) that classification schemes with unequal intervals come at a cost to map-reading. While participants were only around 74% correct across the two maps, open-ended responses indicated that multiple participants struggled to under-  
530 stand the double legend labels. Indeed, most of the map-reading mistakes (85.3% for the baseline map and 84.6% for the

redesigned map) came from selecting the adjacent value above or below the correct one. Mistakes were also more common when cities spanned multiple colors, with participants often incorrectly choosing the lower hazard level, potentially indicating that they failed to notice that part of the city was in a higher hazard level; this appeared to affect both maps equally. Contrary to the suggestions of the expert evaluation (see Supplement S6), double legend labels and cities marked with polygons may be  
535 difficult to read precisely, even for a technical audience.

The redesigned map was successful in generating awareness of each key property of seismic hazard, as well as the critical threshold. Across the six question types, participants were 60.5-89.5% in agreement with the statement (selected either Slightly agree, Agree, or Strongly agree, and 47.3-73.7% of participants selected Agree or Strongly agree), indicating ~~their abundant~~  
a sufficient awareness of the hazard property. Relative to the baseline map, the redesign improved perception of two closely-  
540 related properties of seismic hazard: (1) that it spreads continuously over space and (2) that hazard can occur in areas even if they are not marked high on the map. On the other hand, both maps equally communicated the two other framing properties, that ~~extreme-highest~~  
highest hazard differs from high hazard and that spatial patterns are of primary importance. Both maps communicated which cities required seismic building codes roughly equally, both for cities at the far end of the scale (that would arguably be easier to answer for), and in the middle of the scale. These results held across the sample, regardless of demographics or  
545 academic background, indicating they may be robust to these user characteristics for similar technical audiences.

There are several aspects of the redesigned colors and classification schemes that may explain these evaluation results. The two properties where the redesign outperformed the baseline both have to do with the spatial diffusion and continuity in the regional patterns of seismic hazard. Users had awareness with the redesigned map, but not the baseline, that damaging shaking could be expected in cities that were close to, but not directly within zones of higher hazard (e.g., Karlsruhe, Koblenz, and  
550 Düsseldorf, see Supplement S7). The redesign's classification scheme groups hazard values more objectively and into fewer classes than the baseline, thus avoiding transmitting too much information (Marti et al., 2019). This may have made it easier to identify these cities as having a medium (and sufficiently important) hazard level. Furthermore, these classes were orange in the redesign and blue or green in the baseline; as found in multiple studies (Fyfe and Molnar, 2020; Miran et al., 2017; Thompson et al., 2015), orange may be better associated in Western cultures with damaging hazard than blue/green.

555 Responses to the open-ended questions indicated that there was a slight preference towards the redesigned map but that participants used many of the same explanations to describe preferences for either map. In particular, participants referred to the ability to discriminate colors and order them uniformly for both maps. Participants mentioned psychological aspects of the color to describe their preferences both for the baseline and redesigned map, in contrast to Fyfe and Molnar (2020)'s suggestion that evocative colors may not be preferred by map users. Participants also expressed the importance of classification breaks that  
560 signify a particular meaning. It is clear that the visualization elements (color, classification breaks) around which our redesign was structured were pertinent to these map users, both for their preferences and hazard perception between the maps. While these results were consistent across demographic subgroups, there was a preference for the baseline map only for geoscience researchers (see Table 2), potentially due to the greater ubiquity of the rainbow color scale in this field (Westaway, 2022).

### 5.3 Practical implications and limitations

565 Our criteria-based design method and application to German seismic hazard maps suggest several practical implications for designers of future hazard maps. First, it is possible to isolate empirically-evidenced criteria for color and classification in order to systematize best practices for hazard mapping. We recommend future hazard map designers to follow these criteria to generate candidate maps that are supported by the visualization and cartography literature. To decide between candidate maps, it is helpful to pre-specify a list of communication goals, or properties of the hazard process that are essential to communicate. 570 Finally, it is critical to evaluate the redesigned map with formal user testing, in order to measure whether the map's goals were effectively communicated.

Our evaluation suggested that the specific design choices we made (the Fisher classification scheme together with our customized yellow-orange-red-brown color palette) produced a map that was read sufficiently accurately and succeeded in users perceiving all communication goals. In two of these goals regarding regional spatial spread of seismic hazard, the redesigned 575 map outperformed the initial map, which used a suboptimal color palette and classification scheme; the redesigned map was also slightly more preferred over the initial map. Hazard maps adhering to evidence-based criteria for colors and classification schemes, and designed with key communication targets in mind, can reach these targets better than maps designed without such a framework. ~~While our~~ Our specific design choices may not ~~necessarily~~ be appropriate for other hazard types (i.e., where the hazard values' skewness is a priority to communicate), ~~the criteria-based procedure, the Head-Tails classification scheme~~ 580 may be advantageous over the Fisher scheme); ~~however, the criteria~~ we outline for designing a hazard map ~~is still provide a framework for making these decisions.~~

Our study ~~presented has~~ some limitations that can be addressed in future work. Our isolated criteria are not necessarily comprehensive and other considerations may be important in effective hazard map design. Visualization research suggests that the spatial frequency of patterns in a map may guide which color palette is optimal for it (Reda et al., 2018); that is, 585 high-frequency hazards (e.g., landslides, which are concentrated in space along sharp slopes) may require different color palettes than lower-frequency hazards (e.g., seismic hazard, which spread over larger areas). Furthermore, it may be desirable to compare hazard areas across different regions or return periods, which would affect the selection of the classification scheme. Future redesigns can address these ~~findings~~ additional constraints and build further bridges between the natural hazards and visualization research communities. Furthermore, our evaluation study was limited in both its sampled population (early career 590 researchers in Germany), number of questions (just one per communication goal, per map) and number of maps tested (a single redesign combining both color and classification improvements). Future work should disentangle the effects of color and classification changes through multiple maps, using a sample from a more general population and with an evaluation ~~survey with instrument containing~~ more questions per communication goal.

*Code and data availability.* All code and seismic hazard data needed to produce the different hazard maps are available at [https://osf.io/puerc/?view\\_only=2b747decfbfb4093a9e925e5fe09cd48](https://osf.io/puerc/?view_only=2b747decfbfb4093a9e925e5fe09cd48). 595

*Author contributions.* We use the CASRAI Contributor Roles Taxonomy to categorize author contributions.

**Conceptualization:** MS, FC. **Resources** (developing hazard maps): MS, FC **Methodology** (method development and evaluation): MS, FC, PJS. **Investigation** (evaluation data collection): MS, PJS. **Formal Analysis** (evaluation data analysis): MS, PJS. **Writing - original draft:** MS. **Writing – review & editing:** FC, PJS. **Supervision:** FC, PJS.

600 *Competing interests.* The authors declare that they have no conflict of interest.

*Acknowledgements.* We gratefully acknowledge Christian Bosse, Gottfried Grünthal, and the other colleagues and staff of the German Research Center for Geosciences that supported this work. [This research benefited from the contribution of early career researchers from the ITN-Marie Skłodowska-Curie New Challenges for Urban Engineering Seismology URBASIS-EU project \(Grant Agreement 813137\) and from the DFG Research Training Group “NatRiskChange”. We also thank two anonymous referees and the editor for suggestions that improved this manuscript.](#)

605



## References

- Marc P Armstrong, Ningchuan Xiao, and David A Bennett. Using genetic algorithms to create multicriteria class intervals for choropleth maps. *Annals of the Association of American Geographers*, 93(3):595–623, 2003.
- Jack Baker, Brendon Bradley, and Peter Stafford. *Seismic hazard and risk analysis*. Cambridge University Press, 2021.
- 610 Jennifer Birch. Worldwide prevalence of red-green color deficiency. *JOSA A*, 29(3):313–320, 2012.
- Roger Bivand, Hisaji Ono, Richard Dunlap, Matthieu Stigler, and Maintainer Roger Bivand. Package ‘classint’, 2020.
- David Borland and Russell M Taylor. Rainbow color map (still) considered harmful. *IEEE computer graphics and applications*, 27(2): 14–17, 2007.
- Ann Bostrom, Luc Anselin, and Jeremy Farris. Visualizing seismic risk and uncertainty: A review of related research. *Annals of the New York Academy of Sciences*, 1128(1):29–40, 2008.
- 615 Cynthia A Brewer and Linda Pickle. Evaluation of methods for classifying epidemiological data on choropleth maps in series. *Annals of the Association of American Geographers*, 92(4):662–681, 2002.
- Alzbeta Brychtova and Arzu Çöltekin. An empirical user study for measuring the influence of colour distance and font size in map reading using eye tracking. *The cartographic journal*, 53(3):202–212, 2016.
- 620 Roxana Bujack, Terece L Turton, Francesca Samsel, Colin Ware, David H Rogers, and James Ahrens. The good, the bad, and the ugly: A theoretical framework for the assessment of continuous colormaps. *IEEE transactions on visualization and computer graphics*, 24(1): 923–933, 2017.
- Isidro Cantarino, Miguel Angel Carrion, Francisco Goerlich, and Victor Martinez Ibañez. A ROC analysis-based classification method for landslide susceptibility maps. *Landslides*, 16(2):265–282, 2019.
- 625 Alan HS Chan, SH Han, and S Nanthavanij. Color associations for Hong Kong Chinese, Korean, and Thai-A comparison. In *Proceedings of IEA 14th Triennial Congress, Seoul Korea*, 2003.
- Tom Clarke and Alan Costall. The emotional connotations of color: A qualitative investigation. *Color Research & Application*, 33(5): 406–410, 2008.
- Arzu Çöltekin, Alžběta Brychtová, Amy L Griffin, Anthony C Robinson, Mark Imhof, and Chris Pettit. Perceptual complexity of soil-landscape maps: a user evaluation of color organization in legend designs using eye tracking. *International journal of digital earth*, 10(6): 560–581, 2017.
- 630 Fabio Cramer, Grace E Shephard, and Philip J Heron. The misuse of colour in science communication. *Nature communications*, 11(1): 1–10, 2020.
- Aritra Dasgupta, Jorge Poco, Bernice Rogowitz, Kyungsik Han, Enrico Bertini, and Claudio T Silva. The effect of color scales on climate scientists’ objective and subjective performance in spatial data analysis tasks. *IEEE transactions on visualization and computer graphics*, 2018.
- 635 Michael W Dobson. Choropleth maps without class intervals?: a comment. *Geographical Analysis*, 5(4):358–360, 1973.
- GS Doore et al. Guidelines for using color to depict meteorological information. *Bull. Am. Meteor. Soc*, 74:1709–1713, 1993.
- Doris Dransch, Henry Rotzoll, and Kathrin Poser. The contribution of maps to the challenges of risk communication to the public. *International Journal of Digital Earth*, 3(3):292–311, 2010.
- 640 Dennis Edler, Julian Keil, Marie-Christin Tuller, Anne-Kathrin Bestgen, and Frank Dickmann. Searching for the ‘right’ legend: The impact of legend position on legend decoding in a cartographic memory task. *The Cartographic Journal*, 57(1):6–17, 2020.

- Ian S Evans. The selection of class intervals. *Transactions of the Institute of British Geographers*, pages 98–124, 1977.
- Walter D Fisher. On grouping for maximum homogeneity. *Journal of the American statistical Association*, 53(284):789–798, 1958.
- 645 Meredith Fyfe and Sheri Molnar. Evaluating the use and communication of seismic hazard maps: A case study of Metro Vancouver, British Columbia, Canada. *WIT Transactions on Engineering Sciences*, 129:157–168, 2020.
- JM Gaspar-Escribano and T Iturrioz. Communicating earthquake risk: mapped parameters and cartographic representation. *Natural Hazards and Earth System Sciences*, 11(2):359–366, 2011.
- Helmholtz-Zentrum Potsdam GFZ. D-eqhaz16. URL <https://www-app5.gfz-potsdam.de/d-eqhaz16/index.html>. Plattform zur Abfrage von
- 650 gefährdungskonsistenten Antwortspektren (UHS) für beliebige Punkte in Deutschland sowie von nationalen Erdbebengefährdungskarten nach dem Berechnungsmodell von Grünthal et al. (2018).
- Connor C Gramazio, David H Laidlaw, and Karen B Schloss. Colorgorical: Creating discriminable and preferable color palettes for information visualization. *IEEE transactions on visualization and computer graphics*, 23(1):521–530, 2016.
- Linda J Griffith and S David Leonard. Association of colors with warning signal words. *International Journal of Industrial Ergonomics*, 20
- 655 (4):317–325, 1997.
- Gottfried Grünthal, Dietrich Stromeyer, Christian Bosse, Fabrice Cotton, and Dino Bindi. The probabilistic seismic hazard assessment of Germany—version 2016, considering the range of epistemic uncertainties and aleatory variability. *Bulletin of Earthquake Engineering*, 16(10):4339–4395, 2018.
- Gottfried Grünthal. Personal Communication, 2021.
- 660 Maria Hagemeyer-Klose and Klaus Wagner. Evaluation of flood hazard maps in print and web mapping services as information tools in flood risk communication. *Natural hazards and earth system sciences*, 9(2):563–574, 2009.
- Mark Harrower and Cynthia A Brewer. Colorbrewer. org: an online tool for selecting colour schemes for maps. *The Cartographic Journal*, 40(1):27–37, 2003.
- Katharine Haynes, Jenni Barclay, and Nick Pidgeon. Volcanic hazard communication using maps: an evaluation of their effectiveness.
- 665 *Bulletin of Volcanology*, 70(2):123–138, 2007.
- Simon Horton, Stan Nowak, and Pascal Haegeli. Enhancing the operational value of snowpack models with visualization design principles. *Natural Hazards and Earth System Sciences*, 20(6):1557–1572, 2020.
- Johannes Itten. The art of color the subjective experience and objective rationale of color. 1961.
- George F Jenks. The data model concept in statistical mapping. *International yearbook of cartography*, 7:186–190, 1967.
- 670 Bin Jiang. Head/tail breaks: A new classification scheme for data with a heavy-tailed distribution. *The Professional Geographer*, 65(3): 482–494, 2013.
- Bin Jiang, Xintao Liu, and Tao Jia. Scaling of geographic space as a universal rule for map generalization. *Annals of the Association of American Geographers*, 103(4):844–855, 2013.
- Susan Kennedy. Unclassed choropleth maps revisited/some guidelines for the construction of unclassified and classed choropleth maps.
- 675 *Cartographica: The International Journal for Geographic Information and Geovisualization*, 31(1):16–25, 1994.
- Gordon Kindlmann, Erik Reinhard, and Sarah Creem. Face-based luminance matching for perceptual colormap generation. In *IEEE Visualization, 2002. VIS 2002.*, pages 299–306. IEEE, 2002.
- Christoph Kinkeldey, Alan M MacEachren, Maria Riveiro, and Jochen Schiewe. Evaluating the effect of visually represented geodata uncertainty on decision-making: systematic review, lessons learned, and recommendations. *Cartography and Geographic Information*
- 680 *Science*, 44(1):1–21, 2017.

- Zhilin Li and Zhe Qin. Spacing and alignment rules for effective legend design. *Cartography and Geographic Information Science*, 41(4): 348–362, 2014.
- Adam Light and Patrick J Bartlein. The end of the rainbow? Color schemes for improved data graphics. *Eos, Transactions American Geophysical Union*, 85(40):385–391, 2004.
- 685 Sharon Lin, Julie Fortuna, Chinmay Kulkarni, Maureen Stone, and Jeffrey Heer. Selecting semantically-resonant colors for data visualization. In *Computer Graphics Forum*, volume 32, pages 401–410. Wiley Online Library, 2013.
- David L MacAdam. Visual sensitivities to color differences in daylight. *Josa*, 32(5):247–274, 1942.
- Lindsay W MacDonald. Using color effectively in computer graphics. *IEEE Computer Graphics and Applications*, 19(4):20–35, 1999.
- Carson C MacPherson-Krutsky, Brittany D Brand, and Michael K Lindell. Does updating natural hazard maps to reflect best practices  
690 increase viewer comprehension of risk? *International journal of disaster risk reduction*, 46:101487, 2020.
- Michèle Marti, Michael Stauffacher, and Stefan Wiemer. Difficulties in explaining complex issues with maps: evaluating seismic hazard communication—the swiss case. *Natural Hazards and Earth System Sciences*, 19(12):2677–2700, 2019.
- Bruce A Maxwell. Visualizing geographic classifications using color. *The Cartographic Journal*, 37(2):93–99, 2000.
- Ravi Mehta and Rui Juliet Zhu. Blue or red? exploring the effect of color on cognitive task performances. *Science*, 323(5918):1226–1229,  
695 2009.
- Volker Meyer, Christian Kuhlicke, J Luther, Sebastian Fuchs, S Priest, W Dorner, K Serrhini, Joanna Pardoe, Simon McCarthy, J Seidel, et al. Recommendations for the user-specific enhancement of flood maps. *Natural Hazards and Earth System Sciences*, 12(5):1701–1716, 2012.
- George A Miller. The magical number seven, plus or minus two: Some limits on our capacity for processing information. *Psychological  
700 review*, 63(2):81, 1956.
- Seyed M Miran, Chen Ling, Joseph J James, Alan Gerard, and Lans Rothfusz. User perception and interpretation of tornado probabilistic hazard information: Comparison of four graphical designs. *Applied ergonomics*, 65:277–285, 2017.
- Jean-Claude Muller. Perception of continuously shaded maps. *Annals of the Association of American Geographers*, 69(2):240–249, 1979.
- Judy M Olson and Cynthia A Brewer. An evaluation of color selections to accommodate map users with color-vision impairments. *Annals  
705 of the Association of American Geographers*, 87(1):103–134, 1997.
- Calvin KL Or and Heller HL Wang. Color–concept associations: A cross-occupational and-cultural study and comparison. *Color Research & Application*, 39(6):630–635, 2014.
- Lace Padilla, P Samuel Quinan, Miriah Meyer, and Sarah H Creem-Regehr. Evaluating the impact of binning 2d scalar fields. *IEEE transactions on visualization and computer graphics*, 23(1):431–440, 2016.
- 710 P Samuel Quinan and Miriah Meyer. Visually comparing weather features in forecasts. *IEEE transactions on visualization and computer graphics*, 22(1):389–398, 2015.
- Khairi Reda, Pratik Nalawade, and Kate Ansah-Koi. Graphical perception of continuous quantitative maps: the effects of spatial frequency and colormap design. In *Proceedings of the 2018 CHI Conference on Human Factors in Computing Systems*, pages 1–12, 2018.
- Penny L Rheingans. Task-based color scale design. In *28th AIPR Workshop: 3D Visualization for Data Exploration and Decision Making*, volume 3905, pages 35–43. International Society for Optics and Photonics, 2000.
- 715 Philip K Robertson and John F O’Callaghan. The generation of color sequences for univariate and bivariate mapping. *IEEE Computer Graphics and Applications*, 6(2):24–32, 1986.

- Bernice E Rogowitz, Alan D Kalvin, Adar Pelah, and Aron Cohen. Which trajectories through which perceptually uniform color spaces produce appropriate colors scales for interval data? In *Color and Imaging Conference*, volume 1999, pages 321–326. Society for Imaging Science and Technology, 1999.
- 720 Karen B Schloss, Connor C Gramazio, Allison T Silverman, Madeline L Parker, and Audrey S Wang. Mapping color to meaning in colormap data visualizations. *IEEE transactions on visualization and computer graphics*, 25(1):810–819, 2018.
- Max Schneider, Michelle McDowell, Peter Guttorp, E Ashley Steel, and Nadine Fleischhut. Effective uncertainty visualization for aftershock forecast maps. *Natural Hazards and Earth System Sciences*, 22(4):1499–1518, 2022.
- 725 Kathleen Sherman-Morris, Karla B Antonelli, and Carrick C Williams. Measuring the effectiveness of the graphical communication of hurricane storm surge threat. *Weather, climate, and society*, 7(1):69–82, 2015.
- Ian Spence, Natasha Kutlesa, and David L Rose. Using color to code quantity in spatial displays. *Journal of Experimental Psychology: Applied*, 5(4):393, 1999.
- Reto Stauffer, Georg J Mayr, Markus Dabernig, and Achim Zeileis. Somewhere over the rainbow: How to make effective use of colors in meteorological visualizations. *Bulletin of the American Meteorological Society*, 96(2):203–216, 2015.
- 730 Johji Tajima. Uniform color scale applications to computer graphics. *Computer Vision, Graphics, and Image Processing*, 21(3):305–325, 1983.
- Mary Anne Thompson, Jan M Lindsay, and JC Gaillard. The influence of probabilistic volcanic hazard map properties on hazard communication. *Journal of Applied Volcanology*, 4(1):1–24, 2015.
- 735 Mary Anne Thompson, Jan M Lindsay, and Graham S Leonard. More than meets the eye: Volcanic hazard map design and visual communication. In *Observing the Volcano World*, pages 621–640. Springer, 2017.
- Kristen M Thyng, Chad A Greene, Robert D Hetland, Heather M Zimmerle, and Steven F DiMarco. True colors of oceanography: Guidelines for effective and accurate colormap selection. *Oceanography*, 29(3):9–13, 2016.
- Waldo R Tobler. Choropleth maps without class intervals? *Geographical analysis*, 5(3):262–265, 1973.
- 740 Bruce E Trumbo. A theory for coloring bivariate statistical maps. *The American Statistician*, 35(4):220–226, 1981.
- Sergey Tyagunov, Gottfried Grünthal, Rutger Wahlström, L Stempniewski, and Jochen Zschau. Seismic risk mapping for Germany. *Natural Hazards and Earth System Sciences*, 6(4):573–586, 2006.
- Tingting Wang, Siyun Shu, and Lei Mo. Blue or red? the effects of colour on the emotions of Chinese people. *Asian Journal of Social Psychology*, 17(2):152–158, 2014.
- 745 Colin Ware, Terece L Turton, Roxana Bujack, Francesca Samsel, Piyush Shrivastava, and David H Rogers. Measuring and modeling the feature detection threshold functions of colormaps. *IEEE transactions on visualization and computer graphics*, 25(9):2777–2790, 2018.
- Richard M Westaway. Gc insights: Rainbow colour maps remain widely used in the geosciences. *Geoscience Communication*, 5(1):83–86, 2022.
- Liang Zhou and Charles D Hansen. A survey of colormaps in visualization. *IEEE transactions on visualization and computer graphics*, 22(8):2051–2069, 2015.
- 750