

~~Multi-phase Biogeochemical Model for Microbially Induced~~
~~Desaturation and Precipitation~~ A Multi-phase Biogeochemical Model
for Mitigating Earthquake-Induced Liquefaction via Microbially
Induced Desaturation and Calcium Carbonate Precipitation

Caitlyn A. Hall^{1,2,5,7}, Andre van Turnhout^{3,4}, Edward Kavazanjian, Jr.⁵, Leon A. van Paassen^{5,6,7}, and Bruce Rittmann^{5,7}

¹The Honors College and Biosystems Engineering Department, The University of Arizona, Tucson, AZ, USA

²Biosystems Engineering Department, The University of Arizona, Tucson, AZ, USA

³VALCON, Utrecht, The Netherlands

⁴Delft University of Technology, Delft, The Netherlands

⁵Center for Bio-mediated and Bio-inspired Geotechnics, Arizona State University, Tempe, AZ, USA

⁶Royal Boskalis Westminster N.V., Papendrecht, The Netherlands, USA

⁷Biodesign Swette Center for Environmental Biotechnology, Arizona State University, Tempe, AZ, USA

Correspondence to: Caitlyn A. Hall (cahall@arizona.edu)

Abstract. A next-generation biogeochemical model was developed to explore the impact of the native water source on microbially induced desaturation and precipitation (MIDP) via denitrification. MIDP is a non-disruptive, nature-based ground improvement technique that offers the promise of cost-effective mitigation of earthquake-induced soil liquefaction under and adjacent to existing structures. MIDP leverages native soil bacteria to reduce the potential for liquefaction triggering in the short term through biogenic gas generation (treatment completed within hours to days) and over a longer term through calcium carbonate precipitation (treatment completed in weeks to months). This next-generation biogeochemical model expands earlier modeling to consider multi-phase speciation, bacterial competition, inhibition, and precipitation. The ~~is~~ biogeochemical model was used to explore the impact of varying treatment recipes on MIDP products and by-products in a natural seawater environment. The case study presented herein demonstrates the importance of optimizing treatment recipes to minimize unwanted by-products (e.g., H₂S production) or incomplete denitrification (e.g., nitrate and nitrite accumulation).

Keywords: biogeochemical modeling, liquefaction, denitrification, desaturation, precipitation

30 **1 Introduction**

Microbially induced desaturation and precipitation (MIDP) is a biogeotechnical technique that takes advantage of native subsurface denitrifying bacteria to mitigate earthquake-induced soil liquefaction (O'Donnell et al., 2017a, b; Pham et al., 2018). MIDP mitigates liquefaction in two ways: generation of nitrogen gas (N₂) ~~that desaturates the soil~~ and mineral precipitation (usually calcium carbonate, CaCO₃) ~~that improves soil strength~~. The impact of MIDP on the soil system is illustrated in Figure 1. The generated N₂ desaturates the soil, increasing its compressibility and reducing the increase in pore water pressure during cyclic loading, which is the root cause of earthquake-induced liquefaction. Carbonate precipitation increases the soil strength, thereby increasing the intensity of earthquake shaking necessary to trigger liquefaction. A primary benefit of MIDP for liquefaction mitigation is, being non-disruptive, it can be used underneath existing structures (O'Donnell et al., 2017a; Hall, 2021). Trillions of dollars of existing infrastructure is at risk due to the potential for liquefaction, and there is currently that risk cannot be mitigated in a no cost-effective way way to mitigate that risk. MIDP is currently being evaluated at different experimental scales as a solution to this problem (O'Donnell et al., 2017a, b; Moug et al., 2022).




Figure 1. Pore-scale illustration of MIDP in water (dark blue) saturated sand (light yellow), detailing the gas (light blue), calcium carbonate (white), and biomass (green) production.

For environmental and economic reasons, we assume that local source water ~~is will be~~ used to prepare the MIDP treatment solution (i.e., dissolve the substrates needed to induce denitrification) in practice. Therefore, in developing this technique we must consider how ~~However,~~ naturally occurring constituents in the source water may affect denitrification. For example, a competing electron acceptor (e.g., sulfate) may consume the electron donor (e.g., acetate), leading to incomplete denitrification and the formation of unwanted products (e.g., hydrogen sulfide). In addition, the biogeochemical reactions during MIDP result in changes to alkalinity and pH that may alter process kinetics and final MIDP products.

To quantify the impact of source-water composition and to ~~understand-investigate how~~ the complex biogeochemical interactions that occur during field application, we developed a next-generation biogeochemical model of MIDP. This mathematical model expands upon previous modeling of MIDP, which did not consider the impact of source water on MIDP or the impact of MIDP on the aqueous subsurface environment (Pham, 2017; O'Donnell et al., 2019). Our next-generation MIDP model includes all essential biogeochemical processes based on the constituents commonly observed in the natural groundwater environments, substrates added to stimulate MIDP, and mechanisms that lead to desaturation and precipitation: e.g., N₂-gas formation, acid-base speciation, and CaCO₃ precipitation. Since MIDP often is deployed in coastal areas (due to the prevalence of liquefiable soil deposits in this environment), we include conditions typical for coastal seawater in our model.

2 Model Foundation


The next-generation model builds upon previous MIDP models (Pham, 2017; O'Donnell et al., 2019), but broadens the range of processes considered by the model. Our next-generation model considers microbial growth and decay, alternative microbial metabolic processes, gas production, mineral-solids production, alkalinity and pH, microbial inhibition, and desaturation and precipitation in both fresh water and coastal environments. A comparison of the components and processes considered by the two earlier MIDP models and our next-generation model is provided in Table A1 in Appendix A.

The next-generation model was constructed in Matlab (Little and Moler, 2017), and the code and necessary files are publicly available online at doi.org/10.5281/zenodo.7410676. The modeling equations (e.g., microbial growth, CaCO₃ precipitation, and biogenic gas evolution) were programmed within the original, publicly available van Turnhout Toolbox, a general-form mechanistic [batch](#) model for environmental systems [that considers species in the gas, liquid, and solid phases](#) (van Turnhout et al., 2016). [The van Turnhout Toolbox is program that includes a system of ordinary differential equations that model biogeochemical reactions. The van Turnhout Toolbox is coupled with ORCHESTRA, an extensive database of established geochemical equilibria based on MINTEQ, to simulate](#)~~The van Turnhout Toolbox simulates~~ chemical speciation [during said modeling with ORCHESTRA](#) (Meeussen, 2003), ~~an extensive database of established geochemical equilibria.~~ The MIDP-specific biogeochemical model components (i.e., stoichiometry, type of inhibition and kinetics, potential chemical species) were specified in an input spreadsheet that the program accesses. The degree of saturation and percent (by weight) of mineral precipitation were calculated outside of the van Turnhout Toolbox using model results, as discussed in Section 3.2 of this paper.

[The Toolbox's logic flow and calculation sequence are as follows \(Meeussen, 2003; van Turnhout et al., 2016\), using H₂CO₃, HCO₃⁻, CO₃²⁻, H⁺, and OH⁻ to illustrate the process for the carbonate system.](#)

1. At t = 0, the program loads the input concentrations file, which includes the concentration of all total species (e.g.,

[H₂CO₃ representing DIC, H⁺\) and the stoichiometry for metabolic and kinetic reactions: e.g.,](#)



2. Ordinary differential equations are used to determine compound consumption and production based on the reaction stoichiometry and kinetic equations (e.g., precipitation, biotransformation, and mass transfer) at each time step. For example, the graphic in Figure 2 illustrates that, as $C_2H_3O_2^-$ is consumed from microbial consumption, H_2CO_3 is produced.





Figure 2. Illustration of consumption of the consumption of $C_2H_3O_2^-$ and production of H_2CO_3 during MIDP.

3. At each time step, the following set of linear equations ~~is~~ are solved to determine the relative derived concentrations of H_2CO_3 , HCO_3^- , CO_3^{2-} , H^+ , and OH^- from H_2CO_3 produced in the previous steps. This is done in the ORCHESTRA biochemical module.

a. Mass balance equations – the left side of the equation is the total dissolved inorganic carbon, H_2CO_3 , from the stoichiometry described in steps 1 and 2. The right side are the derived concentrations of species as a result of speciation and indicated with italics.



b. Electroneutrality – all potentially produced charged species related to this balance are considered.



c. Acid equilibrium for H_2CO_3

$$K_a = \frac{[CO_3^{2-}][2H^+]}{[H_2CO_3]}$$

d. Acid equilibrium for HCO_3^-

$$K_a = \frac{[CO_3^{2-}][H^+]}{[HCO_3^-]}$$

e. Water equilibrium

$$K_w = [OH^-][H^+] = 1.0 \cdot 10^{-14}$$

4. pH is calculated based on the derived H^+ concentration based on solving simultaneously 3(a-e).

While the carbonate system is used here as an example, this stepwise process is used for all acid-base species and considers the total system set of reactions and species to achieve equilibrium. The total system electroneutrality considered in the model for all considered species is as follows:

$$H^+ + NH_4^+ + Ca^{2+} + CaHCO_3^+ + CaOH^+ + CaC_2H_3O_2^+ + Fe^{3+} + Fe^{2+} + FeOH^+ + Fe(OH)_2^+ + Na^+ \\ = OH^- + HCO_3^- + CO_3^{2-} + NO_3^- + NO_2^- + C_2H_3O_2^- + SO_4^{2-} + HSO_4^- + HS^- + Cl^-$$

The compounds listed above are defined in the input spreadsheet as possible species. The model then uses ORCHESTRA to determine the concentration of each species based on the biogeochemical reactions and system equilibrium.

Formatted: Normal, Indent: Left: 0.25", No bullets or numbering

Formatted





Formatted

Formatted

Formatted: Normal, Indent: Left: 0.25", Space After: 0 p
Line spacing: single, No bullets or numbering

3 Model Principles

Denitrification is a multi-step process of nitrogen-species reduction. During each reduction step, energy and biomass are produced when paired with oxidation of an electron donor that produces a thermodynamically favorable reduction-oxidation (redox) reaction. The four steps of nitrogen reduction in denitrification conform to the following reduction half reactions, each consuming two or one electron equivalent (e^-) (Rittmann and McCarty, 2020):



In the model developed herein, the four steps were simplified to two steps, nitrate to nitrite and nitrite to dinitrogen gas. The reductions of nitric oxide and nitrous oxide are assumed to occur completely, as they are thermodynamically favorable (Appendix A). In contrast, the accumulation of NO_2^- must be considered explicitly because it is a denitrification inhibition 'bottleneck' and presents a risk to human health (Pham et al., 2018; Almeida et al., 1995). The variables for the equations used in the model described in the next several sections are detailed in Table 1.

Table 1. Notation, units, and description for variables used in the biogeochemical model

Symbol	Units	Description
\hat{q}	$\text{mol}_{\text{donor}} \text{mol}_{\text{biomass}}^{-1} \text{d}^{-1}$	maximum specific rate of electron-donor utilization
X_a	mol L^{-1}	active biomass concentration
C_d	mol L^{-1}	electron donor concentration
K_d	mol L^{-1}	electron donor half-maximum substrate concentration of the
C_a	mol L^{-1}	electron acceptor concentration
K_a	mol L^{-1}	electron acceptor half-maximum substrate concentration
I_i		inhibition factor ($0 < I_i < 1$)
Y	$\text{mol}_{\text{biomass}} \text{mol}_{\text{donor}}^{-1}$	biomass yield from consumed electron donor substrate
μ_{max}	d^{-1}	maximum specific microbial growth rate; product of Y and \hat{q}
b	d^{-1}	endogenous decay
K_i	mol L^{-1}	inhibition constant
C_i	mol L^{-1}	concentration of the inhibiting species
$v_{i[g]}$	$\text{mol L}^{-1} \text{d}^{-1}$	transfer rate from the aqueous phase to the gas phase
k_{La}	d^{-1}	mass transfer rate constant
$C_i[g]$	mol L^{-1}	gas phase concentration of the gas species i
$C_i[aq]$	mol L^{-1}	aqueous phase concentration of the biogenic gas species i
K_H	L atm mol^{-1}	Henry's Law constant
R	$\text{L atm mol}^{-1} \text{K}^{-1}$	universal gas constant
T	K	system's absolute temperature
$[N_2]_g$	$\text{mol L}_{\text{pore}}^{-1}$	produced N_2 gas during MIDP
$[CO_2]_g$	$\text{mol L}_{\text{pore}}^{-1}$	produced CO_2 gas
p	atm	pressure at treatment depth
S_g	$\text{L}_{\text{gas}} \text{L}_{\text{pore}}^{-1}$	gas saturation level
l	$\text{L}_{\text{aq}} \text{L}_{\text{pore}}^{-1}$	aqueous solution in the pore space
p_{N_2}	atm	partial pressure of N_2 gas
K_{H,N_2}	$\text{L}_{\text{aq}} \text{atm}_{N_2} \text{mol}_{N_2}^{-1}$	Henry's constant for N_2 at standard temperature
p_{CO_2}	atm	partial pressure of CO_2 gas
K_{H,CO_2}	$\text{L}_{\text{aq}} \text{atm}_{CO_2} \text{mol}_{N_2}^{-1}$	Henry's constant for CO_2 at standard temperature
$Y_{NO_3^-}$	$\text{mol}_{NO_3^-} \text{mol}_{\text{donor}}^{-1}$	stoichiometric coefficients of NO_3^-
Y_{N_2}	$\text{mol}_{N_2} \text{mol}_{\text{donor}}^{-1}$	stoichiometric coefficients of N_2
Y_{CO_2}	$\text{mol}_{CO_2} \text{mol}_{\text{donor}}^{-1}$	stoichiometric coefficients of CO_2
ϕ	$\text{L}_{\text{pore}} \text{L}_{\text{total}}^{-1}$	soil porosity
R_p	$\text{mol L}^{-1} \text{d}^{-1}$	net rate of precipitation ($R_p > 0$) or dissolution ($R_p < 0$) of minerals
ka	L d^{-1}	combined coefficient for constant mineral growth rate and the average crystal surface area
K_{sp}	$\text{mol}^2 \text{L}^{-2}$	constant solubility product.
Y_{CaCO_3}	$\text{mol CaCO}_3 \text{mol}_{\text{donor}}^{-1}$	$CaCO_3$ yield
$NO_3^- d$	$\text{mol}_{NO_3^-} \text{L}_{\text{pore}}^{-1}$	NO₃⁻ needed to achieve the target desaturation
$[NO_3^-]_C$	$\text{mol L}_{\text{pore}}^{-1}$	NO_3^- needed to achieve the target $CaCO_3$
e	$\text{L}_{\text{pore}} \text{L}_{\text{soil}}^{-1}$	void ratio
ρ_{soil}	$\text{kN L}_{\text{soil}}^{-1}$	soil density
u_{CaCO_3}	$\text{g CaCO}_3 \text{mol}^{-1} \text{CaCO}_3$	molarity to molecular weight conversion coefficient

125

3.1 Microbial Metabolism, Growth, and Decay

The processes within the model follow Monod kinetics, represented as multiplicative dual-substrate limitation (O'Donnell et al., 2019; Bae and Rittmann, 1996).

$$\frac{dC_d}{dt} = -\hat{q}X_a \frac{C_d}{K_d + C_d} \cdot \frac{C_a}{K_a + C_a} I_i \tag{1}$$

130 Eq. 1 considers the electron-donor substrate (C_d) and three electron-acceptor substrates (C_a): NO_3^- and NO_2^- for denitrifying bacteria and SO_4^{2-} for sulfate-reducing bacteria. For preliminary analysis, we assumed an initial denitrifier biomass concentration of 0.5 mmol L^{-1} and sulfate-reducing biomass concentration of 0.25 mmol L^{-1} . The values of the constants (\hat{q} , K_d , and K_a) are in Appendix A, [along with the derivations of said parameters](#). ~~Derivations of important microbial kinetics parameters, found in Appendix A, are based on Rittmann and McCarty (2020). Appendix A also includes preliminary model~~
135 ~~results assuming a reduced initial denitrifier biomass concentration of 0.05 mmol L^{-1} and sulfate-reducing biomass concentration of $0.025 \text{ mmol L}^{-1}$. The comparison of the findings detailed in the results section of this paper and those found in Appendix A illustrate the influence of the initial biomass concentration on the model results. -The main impact of~~
~~xxxxxlowering the initial biomass concentration was yyyyyydelayed start-up time for the microbiological processes, though the trends remained the same for all between all modeled scenarios.-~~ These derivations were used to determine reaction
140 stoichiometry, true yield (Y) and μ_{max} (maximum specific growth rate) for all electron-donor and -acceptor pairs and the nitrogen source. Values of the kinetic and stoichiometric parameters are detailed in Table 2. The inhibition factor I_i is described in a later section [of this paper](#).

Values of half-maximum-rate concentrations (K_d and K_a) in the literature show variability for each electron donor and acceptor pair due to the wide range of environments of the microorganisms (e.g., sediment, estuarine water, wastewater) and
145 the high degree of diversity of microorganisms able to carry out these reactions (Abdul-Talib et al., 2002; Papaspyrou et al., 2014; Vavilin and Rytov, 2015). ~~Table 3~~Table 3 details the constants we used as representative values for each K_d and K_a (for Eq. 1) based on relevant electron-donor and -acceptor pairs and sources of those values. While, these values are not specific to a coastal seawater environment, they have been experimentally validated.

150

155 **Table 2.** Reaction stoichiometry, yield (Y), and maximum specific growth rates (μ_{max}) expected during MIDP, considering acetate as the electron donor and natural electron acceptors. Units for all parameters are in Table 1.

Electron Acceptor	Nitrogen Source	\hat{q}	Y	μ_{max}	Reaction Stoichiometry
Nitrate	Nitrate	8.12	0.82	6.68	$0.222NO_3^- + 0.125C_2H_3O_2^- + 0.146H^+$ $\rightarrow 0.202NO_2^- + 0.147H_2CO_3$ $+ 0.103CH_{1.8}O_{0.5}N_{0.2} + 0.021H_2O$
Nitrite	Nitrate	11.69	0.99	11.6	$0.054NO_3^- + 0.202NO_2^- + 0.270C_2H_3O_2^- + 0.525H^+$ $\rightarrow 0.101N_2 + 0.272H_2CO_3$ $+ 0.268CH_{1.8}O_{0.5}N_{0.2} + 0.154H_2O$
Sulfate	Nitrate	3.74	0.58	2.18	$0.015NO_3^- + 0.072SO_4^- + 0.125C_2H_3O_2^- + 0.284H^+$ $\rightarrow 0.072H_2S + 0.177H_2CO_3$ $+ 0.073CH_{1.8}O_{0.5}N_{0.2} + 0.015H_2O$
Nitrate	Ammonium	6.95	1.01	6.99	$0.236NO_3^- + 0.125C_2H_3O_2^- + 0.025NH_4^+ + 0.10H^+$ $\rightarrow 0.236NO_2^- + 0.124H_2CO_3$ $+ 0.126CH_{1.8}O_{0.5}N_{0.2} + 0.050H_2O$
Nitrite	Ammonium	9.65	1.26	12.2	$0.235NO_2^- + 0.261C_2H_3O_2^- + 0.066NH_4^+ + 0.431H^+$ $\rightarrow 0.118N_2 + 0.193H_2CO_3$ $+ 0.328CH_{1.8}O_{0.5}N_{0.2} + 0.249H_2O$
Sulfate	Ammonium	3.63	0.18	0.66	$0.113SO_4^- + 0.125C_2H_3O_2^- + 0.005NH_4^+ + 0.346H^+$ $\rightarrow 0.113H_2S + 0.227H_2CO_3$ $+ 0.023CH_{1.8}O_{0.5}N_{0.2} + 0.009H_2O$

Table 3. Half-maximum-rate concentrations, K_d and K_a , used for each electron-donor and -acceptor pair


Electron Donor	K_d	Reference	Electron Acceptor	K_a	Reference
Acetate (C ₂ H ₃ O ₂ ⁻)	1.0 · 10 ⁻⁵	(Jia et al., 2020)	Nitrate (NO ₃ ⁻)	5.4 · 10 ⁻⁵	(Abdul-Talib et al., 2002)
Acetate (C ₂ H ₃ O ₂ ⁻)	1.0 · 10 ⁻⁵	(Jia et al., 2020)	Nitrite (NO ₂ ⁻)	2.4 · 10 ⁻⁵	(Abdul-Talib et al., 2002)
Acetate (C ₂ H ₃ O ₂ ⁻)	7.1 · 10 ⁻⁵	(Ingvorsen et al., 1984)	Sulfate (SO ₄ ⁻)	2.00 · 10 ⁻⁴	(Ingvorsen et al., 1984)

160

Microbial growth within the model is represented via reaction kinetics and stoichiometry expressed in Eq. 2:

$$\frac{dX_a}{dt} = X_a Y \hat{q} - b \tag{2}$$

165 Biomass yields (Y) are listed in Table 2. For sulfate-reducing bacteria, b was set to 0.03 d^{-1} , whereas it was set to 0.05 d^{-1} for
denitrifiers (Rittmann and McCarty, 2020). As a result of decay, NH_4^+ is released and can serve as a nitrogen source for
denitrification. Since NH_4^+ is thermodynamically favorable over NO_3^- as a nitrogen source, it is used first before NO_3^- during
denitrification [using a user-defined switch. We used the inhibition function described in Section 3.2 as the switch to interrupt](#)
[biomass from using \$\text{NO}_3^-\$ as the nitrogen source in the presence of \$\text{NH}_4^+\$.](#) Decay involves endogenous respiration, and we
170 assumed that 80% of decayed biomass is available as an acetate for metabolism, while 20% becomes inert biomass (Rittmann
and McCarty, 2020). The stoichiometry for decay is:



3.2 Inhibition

175 [The van Turnhout Toolbox has the capability to model different inhibition mechanisms, but we only used non-competitive](#)
[inhibition during denitrification because the enzymes that perform nitrate, nitrite, and sulfate reduction are different and not](#)
[self-inhibitory \(Glass and Silverstein, 1998\).](#) Denitrification inhibition, which slows nitrate and nitrite reduction rates (Glass
et al., 1997), was included for the reduction of nitrate to nitrite and nitrite to N_2 gas. I_i is a general term for inhibition of either
step, with i indicating which reaction. The form of I_i , shown in Eq. 3 is for non-competitive inhibition, and the inhibition
coefficients for each inhibitor are found in [Table 4](#)~~Table 4~~:

180
$$I_i = \frac{K_i}{K_i + C_i} \tag{3}$$

Table 4. Non-competitive inhibition coefficients (K_i)

Inhibiting Compound	Reduction Process Inhibited	K_i (mol L^{-1})	Source
HNO_2	Nitrate	$2 \cdot 10^{-6}$	(Ma et al., 2010)
HNO_2	Nitrite	$8 \cdot 10^{-8}$	(Glass et al., 1997)
Salinity (as NaCl)	Nitrate, nitrite	0.51^a ; 0.78^b	^a (Panswad and Anan, 1999) ^b (Mariangel et al., 2008)
H_2S	Nitrate, nitrite	$6 \cdot 10^{-5}$	(Pan et al., 2019)
NO_3^-	Sulfide Sulfate	$1 \cdot 10^{-3}$	(Veshareh et al., 2021)
NO_2^-	Sulfate	$1 \cdot 10^{-3}$	(Veshareh et al., 2021)

^aUnacclimated environments were DI and drinking water, ^bAcclimated environments were groundwater and sea water

185 Although several inhibitors could affect MIDP, HNO_2 is the most important inhibitor of the MIDP process (Lilja and
Johnson, 2016). Significant inhibition [\(95% rate reduction\)](#)~~to~~of overall denitrification has been reported at $0.04\text{ mg HNO}_2\text{ L}^{-1}$

Formatted: Subscript

Formatted: Superscript

Formatted: Subscript

Formatted: Superscript

¹, which primarily impacted the intermediate NO_2^- reduction step (approximately 95% rate reduction) (Glass et al., 1997; Abeling and Seyfried, 1992), and a 60% decrease in NO_3^- reduction at $0.08 \text{ mg HNO}_2 \text{ L}^{-1}$ also was reported (Ma et al., 2010). Within the model, HNO_2 inhibits NO_3^- and NO_2^- reductions using different the same inhibition coefficients (Table 4Table 4). The inhibition by HNO_2 is driven by pH speciation because NO_2^- is dominant at a pH of 3.4 and higher and HNO_2 is negligible for $\text{pH} \geq 7.6$. However, only a small concentration of HNO_2 can have a significant impact on denitrification, which underscores the importance of pH and the accumulation of the intermediate NO_2^- and pH.

Competitive inhibition between nitrate and nitrite reductions has been identified, with the presence of nitrate having a larger effect on nitrite reduction than nitrite on nitrate reduction (Lilja and Johnson, 2016; Glass et al., 1997; Almeida et al., 1995; Soto et al., 2007). Nitrite accumulation increases in the presence of nitrate until nitrate is depleted, such that nitrite reduction becomes the dominant process (Glass and Silverstein, 1998). When only nitrite remains, the rate of nitrite reduction increases. However, others have described that, as long as the electrons are adequately provided by the electron donor, competitive inhibition between nitrate and nitrite reductions is not significant (Soto et al., 2007; Ma et al., 2010; van den Berg et al., 2017). Therefore, the model does not include competitive inhibition, although it naturally includes competition for the electron donor between nitrate and nitrite reductions through thermodynamic favorability of nitrate reduction over nitrite reduction.

The model applies different non-competitive inhibition constants for salinity (as NaCl) for nitrate and nitrite reduction because nitrite reduction is more sensitive to salinity than nitrate. Because the magnitude of inhibition depends on experimental conditions and adaptation of the microorganisms, the value of K_i -value may differ for local conditions (Krishna Rao and Gnanam, 1990).

Hydrogen sulfide (H_2S) also can be inhibitory to denitrification (Pan et al., 2019). Nitrate, nitrite, and N_2O reductions have been inhibited by H_2S , though the extent and sensitivity of reduction in the presence of H_2S was experiment-dependent (Senga et al., 2006; Pan et al., 2013; Tugtas and Pavlostathis, 2007; Liang et al., 2020; Cardoso et al., 2006). Within the model, one aqueous-phase H_2S -inhibition constant was used for both NO_3^- and NO_2^- reduction steps.

A $\text{pH} < 6$ can significantly slow denitrification (Glass and Silverstein, 1998) by inhibiting enzyme activity (Šimek and Cooper, 2002) and microbial growth (Estuardo et al., 2008). When the pH goes higher than 8, enzyme activity also can be impeded, leading to reduced denitrification rates or incomplete denitrification. Incidents of a high pH often are temporary, as CaCO_3 precipitation in MIDP buffers the pH (Salek et al., 2015). The benefit of including a pH-inhibition function when predicting denitrification has been demonstrated, but the values of their governing parameters are environment-specific and require fitting (Estuardo et al., 2008). Within the model, we considered the indirect net effect of pH only through HNO_2 inhibition, which does not require environment-specific parameters because the concentration of HNO_2 is automatically calculated within the model structure.

3.3 Biogenic Gas Production

O'Donnell et al. (2019) considered the production of N₂ and CO₂ during denitrification, but did not consider the varying subsurface stresses that would influence phase transfer. The relative concentrations of the produced biogenic gas can affect the distribution of gas at depth, since the gases have different solubilities, as well as different stoichiometries for electron-donor consumption.

Our next-generation MIDP model includes mass-transfer kinetics for transfers of N₂, CO₂, and H₂S from the aqueous phase to the gas phase (or from the gas phase). We considered gas-phase transfer kinetics because assuming instantaneous gas phase transfer clearly would be an oversimplification, based on the review on mass transfer of biologically driven gas production completed by Kraakman et al. (2011). N₂, CO₂, and H₂S concentrations were modeled in the aqueous and gas phases. The rate of transfer of a gaseous compound from the aqueous phase to (or from) the gas phase, $v_{i[g]}$, depends on the gas's degree of super-saturation and a mass-transfer-rate coefficient (Salek et al., 2015):

$$v_{i[g]} = k_l a (C_{i[g]} - \frac{C_{i[aq]} RT}{K_H}) \quad (4)$$

We assigned $k_{l,a}$ values for N₂, CO₂, and H₂S of 5–1 d⁻¹ (Yongsiri et al., 2004; Shin et al., 2002), though the values can vary widely based on porous medium conditions and temperature. We did not include pore-scale kinetics. The aqueous concentrations of CO₂ and H₂S depend on the pH, as described below.

The biogenic gas volume needed to achieve a target level of desaturation (S_g) by N₂ ($[N_2]_g$) and CO₂ ($[CO_2]_g$) was determined by:

$$[N_2]_g + [CO_2]_g = \frac{p S_g}{RT} \quad (5)$$

in which p was assumed to be equal to the sum of the hydraulic pressure at the treatment depth (7.6 m in an upcoming example) and the atmospheric pressure. Gas-phase H₂S was not included in the desaturation calculations because its solubility is much higher than N₂ and CO₂.

Eq. 6 describes the amount of input NO₃⁻ required for desaturation by N₂ and CO₂ ($NO_3^-_d$, mol_{NO₃} L_{pore}⁻¹) at the deepest target treatment depth, which is the lowest depth of the treated zone. The depth increases the pressure (p_{N_2} and p_{CO_2}) and the needed amount of gas production to exceed the solubility threshold (K_{H,N_2} and K_{H,CO_2}) and enter the gas phase, according to Henry's Law. The equation considers the amount of gas needed to overcome the solubility threshold to achieve the target level of desaturation (Hall et al., 2018; Pham, 2017):

$$NO_3^-_d = \frac{\left(\frac{[N_2]_g}{l} + \frac{p_{N_2}}{K_{H,N_2}}\right) Y_{NO_3^-}}{Y_{N_2}} + \frac{\left(\frac{[CO_2]_g}{l} + \frac{p_{CO_2}}{K_{H,CO_2}}\right) Y_{NO_3^-}}{Y_{CO_2}} \quad (6)$$


K_{H,N_2} was set to 1600 and K_{H,CO_2} to 29 (L atm mol⁻¹). We determine the amount of nitrate needed to achieve target desaturation levels at the lowest depth, because greater depth requires a higher concentration of gas to achieve target desaturation levels, as the pressures are at their respective maxima.

Eq. 7 was used to determine the biogenic gas volume (V_g , L_{gas} L_{tot}⁻¹),

$$V_g = \frac{S_g RT \phi}{p} \quad (7)$$

3.4 Solids Precipitation and Dissolution

[PCalcium carbonate](#) precipitation occurs when dissolved inorganic carbon (DIC), produced from microbial substrate conversion of the electron donor, exceeds the solubility of CaCO₃ for the concentration of Ca²⁺ present. The stoichiometry for CaCO₃ precipitation is:



[At the beginning of each run, the concentration of species available for precipitation are calculated as their dissolved form as discussed in Section 2, then solids precipitation is determined.](#) The van Turnhout Toolbox considers precipitation based on equilibrium calculations from the ORCHESTRA module (Meeussen, 2003). This assumption is valid when the rates of precipitation and dissolution of minerals are much faster than the phase transfer between the aqueous and solid phases (Salek et al., 2015). Previous MIDP modeling did not consider precipitation kinetics, but assumed instantaneous equilibrium (Pham, 2017; O'Donnell et al., 2019). Instantaneous equilibrium may be an over-simplification for environmental conditions (Singurindy et al., 2004) in which the mechanisms of crystal nucleation, crystal growth, and mass transfer of reactants to the contact point of crystal growth are important (Rittmann et al., 2002). Therefore, we included precipitation and dissolution kinetics in the next-generation model.

The model considers first-order precipitation and dissolution kinetics with respect to the Ca²⁺ ~~concentration and CO₃²⁻ concentrations~~ (Rittmann et al., 2002; [Chou et al., 1989](#)):

$$R_p = ka \left(1 - \frac{K_{sp}}{[Ca^{2+}][CO_3^{2-}]} \right) [Ca^{2+}] \quad (8)$$

K_{sp} was set to 1.83·10⁻⁸ mol² L⁻² at 25°C for CaCO₃. ka is a combined kinetic coefficient, because it is difficult to separate mass transfer kinetics, crystal growth rate, and solid surface area (Rittmann et al., 2002; Spanos and Koutsoukos, 1998; Rittmann et al., 2003). ka can have a large range depending on the environment and the ease of establishing precipitation nucleation points. We assumed ka was 100 L·d⁻¹, though this value should be used as a fitting parameter subject to experimental validation. Precipitation was implemented using the van Turnhout Toolbox's method for biochemical reactions; ka was specified as a reaction rate, and K_{sp} was among the governing input parameters.

Eq. 9 was used to determine the amount of substrate needed to achieve a target precipitation level, which is determined by the ratio between mass of precipitated CaCO₃ and mass of the soil solids (I_{CaCO_3} , kg CaCO₃ kg soil⁻¹).

Formatted: Subscript

$$[NO_3^-]_c = \frac{[CaCO_3]_{\rho_{soil}} Y_{NO_3^-}}{eu_{CaCO_3} Y_{CaCO_3}} \tag{9}$$

The stoichiometric coefficients considered the total amount of input NO_3^- and produced H_2CO_3 for the total assumed two-step denitrification process. The DIC available for precipitation to provide Y_{CaCO_3} is estimated based on pH-driven speciation at each time step.

While we only considered calcium carbonate precipitation, the model has the flexibility to model precipitation of other minerals. The user would need to add in separate equations to model precipitation kinetics based on the reactants, desired products, and the k_a and K_{eq} values appropriate for the desired precipitation reaction and product.

3.5 Determining pH

Because pH governs the concentration of important aqueous species based on acid/base speciation, the pH influences many of the geochemical reactions involved in MIDP. The pH was determined using the geochemical equilibrium software ORCHESTRA, which is part of the van Turnhout Toolbox. ORCHESTRA uses a mass balance on all species within the system and the products of rate-dependent processes as a function of time (i.e., kinetic, biogeochemical, and phase transfer processes). At each time step, the program performs a mass balance on all complexed species and their fate (e.g., transformed through microbial processes, precipitation, gas phase transfer) (van Turnhout et al., 2016; Meeussen, 2003). The program's logic flow and calculation sequence are found in Appendix A.

4 Case Study MIDP Behavior Seawater Conditions: Model Results and Discussion

To demonstrate the capabilities of the model, we illustrate MIDP behavior when targeting desaturation for liquefaction mitigation in a coastal geochemical environment. In this case study, we demonstrate the impact of precipitation on biochemical reactions and the resulting multi-phase products and by-products resulting from MIDP and other environmental biogeochemical processes (e.g., sulfate reduction). However, we only ~~consider~~reconsider desaturation as a target treatment mechanism and do not model an MIDP treatment recipe optimized for precipitation as a liquefaction-mitigation mechanism. Table 5 details the chemical characteristics used to simulate coastal groundwater conditions, which were assumed to have the same characteristic of seawater due to intrusion (hereafter, referred to as “seawater”). The treatment substrate was added to the baseline level of these components. Table 5 does not reflect the varying concentrations of calcium acetate and calcium nitrate used in the treatment recipes, which are described later. We based the target treatment zone’s soil properties on a case study of microbial desaturation via denitrification in Portland, Oregon presented by Moug et al. (2022). The deepest target treatment depth was 7.6 m. We assumed typical values of total unit weight, dry density, and porosity for uniform clean sand

for the soil (Christopher et al., 2006): total unit weight of 19.5 kN m⁻³ (dry unit weight of 15.6 kN m⁻³; bulk density of 1950 kg m⁻³) and porosity of 0.39.

Table 5. Chemical Characteristics Assumed for a Coastal Seawater Environment

Compound	Coastal Seawater
Nitrate	20.3 ^[1] μmol L ⁻¹
Nitrite	0.14 ^[1] μmol L ⁻¹
Sulfate	28.2 ^[2] mmol L ⁻¹
DIC	2.13 ^[1] mmol L ⁻¹
pH	7.61 ^[1]
Ammonium	0.25 ^[1] μmol L ⁻¹
Iron	0.60 ^[3] nmol L ⁻¹
Sodium	0.47 ^[2] mol L ⁻¹
Calcium	10.3 ^[2] mmol L ⁻¹
Chloride	0.55 ^[2] mol L ⁻¹

^[1]Average of measured values (Alin et al., 2017)

^[2]Reference composition of “standard seawater” from and calculated for pH = 7.61 for acid-base species (Millero et al., 2008; European Commission. Directorate General for Research., 2011)

^[3] (Bruland et al., 2001)

The reported desaturation levels required to increase the cyclic shear resistance for liquefaction mitigation range between 2 to 10% (He and Chu, 2014; O'Donnell et al., 2017a). We chose 10%, which is at the high end of the mitigation range, but well below the desaturation level at which gas starts to migrate upward or spread laterally, reported to occur at 20% for poorly graded (i.e., uniform) fine sands (Pham, 2017).

Following Eq. 5, 7.10 mmol L⁻¹ of total N₂ gas is required to meet a minimum target desaturation level of 10% throughout the entire treatment zone (assuming only desaturation via N₂ gas). To meet the target desaturation, we estimated the treatment recipe to be 22.4 mmol L⁻¹ of nitrate (1.84 g calcium nitrate L⁻¹) and 32.1 mmol L⁻¹ of acetate (2.54 g calcium acetate L⁻¹) using Eq. 6. However, based on background levels of nitrate and nitrite and the use of released ammonium as a nitrogen source, these levels were adjusted to establish the treatment recipe detailed in Table 6. The adjusted values were set to result in complete denitrification (i.e., no residual nitrate or nitrite that relies on bacterial decay as the electron donor) and to not exceed 0.1 mmol L⁻¹ of acetate after complete denitrification. We compared the impact of varying the input levels of acetate (as calcium acetate) on the MIDP treatment to the matched treatment recipe. We tested the impact of addition of an extra 25% of acetate over our original estimations, referred to as the ‘Excess Acetate’ treatment recipe, and 25% less acetate from our original estimation, referred to as the ‘Reduced Acetate’ treatment recipe. For the excess- and reduced-acetate comparisons, we did not adjust the input levels of nitrate (as calcium nitrate) from our original estimations of 22.4 mmol L⁻¹ (1.84 g calcium nitrate L⁻¹). [We assumed that each treatment recipe was added in one application \(i.e., not in a continuous flow-through manner\).](#)

Table 6. MIDP treatment recipes for each modeled condition.

	Original Estimation	Matched	Excess Acetate	Reduced Acetate
Nitrate (mmol L ⁻¹)	22.4 (1.84 g calcium nitrate L ⁻¹)	19.019.9 (1.56 g calcium nitrate L ⁻¹)	22.4 (1.84 g calcium nitrate L ⁻¹)	22.4 (1.84 g calcium nitrate L ⁻¹)
Acetate (mmol L ⁻¹)	32.1 (1.84 g calcium nitrate L ⁻¹)	22.430.9 (1.77 g calcium acetate L ⁻¹)	40.1 (3.17 g calcium acetate L ⁻¹)	24.0 (1.90 g calcium acetate L ⁻¹)

The results of the matched treatment recipe on the subsurface gas volume and saturation profile are shown in the top
two panels of

Formatted Table





Figure 3. For the coastal seawater conditions, the target desaturation level of 10% at 7.6 m (or a degree of saturation of 90%) was achieved by N_2 generation in approximately 2.420 days. The amount of CO_2 produced did not reach its saturation threshold, and CO_2 did not contribute to desaturation at any of the modeled depths. The difference in volume of gas at the different levels is due to the increase in hydrostatic pressure with depth.

The middle panels of Figure 4-3 indicate that adding excess acetate increased the degree of saturation at 7.6 m, which is shown by less than 90% saturation at 7.6 m. In contrast, the bottom two panels show that adding less acetate slowed N_2 generation so that 90% saturation was not reached at 7.6 m in 60 days.







Figure 34. Gas volumes normalized to the total soil volume (left) and degree of saturation by depth for the simulated Coastal seawater conditions. The desaturation target was 10%, or a saturation ratio of 90%.

345 The impacts of the different MIDP treatment recipes on water quality are shown in [Figure 4](#)[Figure-2](#), and the initial
five days of treatment [for each modeled scenario](#) are highlighted in [Figure 5](#)[Figure-3](#). With the matched-treatment recipe,
almost all nitrate and nitrite were consumed by 1.6 days, and [only less than](#) 10^{-4} mol L⁻¹ of acetate remained (Figure [35](#)). Nitrite
accumulation was transient and modest ([3.3](#) mM at its peak); thus, complete denitrification was achieved with this treatment
recipe for coastal seawater conditions (Figure [35](#)). After 1.6 days, sulfate reduction began and continued to occur, driven by
350 microbial endogenous respiration, at a small rate that resulted in the production of more total CO₂ and total H₂S than the
matched treatment over time (Figure [24](#)).

With the excess-acetate recipe, all the nitrate was completely reduced, although small, transient accumulations of
nitrite and nitrous acid occurred (Figure [35](#)). As expected, not all the acetate was consumed with the excess-acetate recipe, and
the remaining acetate led to sulfate reduction and the highest amount of produced H₂S of the three modeled scenarios (Figure
355 [24](#)). Additional N₂ was produced because of the higher amounts of nitrate in the treatment recipe, leading to a level of
desaturation at 7.6 m that exceeded the target 10% value.

For the reduced-acetate test, approximately 20% of the input nitrate remained after all the acetate was consumed, and
this residual nitrate was slowly utilized beyond 1.5 days through biomass endogenous decay (Figure [24](#)). The peak amount of
accumulated nitrite was not as high as the other conditions because of the overall limited nitrate reduction, but some nitrite
360 accumulation remained throughout the modeled 28 days due to the lack of acetate. The dip and quick increase in nitrous acid
around 1.5 to 1.7 days (Figure [35](#)) was due to the shift in electron donor from input acetate to bacterial decay. Not enough
electron donor was available to reduce all of the input nitrate and the accumulated nitrite after 28 days (Figure [24](#)), even though
bacterial decay caused added denitrification. N₂ produced in the reduced-acetate condition did not meet the 10% desaturation
threshold at 7.6 m at the end of the 28-day modeled period.

Formatted: Space After: 0 pt







Figure 42. Water-quality results for 28 days of MIDP in coastal seawater conditions targeting a desaturation level of 10% in three different treatment recipes: empirically matched, 25% excess acetate, and 25% reduced acetate.






Figure 53. Water-quality results for the first 3 days of MDP in coastal seawater conditions targeting a desaturation level of 10% in three different treatment recipes: empirically matched, 25% excess acetate, and 25% reduced acetate.

Nitrite reduction produced most of the base, which is demonstrated by the spike in pH ~~between-after~~ 1.3 and 1.8-4
 days ~~day in all scenarios~~ (Figure 5Figure-3), when the rate of nitrite reduction was at its maximum in each treatment. In the
 matched case, the pH returned to circumneutral after 1.68 days due to the precipitation of CaCO_3 , which consumes base. This
 trend is reinforced by rapid Ca^{2+} consumption in the early treatment time period (Figure 5Figure-3), along with production of
 CaCO_3 in the first ~ 2 days, shown in the right panel of Figure 6Figure-4. DIC production in the excess-acetate treatment
 lagged the matched recipe and was slightly quicker in the reduced-acetate case, which also is seen with the pH trends in Figure
 24 and Figure 35. However, the overall consumption of DIC and subsequent precipitation were slower in the excess- and
 reduced-acetate treatments, which correspond to the longer time for the pH to reach approximately neutral levels. The
 additional CaCO_3 precipitated with the excess acetate resulted from the excess of input calcium, since acetate was added as
 calcium acetate.




Figure 64. DIC concentration and CaCO₃ precipitated during the first 3 days of MIDP in coastal seawater conditions targeting a desaturation level of 10%.

Microbial decay coupled to sulfate reduction also produced more DIC (left panel of Figure 46), promoting additional CaCO₃ precipitation after the completion of denitrification (after day 2 in Figure 4). In the excess-acetate and matched treatments, an increase in DIC after 20-15 days was due to the increased rate of sulfate reduction because of the additional electron donor (Figure 42).

In summary, the simulations show that the matched-acetate recipe optimized MIDP treatment targeted at desaturation for coastal seawater conditions by maximizing the desired outcome (i.e., N₂ production for desaturation) while minimizing undesired by-products (e.g., nitrite and nitrous-oxide accumulation from incomplete denitrification, residual acetate, and H₂S from sulfate reduction).

5 Conclusion

The next-generation biogeochemical model expanded our previous biogeochemical models for MIDP by considering microbial stoichiometry and kinetics for two steps of denitrification and for sulfate reduction. The next-generation model also includes gas-liquid mass-transfer kinetics for N₂ and CO₂, CaCO₃ precipitation kinetics, microbial competition, and inhibition by HNO₂, salinity, and sulfide. Model simulations demonstrated that adding nitrate and acetate using a properly matched recipe led to rapid desaturation without causing unwanted outcomes: incomplete desaturation and accumulations of nitrite and nitrous oxide with too-little acetate, or residual acetate and accelerated H₂S generation with excess acetate. The model can be used to optimize treatment recipes for maximizing desaturation or precipitation in most subsurface groundwater environments for liquefaction mitigation. However, field data describing the environmental biogeochemical characteristics (e.g., pH, background chemical concentrations) for the most optimized results is necessary to understand the potential biogeochemical reactions and processes that may impact MIDP, and subsequently, liquefaction mitigation.

Acknowledgements

The work presented in this paper was funded by the US National Science Foundation (NSF) Engineering Research Center (ERC) program under collaborative agreement ERC-1449501. Any opinions, findings and conclusions or recommendations expressed in this paper are those of the authors and not of the NSF.

Author Contribution

CH and AvT co-developed the model. CH drafted the first version of this paper with input from AvT, LvP, EK, and BR.

Code Availability

The next-generation model was constructed in Matlab and the code and necessary files are publicly available online at
415 doi.org/10.5281/zenodo.7410676 (CC 4.0).

Competing Interests

The authors have no competing interests to declare.

References

- 420 Abdul-Talib, S., Hvitved-Jacobsen, T., Vollertsen, J., and Ujang, Z.: Half saturation constants for nitrate and nitrite by in-sewer anoxic transformations of wastewater organic matter, *Water Sci Technol*, 46, 185–92, 2002.
- Abeling, U. and Seyfried, C. F.: Anaerobic-Aerobic Treatment of High-Strength Ammonium Waste-Water - Nitrogen Removal via Nitrite, *Water Science and Technology*, 26, 1007–1015, 1992.
- 425 Alin, S.R., Feely, R. A., Hales, B., Byrne, R. H., Cochlan, W., Liu, X., and Greeley, D.: Dissolved inorganic carbon, total alkalinity, pH on total scale, and other variables collected from profile and discrete sample observations using CTD, Niskin bottle, and other instruments from NOAA Ship Ronald H. Brown in the U.S. West Coast California Current System from 2016-05-08 to 2016-06-06 (NCEI Accession 0169412), edited by: NOAA and Information, N. C. for E., , <https://doi.org/10.7289/v5v40shg>, 2017.
- 430 Almeida, J. S., Julio, S. M., Reis, M. A. M., and Carrondo, M. J. T.: Nitrite Inhibition of Denitrification by *Pseudomonas-Fluorescens*, *Biotechnology and Bioengineering*, 46, 194–201, <https://doi.org/10.1002/bit.260460303>, 1995.
- Bae, W. and Rittmann, B. E.: A structured model of dual-limitation kinetics, *Biotechnology and Bioengineering*, 49, 683–689, [https://doi.org/10.1002/\(SICI\)1097-0290\(19960320\)49:6<683::AID-BIT10>3.0.CO;2-7](https://doi.org/10.1002/(SICI)1097-0290(19960320)49:6<683::AID-BIT10>3.0.CO;2-7), 1996.
- 435 van den Berg, E. M., Rombouts, J. L., Kuenen, J. G., Kleerebezem, R., and van Loosdrecht, M. C. M.: Role of nitrite in the competition between denitrification and DNRA in a chemostat enrichment culture, *AMB Express*, 7, 91, <https://doi.org/10.1186/s13568-017-0398-x>, 2017.
- Bruland, K. W., Rue, E. L., and Smith, G. J.: Iron and macronutrients in California coastal upwelling regimes: Implications for diatom blooms, *Limnology and Oceanography*, 46, 1661–1674, <https://doi.org/10.4319/lo.2001.46.7.1661>, 2001.
- Cardoso, R. B., Sierra-Alvarez, R., Rowlette, P., Flores, E. R., Gómez, J., and Field, J. A.: Sulfide oxidation under chemolithoautotrophic denitrifying conditions, *Biotechnol Bioeng*, 95, 1148–57, <https://doi.org/10.1002/bit.21084>, 2006.
- 440 Chou, L., Garrels, R. M., and Wollast, R.: [Comparative study of the kinetics and mechanisms of dissolution of carbonate minerals](https://doi.org/10.1016/0009-2541(89)90063-6), *Chemical Geology*, 78(3-4), 268-282, [https://doi.org/10.1016/0009-2541\(89\)90063-6](https://doi.org/10.1016/0009-2541(89)90063-6), 1989.
- Christopher, B., Schwartz, C., and Boudreau, R.: Chapter 5.0 Geotechnical Inputs For Pavement Design, in: *Geotechnical Aspects of Pavements Reference Manual*, U.S. Department of Transportation Federal Highway Administration, 2006.
- 445 Estuardo, C., Marti, M. C., Huilinar, C., Lillo, E. A., and von Bennewitz, M. R.: Improvement of nitrate and nitrite reduction rates prediction, *Electronic Journal of Biotechnology*, 11, <https://doi.org/10.2225/vol11-issue3-fulltext-6>, 2008.
- European Commission. Directorate General for Research.: *Guide to best practices for ocean acidification research and data reporting.*, Publications Office, LU, 2011.
- Glass, C. and Silverstein, J.: Denitrification kinetics of high nitrate concentration water: pH effect on inhibition and nitrite accumulation, *Water Research*, 32, 831–839, [https://doi.org/10.1016/s0043-1354\(97\)00260-1](https://doi.org/10.1016/s0043-1354(97)00260-1), 1998.
- 450 Glass, C., Silverstein, J., and Oh, J.: Inhibition of denitrification in activated sludge by nitrite, *Water Environment Research*, 69, 1086–1093, <https://doi.org/10.2175/106143097x125803>, 1997.

Hall, C., van Paassen, L., Rittmann, B., Kavazanjian, E., DeJong, J., and Wilson, D.: Predicting desaturation by biogenic gas formation via denitrification during centrifugal loading, 7th International Conference on Unsaturated Soils, Hong Kong, China, 2018.

455 Hall, C. A.: Biogeochemical Modeling of Microbially Induced Desaturation and Precipitation, Ph.D., Arizona State University, United States -- Arizona, 189 pp., 2021.

He, J. and Chu, J.: Undrained Responses of Microbially Desaturated Sand under Monotonic Loading, *Journal of Geotechnical and Geoenvironmental Engineering*, 140, 04014003, [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0001082](https://doi.org/10.1061/(ASCE)GT.1943-5606.0001082), 2014.

460 Ingvorsen, K., Zehnder, A. J. B., and Jørgensen, B. B.: Kinetics of Sulfate and Acetate Uptake by *Desulfobacter postgatei*, *Applied and Environmental Microbiology*, 47, 403, 1984.

Jia, M., Winkler, M. K. H., and Volcke, E. I. P.: Elucidating the Competition between Heterotrophic Denitrification and DNRA Using the Resource-Ratio Theory, *Environmental Science & Technology*, 54, 13953–13962, <https://doi.org/10.1021/acs.est.0c01776>, 2020.

465 Krishna Rao, R. and Gnanam, A.: Inhibition of nitrate and nitrite reductase activities by salinity stress in *Sorghum vulgare*, *Phytochemistry*, 29, 1047–1049, [https://doi.org/10.1016/0031-9422\(90\)85400-A](https://doi.org/10.1016/0031-9422(90)85400-A), 1990.

Liang, Z., Sun, J., Zhan, C., Wu, S., Zhang, L., and Jiang, F.: Effects of sulfide on mixotrophic denitrification by *Thauera*-dominated denitrifying sludge, *Environmental Science: Water Research & Technology*, 6, 1186–1195, <https://doi.org/10.1039/C9EW01014A>, 2020.

470 Lilja, E. E. and Johnson, D. R.: Segregating metabolic processes into different microbial cells accelerates the consumption of inhibitory substrates, *ISME J*, 10, 1568–1578, <https://doi.org/10.1038/ismej.2015.243>, 2016.

Little, J. and Moler, C.: Matlab, 2017.

Ma, J., Yang, Q., Wang, S. Y., Wang, L., Takigawa, A., and Peng, Y. Z.: Effect of free nitrous acid as inhibitors on nitrate reduction by a biological nutrient removal sludge, *Journal of Hazardous Materials*, 175, 518–523, <https://doi.org/10.1016/j.jhazmat.2009.10.036>, 2010.

475 Mariangel, L., Aspe, E., Marti, M. C., and Roeckel, M.: The effect of sodium chloride on the denitrification of saline fishery wastewaters, *Environmental Technology*, 29, 871–879, <https://doi.org/10.1080/09593330802015318>, 2008.

Meeussen, J. C. L.: ORCHESTRA: An object-oriented framework for implementing chemical equilibrium models, *Environmental Science & Technology*, 37, 1175–1182, <https://doi.org/10.1021/es025597s>, 2003.

480 Millero, F. J., Feistel, R., Wright, D. G., and McDougall, T. J.: The composition of Standard Seawater and the definition of the Reference-Composition Salinity Scale, *Deep Sea Research Part I: Oceanographic Research Papers*, 55, 50–72, <https://doi.org/10.1016/j.dsr.2007.10.001>, 2008.

Moug, D. M., Sorenson, K. R., Khosravifar, A., Preciado, M., Stallings Young, E., van Paassen, L., Kavazanjian, E., Zhang, B., Stokoe, K. H., Menq, F. M., and Wang, Y.: Field Trials of Microbially Induced Desaturation in Low-Plasticity Silt, *Journal of Geotechnical and Geoenvironmental Engineering*, 148, 05022005, [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0002890](https://doi.org/10.1061/(ASCE)GT.1943-5606.0002890),
485 2022.

- O'Donnell, S. T., Rittmann, B. E., and Kavazanjian, E.: MIDP: Liquefaction Mitigation via Microbial Denitrification as a Two-Stage Process. I: Desaturation, *Journal of Geotechnical and Geoenvironmental Engineering*, 143, [https://doi.org/10.1061/\(asce\)gt.1943-5606.0001818](https://doi.org/10.1061/(asce)gt.1943-5606.0001818), 2017a.
- 490 O'Donnell, S. T., Kavazanjian, E., and Rittmann, B. E.: MIDP: Liquefaction Mitigation via Microbial Denitrification as a Two-Stage Process. II: MICP, *Journal of Geotechnical and Geoenvironmental Engineering*, 143, [https://doi.org/10.1061/\(asce\)gt.1943-5606.0001806](https://doi.org/10.1061/(asce)gt.1943-5606.0001806), 2017b.
- O'Donnell, S. T., Hall, C. A., Kavazanjian, E., and Rittmann, B. E.: Biogeochemical Model for Soil Improvement by Denitrification, *Journal of Geotechnical and Geoenvironmental Engineering*, 145, [https://doi.org/10.1061/\(asce\)gt.1943-5606.0002126](https://doi.org/10.1061/(asce)gt.1943-5606.0002126), 2019.
- 495 Pan, Y., Ye, L., and Yuan, Z.: Effect of H₂S on N₂O reduction and accumulation during denitrification by methanol utilizing denitrifiers, *Environ Sci Technol*, 47, 8408–15, <https://doi.org/10.1021/es401632r>, 2013.
- Pan, Y., Liu, Y., Wang, D., and Ni, B.-J.: Modeling effects of H₂S on electron competition among nitrogen oxide reduction and N₂O accumulation during denitrification, *Environmental Science: Water Research & Technology*, 5, 533–542, <https://doi.org/10.1039/C8EW00873F>, 2019.
- 500 Panswad, T. and Anan, C.: Specific oxygen, ammonia, and nitrate uptake rates of a biological nutrient removal process treating elevated salinity wastewater, *Bioresource Technology*, 70, 237–243, [https://doi.org/10.1016/S0960-8524\(99\)00041-3](https://doi.org/10.1016/S0960-8524(99)00041-3), 1999.
- Papaspyrou, S., Smith, C. J., Dong, L. F., Whitby, C., Dumbrell, A. J., and Nedwell, D. B.: Nitrate Reduction Functional Genes and Nitrate Reduction Potentials Persist in Deeper Estuarine Sediments. Why?, *PLOS ONE*, 9, e94111, <https://doi.org/10.1371/journal.pone.0094111>, 2014.
- 505 Pham, V.: Bio-based ground improvement through Microbial Induced Desaturation and Precipitation (MIDP), Delft University of Technology, <https://doi.org/10.4233/UUID:3997066A-0AD6-4DE2-9C79-E5E474BAE20F>, 2017.
- Pham, V. P., van Paassen, L. A., van der Star, W. R. L., and Heimovaara, T. J.: Evaluating Strategies to Improve Process Efficiency of Denitrification-Based MICP, *Journal of Geotechnical and Geoenvironmental Engineering*, 144, [https://doi.org/10.1061/\(asce\)gt.1943-5606.0001909](https://doi.org/10.1061/(asce)gt.1943-5606.0001909), 2018.
- 510 Rittmann, B. and McCarty, P.: *Environmental Biotechnology: Principles and Applications*, McGraw-Hill Companies, Incorporated, 2020.
- Rittmann, B. E., Banaszak, J. E., VanBriesen, J. M., and Reed, D. T.: Mathematical modeling of precipitation and dissolution reactions in microbiological systems, *Biodegradation*, 13, 239–250, <https://doi.org/10.1023/A:1021225321263>, 2002.
- 515 Rittmann, B. E., Banaszak, J. E., Cooke, A., and Rowe, R. K.: Biogeochemical Evaluation of Mechanisms Controlling CaCO₃(s) Precipitation in Landfill Leachate-Collection Systems, *Journal of Environmental Engineering*, 129, 723–730, [https://doi.org/10.1061/\(ASCE\)0733-9372\(2003\)129:8\(723\)](https://doi.org/10.1061/(ASCE)0733-9372(2003)129:8(723)), 2003.
- Salek, S. S., van Turnhout, A. G., Kleerebezem, R., and van Loosdrecht, M. C. M.: pH control in biological systems using calcium carbonate, *Biotechnology and Bioengineering*, 112, 905–913, <https://doi.org/10.1002/bit.25506>, 2015.
- 520 Senga, Y., Mochida, K., Fukumori, R., Okamoto, N., and Seike, Y.: N₂O accumulation in estuarine and coastal sediments: The influence of H₂S on dissimilatory nitrate reduction, *Estuarine, Coastal and Shelf Science*, 67, 231–238, <https://doi.org/10.1016/j.ecss.2005.11.021>, 2006.

Shin, W. S., Park, J. C., and Pardue, J. H.: Oxygen dynamics in petroleum hydrocarbon contaminated salt marsh soils: III. A rate model, *Environmental Technology*, 24(7), 831–843, <https://doi.org/10.1080/09593330309385620>

Šimek, M. and Cooper, J. E.: The influence of soil pH on denitrification: progress towards the understanding of this interaction over the last 50 years, *European Journal of Soil Science*, 53, 345–354, <https://doi.org/10.1046/j.1365-2389.2002.00461.x>, 2002.

Singurindy, O., Berkowitz, B., and Lowell, R. P.: Carbonate dissolution and precipitation in coastal environments: Laboratory analysis and theoretical consideration, *Water Resources Research*, 40, <https://doi.org/10.1029/2003wr002651>, 2004.

Soto, O., Aspé, E., and Roeckel, M.: Kinetics of cross-inhibited denitrification of a high load wastewater, *Enzyme and Microbial Technology*, 40, 1627–1634, <https://doi.org/10.1016/j.enzmictec.2006.11.014>, 2007.

Spanos, N. and Koutsoukos, P. G.: Kinetics of Precipitation of Calcium Carbonate in Alkaline pH at Constant Supersaturation. Spontaneous and Seeded Growth, *The Journal of Physical Chemistry B*, 102, 6679–6684, <https://doi.org/10.1021/jp981171h>, 1998.

Tugtás, A. E. and Pavlostathis, S. G.: Effect of sulfide on nitrate reduction in mixed methanogenic cultures, *Biotechnology and Bioengineering*, 97, 1448–1459, <https://doi.org/10.1002/bit.21338>, 2007.

van Turnhout, A. G., Kleerebezem, R., and Heimovaara, T. J.: A toolbox to find the best mechanistic model to predict the behavior of environmental systems, *Environmental Modelling & Software*, 83, 344–355, <https://doi.org/10.1016/j.envsoft.2016.05.002>, 2016.

Vavilin, V. A. and Rytov, S. V.: Nitrate denitrification with nitrite or nitrous oxide as intermediate products: Stoichiometry, kinetics and dynamics of stable isotope signatures, *Chemosphere*, 134, 417–26, <https://doi.org/10.1016/j.chemosphere.2015.04.091>, 2015.

Veshareh, M. J., Kjeldsen, K. U., Findlay, A. J., Nick, H. M., Røy, H., and Marietou, A.: Nitrite is a more efficient inhibitor of microbial sulfate reduction in oil reservoirs compared to nitrate and perchlorate: A laboratory and field-scale simulation study, *International Biodeterioration & Biodegradation*, 157, 105154, <https://doi.org/10.1016/j.ibiod.2020.105154>, 2021.

Yongsiri, C., Vollertsen, J., Rasmussen, M., and Hvitved-Jacobsen, T.: Air–Water Transfer of Hydrogen Sulfide: An Approach for Application in Sewer Networks, *Water Environment Research*, 76, 81–88, <https://doi.org/10.2175/106143004X141618>, 2004.