

Large-scale automated emission measurement of individual vehicles with point sampling

Markus Knoll¹, Martin Penz¹, Hannes Juchem², Christina Schmidt^{2,3}, Denis Pöhler^{2,3}, and Alexander Bergmann¹

¹Institute of Electrical Measurement and Sensor Systems, Graz University of Technology, Inffeldgasse 33/I, 8010 Graz, Austria

²Institute of Environmental Physics, Heidelberg University, INF 229, 69120 Heidelberg

³Airyx GmbH, Justus-von-Liebig-Str. 14, 69214 Eppelheim, Germany

Correspondence: Markus Knoll (markus.knoll@tugraz.at)

Abstract. Currently, emissions from internal combustion vehicles are not properly monitored throughout their life cycle. In particular, a small share of vehicles (< 20 %) with malfunctioning after-treatment systems and old vehicles with outdated engine technology are responsible for the majority (60-90 %) of traffic-related emissions. Remote emission sensing (RES) is a method used for screening emissions from a large number of in-use vehicles. Commercial open-path RES systems are capable of providing emission factors for many gaseous compounds, but they are less accurate and reliable for particulate matter (PM). Point sampling (PS) is an extractive RES method where a portion of the exhaust is sampled and then analyzed. So far, PS studies have been conducted predominantly on a rather small scale and have mainly analyzed heavy duty vehicles (HDV), which have high exhaust flow rates. In this work, we present a comprehensive PS system that can be used for large-scale screening of PM and gas emissions, largely independent of the vehicle type. The developed data analysis framework is capable of processing data from thousands of vehicles. The core of the data analysis is our peak detection algorithm (TUG-PDA), which determines and separates emissions down to a spacing of just a few seconds between vehicles. We present a detailed evaluation of the main influencing factors on PS measurements by using about 100,000 vehicle records collected from several measurement locations, mainly in urban areas. We show the capability of the emission screening by providing real-world black carbon (BC), particle number (PN) and nitrogen oxides (NO_x) emission trends for various vehicle categories such as diesel and petrol passenger cars or HDVs. Comparisons with open-path RES and PS studies show overall good agreement and demonstrate the applicability even for the latest Euro emission standards, where current open-path RES systems reach their limits.

1 Introduction

Exhaust emissions from combustion-based vehicles are negatively affecting human health and our environment. Of specific interest are nitrogen oxides (NO_x) and particulate matter (PM) emissions due to the known impact on health, environment and climate (Mannucci et al., 2015; EEA, 2017). NO_x emissions remain a widespread problem, especially for diesel-powered vehicles, where tampered, defective and old vehicles are the main source of high emission levels (Meyer et al., 2023). For PM it is well known from literature, that a small share of vehicles (< 20 %) contribute to the vast amount (60-90 %) of emissions

(Park et al., 2011; Burtscher et al., 2019; Boveroux et al., 2019; Bainschab et al., 2020). This is due to malfunctioning after-treatment systems, such as defective diesel particulate filters (DPF) and old vehicles with degenerated or outdated technologies.

25 It would be highly beneficial to human health and our environment if these high emitters could be identified and subsequently maintained to significantly reduce emissions. Most current regulations are only related to type approval procedures, but do not consider deterioration (e.g., of the exhaust after-treatment system), defects that are not properly repaired or tampering that occurs in the lifetime of the vehicles (Mock and German, 2015; Bainschab et al., 2020). Particle number (PN) and black carbon (BC) are two PM metrics of particular interest. In addition to its impact on health and climate, BC is a suitable tracer

30 for vehicles with high PM emissions (Salimbene et al., 2021; Rönkkö et al., 2023). Interest in real-world PN emissions is growing due to newly introduced regulations (Giechaskiel et al., 2021) and known health effects on the human respiratory and cardiovascular systems (Oberdörster et al., 2005; Brook et al., 2010).

Different strategies exist which try to address these issues. PN concentration measurements during periodic technical inspections are currently implemented in several European countries like Germany, the Netherlands, Switzerland and Belgium. The

35 PN inspections should identify malfunctioning vehicles during low-idle operation (Bainschab et al., 2020; Giechaskiel et al., 2020; Melas et al., 2021; Giechaskiel et al., 2021). A disadvantage of the periodic technical inspections is that they are in the best case annual, one-time measurements performed under non real driving conditions, which can potentially be circumvented by tampering or by manipulating measurements.

Another approach taken for high emitter identification and the screening of real-world emissions of in-use vehicles is remote

40 emission sensing (RES). RES is employed directly at the roadside to measure emissions from passing vehicles under real driving operating conditions (Bishop et al., 1989; Borcken-Kleefeld and Dallmann, 2018). One advantage of RES is that the vehicles are measured during their normal operation, which complicates fraud. Commercially available RES systems are open-path systems that detect the light extinction of the exhaust plume at different wavelengths to measure different pollutants emitted by passing vehicles (Bishop et al., 1989; Stedman et al., 1992; Moosmüller et al., 2003; Burgard et al., 2006). These

45 systems deliver statistically acceptable emission factors (EFs) for gaseous species, but EFs are inaccurate for particulates. In particular, PM emissions of the latest Euro emission standards (Euro 6, Euro VI and beyond) are below the quantification limit of open-path RES systems (Gruening et al., 2019; Cha and Sjödin, 2022; Jerksjö et al., 2022). Other PM metrics such as PN or BC are not measured by these systems as they only give PM mass emission estimates (Knoll et al., Under review). Complementary RES concepts exist which can be applied to counteract the downsides of these systems. In plume chasing, a

50 measurement vehicle equipped with laboratory grade analyzers traces vehicles under test. Several studies (Ježek et al., 2015; Järvinen et al., 2019; Pöhler et al., 2019; Wang et al., 2020) have shown that reliable EFs can be determined by chasing the vehicle under test over a short time period. The disadvantage of plume chasing is that it is a rather labor-intensive method which can only be applied to a small number (< 200) of vehicles per chasing vehicle and day.

Extractive point sampling (PS) is a roadside measurement technique (see Fig. 1) that can be used to capture the plumes from

55 passing vehicles by sampling the diluted exhaust (Hansen and Rosen, 1990; Janhäll and Hallquist, 2005; Hak et al., 2009; Ban-Weiss et al., 2009). Compared to open-path RES systems the installation of the measurement setup is relatively simple. The sample is usually directly extracted at the road surface or at the roadside, as close as possible to the tailpipe of the passing

vehicles. A small shelter or a van next to the sample extraction houses the instruments that analyze the captured emissions of the passing vehicles (Hak et al., 2009). With PS, particle metrics such as PN and BC as well as gaseous compounds can be measured equally well if suitable instruments are selected. PS studies have predominantly measured heavy duty vehicles (HDV) or buses by sampling from the roadside (Hallquist et al., 2013; Watne et al., 2018; Liu et al., 2019; Zhou et al., 2020) or, by sampling from the top of tunnels or bridges for HDVs with a vertical exhaust pipe, which are common in the US (Ban-Weiss et al., 2008, 2009, 2010; Dallmann et al., 2011, 2012; Preble et al., 2015; Bishop et al., 2015; Preble et al., 2018; Sugrue et al., 2020). In these applications, the plumes can be resolved relatively easily, as specific vehicle types are measured or measurements are carried out at selected locations (e.g. bus stations). In dense traffic, difficulties arise when using instruments with limited dynamic range or large response time because the plumes can not be separated (Hak et al., 2009). Detailed analysis of fleet emissions by characteristics such as emission standard, manufacturer or vehicle age were performed mainly in PS studies measuring HDVs and buses (Dallmann et al., 2011; Bishop et al., 2015; Preble et al., 2015, 2018; Liu et al., 2019; Zhou et al., 2020). PS systems capable of large-scale emission screening independent of vehicle type are rare and have only been applied for vehicles classified by length (Wang et al., 2015, 2017) or number of axes and tires (Ban-Weiss et al., 2008, 2010; Dallmann et al., 2013, 2014) or for gaseous compounds using sensor networks (Chu et al., 2022). To the best of our knowledge, there are only individual PS studies in which the LDV emissions of a few test vehicles were determined based on characteristics such as the Euro emission standard (Hak et al., 2009; Ježek et al., 2015). Analysis of emissions by emission standard, manufacturer or age provides more detailed information, e.g. on whether emission limits are generally being met or whether certain manufactures or vehicles stand out.

In this work, we present a comprehensive PS technique used for large-scale emission screening of individual vehicles, largely independent of the vehicle type. The PS setup measures different PM metrics as well as gaseous compounds and allows emission measurements to be carried out in dense traffic down to a distance of just a few seconds between the vehicles. The core of this work is a data analysis framework that is capable of processing data from thousands of vehicles. The main part of the data analysis is our peak detection algorithm (TUG-PDA)¹, which separates emissions down to a spacing of a few seconds between the vehicles. We provide a detailed insight into the developed PS methodology by discussing the dependencies and key factors, including instrument selection criteria, measurement site selection, sample extraction, vehicle dependencies and weather influences. We show the capability of the system by providing real-world BC, PN and NO_x emission trends for passenger cars and HDVs up to the latest Euro emission standards. We use the term pollutant for all measured analytes except CO₂. Important definitions for RES emission calculations are described in Appendix A.

¹TUG stands for Technical University of Graz

2 Method

2.1 Measurement setup

We propose a PS setup as illustrated in Fig. 1, which allows automated post-processing down to a small distance between the vehicles. The main components are described below.




Figure 1. Schematic (left) and picture (right) of the proposed PS measurement setup, highlighting the required equipment.

90 **Vehicle pass detection:** The exact passing time of the vehicles is of great significance for automated post-processing. This is especially the case if several vehicles pass by the measurement location and they have only a small spacing between them. The exact passing time is required during data post-processing to resolve the different plumes correctly. Important variables related to the vehicle condition during the passing are the speed and acceleration. These are required to determine the vehicle specific power (VSP) (see Appendix A3). Emissions from passing vehicles strongly depend on the engine load conditions.

95 Therefore, they must be treated accordingly (Bernard et al., 2018; Davison et al., 2020). For this purpose, we deployed custom-built light barriers to measure the passing time, speed and acceleration of the passing vehicles. Using light barriers restricts the measurement location to single-lane roads or roads with islands between the lanes. Alternatively, vehicle detection can be performed with radar, video, or LiDAR systems.

License plate recognition: Vehicle technical data are required for several post-processing steps which are described in more detail in the data analysis section later on. Automated number plate recognition (ANPR) systems are commonly used for license plate detection. Depending on the system, additional attributes such as the vehicle pass time or acceleration can be measured.

100 Attention must be paid to the ANPR camera performance, as several influencing factors can exist. License plates are often dirty (especially in winter) or the ANPR camera may not be able to correctly detect all the plates of the passing vehicles, especially

if they pass within short intervals. This impedes data post-processing and underlines the importance of accurate vehicle pass
105 detection. In our setup, the ANPR camera is mounted in the front cabin of the measurement van (see Fig. 1), allowing the
license plates to be detected about 2-3 s after the vehicle passes the light barriers. Based on our practical experience, we
recommend determining the vehicle pass time separately from acquiring the license plate data.

Emission measurement: The emission measurement can be split into two main parts: First, the emissions are sampled and
second, these are subsequently analyzed with the employed instrumentation. A schematic of the emission measurement setup
110 used during one of the campaigns can be found in the supplementary material.

– Sampling: The importance of sample extraction is often underestimated. In PS, the sampling is usually performed with
a simple tube which collects the diluted exhaust from the passing vehicles (Hak et al., 2009; Hallquist et al., 2013; Liu
et al., 2019; Zhou et al., 2020). We sample either from the middle of the road or from the roadside depending on the
circumstances (e.g. permissions, road conditions). When sampling from the center of the road, we covered the tube with
115 a small cable duct that was taped to the road. The position of the sampling inlet strongly influences the strength (dilution)
of the measured plume and even determines whether the plume can be captured at all. In general, the closer the sample
inlet is to the emission source (tailpipe), the smaller the dilution and the higher the capture rate are. We found typical
dilution factors between 100 and 500, which is in good agreement with literature (Hak et al., 2009). In addition, the
length of the sampling line must be considered in relation to the sample flow. The pressure drop should be minimal and
120 the losses must be taken into account, especially when performing PM measurements (Kulkarni et al., 2011). Attention
should also be paid to the material of the tubing. We use tygon tubing for particle measurement because of the flexibility
and low particle losses (Giechaskiel et al., 2012).

– Instrumentation: Instrument characteristics have a great influence on the quality of the measured emission data. Sugrue
et al. (2020) compared high- and low cost BC and CO₂ sensors for their application in PS. They found that low-cost
125 CO₂ sensors may be an adequate substitute for research-grade analyzers in contrast to low-cost BC instruments. In their
conclusion, they also emphasized that sensors should be tested under field-conditions. Hak et al. (2009) mentioned in
their PS experiments that the small dynamic range of the condensation particle counter used constrained the PN mea-
surements. Therefore, they used a dilution volume which extended the measured emission concentration peaks and the
fall time of the signals to 5-15 s. The dilution and the relatively large response times of the particle instruments limited
130 the operation to low-traffic situations. Based on the recommendations by Hak et al. (2009) and our own experiences, we
have defined the most important requirements for the instruments, which are stated in Table 1. These must be respected
to avoid significant problems in PS. In addition, recommendations are given for the different requirements. The emission
events associated with the passing vehicles are of very transient nature. To capture these events, instruments must have a
fast response time ($t_{90} < 1-2$ s) and a high time resolution (at least 1 s). In PS, the sampled emissions are highly diluted.
135 Therefore, small concentrations must be resolved. To accurately measure the varying concentrations, the instruments
must have a high dynamic range. The measured concentrations can be within a range of four orders of magnitude and
depend on the vehicle type, engine state, sampling position and environmental conditions, as well as other factors. It

is also important to ensure that the species of interest is measured with minimal cross-sensitivity to other compounds. Therefore, instruments with qualified measurement principles should be selected. Environmental conditions (e.g., temperature, relative humidity, background (BG) concentrations) differ depending on the measurement location, time and season of the year and care should be taken to ensure that they do not affect the instruments. RES campaigns often last for long periods of time (several weeks or months). Therefore, instruments must be stable over the long term. Due to restrictions in the use of calibration sources such as gas bottles or particle sources, the instruments should feature stable calibration over periods of weeks even under harsh environments. Instruments which do not require in-field calibration are preferred. To perform measurements under all conditions, an instrument housing is required, which can be a small shelter or a measurement van.

Problem	Instrument requirement	Recommendation
Transient nature of emission events	Short (t_{90}) response time High time resolution	$\leq 1-2$ s ≤ 1 s
High exhaust dilution in ambient air	Low limit of detection (at 1 s time resolution)	BC: $1 \mu\text{g m}^{-3}$ PN: $1,000 \# \text{ cm}^{-3}$ CO ₂ : 5 ppm NO ₂ : 2 ppb NO _x : 5 ppb
Varying concentrations	High dynamic range	BC: 0 - 2 mg m^{-3} PN: 0 - $2\text{e}6 \# \text{ cm}^{-3}$ CO ₂ : 0 - 3,000 ppm NO ₂ : 0 - 2,000 ppb NO _x : 0 - 10,000 ppb
Interfering species	Minimal cross sensitivity Minimal artefact formation	Qualified measurement principle For PN: Solid particle number (SPN) measurement

Table 1. Instrument requirements, problem statements and recommendations for PS emission measurements of selected particle metrics and gases.

Monitoring of environmental conditions: It is advantageous to make additional measurements of environmental conditions at the measurement location. Local monitoring of wind speed and direction provides information relevant for the sample extraction and can improve the post-processing. Measurements of precipitation, ambient temperature and relative humidity can also provide useful information and help to understand anomalies. We have used data from weather stations either in the area or preferably directly at the PS site.

2.2 Data analysis

The data analysis deals with the determination of representative EFs from the collected measurement data of the captured vehicles. The following aspects must be taken into account:

- 155 – Handling and harmonization of data (concentration time series) collected with various instruments.
- Consideration of measurement parameters such as sampling delay or instrument response times.
- Detection and separation of the plumes from the passing vehicles.
- Relation between vehicle pass (time), concentration time series and license plates.
- Dealing with changing environmental conditions (e.g., BG concentrations, other emission sources, weather conditions)
- 160 that can affect the measurement

In order to deal with the requirements listed above, a comprehensive software framework has been developed. The developed procedure is divided into three major processing steps, namely the pre-processing, the emission event processing and the emission analysis and statistics. The pre-processing reads the raw time series files from various instruments and the recorded data from the light barriers (time, speed, acceleration) and prepares them for the next processing steps. These data are analyzed

165 in the emission event processing part of the procedure. The EFs are then calculated in the emission analysis step, and statistics are performed to subsequently evaluate the EFs. An overview of the data analysis procedure is visualized in Fig. 2. The software framework is designed for modularity and extensibility. New instruments and measurement campaigns can be easily integrated into the framework by copying existing instruments or campaigns and adjusting the parameters. The software has not been developed for specific instruments and in general any measurement device that provides continuous measurement data

170 can be integrated. However, we strongly recommend to consider the recommendations in Table 1 when selecting instruments to achieve the best possible results. The software framework is implemented in Python by using common libraries such as Pandas, NumPy, Matplotlib, or SciPy. The basic framework of the software can be found here: <https://gitlab.com/tug-ems/point-sampling.git>.

2.2.1 Pre-processing

175 Prior to the actual emissions calculations, three main steps are taken to prepare the raw instrument data.

1. Time series data from the different instruments are time-aligned based on manual pollution peaks (e.g. taken with a lighter) taken during the measurement campaign (time alignment to ± 1.0 s, see supplementary material).
2. The time resolution of the CO₂ and pollutant data is equated (default time resolution of 0.5 s) and the CO₂ and pollutant data sets are combined into a composite data set.




Figure 2. Overview of the PS data analysis procedure.

180 3. The time series data are then smoothed with a rolling Gaussian filter (default window size 5 samples) to reduce the dependence on short variations and outliers. If instruments with large differences in response times ($\Delta t > 2$ s) are used, the response function of the instruments must be aligned.

2.2.2 Emission event processing

We have developed a dedicated algorithm, TUG-PDA, which separates the measured emissions and assigns them to the by-passing vehicles. The algorithm is fully configurable with various adjustable parameters defining thresholds or quality assurance (QA) measures. Fig. 3 shows the main processing steps of the TUG-PDA algorithm, separated for CO₂ on the left and for pollutant emissions on the right. The TUG-PDA loops through all vehicle pass data and is applied first to CO₂ and afterwards to each pollutant (e.g. NO_x, BC). The CO₂ time series and the time series of the measured pollutants (e.g., BC, PN, NO_x) are separately processed, since PM and gaseous emissions can occur at a different time. The main processing steps are the same, but several processing steps are only performed when processing CO₂ emissions (plume strength), or when processing

185

190

pollutant emissions (cross-checks with CO₂). The processing steps are explained in the following paragraphs, including step numbers that refer to Fig. 3 (TUG-PDA overview) and Fig. B1 (TUG-PDA details).

1 Start conditions: The vehicle pass time is used as the starting point for the plume detection. Several QA measures (shaded boxes in Fig. B1) are implemented to prevent wrongly assigned emissions or inaccurate results. The following steps are performed and the conditions must be met to continue processing the current vehicle.

- 1a Vehicle distance: First, when a new vehicle pass is fetched, it is checked whether the distance to the next vehicle pass is sufficient (≥ 3 s). If this is not the case, the processing of the current vehicle is stopped and the algorithm proceeds to the next vehicle. With a spacing of less than 3 s, there is a large uncertainty that emissions will be attributed to the wrong vehicle due to differences in the sampling delay between vehicles.
- 1b CO₂ emission valid: When processing pollutant emissions, the processing of the current vehicle is skipped if no valid CO₂ plume was detected during CO₂ processing.
- 1c Search for emission gradient (peak): The TUG-PDA searches (default window: -1 s to 6 s) for a sequence of data points with positive concentration gradients above a defined threshold (see Table 2) of the processed analyte around the vehicle pass time (visualized in Fig. 4). There must be either at least two data points of the analyte with a gradient above the threshold or one data point with a very large gradient (> 10 times the threshold). The time of the first rising gradient is used as the starting point for the plume integration.

Analyte	Threshold
CO ₂	8 ppm s ⁻¹
BC	4 ($\mu\text{g m}^{-3}$) s ⁻¹
PN	4,000 ($\# \text{ cm}^{-3}$) s ⁻¹
NO _x	12 ppb s ⁻¹

Table 2. Default gradient thresholds defined in the TUG-PDA for the peak search.

- 1d Separability: The detected gradient (plume) must not be from a previous vehicle. The processing is skipped if either:
 - A rising gradient (start condition) from the previous vehicle is found within a pre-defined time frame (default: 3 s before the vehicle pass of the current vehicle) and the plume directly interferes with the current vehicle.
 - Or a significantly higher pollutant concentration was measured in the last period (default: 25 s) than for the current vehicle and the current vehicle is likely to be affected by this emission. This is the case when the emission of the previous vehicle was much higher than the peak of the current vehicle and the BG concentration before the current vehicle is still significantly higher than the BG without vehicles.
- 1e Pollutant vs CO₂: The pollutant peak must start within a pre-defined window compared to the CO₂ peak (default window: -1 to 3 s).




Figure 3. Emission event processing - flow charts of the peak detection algorithm (TUG-PDA). CO₂ and pollutant (e.g., BC, PN, NO_x) emissions are processed separately. The algorithm is applied first to CO₂ (left) and then to the individual pollutant emissions (right). A detailed flow chart can be found in the Appendix (Fig. B1)

2 BG determination: Before integrating the peak, the BG concentration is determined. We divide the BG determination into the following two cases:

- No interference: If there is no interference from a previous vehicle, this case is used. We found that the minimum of the running mean concentration just before the vehicle pass was the best fit as it represents the actual condition. In this study we used a window of 4 s (8 samples) before the integration start time. Similar approaches have been used in the literature to determine BG concentrations (Ban-Weiss et al., 2008; Wang et al., 2015).
- Interference: The plumes overlap when vehicles pass the measurement point within a short period of time. In this case, the mean value is taken between the median concentration directly before the starting point of the integration (default window size: 3 s) and a general BG value taken within the last few minutes that is not influenced by vehicles. Here we search for the last time frame in which no vehicle plume was detected. If no such window (default length: 8 s) is found in the last 10 minutes, a statistically determined BG value is calculated by removing emissions above the 75th percentile of




Figure 4. Time series example of sampled PS data (BC, CO₂) from two vehicle passages. The integrated areas of the CO₂ and BC emission concentrations are highlighted for the first passing vehicle using the TUG-PDA as described in Sect. 2.2.2. The start time range of the algorithm is indicated for the first vehicle pass.

the dataset used. A moving average filter (default window size: 30 s) is applied to the resulting dataset and the minimum value is used as BG. Examples of BG subtracted emissions from overlapping plumes are shown in Fig. 5.

3 Emission integration and separation: After determining the BG, the concentration of the exhaust plume is integrated until one of the defined stop conditions is reached (see Fig. B1):

- Stop 1: The maximum allowed duration (default length: 25 s) of the emission event is exceeded.
- Stop 2: The concentration falls below the BG concentration.
- Stop 3: Another vehicle pass is observed and the concentration gradient increases.
- Stop 4 (Pollutant only): The pollutant integration exceeds the stop time of the CO₂ event by a defined value (default: 3 s).
- Stop 5 (Pollutant only): The integration interval of the pollutant emission event (duration of the integrated areas) exceeds the integration interval of the CO₂ emission event by a defined value (default: 1 s).

In addition to the QA measures applied during the start conditions, the following tests are performed after the integration to verify whether the emission is considered valid:

- 3a Duration: The integration interval must exceed a minimum value (default: 3 s).
- 3b Plume strength (CO₂ only): The integrated CO₂ area must be greater than a defined minimum (default: 80 ppm s).

- 3c Pollutant vs CO₂: The integration interval of the CO₂ emission event including a pre-defined factor (default: $t_{\max \text{ diff}} = 0.6$) must not be greater than the integration interval of the pollutant emission event.
- 3d Pollutant vs CO₂: The CO₂ and pollutant integration intervals must overlap to a certain extent (default: by at least 50 percent).

245

L Low emitter processing: When processing the pollutant data, a special case is implemented in order to consider low emitters (Fig. 3, highlighted in dark gray). This is the case if either no emission gradient (peak) was found, the duration of the emission event is below the lower limit of the integration interval, or if the integration interval of CO₂ is too long compared to the integration interval of the pollutant. If one of the three conditions is not met, then the pollutant concentration is integrated over the same time period as the captured CO₂ event associated with the passing vehicle. Similarly to the general procedure, the BG determination is separated into the two cases described (without/with interference) and the integration is stopped if another vehicle pass is observed and the measured concentration increases.

250

4 Store results: The emission event is considered valid (highlighted in green in Fig. 3) if the start and post integration QA conditions are met. If these conditions are not met the emission event is invalid. The TUG-PDA continues processing the next vehicle pass.

255

Once the TUG-PDA has finished processing all the vehicle passes, the emission ratios (ER) of each vehicle pass (see Sect. A1) are calculated.

Alternative methodologies exist for emission processing in PS. The captured CO₂ and pollutant emissions are commonly integrated over the same time frame (Ban-Weiss et al., 2009; Ježek et al., 2015; Liu et al., 2019; Zhou et al., 2020). Automated PS emission processing and peak detection algorithms can also be found in previous studies. Wang et al. (2015) presented a plume identification algorithm that takes different approaches in the case of plume separation (minimum plume length of 10 s) or low emitter detection. An open source mobile air quality dashboard, including a real-time peak detection algorithm was published by Kelly et al. (2023). Another new approach proposed by Farren et al. (2023) is the so-called rolling regression method. This algorithm simplifies data processing by calculating the ERs for three consecutive data samples, which makes the BG determination redundant. This is a particularly promising approach for short emission events of high emitter. One challenging aspect of this approach is the determination of low emissions from the latest emission standards. Another aspect is that the instrument responses for CO₂ and measured pollutants must be perfectly matched when taking this approach. The applicability of this approach to evaluate PM pollutants still needs to be studied due to the disparity between gaseous and PM emissions.

260

265

270 2.2.3 Emission analysis and statistics

Once the ERs of passing vehicles have been determined the measurement results are combined with the vehicle's technical data. Several details from the vehicle technical data are required during the emission analysis to calculate EFs and to perform further statistical analysis. Necessary fields for our post-processing are:

- The fuel type (e.g., gasoline, diesel) to calculate fuel-based EFs.

- 275
- The CO₂ emissions measured during the type-approval process of the vehicle model are required to calculate the distance-related EFs.
 - The European emission standard class is used to classify vehicles according to their emission limits.
 - The vehicle category is used to perform detailed evaluations for specific vehicle types.

With the help of our local partners, we obtained the necessary technical data from the government authorities. The captured license plates are pseudo-anonymized to respect privacy rules.

As part of our data post-processing procedure, the vehicle technical data as requested from the authorities and detected by the ANPR camera must be related to the ERs. These are then assigned to the passing time as gathered with the light barriers. We use the speed and acceleration information of the passing vehicles to match the passing time with the detected license plate. This generally sounds like a simple task. However, not all license plates are correctly detected by the ANPR camera for various reasons (e.g., dirt, poor light conditions, too little distance between the vehicles). This makes the task of correctly matching the data from the ANPR camera and light barriers challenging, and specially for vehicles that follow each other closely.

2.3 Capture rate

In RES, the proportion of valid measurement records is a significant indicator. We call this indicator the capture rate (CR), which is the ratio between the number of vehicle passes for which valid EFs can be calculated and all vehicle passages (Eq. 1).

290

$$CR = \frac{\# \text{ valid } EF}{\# \text{ all vehicle passes}} \quad (1)$$

What is considered as a valid measurement is always subjective. We consider the calculated emissions to be valid if the plume from the passing vehicle was properly captured and an EF can be calculated. This is the case if the following conditions are considered to be true:

- The integrated CO₂ plume is greater than a specified threshold. In this study, 80 ppm s was used.
- The emissions of the passing vehicle can be separated from those of other vehicles. This is not the case if the plumes cannot be separated or if the emissions can't be unambiguously assigned to one vehicle (see Fig. B1).

3 Results and discussion

3.1 TUG-PDA emission separation capabilities

The TUG-PDA resolves emissions down to a small distance (default: 3 s) between vehicles, if the time between the vehicles is large enough (greater than 3 s) and if a dedicated CO₂ peak from the vehicle is observed. Several tests are implemented to determine whether the emissions really come from the current vehicle or are caused by interference from previous vehicles or

another source. If other influences are observed, the distance between the vehicles is too small, or overlapping plumes cannot be separated, the measurement is invalid and the emissions for the vehicle cannot be determined. Plume separation can be tuned using several parameters such as *gradient thresholds* (Table 2), *the minimum time allowed between vehicles* or *the minimum number of samples required* as used in the software. This can be very useful for instruments with different response times and for locations with dense traffic to obtain a sufficient number of measurements. Restricting measuring to low-traffic areas would severely limit the application.

Fig. 5 shows two PS time series examples that demonstrate the capabilities and the limitations of the TUG-PDA for plume separation from passing vehicles. The BC and CO₂ emissions assigned to the passing vehicles are highlighted in black and blue, respectively. In both examples, the BG concentrations are subtracted from the integrated areas. In the data shown in Fig. 5 on the left, the TUG-PDA is able to separate emissions for three (V1, V3, V4) out of four vehicles. CO₂ and BC peaks are evident for all four passing vehicles, but to varying degrees. For the vehicles V1, V3 the algorithm stops integrating the emissions because another vehicle (V2 and V4) is passing and the concentrations are rising. For vehicle V4, the integration is stopped because the BG value is undercut. The plume detected from vehicle V2 is invalid because the CO₂ gradient is not above the threshold and the integrated area is below the minimum value (80 ppm s). The algorithm can be easily tuned to detect emissions from vehicle V2, but as plume strength decreases, inaccuracies increase. This is due to the increasing dependence on the BG determination and is even more pronounced when the plumes overlap. The right part of Fig. 5 shows a data example where the emissions of most passing vehicles cannot be resolved properly due to high traffic density. The emissions of the vehicles V1 and V2 can be resolved as the distance between the vehicles is large enough (≥ 3 s) and two distinct CO₂ peaks are detected. Both vehicles can be considered as low BC emitters as no BC peaks were measured. No EFs can be determined for the vehicles V4, V5, V8, V9 and V10 because the distance between the vehicles is too small and no distinct CO₂ peaks can be assigned to them. The vehicles V3, V6 and V7 do not show clear CO₂ peaks, either because they are too weak or because they are superimposed by the emissions of a preceding vehicle.

In the current implementation of the TUG-PDA, the BG determination for overlapping plumes is done by calculating an average value between the median concentration directly between the overlapping plumes and a common BG when no vehicle is passing. This is a simple estimation and entails deviations from the actual situation. This can be seen, for example, in Fig. 5 (left) for vehicle V4. The BC background is overestimated. This results in a too small integrated area (BC4) and thus underestimated emissions. This can also be seen to a smaller extent for vehicle V3, where both CO₂ (CO₂3) and BC (BC3) backgrounds are underestimated, leading to an overestimation of both areas.

It is important to know how accurate the determined EFs are due to the assumptions made in the calculations for overlapping plumes and the complexity of resolving superimposed emissions. We therefore assessed the impact of interference from other vehicles/sources on the resulting EFs. The TUG-PDA distinguishes between the following three cases of interference:

- Overlap: The plume from the current vehicle overlaps with the plume of a previous vehicle. The two plumes must be separated.




Figure 5. Two PS time series examples (BC, CO₂) from captured plumes. The yellow, vertical, dashed lines mark the point at which the vehicles passed the PS spot. **Left:** Emissions can be separated for three (V1, V3, V4) of the four vehicles. The assigned emissions are highlighted in different colors (BC1-BC4 and CO₂1-4). **Right:** For most vehicle passes, the emissions for individual vehicle passes are not separable. Ten vehicle passes are shown, of which emissions are determined for two (BC1,2 and CO₂1,2).

- 335
- Cut-off: The plume from the current vehicle interferes with the next vehicle. The emission integration stops for the current vehicle and the entire plume has not been captured.
 - Overlap + cut-off: The above two cases are applicable. The plume from the current vehicle is influenced by the plume from the previous vehicle and the exhaust plume from the next vehicle.

These cases are marked in the algorithm and can be used for further analysis. This marking is done individually for the different emission signals (e.g. CO₂, BC, NO_x), as they are processed separately.

340

As an example, we investigated the influence of interfering plumes on the determined BC emissions of petrol-powered passenger cars. Only overlapping CO₂ signals are taken into account and no superposition of BC emissions. The inclusion of BC interferences distorts the results, as these consist mainly of high emitters (see Appendix Fig. C1). The emission distributions shown (Fig. 6) are separated into a combined data set (with and without interference), measured interference-free emissions, and the three cases in which the TUG-PDA categorizes interference. We did not find a strong influence of plume interference on the results. The determined EFs are statistically comparable between the different datasets with and without interference from other vehicles. The largest deviation was found for plumes that were cut-off. The median EFs were 19 % lower than in cases without interference. The sample size shows that the majority of the emissions determined were influenced by an interference. If only plumes without interference were considered, the number of measurements would be greatly reduced. We also looked at how accurate the EF can be calculated using only a fraction of the plume. Therefore, we selected only plumes without interference from other vehicles and calculated EFs using the TUG-PDA when the algorithm used only a fraction of the plume in the interval between 3 s and 23 s. Similarly to the investigation shown in Fig. 6, we found that when only a fraction of the plume is used that the EFs are underestimated. The median underestimation for an early cut-off at 3 s is 27 %. The deviation decreases with increasing fraction of the plume (see Appendix Fig. C2).

345

350




Figure 6. Influence of interference from other vehicles/sources on the BC emission distributions determined with the TUG-PDA. Measured EFs of petrol-powered passenger cars are used for comparison. Interference data includes both overlapping plumes and plume cut-offs (interference = overlap and/or cut-off). The whiskers represent the 2.5 and the 97.5 percentiles.

355 3.2 Factors influencing point sampling measurements

In the following part, the most important factors influencing PS measurements are discussed and the resulting impacts are shown on basis of around 100,000 vehicle emission records gathered during 4 measurement campaigns. The measurement campaigns were conducted in the Netherlands, Italy, Poland and Czechia. The results include data from 9 monitoring sites, with data from the specially developed Black Carbon Tracker (BCT) being used to assess the various factors. The BCT measures
 360 BC with a photoacoustic based sensor cell and CO₂ with a non-dispersive infrared (NDIR) sensor integrated into one device. The device was developed based on the recommendations listed in Table 1 as part of the CARES project (Knoll et al., 2021). The impact of misaligned measurement data on the resulting ERs is discussed in the supplementary material.

3.2.1 Instrument characteristics

For our study we selected two instruments, our custom-designed BCT and the Aethalometer AE33 (Magee Scientific), for
 365 their applicability in determining BC emissions using the developed TUG-PDA. The Aethalometer AE33 is widely used in environmental science for BC measurements and source appointment and is commonly used in PS studies to quantify BC emissions (Ježek et al., 2015; Preble et al., 2018; Zhou et al., 2020; Sugrue et al., 2020). We characterized the BCT and the AE33 in the laboratory for properties relevant for PS (see Table 1). A miniCAST soot generator (Jing Ltd, Model 6204 Type B) was used as the particle source. The instruments measured in parallel downstream of a catalytic stripper which removed volatile
 370 compounds (Knoll et al., 2021). The measurements showed a very good correlation ($R^2 = 0.99$) between the Aethalometer and the BCT. Comparable limit of detection (1 s, 3 σ) were determined for both instruments, with values of 1.01 $\mu\text{g m}^{-3}$ for the Aethalometer and 1.12 $\mu\text{g m}^{-3}$ for the BCT. The limit of detection of the instruments defines the extent to which emissions can be resolved. This is particularly important for accurately quantifying emissions from vehicles that meet the latest emission

standards. The t_{90} response times of the two instruments were measured in the laboratory: 0.9 s for the BCT and 7 s for the
375 Aethalometer. A small response time enables the separation of highly transient emission events. This determines how close
vehicles can drive to each other in order to be able to resolve the emissions. Fig. 7 shows two emission time series of the
two instruments during one of the measurement campaigns. Two vehicles pass by the PS spot during the shown time frame
with an interval of six seconds. The BCT responds quickly to the captured BC emissions from the first passing vehicle (V1).
A distinct peak is noted where the measured concentration is again below 10 % of the peak concentration of the first vehicle
380 when the second vehicle (V2) passed by. The emissions captured for the two vehicles overlap, but they can be separated
using the BCT. In contrast, the AE33 response time is much slower and the maximum concentration is reached after the
second vehicle (V2) has passed by. In this case it is not possible to separate the BC emissions of the two vehicles using the
AE33. This example illustrates the importance of choosing instruments with a fast response time when measuring in dense
traffic. Individual characteristics (see Table 1), such as the response time, that do not meet the requirements severely limit
385 the application. However, the Aethalometer can also be used for PS, as has already been demonstrated in several studies. The
traffic density must be low enough (distance between vehicles greater than 7-10 s) or only certain types of vehicles (e.g. HDVs
with vertical exhaust pipes) are measured, which naturally entail a greater distance between exhaust plumes.




Figure 7. Emission concentration time series example of two instruments with different response times. Gray (Black Carbon Tracker) and brown (Magee Aethalometer AE33) shaded areas show the integrated areas of the BC emissions from the first passing vehicle as determined with the TUG-PDA.

3.2.2 Measurement location and sampling position

Special care must be taken when selecting suitable measurement locations. Besides the legal regulations (e.g. for the placement
390 of equipment), the following aspects influence the selection:

- Road properties (single or multi-lane, lane width, road gradient)

- Traffic conditions (traffic flow, distance between passing vehicles, number and type of vehicles) and vehicle operating conditions (VSP, see Appendix A3)
 - Influence of environmental and background conditions (see supplementary material)
- 395 – Cross-interference from other pollution sources

In the following evaluations (e.g., Fig. 8, 9), we assess the influences of the above mentioned aspects on PS measurements. The results from the different measurement locations are labeled with numbers. Different sampling positions or traffic situations were evaluated on individual locations. These are labeled with x.x (e.g., 1.1). This should facilitate the interpretation of the results and the comparison between the different impact factors, as they were not determined independently.

400 One selection criteria of PS campaigns is often the number of vehicles per site and day. Conducting campaigns on highly frequented roads guarantees a high number of vehicle passes. This is to a certain extent beneficial, as it allows for the collection of a large number of emission records. If the traffic density is too high for PS, the emissions from the individual passing vehicles cannot be properly resolved because they superimpose (e.g. Fig. 5, right). Not only the traffic density, but also the general traffic flow must be considered. Measurements are often performed after a crossroad or traffic light. Such conditions can lead to a high
405 number of vehicles passing within a short period of time and a short distance from each other. This prevents emissions from being properly resolved. Therefore, we evaluated the CR as a function of the median vehicle distance at different measurement locations. The CR generally increases with median vehicle distances at the measurement locations (Fig. 8, left). It is noticeable that even in relatively dense traffic (median vehicle distances 3.3 - 6.2 s), a high CR (31 - 38 %) can be achieved if the sampling is done from the middle of the road.

410 In order to select the measurement site, the road itself and the topography must be evaluated. We examined the influence of the VSP on the CR for the three sampling positions (left, middle, right). For this investigation, only speed, acceleration and the road gradient were used to calculate the VSP (see Appendix A3). The determined VSP values for the different measurement locations are clustered and averaged. We observed only a small impact of the VSP on the CR (Fig. 8, right). The CR increases slightly with increasing VSP regardless of the sampling position. A certain engine load (e.g., $VSP > -5 \text{ kW } \tau^{-1}$ according
415 to Bernard et al. (2018)) is required for the measured vehicles, which can be accomplished in locations with a positive road gradient or at locations where vehicles accelerate (e.g. road crossings, slip roads). Roads with declining gradients should generally not be chosen due to lack of engine load. The road type must be considered in terms of space for the measurement setup and cross interference from other vehicles. In general, single-lane roads are preferred, as well as two-lane roads where the measured direction has a positive gradient. Vehicles driving on the opposite lane have a negative VSP and therefore only a
420 small influence on the measurements.

The approach used to collect the exhaust has a major impact on the quality and strength of the signal. We found a direct relation between the CO₂ signal strength (see supplementary material) and the CR (Fig. 9, left). A higher CO₂ signal generally leads to a higher CR. The highest CR can be achieved if the sample extraction is performed from the middle of the road. By using this central setup, a CO₂ plume could be captured for an average of 34 % of the vehicles. Sampling from the left roadside
425 delivers on average a CR of 25 % as compared to 17 % if the sample is extracted from the right side. In most regions in Europe,




Figure 8. Evaluation of two traffic related impact factors and their influence on the capture rate. **Left:** The capture rate is shown as a function of the median vehicle distance at different measurement locations (indicated by numbers as in Fig. 9). **Right:** The calculated VSPs are clustered and shown separately for the different sampling positions.

sampling from the left is favored over the right side. Vehicles from manufacturers in Europe (e.g., VW, BMW, Mercedes, Fiat) have usually the tailpipe on the left-hand side, unlike manufacturers in Asia or the United States (e.g., Toyota, Kia). At two measurement locations (3 and 7), the sampling was conducted from both, the roadside and from the center of the road. Two to three times higher CRs were obtained when sampling from the middle of the road (Fig. 9, middle and Fig. 8, left).

430 Measurements from the center of the road allows sample extraction in the closest proximity of the source and is therefore less influenced by traffic (Fig. 8, left), wind or tailpipe position. We found no significant influence on the driving behavior when the sampling was done from the center of the road through the covered tube. In addition to the influence of the sampling side, the sampling height also has a major impact on the sample extraction. Higher CRs and stronger CO₂ signals are achieved at lower sampling inlet heights for most vehicles in Europe. An exception are L-type vehicles (e.g. motorcycles) with tailpipes

435 pointing straight or even upwards. The width of the road has a non-negligible impact on measurements from the roadside (Fig. 9, right). At two locations (1, 2), the sampling was conducted at two positions (1.1, 1.2 and 2.1, 2.2) at the same roadside with differences in road width and sampling height. For both, it can be seen that a smaller road width and a lower sampling height lead to a higher CR. Measurement locations where the sampling was done from the right side (2, 3, 5, 7) generally have a rather low CR. An exception is location 5, where the highest CR of all measurement sites was achieved. Location 5 stands

440 out with good characteristics of all influencing factors such as a small lane width (3.5 m), a low sampling height (5 cm) and a high median vehicle distance of 10.6 s (~ 2.500 vehicle per day). The highest absolute number of valid measurements per hour was achieved at location 8 with 103 valid ERs per hour.




Figure 9. Three plots show the influence of the sampling position and road width on the capture rate. **Left:** Mean capture rate at the three sampling positions, combined from all measurement sites. **Middle:** Capture rate as a function of the height of the sampling inlet. The measurements were performed at different measurement locations, which are indicated by the numbers. **Right:** Capture rate as a function of the lane width for roadside measurements.

3.2.3 Weather conditions

Harsh weather conditions can have a substantial impact on RES measurements. For both PS and RES, the literature lacks
 445 detailed assessments that examine the effects of environmental conditions. Of particular interest are the dependencies related
 to precipitation and wind conditions. During the measurement campaigns, a weather station was either located directly next to
 the PS site or in the vicinity. The weather data used were available on at least hourly basis. To allow an unbiased comparison,
 only datasets were used where the compared meteorological conditions were present during the measurement campaigns.

Rain: We found that the PS measurements were not significantly influenced by rain. CRs are comparable during rainy
 450 (29.3 %) and dry (29.8 %) conditions (Fig. 10, left). Similar values were also determined for the average CO₂ plume of the
 passing vehicles. During dry periods, an average CO₂ plume of 525 ppm s was measured as compared to 536 ppm s under wet
 conditions. We were particularly interested in discovering whether these conditions impacted PM emissions. For this purpose,
 we performed a Monte Carlo simulation by drawing 100 samples of the measured ERs of the passing vehicles from the different
 measurement sites 1,000 times. We calculated the mean ERs from the 100 samples and the distribution of the mean values is
 455 shown in Fig. 10 in the right plot. Statistically, no significant difference was observed between the ERs calculated in dry and
 rainy conditions with median values of 110 and 134 mg (kg CO₂)⁻¹, respectively. The slight differences may result, for example,
 from different driving behavior in wet conditions.

Wind: Wind direction and wind speed affect the dilution and transport of the plume. We assessed the effect of wind speed
 and wind direction on the measurements. The wind speed was segmented according to the Beaufort scale (Singleton, 2008).
 460 We found that with increasing wind speed the CR steadily decreases (Fig. 11, left). A similar trend can be observed for the
 measured average CO₂ plume of the passing vehicles. A higher CO₂ signal (519 ppm s) was measured under calm conditions
 (< 20 km h⁻¹) than under windier (21-39 km h⁻¹) conditions (425 ppm s). A similar influence of wind speed on the CR was
 reported by Dallmann et al. (2011) in their top-down PS study for HDVs. They reported lower CRs in June (61 % unsuccessful
 plume captures) than in November (36 % unsuccessful plume captures), where average wind speeds were twice as high. In




Figure 10. Effect of precipitation on PS measurements. Measurements are compared for rainy ($> 0.05 \text{ mm h}^{-1}$) and dry weather conditions. Capture rates (**left**) and mean BC ratios (**right**) measured in both conditions are compared.

465 contrast to our results, they found that the dilution of the captured plumes was similar for both wind conditions. Not only the wind speed is relevant, but also the direction in which the wind blows the exhaust plume. We evaluated the impact of the wind direction on the PS measurements under calm ($< 11 \text{ km h}^{-1}$) and breezier ($> 11 \text{ km h}^{-1}$) conditions. For this purpose, we separated the wind directions into wind blowing the exhaust plume towards the measurement location and wind blowing it away from the sampling point. The wind directions are indicated in the supplementary material. A significant
 470 influence was observed at a rural measurement location (Fig. 11, right). The CR is higher under calm conditions and when winds are blowing towards the sampling position. We performed the same evaluation in urban environments. Here, we could not observe such a trend with similar CRs regardless of the wind direction (see supplementary material). We assume that this is mainly related to differences between the local wind conditions (local turbulences) directly at the PS spot and the wind measured at the weather station. Generally, wind conditions in street canyons are much calmer than those in open spaces,
 475 which is beneficial for PS applications.




Figure 11. Influence of different wind conditions on the capture rate. **Left:** Wind speed at urban measurement locations. **Right:** Wind speed and direction at a rural measurement site.

Temperature: The influence of temperature is investigated in Fig. 12 for low (≤ 10 °C) and high temperatures (> 10 °C). Ambient temperatures ranged from -7.3 °C to 28.2 °C during the different measurement campaigns. No significant difference was observed with an average CR of 28 % at low temperatures and of 29 % at high temperatures. The effects of ambient temperature and humidity are not expected to have an impact on the PS measurement itself, if the instrumentation used are either properly stored or can perform measurements under such conditions. Ambient temperature is expected to have an impact mainly on the passing vehicles and their exhaust after-treatment systems (Kwon et al., 2017; Ko et al., 2019).




Figure 12. Influence of ambient temperature on the capture rate.

3.3 Measurement campaign

In total, for the city measurement campaigns in Italy, Poland and Czechia, it was possible to collect technical data from authorities for 66,803 of the recorded vehicles. The technical data sets collected were pseudo-anonymised to comply with the data protection regulations of the individual countries. Based on the collected technical data sets, we determined with our data analysis framework (see Sect. 2.2) the emissions of 22,160 vehicles. Measurements were conducted with our described setup (see Sect. 2.1). Several instruments were used in the campaigns to measure BC, PN and NO_x EFs. The newly developed BCT was used to measure BC and CO_2 , a custom designed diffusion charger (Schriebl et al., 2020) measured PN concentrations and an ICAD (Airyx GmbH, Horbanski et al. (2019)) was deployed for NO_x and CO_2 measurements. A schematic of the emission measurement setup can be found in the supplementary material.

3.3.1 Fleet composition and capture rate

The measurements were carried out in city centers, which is also reflected in the vehicle fleet. The vehicle types were classified according to the vehicle categories of the United Nations Economic Commission for Europe (UNECE). The largest share of vehicles measured were passenger cars (84.1 %). A much smaller share of L-type vehicles (1.4 %) and HDV and buses (0.8 %) were recorded (Fig. 13, left upper plot). We determined the CRs for the different vehicle categories to verify the ability to measure different vehicle types (Fig. 13, left lower plots). The highest CR could be achieved for HDVs and buses (55 %), followed by passenger cars (22 %) and L-type vehicles (17 %). Previous PS studies (Dallmann et al., 2011, 2012) reported

CRs for HDVs using top-down measurements from a bridge and a tunnel. In these studies CRs ranged from 12 % to 59 % for individual trucks and from 16 % to 44 % for groups of trucks. In general, it can be said that the CR depends on the exhaust flow rate of the vehicles. HDVs and buses have much greater exhaust flow rates than passenger cars or L-type vehicles. This is also reflected when looking at the average integrated exhaust plume of the different vehicle categories. The average integrated exhaust plume of HDVs and buses (947 ppm s CO₂) was significantly higher than those of passenger cars (459 ppm s CO₂) and L-type vehicles (374 ppm s CO₂). A lower percentage of L-type vehicles is measured not only because of the smaller exhaust flow rate, but also because of the direction of the exhaust pipe. In contrast to HDVs, buses and passenger cars, the exhaust pipe for L-type vehicles often points upwards, which is disadvantageous when sampling from low heights. Looking at the distribution of the fuel type of the measured vehicles, a similar number of diesel (45.2 %) and petrol (46.5 %) vehicles were measured. A small share of CNG, LPG or bi-fuel (petrol/diesel + CNG/LPG, 2.6 %) was captured (Fig.13, right upper plot). In contrast to the vehicle type, the CR is rather independent of the fuel type (Fig. 13, right lower plot). EFs could be determined for 24 % of diesel vehicles, which is slightly higher CR compared to 22 % of petrol vehicles. This is mainly due to the fact that vehicles with a larger engine displacement (e.g. trucks or buses) are mostly powered by diesel engines, while smaller vehicles are mostly equipped with petrol engines (e.g. L-type vehicles).




Figure 13. Measured vehicle fleet split into vehicle categories (**left**) and fuel type (**right**). Capture rates for the different types are shown in the lower plots. The data contains multiple passes of the same vehicles.

3.3.2 Fleet emission characteristics

Fuel-based EFs (see Appendix A1) were determined for the measured vehicles using the collected technical vehicle data. The fuel-based EF accounts for the larger total emissions from large vehicles such as HDVs and buses and makes all derived EFs comparable. Statistical evaluations were carried out for various vehicle categories and Euro emission standards (Fig. 14 to Fig. 16). Upper and lower whiskers represent the 97.5 and 2.5 percentile, respectively. The number of vehicles in each category

is indicated by the numbers in the brackets. Emissions from hybrid electric vehicles are included in the statistics. There are mainly two reasons for negative EFs. First, negative EFs result from low emitting vehicles where the determined background is higher than the measured emissions during the captured CO₂ plume. Second, the emissions of other vehicles interfere with the measurement of the current vehicle.

BC emissions from petrol-powered passenger cars (M1 category) decrease from Euro 2 to Euro 6 emission standards. The mean values decreased from 256 to 103 mg (kg fuel)⁻¹ and median values decreased from 57 to 37 mg (kg fuel)⁻¹. For passenger cars with diesel engine, BC emissions decrease significantly with increasing Euro emission standards and decreasing vehicle age from 2.37 g (kg fuel)⁻¹ (median: 1.08 g (kg fuel)⁻¹) for Euro 2 down to 81 mg (kg fuel)⁻¹ (median: 30 mg (kg fuel)⁻¹) for Euro 6. This corresponds to a reduction by a factor of more than 30 from Euro 2 to Euro 6 on the median. The impact of the introduction of DPFs sticks out from Euro 5 onwards. BC emissions from Euro 6 diesel vehicles are below of those from Euro 6 petrol vehicles. Similar trends can be observed for BC emissions of HDVs and buses. The BC EFs of both HDVs and buses drop significantly from Euro III to Euro V. Measured buses were mainly well maintained city operated Euro V and VI vehicles, with BC emissions even lower than those of Euro 6 passenger cars.




Figure 14. Distribution of fuel-based BC EFs in dependence of the Euro emission standard for different vehicle categories. Passenger cars are split into petrol and diesel-powered vehicles. The numbers in brackets represent the sample size.

PN measurements were performed for particles larger than 23 nm (D₅₀ cut-off at 23 nm) using a catalytic stripper to remove volatile compounds (Giechaskiel et al., 2014). PN and BC results agree well for the different vehicle categories and Euro emission standards, as only the solid particle fraction was measured (Fig. 15). The impact of the introduction of DPF for diesel passenger cars is even more pronounced for PN than for BC. Median PN EFs decrease from Euro 2 to Euro 6 from 1,842 to 22 · 10¹² particles per kg fuel by a factor of more than 80. The greater reduction of PN compared to BC EFs can

535 be related to DPF filtration efficiency, which depends on the particle size distribution (Yang et al., 2009; Rossomando et al., 2021). Vehicle exhaust PN consists mainly of a large number of small particles below 60 nm, while the main contributor to BC mass concentration are accumulation mode particles (Giechaskiel et al., 2014). However, a shift towards smaller particles sizes caused by newer engine technologies must be taken into account.




Figure 15. Distribution of fuel-based PN EFs in dependence of the Euro emission standard for different vehicle categories. PN measurements were performed for solid particles greater than 23 nm. Passenger cars are split into petrol and diesel-powered vehicles. The numbers in brackets represent the sample size.

NO_x emission levels of petrol-powered passenger cars are steadily decreasing from Euro 2 to Euro 6 (Fig. 16). Median values decrease from 5.74 g (kg fuel)⁻¹ to 0.87 g (kg fuel)⁻¹. The effects of “Dieselgate“ are reflected in the NO_x emissions of diesel passenger cars, which primarily affect Euro 5 and Euro 6 vehicles. NO_x EFs stagnate for Euro 2 to 5 vehicles, with median values ranging from 9.78 to 13.31 g (kg fuel)⁻¹. For Euro 6 vehicles, NO_x EFs decrease significantly with a median value of 2.85 g (kg fuel)⁻¹. In contrast to BC and PN, NO_x EFs for HDVs and buses are higher compared to emissions of passenger cars. This applies to all Euro classes. HDVs tend to have a higher mileage, which affects the deterioration of the vehicle’s condition. In addition, intentional tampering of the NO_x reduction system is believed to be more common in commercial vehicles than in private vehicles.

Table 3 compares average emissions of selected Euro emission standards from this study with previous open-path RES and PS studies. The average BC EFs from this study are compared with the PM EFs from other studies. BC can be assumed to be a subset of PM. For diesel vehicles, BC typically accounts for the largest share of PM emissions. This is especially the case for older Euro emission standards and vehicles with defective DPF. The proportion of BC emissions for petrol vehicles is typically




Figure 16. Distribution of fuel-based NO_x EFs in dependence of the Euro emission standard for different vehicle categories. Passenger cars are split into petrol and diesel-powered vehicles. The numbers in brackets represent the sample size.

lower, except under specific conditions (Platt et al., 2017; Yang et al., 2019; Bessagnet et al., 2022). PN EFs are reported only for PS studies, because only rough estimates from open-path RES studies can be made for PN.

Average BC EFs from this study and PM EFs from open-path studies are in a similar range for petrol and diesel passenger cars. The average PM EFs reported from open-path RES studies are subject to a large variation. The measured emissions can vary widely depending on several factors such as fleet characteristics (e.g. vehicle type, manufacturer, mileage, age) or the measurement location. Determined average BC EFs from this study for Euro 5 and 6 passenger cars are higher than those found in open-path RES studies. One reason for this can be the quantification limit of open-path RES instruments for PM measurements. Several studies pointed out difficulties in quantifying emissions of newer Euro emission standards, which was reflected in negative average EFs (Gruening et al., 2019; Cha and Sjödin, 2022; Jerksjö et al., 2022). The average NO_x EFs from the selected open-path RES studies vary to a much smaller extent. Determined NO_x EFs for passenger cars of this study agree well with literature values for almost all Euro emission standards given.

The calculated EFs of HDVs and buses from this study are compared with selected literature from both PS studies and open-path RES studies. The selected PS studies were conducted solely in Sweden. BC EFs of this study and PM EFs of literature studies are in similar ranges for Euro III to Euro V standards. Differences are mainly observed for Euro VI HDVs. These can arise from differences in fleet characteristics or vehicle age, causing deterioration of the exhaust after-treatment system. This could be particularly the case for newer Euro VI HDVs, where 2-3 years between the studies can have a significant impact. Negative PM EFs reported by open-path RES studies can be referred to limits in instrument accuracy similar to those for passenger cars. PN EFs for HDVs and buses reported in previous PS studies are generally higher than those reported

in this study. This can be attributed to the different size characteristics of the used PN instruments. Particles larger than 5.6
570 nm were measured by Hallquist et al. (2013), Liu et al. (2019) and Zhou et al. (2020). In this study, the D₅₀ cut-off was 23
nm (Schriebl et al., 2020). We performed solid particle number (SPN) measurements with a cut-off at 23 nm to comply with
current emission regulations and to be able to relate the calculated EFs to official limits. Determined NO_x EFs of HDV and
buses are in good agreement with literature data of PS and open-path RES studies. Similar to diesel passenger cars, NO_x
EFs of this study for HDV and buses are slightly lower compared to literature data of open-path RES studies. NO_x EFs of
575 literature PS studies span over a wide range, which can be referred to differences in vehicle exhaust after-treatment systems. In
Hallquist et al. (2013), open-path RES data was used to determine NO_x EFs. Which EFs are more accurate cannot be judged
from the comparison as several reasons influence the derived EFs like measurement location, vehicle fleet, driving properties,
environmental conditions, instrument characteristics or data analysis methods. A detailed comparison of our PS system with
other simultaneous measurements will be part of a separate study.

580 **4 Summary and conclusions**

This paper presents a PS system capable of screening vehicle fleets largely independent of the vehicle type. Our approach
allows the direct measurement of different particle metrics such as BC or PN as well as different gaseous compounds (e.g.
NO_x). In particular, PN is a relevant metric today with knowledge of the health effects of ultrafine particles (Oberdörster et al.,
2005; Brook et al., 2010; Mannucci et al., 2015), but also concerning currently introduced emission legislations (Bainschab
585 et al., 2020; Giechaskiel et al., 2021). Newly introduced Euro emission standards bring along stringent requirements, where
current open-path RES systems reach their quantification limits, especially for PM (Grüening et al., 2019; Cha and Sjödin,
2022; Jerksjö et al., 2022). Compared to commercial open-path RES systems, the installation of the PS measurement setup is
relatively simple. The method is quite flexible when it comes to where the sample extraction is performed and what instruments
are used to measure the species of interest. We presented a comprehensive data analysis framework that is capable of processing
590 emissions from thousands of vehicles. The core is the TUG-PDA, which determines and separates vehicle emissions down to
a distance of 3 s between the vehicles, if appropriate instruments are used. We have shown that emissions from overlapping
plumes can be measured with similar accuracy as when there is no overlap. As an application example, we presented the first
results of measurement campaigns in three different European cities in which we made use of our PS method. We showed
distributions of measured BC, PN and NO_x EFs of different vehicle types and Euro emission standards. The results are in good
595 agreement with relevant literature studies and show the potential for screening emissions of different vehicle types, including
those meeting newly introduced emission standards.

We evaluated important impact factors influencing PS measurements that should be considered when planning and imple-
menting PS campaigns. The most important influences are summarized in the following:

- Instruments used for PS campaigns should be properly chosen (see Table 1). Response time, dynamic range and limit of
600 detection are the most significant factors. The response time should be as low as possible (< 1-2 s). The dynamic range

Study	Vehicle type - fuel type	Euro standard	Av. EF BC/PM mg (kg fuel) ⁻¹	Av. EF PN 10 ¹² # (kg fuel) ⁻¹	Av. EF NO _x g (kg fuel) ⁻¹
This study	Passenger cars - petrol	Euro 3	188 ^a	243 ^c	7.0
Open-path RES studies ^{1,2,3,4}			30 - 670 ^b	-	5.1 - 14.5
This study		Euro 4	153 ^a	174 ^c	5.7
Open-path RES studies ^{1,2,3,4}			20 - 200 ^b	-	3.8 - 7.2
This study		Euro 5	166 ^a	210 ^c	3.9
Open-path RES studies ^{1,2,3,4}			30 - 90 ^b	-	2.5 - 3.3
This study		Euro 6	103 ^a	132 ^c	2.3
Open-path RES studies ^{1,2,3,4}			0 - 95 ^b	-	-0.5 - 3.2
This study	Passenger cars - diesel	Euro 3	1787 ^a	2223 ^c	14.3
Open-path RES studies ^{1,2,3,4}			170 - 1840 ^b	-	13.7 - 18.7
This study		Euro 4	918 ^a	1377 ^c	13.5
Open-path RES studies ^{1,2,3,4}			130 - 1080 ^b	-	11.6 - 15.4
This study		Euro 5	261 ^a	351 ^c	12.6
Open-path RES studies ^{1,2,3,4}			20 - 270 ^b	-	11.7 - 14.4
This study		Euro 6	81 ^a	117 ^c	5.5
Open-path RES studies ^{1,2,3,4}			10 - 70 ^b	-	5.8 - 8.5
This study	Buses, heavy duty - diesel	Euro III	1579, 2620 ^a	2465, 2039 ^c	20.6, 22.7
PS studies ^{6,7,8}			30 - 1820 ^b	730 - 3900 ^d	16 - 43.3 ^e
Open-path RES studies ^{1,4}			250 - 2100 ^b	-	24.6 - 27.5
This study		Euro IV	443, 384 ^a	651, 458 ^c	13.7, 25.6
PS studies ^{6,8}			172 - 1845 ^b	870 - 3200 ^d	14 - 19.8 ^e
Open-path RES studies ^{1,4,5}			220 - 1250 ^b	-	17.8 - 21.5
This study		Euro V	63, 287 ^a	77, 520 ^c	5.5, 15.4
PS studies ^{6,7,8}			146 - 258 ^b	650 - 1600 ^d	15 - 37 ^e
Open-path RES studies ^{1,2,4,5}			40 - 360 ^b	-	13.1 - 25.3
This study		Euro VI	35, 43 ^a	38, 87 ^c	3.7, 6.4
PS studies ⁸			5 ^b	850 ^d	3.1
Open-path RES studies ^{1,2,4,5}			-50 - 190 ^b	-	2.8 - 8.7

Table 3. Comparison of average fuel-based BC/PM, PN and NO_x EFs of this study with selected open-path RES and PS literature data. Emissions are ordered by vehicle category, fuel type and Euro emission standard. BC/PM column show either BC or PM EFs. ¹Hooftman et al. (2019), ²Bernard et al. (2021), ³Jerksjö et al. (2022), ⁴Cha and Sjödin (2022), ⁵Lee et al. (2022), ⁶Hallquist et al. (2013), ⁷Liu et al. (2019), ⁸Zhou et al. (2020), ^aBC, ^bPM, ^cPN > 23 nm, ^dPN > 5.6 nm, ^eNO EFs of Hallquist et al. (2013) were determined by open-path RES, NO₂ measurements are estimated.

should be large enough to cover both low and high emitters. The limit of detection should be low enough to accurately determine the emissions from the evaluated species.

- 605 – When selecting the measurement site, the traffic conditions must be taken into account. An ideal condition is a steady traffic flow with sufficient distance (≥ 3 s with appropriate instrumentation) between the vehicles to collect a high number of valid emission records. At the measurement site, the passing vehicles should be under considerable engine load. This can either be in appropriate traffic situations where vehicles accelerate (e.g., after crossing, slip road) or at roads with positive gradients.
- 610 – The sampling should be performed as close to the exhaust source (tailpipe) as possible. The best results can be achieved if the sample extraction is performed from the middle of the road with the sampling tube directly attached to the road. When sampling from the side, the road width (smaller roads preferred) and the sampling height (as low as possible) have a significant influence on the CR. In addition, the position of the exhaust pipe of the fleet of interest should be examined in advance to determine the best sampling position.
- 615 – The CR depends on the wind speed and direction. Windy conditions that transport the exhaust plume away from the sampling point have a negative effect on the CR. The influence of wind can be minimized by choosing an appropriate measurement location (e.g., street canyon). Other weather factors such as temperature or precipitation have negligible impact.

Future work will involve a detailed analysis of the gathered BC, PN, and NO_x emissions. Several open questions will be addressed such as how PS measurements relate to those made by reference equipment such as PEMS or other RES methods (Knoll et al., Under review). Further development of the TUG-PDA could address improvements in the determination of BG for overlapping plumes (e.g. using a linear approximation between the start and end of the peak) or the use of adaptive thresholds and parameters depending on the measurement location. Another interesting aspect to investigate is the reproducibility and reliability of individual measurements. This is particularly important for the potential identification of high emitters. Commercial open-path RES systems are associated with a high degree of uncertainty when considering individual measurements (Huang et al., 2020; Qiu and Borken-Kleefeld, 2022). PS results indicate that single measurements are more reliable due to the longer measurement duration. It would be a great step forward if this could be proven and applied in the future to identify individual high emitters.

Appendix A: Remote emission sensing definitions

A1 Emission ratio and fuel-based emission factor

Emissions of combustion-based vehicles are generally reported as EFs. In RES, fuel-based EFs are used to express emissions from the measured vehicles (Hansen and Rosen, 1990; Borcken-Kleefeld and Dallmann, 2018; Bernard et al., 2018). Fuel-based emissions are expressed as a mass fraction of the emitted pollutant per mass of burned fuel. The amount of burned fuel is calculated based on the measured CO₂ concentration of the passing vehicle by using the carbon mass balance method (Bishop et al., 1989; Hansen and Rosen, 1990; Stedman et al., 1992; Singer and Harley, 1996; Ban-Weiss et al., 2009; Hak et al., 2009) and under the assumption that the majority (> 90 %) of the carbon content in the fuel is oxidized to CO₂ during the combustion process. By relating the measured pollutant P (e.g., BC, PN, NO_x) to the measured CO₂ concentration, an ER can first be calculated (Stedman et al., 1992; Hansen and Rosen, 1990). In our approach (see Eq. A1), we use different start (t_1 , t_3) and stop times (t_2 , t_4) for the pollutant and CO₂ integration. Similarly, the BG values are determined independently ($[P]_{t_{p0}}$, $[CO_2]_{t_{CO20}}$).

$$ER = \frac{\int_{t_1}^{t_2} ([P]_t - [P]_{t_{p0}}) dt}{\int_{t_3}^{t_4} ([CO_2]_t - [CO_2]_{t_{CO20}}) dt} \quad (A1)$$

By multiplying the ER with the mass fraction of carbon in fuel ω_c a fuel-based emission factor EF_{fb} (Ban-Weiss et al., 2009; Hak et al., 2009) can be calculated:

$$EF_{fb} = ER \cdot \omega_c, \quad (A2)$$

where ω_c discriminates among different fuel types (see Table A1). Regarding PS measurements, the emission events last for several seconds. The measured concentrations of the pollutant and CO₂ for one vehicle pass are commonly integrated and the results are related to each other. The start and stop times of the emission event define the integration intervals and these are represented by t_1 and t_2 , respectively. The measured emissions are superimposed by BG concentrations of the different species in ambient air. For that reason, a BG correction is required, where t_0 specifies the point of time from which the BG concentration is used. The BG is usually determined on the basis of the concentration at the integration starting point, t_1 . When plumes overlap or impacts from other sources occur, this concentration may be underestimated.

A2 Distance-based emission factor

Fuel-based EFs do not distinguish between vehicles with different fuel consumption. Therefore, fuel-based EFs favor vehicles with higher fuel consumption. Distance-based EFs, on the contrary, include the fuel consumption and are, therefore, usually used to compare vehicle emissions (Bernard et al., 2018). However, distance-based EFs cannot be directly calculated in RES due to the snapshot measurement. An estimate can be calculated using the type approval CO₂ consumption (Avg_{CO_2}) which is

Fuel type	ω_c
Gasoline (2016 E0)	0.864
Diesel (B0)	0.861
CNG	0.708-0.717
LPG	0.824
LNG	0.749-0.756

Table A1. Typical mass fraction of carbon in common fuel types from JRC (2020).

655 obtained from the vehicle technical information. The official CO₂ emissions from passenger cars have been shown to differ increasingly from real-world emissions (Tietge et al., 2017). Therefore, a correction factor (RWG_{CO_2}) including the real-world CO₂ gap can be included according to Bernard et al. (2018). Making this assumption, a distance-based EF can be calculated as follows:

$$EF_{db} = ER \cdot Avg_{CO_2} \cdot RWG_{CO_2} \quad (A3)$$

660 In a recent publication by Davison et al. (2020), a new approach was presented to calculate the distance-based EF in RES studies using the VSP. A good agreement was found between the outcome of their approach and validation measurements made with portable emission measurement systems (PEMS).

A3 Vehicle specific power

VSP is often used when performing emission modeling of combustion-based vehicles to estimate vehicle operating conditions. 665 Using VSP, insights can be gained to estimate the engine load when a vehicle passes the measurement point. For example, this can be used to exclude vehicles with a small VSP ($< -5 \text{ kW t}^{-1}$) due to the disabled fuel injection in the engine (and therefore unexpected CO₂ emissions) (Bernard et al., 2018). The VSP is defined according to Jimenez-Palacios (1999) by the sum of the relevant power variables related to the mass of the vehicle:

$$VSP = \frac{\frac{d}{dt}(E_{Kin} + E_{Pot}) + F_{Rol} \cdot v + F_{Aero} \cdot v}{m} = v \cdot (a \cdot (1 + \epsilon) + g \cdot grade + g \cdot C_R + \frac{1}{2} \cdot \rho_a \cdot C_D \frac{A}{m} \cdot (v + v_w)^2) \quad (A4)$$

670 Where E_{Kin} and E_{Pot} are the kinetic and the potential energies, respectively, v is the speed of the vehicle, F_{Rol} is the force from the rolling friction, F_{Aero} is the aerodynamic drag force, m is the mass of the vehicle, a is the vehicle acceleration, ϵ is the mass factor, g is the gravity of Earth, $grade$ is the road gradient, C_R is the coefficient of the rolling resistance, ρ_a is the density of ambient air, C_D is the drag coefficient, A is the projected frontal area of the vehicle and v_w is the headwind impacting the vehicle.

Fig. B1 shows the detailed flow chart of the TUG-PDA.




Figure B1. Emission event processing - detailed flow charts of the peak detection algorithm (TUG-PDA). CO₂ and pollutant (e.g., BC, PN, NO_x) emissions are processed separately. The algorithm is applied first to CO₂ (left) and then to the individual pollutant emissions (right). The shaded boxes are QA conditions. The processing of low emitters is highlighted in blue. Specific processing steps are only applied to CO₂ (3b) or to pollutants (1b, 1e, Stop 4, Stop5, 3c, 3d, 3.1). The following abbreviations are used: min - minimum, mov avg - moving average, conc - concentration, BG - background.

Appendix C: TUG-PDA emission separation capabilities

Fig. C1 shows the influence of interference, but additionally includes the superposition of the measured BC emissions to the superposition of CO₂ emissions. The emission distributions are separated in the same manner as in Fig. 6 into the measured CO₂ plumes with and without interference from other vehicles/sources. Compared to Fig. 6, measured CO₂ plumes which were interfered are slightly higher compared to plumes without interference. This is due to the fact that most of the BC superimposed vehicle emissions are contained in the inference datasets. These are mainly vehicles with higher emissions, as BC peaks could be detected.




Figure C1. Influence of interference (CO₂ and BC) from other vehicles/sources on the BC emission distributions determined with the TUG-PDA. Measured EFs of petrol-powered passenger cars are used for comparison. Interference data includes both overlapping plumes and plume cut-offs (interference = overlap and/or cut-off).

Figure C2 shows how accurate EFs can be calculated when using only a fraction of the plume. Therefore, the algorithm selected 82 plumes that were not affected by emissions from other vehicles. The average plume length of this selection was 18 s and 30 of the plumes were longer than 25 s. The full distribution using the algorithm's defined maximum plume length of 25 s is shown in Figure C2 on the left. Figure C2 (right) shows the deviation from the full plume when only a fraction between 3 s and 23 s is used. The median deviation is maximum at 3 s with 27 % and decreases steadily with increasing plume fraction.




Figure C2. Deviation when using only a fraction of the plume to calculate EFs compared to using the entire plume. **Left:** Distribution of EFs of plumes without interference from other vehicles. **Right:** Deviation from full plume (25 s) using only fractions between 3 s and 23 s.

Code availability. The code of the software framework is available under: <https://gitlab.com/tug-ems/point-sampling.git>.

690 *Data availability.* Measurement data is available in the CARES database for the PS measurements and on request to the authors.

Author contributions. The conceptualization was done by MK and AB. The measurements were conducted by MK, HJ and CS. The methodology and investigations were completed by MK, MP, HJ, CS, DP and AB. The software and material preparation were done by MK. MK drafted the original manuscript, which was reviewed by MP, HJ, CS, DP and AB. The project was supervised at Graz University of Technology by AB.

695 *Competing interests.* The authors declare that they have no conflict of interest.

Acknowledgements. This work is supported by TU Graz Open Access Publishing Fund. This work received funding from the EU H2020 project CARES (grant agreement No. 814966). We want to thank Åke Sjödin (IVL) for the great support during the whole project. We thank Yoann Bernard (ICCT) for the organization of the overall campaigns. We want to thank Åsa Hallquist (IVL) for the support with the PS measurements. We thank Norbert Ligterink, Thomas Frateur, Quinn Vroom and Jan Pieter Lollinga from TNO for the support during the
700 characterization experiments and Prague campaign, and for providing an ANPR camera system for all measurement campaigns. We thank David Carslaw and Naomi Farren for their support during the project. Many thanks to Simone Casadei and Tommaso Rossi from Innovhub and Silvia Moroni and Marco Bedogni from AMAT for the organization and their help during the Milan campaign. We want to thank ZTP
705 Krakow and Bartosz Piłat for the support during the Krakow campaign. Many thanks to Michal Vojtíšek and Martin Pechout for their help during the Krakow and Prague campaigns. We thank Jens Borken-Kleefeld for the continuous support during the project. Finally, we want to thank Sitaram Stepponat and Andreas Steiner for their continuous support and discussions during the project, especially for the preparation of the measurement campaigns.

References

- Bainschab, M., Schriefl, M. A., and Bergmann, A.: Particle number measurements within periodic technical inspections: A first quantitative assessment of the influence of size distributions and the fleet emission reduction, *Atmospheric Environment*, X, 8, <https://doi.org/10.1016/j.aeaoa.2020.100095>, 2020.
- Ban-Weiss, G. A., McLaughlin, J. P., Harley, R. A., Lunden, M. M., Kirchstetter, T. W., Kean, A. J., Strawa, A. W., Stevenson, E. D., and Kendall, G. R.: Long-term changes in emissions of nitrogen oxides and particulate matter from on-road gasoline and diesel vehicles, *Atmospheric Environment*, 42, 220–232, <https://doi.org/10.1016/j.atmosenv.2007.09.049>, 2008.
- Ban-Weiss, G. A., Lunden, M. M., Kirchstetter, T. W., and Harley, R. A.: Measurement of black carbon and particle number emission factors from individual heavy-duty trucks, *Environmental Science and Technology*, 43, 1419–1424, <https://doi.org/10.1021/es8021039>, 2009.
- Ban-Weiss, G. A., Lunden, M. M., Kirchstetter, T. W., and Harley, R. A.: Size-resolved particle number and volume emission factors for on-road gasoline and diesel motor vehicles, *Journal of Aerosol Science*, 41, 5–12, <https://doi.org/10.1016/j.jaerosci.2009.08.001>, 2010.
- Bernard, Y., Tietge, U., German, J., and Muncrief, R.: White paper: Determination of real-world emissions from passenger vehicles using remote sensing data, Tech. rep., International Council on Clean Transportation, <https://www.trueinitiative.org/data/publications/determination-of-real-world-emissions-from-passenger-vehicles-using-remote-sensing-data>, 2018.
- Bernard, Y., Dallmann, T., Lee, K., Rintanen, I., and Tietge, U.: Evaluation of real-world vehicle emissions in Brussels, Tech. rep., International Council on Clean Transportation, <https://www.trueinitiative.org/media/792040/true-brussels-report.pdf>, 2021.
- Bessagnet, B., Allemand, N., Putaud, J.-P., Couvidat, F., André, J.-M., Simpson, D., Pisoni, E., Murphy, B., and Thunis, P.: Emissions of Carbonaceous Particulate Matter and Ultrafine Particles from Vehicles-A Scientific Review in a Cross-Cutting Context of Air Pollution and Climate Change, *Applied Sciences*, 2022, 3623, <https://doi.org/10.3390/app12073623i>, 2022.
- Bishop, G. A., Starkey, J. R., Ihlenfeldt, A., Williams, W. J., and Stedman, D. H.: IR Long-Path Photometry A Remote Sensing Tool for Automobile Emissions, *ANALYTICAL CHEMISTRY*, 61, 53, <https://pubs.acs.org/sharingguidelines>, 1989.
- Bishop, G. A., Hottor-Raguindin, R., Stedman, D. H., McClintock, P., Theobald, E., Johnson, J. D., Lee, D. W., Zietsman, J., and Misra, C.: On-road heavy-duty vehicle emissions monitoring system, *Environmental Science and Technology*, 49, 1639–1645, <https://doi.org/10.1021/es505534e>, 2015.
- Borken-Kleefeld, J. and Dallmann, T.: White paper: Remote sensing of motor vehicle exhaust emissions, Tech. rep., International Council on Clean Transportation, www.theicct.org, 2018.
- Boveroux, F., Cassiers, S., Buekenhoudt, P., Chavatte, L., Meyer, P. D., Jeanmart, H., Verhelst, S., and Contino, F.: Feasibility study of a new test procedure to identify high emitters of particulate matter during periodic technical inspection, *SAE Technical Papers*, 2019-April, <https://doi.org/10.4271/2019-01-1190>, 2019.
- Brook, R. D., Rajagopalan, S., Pope, C. A., Brook, J. R., Bhatnagar, A., Diez-Roux, A. V., Holguin, F., Hong, Y., Luepker, R. V., Mittleman, M. A., Peters, A., Siscovick, D., Smith, S. C., Whitsel, L., and Kaufman, J. D.: Particulate matter air pollution and cardiovascular disease: An update to the scientific statement from the american heart association, *Circulation*, 121, 2331–2378, <https://doi.org/10.1161/CIR.0b013e3181dbee1>, 2010.
- Burgard, D. A., Bishop, G. A., Stadtmuller, R. S., Dalton, T. R., and Stedman, D. H.: Spectroscopy Applied to On-Road Mobile Source Emissions, *Applied Spectroscopy*, 60, 2006.
- Burtscher, H., Lutz, T., and Mayer, A.: A New Periodic Technical Inspection for Particle Emissions of Vehicles, *Emission Control Science and Technology*, 5, 279–287, <https://doi.org/10.1007/s40825-019-00128-z>, 2019.

- Cha, Y. and Sjödin, A.: Remote Sensing Measurements of Vehicle Emissions in Sarajevo, Tech. rep., IVL Swedish Environmental Research Institute, <https://www.ivl.se/download/18.5ae47fd818530c6f06012a7c/1680696264314/C727.pdf>, 2022.
- 745 Chu, M., Brimblecombe, P., Wei, P., Liu, C. H., Du, X., Sun, Y., Yam, Y. S., and Ning, Z.: Kerbside NO_x and CO concentrations and emission factors of vehicles on a busy road, *Atmospheric Environment*, 271, <https://doi.org/10.1016/j.atmosenv.2021.118878>, 2022.
- Dallmann, T. R., Harley, R. A., and Kirchstetter, T. W.: Effects of diesel particle filter retrofits and accelerated fleet turnover on drayage truck emissions at the port of Oakland, *Environmental Science and Technology*, 45, 10 773–10 779, <https://doi.org/10.1021/es202609q>, 2011.
- 750 Dallmann, T. R., Demartini, S. J., Kirchstetter, T. W., Herndon, S. C., Onasch, T. B., Wood, E. C., and Harley, R. A.: On-road measurement of gas and particle phase pollutant emission factors for individual heavy-duty diesel trucks, *Environmental Science and Technology*, 46, 8511–8518, <https://doi.org/10.1021/es301936c>, 2012.
- Dallmann, T. R., Kirchstetter, T. W., Demartini, S. J., and Harley, R. A.: Quantifying on-road emissions from gasoline-powered motor vehicles: Accounting for the presence of medium- and heavy-duty diesel trucks, *Environmental Science and Technology*, 47, 13 873–13 881, <https://doi.org/10.1021/es402875u>, 2013.
- 755 Dallmann, T. R., Onasch, T. B., Kirchstetter, T. W., Worton, D. R., Fortner, E. C., Herndon, S. C., Wood, E. C., Franklin, J. P., Worsnop, D. R., Goldstein, A. H., and Harley, R. A.: Characterization of particulate matter emissions from on-road gasoline and diesel vehicles using a soot particle aerosol mass spectrometer, *Atmospheric Chemistry and Physics*, 14, 7585–7599, <https://doi.org/10.5194/acp-14-7585-2014>, 2014.
- 760 Davison, J., Bernard, Y., Borken-Kleefeld, J., Farren, N. J., Hausberger, S., Åke Sjödin, Tate, J. E., Vaughan, A. R., and Carslaw, D. C.: Distance-based emission factors from vehicle emission remote sensing measurements, *Science of the Total Environment*, 739, <https://doi.org/10.1016/j.scitotenv.2020.139688>, 2020.
- EEA: Air quality in Europe : 2017 report., Tech. rep., European Environment Agency. and European Topic Centre on Air Pollution and Climate Change Mitigation (ETC/ACM), 2017.
- 765 Farren, N. J., Schmidt, C., Juchem, H., Pöhler, D., Wilde, S. E., Wagner, R. L., Wilson, S., Shaw, M., and Carslaw, D. C.: A plume dilution approach to quantify emissions from local combustion processes., *Science of The Total Environment*, 2023.
- Giechaskiel, B., Arndt, M., Schindler, W., Bergmann, A., Silvis, W., and Drossinos, Y.: Sampling of Non-Volatile Vehicle Exhaust Particles: A Simplified Guide, *SAE International Journal of Engines*, 5, 379–399, <https://doi.org/10.4271/2012-01-0443>, 2012.
- Giechaskiel, B., Maricq, M., Ntziachristos, L., Dardiotis, C., Wang, X., Axmann, H., Bergmann, A., and Schindler, W.: Review of motor vehicle particulate emissions sampling and measurement: From smoke and filter mass to particle number, *Journal of Aerosol Science*, 67, 48–86, <https://doi.org/10.1016/j.jaerosci.2013.09.003>, 2014.
- 770 Giechaskiel, B., Lähde, T., Suarez-Bertoa, R., Valverde, V., and Clairotte, M.: Comparisons of laboratory and on-road type-approval cycles with idling emissions. Implications for periodical technical inspection (PTI) sensors, *Sensors (Switzerland)*, 20, 1–18, <https://doi.org/10.3390/s20205790>, 2020.
- 775 Giechaskiel, B., Melas, A., Martini, G., and Dilara, P.: Overview of vehicle exhaust particle number regulations, *Processes*, 9, <https://doi.org/10.3390/pr9122216>, 2021.
- Gruening, C., Bonnel, P., Clairotte, M., Giechaskiel, B., Valverde, V., Zardini, A., and Carriero, M.: Potential of Remote Sensing Devices (RSDs) to screen vehicle emissions Assessment of RSD measurement performance, *JRC Technical Reports*, <https://doi.org/10.2760/277092>, 2019.

- 780 Hak, C. S., Hallquist, M., Ljungström, E., Svane, M., and Pettersson, J. B.: A new approach to in-situ determination of roadside particle emission factors of individual vehicles under conventional driving conditions, *Atmospheric Environment*, 43, 2481–2488, <https://doi.org/10.1016/j.atmosenv.2009.01.041>, 2009.
- Hallquist, A. M., Jerksjö, M., Fallgren, H., Westerlund, J., and Å Sjödin: Particle and gaseous emissions from individual diesel and CNG buses, *Atmospheric Chemistry and Physics*, 13, 5337–5350, <https://doi.org/10.5194/acp-13-5337-2013>, 2013.
- 785 Hansen, A. D. and Rosen, H.: Individual measurements of the emission factor of aerosol black carbon in automobile plumes, *Journal of the Air and Waste Management Association*, 40, 1654–1657, <https://doi.org/10.1080/10473289.1990.10466812>, 1990.
- Hoofman, N., Norbert, L., and Akshay, B.: Analysis of the 2019 Flemish remote sensing campaign Final report, Tech. rep., Departement Omgeving, <https://publications.tno.nl/publication/34638150/2gBdxC/hooftman-2020-analysis.pdf>, 2019.
- Horbanski, M., Pöhler, D., Lampel, J., and Platt, U.: The ICAD (iterative cavity-enhanced DOAS) method, *Atmospheric Measurement*
- 790 *Techniques*, 12, 3365–3381, <https://doi.org/10.5194/amt-12-3365-2019>, 2019.
- Huang, Y., Surawski, N. C., Yam, Y. S., Lee, C. K., Zhou, J. L., Organ, B., and Chan, E. F.: Re-evaluating effectiveness of vehicle emission control programmes targeting high-emitters, *Nature Sustainability*, 3, 904–907, <https://doi.org/10.1038/s41893-020-0573-y>, 2020.
- Janhäll, S. and Hallquist, M.: A novel method for determination of size-resolved, submicrometer particle traffic emission factors, *Environmental Science and Technology*, 39, 7609–7615, <https://doi.org/10.1021/es048208y>, 2005.
- 795 Jerksjö, M., Åke Sjödin, Merelli, L., Varella, R., and Sandström-Dahl, C.: Remote emission sensing compared with other methods to measure in-service conformity of light-duty vehicles, Tech. rep., IVL Swedish Environmental Research Institute, AVL MTC, 2022.
- Ježek, I., Drinovec, L., Ferrero, L., Carriero, M., and Močnik, G.: Determination of car on-road black carbon and particle number emission factors and comparison between mobile and stationary measurements, *Atmospheric Measurement Techniques*, 8, 43–55, <https://doi.org/10.5194/amt-8-43-2015>, 2015.
- 800 Jimenez-Palacios, J. L.: Understanding and Quantifying Motor Vehicle Emissions with Vehicle Specific Power and TILDAS Remote Sensing, Ph.D. thesis, Massachusetts Institute of Technology, 1999.
- JRC: JEC Well-To-Wheels report v5, Tech. rep., Joint Research Center, European Commission, <https://doi.org/10.2760/100379>, 2020.
- Järvinen, A., Timonen, H., Karjalainen, P., Bloss, M., Simonen, P., Saarikoski, S., Kuuluvainen, H., Kalliokoski, J., Maso, M. D., Niemi, J. V., Keskinen, J., and Rönkkö, T.: Particle emissions of Euro VI, EEV and retrofitted EEV city buses in real traffic, *Environmental Pollution*,
- 805 *250*, 708–716, <https://doi.org/10.1016/j.envpol.2019.04.033>, 2019.
- Kelly, C., Fawkes, J., Habermehl, R., de Ferreyro Monticelli, D., and Zimmerman, N.: PLUME Dashboard: A free and open-source mobile air quality monitoring dashboard, *Environmental Modelling and Software*, 160, <https://doi.org/10.1016/j.envsoft.2022.105600>, 2023.
- Knoll, A., Lang, B., and Bergmann, A.: Performance of Black Carbon Instruments for Extractive Remote Emission Sensing, <https://aaarabstracts.com/2021/AbstractBook.pdf>, aAAR conference 2021, 2021.
- 810 Knoll, M., Penz, M., Schmidt, C., Pöhler, D., Rossi, T., Casadei, S., Bernard, Y., Hallquist, A. M., Sjödin, A., and Bergmann, A.: Evaluation of the point sampling method and inter-comparison with remote emission sensing systems for screening real world car emissions, *Science of the Total Environment*, Under review.
- Ko, J., Myung, C. L., and Park, S.: Impacts of ambient temperature, DPF regeneration, and traffic congestion on NOx emissions from a Euro 6-compliant diesel vehicle equipped with an LNT under real-world driving conditions, *Atmospheric Environment*, 200, 1–14,
- 815 <https://doi.org/10.1016/j.atmosenv.2018.11.029>, 2019.
- Kulkarni, P., Baron, P. A., and Willeke, K.: *Aerosol measurement : principles, techniques, and applications*, Wiley, 2011.

- Kwon, S., Park, Y., Park, J., Kim, J., Choi, K. H., and Cha, J. S.: Characteristics of on-road NO_x emissions from Euro 6 light-duty diesel vehicles using a portable emissions measurement system, *Science of the Total Environment*, 576, 70–77, <https://doi.org/10.1016/j.scitotenv.2016.10.101>, 2017.
- 820 Lee, K., Bernard, Y., Dallmann, T., Tietge, U., Pniewska, I., and Rintanen, I.: Evaluation of real-world vehicle emissions in Warsaw, Tech. rep., International Council on Clean Transportation, <https://theicct.org/wp-content/uploads/2022/04/true-warsaw-emissions-apr22.pdf>, 2022.
- Liu, Q., Å. M. Hallquist, Fallgren, H., Jerksjö, M., Jutterström, S., Salberg, H., Hallquist, M., Breton, M. L., Pei, X., Pathak, R. K., Liu, T., Lee, B., and Chan, C. K.: Roadside assessment of a modern city bus fleet: Gaseous and particle emissions, *Atmospheric Environment: X*, 825 3, <https://doi.org/10.1016/j.aeoa.2019.100044>, 2019.
- Mannucci, P. M., Harari, S., Martinelli, I., and Franchini, M.: Effects on health of air pollution: a narrative review, *Internal and Emergency Medicine*, 10, 657–662, <https://doi.org/10.1007/s11739-015-1276-7>, 2015.
- Melas, A., Selleri, T., Suarez-Bertoa, R., and Giechaskiel, B.: Evaluation of solid particle number sensors for periodic technical inspection of passenger cars, *Sensors*, 21, <https://doi.org/10.3390/s21248325>, 2021.
- 830 Meyer, M., Bernard, Y., German, J., and Dallmann, T.: Reassessment of Excess NO_x from European Diesel Cars following the Court of Justice of the European Union Rulings, Tech. rep., International Council on Clean Transportation, <https://theicct.org/wp-content/uploads/2023/03/dieselgate-emissions-diesel-cars-Europe-mar23.pdf>, 2023.
- Mock, P. and German, J.: The future of vehicle emissions testing and compliance how to align regulatory requirements, customer expectations, and environmental performance in the european union, Tech. rep., International Council on Clean Transportation, White paper, 835 https://theicct.org/wp-content/uploads/2021/06/ICCT_future-vehicle-testing_20151123.pdf, 2015.
- Moosmüller, H., Mazzoleni, C., Barber, P. W., Kuhns, H. D., Keislar, R. E., and Watson, J. G.: On-Road Measurement of Automotive Particle Emissions by Ultraviolet Lidar and Transmissometer: Instrument, *Environmental Science and Technology*, 37, 4971–4978, <https://doi.org/10.1021/es034443p>, 2003.
- Oberdörster, G., Oberdörster, E., and Oberdörster, J.: Nanotoxicology: An Emerging Discipline Evolving from Studies of Ultrafine Particles, 840 *Environmental Health Perspectives*, 113, 823–839, <https://doi.org/10.1289/ehp.7339>, 2005.
- Park, S. S., Kozawa, K., Fruin, S., Mara, S., Hsu, Y. K., Jakober, C., Winer, A., and Herner, J.: Emission Factors for High-Emitting Vehicles Based on On-Road Measurements of Individual Vehicle Exhaust with a Mobile Measurement Platform, *Journal of the Air and Waste Management Association*, 61, 1046–1056, <https://doi.org/10.1080/10473289.2011.595981>, 2011.
- Platt, S. M., Haddad, I. E., Pieber, S. M., Zardini, A. A., Suarez-Bertoa, R., Clairotte, M., Daellenbach, K. R., Huang, R. J., Slowik, J. G., 845 Hellebust, S., Temime-Roussel, B., Marchand, N., Gouw, J. D., Jimenez, J. L., Hayes, P. L., Robinson, A. L., Baltensperger, U., Astorga, C., and Prévôt, A. S.: Gasoline cars produce more carbonaceous particulate matter than modern filter-equipped diesel cars, *Scientific Reports*, 7, <https://doi.org/10.1038/s41598-017-03714-9>, 2017.
- Preble, C. V., Dallmann, T. R., Kreisberg, N. M., Hering, S. V., Harley, R. A., and Kirchstetter, T. W.: Effects of Particle Filters and Selective Catalytic Reduction on Heavy-Duty Diesel Drayage Truck Emissions at the Port of Oakland, *Environmental Science and Technology*, 49, 850 8864–8871, <https://doi.org/10.1021/acs.est.5b01117>, 2015.
- Preble, C. V., Cados, T. E., Harley, R. A., and Kirchstetter, T. W.: In-Use Performance and Durability of Particle Filters on Heavy-Duty Diesel Trucks, *Environmental Science and Technology*, 52, 11 913–11 921, <https://doi.org/10.1021/acs.est.8b02977>, 2018.
- Pöhler, D., Engel, T., Roth, U., Reber, J., Horbanski, M., Lampel, J., and Platt, U.: NO_x RDE measurements with Plume Chasing-Validation, detection of high emitters and manipulated SCR systems, 23rd Transport and Air Pollution Conference, Thessaloniki 2019, 2019.

- 855 Qiu, M. and Borken-Kleefeld, J.: Using snapshot measurements to identify high-emitting vehicles, *Environmental Research Letters*, 17, <https://doi.org/10.1088/1748-9326/ac5c9e>, 2022.
- Rossomando, B., Meloni, E., de Falco, G., Sirignano, M., Arsie, I., and Palma, V.: Experimental characterization of ultrafine particle emissions from a light-duty diesel engine equipped with a standard DPF, in: *Proceedings of the Combustion Institute*, vol. 38, pp. 5695–5702, Elsevier Ltd, <https://doi.org/10.1016/j.proci.2020.09.011>, 2021.
- 860 Rönkkö, T., Saarikoski, S., Kuittinen, N., Karjalainen, P., Keskinen, H., Järvinen, A., Mylläri, F., Aakko-Saksa, P., and Timonen, H.: Review of black carbon emission factors from different anthropogenic sources, *Environmental Research Letters*, 18, <https://doi.org/10.1088/1748-9326/acbb1b>, 2023.
- Salimbene, O., Morreale, S., and Pilla, F.: Health Risk Assessment and Black Carbon: State of Art and new Prospectives, in: *Air Pollution XXIX*, vol. 252, pp. 149–159, WITPress, <https://doi.org/10.2495/AIR210141>, 2021.
- 865 Schriebl, M. A., Nishida, R. T., Knoll, M., Boies, A. M., and Bergmann, A.: Characterization of particle number counters based on pulsed-mode diffusion charging, *Aerosol Science and Technology*, 54, 772–789, <https://doi.org/10.1080/02786826.2020.1724257>, 2020.
- Singer, B. C. and Harley, R. A.: A Fuel-Based Motor Vehicle Emission Inventory, *Journal of the Air and Waste Management Association*, 46, 581–593, <https://doi.org/10.1080/10473289.1996.10467492>, 1996.
- Singleton, F.: The Beaufort scale of winds - Its relevance, and its use by sailors, *Weather*, 63, 37–41, <https://doi.org/10.1002/wea.153>, 2008.
- 870 Stedman, D. H., Bishop, G. A., Guenther, P. L., Peterson, J. E., and Beaton, S. P.: Remote Sensing of On-Road Vehicle Emissions, University of Denver, Digital Commons @ DU, https://digitalcommons.du.edu/feat_publications, 1992.
- Sugrue, R. A., Preble, C. V., and Kirchstetter, T. W.: Comparing the use of high-to low-cost black carbon and carbon dioxide sensors for characterizing on-road diesel truck emissions, *Sensors (Switzerland)*, 20, 1–18, <https://doi.org/10.3390/s20236714>, 2020.
- Tietge, U., Mock, P., German, J., Bandivadekar, A., and Ligterink, N.: From Laboratory to road. A 2017 update of official and "real-world" fuel consumption and CO₂ values for passenger cars in Europe, Tech. rep., International Council on Clean Transportation, White paper, https://theicct.org/sites/default/files/publications/Lab-to-road-2017_ICCT-white%20paper_06112017_vF.pdf, 2017.
- 875 Wang, H., Wu, Y., Zhang, K. M., Zhang, S., Baldauf, R. W., Snow, R., Deshmukh, P., Zheng, X., He, L., and Hao, J.: Evaluating mobile monitoring of on-road emission factors by comparing concurrent PEMS measurements, *Science of the Total Environment*, 736, <https://doi.org/10.1016/j.scitotenv.2020.139507>, 2020.
- 880 Wang, J. M., Jeong, C. H., Zimmerman, N., Healy, R. M., Wang, D. K., Ke, F., and Evans, G. J.: Plume-based analysis of vehicle fleet air pollutant emissions and the contribution from high emitters, *Atmospheric Measurement Techniques*, 8, 3263–3275, <https://doi.org/10.5194/amt-8-3263-2015>, 2015.
- Wang, J. M., Jeong, C. H., Zimmerman, N., Healy, R. M., Hilker, N., and Evans, G. J.: Real-World Emission of Particles from Vehicles: Volatility and the Effects of Ambient Temperature, *Environmental Science and Technology*, 51, 4081–4090, <https://doi.org/10.1021/acs.est.6b05328>, 2017.
- 885 Watne, A. K., Psichoudaki, M., Ljungström, E., Breton, M. L., Hallquist, M., Jerksjö, M., Fallgren, H., Jutterström, S., and Åsa M. Hallquist: Fresh and Oxidized Emissions from In-Use Transit Buses Running on Diesel, Biodiesel, and CNG, *Environmental Science and Technology*, 52, 7720–7728, <https://doi.org/10.1021/acs.est.8b01394>, 2018.
- Yang, H.-H., Dhital, N. B., Wang, L.-C., Hsieh, Y.-S., Lee, K.-T., Hsu, Y.-T., and Huang, S.-C.: Chemical characterization of fine particulate matter in gasoline and diesel vehicle exhaust, *Aerosol and Air Quality Research*, 19, 1439–1449, <https://doi.org/10.4209/aaqr.2019.04.0191>, 2019.

Yang, J., Stewart, M., Maupin, G., Herling, D., and Zelenyuk, A.: Single wall diesel particulate filter (DPF) filtration efficiency studies using laboratory generated particles, *Chemical Engineering Science*, 64, 1625–1634, <https://doi.org/10.1016/j.ces.2008.12.011>, 2009.

895 Zhou, L., Liu, Q., Lee, B. P., Chan, C. K., Åsa M. Hallquist, Åke Sjödin, Jerksjö, M., Salberg, H., Wängberg, I., Hallquist, M., Salvador, C. M., Gaita, S. M., and Mellqvist, J.: A transition of atmospheric emissions of particles and gases from on-road heavy-duty trucks, *Atmospheric Chemistry and Physics*, 20, 1701–1722, <https://doi.org/10.5194/acp-20-1701-2020>, 2020.