

Dear Editor,

We are writing to express our gratitude for the insightful and constructive comments provided by the reviewers for our manuscript titled "Lahar events in the last 2,000 years from Vesuvius eruptions. Part 2: Formulation and validation of a computational model based on a shallow layer approach" (Preprint egusphere-2023-1301). We are pleased to inform you that we have carefully considered the feedback and suggestions provided by Reviewer 1 and Reviewer 2 and have revised our paper in accordance with their recommendations.

Reviewer 1's comments highlighting the need to show the influence of dynamic pressure. In response, we discussed this point and added a new figure showing two dynamic pressure maps. Additionally, Reviewer 1 suggested several technical corrections which have been addressed.

Reviewer 2's feedback was mostly focused on the capability of the model to perform a counterfactual analysis of the 1631 event. As per this suggestion, we now discuss this point in the Conclusion section, with a reference to the work done in the companion paper Sandri et al. where we considered alternative hydraulic catchment, together with the variability in the initial volume, in the initial water fraction and initial thickness of the ash deposit. These addition helps to better put our paper in the context of risk analysis.

In addition to the suggested revisions, we have made some minor changes to the text, ranging from improvements in clarity and coherence to the correction of typographical errors. We also replaced the original figures with new ones with a higher resolution.

We believe that the revisions made in response to the reviewers' feedback have substantially enhanced the quality and impact of our manuscript. We are confident that the changes we have implemented align well with the standards of rigor and clarity that Solid Earths upholds.

Enclosed herewith, please find the detailed answers to all reviewer's comments, the list of new references added to the manuscript, and a revised version of our manuscript highlighting all the changes. We kindly request that you consider our revised submission for publication in Solid Earth. We would also like to extend our gratitude to the reviewers for their time, expertise, and dedication in helping us improve the quality of our work.

Thank you for considering our revised manuscript. We eagerly await your decision and remain at your disposal for any further information or clarification.

Sincerely,

Mattia de' Michieli Vitturi, Antonio Costa, Mauro A. Di Vito, Laura Sandri, Domenico M. Doronzo

## ANSWERS TO REVIEWERS


Reviewers' comments are in bold.

**RC1:** 'Comment on egosphere-2023-1301', Anonymous Referee #1, 05 Sep 2023 reply

**COMMENT.** Historically, flow thickness has been employed as a determinant factor. It might be instructive—though not imperative—to scrutinize the influence on dynamic pressure, particularly if a notable alteration is discerned. The manuscript is methodically robust and coherently structured. Both the objectives and the conclusions drawn are lucid and of significant import.

**ANSWER.** *We thank the reviewer for the suggestion. We added a new figure in the paper showing two dynamic pressure maps. The figure is described in the paper by the following text:*

“Flow thickness may also be combined with dynamic pressure in order to assess, for different couples of thickness and dynamic pressure thresholds, the areas where these thresholds are exceeded simultaneously. Figure 13 shows, for two different thickness thresholds, the values of dynamic pressure exceeded during 24 hours of simulation. For example, in Figure 13b, the light green pixels represent the area where at some time the lahar produced, simultaneously, a thickness of at least 2 m and a dynamic pressure larger than 2000 Pa and smaller than 5000 Pa. “



*Figure 13.* Maps of exceedance of flow thickness and dynamic pressure: (a) thickness threshold 0.5m; (b) thickness threshold 2m. The colors represent the dynamic pressure thresholds exceeded during the 24 hours of simulation simultaneously with the thickness threshold.

### Technical corrections

#### 1. Missing reference (citation in bibliography)

##### a. Line 44 (IEA et al, 2016)

*The following reference has been added to the bibliography:*

*International Atomic Energy Agency (IAEA): Volcanic Hazard Assessments for Nuclear Installations: Methods and Examples in Site Evaluation, IAEA-TECDOC-1795, IAEA, Vienna, 2016.*

**b. Line 228 (Biagioli et al 2022) but bibliography says 2021**

*Fixed at line 228 (2021 is correct).*

**c. Line 250 Is Sandri et al 2023 the same that Sandri et al (this issue)? If yes please change Sandri et al 2023 citation, if not reference is missing**

*Changed here and in other lines to Sandri et al (this issue)*

**d. Line 334 missing reference (Bisson et al 2014)**

*The following reference has been added to the bibliography:*

*Bisson, M., Spinetti, C., & Sulpizio, R.: Volcaniclastic flow hazard zonation in the Sub-Apennine Vesuvian area using GIS and remote sensing. Geosphere, 10(6), 1419-1431, <https://doi.org/10.1130/GES01041.1>, 2014.*

**e. Line 466 review reference (Hong at al, 2016) by (Hong et al.,2016)**

*Fixed*

**2. Figures legend**

**a. Figure 3 wrong legend (solid fraction title does not correspond with the i. caption and text)**

*The problem was with Figure 2 and not Figure3. Now the text and the caption has been fixed. Thanks!*

**b. Please review Figure 5, the descriptions in the text (from line 277 to 304) do not correspond to the assigned label (a,b,c,d,e,f) figures that seem to be switched.**

*The reviewer is right. We switched the top and middle panels in the figure, and we fixed the text.*

**c. Lines 443 are talking about Figure 8 but Figure 7 is referenced**

*Fixed*

**d. Line 447 ¿Is it possible to show in Figure 7 the locations mentioned in line 447?**

*Added all the locations, apart from Acerra which is covered by the legend.*

**e. Missing (a,b,c,d) in Figure 13**

*Added letters and improved the quality of the figure.*

**f. Line 582 mention Figure 12a (does not exist)**

*We fixed the Figure reference (the correct one is 13a) and added a reference to Figure 16 in the text.*

**g. Missing (a,b,c,d) in Figure 17**

*Added letters and improved the quality of the figure.*

RC2: 'Comment on egusphere-2023-1301', Gordon Woo, 03 Oct 2023 reply

**COMMENT.** Using their enhanced modelling capability, it would be possible to consider alternative realisations of the 1631 events, inter alia, taking account of the substantial variability in the initial conditions and other model parameters. This counterfactual analysis would be very insightful and instructive for lahar risk analysis (Aspinall and Woo, 2019, Counterfactual analysis of runaway volcanic explosions, *Front.Earth.Sci.*). Such counterfactual risk analysis may be deferred to another publication, but some discussion would be useful for this paper.

ANSWER. *We thank the reviewer for the suggestion. We added this sentence at the end of the paper:*

*“The companion paper by Sandri et al. (this issue) will show an application of the presented model for hazard analysis of lahars from Vesuvius deposits in the Neapolitan area, where a wide range of initial conditions are investigated to produce probabilistic hazard maps. To reach this goal, the companion paper considers eleven hydraulic catchments threatening the Campanian Plain, and in each catchment a large number of simulations accounts for the variability in the initial lahar volume, initial water fraction and initial mass load of the ashfall deposit. The database of simulations considered in the analysis by Sandri et al. (this issue) would allow one also to consider alternative realisations of the 1631 events, permitting for a counterfactual analysis that can be very insightful for lahar risk analysis (Aspinall and Woo, 2019), and it will be the focus of future research.”*

*In addition, we added Aspinall and Woo (2019) to the list of references.*

## NEW REFERENCES ADDED TO THE MANUSCRIPT

Aspinall, W., and Woo, G.: Counterfactual analysis of runaway volcanic explosions. *Frontiers in Earth Science*, 7, 222, <https://doi.org/10.3389/feart.2019.00222>, 2019.

Bisson, M., Spinetti, C., & Sulpizio, R.: Volcaniclastic flow hazard zonation in the Sub-Apennine Vesuvian area using GIS and remote sensing. *Geosphere*, 10(6), 1419-1431, <https://doi.org/10.1130/GES01041.1>, 2014.

International Atomic Energy Agency (IAEA): *Volcanic Hazard Assessments for Nuclear Installations: Methods and Examples in Site Evaluation*, IAEA-TECDOC-1795, IAEA, Vienna, 2016.

# 1 Lahar events in the last 2,000 years from Vesuvius eruptions. Part 2 2: Formulation and validation of a computational model based on 3 a shallow layer approach

4 Mattia de' Michieli Vitturi<sup>1</sup>, Antonio Costa<sup>2</sup>, Mauro A. Di Vito<sup>3</sup>, Laura Sandri<sup>2</sup>, Domenico M.  
5 Doronzo<sup>3</sup>

6  
7 <sup>1</sup>Istituto Nazionale di Geofisica e Vulcanologia, Sezione di Pisa, Pisa, 56125, Italy

8 <sup>2</sup>Istituto Nazionale di Geofisica e Vulcanologia, Sezione di Bologna, Bologna, 40128, Italy

9 <sup>3</sup>Istituto Nazionale di Geofisica e Vulcanologia, Osservatorio Vesuviano, Napoli, 80124, Italy

10 *Correspondence to:* Mattia de' Michieli Vitturi (mattia.demichielivitturi@ingv.it)

11 **Abstract.** In this paper we present a new model for the simulation of lahars, based on the depth-averaged code IMEX-  
12 SfloW2D with new governing and constitutive equations introduced to better describe the dynamics of lahars. A thorough  
13 sensitivity analysis is carried out to identify the critical processes (such as erosion and deposition) and parameters (both  
14 numerical and physical) controlling lahar runout, using both synthetic and real cases topographies. In particular, an  
15 application of the model to a syn-eruptive lahar from a reference-size eruption from Somma-Vesuvius, affecting the  
16 Campanian Plain (Southern Italy), described in Di Vito et al. (this issue), -is used in this work for the sensitivity analysis.  
17 Effects of erosion and deposition are investigated by comparing simulations with and without these processes. By  
18 comparing flow thickness and area covered by the flow and their evolution with time, we show that the modelling of both  
19 the processes is important to properly simulate the effects of the bulking and debulking and the associated changes in  
20 rheology. From a computational point of view, the comparison of simulations obtained for different numerical grids (from  
21 25 m to 100 m), scheme order, and grain size discretization were useful to find a good compromise between resolution  
22 and computational speed. The companion paper by Sandri et al. (this issue) shows an application of the presented model  
23 for probabilistic volcanic hazard assessment for lahars from Vesuvius deposits in the Neapolitan area.

## 24 1 Introduction

25 Water saturated flows made from volcanic deposits are known as “lahar”, an Indonesian term used to indicate muddy  
26 flows. As typical in the volcanological literature, here we will use the term lahar to denote any water saturated flows,  
27 from hyperconcentrated flow, carrying up to 50 vol % sediment, to lower concentration flows (< 10 % sediment). These  
28 wet granular flows are commonly characterised by a high flow density and can have high flow velocity, generating large  
29 dynamic pressures able to destroy even buildings and infrastructures. Moreover, this kind of flows can inundate large  
30 areas, disrupting ground transportation networks, human settlements, power lines, industry, agriculture (e.g., Zanchetta  
31 et al., 2004).

32 Lahars can form from the remobilization of unconsolidated tephra, as for the hundreds of lahars generated by torrential  
33 rains after the 1991 Pinatubo eruptions in the Philippines (Van Westen and Daag, 2005). In other cases, as at Mount St.  
34 Helens, lahars can result from dome collapses and the associated volcanic explosions (Scott, 1988). Additionally,

35 devastating lahars can form when a pyroclastic flow melts snow or ice caps (Major and Newhall, 1989), as occurred for  
36 the 1995 eruption on the glaciated Nevado del Ruiz, Colombia (Pierson et al., 1990). Mt. Rainier is another example of a  
37 volcano that experienced several lahars of this kind in the past. Lahars can also form ~~also~~ in eruptions beneath crater  
38 lakes, as at Keluth, Indonesia (Mastin and Witter, 2000) and Ruapehu, New Zealand (Lecointre et al., 2004).

39 If lahars are generated before, during, or after the eruption they are named pre-eruptive, syn-eruptive, or post-eruptive  
40 lahars (Vallance and Iverson, 1995). The term syn-eruptive must not be taken literally, but indicates a lahar generated  
41 during or in the period immediately following an eruption. Besides a triggering mechanism, generation of a lahar requires  
42 *i*) an adequate water source, which can be hydrothermal water, rapidly melted snow and ice, crater lake water, and rainfall  
43 runoff, *ii*) abundant unconsolidated debris that typically includes pyroclastic flow and fall deposits, glacial drift,  
44 colluvium, and soil, and *iii*) steep slopes and substantial relief at the source (IAEA, 2016). Because lahars are water  
45 saturated flows, for which both liquid and solid interactions are fundamental, their behaviour is different from other  
46 related phenomena common to volcanoes such as debris avalanches and floods. In terms of fragment size distribution, the  
47 material carried by lahars ranges in diameter from about  $10^{-6}$  m to 10 m. Lahars can have temperature up to 100 °C and  
48 can change character downstream, through processes of flow bulking (erosion and incorporation of secondary debris as  
49 they move downstream) and debulking (a process in which the lahar selectively deposits certain particles, owing to their  
50 size or density, as it moves downstream). Primary particles in lahar deposits derive from contemporaneous eruption  
51 deposits or, in the case of avalanche induced lahar deposits, from the original avalanche mass; secondary particles derive  
52 from the erosion and incorporation of downstream volcanoclastic debris, alluvium, colluvium glacial drift, bedrock, etc.  
53 Many properties of lahars including, but not limited to, particle concentration, granulometry and componentry, bulk  
54 rheology and velocity are highly variable in both time (i.e. unsteadiness) and space (i.e. non-uniformity).

55 Several methods have been proposed to assess the related hazard, ranging from simple empirical models like LAHARZ  
56 (Iverson et al., 1998), which can be used to estimate the inundated areas, to geophysical mass-flow models which use  
57 different rheological laws, such as Newtonian, Bingham, Bagnold, or Coulomb models, depending on flow behaviour,  
58 (e.g., TITAN2D, Pitman et al., 2003; Patra et al., 2005; FLO2D, O'Brien et al., 1993; VolcFlow, Kelfoun and Druitt,  
59 2005; Kelfoun et al., 2009) and can furnish values of critical variables, such as velocity and dynamic pressure. A different  
60 approach, based on a fully three-dimensional model of two-phase flows, can be found in Darteville (2004) and Meruane  
61 et al. (2010). One of the most general two-phase debris-flow models was developed by Pudasaini (2012), and it includes  
62 many essential physical phenomena observable in debris flows. Mohr-Coulomb plasticity is used to close the solid stress.  
63 The reader is addressed to Pudasaini (2012) and references therein for a general review of the topic. More recently,  
64 building on the Pudasaini (2012) two-phase flow model, Pudasaini and Margili (2019) presented a new mass flow model  
65 (r.avaflow, <https://www.landslidemodels.org/r.avaflow>) accounting for the complexity of geomorphic mass flows  
66 consisting of coarse particles, fine particles, and viscous fluid.

67 In this work we present a new simplified model developed for the aim of lahar hazard assessment. The model, discussed  
68 in Section 2, is based on the Saint-Venant depth-averaged equations, coupled with source terms accounting for friction  
69 and with terms for erosion/deposition of solid particles. Then in Section 3 we present a few examples of model validation  
70 and applications, and in Section 4 a short discussion and conclusion.

## 71 **2 Physical-numerical model**

72 The physical model for lahars is based on the shallow layer approach and on the solutions of a set of depth-averaged  
 73 transport equations. As we explain below numerical solution was obtained by modifying the IMEX-SfloW2D code (de'  
 74 Michieli-Vitturi et al., 2019), with new governing and constitutive equations introduced to better simulate lahars  
 75 dynamics. In this section, we briefly introduce all model variables, and we describe the governing equations.

## 76 2.1 Model governing equations

### 77 2.1.1 Depth-averaged transport equations

78 In this section, we present the set of partial differential equations governing the dynamics of lahars. Assuming that the  
 79 lahar flow is a homogeneous mixture of water and  $n_s$  solid phases (see Fig. 1), its density  $\rho_m(x, y, t)$  is defined in terms  
 80 of the volumetric fractions  $\alpha_{(\cdot)}$  and densities  $\rho_{(\cdot)}$  of the components:

$$\rho_m = \alpha_w \rho_w + \sum_{i_s=1}^{n_s} \alpha_{s,i_s} \rho_{s,i_s} \quad (1)$$

81 where the subscript  $w$  denotes the water phase and the subscript  $s, i_s$  denote the class  $i_s$  of the solid phase. Equations are  
 82 written in global Cartesian coordinates  $(x, y)$ , with  $x$  and  $y$  orthogonal to the  $z$ -axis, assumed to be parallel to  
 83 gravitational acceleration  $g = (0, 0, g)$ . We denote the flow thickness with  $h(x, y, t)$  and the depth-averaged horizontal  
 84 components of the flow velocity with  $u(x, y, t)$  and  $v(x, y, t)$ , assuming that, due to the flow turbulence, solid phases are  
 85 well mixed with the liquid carrier phases, and they have the same horizontal velocity. The flow moves over a topography,  
 86 described by the variable  $B(x, y, t)$ . In principle, topography can change with time, but as first approximation we neglect  
 87 the changes associated with erosion and deposition, while these processes are modelled and accounted for the flow  
 88 dynamics. Thus, we assume the topography being a function of space only.

89 With the notation introduced above, conservation of mass for the flow mixture writes in the following way:

$$\frac{\partial \rho_m h}{\partial t} + \frac{\partial (\rho_m h u)}{\partial x} + \frac{\partial (\rho_m h v)}{\partial y} = \sum_{i_s=1}^{n_s} [\rho_{s,i_s} (E_{s,i_s} - D_{s,i_s})] + \rho_w \left\{ D_w + \frac{\alpha_d}{1 - \alpha_d} \sum_{i_s=1}^{n_s} [(E_{s,i_s} - D_{s,i_s})] \right\}, \quad (2)$$

90 where  $E_s$  and  $D_s$  are the volumetric rate of erosion and deposition of solid particles, respectively, and  $D_w$  is the rate of  
 91 loss of water, not associated with the deposition of particles (for example associated with evaporation or other processes).  
 92 The first term on the right-hand side accounts for the loss and entrainment of solid particles, while the last term accounts  
 93 for the loss of water. This term accounts not only for the loss due to the rate  $D_w$ , but also for the loss associated with  
 94 particle erosion and sedimentation. In fact, we assume both the pre-existing erodible layer and the flow deposit water-  
 95 saturated, with the volume fraction of water given by  $\alpha_w$ .

96 The two equations for momentum conservation are:

$$\begin{aligned} \frac{\partial(\rho_m hu)}{\partial t} + \frac{\partial}{\partial x} \left( \rho_m hu^2 + \frac{1}{2} \rho_m gh^2 \right) + \frac{\partial}{\partial y} (\rho_m huv) = -\rho_m gh \frac{\partial B}{\partial x} + F_x \\ - u \left[ \sum_{i_s=1}^{n_s} (\rho_{s,i_s} D_{s,i_s}) + \rho_w \left( D_w + \frac{\alpha_d}{1 - \alpha_d} \sum_{i_s=1}^{n_s} D_{s,i_s} \right) \right], \end{aligned} \quad (3a)$$

97

$$\begin{aligned} \frac{\partial(\rho_m hv)}{\partial t} + \frac{\partial}{\partial x} (\rho_m huv) + \frac{\partial}{\partial y} \left( \rho_m hv^2 + \frac{1}{2} \rho_m gh^2 \right) = \\ -\rho_m gh \frac{\partial B}{\partial y} + F_y - v \left[ \sum_{i_s=1}^{n_s} (\rho_{s,i_s} D_{s,i_s}) + \rho_w \left( D_w + \frac{\alpha_d}{1 - \alpha_d} \sum_{i_s=1}^{n_s} D_{s,i_s} \right) \right], \end{aligned} \quad (3b)$$

98 where  $F = (F_x, F_y)$  is the vector of frictional forces and the last term on the right-hand side of both the equations considers  
 99 the loss of momentum associated with particle sedimentation. Please note that there are no terms associated with erosion  
 100 of solid particles in the momentum equations, because they do not carry any horizontal momentum within the flow,  
 101 although they change the inertia terms.

102 Flow temperature  $T$  changes with entrainment of water and solid particles eroded from the underlying terrain, and this in  
 103 turn can change lahars property (for example viscosity). For this reason, we also solve for a transport equation for the  
 104 internal energy  $e = C_v T$  (with  $C_v$  being the mass averaged specific heat in the flow):

$$\begin{aligned} \frac{\partial}{\partial t} (\rho_m h e) + \frac{\partial}{\partial x} (\rho_m h u e) + \frac{\partial}{\partial y} (\rho_m h v e) \\ = \sum_{i_s=1}^{n_s} [\rho_{s,i_s} C_{s,i_s} (T_s E_{s,i_s} - T D_{s,i_s})] + \rho_w C_w \frac{\alpha_d}{1 - \alpha_d} \sum_{i_s=1}^{n_s} [(T_s E_{s,i_s} - T D_{s,i_s})] \end{aligned} \quad (4)$$

105 where  $C_s, C_w$  are the specific heats of solid and water, respectively, and  $T_s$  is the substrate temperature before erosion. In  
 106 this equation, heat transfer by thermal conduction is neglected, as well as thermal radiation and heating due to friction.

107 Additional transport equations for the mass of  $n_s$  solid classes are also considered:


$$\frac{\partial (s, i_s \rho_{s,i_s} h)}{\partial t} + \frac{\partial (\alpha_{s,i_s} \rho_{s,i_s} hu)}{\partial x} + \frac{\partial (\alpha_{s,i_s} \rho_{s,i_s} hv)}{\partial y} = \rho_{s,i_s} (E_{s,i_s} - D_{s,i_s}), \quad i_s = 1, \dots, n_s \quad (5)$$

108 Finally, we have  $n_s$  equations for the volume of solid particles in the water-saturated erodible layer:

$$\frac{\partial \alpha_{s,i_s} h_{s,i_s}}{\partial t} = (E_{s,i_s} - D_{s,i_s}), \quad i_s = 1, \dots, n_s \quad (6)$$

109 where  $h_{s,i_s}$  is the thickness of each solid class in the layer, related to the total thickness  $h_e$  of this layer by the  
 110 relationship:

$$h_e = \frac{1}{1 - \alpha_w} \sum_{i_s=1}^{n_s} h_{s,i_s}. \quad (7)$$



111

112 *Figure 1. Sketch of the lahar.*

113

114 **2.1.2. Constitutive equations**

115 The set of equations (1-7) constitute a set of  $4 + n_s$  partial differential equations for the unknown state variables  $Q = h$ ,  
 116  $u, v, T, \alpha_{s,1}, \dots, \alpha_{s,n_s}$ . In order to close the system and to be able to solve the equations, the terms accounting for friction,  
 117 deposition, erosion should be defined as functions of the state variables  $Q$ .

118 The friction term appearing in the momentum equations is written in the following way:

$$F = (F_x, F_y) = \rho_m g h \left( \frac{u}{\sqrt{u^2 + v^2}} s_f, \frac{v}{\sqrt{u^2 + v^2}} s_f \right) \quad (8)$$

119

120 where  $s_f$  is defined, accordingly to O'Brien et al. (1993), as the total friction slope, given by the sum of three non-  
 121 dimensional terms:

$$s_f = s_y + s_v + s_t. \quad (9)$$

122 Here,  $s_y$  is the velocity-independent yield slope,  $s_v$  is the viscous slope and  $s_t$  is the turbulent slope. These three terms,  
 123 as done in the numerical code FLO-2D, are written in the following way:

$$s_f = \frac{\tau_y}{\rho_m g h} + \frac{K \mu \sqrt{u^2 + v^2}}{8 \rho_m g h^2} + \frac{n_{td}^2 (u^2 + v^2)}{h^{4/3}} \quad (10)$$

124 where  $\tau_y$  is yield strength,  $K$  is an empirical resistance parameter,  $\mu$  is fluid viscosity and  $n_t$  is the Manning roughness  
 125 coefficient. In FLO-2D model (O'Brien et al., 1993), yield strength  $\tau_y$  and fluid viscosity  $\mu_m$  are defined through two  
 126 empirical relationships derived from field observations:

$$\mu_m = a_1 \exp(b_1 \alpha_s) \quad (11a)$$

127

$$\tau_y = a_2 \exp(b_2 \alpha_s) \quad (11b)$$

128

129 where  $a_i$  and  $b_i$  are coefficients defined by laboratory experiments and  $\alpha_s$  is the total volumetric fraction of solid ( $\alpha_s =$   
 130  $\sum_{i_s=1}^{n_s} \alpha_{s,i_s}$ ). In the original formulation of O'Brian et al., (1993) the empirical parameters  $a_1$  e  $b_1$  are model constants,  
 131 which do not vary with flow temperature. Here, we notice that the parameter  $a_1$  has the units of a dynamic viscosity and  
 132 it can be seen as the limit viscosity of the mixture when the dispersed solid fraction goes to zero. Thus, it should represent  
 133 the dynamic viscosity of water. Commonly this parameter can be assumed to be constant, but in order to account for the  
 134 dependence of water viscosity on its temperature, which could potentially affect lahar dynamics and runout, here we  
 135 account for an additional correction factor  $\Gamma(T^c)$ , function of the temperature expressed in Celsius degrees:

$$a_1 = [\mu^{ref} \cdot \Gamma(T^c)]. \quad (12)$$

136

137 where  $\mu^{ref}$  denotes the viscosity at a reference temperature  $T^{ref}$ . Following Crittenden et al. (2012), the equation used  
 138 to compute the factor  $\Gamma(T^c)$  is given by:

$$\Gamma(T) = C \cdot \gamma \cdot 10^A$$

139

140 where:

$$\begin{cases} \gamma = 10^{-3}, & \text{for } 0 < T^c < 20^\circ\text{C} \\ \gamma = (1.002 \cdot 10^{-3})(10^B), & \text{for } T^c \geq 20^\circ\text{C} \end{cases}$$

141

$$\begin{cases} A = \frac{1301}{998.333 + 8.1855(T^c - 20) + 0.00585(T^c - 20)^2} - 1.30223 & \text{for } 0 < T^c < 20^\circ\text{C} \\ A = \frac{1.3272(20 - T^c) - 0.001053(T^c - 20)^2}{T^c + 105} & \text{for } T^c \geq 20^\circ\text{C} \end{cases}$$

142


143 and  $C$  is a constant such that  $\Gamma(T^{c,ref}) = 1$ . With this choice, when  $T^c = T^{c,ref}$  and  $\alpha_s = 0$ ,  $\mu = \mu^{ref}$ . With respect to  
 144 the original work of O'Brian et al., (1993), also the original relationship for yield strength has been modified. In fact, here  
 145 we take:

$$\tau_y = a_2(\exp(b_2\alpha_s) - 1) \quad (13)$$

146  
 147 In this way, yield stress disappears when solid fraction  $\alpha_s$  goes to zero, recovering the Newtonian behaviour of water.


148  
 149 The values of the three components of the total friction slope (see Eq. 10) strongly depends on volumetric solid fraction,  
 150 on flow thickness and velocity. In Figure 2, for fixed values of the empirical parameters  $a_i$  and  $b_i$  ( $i=1,2$ ) and for three  
 151 different values of the total solid volume fraction ( $\alpha_s = 0.1$  on the top left;  $\alpha_s = 0.325$  in the middle;  $\alpha_s = 0.56$  on the  
 152 bottom right), we plotted the values of the three terms as function of flow thickness and velocity. These diagrams (in  
 153 logarithmic scale for all the variables) highlight how these terms can vary in a non-linear way by several orders of  
 154 magnitude when thickness, velocity and solid fraction vary in ranges that can be observed in lahars, potentially resulting  
 155 in the presence of a stiff term in the system of equations. For this reason, ~~it is needed~~ a robust solver that allows the  
 156 coupling between the gravitational and frictional terms ~~is needed to be accurately simulated~~.

157  
 158



159 Figure 2. Contribution of the yield slope ( $s_y$ ), viscous slope ( $s_v$ ) and turbulent slope ( $s_{td}$ ) to the total friction slope for  
 160 three different solid volume fractions: 10% (left); 2535% (middle); 650% (right). The friction parameters have the  
 161 following values:  $K = 24.0$ ;  $a_1 = 8.9 \cdot 10^{-4}$ ;  $b_1 = 22.1$ ;  $n_t = 0.1$ ;  $a_2 = 0.272$ ;  $b_2 = 22.0$ .

162 We also note that the presence of the yield strength term, i.e. a term independent of the velocity that opposes the motion,  
 163 allows the flow to stop with a thickness that depends on the slope of the topography and on the fraction of solid material  
 164 in the flow. This critical thickness can be calculated analytically and allows for the validation of the correct  
 165 implementation of the discretization of the friction terms in the numerical model. Below we present a figure illustrating  
 166 this relationship, where each line represents the critical thickness threshold line between the steady and unsteady condition  
 167 for different total solid percentages in the flow. We can see that, approximately, an increase of 10% in the solid volume  
 168 fraction, for a fixed slope, corresponds to a factor 4.5 increase in the critical thickness. We also observe that such a critical  
 169 thickness is not only relevant for flow stoppage, but also for the initial triggering of the flow, and that this relationship  
 170 can be formulated also in terms of critical liquid volume fraction. Thus, given a thickness of the permeable layer and a  
 171 slope, we can compute the critical liquid volume fraction over which the lahar is triggered because the gravitational force  
 172 exceeds the yield strength. For example, a slope of  $20^\circ$  and a thickness of 1 m, a 60% liquid volume would trigger a lahar,  
 173 while a 50% liquid volume would not. It is also worth to note that these critical thresholds depend on the values of the  
 174 parameters for the yield strength.



175  
 176 Figure 3. Critical thickness as a function of topography slope and solid volume fraction computed with the following  
 177 values for the yield strength parameters:  $a_2 = 0.272$ ;  $b_2 = 22.0$ . The four black dots represent couples of slope and  
 178 thickness values used to test the capability of the numerical solver to properly reproduce the triggering conditions of  
 179 lahars.

### 180 2.1.3 Erosion term

181 Following the parameterization by Fagents and Baloga (2006), we adopted an empirical relationship for the volumetric  
 182 erosion rate  $E_{tot}$  of the substrate:

$$E_{tot} = \epsilon h \sqrt{u^2 + v^2} (1 - \alpha_s). \quad (14)$$

183 This relation states that erosion is proportional to the thickness of the flow, the modulus of flow velocity and the  
 184 volumetric fraction of water in the flow, through an empirical constant  $\epsilon$  (with units 1/[L]). In the original work by Fagents  
 185 and Baloga (2006), it is assumed that the rate of turbulent entrainment diminishes with increasing flow density. In fact,  
 186 as the flow entrains solid sediment, turbulence is progressively dampened (Costa, 1988). Here, because the density is  
 187 linearly proportional to the water volume fraction, we directly introduced a dependence of the erosion rate on this variable.  
 188 From the total erosion rate, we compute the entrainment rates of the solid phases, which are then used in the governing  
 189 equations, as:

$$E_{i_s} = \beta_{i_s}(1 - \alpha_d)E_{tot} \quad (15)$$

190 where  $\beta_{i_s}$  are the relative volumetric fractions of the solid particles in the erodible substrate ( $\sum \beta_{i_s} = 1$ ). When erosion  
 191 occurs, not only solid particles are entrained in the flow, but also the water present in the deposit, here assumed to saturate  
 192 its voids. This water entrainment from the erodible substrate is given by:

$$E_w = \alpha_d E_{tot}. \quad (16)$$

193

#### 194 2.1.4 Sedimentation term

195 Sedimentation of particles from the flow is modelled as a volumetric flux at the flow bottom and it is assumed to occur  
 196 at a rate which is proportional to the volumetric fraction of particles in the flow and to the particle settling velocity  $w_s$ :

$$D_{s,i_s} = \alpha_{s,i_s} \cdot w_{s,i_s}(d_{s,i_s}, \rho_{s,i_s}, \nu_m). \quad (17)$$

197 The particle settling velocity  $w_{s,i_s}$  is a function of the particle diameter  $d_{s,i_s}$ , the particle density  $\rho_{s,i_s}$  and the mixture  
 198 kinematic viscosity  $\nu_m = \frac{\mu_m}{\rho_m}$ , and it is obtained by solving the following non-linear equation:

$$w_s^2(d_{s,i_s})C_D(Re) = \frac{4}{3}d_{s,i_s}g\left(\frac{\rho_{s,i_s} - \rho_a}{\rho_a}\right).$$


199 The gas-particle drag coefficient  $C_D$  is a function of the particle Reynolds number ( $Re = \frac{d_{s,i_s}w_s}{\nu_m}$ ), and it is calculated by  
 200 assuming spherical particles (although in the future can be generalized for more realistic shapes; Bagheri and Bonadonna,  
 201 2015; Dioguardi et al., 2016) through the following relations (Gidaspow, 1994):

$$\begin{cases} C_D = \frac{24}{Re}(1 + 0.15Re^{0.687}) & Re \leq 1000, \\ C_D = 0.44 & Re > 1000. \end{cases}$$

202

203 The dependence of the Reynolds number on the mixture kinematic viscosity acts on the settling velocity as a sort of  
 204 hindered settling. In fact, mixture viscosity increases with the total volumetric fraction of solids, and thus the settling  
 205 velocity decreases. This approach is described in Koo (2009), where several effective-medium models are analysed for  
 206 determining settling velocities of particles in a viscous fluid. Effective-medium theories have been developed for

207 predicting the transport properties of suspensions consisting of multiple particles in a fluid. In particular, the sedimentation  
 208 velocity is computed using the effective viscosity of the suspension, instead of the viscosity of the continuous phase.



209  
 210 *Figure 4. Effective settling velocity. Values of the settling velocity are represented by the different contours, as a function*  
 211 *of particle diameter and total solid volume fraction.*

212 When considering the settling of solid particles, it is important to remind that we assume the flow deposit formed because  
 213 of sedimentation being saturated in water, with the volume fraction of water given by  $\alpha_w$ . Thus, the lahar does not loose  
 214 solid particles only because of sedimentation, but water too, with the volumetric deposition rate of water related to that  
 215 of solid particles by the following equation:

$$D_w = \frac{\alpha_d}{1 - \alpha_d} \sum_{i_s=1}^{n_s} D_{s,i_s}. \quad (18)$$

216  
 217 **2.2 Numerical implementation**  
 218

219 The numerical solution of the equations is based on the algorithm developed by de' Michieli Vitturi et al. (2019) for the  
 220 code IMEX-Sflow2D, and in particular on an operator splitting technique, where the advective, gravitational, and friction  
 221 terms governing the fluid-dynamics of the lahar are integrated in one step, while the erosion and deposition terms are  
 222 integrated in a second step. This allows ad-hoc numerical methods to be used for the different physical processes,  
 223 optimizing and simplifying the overall solution process.

224 The numerical integration of the advective, gravitational and frictions terms is based an Implicit-Explicit (IMEX) Runge-  
 225 Kutta scheme, where the conservative fluxes and the gravitational terms are treated explicitly, while the stiff terms of the  
 226 equations, represented by friction, are integrated implicitly. For the explicit spatial discretization of the fluxes, a modified  
 227 version of the finite-volume central-upwind Kurganov and Petrova (2007) scheme has been adopted. The scheme,  
 228 described in de' Michieli Vitturi et al. (2019) and Biagioli et al. (2021), has a second-order accuracy in space and  
 229 guarantees the positivity of the flow thickness. The spatial accuracy is obtained with a discontinuous piecewise bi-linear  
 230 reconstruction of the flow variables, in order to compute their values at the sides of each cell interface and thus the

231 numerical fluxes. The slopes of the linear reconstructions of flow variables in the  $x$ - and  $y$ -direction are constrained by  
232 appropriate geometric limiters, allowing switching between low and high-resolution schemes.  
233 The implicit part of the IMEX Runge-Kutta scheme is solved using a Newton-Raphson method with an optimum step  
234 size control, where the Jacobian of the implicit terms is computed with a complex-step derivative approximation. The use  
235 of an implicit discretization of the stiff friction terms allows for larger time steps, controlled by the CFL condition,  
236 establishing a relationship between time step, flow velocity and cell sizes.  
237 After each Runge-Kutta procedure, the erosion, deposition, and air entrainment term are integrated explicitly and the flow  
238 variables and the topography at the centres of the computational cells are updated.  
239 The numerical scheme is also designed to be well-balanced, i.e. to correctly preserve steady-states. This property is  
240 important for the numerical simulation of lahars, for which the flow should be triggered only when the gravitational force  
241 exceeds the frictional forces, and thus a proper balance of these terms must exist also in the discretized equations resulting  
242 from the numerical schemes.

243

### 244 **3 Model validation and applications**

245

246 In this section we present a few applications of the proposed lahar model aimed at showing its robustness, applicability,  
247 and performance. Concerning the numerical tests aimed at demonstrating the mathematical accuracy for the code  
248 verification, the reader is addressed to de' Michieli Vitturi et al. (2019) where the code IMEX-Sflow2D, on which our  
249 model is based, was presented. Applications of the code to hazard assessment for lahars in the Neapolitan area will be  
250 presented in the companion paper by Sandri et al. ([2023this issue](#)).

251 Firstly, we present the case of a lahar flow on a synthetic topography in order to investigate the triggering conditions.  
252 Secondly, we introduce and describe all the needed variables to perform an application on real topography, that is the  
253 Valle di Avella, one of the Apennine valleys adjacent to Mt. Vesuvius, where in the companion papers by Di Vito et al.  
254 (this issue) and Sandri et al. (this issue) we also performed geological investigations and hazard analysis for lahar. In such  
255 test area we explore the effects that can potentially affect the results, such as computational grid size, numerical scheme  
256 order, water temperature, discretization of the grain size distribution, and erosion and deposition terms. As the two latter  
257 processes are by far the most relevant on the key output variables such as run-distance, flow thickness and speed, in the  
258 last subsection we use field observations to calibrate erosion and deposition terms.

259

#### 260 **3.1 Simulations on a synthetic topography: lahar trigger conditions**

261

262 The first set of simulations we present is aimed at testing the capability of the numerical code to properly reproduce the  
263 triggering conditions of a lahar, in terms of the relationship between initial thickness, solid fraction and slope. As  
264 previously stated, the values of the friction parameters controlling the yield strength define a unique relationship between  
265 thickness, slope and solid fraction resulting in a threshold for the mobility of the flow (see Fig. 2).

266 For the tests we consider a high- and low-angle slope (5 and 40 degrees respectively) and two values of the initial thickness  
267 (1 and 2 meters) with different values of the solid fraction (30% and 40%).

268 The topography has a constant slope for  $x < 0$  m and is flat for  $x > 0$  m. In the left region of the domain, from  $x = -55$  m to  
269  $x = -50$  m, the topography is excavated with a constant depth (1 or 2 meters). Then, from  $x = -50$  m, this region is connected  
270 to the original topography with a quadratic function, in order to have a smooth transition and a horizontal slope at the  
271 right end. The excavated volume is then filled with the liquid/solid mixture. In this way the free surface elevation of the

272 initial volume corresponds to the original topography elevation. The topography and the free surface are shown in the  
273 panels of Fig. 5 with cyan and orange solid lines, respectively.

274 For this suite of tests, both erosion and sedimentation are neglected, in order to have a constant solid volume fraction  
275 during the simulations and thus a better understanding of its effect on flow mobility. For all the simulations done, we  
276 present in Fig. 5 the solutions in terms of the free surface of the flow at  $t=100$  s, corresponding to a steady state. In panel  
277 (a) the final solution obtained for a slope of 7 degrees, an initial thickness of 1 m and a solid volume percentage of 40%  
278 is shown. By looking at the diagram presented in Fig. 3, we can see that the black marker for this combination of slope  
279 and thickness lies below the critical curve for 40% solid (purple line), thus the gravitational forces are smaller than the  
280 yield strength and the initial volume should not move. Indeed, this is what happens in panel (a), even if a careful analysis  
281 shows that on the left part of the volume there is a small change in the final free surface with respect to the initial constant  
282 slope. This is an effect of the grid discretization, which results in a large slope for a very small area, over which the flow  
283 is mobilized.

284 Panel (c) shows the final solution for the same condition as panel (a), except the initial thickness increased to 2 m. For  
285 this thickness, and for a slope of 7 degrees, the marker in Fig. 3 is above the critical curve for 40% solid (purple line), and  
286 thus the yield strength of the initial volume does not exceed the gravitational force. The liquid/solid mixture in this case  
287 is mobilized with a small runout of a few meters at  $t=100$  s. Both the flow thickness and the free surface slope decrease,  
288 leading to a new steady condition reached when the flow momentum is dissipated by the friction forces.


289 Flow mobility increases also by decreasing the solid fraction. This is shown in panel (e), representing the final solution  
290 for the same condition as panel (a), except for the solid volume percentage, lowered from 40% to 30%. By looking at the  
291 diagram presented in Fig. 3, we can see that for this combination of slope and thickness the black marker lies well above  
292 the critical curve for 30% solid volume (yellow line). In fact, the mixture moves along the slope and is able to reach the  
293 topography break in slope, where most of the initial volume has reached a stable condition at  $t=100$  s. We observe that a  
294 small portion of the flow is left at the base of the excavated area.

295 In the right panels of Fig. 5, a similar analysis is presented for a slope of 40 degrees. The first two simulations we present  
296 are done with 50% solid volume (Fig. 3, green line), and initial thickness slightly below (1 m) and above (2 m) the critical  
297 thickness for flow mobility. These initial conditions are represented by the right markers in Fig. 3. Fig. 5 (b) shows that,  
298 as expected, with an initial thickness of 1 m the flow does not move and at  $t=100$  s the free surface has not changed with  
299 respect to the initial condition, represented by the free surface parallel to the unmodified topography. When the initial  
300 thickness is increased to 2 m (Fig. 5d), the flow starts to move with a final runout of a few meters only at  $t=100$  s, because  
301 of the high yield strength associated with the large solid fraction. An initial thickness of 1 m, associated with a 30% solid  
302 volume, results in a flow capable of moving along the 40 degrees slope leaving no deposit behind it, as shown in Fig. 5  
303 panel (f). In fact, in this case, almost the whole initial volume reaches the flat part of the topography, with a long runout  
304 and a thin deposit due to the speed gained by the flow on the high-slope region.

305

306

307



309

310

Figure 5. Flow free surface (red line) and topography (blue line) for 6 simulations with different initial solid volume and thickness and different slope.

311

312

313

### 3.2 Application to real topography: variables definition

314

315

316

317

318

319

320

321

322

323

As an application of the model, we consider a syn-eruptive lahar from a medium-sized eruption at Somma-Vesuvius, that is characterized by a total erupted mass between  $10^{11}$  and  $10^{12}$  kg (Macedonio et al., 2016; Sandri et al., 2016). To this aim, as test case, we selected a synthetic deposit taken from one of the tephra fallout simulations made using the code Hazmap (Macedonio et al., 2005) presented by Sandri et al. (2016); we considered a lahar generated by heavy rainfall and we modelled the dynamics of the lahar in the Valle di Avella. In Sandri et al. (2016) a large number of tephra fallout simulations were performed for a Probabilistic Volcanic Hazard Analysis by varying the wind field and the size and intensity of the eruption. Among those, we selected a simulation that produced a substantial deposit (of the order of a few decimetres) on the Apennine flanks facing the Valle di Avella. The Eruption Source Parameters associated to this simulation are an eruptive-column height equal to 10.9 km, a mass eruption rate equal to  $2.89 \times 10^6$  kg/s, a duration of the

324 fallout phase of 10 hours and total erupted mass as tephra fallout equal to  $1.04 \times 10^{11}$  kg. The wind conditions are those  
325 reported in the ERA5 reanalysis database for 14 December 2001.

326 For a correct modelling of the areas invaded by lahars it is necessary to use a digital terrain model (DEM) as accurate as  
327 possible, such as that described in the companion paper by Sandri et al. ([this issue 2023](#)) which is used for this application.  
328 For real life applications, a critical element in the definition of the initial conditions of a syn-eruptive lahar is the proper  
329 identification of the areas of the topography where a lahar can be triggered, and the lahar's initial volume.  
330 As regards the former, as already seen, the terrain slope is a key factor. On the basis of empirical observations, we assume  
331 that lahars cannot be generated if the slope is: (i) less than a minimum threshold angle for remobilization ( $\theta_{min}$ ), or (ii)  
332 greater than an upper threshold angle ( $\theta_{max}$ ), which prevents the accumulation, during the deposit phase of fallout  
333 material, and which therefore cannot be remobilized by rainfall later to generate a lahar. The slope angle  $\theta_{max}$  is fixed  
334 here at 40 degrees (Bisson et al. 2014). As explained in the companion paper by Sandri et al. ([this issue 2023](#)), the value  
335 of the lower threshold depends on the local granulometry and other factors that are necessary to be considered for a hazard  
336 quantification in order to consider the uncertainty associated with this parameter. For this application we fixed  $\theta_{min} =$   
337  $30^\circ$ . Thus, on our computational grid we consider as possible source of the lahar only the cells with a slope between  $30^\circ$   
338 and  $40^\circ$ .

339 As regards the initial lahar volume, this is a consequence of the initial remobilization thickness  $h_{tot}$  (see Figure 6 for a  
340 graphical representation of the variables related to thicknesses and porosity) and of the area of remobilization. In turn,  
341  $h_{tot}$  mostly depend on two parameters:

- 342 • the thickness of available compacted deposit,  $h_s$  (i.e., devoid of the water filling its pore); in this application the  
343 fallout deposit thickness is given by the ground tephra load provided by the Hazmap simulation, and selected  
344 from Sandri et al. (2016);
- 345 • the amount of available water, denoted by  $h_r$ . Analysing the time series of rainfall at the OVO station located at  
346 the historical site of the Vesuvian Observatory since 1940 and the data shown by Fiorillo and Wilson (2004), the  
347 maximum rainfall was of the order of few tens of cm (the maximum recorded was 50 cm fallen in 48 hours near  
348 Salerno on 26-10-1954). For this application we set the thickness of rainwater available to mobilize the water-  
349 saturated deposit to  $h_r = 0.5$  m, i.e., equal to the maximum recorded value. We stress that this is a conservative  
350 choice, since lahars can also originate with less rainwater available, but in such cases their initial thickness (and  
351 thus, volume) will be smaller. However, we also acknowledge that we are not accounting for the expected  
352 increases in the maximum rainfall in a few hours, due to global warming, that are becoming more and more  
353 frequent during the current decade (Esposito et al., 2018, Vallebona et al., 2015).


354  
355 Let us call  $h_w$  the thickness of the water layer that we could extract from the water-saturated deposit; then  $h_w$  and  $h_s$  can  
356 be respectively expressed as a fraction of the thickness of the water-saturated deposit,  $h_d$ , which has a porosity  $\alpha_d$ , as:

$$h_w = h_d \alpha_d \quad (19)$$

357  
358 and

$$h_s = h_d (1 - \alpha_d) \quad (20)$$

359  
360  
361



363 *Figure 6. Definition of the variables used to define the initial thickness mobilizable  $h_{tot}$ . (a) The water-saturated deposit*  
 364 *of thickness  $h_d$ , with porosity  $\alpha_d$ , and the layer of rain water available of maximum thickness  $h_r = 50$  cm (assumed). (b)*  
 365 *same as in (a) but if we imagine to extract all the pore-filling water and separate it into a layer of water of thickness  $h_w$ ,  
 366 *and a layer of compacted deposit of thickness  $h_s$ , which is the tephra fallout deposit simulated by Hazmap simulator, in*  
 367 *this study. (c) the thickness of the mobilizable layers of deposit  $\bar{h}_s$ , rain water  $\bar{h}_r$  and pore-filling water  $\bar{h}_w$  depends on*  
 368 *the availability of rain and deposit and the fixed solid fraction  $\alpha_s$  of the initial flow.**

369  
 370  
 371 The initial flow thickness that is remobilized,  $h_{tot}$ , will be the sum of three thicknesses:

- 372 •  $\bar{h}_s \leq h_s$  from the solid part of the deposit,
- 373 •  $\bar{h}_w \leq h_w$ , from the water already filling the pores, and
- 374 •  $\bar{h}_r \leq h_r$ , from the rain (as said above, we assume  $h_r = 0.5$  m).

375  
 376 There are relations linking these three addends. In particular, due to the condition of water saturation in the deposit

377

$$\alpha_d = \frac{\bar{h}_w}{\bar{h}_s + \bar{h}_w}, \quad (21)$$

378  
 379 so that

380

$$\bar{h}_w = \frac{\alpha_d}{(1 - \alpha_d)} \bar{h}_s. \quad (22)$$

381  
 382 Moreover, in the initial flow volume there is a relationship between water and solid content, in terms of initial  
 383 volumetric fraction  $\alpha_s$ :

384

$$\alpha_s = \frac{\bar{h}_s}{\bar{h}_s + \bar{h}_w + \bar{h}_r}, \quad (23)$$

385  
386 so that (combining equation 22)  
387

$$\bar{h}_r = \frac{(1 - \alpha_s)}{\alpha_s} \bar{h}_s - \frac{\alpha_d}{(1 - \alpha_d)} \bar{h}_s = \frac{1 - \alpha_d - \alpha_s}{\alpha_s(1 - \alpha_d)} \bar{h}_s \quad (24)$$

388  
389 We see from equations 22 and 24 that both  $\bar{h}_w$  and  $\bar{h}_r$  are linear functions of  $\bar{h}_s$ . Considering the initial availability of  
390 remobilizable deposits, we can state that  
391

$$\bar{h}_w + \bar{h}_s \leq h_d \quad (25)$$

392  
393 or, using equation 22,  
394

$$\bar{h}_s \leq (1 - \alpha_d)h_d \quad (26)$$

395  
396 Considering, on the other hand, the available water from rain, we have

$$\bar{h}_r \leq h_r \quad (27)$$

397  
398 or, using equation 24,  
399

$$\bar{h}_s \leq \frac{(1 - \alpha_d)\alpha_s}{(1 - \alpha_d) - \alpha_s} h_r \quad (28)$$

400  
401 The maximum solid thickness  $\bar{h}_s$  that can be remobilized, considering the availability of water-saturated deposits and  
402 rain, and the a priori sampled initial solid fraction  $\alpha_s$ , is then the maximum satisfying both conditions in equations 26  
403 and 28, i.e.:  
404


$$\bar{h}_s \leq \min \left\{ \frac{(1 - \alpha_d)\alpha_s}{(1 - \alpha_d) - \alpha_s} h_r; (1 - \alpha_d)h_d \right\} \quad (29)$$


405  
406 Once this is known, we can get the total initial thickness of the lahar, by simply computing it as

$$h_{tot} = \frac{\bar{h}_s}{\alpha_s} \quad (30)$$

407  
408 The ashfall deposit which does not contribute to the initial volume of the lahar is added to the pre-existing topography as  
409 an erodible layer. The contribution of the ash fall deposits in the intermediate and distal areas has been significant in the  
410 past sub-plinian eruptions, as shown in the paper by Di Vito et al. (this issue).  
411 The steps described above are represented in Figure 7 for the real-topography test application to Valle di Avella, from the  
412 identification of areas “prone” to remobilization on the basis of geomorphological features, the terrain slope (top panel,

413 red pixels), to the application of the criterion in equation 29 and 30 to compute the initial thickness of lahar (bottom panel)  
414 from the rainwater available and the ashfall deposit (top panel, contour lines). For the case presented in Figure 7 we  
415 assumed a deposit porosity  $\alpha_d = 0.22$  and an initial solid fraction in the lahar  $\alpha_s = 0.29$ . With these values, equations  
416 29 and 30 give, for an ashfall deposit thickness of 0.4m and an amount of rain of 0.5m, an initial lahar thickness of  
417 approximately 0.8m.  
418 Concerning the grain size distribution of the remobilized deposits here we used that obtained by Di Vito et al. (this issue)  
419 on the basis of field data analysis.





420

421 *Figure 7. Steps for the definition of the initial lahar thickness. The top panel shows grid cells with slope between  $\theta_{min}$*   
 422 *and  $\theta_{max}$  (red pixels) and the HAZMAP deposit thickness (contour lines). The bottom panel shows the initial lahar*  
 423 *thickness.*

### 424 3.3 Application to real topography: sensitivity tests and description of the relevant output variables

425


426 We conduct a series of sensitivity tests on the real-topography test area, in order to quantify the relevance of different  
 427 terms and processes on the output of the simulations, in terms of flow thickness and/or area.

428 We first present a reference simulation, extracted from the ensemble of simulations presented in Sandri et al. (this issue),  
 429 and for this case we show the temporal evolution of the flow and the most relevant output produced by the model. Then,  
 430 with respect to this simulation, we vary several parameters to show the sensitivity of the results to several model  
 431 parameters.

432

#### 433 3.3.1 Flow evolution and relevant output

434 In this section we describe a reference simulation, obtained for a computational grid with cells of 50m and a second-order  
 435 numerical scheme in space, by applying a van Leer slope limiter to the reconstruction of the flow variable. For this  
 436 simulation, the total grain size distribution is discretized with 6 bins, from  $\phi = -3$  to  $\phi = -7$ , and we assume an initial  
 437 temperature of the lahar of 373K. While we recognize that this temperature is more adequate for syn-eruptive lahars from  
 438 pyroclastic density current deposits, here we used this value to better show the effect of the temperature on the lahar  
 439 dynamics. In fact, later in the paper, we compare the results with those obtained with a colder lahar (300K).



441

442 *Figure 8. Lahar thickness temporal evolution: top-left at(a) 3600s; top-right at(b) 7200s; bottom-left(c) at 43200s;*  
 443 *bottom-right(d) at 86400s.*

444

445

446

447

448

449


450

451

452


The initial thickness of the lahar is shown in the bottom panel of Figure 7, and its temporal evolution is presented in the four panels of Figure 8. After one hour from the mobilization (Figure 78a, top-left panel) the lahar already invaded a large portion of the Valle di Avella, with its maximum thickness reaching a few meters in its southern part, and a thickness of few millimetres still moving on the flanks of the Apennines facing the valley. At this time, After 1 hour of flow time, the lahar has already reached the localities of Avella, Roccarainola and Camposano, which all are inside the case-study valley, while after 2 hours the lahar has reached the city of Nola, just outside the valley. After 12 hours of flow time, the lahar has already reached the localities of Marigliano and Cancellò Scalo, the first being in the more open plain, while the second nearby the NWW Apennine sector of the valley. After 24 hours of flow time, the lahar has already reached the city of Acerra in the open plain. Although this simulation is not aimed at reproducing a particular

453 event from the past, but at showing the model's ability to describe the different phenomena that may characterize a future  
 454 lahar in the Avella Valley, it is interesting to note that these reaches are corroborated by some historical sources on the  
 455 "1631" events, for which it is reported that the localities of Marigliano and Nola were reached by those lahars and by  
 456 geological pieces of evidences reported in Di Vito et al. (this issue).




457  
 458 *Figure 9. Area of the lahar versus time for the reference simulation. For the computation of the area two thresholds on*  
 459 *thickness have been applied: a physical one (solid blue line,  $h \geq 10^{-3}$  m), and a numerical one (dashed red line,  $h \geq$*   
 460  *$10^{-5}$  m). The inset represents a detail of the first hour of simulation.*

461 The area invaded by the lahar changes with time and its evolution is presented in Figure 9. The model computes at each  
 462 time step the invaded area as the sum of the areas of the grid cells where flow thickness is greater than a fixed threshold.  
 463 For this analysis, two thresholds on the minimum flow thickness have been applied, a “physical” threshold set to  $10^{-3}$  m  
 464 (represented in Figure 8-9 by the solid blue line), which allows to analyse the dynamics of the bulk of the lahar, and a  
 465 “numerical” threshold set to  $10^{-5}$  m (represented by the dashed red line). It is important to remark that such a small  
 466 threshold does not correspond to a thickness for which the flow is properly described by our model equations, because  
 467 for such values forces like surface tension becomes larger than gravity and friction (Hong et al., 2016). In any case, this  
 468 small threshold can provide information on the dynamics of the very thin tail of the lahar, where the velocity goes rapidly  
 469 to zero because of friction forces. Figure 9 shows that, for the larger physical threshold, at the beginning of the simulation  
 470 (first 15 minutes) there is a rapid decrease in the area, due the channelization phase of the flow mobilized from the flanks  
 471 of the Apennines. After this initial phase, the flow reaches the Valle di Avella and starts to spread out, with the area of  
 472 the lahar increasing with time. For the lower thickness threshold, we observe that the area rapidly increases during the  
 473 initial slumping phase of the lahar and it reaches its maximum after approximately 1 hour after the mobilization. Then it  
 474 decreases, first rapidly and then more slowly, increasing again after 15 hours. This is due to the fact that tail of the flow  
 475 gets thinner with time and, as previously described, the presence of the yield strength term in the friction allows the flow  
 476 to stop with a thickness that depends on the slope of the topography and on the fraction of solid material left in the flow.  
 477 Thus, when the thickness is small enough, the tail of the lahar slows down and stops moving. Because of that, erosion  
 478 becomes negligible and at the same time deposition occurs, further increasing the thinning of the deposit and the loss of  
 479 sediments and water by the flow. This is well shown by the evolution of flow thickness on the flanks of the Apennines,  
 480 as illustrated in Figure 8. After one hour from the mobilization, thickness is less than 1 millimetre and, for the slope of  
 481 the Apennines and the water content of the flow, this value is well below the critical thickness (see Figure 3). Because of  
 482 that, the flow stops to move and the only process occurring is the loss of water and sediments.




485 *Figure 10. Total deposition (left) and erosion (right) after 24 hours of simulation.*

486 The mobility of the flow is mostly controlled by the solid fraction within the lahar, and this fraction can change because  
 487 of erosion and deposition. Thus, the total erosion and deposition are important factors controlling the area invaded by the  
 488 lahar. The final deposit and erosion thickness are presented in the left and right panels of Figure 10, respectively, showing  
 489 a significant erosion where the flow is channelized, reaching a maximum value of a few decimetres. Conversely,  
 490 deposition mostly occurs in the flat areas invaded by the lahar where the flow slows down, producing a maximum deposit  
 491 thickness of the order of 1m.




492  
 493 *Figure 11. Total deposit thickness after 24 hours of simulation for the 6 different classes of particles: (a)  $\phi = -3$ ; (b)*  
 494  *$\phi = -1$ ; (c)  $\phi = 1$ ; (d)  $\phi = 3$ ; (e)  $\phi = 5$ ; (f)  $\phi = 7$ . The insets in each panel show the initial total grain size*  
 495 *distribution of the lahar, and the class for which the deposit is shown in the panel is represented in orange.*

496  
 497 As shown by equation 17, deposition is proportional to the settling velocity of the sediments, which increases with their  
 498 sizes. This reflects in different depositional patterns for the different classes of particles, shown in the panels of Figure  
 499 11. We observe that the thickness of the deposit for the different classes does not depends only on the settling velocities,  
 500 but also on the amount of sediments available for deposition, and thus on the initial grain size distribution of the lahar.  
 501 This explains why the larger contribution to the deposit is given by class  $\phi = 5$ , for which the maximum thickness deposit  
 502 24 hours after the mobilization of the lahar is about 1 m. For classes  $\phi = -3$  and  $\phi = -1$  the initial mass fractions are  
 503 similar, and the difference in the final deposit is mostly due to the differences in settling velocities. In fact, Figure 4 shows  
 504 that, for the same total solid volume fraction of the lahar, a difference in size in the Krumbein scale of  $2\phi$  results in a  
 505 difference in the settling velocity, and thus in the deposition rate, of one order of magnitude.  
 506



507  
508 *Figure 12. Maximum thickness of the flow in each cell of the computational grid during the 24 hours of simulation.*

509 From the perspective of hazard assessment, it is not important the flow thickness at the end of the simulation (here 24  
510 hours after the mobilization), but the maximum thickness registered at each location reached by the lahar in the same time  
511 span, as shown in [figure Figure 12](#). This figure shows that the maximum thickness can exceed several meters over a large  
512 area of the domain, allowing to identify the areas where the hazard is significant. Flow thickness may also be combined  
513 with dynamic pressure in order to assess, for different couples of thickness and dynamic pressure thresholds, the areas  
514 where these thresholds are exceeded simultaneously. Figure 13 shows, for two different thickness thresholds, the values  
515 of dynamic pressure exceeded during 24 hours of simulation. For example, in Figure 13b, the light green pixels represent  
516 the area where at some time the lahar produced, simultaneously, a thickness of at least 2 m and a dynamic pressure larger  
517 than 2000 Pa and smaller than 5000 Pa.




519  
520 *Figure 13. Maps of exceedance of flow thickness and dynamic pressure: (a) thickness threshold 0.5 m; (b) thickness*  
521 *threshold 2 m. The colors represent the dynamic pressure thresholds exceeded during the 24 hours of simulation*  
522 *simultaneously with the thickness threshold.*

### 523 3.3.2 Effects of grid size and numerical scheme order

524 In this section we want to present the effects of the resolution of the computational grid and of the spatial numerical  
525 scheme adopted (first and second order schemes). We remind that the DEM resolution used for the simulations is 10 m,  
526 while the computational grid resolution used for the reference simulation presented in the previous section was 50m.  
527 Thus, the smaller topographical features present in the original DEM are smoothed in the computational grid, possibly

528 with an effect on the dynamics of the simulated flow. Here, we focus our interest to the first 2 hours of the simulation,  
 529 thus the phase where the details of the topography can be more important, because of the important canalization effects  
 530 acting on the lahar when moving down the flanks of the Apennines into the Valle di Avella. All the simulations for this  
 531 analysis have been performed on 16 cores of a Multicore shared memory server SuperMicro 4×16-core AMD 2.3 GHz.  
 532



533  
 534 *Figure 143. Maps of flow thickness at  $t=7200s$  for simulations with different grids or different numerical schemes: (a)*  
 535 *50m grid resolution and 2nd order scheme with geometric limiter; (b) 100m grid resolution and 2nd order scheme with*  
 536 *geometric limiter; (c) 25m grid resolution and 2nd order scheme with geometric limiter; (d) 50m grid resolution and*  
 537 *1st order scheme (no geometric limits used).*

538  
 539 In Figure 143 we compare the flow thickness of the reference simulation (~~top-left~~Figure 14a) with: a simulation obtained  
 540 with a 100m resolution computational grid (~~top-right~~Figure 14b); a simulation obtained with a 25m resolution


541 computational grid (~~bottom-left~~Figure 14c); a simulation with a 50m resolution computational grid but with a first-order  
542 spatial scheme (~~bottom-right~~Figure 14d). While there is a remarkable difference in the area invaded by the flow between  
543 the reference 50m simulation and the 100m simulation, the difference between the reference simulation and the 25m one,  
544 in particular for significant flow thicknesses, is very small. We also have to account that theoretically the computational  
545 time required for a simulation, when the grid cell size is decreased by a factor 2, increases by a factor  $2^3$ . In fact, the  
546 number of horizontal cells increases by a factor  $2^2$ , being the simulation two-dimensional, and the time step decreases by  
547 a factor 2, due to the well-known linear relationship between spatial and temporal step associated with the use of an  
548 explicit integration scheme (CFL condition, Courant et al. 1928). In addition to this, the CPU time required for the  
549 initialization of the arrays and for the input/output procedures must be accounted. For this particular case, the 100m, 50m  
550 and 25m resolution simulations required 1023s, 6916s, and 50289s, respectively. This suggests that, with the DEM we  
551 used, a 50m resolution is adequate for a proper description of the flow dynamics, also in view of the utilization of the  
552 simulations for hazard studies, where a large number of runs is required and the computational time is an important  
553 constraint.

554 Finally, in the bottom-right panel of Figure 143, we can see the output of a simulation with the same resolution of the  
555 reference one (50 m), but without the use of geometric limiters for the linear reconstruction of flow variables at the  
556 interfaces of the computational cells. This makes the discretization scheme of first order, with respect to the second order  
557 obtained for the reference simulation. The difference in the results is striking, with the first order simulation being more  
558 similar to the simulation obtained with the 100m grid, and the second order simulation being similar to that obtained with  
559 the 25m grid. The computational overhead associated with the use of geometrical limiters is small (6916 seconds vs 6770  
560 seconds), thus their use is strongly suggested for this kind of simulations.

561

### 562 3.3.3 Effects of grain size discretization

563 In this section we present the sensitivity of model results to the discretization of grain size distribution. With respect to  
564 the reference simulation, where 6 classes were used, here we compare the solution after 4 hours from the mobilization of  
565 the lahar with those at the same time for two simulations with the total grain size distribution described by 3 and 12  
566 particle size classes, respectively. The results of this analysis are presented in Figure 154, with the final flow thickness  
567 presented on the left panels and the deposit thickness on the right panels. The plots show small differences between the  
568 simulations with 3 (Figure 154 a-b) and 6 classes (Figure 154 c-d), which become almost negligible when comparing  
569 the simulations with 6 and 12 classes (Figure 14 e-f). For this test case, the increase in the number of classes, from 6 to  
570 12, resulted in an increase of the computational time of a factor 1.3. Thus, the choice of using 6 classes for the reference  
571 simulations represents a good compromise between accuracy and efficiency.



572

573

574

Figure 154. Maps of flow thickness (left) and deposit thickness (right) at  $t=14400s$  for simulations with different discretization of the total grain size distribution: (a-b) 3 classes; (c-d) 6 classes; (e-f) 12 classes.

575

576

577


### 3.3.4 Effect of initial temperature

578

In this section we present a comparison between the output of the reference simulation ( $T=373K$ ) and a simulation with a lower initial temperature ( $T=300K$ ).

579


580



581

582 *Figure 165. Area of the lahar versus time for the simulations with different initial temperatures: 300K (blue line) and*  
 583 *373K (red line). The area is computed as the sum of the areas of the grid cells where flow thickness is greater than*  
 584  *$10^{-3}m$ .*

585 Figure 165 shows the invaded area (computed the area as the sum of the areas of the grid cells where flow thickness is  
 586 greater than or equal  $10^{-3}m$ ) versus time for the two simulations, where the result for the reference simulation is presented  
 587 with a red line, while the result for the colder case is plotted with a blue line. We remark that here we are not plotting the  
 588 area of the deposit of the lahar, but the area where the lahar is still moving, in order to better understand how flow viscosity  
 589 affects the dynamics of the flow. In the initial phase ( $<60s$ ), the difference between the two cases is negligible, while it  
 590 becomes more significant with time, with the area of the colder flow exceeding that of the reference one. This can seem  
 591 counterintuitive, because we expect an increased mobility for the hotter flow due to the lower viscosity, and thus a larger  
 592 runout. But the initial phase is dominated by flow channelization, which is increased by the larger mobility, and which  
 593 results in a smaller footprint of the lahar. The different viscosity of the flow also affects the tail of the flow in a twofold  
 594 way. Indeed, the lower viscosity results in a larger settling the velocity of the sediments and a debulking which further  
 595 increases the flow mobility. This is evident by looking at the reduced footprint of the flow left on the Apennines flanks  
 596 in the simulation with the higher initial temperature (Figure 142a) with respect to the simulation with the lower initial  
 597 temperature (Figure 17).



598

599

Figure 176. Maps of flow thickness at  $t=7200s$  for a simulation with an initial temperature  $T=300K$ .

600

### 601 3.3.5 Effects of erosion and deposition

602

As shown in the previous comparison, viscosity of the flow has an effect on the debulking process, which in turn can affect the lahar propagation. Here we focus our attention on the effects of the main processes controlling lahar bulking and debulking, i.e. the deposition and erosion processes.

603

604

This is done by comparing in Figure 187 the first 2 hours of the reference simulation (Figure 18a) with 3 additional test cases: a simulation without erosion (top-right Figure 18b); a simulation without deposition (bottom-left Figure 18c); a simulation without erosion and deposition (bottom-right Figure 18d).

605

606

By comparing the flow thickness and the area covered by the flow of the reference simulation and that without erosion, we can see the twofold effect of the bulking associated with erosion. On one hand we observe the larger flow thickness; on the other hand, we observe a smaller runout, due to the lower mobility associated with a higher solid volume fraction. This is particularly true in the Valle di Avella, where the front of the flow advanced about 2km more for the simulation without erosion.

607

608


609


610

611

612

613





614

615

616

617

*Figure 187. Maps of flow thickness at  $t=7200s$  for simulations with and without erosion and deposition: (a) reference simulation with erosion and deposition; (b) simulation with deposition and without erosion; (c) simulation with erosion and without deposition; (d) simulation without erosion and deposition.*

618

#### 4 Conclusions

619

620

A new shallow layer model for describing lahar transport was presented. The proposed model does not describe all the general aspects of lahar behaviour (see Pudasaini, 2012) but contains the essential physics needed to reproduce the general features of lahars observed in nature, crucial for assessing their hazard.

621

In particular the model considers realistic particle size distribution, surface erosion and deposition processes through semi-empirical parameterizations calibrated from field data.

622

The model was developed with the aim to describe lahar propagation and deposits and assess their hazard in contexts similar to that of the Vesuvius area, which is highly populated and prone to this kind of phenomenon after heavy rains (e.g., Fiorillo and Wilson, 2004).

623

The critical variables were identified and several sensitivity tests carried out, using synthetic and real cases topographies. The variables used in order to define the source are the initial mobilizable thickness, the water-saturated deposit thickness, the layer of rain water, and the thickness of compacted deposit, which is related to the others through the substrate porosity.

624

The steps used for the assessment of the initial lahar thickness were presented for the real-topography test application to Valle di Avella.

625

626

627

628

629

630

634 The comparison of simulations obtained for different numerical grids (from 25 m to 100 m), scheme order, and grain size  
635 discretization were useful to find a good compromise between resolution and computational speed. The used DEM was  
636 however at a resolution (10 m) finer than that of the computational grid.

637 The friction term is defined as the sum of a velocity-independent yield slope, a viscous slope, and turbulent slope (O'Brien  
638 et al., 1993). The yield strength and the fluid viscosity are considered functions of the total solid volumetric fraction in a  
639 consistent way. The values of the three terms strongly depends on volumetric solid fraction, on flow thickness, and  
640 velocity. They can vary in a non-linear way by several orders of magnitude when thickness, velocity and solid fraction  
641 vary in ranges typical for lahars. This can produce a stiff term in the system of equations, and, for this reason, it is needed  
642 a robust solver that allows the coupling between the gravitational and frictional terms to be accurately simulated.

643 Energy transport and temperature effects were also explored in order to better understand how flow viscosity affects the  
644 dynamics of the flow. When the friction is dominated by the yield slope term, the difference between the high and low  
645 temperature cases is negligible, while it becomes more significant with time, with the area of the colder flow exceeding  
646 that of the cold one. In fact, the lower viscosity in the case of the hot flow, beside an increased mobility, results also in a  
647 larger settling the velocity of the sediments and a debulking which further increases the flow mobility, producing a  
648 reduced footprint deposit area of the flow.

649 Effects of erosion and deposition were investigated by comparing thea simulations i) without erosion, ii) without  
650 deposition, iii) without erosion and deposition, and iv) with erosion and deposition. By comparing flow thickness and  
651 area covered by the flow, we can see the twofold effect of the bulking associated with erosion, that consists in larger flow  
652 thicknesses and smaller runouts, due to the lower mobility associated with higher solid volume fractions.

653 The companion paper by Sandri et al. (this issue) will show an application of the presented model for hazard analysis of  
654 lahars from Vesuvius deposits in the Neapolitan area, where a wide range of initial conditions are investigated to produce  
655 probabilistic hazard maps. To reach this goal, the companion paper considers eleven hydraulic catchments threatening  
656 the Campanian Plain, and in each catchment a large number of simulations accounts for the variability in the initial lahar  
657 volume, initial water fraction and initial mass load of the ashfall deposit. The database of simulations considered in the  
658 analysis by Sandri et al. (this issue) would allow one also to consider alternative realizations of the 1631 events, permitting  
659 for a counterfactual analysis that can be very insightful for lahar risk analysis (Aspinall and Woo, 2019), and it will be  
660 the focus of future research.

661

#### 662 **Author Contribution**

663 MdMV, AC and LS defined the set of governing equations of the model. MdMV, LS, AC, MDV and DD defined the  
664 equations for the initial conditions. MdMV developed the code. MdMV, LS, AC, MDV and DD defined the set of  
665 simulations and MdMV performed them. MdMV prepared the manuscript with contributions from all co-authors.

666

#### 667 **Competing interests**

668 The authors declare that they have no conflict of interest.

669

#### 670 **Acknowledgments**

671 This work has been produced within the 2012–2021 agreement between Istituto Nazionale di Geofisica e Vulcanologia  
672 (INGV) and the Italian Presidenza del Consiglio dei Ministri, Dipartimento della Protezione Civile (DPC), Convenzione  
673 B2. We ~~also~~ thank Marina Bisson and Roberto Gianardi for providing the DEM used for the simulations. We are grateful

674 [for the constructive feedback provided by an anonymous reviewer and by Dr. Gordon Woo, whose valuable comments](#)  
675 [and suggestions greatly contributed to the improvement of this manuscript.](#)

676

677 **References**

678

679 Aspinall, W.P., Charbonnier, S.J., Connor, C.B., Connor, L., Costa, A., Courtland, L.M., Delgado Granados, H., Godoy,  
680 A., Hibino, K., Hill, B.E. and Komorowski, J.C.: Volcanic hazard assessments for nuclear installations: methods and  
681 examples in site evaluation, IAEA-TECDOC-1795, IAEA, 2016.

682

683 [Aspinall, W., and Woo, G.: Counterfactual analysis of runaway volcanic explosions. \*Frontiers in Earth Science\*, 7, 222,](#)  
684 <https://doi.org/10.3389/feart.2019.00222>, 2019.

685

686 Bagheri, G.H., Bonadonna, C., Manzella, I. and Vonlanthen, P.: On the characterization of size and shape of irregular  
687 particles, *Powder Technology*, 270, 141-153, <https://doi.org/10.1016/j.powtec.2014.10.015>, 2015.

688

689 Biagioli, E., de' Michieli Vitturi, M., and Di Benedetto, F.: Modified shallow water model for viscous fluids and positivity  
690 preserving numerical approximation, *Applied Mathematical Modelling*, 94, 482-505,  
691 <https://doi.org/10.1016/j.apm.2020.12.036>, 2021.

692

693 [Bisson, M., Spinetti, C., & Sulpizio, R.: Volcaniclastic flow hazard zonation in the Sub-Apennine Vesuvian area using](#)  
694 [GIS and remote sensing. \*Geosphere\*, 10\(6\), 1419-1431, <https://doi.org/10.1130/GES01041.1>, 2014.](#)

695

696 Costa, J.E.: Rheologic, geomorphic and sedimentologic differentiation of water floods, hyperconcentrated flows and  
697 debris flows, in: *Flood geomorphology*, edited by Baker, V.R., Kochel, R.C. and Patton, P.C., Wiley-Interscience, 113-  
698 122, 1988.

699

700 Courant, R., Friedrichs, K. & Lewy, H.: On the Partial Difference Equations of Mathematical Physics, *Math. Ann.*, 100 ,  
701 32-74, <https://doi.org/10.1007/BF01448839>, 1928.

702

703 Crittenden, J.C., Trussell, R.R., Hand, D.W., Howe, K.J. and Tchobanoglous, G.: *MWH's water treatment: principles and*  
704 *design*, John Wiley & Sons, <https://doi.org/10.1002/9781118131473>, 2012.

705

706 Dartevelle, S.: Numerical modeling of geophysical granular flows: 1. A comprehensive approach to granular rheologies  
707 and geophysical multiphase flows, *Geochemistry, Geophysics, Geosystems*, 5(8), Q08003,  
708 <https://doi.org/10.1029/2003GC000636>, 2004.

709

710 de' Michieli Vitturi, M., Esposti Ongaro, T., Lari, G. and Aravena, A.: IMEX\_SfloW2D 1.0: a depth-averaged numerical  
711 flow model for pyroclastic avalanches, *Geoscientific Model Development*, 12.1, 581-595, [https://doi.org/10.5194/gmd-](https://doi.org/10.5194/gmd-12-581-2019)  
712 [12-581-2019](https://doi.org/10.5194/gmd-12-581-2019), 2019.

713

714 Dioguardi, F. and Mele, D.: A new shape dependent drag correlation formula for non-spherical rough particles.  
715 Experiments and results, Powder Technology, 277, 222-230, <https://doi.org/10.1016/j.powtec.2015.02.062>, 2015.  
716

717 Di Vito M.A., Rucco I., de Vita S., Doronzo D.M., Bisson M., de' Michieli Vitturi M., Rosi M., Sandri L., Zanchetta G.,  
718 Zanella E., Costa A.: Lahar events in the last 2,000 years from Vesuvius eruptions. Part 1: Distribution and impact on  
719 densely-inhabited territory estimated from field data analysis, Solid Earth, this issue.  
720

721 Esposito, G., Matano, F. and Scepi, G.: Analysis of increasing flash flood frequency in the densely urbanized coastline  
722 of the Campi Flegrei volcanic area, Italy, Frontiers in Earth Science, 6, p.63, <https://doi.org/10.3389/feart.2018.00063>,  
723 2018.  
724

725 Fagents, S. A., and Baloga, S. M.: Toward a model for the bulking and debulking of lahars, J Geophys Res: Solid  
726 Earth, 111.B10, <https://doi.org/10.1029/2005JB003986>, 2006.  
727

728 Fiorillo, F. and Wilson, R.C.: Rainfall induced debris flows in pyroclastic deposits, Campania (southern Italy),  
729 Engineering Geology, 75(3-4), 263-289, <https://doi.org/10.1016/j.enggeo.2004.06.014>, 2004.  
730

731 Gidaspow, D.: Multiphase flow and fluidization: continuum and kinetic theory descriptions, Academic press, 1994.  
732

733 Hong, Y. J., Tai, L. A., Chen, H. J., Chang, P., Yang, C. S., & Yew, T. R.: Stable water layers on solid surfaces. Physical  
734 Chemistry Chemical Physics, 18(8), 5905-5909, <https://doi.org/10.1039/C5CP07866K>, 2016.  
735

736 [International Atomic Energy Agency \(IAEA\): Volcanic Hazard Assessments for Nuclear Installations: Methods and](#)  
737 [Examples in Site Evaluation, IAEA-TECDOC-1795, IAEA, Vienna, 2016.](#)  
738

739 Iverson, R. M., Schilling, S. P., & Vallance, J. W.: Objective delineation of lahar-inundation hazard zones, Geological  
740 Society of America Bulletin, 110(8), 972-984, [https://doi.org/10.1130/0016-7606\(1998\)110<0972:ODOLIH>2.3.CO;2](https://doi.org/10.1130/0016-7606(1998)110<0972:ODOLIH>2.3.CO;2),  
741 1998.  
742

743 Kelfoun, K. and Druitt, T.H.: Numerical modeling of the emplacement of Socompa rock avalanche, Chile, Journal of  
744 Geophysical Research: Solid Earth, 110(B12), <https://doi.org/10.1029/2005JB003758>, 2005.  
745

746 Kelfoun, K., Samaniego, P., Palacios, P. and Barba, D.: Testing the suitability of frictional behaviour for pyroclastic flow  
747 simulation by comparison with a well-constrained eruption at Tungurahua volcano (Ecuador), Bulletin of volcanology,  
748 71(9), 1057-1075, <https://doi.org/10.1007/s00445-009-0286-6>, 2009.  
749

750 Koo, S. and Sangani, A.S.: Effective-medium theories for predicting hydrodynamic transport properties of bidisperse  
751 suspensions, Physics of Fluids, 14(10), 3522-3533, <https://doi.org/10.1063/1.1503352>, 2002.  
752

753 Kurganov, A., and Petrova, G.: A second-order well-balanced positivity preserving central-upwind scheme for the Saint-  
754 Venant system. *Communications in Mathematical Sciences*, 5(1), 133-160,  
755 <https://dx.doi.org/10.4310/CMS.2007.v5.n1.a6>, 2007.  
756

757 Lecointre, J., Hodgson, K., Neall, V. and Cronin, S.: Lahar-triggering mechanisms and hazard at Ruapehu volcano, New  
758 Zealand: *Natural hazards*, 31(1), 85-109, <https://doi.org/10.1023/B:NHAZ.0000020256.16645.eb>, 2004.  
759

760 Macedonio, G., Costa, A., and Folch A.: Ash fallout scenarios at Vesuvius: Numerical simulations and implications for  
761 hazard assessment, *J Volcanol Geotherm Res*, 178, 366–377, <https://doi:10.1016/j.jvolgeores.2008.08.014>, 2008.  
762

763 Major, J.J. and Newhall, C.G.: Snow and ice perturbation during historical volcanic eruptions and the formation of lahars  
764 and floods, *Bulletin of volcanology*, 52(1), 1-27, <https://doi.org/10.1007/BF00641384>, 1989.  
765

766 Mastin, L.G. and Witter, J.B.: The hazards of eruptions through lakes and seawater, *Journal of Volcanology and*  
767 *Geothermal Research*, 97(1-4), 195-214, [https://doi.org/10.1016/S0377-0273\(99\)00174-2](https://doi.org/10.1016/S0377-0273(99)00174-2), 2000.  
768

769 Meruane, C., Tamburrino, A., and Roche, O.: On the role of the ambient fluid on gravitational granular flow dynamics,  
770 *Journal of Fluid Mechanics*, 648, 381–404, <https://doi.org/10.1017/S0022112009993181>, 2010.  
771

772 O'Brien, J. S., Julien, P. Y. and Fullerton, W. T.: Two-dimensional water flood and mudflow simulation, *J Hydraulic*  
773 *Engineering* 119.2, 244-261, [https://doi.org/10.1061/\(ASCE\)0733-9429\(1993\)119:2\(244\)](https://doi.org/10.1061/(ASCE)0733-9429(1993)119:2(244)), 1993.  
774

775 Patra, A.K., Bauer, A.C., Nichita, C.C., Pitman, E.B., Sheridan, M.F., Bursik, M., Rupp, B., Webber, A., Stinton, A.J.,  
776 Namikawa, L.M. and Renschler, C.S.: Parallel adaptive numerical simulation of dry avalanches over natural terrain,  
777 *Journal of Volcanology and Geothermal Research*, 139(1-2), 1-21, <https://doi.org/10.1016/j.jvolgeores.2004.06.014>,  
778 2005.  
779

780 Pierson, T.P., Janda, R.J., Thouret, J.C., Borerro, C.A.: Perturbation and melting of snow and ice by the 13 November  
781 1985 eruption of Nevado del Ruiz, Colombia, and consequent mobilization, flow and deposition of lahars. *J. Volcanol.*  
782 *Geoth. Res.* 41, 17-66, [https://doi.org/10.1016/0377-0273\(90\)90082-Q](https://doi.org/10.1016/0377-0273(90)90082-Q), 1990  
783

784 Pitman, E.B., Nichita, C.C., Patra, A., Bauer, A., Sheridan, M. and Bursik, M.: Computing granular avalanches and  
785 landslides, *Physics of fluids*, 15(12), 3638-3646, <https://doi.org/10.1063/1.1614253>, 2003.  
786

787 Pudasaini, S.P.: A general two-phase debris flow model, *J. Geophys. Res.*, 117, F03010,  
788 <https://doi:10.1029/2011JF002186>, 2012.  
789

790 Pudasaini, S. P., & Mergili, M.: A multi-phase mass flow model, *Journal of Geophysical Research: Earth Surface*,  
791 124(12), 2920-2942, <https://doi.org/10.1029/2019JF005204>, 2019  
792

793 Sandri, L., Costa, A., Selva, J., Tonini, R., Macedonio, G., Folch, A., and Sulpizio, R.: Beyond eruptive scenarios:  
794 assessing tephra fallout hazard from Neapolitan volcanoes, *Sci Rep*, 6, 24271, <https://doi.org/10.1038/srep24271>, 2016.  
795  
796 Sandri, L., de' Michieli Vitturi, M., Costa, A., Di Vito, M.A., Rucco, I., Doronzo, D., Bisson, M., Gianardi, R., Sulpizio,  
797 R., and Zanchetta, G.: Lahar events in the last 2,000 years from Vesuvius eruptions. Part 3: Hazard assessment over the  
798 Campanian Plain, *Solid Earth*, this issue.  
799  
800 Scott, K.M.: Origins, Behavior, and Sedimentology of Lahars and Lahar-runout Flows in the Toutle-Cowlitz River  
801 System, U.S. Geological Survey, Professional Paper, 1447-A, <https://doi.org/10.3133/pp1447A>, 1988.  
802  
803 Vallance, J.W., and Iverson, R.M.: Lahars and their deposits, in : *The encyclopedia of volcanoes*, edited by Haraldur  
804 Sigurdsson, Academic Press, 649-664, <https://doi.org/10.1016/B978-0-12-385938-9.00037-7>, 2015.  
805  
806 Vallebona, C., Pellegrino, E., Frumento, P. and Bonari, E.: Temporal trends in extreme rainfall intensity and erosivity in  
807 the Mediterranean region: a case study in southern Tuscany, Italy, *Climatic Change*, 128(1), pp.139-151,  
808 <https://doi.org/10.1007/s10584-014-1287-9>, 2015  
809  
810 Van Westen, C.J. and Daag, A.S.: Analysing the relation between rainfall characteristics and lahar activity at Mount  
811 Pinatubo, Philippines. *Earth Surface Processes and Landforms*, 30(13), 1663-1674, <https://doi.org/10.1002/esp.1225>,  
812 2005.  
813  
814 Zanchetta, G., Sulpizio, R., Pareschi, M.T., Leoni, F.M. and Santacroce, R.: Characteristics of May 5–6, 1998  
815 volcaniclastic debris flows in the Sarno area (Campania, southern Italy): relationships to structural damage and hazard  
816 zonation, *Journal of volcanology and geothermal research*, 133(1-4), 377-393, [https://doi.org/10.1016/S0377-  
817 0273\(03\)00409-8](https://doi.org/10.1016/S0377-0273(03)00409-8), 2004.  
818