

1 Response to reviewer comments  
2  
3 Preprint egusphere-2023-1740  
4 <https://doi.org/10.5194/egusphere-2023-1740>  
5  
6

## 7 **Reviewer 1**

---

8  
9 Review of Manuscript egusphere-2023-1740  
10 Testing the 2020 European Seismic Hazard and Risk Models using data from the 2019 Le  
11 Teil (France) earthquake  
12

13 This manuscript presents a comparison between building damage states as observed in the  
14 field after the 2019 Le Teil earthquake and those calculated by means of combining different  
15 components of existing risk models from different sources (not just the 2020 European  
16 Seismic Hazard and Risk Models). The damage survey has been processed by the authors  
17 according to expert judgment to obtain damage in terms of the EMS-98 scale. Different  
18 rupture models from the literature, as well as the USGS ShakeMap for this earthquake, are  
19 used to generate several realisations of ground motion fields in terms of peak ground and  
20 spectral acceleration (PGA, SA). The PGA values are then converted to macroseismic  
21 intensities using conversion equations, and these macroseismic intensities results are  
22 compared against the 7.5 value obtained in existing literature from field surveys with the  
23 purpose of selecting one rupture model to be used for the subsequent damage calculations  
24 carried out using the OpenQuake engine. Three main comparisons in terms of damage are  
25 carried out, combining different components (e.g., exposure, fragility, site effects) of different  
26 risk models as well as different risk calculation methods/software, and contrasting them  
27 against the results of the processed damage survey of the 2019 Le Teil earthquake.  
28

29 While the work presented in this manuscript is of interest to the research community to  
30 understand how different existing models and modelling choices affect the calculated  
31 damage and, most importantly, how the calculated damage compares against observations  
32 from a real earthquake, the manuscript has many significant shortcomings that would need to  
33 be addressed before it can be published in NHESS. I thus recommend that the manuscript  
34 be reconsidered for publication after major revisions.  
35

36 [We thank the reviewer for their constructive and helpful comments. We have tried to address  
37 them to the best of our knowledge, as detailed below.](#)  
38  
39

## 40 **Reviewer 1 - Main Comments**

41  
42 1. In my view, the title of the paper does not accurately describe its contents, due to three  
43 main reasons:  
44

45 1.1. The word “testing” is being used loosely throughout the manuscript (see point 2  
46 below).  
47

48 [Review round 1 reply](#)

49 [We agree with your comment \(i.e., leaving the word “testing” to the context of actual  
50 statistical tests\), and we will revise the manuscript accordingly, by replacing the word  
51 “testing” by “comparison” or “evaluation” wherever it is applicable.](#)  
52

53  
54 [Description of revision](#)

55 The terms “test” and “testing” have been replaced throughout the manuscript.  
56  
57

58 1.II. The paper makes comparisons using a variety of sources of model components  
59 (exposure, fragility, ruptures) that are not just from the 2020 European Seismic Hazard  
60 and Risk Models (ESHM20, ESRM20). The ground motion model used and labelled as  
61 being the ESHM20 one does not seem to be the model actually implemented in ESHM20  
62 but a previous version. When using the ESRM20 exposure model the building classes  
63 are “simplified”, effectively changing the ESRM20 exposure model. To my understanding  
64 (as such an outline is missing in the introduction), three comparisons in terms of damage  
65 are carried out:  
66

67 1.II.1) Section 3.3.1: Comparison between (a) damage calculated with the  
68 Armagedom software, using the vulnerability index approach, EMS-98 vulnerability  
69 classes, and an in-house exposure model, and (b) damage calculated with  
70 OpenQuake, using fragility models from the European Seismic Risk Model 2020  
71 (ESRM20) selected to be equivalent to the EMS-98 vulnerability classes, and the in-  
72 house exposure model converted onto ESRM20 building classes.  
73

74 1.II.2) Section 3.3.3: Comparison between (a) damage processed from the field  
75 survey, (b) damage calculated using the USGS ShakeMap, (c) damage calculated  
76 with OpenQuake, (seemingly) using the Kotha et al. (2020) GMPE (not the version  
77 used in ESHM20/ESRM20), and the BRGM VS30 model (which I infer is the ESRM20  
78 VS30 model derived from geology, not used in ESRM20), and (d) the same as (c) but  
79 using the ESRM20 VS30 model derived from topography (used in ESRM20 for  
80 cratonic and subduction areas, but not for shallow crustal areas, which is the case of  
81 France). All cases use the same exposure model, a building-by-building model based  
82 on the individual buildings from the damage survey to which ESRM20 building  
83 classes were assigned by the authors. All cases use the ESRM20 fragility models.  
84

85 1.II.3) Section 3.3.4: Comparison between (a) damage processed from the field  
86 survey and (b through g) six combinations of the following components:  
87

88 1.II.3.i. Exposure models: (i) the ESRM20 aggregated exposure model defined by  
89 administrative unit (one administrative unit), but with a large modification to the  
90 building classes that makes it different from the ESRM20 exposure model, and (ii)  
91 an in-house model derived from statistical data (8 or 9 centroids), to which  
92 ESRM20 building classes were assigned.  
93

94 1.II.3.ii. Site models: (i) the BRGM VS30 model (which I infer is the ESRM20  
95 VS30 model derived from geology, not used in ESRM20), values retrieved for the  
96 centroid of the administrative unit or 8-9 points of the exposure models, and (ii)  
97 the ESRM20 VS30 model derived from topography (used in ESRM20 for cratonic  
98 and subduction areas, but not for shallow crustal areas, which is the case of  
99 France), with the value for the ESRM20 exposure being a population-weighted  
100 average of the whole administrative unit and the values for the inhouse exposure  
101 model being retrieved from the 30 arc-sec cell that contains each of the 8- 9  
102 points.  
103

104 1.II.3.iii. Ground motions: (i) the USGS ShakeMap, and (ii) calculated with  
105 OpenQuake using the Kotha et al. (2020) GMPE (not the version used in  
106 ESHM20/ESRM20). As can be seen, no “pure” components of ESHM20/ESRM20  
107 appear to have been being used (“pure” = exactly as they have been used in the  
108 ESHM20/ESRM20 models) and several components from other sources are

109 being used as well. The title should reflect that the models being compared come  
110 from a variety of sources and decisions from the authors.

111  
112 1.III. Finally, “testing [...] hazard and risk models” may be misleading, as it can be easily  
113 interpreted as testing the full probabilistic seismic hazard and risk models (i.e.,  
114 probabilities of exceedance of ground motion, average annual losses, etc.), which is not  
115 what is done in the paper (and, furthermore, cannot be done using data from one single  
116 earthquake).

117  
118 To sum up, the paper shows comparisons (no statistical tests) of observed damage against  
119 damage calculated using components of risk models from different sources. I believe it is  
120 fundamental that a new title be assigned to the manuscript, taking into consideration the  
121 comments above.

#### 122 [Review round 1 reply](#)

123 Indeed, there are no “pure” components of ESHM20/ESRM20 that have been used, and there  
124 are no statistical tests in the manuscript. We will revise it according to comments 1.I-1.III.

125  
126  
127 We propose a new title for the manuscript:

128  
129 “Comparing components of the 2020 European Seismic Hazard and Risk Models using data  
130 from the 2019 Le Teil (France) earthquake”

#### 131 132 133 [Description of revision](#)

134 The title of the manuscript has been revised.

135  
136  
137 2. I have found the word “testing” being used loosely throughout the manuscript as a  
138 synonym of “comparing”, “validating”, “verifying”, “carrying out quality assurance”, etc. The  
139 word “testing” usually implies a formal statistical procedure using statistical indicators of  
140 goodness of fit, similarity between distributions, etc., which are not what is presented in the  
141 paper. The paper mostly carries out comparisons, without quantifying differences across  
142 different models/components. Please avoid over-using and overstretching in meaning the  
143 word “testing”, rewording where necessary. Some outstanding examples:

144  
145 2.a. The title in itself. The European Seismic Hazard and Risk Models are probabilistic  
146 models. The paper uses some of their components to carry out ground motion and  
147 damage calculations that are compared against damage observations from one  
148 earthquake. One earthquake cannot test or validate a probabilistic model, only its  
149 components.

150  
151 2.b. Line 34: Bommer et al. (2013) call their work “quality assurance” and not “testing”.  
152 Throughout the paper they use the word “check” far more than they use the word “test”.

153  
154 2.c. Sections 3.1 and 3.2: These sections are not testing ground motions or  
155 macroseismic intensities, they are comparing ground motions and macroseismic  
156 intensities calculated with different rupture models (against one value of macroseismic  
157 intensity) with the purpose of selecting one rupture to use in the remaining comparisons  
158 of the paper. The PGA and SA values are not compared against instrumental  
159 measurements at all (values of PGA are mentioned in lines 64-66 but not marked on the  
160 plots or mentioned again in Section 3.1). The sections are presented as “tests” when, in  
161 reality, they are an intermediate comparative step to select rupture parameters.

#### 162 163 [Review round 1 reply](#)

164 We agree with comments 2 and 2a-2c and we will revise the manuscript accordingly.  
165 Specifically, we will replace “testing” with terms such as “comparison” or “evaluation”, and “test”  
166 with “check” or “compare” or a comparable term.

167  
168 Moreover, the revised manuscript will state that the comparisons in Sections 3.1-3.2 serve the  
169 purpose of selecting rupture parameters.

170  
171  
172 Description of revision

173 The manuscript has been revised based on the reviewer’s comments and our reply (lines 55).

174  
175  
176 3. In line with the first point above, and with the purpose of aiding the reader to navigate  
177 comparisons carried out across so many different options, please re-phrase the last  
178 paragraph of the introduction to describe more accurately the work contained in the paper:

179  
180 3.a. Lines 46-47: This sentence states that the work is done “to test components of the  
181 ESHM20 and the ESRM20” models, giving the impression that only ESHM20 and  
182 ESRM20 components will be used, but components from other models are used as well,  
183 and these are not mentioned at all here. Please mention the other models used.

184  
185 3.b. Line 48: I suggest not using the expression “scenario simulations” to refer to ground  
186 motion scenarios calculated by means of ground motion models, as the word  
187 “simulations” is usually used to refer to physics-based ground motion simulations (this is  
188 not critical).

189  
190  
191 Review round 1 reply

192 The last paragraph of the introduction will be rephrased according to comments 3a-3b.

193  
194 Lines 46-47: “to compare components of the ESHM20 and the ESRM20 with local site  
195 effects models, exposure models and damage estimation methods,…”  
196 We also plan to expand this paragraph by using the summary made by the Reviewer in  
197 Comment 1.

198  
199 Line 48: we replace “simulations’ by “computations”.

200  
201  
202 Description of revision

203 The last paragraph of the introduction has been revised. It mentions the other models  
204 used, and it includes a summary of the comparisons in the paper (lines 50-63).  
205 The term “scenario simulations” has been replaced with “scenario computations”  
206 throughout the manuscript.

207  
208  
209 3.c. Lines 49-50: This sentence may give the impression that “the most compatible  
210 scenario simulation” is selected in terms of the one that gives the results closest to the  
211 USGS ShakeMap, but this is not what is stated in lines 50-52 or in Sections 3.1/3.2 (and  
212 further along in the paper), which show comparisons of all rupture models with respect to  
213 each other (including the USGS ShakeMap) and finally comparing intensities against the  
214 value reported by Schlupp et al. (2022).

215  
216 Review round 1 reply

217 Actually, the so-called “USGS ShakeMap” is a shake-map generated by us, using our data  
218 (seismic stations measurements, site effect model, specific ground-motion model), with the  
219 USGS ShakeMap v4 code.

220  
221 In order to avoid any confusion, we will use the word “shake-map” (lower case) when it is  
222 our own product (although it has been generated using the USGS ShakeMap algorithm),  
223 as opposed to the wording “USGS ShakeMap” (trademark product downloaded from the  
224 USGS website). We will correct this sentence in order to clarify this.

225  
226 We will also add a table that summarizes all the shale-maps / ground-motion fields that  
227 have been generated:  
228

GM Map ID	Type	GMM	Site model	Rupture model	Observations
GM1	ground-motion field	KoohaEtAl2020Site	BRGM soil classes to $V_{S30}$	Ritz et al.	No
GM2	ground-motion field	KoohaEtAl2020ESHM20SlopeGeology	Slope & Geology (ESRM20 data)	Ritz et al.	No
GM3	ground-motion field	KoohaEtAl2020Site	ESRM20 $V_{S30}$ data	Ritz et al.	No
GM4	shake-map	KoohaEtAl2020Site	BRGM Soil class to $V_{S30}$	Ritz et al.	Seismic stations

229  
230 [Description of revision](#)

231 The “shake-map” is used throughout the revised manuscript to refer to our analyses  
232 using the ShakeMap algorithm.

233 The table above has been added to the revised manuscript (Table 5-1) and the text has  
234 been revised (lines 324-328).

235  
236  
237 3.d. Lines 49-52: The meaning of “the most compatible scenario simulation” and “the  
238 most plausible scenario simulation” is not clear. After reading the paper, I believe the  
239 authors mean “the most compatible earthquake rupture”, or “the earthquake rupture that  
240 leads to the most compatible macroseismic intensities”.

241  
242 [Review round 1 reply](#)

243 Thank you for suggesting a clear and precise term. We will use it to revise the manuscript  
244 according to comments 3c-3d.

245  
246 [Description of revision](#)

247 The manuscript has been revised based on your suggestion (lines 69-40).

248  
249  
250 3.e. Lines 46-54: While several sentences are dedicated to explaining the comparison of  
251 ground motions and macroseismic intensities (which is only a preliminary step to select a  
252 suitable rupture to carry out the damage comparisons), very little is said about the core of  
253 the work. Please consider delineating the content of the three damage comparisons in a  
254 similar fashion to what I have written above under point (1), or perhaps with a figure. This  
255 is relevant to help the user navigate the paper, as so many different  
256 considerations/decisions are being made in each case.

257  
258 [Review round 1 reply](#)

259 Yes, we will do so based on your comments under point 1. We will also add a figure to  
260 summarize the various steps and comparisons.  
261

#### 262 Description of revision

263 The revised manuscript delineates the content of the damage comparisons (lines 55-83;  
264 text added in response to comments 3a-b).

265 The revised manuscript includes also a figure (Figure 1), which summarizes the various  
266 steps leading up to the comparisons.  
267

268  
269 4. The authors state (lines 113 and 315) that they are using the Kotha et al. (2020) ground  
270 motion prediction equation (GMPE) in the form of its KothaEtAl2020Site implementation in  
271 OpenQuake. However, all ESHM20/ESRM20 sources indicate that this is not the final GMPE  
272 used in ESHM20 and ESRM20. This being the case, the KothaEtAl2020Site GMPE should  
273 not be labelled as “ESHM20 GMF” (e.g., line 314), as this can be misleading for the reader.  
274

275 A more fundamental implication is that, with this GMPE being used, it is not the ESHM20  
276 ground motion model that is being “tested”, as implied in the title. Weatherill et al. (2020) and  
277 the ESHM20 report (Danciu et al., 2021) explain that a series of modifications were  
278 introduced to the Kotha et al. (2020) GMPE for the implementation in ESHM20 and ESRM20.  
279 Fundamentally, and given that the authors of the present manuscript emphasise the  
280 comparison of different VS30 models, KothaEtAl2020Site has a different amplification  
281 function for site effects, and the site-to-site variability of the GMPE was calibrated only on  
282 measured VS30, which means that an incompatibility arises when using it with inferred  
283 values of VS30. As explained in the OpenQuake documentation<sup>1</sup>:  
284

285 4.a. KothaEtAl2020Site is a “preliminary adaptation of the Kotha et al. (2020) GMPE  
286 using a polynomial site amplification function dependent on Vs30 (m/s)”.

287  
288 4.b. KothaEtAl2020ESHM20 is an “adaptation of the Kotha et al. (2020) GMPE for  
289 application to the 2020 European Seismic Hazard Model, as described in Weatherill et al.  
290 (2020)”. Page 89 of the ESHM20 report (Danciu et al., 2021) explains that  
291 KothaEtAl2020ESHM20 is the GMPE used in ESHM20. Site effects in this  
292 implementation depend on VS30 and whether that VS30 is a measured quantity or  
293 inferred from proxies (e.g., slope), so as to account for the uncertainty associated with  
294 using inferred values. Page 69 of Danciu et al. (2021) specifies that ESHM20 refers to  
295 ground motions on the “reference rock” (VS30 of 800 m/s everywhere). The ESHM20  
296 logic tree input file<sup>2</sup> also shows that KothaEtAl2020ESHM20 is being used for the  
297 calculations.  
298

299 4.c. KothaEtAl2020ESHM20SlopeGeology is an “adaptation of the ESHM20-  
300 implemented Kotha et al. (2020) model for use when defining site amplification based on  
301 slope and geology rather than inferred/measured Vs30”. The ESRM20 logic tree input  
302 file<sup>3</sup> and its “cut” version used for shallowcrustal areas when comparing against past  
303 earthquakes<sup>4</sup> indicate that this is the GMPE used in ESRM20 to calculate losses. Site  
304 effects in this implementation depend on slope and geology, not VS30 (e.g., second

---

<sup>1</sup> <https://docs.openquake.org/oq-engine/master/reference/openquake.hazardlib.gsim.html#openquake.hazardlib.gsim>

<sup>2</sup> [https://gitlab.seismo.ethz.ch/efehr/eshm20/-/blob/master/oq\\_computational/oq\\_configuration\\_eshm20\\_v12e\\_region\\_main/gmpe\\_complete\\_logic\\_tree\\_5br.xml](https://gitlab.seismo.ethz.ch/efehr/eshm20/-/blob/master/oq_computational/oq_configuration_eshm20_v12e_region_main/gmpe_complete_logic_tree_5br.xml)

<sup>3</sup> [https://gitlab.seismo.ethz.ch/efehr/esrm20/-/blob/main/Hazard/gmpe\\_logic\\_tree\\_5br\\_slope\\_geology.xml](https://gitlab.seismo.ethz.ch/efehr/esrm20/-/blob/main/Hazard/gmpe_logic_tree_5br_slope_geology.xml)

<sup>4</sup> [https://gitlab.seismo.ethz.ch/efehr/esrm20\\_scenario\\_tests/-/blob/main/models/esrm20/GMPE/gmpe\\_logic\\_tree\\_5br\\_shallow\\_default.xml](https://gitlab.seismo.ethz.ch/efehr/esrm20_scenario_tests/-/blob/main/models/esrm20/GMPE/gmpe_logic_tree_5br_shallow_default.xml)



305 paragraph of Section 3.2 of the ESRM20 report, page 16). ESRM20 uses this model  
306 together with the slope and geology of the ESRM20 model, which can be retrieved with  
307 the “exposure-to-site” tools cited in the present manuscript.  
308

309 As a consequence, reference (, not VS30), as in ESRM20. One should also note that using  
310 KothaEtAl2020ESHM20 with VS30 values other than 800 m/s would not necessarily be  
311 representative of either the ESHM20 or ESRM20 models.  
312

#### 313 [Review round 1 reply](#)

314 In the revised manuscript, we will now apply the correct KothaEtAl2020ESHM20SlopeGeology  
315 GMM when applying the “ESHM20 model”, according to Comment 4. However, we will also  
316 apply the KothaEtAl2020Site when using the Vs30-based site effect model available at BRGM.  
317 These differences will be detailed in the Table above (answer to Comment 3).  
318

319 As far as Comment 4.c is concerned, the ESRM20 uses a collapsed version of the ESHM20  
320 source model logic tree for 2 reasons: 1) to avoid high computational costs for calculations  
321 with respect to the generation of stochastic event sets and the associated ground motion fields,  
322 2) to avoid undesirable correlations in the source parameters due to the approach for  
323 propagating uncertainty, which assigns to all sources the same category of activity rate. In our  
324 manuscript, we are assessing damage after a single event. Therefore, no source logic tree is  
325 used.  
326

327  
328 5. Associated with the previous point, I believe it is very important that clarity is added with  
329 respect to the site models used in the comparisons. When comparing against Weatherill et  
330 al. (2023) (cited by the authors) and the ESHRM20 documentation, the explanations (e.g.,  
331 lines 266-272) in the paper lack from some clarity:  
332

333 5.a. It is not fully clear what the “BRGM’s VS30 database” refers to, as there are two  
334 VS30 models in the cited reference Weatherill et al. (2023): one based on topography  
335 alone, and another based on geology alone. The ESRM20 exposure-to-site tools (which  
336 the authors use and cite in the present manuscript) return the VS30 values from the  
337 topography-based model, as the comparisons in Weatherill et al. (2023) showed that it  
338 performed better than the geology-based one. As Table 3-5 (line 310) shows different  
339 VS30 values for the two (and quite round values for the BRGM case), I infer that the  
340 “BRGM’s VS30 database” refers to the geology-based VS30 model presented in  
341 Weatherill et al. (2023). Please clarify in the manuscript.  
342

#### 343 [Review round 1 reply](#)

344 We apologize that there has been a confusion regarding the reference and origin of the  
345 “BRGM’s VS30 database”. The model that we used in the manuscript is an EC8 soil class  
346 map assembled at BRGM for the French territory: this map of soil classes has then been  
347 converted into a Vs30 map by taking the median value of each EC8 soil class. The  
348 associated reference is a BRGM report (Roullé & Monfort, 2016), where the map is based  
349 on local knowledge of geology and soil classes. It is not linked to the Weatherill et al. (2023)  
350 reference. We will add some sentences to clarify this aspect.  
351

351 Associated reference:

352 Monfort, C., & Roullé, A. (2016). Estimation statistique de la répartition des classes de sol  
353 Eurocode 8 sur le territoire français - Phase 1 : Rapport final. BRGM Report RP-66250-  
354 FR.  
355

#### 356 [Revision description](#)

357 The creation of the site model based on the soil classes in Monfort and Roullé (2016) is  
358 described in the revised manuscript (lines 286-290).  
359

360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414

5.b. The manuscript would benefit from adding some sentences regarding the resolution of each of the two models, as this is relevant for the reader to understand what is being compared (e.g., in lines 267- 272). From Fig. 7 of Weatherill et al. (2023) it looks like in the “BRGM’s VS30 database” there are three geologic units, associated with three ranges of VS30 values (is the uncertainty being sampled to assign values in the paper?). The “point” workflow of the ESRM20 exposure-to-site tool returns the values associated with the 30-arcsec cell to which the target point belongs, as 30-arcsec is the resolution of the model.

[Review round 1 reply](#)

The resolution of the BRGM Vs30 model is based on a geological map at the (1/50000 scale). We will add a sentence comparing this value to the resolution of the ESRM20 exposure-to-site tool (30-arcsec).

[Description of revision](#)

The revised manuscript mentions the resolutions of the two models (line 288).

5.c. It is noted that the VS30 values returned by the exposure-to-site tool are not used in ESRM20 in France (non-cratonic shallow seismicity). These VS30 values are used with the craton and subduction GMPEs selected for the areas of Europe where the shallow-crustal ESHM20 GMPE (i.e., KothaEtAl2020ESHM20SlopeGeology) is not applicable (e.g., see page 16 of the ESRM20 report, Crowley et al., 2021). The GMPE used for ESRM20 (i.e., KothaEtAl2020ESHM20SlopeGeology in OpenQuake) calculates site amplification based on slope and geology directly, not VS30. Please clarify in the manuscript that the VS30 values labelled as ESHM20 are actually not used in ESHM20/ESRM20 in France.

[Review round 1 reply](#)

We agree with this comment: as stated above, we will now use the KothaEtAl2020ESHM20SlopeGeology GMM to represent the “ESHM20 model” (GM2 in the above table). As a result, we will use the ESRM20 slope and geology data directly. For the generation of other ground-motion scenarios, we will still use the BRGM Vs30 model for France associated with the KothaEtAl2020Site GMM in order to be consistent. We will clarify this in the revised manuscript.

[Description of revision](#)

The Sections 3.3 and 5.1 describe how this GMM is used in the revised manuscript.

d. From my understanding, the site amplification model and VS30 maps are part of ESRM20 and not ESHM20, as ESHM20 focused on hazard on the reference rock. Please name them as ESRM20, not ESHM20.

[Review round 1 reply](#)

We will rename them accordingly in the revised manuscript.

[Description of revision](#)

The revised manuscript uses the name ESRM20  $V_{S30}$  instead of ESHM20  $V_{S30}$ .

6. In my view, it is necessary to add a map that shows the resolution/locations of the different exposure models and site models, the spatial extent of the municipality of Le Teil, the location of the selected rupture plane, etc. This is important for the reader to be able to



415 understand the different models that are being compared and interpret the differences  
416 observed.

417

418 [Review round 1 reply](#)

419 Thank you for suggesting this. Such maps will be added to the revised manuscript.

420

421 [Description of revision](#)

422 A map has been added to the manuscript (Figure 2).

423

424

425 7.a The conclusions section is too short and does not discuss the results with depth. It only  
426 focuses on marginal observations. It consists of three paragraphs, the first (and longest) of  
427 which focuses extensively on the comparison of macroseismic intensities (which is not the  
428 core of this work), the second of which briefly mentions that the exposure model was a key  
429 difference-maker in the results, without elaborating on reasons, and the third paragraph  
430 discusses potential improvements to the analysis by changing the criteria used to post-  
431 process the field damage survey, highlights the need for more standardised field survey  
432 practices, and comments about the importance of accounting for buildings not included in the  
433 survey, which has not been discussed in the paper and for which explanations are not given.  
434 Please rewrite the conclusions focusing on the large number of different model components  
435 that have been compared, to reflect the work done.

436

437 [Review round 1 reply](#)

438 The conclusions will be revised based on this comment. Thank you for your comment and your  
439 guidance. The points around which the conclusions will be revised:

440

441 - The comparison of macroseismic intensities, as well as the other comparisons will be  
442 discussed in the conclusions;

443 - The effect of the exposure model on the results will be discussed in terms of the number of  
444 estimated damages, and in terms of the included building classes and their fragility;

445 - The effect of accounting for buildings not included in the survey will be discussed in the  
446 manuscript and in the conclusions.

447

448 [Description of revision](#)

449 The conclusions have been revised.

450

451

452 7.b I have found the statement about the effect of the exposure model (lines 359-362) quite  
453 hard to see in Fig. 5, which shows so many different models. Moreover, lines 323-333 focus  
454 on the differences due to the VS30 model, not the exposure. I strongly recommend to find  
455 alternative ways to show and compare these results (perhaps several plots "grouping" results  
456 according to exposure, or VS30), and potentially even to quantify the differences between  
457 models, so that it becomes clearer to the reader whether exposure or site effects have had a  
458 greater influence in the discrepancies with observed values.

459

460 [Review round 1 reply](#)

461 Once more we would like to thank you for your comment and your guidance. In the revised  
462 manuscript, we will describe the effect of the different exposure models in Section 3.3.4. We  
463 will add different plots, which will group results by exposure or  $V_{S30}$ . Moreover, the differences  
464 between models will be quantified by selecting one case as the reference, and by subsequently  
465 calculating the ratio of the probability of a damage grade in the other cases to the probability  
466 of a damage grade in the reference case.

467

468 [Description of revision](#)

469 In the revised manuscript, the effect of the exposure and the  $V_{S30}$  models are discussed with  
 470 the help of figures 6 and 7, respectively.

471  
 472

473 7.c The importance of including in the calculations buildings that were not part of the damage  
 474 survey is mentioned in the conclusions (lines 368-369), but I cannot find it discussed before.  
 475 Please explain why it is important to include those buildings and comment on why the  
 476 damage survey seems to cover such a small proportion of the buildings of the municipality of  
 477 Le Teil. Did they only survey buildings on demand from the owner? Can it be assumed that  
 478 the rest of the buildings were undamaged? This is important as well to interpret the plots in  
 479 Fig. 5.

480  
 481 Review round 1 reply

482 Indeed, surveys were done upon requests from the owners. Because of this, there is a potential  
 483 bias in the damage distribution based on the observations. On the other hand, it cannot be  
 484 guaranteed that the rest of the buildings were undamaged. This issue will be discussed in the  
 485 revised manuscript. Thank you very much for raising this point.

486  
 487 We propose to add a table that will clarify the way the buildings have been surveyed:  
 488

Observed Damage Data ID	Exposure resolution	Exposure data	Damage estimation method	Damage conversion method	
DD1	Building-by-building (327 buildings)	AFPS emergency survey	AFPS emergency observations on 327 buildings (Green/Yellow/Red tags)	Conversion to EMS-98 damage grades (Tab. 2.1)	Related to Fig. 4
DD2	Infra-municipality districts (2778 buildings)	National statistics database (BRGM-CCR)	AFPS emergency observations on 327 buildings (Green/Yellow/Red tags) + "Extrapolation"	Conversion to EMS-98 damage grades with expert judgment (Tab. 3.6)	Related to Fig. 5
DD3	Infra-municipality districts (2778 buildings)	National statistics database (BRGM-CCR)	AFPS emergency observations on 327 buildings (Green/Yellow/Red tags) + "Extrapolation"	Conversion to EMS-98 damage grades (Tab. 2.1) + Bias adjustment on total number of 2778 buildings (accounting for non-surveyed buildings)	Related to Fig. 5

489  
 490 Description of revision

491 The table above has been added to the manuscript (Table 2-3). Moreover, importance of  
 492 including in the calculations buildings that were not part of the damage survey is explained in

493 the revised manuscript after the revision with respect to the comment 5 in the section  
494 "Reviewer 1 - Other Comments on Content".

495  
496

497 Apart from this, the first paragraph (lines 350-357) talks extensively about macroseismic  
498 intensities calculated with the AS2000 model. The acronym AS2000 is not defined at all  
499 within the text. Line 354 suggests the AS2000 has been used to convert from SA(1 s) to  
500 macroseismic intensity, and , lines 355- 357 highlight that SA(1 s) is not representative of the  
501 buildings in Le Teil, but Section 3.2 discusses two models that convert from PGA/PGV (not  
502 SA) to macroseismic intensity. I thus infer AS2000 stands for Atkinson and Sonley (2000),  
503 one of the conversion models used by the Armagedom software, according to Sedan et al.  
504 (2013). However, no macroseismic intensity values calculated using the Atkinson and Sonley  
505 (2000) conversion equation are presented in the paper. Please revise and correct as needed.

506  
507

[Review round 1 reply](#)

508 We apologize for this confusion: the reference to the Atkinson & Sonley (2000) GMICE comes  
509 from a previous working version of the manuscript. Eventually, this GMICE has not been used  
510 in the intensity computations (we confirm that the SA(1s) ground-motion parameter is of little  
511 interest to the studied building stock). The manuscript will be corrected by removing references  
512 to this model.

513  
514

[Description of revision](#)

515 Any reference to the Atkinson & Sonley (2000) GMICE has been removed.

516  
517

518 8. Similarly to the conclusions, the abstract would need a revision to include mention of all  
519 other models that have been used, as per my previous comments. Please revise the last  
520 sentence of the abstract (lines 17-19), which vaguely hints on conclusions that do not match  
521 the conclusions section or the content of the work.

522  
523

[Review round 1 reply](#)

524 The abstract will be revised so that it takes into account your comments, and the closing  
525 statements will match the content. Thank you for this comment.

526  
527

[Description of revision](#)

528 The abstract has been revised.

529 **Reviewer 1 - Other Comments on Content**

530

531 1. Line 56: Please remove “and risk” from the title, as the section does not describe seismic  
532 risk in the area.

533

534 [Review round 1 reply](#)

535 [This will be removed from the title. Thank you for this comment.](#)

536

537 [Description of revision](#)

538 [This has been removed from the manuscript.](#)

539

540

541 2. Lines 70-74: While this statement can be generally valid, it is noted that the ground motion  
542 model used in ESHM20 is a backbone model whose central tendency is derived from  
543 European data that may be lacking representation of such shallow earthquakes with a  
544 relatively large stress drop, but whose different branches account for the possibility of having  
545 more “unusual” stress parameters (i.e., uncertainty in the stress drop is treated as an  
546 epistemic uncertainty). Please see Kotha et al. (2020) and Weatherill et al. (2020) and  
547 consider rephrasing (otherwise it suggests that the authors agree with Causse et al. 2021 in  
548 this particular case and believe a priori that the ESHM20 ground motion model cannot be  
549 able to represent this earthquake).

550

551 [Review round 1 reply](#)

552 [The manuscript will be revised according to this comment. We do not wish to express any](#)  
553 [agreement or disagreement with Causse et al. \(2021\), only to report their findings. However,](#)  
554 [we do acknowledge –and the revised manuscript will do so too– that the ESHM20 ground](#)  
555 [motion model may be able to represent the ground shaking generated by this earthquake.](#)  
556 [We propose to add the following sentence at the end of the paragraph:](#)

557

558 [“However, it should be noted that some branches in the ESHM20 GMM logic tree should be](#)  
559 [able to account for the possibility of having extreme stress parameter values, by treating](#)  
560 [uncertainty in the stress drop as a source of epistemic uncertainty \(Kotha et al., 2020;](#)  
561 [Weatherill et al., 2020\).”](#)

562

563 [Description of revision](#)

564 [The sentence above has been added to the manuscript \(lines 107-109\).](#)

565

566

567 3. Line 101, Table 2-1: There are some aspects of the table that would benefit from  
568 clarification in the text:

569

570 3.a. How should the reader interpret the first four columns that contain “R” and empty  
571 spaces? Does it mean that while a certain parameter is red, the EMS-98 damage grade  
572 is as indicated, irrespective of the other parameters? Are the four components ordered as  
573 per a hierarchy? I.e. if both vertical and horizontal structural elements are red, then it is  
574 damage grade 5, but if the horizontal structural elements are red and the vertical ones  
575 are yellow or green, then it is 4?

576

577 [Review round 1 reply](#)

578 [Yes, in the cases where a given parameter is red the damage grade is assigned](#)  
579 [irrespective of the other parameters.](#)

580

581 [Yes, the four components are ordered hierarchically. Yes, if both vertical and horizontal](#)  
582 [structural elements are red, then the damage grade 5 is assigned, but if the horizontal](#)

583 structural elements are red and the vertical are yellow or green, then the grade 4 is  
584 assigned.

585

586 We will add this clarification in the revised manuscript.

587

588 [Description of revision](#)

589 The clarification above has been added to the manuscript (line 143).

590

591

592 3.b. The far right column shows all components in green and the damage grade resulting  
593 in 1. Is this because all entries in the survey have some sort of damage and thus “green”  
594 is to be interpreted as “damaged, but usable” and not include “undamaged”? It calls the  
595 reader’s attention that everything is green and the damage grade is not zero. Please  
596 comment in the paper.

597

598 [Review round 1 reply](#)

599 Indeed, in the cases where everything is green, the damage grade 1 is assigned (damage  
600 grade 1 corresponds to no structural damage and slight non-structural damage). This  
601 assignment is done based on our judgement. The dataset that we used contains only  
602 damage observations, which were made during inspections on request by the building  
603 owners. We consider that slight non-structural damage was the cause that led the owners  
604 to request an inspection of their building. We will add this clarification in the revised  
605 manuscript.

606

607 [Description of revision](#)

608 The clarification above has been added to the manuscript (line 144).

609

610

611 4. Line 106, Table 2-2:

612

613 4.a. In the caption, please clarify this is the buildings’ “final” tag (as opposed of tags by  
614 components). “... as a function of the buildings’ final tags for the entire dataset”.

615

616 [Review round 1 reply](#)

617 This will be corrected in the revised manuscript. Thank you for this comment.

618

619 [Description of revision](#)

620 This has been corrected.

621

622

623 4.b. It calls my attention that several green buildings end up classified as ESM-98  
624 damage grade 3, which corresponds to moderate structural damage and heavy non-  
625 structural damage. I would expect moderate structural damage to lead to the need of  
626 further inspection and repair before the building can be used, while “green” means that  
627 the building can be used again immediately. This could be the reason why in Fig. 4 the  
628 “observation based” probabilities for damage grade 2 are notably low when compared  
629 against damage grades 1 and 3 (the distribution has an unusual “valley” in damage grade  
630 2). Can it be that several of the green buildings that ended up classified as damage grade  
631 3 are, actually, damage grade 2? Moreover, Table 3-6 suggests the authors also believe  
632 green should map only to damage grade 1 or 2.

633

634 [Review round 1 reply](#)

635 This is a very good point, and we agree with this comment. Indeed, there may be green  
636 buildings, which could have been assigned a damage grade 2. The classification that we  
637 propose assigns damage grade 3, when the vertical or the horizontal structural elements



638 have a yellow tag. We believe that a yellow tag with respect to the structural elements  
 639 signifies moderate structural damage, hence damage grade 3. The fact that in these cases  
 640 a green tag was assigned, perhaps indicates that a further inspection took place, which  
 641 either reclassified the damage as green structural damage, or as yellow non-structural  
 642 damage. We acknowledge that our mapping scheme can be refined to take into account  
 643 such cases.

644  
 645 The “valley” in damage grade 2, which you refer to, will be discussed in the revised  
 646 manuscript based on your comments and this response.

647  
 648 Description of revision

649 The revised manuscript comments on the “valley” in damage grade 2 (line 456).

650  
 651  
 652 5. Associated with the previous point, there seem to be different probabilities of damage and  
 653 numbers of damaged buildings from observations presented in different plots and the text,  
 654 which I have found confusing. I have found/observed:

655  
 656 5.a. The probabilities of damage from observations differ in Fig. 4 with respect to Fig. 5.

657  
 658 Review round 1 reply

659 Thank you for raising this issue. Please accept our apologies for omitting the calculation of  
 660 the probabilities in Fig. 5.a labelled as “Observation-based”. These probabilities take into  
 661 account the probabilities in Fig. 4 as well as our presumption that the damage grade  
 662 probabilities for the buildings that have not been inspected are different, because the  
 663 inspections were made upon owner request. The calculation of the probabilities in Fig. 5.a is  
 664 done with the following tables (Tables 5.a.1-4). Table 5.a.1 includes the probabilities of the  
 665 damage grades conditioned on colour tags. In Table 5.a.2, the total probabilities of the  
 666 damage grades is calculated. Table 5.a.3 gives the damage grade probabilities conditioned  
 667 on whether a building has been inspected. The first line of Table 5.a.3 includes the  
 668 probabilities based on the damage observations. The second line includes values selected  
 669 based on our judgement. The calculation of the total probabilities of the damage grades for  
 670 inspected and uninspected buildings, which are the probabilities in Fig. 5.a labelled as  
 671 “Observation-based”, is given in Table 5.a.4. The description of this calculation as well as  
 672 Tables 5.a.1-4 will be included in the revised manuscript.

673  
 674  
 675 Table 5.a.1: Probabilities of the damage grades conditioned on the colour tag assigned to a  
 676 building that has been inspected during the survey

tag	n_buildings	P(tag)	P(DG1 tag)	P(DG2 tag)	P(DG3 tag)	P(DG4 tag)	P(DG5 tag)
Green	238	0.475	0.610	0.150	0.240	0.000	0.000
Yellow	157	0.313	0.000	0.000	0.900	0.080	0.020
Red	106	0.212	0.000	0.000	0.000	0.640	0.360

677  
 678  
 679 Table 5.a.2: Calculation of the total probability of the damage grades for buildings inspected  
 680 during the survey

tag	P(DG1 tag)·P(tag)	P(DG2 tag)·P(tag)	P(DG3 tag)·P(tag)	P(DG4 tag)·P(tag)	P(DG5 tag)·P(tag)
Green	0.290	0.071	0.114	0.000	0.000
Yellow	0.000	0.000	0.282	0.025	0.006
Red	0.000	0.000	0.000	0.135	0.076
Sum:	0.290	0.071	0.396	0.160	0.082

681

682  
683  
684  
685

Table 5.a. 3: Probabilities of the damage grades conditioned on whether a building has been inspected (the probabilities for inspected buildings are based on the damage observations, the probabilities for the uninspected buildings are based on expert judgement)

Inspected	P(Insp.)	P(DG1 Insp.)	P(DG2 Insp.)	P(DG3 Insp.)	P(DG4 Insp.)	P(DG5 Insp.)
TRUE	0.180	0.290	0.071	0.396	0.160	0.082
FALSE	0.820	0.500	0.300	0.100	0.050	0.050

686  
687  
688  
689

Table 5.a.4: Calculation of the total probabilities of the damage grades accounting for both inspected and uninspected buildings

Inspected	P(DG1 Insp.)·P(Insp.)	P(DG2 Insp.)·P(Insp.)	P(DG3 Insp.)·P(Insp.)	P(DG4 Insp.)·P(Insp.)	P(DG5 Insp.)·P(Insp.)
TRUE	0.052	0.013	0.071	0.029	0.015
FALSE	0.410	0.246	0.082	0.041	0.041
Sum:	0.462	0.259	0.153	0.070	0.056

690

Description of the revision

The tables 5.a.1-4 have been added to the manuscript (Tables 2-4 – 2-7), as well as a paragraph (lines 161-191).

691  
692  
693  
694  
695  
696  
697  
698

5.b. The numbers of buildings from observations in Fig. 5b are much larger than the 327 buildings included in the damage survey. Why is this the case?

Review round 1 reply

Thank for this question. The numbers of buildings in Fig. 5b are calculated by multiplying the total number of buildings in the exposure model by the probabilities in Fig. 5a. The numbers reported as “Observation-based” result from the multiplication with the probabilities calculated according to our response to the previous comment (comment 5.a). We acknowledge that the figure may mislead the reader to think that the numbers in Fig. 5b correspond to numbers of observations. Therefore, we will rename the label “Observation-based” in the legends in Fig. 5a-5b to “Calc. on insp.”, shorthand for “Calculation based on the damage grade probabilities for inspected and uninspected buildings”.

699

Description of revision

The revised manuscript explains how the numbers of buildings in Fig. 6-8 are calculated (lines 161-191), and the labels DD2 and DD3 have replaced the label “Observation-based” in Fig 6-8.

700  
701  
702  
703  
704  
705  
706  
707  
708  
709

5.c. At the same time, the plots in Fig. 5 have two separate categories, “Exp. judg.-based” and “Observation-based”, but I have found no explanation regarding what this means, as lines 324-326 only say “Two of the sources consist of probabilities based on expert judgement (“Exp. judg.- based”), and probabilities based on our conversion of the damage observations to damage grades (“Observation-based”), but the meaning of “based on expert judgement” is not explained. It is noted as well that “our conversion of the damage observations to damage grades” is also “expert judgment”, and thus the difference between the two requires a more detailed clarification.

710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725

Review round 1 reply

726 It is true that both results labelled as “Exp. judg.-based” and “Observation based” have  
727 been calculated using expert judgment to different extents. Please see our responses to  
728 comments 5.a and 5.d, which also respond to comment 5.c.

729  
730 Description of revision

731 The calculation of the probabilities labelled as DD2 (the label used in the revised  
732 manuscript instead of “Observation-based”), and DD3 is described in the revised  
733 manuscript (lines 161-191).

734  
735  
736 5.d. The above makes me wonder if one of the two “observation” labels in the plots in Fig.  
737 5 has been created using Table 3-6. I have been unable to find any reference to Table 3-  
738 6. Please clarify if Table 3-6 is being used and reference it within the text if this is the  
739 case.

740  
741 Review round 1 reply

742 Yes, Table 3-6 is used for one of the probabilities in Fig 5.a labelled “Exp. judg.-based”.  
743 We will clarify this with a more precise nomenclature. We will add a table that explains how  
744 the “observations-based” damage distributions have been generated (see table in our  
745 answer to Comment 7.c in the section “Reviewer 1 - Main Comments”). That table will  
746 include a reference to Table 3-6.

747  
748 Description of revision

749 The Table 3-6 is now numbered as Table 2-8 in the revised manuscript and its use is  
750 described in lines 161-191.

751  
752  
753 5.e. If more than one method has been used to obtain damage grades from the survey  
754 data (apart from the one described in Section 2.2), all methods need to be specified (and  
755 given distinct names/labels) in Section 2.2.

756  
757 Review round 1 reply

758 We agree with your suggestion: see our answer above and our proposition to add a table  
759 describing these methods (answer to Comment 7.c in the section “Reviewer 1 - Main  
760 Comments”).

761  
762 Description of revision

763 These methods are described in Section 2.2.

764  
765  
766 5.f. The conclusions state “The proposed testing procedure based on the observed  
767 damages could be improved by introducing a probabilistic rule for the conversion of  
768 damage observations on the three level colour tag (red, yellow, green) scale to the EMS-  
769 98 damage scale” (lines 364-365). To my understanding, this is exactly what Table 3-6 is  
770 showing. If this is the case, and it has been used, then please adjust the conclusions.

771  
772 Review round 1 reply

773 We acknowledge that the manuscript is not clear. The revised manuscript will say instead  
774 that one could introduce a conversion rule, which would return damage grade probabilities  
775 instead of a single value for the damage grade as a function of the colour tags for structural  
776 and non-structural elements. Thank you for this comment.

777  
778 Description of revision

779 The conclusions have been revised (lines 593-595).

780

781  
 782 5.g. I cannot find any reason for Table 3-6 not to be used. Showing and discussing  
 783 “observed” damage results obtained using both strategies (Table 2-1 and Table 3-6),  
 784 which is potentially what is shown in Fig. 5 but not sufficiently explained, would convey to  
 785 the reader the inherent uncertainty involved in the comparison between the models and  
 786 the observations (i.e., “observations” are not a ground truth), which is fundamental in any  
 787 comparison between models and data (i.e., the uncertainties do not only exist in the  
 788 models).

789 [Review round 1 reply](#)

790 Thank you for this comment. Table 3-6 is used to calculate the probabilities in Fig. 5.a  
 791 labelled as “Exp. judg.-based”.

792  
 793 [Description of revision](#)

794 The Table 3-6 is numbered Table 2-8 in the revised manuscript and its use is described in  
 795 lines 187-191.

796  
 797  
 798  
 799 6. Associated with the previous point, please explain in the paper how the ESRM20 damage  
 800 scale (associated with the ESRM20 fragility models) was converted into the EMS-98 scale,  
 801 as this is another source of uncertainty in the comparison.

802  
 803 [Review round 1 reply](#)

804 Thank you very much for this comment. Indeed, this conversion can be a source of uncertainty.  
 805 It will be described in the revised manuscript. The conversion was done by matching the  
 806 damage states/grades based on the structural damage since both scales assume the level of  
 807 non-structural damage based on the level of structural damage. A table like the following will  
 808 be added to the manuscript:

809  
 810 Table: Conversion of the damage scale of the ESRM20 fragility models to the EMS-98 damage  
 811 scale on the basis of structural damage

ESRM20	EMS98
D0 no damage (combined structural and non-structural damage) [This damage state is not explicitly mentioned by the damage scale, but it is implied]	Grade 0 No damage [This damage state is not explicitly mentioned by the damage scale, but it is implied]
	Grade 1: Negligible to slight damage (no structural damage, slight non-structural damage)
D1 slight (combined structural and non-structural damage)	Grade 2: Moderate damage (slight structural damage, moderate non-structural damage)
D2 moderate (combined structural and non-structural damage)	Grade 3: Moderate damage (moderate structural damage, heavy non-structural damage)
D3 extensive (combined structural and non-structural damage)	Grade 4: Very heavy damage (heavy structural damage, very heavy non-structural damage)
D4 complete (combined structural and non-structural damage)	Grade 5: Destruction (very heavy structural damage)

812  
 813  
 814  
 815 [Description of revision](#)

816 The conversion is described in the revised manuscript (lines 473-475, Table A4)

817

818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860

7. Lines 110 and 161: The titles of Sections 3.1 and 3.2 need to be changed, as they do not reflect the content of these sections. Neither section presents a test. They are both a procedure to select a rupture model to carry out the damage comparisons. The first sentence of Section 3.1 needs to be changed as well, as the section does not present a comparison against macroseismic intensities.

[Review round 1 reply](#)

The titles of Sections 3.1 and 3.2, as well as the first sentence of Section 3.1, will be changed in the revised manuscript based on the comment. Indeed, these sections are a procedure to select a rupture model to carry out the damage comparisons.

[Description of revision](#)

In the revised manuscript, the titles of Sections 3.1 and 3.2 have been changed (new Sections 4.1 and 4.2).

8. Line 111 (and other instances): Although the citation of the Wald et al. (2022) paper indicates that it is the USGS ShakeMap that is being used, it would be good to be explicit (by saying "USGS ShakeMap"), as the USGS ShakeMap software is also used by other organisations with their own configuration (e.g., the European ShakeMap, the Italian ShakeMap).

[Review round 1 reply](#)

We will clarify this sentence, as stated in our answer to Comment 3c. In this study, we have generated the shake-map ourselves, using our specific configuration of the USGS ShakeMap software.

[Description of revision](#)

Please see the description of the revision based on Comment 3c in the section "Reviewer 1 - Main Comments".

9. Line 114: Which site model was used for the ground motion comparisons?

[Review round 1 reply](#)

Thank you for this question. The revised manuscript will describe the site model that was used. It is a site model including one point for each exposure centroid, with the same coordinates as its corresponding exposure centroid. The  $V_{S30}$  was inferred based on the EC8 soil class map by the BRGM for the French territory (Roullé & Monfort, 2016). Specifically, the median of each class was taken as the  $V_{S30}$ . The outputs of the  $V_{S30}$  site model for the exposure centroids are given in the next table, which could be added to the revised manuscript:

Centroid	latitude	longitude	region	brgm $V_{S30}$ (m·s <sup>-1</sup> )	ESRM20 $V_{S30}$ (m·s <sup>-1</sup> )	$V_{S30}$ Type	geology	slope
0	44.5546	4.6835	1	800	807	inferred	CRETACEOUS	0.0823
1	44.5453	4.6804	1	270	831	inferred	CRETACEOUS	0.0645
2	44.5414	4.6846	1	270	730	inferred	HOLOCENE	0.0487
3	44.5405	4.6498	1	800	726	inferred	CRETACEOUS	0.0768
4	44.5347	4.6713	1	800	831	inferred	CRETACEOUS	0.0467
5	44.5500	4.6909	1	270	699	inferred	HOLOCENE	0.0160
6	44.5442	4.6699	1	800	830	inferred	CRETACEOUS	0.0522
7	44.5547	4.6692	1	580	840	inferred	CRETACEOUS	0.0503



8	44.5315	4.6953	1	270	644	inferred	HOLOCENE	0.0439
---	---------	--------	---	-----	-----	----------	----------	--------

861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914

Associated reference :  
Monfort, C., & Roullé, A. (2016). Estimation statistique de la répartition des classes de sol Eurocode 8 sur le territoire français - Phase 1 : Rapport final. BRGM Report RP-66250-FR.

Description of revision

The Table 3-5 has been revised. It is now numbered Table 3-3, and it includes the parameters for the site models. Moreover, the revised manuscript describes the site models in Section 3.

10. Line 139 states that the ground motions were “aggregated over all exposure centroids”, but it is not specified whether the values shown are means or medians (of all points). Please specify.

Review round 1 reply

The scenario analyses generated samples of the ground motion intensity measures at the locations of the exposure centroids. The boxplots concern the entirety of the samples for all centroids. Thank you for this comment. This will be clarified in the revised manuscript.

Description of revision

The revised manuscript clarifies how the distributions, the means, and the medians of the values are represented (lines 342-345).

11. Line 139: It is stated that ground motions are calculated at the exposure centroids. However:

11.a. To my understanding, OpenQuake does not calculate the ground motions at the exposure points themselves but at the points of the site model that are closest neighbours to the exposure points (and assigns the ground motions to the exposure points by closest neighbours, not interpolation). This can be checked by looking at the sitemesh\_XXX.csv output by OpenQuake, as this shows the locations at which ground motions were calculated. If this is the case, it would be relevant to know what site model is being used and its resolution with respect to the resolution of the exposure points.

Review round 1 reply

Thank you for this comment. The site model includes points with coordinates identical with those of the exposure points. The manuscript will be revised accordingly. See also the reply to Comment 9 in the section “Reviewer 1 - Other Comments on Content”.

Description of revision

The lines 303-304 have been added to the manuscript.

11.b. At this stage, the exposure model has not been described, and different exposure models are used later on in the paper. Please indicate if the “exposure centroids” refer to the building-by-building data of the post-earthquake damage survey or other locations.

Review round 1 reply

The exposure centroids refer to the 9 centroids of the 9 intra-municipal districts in BRGM’s exposure model for the town of Le Teil (Table 3-5). This will be clarified in the revised manuscript. Thank you for this comment.

915 [Description of revision](#)

916 The revised manuscript describes the exposure models in Section 3.2 before the  
917 comparison with respect to intensity measures in Section 4.1.

918  
919

920 12. Lines 149-150: It would be relevant to comment on whether the USGS ShakeMap for this  
921 earthquake was constrained with direct ground motion measurements (from stations) and/or  
922 Did You Feel It macroseismic intensity observations. For reproducibility, please include as  
923 well the version of the USGS ShakeMap used, as the USGS recalculates ShakeMaps when  
924 new data or new algorithms become available.

925  
926 [Review round 1 reply](#)

927 As stated in previous answers to comments ,we have generated the shake-map ourselves,  
928 using our specific configuration of the USGS ShakeMap software (version 4). The parameters  
929 related to this shake-map are detailed in the table that we propose to add (see GM4 in the  
930 table added in the answer to Comment 3c in the section “Reviewer 1 - Main Comments”).

931  
932 The shake-map for this earthquake was constrained with ground motion measurements only  
933 (no DYFI). However, the closest stations are over 15 km from the epicentre, which leads to  
934 practically no constraint. We will discuss this issue in the revised manuscript.

935  
936 [Description of revision](#)

937 Please see the description of the revision based on Comment 3c in the section “Reviewer 1 -  
938 Main Comments”. Moreover, the lines 152-155 have been added to the manuscript.

939  
940

941 13. Line 151, Fig. 1: It would help the reader if the vertical axis contained the non-logarithmic  
942 values of the IM (potentially side by side with the logarithmic ones, or as a scale on the right  
943 side of the plot).

944  
945 [Review round 1 reply](#)

946 Fig. 1 will be revised according to this comment.

947  
948 [Description of revision](#)

949 A scale on the right side of the plot has been added. The figure now is numbered as Figure  
950 2.

951  
952

953 14. Line 181, Table 3-2: Is it relevant to show the parameters for the CA2015 model and not  
954 the FM2010 model?

955  
956 [Review round 1 reply](#)

957 The parameters for the FM2010 model will be added to the revised manuscript as well.

958  
959

959 [Description of revision](#)

960 The parameters for the FM2010 model are included in the revised manuscript (Table 3-3).

961  
962

963 15. Lines 193 and 197 use the acronym “KO2020”, which has not been defined.

964  
965 [Review round 1 reply](#)

966 Any reference to KO2020 will be removed, and the rest of the manuscript will be revised  
967 accordingly. We apologize that this was left after a revision of a working version of the  
968 manuscript. Thank you for this comment.

969

970 [Description of revision](#)

971 The revised manuscript does not use the acronym KO2020.

972

973

974 16. Lines 210-226: There are some aspects of the comparison shown in Section 3.3.1 that  
975 are not explained and are relevant for interpreting the results. Please specify in the paper:

976

977 16.a. Lines 212-213 state that the “ESHM20 ground motion logic tree” was used, but so  
978 far there has been no reference to the ESHM20 ground motion logic tree, only to the  
979 KothaEtAl2020Site implementation of the Kotha et al. (2020) GMPE, which, as explained  
980 earlier, is not the one used in ESHM20. Please clarify which logic tree is being used.

981

982 [Review round 1 reply](#)

983 Thank you for requesting this clarification. Indeed, in Section 3.2 no ground motion logic  
984 tree is used. For the calculation in Section 3.3.1, the ESHM20 ground motion logic tree is  
985 being used, which employs the GMPE «KothaEtAl2020ESHM20». The revised manuscript  
986 will include this clarification.

987

988 From a technical point of view, the file gmpe\_complete\_logic\_tree\_5br.xml was edited by  
989 removing all other «logicTreeBranchSet» other than «branchSetID="Shallow\_Def"», which  
990 corresponds to the regime of the study area, because errors related to the removed  
991 branches were preventing the completion of the analysis. In our opinion, this technical  
992 detail will not be of interest to the readers, but it will be included in the revised manuscript  
993 if you consider it should be.

994

995 [Description of revision](#)

996 The revised manuscript specifies the GMPE and the logic tree that is used in the  
997 comparison in section 3.3.1.

998

999

1000 16.b. Lines 214-215: If “equivalent” exposure and fragility models are being used “so as  
1001 to limit the effect of these two factors on the differences between the two estimations”,  
1002 what is the purpose of this comparison? Comparing a model in Armagedom against a  
1003 model in OpenQuake? Is the equivalence between the models fully guaranteed? Please  
1004 clarify the purpose of the comparison presented in Section 3.3.1.

1005

1006 [Review round 1 reply](#)

1007 OpenQuake and Armagedom use different methods for the damage estimation.

1008

1009 As mentioned previously, Armagedom uses the RISK-UE semi-empirical macroseismic  
1010 method. This is based on the intensity values and a vulnerability index for the calculation  
1011 of the mean damage degree for the beta distribution.

1012

1013 OpenQuake uses ground motion intensities and fragility curves.

1014

1015 The two methods are obviously different, but, no matter what their path, the results of both  
1016 methods have the same aim: asses the damages after an earthquake. Considering this  
1017 same objective, the results from the two methods can be compared.

1018

1019 Nevertheless, we agree with your comment, and we will add a paragraph to summarise  
1020 both methods.

1021

1022 A few articles attempt to address the issue (e.g. Lestuzzi et al. 2016).

1023 Lestuzzi, P., Podestà, S., Luchini, C. et al. Seismic vulnerability assessment at urban scale  
1024 for two typical Swiss cities using Risk-UE methodology. Nat Hazards 84, 249–269 (2016).  
1025 <https://doi.org/10.1007/s11069-016-2420-z>  
1026

1027  
1028 Description of revision

1029 A paragraph has been added to the manuscript (lines 249-260), which underlines the main  
1030 differences between the two analysis tools and clarifies the purpose of this comparison.  
1031

1032  
1033 16.c. Lines 215-216: Please clarify in the paper the meaning of “the exposure model in  
1034 Armagedom”. I am not familiar with the software, but the paper of Sedan et al. (2013)  
1035 gives the impression that Armagedom is a software and the user can input any exposure  
1036 model as desired. Please clarify in the paper how this exposure model was defined.  
1037

1038 Review round 1 reply

1039 Yes, we will explain the exposure model used in Armagedom, based on vulnerability  
1040 indices of building classes. A more detailed answer and paragraph is available below (see  
1041 answer to Comment 25). Yes, Armagedom is able to treat any exposure model, as long as  
1042 the preliminary step of converting building class to vulnerability indices is carried out.  
1043

1044 Description of revision

1045 The revised manuscript gives details on the exposure model used in the calculation with  
1046 Armagedom (lines 251-253, 259-260).  
1047

1048  
1049 16.d. Lines 215-221: Does the exposure model used in OpenQuake maintain the 9  
1050 centroids mentioned in line 217?  
1051

1052 Review round 1 reply

1053 Yes, it does.  
1054

1055 Description of revision

1056 This is specified in the revised manuscript (lines 246-247).  
1057

1058  
1059 16.e. Please comment in the paper (a paragraph would suffice) about the details of the  
1060 damage calculation in Armagedom: use of conversion models to transform PGA into  
1061 macroseismic intensity, calculation of a mean damage grade as a function of  
1062 macroseismic intensity, distribution into damage grades under the assumption of a Beta  
1063 distribution, etc. This method is fundamentally different from the calculation carried out in  
1064 OpenQuake in terms of PGA/SA, with damage grades directly retrieved from the fragility  
1065 model, conversion of ESRM20 damage grades into ESM-98 damage grades, etc. Without  
1066 these details and comparisons, it may not be fully evident to the reader what the purpose  
1067 of this section is.  
1068

1069 Review round 1 reply

1070 Thank you for this comment. It is indeed worth describing the procedure used by  
1071 Armagedom and highlighting the differences from the calculation in OpenQuake. A  
1072 paragraph on this subject will be added to the revised manuscript.  
1073

1074 Description of revision

1075 A paragraph has been added to the revised manuscript (lines 249-255).  
1076  
1077

1078 16.f. Lines 224-225: These sentences compare the values obtained against observations,  
1079 but the percentages of “heavy” and “very heavy” damage observed are not reported.  
1080 Please add them in the text. It is also not clear why the observed values are not shown in  
1081 Fig. 3, given that they are shown later in Figs. 4 and 5 (converting number of buildings  
1082 into proportions, as in the other plots, or using a right-hand axis with a different scale on  
1083 the same plot).

1084

1085 Review round 1 reply

1086 Thank you for this comment. Indeed the values calculated based on the observations  
1087 should have been included in Fig. 3, and they will be included in the revised manuscript.  
1088 We should note that since the percentages concern the entire town of Le Teil, the  
1089 percentages calculated based on the observations are calculated according to our  
1090 response to comment 4 in the section “Reviewer 1 - Other Comments on Content”. The  
1091 revised manuscript will also report the percentages for “heavy” and “very heavy” damage.

1092

1093 Description of revision

1094 The percentages of “heavy” and “very heavy” damage are reported in the manuscript (line  
1095 268).

1096 The observed values have been added to the figure (the new number of the figure is Fig.  
1097 4, line 277)

1098

1099

1100 16.g. Do the OpenQuake damage results correspond to the average damage resulting  
1101 from all 1,000 ground motion realisations (only mentioned in Section 2.1) and all logic  
1102 tree branches (if a ground motion logic tree was indeed used)? Please specify.

1103

1104 Review round 1 reply

1105 Yes, they do correspond to the average damage from all ground motion realisations for all  
1106 logic tree branches. The manuscript will be revised accordingly. Thank you for this  
1107 comment.

1108

1109 Description of revision

1110 This is specified in the revised manuscript (line 266-267).

1111

1112

1113 16.h. Does Armagedom calculate different ground motion fields (1,000 as well?) to  
1114 account for ground motion uncertainty?

1115

1116 No, currently, Armagedom does not generate stochastic samples of ground-motion fields.  
1117 It applies the GMM and estimates only the mean ground-motion parameters across the  
1118 map.

1119

1120

1121 17. Line 240: To my knowledge, the most recent reference of GED4ALL is Silva et al. (2022),  
1122 and the preferred name for this building taxonomy is “GEM Building Taxonomy v3.0”:

1123

1124 Silva V, Brzev S, Scawthorn C, Yepes C, Dabbeek J, Crowley H (2022) A building  
1125 classification system for multi-hazard risk assessment. International Journal of Disaster Risk  
1126 Science 13:161–177. <https://www.doi.org/10.1007/s13753-022-00400-x>

1127

1128 Review round 1 reply

1129 Thank you for indicating the correct reference. It will be corrected in the revised manuscript.

1130

1131 Description of revision



1132 In the revised manuscript, GED4ALL has been replaced by “GEM Building Taxonomy v3.0”,  
1133 and the reference of Silva et al. (2022) has been added (line 284).

1134  
1135

1136 18. Line 240: I would suggest to re-phrase “we selected a GED4ALL building class based  
1137 on...” as “we defined building classes in terms of the GEM Building Taxonomy v3.0 (Silva et  
1138 al., 2022), based on the building materials and the number of storeys”. The current phrasing  
1139 may erroneously convey that the taxonomy consists of a pre-defined list of building classes  
1140 to choose from, instead of a classification system of attributes to be concatenated.

1141

1142 [Review round 1 reply](#)

1143 Thank you very much for this suggestion. We see how the phrasing may be misleading. As  
1144 suggested, we will rephrase this in the revised manuscript.

1145

1146 [Description of revision](#)

1147 The manuscript has been rephrased as indicated (line 284).

1148

1149

1150 19. Line 245, Table 3-4: It is interesting that fragility models for infilled frames (“CR\_LFINF”)  
1151 were selected for dual frame-wall systems (“CR/LDUAL”), instead of using the “CR\_LDUAL”  
1152 fragility models directly (one of which is mentioned in Table 3-3). Please comment in the  
1153 paper on this choice. Moreover, the reinforced concrete ESRM20 classes selected  
1154 correspond to different values of the lateral force coefficient, and it is not clear how this could  
1155 be selected from the damage dataset. Please comment.

1156

1157 [Review round 1 reply](#)

1158 Thank you for this comment. We made the arbitrary choice to classify the reinforced concrete  
1159 buildings in the dataset as CR/LDUAL. We should have simply assigned to them a CR class.

1160

1161 We agree that the lateral force coefficient may not be selected based on the damage dataset.  
1162 Moreover, we did not consider it during the selection of the fragility models. We assigned an  
1163 EMS98 vulnerability class based on the year of construction. Subsequently, we selected  
1164 fragility models, which we considered to be in agreement with the construction material and  
1165 the EMS98 vulnerability classes.

1166

1167 [Description of revision](#)

1168 In Table 3-4 (line 295), the GEM Building Taxonomy v3.0 class the building classes  
1169 CR/LDUAL/HAPP:2 and CR/LDUAL/HAPP:4 have been replaced by CR/HAPP:2 and  
1170 CR/HAPP:4, respectively.

1171 The revised manuscript comments on the lateral force coefficient related to the ESRM20  
1172 building classes (287-291).

1173

1174

1175 20. Lines 249-254: Please specify the GMPE used.

1176

1177 [Review round 1 reply](#)

1178 The GMPE KothaEtAl2020Site has been used; but with the proposed revisions, we will now  
1179 apply two GMMs (KothaEtAl2020Site and KothaEtAl2020ESHM20SlopeGeology). This will  
1180 be better explained thanks to the following table:

1181

GM Map ID	Type	GMM	Site model	Rupture model	Observations
GM1	ground-motion field	KothaEtAl2020 Site	BRGM soil classes to Vs30	Ritz et al.	No

GM2	ground-motion field	KothaEtAl2020 ESHM20Slope Geology	Slope & Geology (ESRM20 data)	Ritz et al.	No
GM3	ground-motion field	KothaEtAl2020 Site	ESRM20 Vs30 data	Ritz et al.	No
GM4	shake-map	KothaEtAl2020 Site	BRGM Soil class to Vs30	Ritz et al.	Seismic stations

1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212

Description of revision

The GMPE is specified in the manuscript (lines 308-310), and the table above has been added (Table 3-6).

21. Lines 254-256: The label “SM – brgm VS30” suggests that the BRGM model was used together with the USGS ShakeMap. How was this site model incorporated to the ShakeMap? Does this mean the ShakeMap used in the paper is not the one downloaded from the USGS but the authors have run the ShakeMap software themselves? Please clarify in the manuscript.

Review round 1 reply

As stated in previous answers to comments, we have generated the shake-map ourselves, using our specific configuration of the USGS ShakeMap software (version 4). The parameters related to this shake-map are detailed in the table that we propose to add (see GM4 in the table added in the answer to Comment 3c in the section “Reviewer 1 - Main Comments”). We will revise the nomenclature of these labels (“SM – brgm Vs30”) according to that new table.

22. Line 283 (Fig. 4) and Line 341 (Fig. 5): Please clarify if the proportions of buildings in each damage grade stemming from the calculations have been calculated with respect to the total number of buildings (including undamaged ones) or only the number of damaged buildings (which I understand is the case for the observation values).

Review round 1 reply

Thank you for requesting this clarification. In the revised manuscript, it will be clarified by a new table (as introduced in our answer above), which will explain the number of buildings considered in each comparison (differences between Fig. 4 and Fig. 5):

Observed Damage Data ID	Exposure resolution	Exposure data	Damage estimation method	Damage conversion method	
DD1	Building-by-building (327 buildings)	AFPS emergency survey	AFPS emergency observations on 327 buildings (Green/Yellow/Red tags)	Conversion to EMS-98 damage grades (Tab. 2.1)	Related to Fig. 4
DD2	Infra-municipality districts (2778 buildings)	National statistics database (BRGM-CCR)	AFPS emergency observations on 327 buildings (Green/Yellow/Red tags) + “Extrapolation”	Conversion to EMS-98 damage grades with expert judgment (Tab. 3.6)	Related to Fig. 5

DD3	Infra-municipality districts (2778 buildings)	National statistics database (BRGM-CCR)	AFPS emergency observations on 327 buildings (Green/Yellow/Red tags) + "Extrapolation"	Conversion to EMS-98 damage grades (Tab. 2.1) + Bias adjustment on total number of 2778 buildings (accounting for non-surveyed buildings)	Related to Fig. 5
-----	---	---	--	---	-------------------

1213  
1214  
1215  
1216  
1217  
1218  
1219

Description of revision

The proportions of buildings in the calculations has been specified (Table 3-10, and lines 423-439). Please also see the revision with respect to comment 5a in the section "Reviewer 1 - Other Comments on Content".

1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229

23. Line 284 (caption of Fig. 4), and Table A3: Please clarify what the acronym "BRGM/CCR" refers to. I find it confusing that it is named in Fig. 4, which corresponds to analyses carried out using the building-by-building exposure based on the 327 surveyed buildings, and then in Table A3, which lists 2,778 buildings, which is the number reported in both Sections 3.3.1 (line 216, "the exposure model in Armagedom, which includes 2778 buildings") and 3.3.4 (lines 293-294, "the second exposure model ("brgm exp.") is based on national statistical data, and includes 9 centroids with 2778 buildings"). Please clarify the relation between the exposure models used in Sections 3.3.1 and 3.3.4: are they the same? Please add reference to Table A3 within the text.

1230  
1231  
1232  
1233  
1234

Review round 1 reply

The nomenclature of the exposure models will be clarified: the "BRGM/CCR" label refers to the same exposure model as "brgm-exp". This will also be clarified by the above table of observed damage data.

1235

We will add a reference to Table A3 in the text.

1236  
1237

Description of revision

1238  
1239

The caption of Fig. 4 (Fig. 5 in the revised manuscript) has been corrected, as well as the caption of Table A3.

1240

A reference to Table A3 has been added (line 369).

1241  
1242

1243  
1244  
1245  
1246  
1247

24. Lines 291-293, and Tables A1 and A2: It is not clear why the ESRM20 exposure model is not being used directly as it is, including its exposure-to-vulnerability mapping. The changes introduced by the authors mean that the calculations carried out with this model may not necessarily reflect what would have been obtained with the "original" ESRM20 model.

1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255

Moreover, the choice of fragility classes for each exposure class shown in Table A1 appears as contradictory. In the screenshot of Table A1 below, I have marked the differences in the classes and annotated the classes used in ESRM20, which can be consulted in the esrm20\_exposure\_vulnerability\_mapping.csv file of the ESRM20 v1.0 repository<sup>5</sup>. The differences are associated with the number of storeys (e.g., a 4-storey class has been selected for a 6-and-above-storey class, first row) and the lateral force coefficient and/or design code level (e.g., a low code class with 15% lateral force coefficient has been selected for a no-code class, seventh row). Please justify the need to use a "simplified" version of the

<sup>5</sup> [https://gitlab.seismo.ethz.ch/efehr/esrm20/-/blob/v1.0/Vulnerability/esrm20\\_exposure\\_vulnerability\\_mapping.csv](https://gitlab.seismo.ethz.ch/efehr/esrm20/-/blob/v1.0/Vulnerability/esrm20_exposure_vulnerability_mapping.csv)

1256 exposure model (instead of the original ESRM20 exposure) and explain the criteria used to  
 1257 assign new classes in Table A1 (in the main body of the paper).  
 1258

**Table A1 Selected ESRM20 fragility classes based on the building types in Le Teil according to the ESRM20**

Original ESRM20 type	N. buildings	Selected ESRM20 frag. class	# class
CR/LDUAL+CDL+LFC:4.0/HBET:6-	3	CR_LDUAL-DUL_H4 H6	1
CR/LDUAL+CDL+LFC:4.0/HBET:3-5	7	CR_LDUAL-DUL_H4	1
CR/LDUAL+CDN/HBET:6-	2	CR_LDUAL-DUL_H4 H6	1
CR/LFINF+CDL+LFC:4.0/H:2	67	CR_LFINF-CDL-10_H2 CDL-5	2
CR/LFINF+CDM+LFC:4.0/H:1	42	CR_LFINF-CDM-10_H2 CDM-5_H1	3
CR/LDUAL+CDM+LFC:4.0/HBET:6-	1	CR_LDUAL-DUL_H4 H6	1
CR/LFLS+CDN/HBET:6-	9	CR_LFINF-CDL-15_H4 CDN-0_H6	4
CR/LFINF+CDL+LFC:4.0/H:1	76	CR_LFINF-CDM-10_H2 CDL-5_H1	2
CR/LDUAL+CDM+LFC:4.0/HBET:3-5	3	CR_LDUAL-DUL_H4	1
MUR+CL/LWAL+CDN/H:2	378	MUR-CL99_LWAL-DNO_H2	5
CR/LFINF+CDM+LFC:4.0/H:2	37	CR_LFINF-CDM-10_H2 CDM-5	3
MUR+CL/LWAL+CDN/H:1	690	MUR-CL99_LWAL-DNO_H1	6
MUR+ST/LWAL+CDN/H:2	130	MUR-CL99_LWAL-DNO_H2 STDRE	5
CR+PC/LWAL+CDN/HBET:3-5	53	CR_LDUAL-DUL_H4	1
W/LWAL+CDN/H:1	100	W_LFM-DUL_H2 H1	7
W/LWAL+CDN/H:2	43	W_LFM-DUL_H2	7
CR+PC/LWAL+CDN/HBET:6-	1	CR_LDUAL-DUL_H4 H6	1
CR/LFINF+CDN/HBET:3-5	38	CR_LFINF-CDL-15_H4 CDN-0	4

1259  
 1260

1261 [Review round 1 reply](#)

1262 The ESRM20 model includes a number of building classes, which is higher than the number  
 1263 of classes in the BRGM exposure model. Moreover, the ESRM20 model includes classes with  
 1264 a small percentage of the total number of buildings, which could be grouped with similar  
 1265 classes. For example, we decided to group in Class 1 (revised Table A1) buildings categories  
 1266 with 6 or more storeys, which have a small number of buildings, together with buildings with 3-  
 1267 5 storeys on the basis of the similarity of their load-bearing systems.

1268  
 1269 The merger of similar classes and the reduction of the total number of classes had the goal of  
 1270 simplifying the comparisons. Moreover, we hoped that, if there were comparable classes, we  
 1271 would be able to attribute differences in the results to specific classes based on the numbers  
 1272 and probabilities of damage per building class.

1273  
 1274 **Revised Table A1**

Original ESRM20 type	N. buildings	Selected ESRM20 frag. class	Class
CR+PC/LWAL+CDN/HBET:3-5	53	CR_LDUAL-DUL_H4	1
CR/LDUAL+CDL+LFC:4.0/HBET:3-5	7	CR_LDUAL-DUL_H4	1
CR/LDUAL+CDM+LFC:4.0/HBET:3-5	3	CR_LDUAL-DUL_H4	1
CR/LDUAL+CDL+LFC:4.0/HBET:6-	3	CR_LDUAL-DUL_H4	1
CR/LDUAL+CDN/HBET:6-	2	CR_LDUAL-DUL_H4	1
CR+PC/LWAL+CDN/HBET:6-	1	CR_LDUAL-DUL_H4	1
CR/LDUAL+CDM+LFC:4.0/HBET:6-	1	CR_LDUAL-DUL_H4	1
CR/LFINF+CDL+LFC:4.0/H:1	76	CR_LFINF-CDL-10_H2	2
CR/LFINF+CDL+LFC:4.0/H:2	67	CR_LFINF-CDL-10_H2	2
CR/LFINF+CDM+LFC:4.0/H:1	42	CR_LFINF-CDM-10_H2	3
CR/LFINF+CDM+LFC:4.0/H:2	37	CR_LFINF-CDM-10_H2	3
CR/LFINF+CDN/HBET:3-5	38	CR_LFINF-CDL-15_H4	4
CR/LFLS+CDN/HBET:6-	9	CR_LFINF-CDL-15_H4	4
MUR+CL/LWAL+CDN/H:2	378	MUR-CL99_LWAL-DNO_H2	5
MUR+ST/LWAL+CDN/H:2	130	MUR-CL99_LWAL-DNO_H2	5
MUR+CL/LWAL+CDN/H:1	690	MUR-CL99_LWAL-DNO_H1	6
W/LWAL+CDN/H:1	100	W_LFM-DUL_H2	7
W/LWAL+CDN/H:2	43	W_LFM-DUL_H2	7

1275

1276 However, in response to your suggestion, we propose to do an extra analysis using the original  
1277 ESRM20 exposure model, in order to check potential differences. This will be discussed in the  
1278 revised manuscript.

1279  
1280 Revision description

1281 Table A1 has been revised, and the manuscript justifies the simplification of the exposure  
1282 model (lines 367-373).

1283 An additional analysis has been done using the original ESRM20 exposure model, whose  
1284 results are included in Fig. 6 (labelled “ESRM20 Vs30 – ESHM20 GMF – Orig. ESRM20  
1285 exp.”). Despite the incoherencies with respect to the lateral force coefficient and/or design  
1286 code level, the calculated damage presents insignificant differences from the calculation  
1287 using the simplified exposure (“ESRM20 Vs30 – ESHM20 GMF – ESRM20 exp.”).

1288  
1289  
1290 25. Lines 291, 294: Please clarify in the manuscript that only residential buildings from the  
1291 ESRM20 exposure model are being included in the calculation (I have deduced this from  
1292 looking at the ESRM20 exposure model for France). Please clarify as well if the BRGM  
1293 exposure considers only residential buildings as well, and whether it covers the same spatial  
1294 extent (even better if using a map). Please clarify if the damage observations only cover  
1295 residential buildings as well.

1296  
1297 Review round 1 reply

1298 Yes, for the aggregated exposure models (Section 3.3.4) the BRGM exposure considers only  
1299 residential buildings as well and it covers the same spatial extent (Teil administrative borders).  
1300 The residential exposure data were extracted from the building census database at the  
1301 municipality (and infra-municipality) level, provided freely by the national statistical database  
1302 INSEE. Based on structural criteria available, as well as a pilot project in Bouches-du-Rhône  
1303 Department (Sedan et al., 2008), which compared field investigation data and INSEE data at  
1304 the departmental scale level, we derived a matrix—consisting of a cross between the age of  
1305 construction, number of stories, and type of construction—for a simplified description of the  
1306 vulnerability based on the INSEE data. Therefore, starting from INSEE statistics, we classified  
1307 the buildings into EMS98 taxonomy classes. The EMS98 scale associates vulnerability classes  
1308 (A, B, C, D, E, and F) to the most common structural types (masonry, reinforced concrete,  
1309 steel, and wood), indicating the most likely, probable, and less probable ranges that a structural  
1310 type belongs to a given vulnerability class. Then, the EMS98 taxonomy classes were converted  
1311 into RISK-UE vulnerability indices, based on the method developed by (Lagomarsino and  
1312 Giovinazzi, 2006; Milutinovic and Trendafiloski, 2003). A national classification was done in  
1313 the past by brgm. More details about this procedure can be find in Fayjaloun et al. (2021).

1314  
1315 For “building-by-building” exposure model (Sect 3.3.3) we used the AFPS database that  
1316 concerns, as well, only the residential buildings.

1317  
1318 Associated reference:  
1319 Fayjaloun, R., Negulescu, C., Roullé, A., Auclair, S., Gehl, P., & Faravelli, M. (2021). Sensitivity  
1320 of earthquake damage estimation to the input data (soil characterization maps and building  
1321 exposure): Case study in the Luchon Valley, France. *Geosciences*, 11(6), 249.

1322  
1323  
1324 Description of revision

1325 The manuscript specifies that the exposure models and the damage observations concern  
1326 residential buildings (lines 423-426, 435).

1327  
1328  
1329 26. Lines 300-304: By using a weighting scheme for the so-called “ESHM VS30” model but  
1330 not for the BRGM model, this comparison becomes not just about the VS30 models but the

1331 different ways of assigning values to an aggregated area. It would be useful to highlight this  
1332 further in the text.

1333

1334 [Review round 1 reply](#)

1335 Thank you for pointing this out. We will add a sentence on this issue in the text:

1336 "It should be noted that these two different ways to collect Vs30 values at the centroids  
1337 (weighted mean of Vs30 values across the area versus punctual value at the centroid) may  
1338 constitute an additional source of discrepancy, in addition to the initial differences between the  
1339 two Vs30 models."

1340

1341 [Description of revision](#)

1342 The sentence above has been added to the manuscript (lines 452-454).

1343

1344

1345 27. Line 310, Table 3-5: The table shows 8 locations but the text (line 294) says "9  
1346 centroids". Please correct where needed.

1347

1348 [Review round 1 reply](#)

1349 We apologize for this mistake, as a line of the table was erased. The table will be corrected so  
1350 that it shows 9 locations. This will also be corrected throughout the manuscript in the revised  
1351 version.

1352

1353 The new table will also contains new fields, providing values for the slope and geology related  
1354 to the 9 locations (since these parameters will be used by the  
1355 KothaEtAl2020ESHM20SlopeGeology GMM). The new version of the table is shown in the  
1356 answer to Comment 9.

1357

1358 [Description of revision](#)

1359 The table has been corrected (Table 3-8, line 466).

1360



## Reviewer 1 - Language Use, Typos

Please make the following changes.

1. What do the authors mean with “ShakeMap analyses”? It seems to me that, in most cases, the authors simply mean “ShakeMaps”. Please revise and re-phrase all instances along the paper. Examples:

2.a. Line 14: Just “ShakeMaps in order to...”.

2.b. Line 49: Just “to distributions given by ShakeMaps”.

2. Line 10: “validated individually, although testing and validating”.

3. Line 12: “damage from past earthquakes”.

4. Line 15: “components of the 2020 European Seismic Hazard Model” (not “Euro-Mediterranean”).

5. Line 16: “the degree of damage” or “the damage grade”.

6. Line 22: “insured and uninsured direct economic losses”. I assume this was the intention, as only indirect economic losses are mentioned otherwise.

7. Line 23: “(PSHA, PSRA are...” (not “PSHR”).

8. Line 53: Please define VS30 in its first appearance (this line).

9. Line 77: “vulnerability classes” (small letters).

10. Line 93: “data in the forms that we used are” (no commas).

11. Line 101, Table 2-1: “Vertical load-bearing” and “Horizontal load-bearing” (not “loads”).

12. Line 115: “the ruptures in the ShakeMap as well as”.

13. Line 121: “scaling relation”.

14. Line 123: “we assume that its geometric centroid is located at the hypocentre”.

15. Line 131, Table 3-1: In the caption, “Rupture parameters associated with the five source models”.

16. Line 156, Fig. 1, caption: “ground motion intensity measures aggregated from all exposure centroids”.

17. Line 164: “to identify the ruptures leading to”.

18. Line 168: The equation starts “MCS =” but the subscript of the standard deviation says “MMI”. Is this correct? (See line 170 as well).

19. Line 177: “The CA2015 model”.

20. Line 201: “(FM2010), and b) the macroseismic intensity”.

- 1416 21. Line 203: “PGA given by and the ground motion-to-intensity”.  
1417  
1418 22. Line 210, caption: “at the exposure centroids of the BRGM exposure in the site  
1419 models...” (or appropriate name for the exposure model).  
1420  
1421 23. Line 350: “closer to the estimation of EMS-98 macroseismic intensity by Schlupp et al.  
1422 (2022)”. The text before that statement had not yet mentioned macroseismic intensity.  
1423  
1424

## 1425 **Reviewer 1 - Issues with References**

1426

- 1427 1. Line 384: There are numbers at the end of “Munson” and “Stamatakos”.  
1428  
1429 2. Lines 396-397: The citation of Crowley et al. (2021) is incomplete (no initials of first  
1430 names, no DOI, mention of EFEHR Technical Report 002 missing). Please cite as (apply  
1431 journal formatting style):  
1432

1433 Crowley, H., Dabbeek, J., Despotaki, V., Rodrigues, D., Martins, L., Silva, V., Romão, X.,  
1434 Pereira, N., Weatherill, G. and Danciu, L., 2021. European Seismic Risk Model (ESRM20),  
1435 EFEHR Technical Report 002, V1.0.1, 84 pp, [https://doi.org/10.7414/EUC-EFEHR-TR002-](https://doi.org/10.7414/EUC-EFEHR-TR002-ESRM20)  
1436 ESRM20  
1437

- 1438 3. Lines 408-411: The citation of Danciu et al. (2021) is not fully correct. Please cite as :  
1439

1440 Danciu, L., Nandan, S., Reyes, C., Basili, R., Weatherill, G., Beauval, C., Rovida, A.,  
1441 Vilanova, S., Sesetyan, K., Bard, P.-Y., Cotton, F., Wiemer, S., and Giardini, D.: The 2020  
1442 update of the European Seismic Hazard Model: Model Overview, EFEHR Technical Report  
1443 001, V1.0.0, <https://doi.org/10.12686/A15>, 2021.  
1444

### 1445 [Review round 1 reply](#)

1446 [The issues with the References, as well as the typos and the instances of incorrect language](#)  
1447 [use will be corrected in the revised manuscript. Thank you for pointing them out.](#)  
1448

### 1449 [Description of revision](#)

1450 [The instances of incorrect language use, the issues with references, and the typos have been](#)  
1451 [corrected.](#)  
1452

1453 **Reviewer 2**

---

1454

1455 Review of Manuscript egosphere-2023-1740

1456 Testing the 2020 European Seismic Hazard and Risk Models using data from the 2019 Le  
1457 Teil (France) earthquake

1458

1459 The manuscript is a research study devoted to carry out a testing and validation study of  
1460 components involved in the seismic hazard and seismic risk estimation. The testing of  
1461 ground motion and damage to building is done using several models, observations of ground  
1462 shaking and observed damage from past earthquakes. The authors investigate if the  
1463 obtained scenarios are consistent with observations and the reason for the obtained  
1464 differences.

1465

1466 The topic of the paper is very interesting and suitable for the readers of the journal. However,  
1467 the title and the redaction of the manuscript do not help to get this goal. The focus on  
1468 European Seismic Hazard and Risk Models distracts from the very interesting part of the  
1469 manuscript.

1470

1471 The manuscript should be focused as a sensitivity study of the ground motion estimation and  
1472 damage estimation using different input models and how these are closest or not to the  
1473 observed data from Le Teil earthquake.

1474

1475 Therefore, each section must be introduced with the models that are going to be compared,  
1476 why are those comparisons going to be done in that section?.

1477

1478 Additionally, each comparison must be explained more in detail so the reader can see clearly  
1479 which models are kept constant and which are compared.

1480

1481 Finally, the author must try to rewrite the conclusions according to the comparisons they are  
1482 doing. My final recommendation is to reconsider the publication of the manuscript after major  
1483 revisions.

1484

1485 [We thank the reviewer for their positive and constructive comments. We agree that the topic](#)  
1486 [of the paper should lean more towards the comparison of various components of the damage](#)  
1487 [estimation \(rupture model, ground-motion model, exposure model, fragility model\) instead of](#)  
1488 [sticking strictly to the ESHM20 and ESRM20 framework.](#)

1489

1490 [We will clarify the nature and objective of the various comparisons by adding more details in](#)  
1491 [the Introduction \(addition of a Figure explaining the structure of the paper\) and new tables](#)  
1492 [detailing the various models and their assumptions \(see our answers to Comment 1\).](#)

1493

1494 [We will also enrich the Conclusions section with an account of our findings.](#)

1495

1496 [The answers to the reviewer's comments are detailed below.](#)

1497

1498 **REVIEWER 2 - MAIN COMMENTS**

1499

1499 The concept ShakeMap analysis is not clear. The authors cite Wald et al. 2022, but they  
1500 should explain better.

1501

1502 [Review round 1 reply](#)

1503

1504 [We will add a few lines to explain the concept of ShakeMap \(objective, algorithm, observations](#)  
1505 [used, etc.\). It should be noted that we have generated the shake-map ourselves, using our](#)  
1506 [specific configuration of the USGS ShakeMap software \(version 4\). The parameters related to](#)

1506 this shake-map are detailed in the last row of the following table that we propose to add (model  
1507 GM4):  
1508  
1509

GM Map ID	Type	GMM	Site model	Rupture model	Observations
GM1	ground-motion field	KothaEtAl2020 Site	BRGM soil classes to Vs30	Ritz et al.	No
GM2	ground-motion field	KothaEtAl2020 ESHM20Slope Geology	Slope & Geology (ESRM20 data)	Ritz et al.	No
GM3	ground-motion field	KothaEtAl2020 Site	ESRM20 Vs30 data	Ritz et al.	No
GM4	shake-map	KothaEtAl2020 Site	BRGM Soil class to Vs30	Ritz et al.	Seismic stations

1510  
1511 [Description of revision](#)  
1512 Lines 56-57 have been added explaining briefly what shake-map analyses are used for and  
1513 why they are used in this paper.  
1514

1515  
1516 **Line 62.** When describing the earthquake, you have to indicate also the registered  
1517 magnitude and focal depth. Also, they indicate a estimated near-faults PGAs with a 68%  
1518 confidence interval of 0.3-1.9g . Is this a range in the rupture area? Which is the size of the  
1519 rupture? How can you explain such a high attenuation because the at 15 km the recorded  
1520 PGA was only 0.04 g (that is a reduction of 77% of the PGA in 15 km if compared with 0.3g).  
1521

1522 [Review round 1 reply](#)  
1523 We will modify the sentence in order to specify the magnitude and focal depth (however, keep  
1524 in mind that several models have proposed different depths and magnitudes):  
1525 “The Le Teil earthquake took place on the 11th of November 2019, and its epicentre is located  
1526 at 44.518° N 4.671° E (Ritz et al., 2020), with a focal depth of 1 km and a magnitude Mw 4.9  
1527 (Ritz et al., 2020), in close proximity to the municipality of Le Teil and the town of Montélimar  
1528 in the Lower Rhône valley in France.”  
1529

1530 Causse et al. (2021) estimated a PGA with a 68 % confidence interval of 0.3-1.9 g in the fault  
1531 projection on ground surface.  
1532

1533 In the scenario calculations we use ruptures, whose size is equal to the median rupture area  
1534 given by the Wells and Coppersmith (1994) scaling law. In the case of the rupture model  
1535 according to the parameters based on Ritz et al. (2020), the area of the rupture model is equal  
1536 to 6.49 km<sup>2</sup>. The revised manuscript will include these details.  
1537

1538 The observed high attenuation of PGA is probably due to the very shallow rupture: the Le Teil  
1539 earthquake is a specific event, which generated very high large intensities right next to the  
1540 epicentre, however the ground motion attenuated very quickly.  
1541

1542 [Description of revision](#)  
1543 The manuscript has been revised (lines 86-88, 100-103, 94, 212-214).  
1544

1545  
1546 **Line 75.** Do not use number for macroseismic intensity, it is better to say VII-VIII instead 7-8  
1547

1548 In line 81, we mention a decimal intensity of 7.5 (this was mentioned as is in the publication by  
1549 Schlupp et al., 2022). In order to remain faithful to that publication and to be consistent, we  
1550 propose to keep numbers to express macroseismic intensity. For the sake of consistency, we  
1551 will also use “intensity 7” instead of “intensity VII” in line 79.

1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606

The use of numbers instead of letters for macroseismic intensity has been advocated by Musson et al. (2010).

Associated reference:

Musson, R. M., Grünthal, G., & Stucchi, M. (2010). The comparison of macroseismic intensity scales. *Journal of Seismology*, 14, 413-428.

**Line 110.** Regarding the test based on the intensity of the seismic ground motion. The authors compare the different scenarios pointing that the lowest PGA and Sa0.3s must be due to differences in the rupture distance but they do not say anything about which scenarios is closest to the observed ground motion. Which models fit better the observations?

[Review round 1 reply](#)

It is very difficult to compare the models with measured observations (i.e., recordings of seismic stations), since such measures are very sparse (the nearest station is around 15km from the epicentre). Therefore, in the absence of measures in the epicentral area, it is difficult to compare the effects of different rupture distances in this area to measured ground-motions (this is where the relative differences in rupture distance are the largest, as they are greatly reduced further away from the epicentre). This is why we use macroseismic intensity (precise estimates obtained from field surveys) for the comparison. We will add a couple of sentences of explanations on this issue in the text.

[Description of revision](#)

Lines 360-365 have been added to the manuscript.

**Line 160.** Regarding the test based on the macroseismic intensity. I do not understand what the authors are trying to demonstrate. If you are using correlations from Ground Motion to Intensity the results that you are going to obtain should be similar to the obtained in the previous section. If the idea is to see which is the best GMICEs for the region, then using only those scenarios is not enough, the authors should look for the most recent correlation (using a higher number of observations ground motions and macroseismic intensity) and simply use that relationship with the corresponding standard deviation and probably the observed intensity at Le Tail will be in that range.

[Review round 1 reply](#)

Thank you for this comment. The comparisons based on the macroseismic intensity serve the purpose of selecting one rupture to use in subsequent comparison. This will be clarified in the revised manuscript.

[Description of revision](#)

This is clarified in lines 359-360.

**Line 209.** Estimation of damage using different risk analysis tools

Here the authors compare the damage results using Armagedom and OpenQuake but the section should be explained better. As far as I understand the damage obtained with Armagedom is obtained using the ground motion modelled by the deterministic scenarios (all of used in the previous sections?, one of them?) and the semi-empirical macroseismic method, but regarding Openquake the authors indicate the use the ESHM20 ground motion logic tree (is this meaning you are comparing damage using a deterministic scenarios with damage from a probabilistic hazard map? It sound strange to me. Can you clarify?

1607 [Review round 1 reply](#)  
1608 For the estimation of damages, Armagedom uses a ground motion or a macroseismic intensity  
1609 map. This map can be modelled either for a deterministic scenario (magnitude, epicentre,  
1610 ground-motion models), by numerical simulation or by a probabilistic procedure (probabilistic  
1611 hazard map). The ground motion map can be derived by Armagedom or can be uploaded from  
1612 the output of other softwares (ShakeMap, OpenQuake hazard module, etc.). The acceleration  
1613 ground-motion map must then be converted to macroseismic intensity with a GMICE. In  
1614 addition, an observed macroseismic intensity map can also directly be used for damage  
1615 estimation with Armagedom.

1616  
1617 As you well understood, the intensity map is used with the RISK-UE semi-empirical  
1618 macroseismic method for damage calculation (hence the need for intensity map).  
1619

1620 The calculation with OpenQuake is not a classical PSHA. It is a scenario calculation, where  
1621 the rupture is deterministically defined. Although a ground motion logic tree can be used in  
1622 combination with a deterministically defined rupture, we do not use any ground motion logic  
1623 trees, we only use a single GMPE.  
1624

#### 1625 [Description of revision](#)

1626 The calculation with Armagedom is now compared to the damage scenario DS1.  
1627

1628  
1629 Which is the method used in OPENQUAKE for the damage estimation is also the same used  
1630 in Armagedom? Is it a different method? You have explained how this is done to be sure that  
1631 you can compare the results.  
1632

#### 1633 [Review round 1 reply](#)

1634 OpenQuake and Armagedom use different methods for the damage estimation.  
1635

1636 As mentioned previously, Armagedom uses the RISK-UE semi-empirical macroseismic  
1637 method. This is based on the intensity values and a vulnerability index for the calculation of  
1638 the mean damage degree for the beta distribution.  
1639

1640 OpenQuake uses ground motion intensities and fragility curves.  
1641

1642 The two methods are obviously different, but, no matter what their path, the results of both  
1643 methods have the same aim: asses the damages after an earthquake. Considering this same  
1644 objective, the results from the two methods can be compared.  
1645

1646 Nevertheless, we agree with your comment, and we will add a paragraph to summarise both  
1647 methods.  
1648

1649 A few articles attempt to address the issue (e.g. Lestuzzi et al. 2016).  
1650 Lestuzzi, P., Podestà, S., Luchini, C. et al. Seismic vulnerability assessment at urban scale  
1651 for two typical Swiss cities using Risk-UE methodology. Nat Hazards 84, 249–269 (2016).  
1652 <https://doi.org/10.1007/s11069-016-2420-z>  
1653

#### 1654 [Description of revision](#)

1655 The method used in Armagedom is described in lines 521-532.  
1656  
1657

1658 **Line 237.** Regarding the Damage based on observations. Again, this is rather difficult to  
1659 understand. The paragraph starts speaking about test related to vulnerability and risk  
1660 modelling, but the conclusion of the paragraph is simply a table assigning building  
1661 taxonomies to the building database. If the author wants to create different taxonomies to



1662 their database, they should name the section: Vulnerability estimation or something related  
1663 to that.

1664  
1665 [Review round 1 reply](#)

1666 We understand the remark of the reviewer. Yes, the name of the Section is not adequate, and  
1667 this will be changed in the revised manuscript.

1668  
1669 We do not want to create different (new) taxonomies to our database, we just want to assign,  
1670 based on the structural information in the AFPS forms, the building in the existing taxonomies  
1671 (both RISKUE and ESRM20 building classes). The names of these two taxonomies are  
1672 different but there is a real physical correspondence between these two typologies, based on  
1673 the construction code, construction material, load-bearing resistant system, etc.).

1674  
1675 [Description of revision](#)

1676 The estimations based on the observations are described in the revised section 2.2 “Post-  
1677 seismic emergency diagnoses dataset”.

1678  
1679  
1680 **Line 248.** Regarding Estimated damage based on a “building-by-building” Here the authors,  
1681 compare the building-by-building damage results using OPENQUAKE when using Ritz et al.  
1682 scenario and Shakemap analysis (try to find a better name for this). Initially those analysis  
1683 use the same Vs30 model and they also include a new Vs30 model (named ESHM20 Vs30)  
1684 to the Ritz et al. scenario. Again, this is very messy. If you want to compare the influence of  
1685 the ground motion scenario, it is clear the comparison between Ritz and Shakemap using the  
1686 same Vs30 model but if you want to compare the Vs30 influence you should also include the  
1687 Shakemap scenario with the ESHM20 Vs30 model to be consistent.

1688  
1689 [Review round 1 reply](#)

1690 We agree that our presentation of the various comparisons in the submitted manuscript is  
1691 unclear. We will revise the nomenclature and we will clarify the assumptions behind each  
1692 scenario, using a table like this:

1693

GM Map ID	Type	GMM	Site model	Rupture model	Observations
GM1	ground-motion field	KothaEtAl2020 Site	BRGM soil classes to Vs30	Ritz et al.	No
GM2	ground-motion field	KothaEtAl2020 ESHM20Slope Geology	Slope & Geology (ESRM20 data)	Ritz et al.	No
GM3	ground-motion field	KothaEtAl2020 Site	ESRM20 Vs30 data	Ritz et al.	No
GM4	shake-map	KothaEtAl2020 Site	BRGM Soil class to Vs30	Ritz et al.	Seismic stations

1694

1695 [Description of revision](#)

1696 The section on the estimations using the “building-by-building” exposure model has been  
1697 revised (Section 5.1) and includes the table above (Table 5-1).

1698  
1699 **Line 287.** Regarding Estimated damage based on aggregated exposure model. Here the  
1700 authors carry out many different comparisons. Again, it is very messy, and it is not clear why  
1701 you are doing it and what are you looking for.

1702  
1703 [Review round 1 reply](#)

1704 Again, we will take greater care of explaining these various comparisons. We propose to add  
1705 the following table to summarize the different damage estimation models:

1706

Damage scenario ID	GM Map ID	Exposure model
DS1	GM1	BRGM exposure
DS2	GM1	ESRM20 exposure
DS3	GM2	BRGM exposure
DS4	GM2	ESRM20 exposure
DS5	GM3	BRGM exposure
DS6	GM3	ESRM20 exposure
DS7	GM4	BRGM exposure
DS8	GM4	ESRM20 exposure

1707  
1708  
1709  
1710

These damage scenarios can then be compared to the damage “observations” DD2 and DD3, as introduced in the following table:

Observed Damage Data ID	Exposure resolution	Exposure data	Damage estimation method	Damage conversion method	
DD1	Building-by-building (327 buildings)	AFPS emergency survey	AFPS emergency observations on 327 buildings (Green / Yellow / Red tags)	Conversion to EMS-98 damage grades (Tab. 2.1)	Related to Fig. 4
DD2	Infra-municipality districts (2778 buildings)	National statistics database (BRGM-CCR)	AFPS emergency observations on 327 buildings (Green / Yellow / Red tags) + “Extrapolation”	Conversion to EMS-98 damage grades with expert judgment (Tab. 3.6)	Related to Fig. 5
DD3	Infra-municipality districts (2778 buildings)	National statistics database (BRGM-CCR)	AFPS emergency observations on 327 buildings (Green/Yellow/Red tags) + “Extrapolation”	Conversion to EMS-98 damage grades (Tab. 2.1) + Bias adjustment on total number of 2778 buildings (accounting for non-surveyed buildings)	Related to Fig. 5

1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732

#### Description of revision

In the revised manuscript, the damage estimations based on the aggregated exposure models are presented in Section 5.2. The aggregated exposure models are described in Section 3.2. The tables above have been added (Tables 2-3, 5-2).

**Conclusions:** The first conclusion is that the FM2010 model is the best to estimate macroseismic intensity since it is closer to Schlupp et al. (2022). Is this the model used in your national seismic hazard maps or shakemaps to convert from ground motion to macroseismic intensity? Is it only appropriate for the Le Teil region?

#### Review round 1 reply

The national seismic hazard map is not based on the use of GMICE. In mainland France, the “official” shake-map generated by BCSF uses the GMICE by Caprio et al. (2015). We will add a sentence of discussion on this.

#### Description of revision

This subject is no longer part of the conclusions.

1733 Along the paper you have made multiple comparison, so it would be nice if the conclusions  
1734 also indicate the main conclusion about those comparisons. At the moment, 11 lines are  
1735 conclusions regarding the ground motion comparisons (sections 3.1 and 3.2) and 11 lines  
1736 are conclusions regarding the rest of comparisons (3.3.1 to 3.3.4).

1737

1738 [Review round 1 reply](#)

1739 We will add a paragraph of main conclusions in the Conclusions section. This comment is also  
1740 in line with a remark from Reviewer 1.

1741

1742 [Description of revision](#)

1743 A paragraph has been added to the conclusions (lines 568-578).