



Research and application of flexible measuring array for deep displacement of landslide

Yang Li^{1,2}, Zhong Li^{1,2}, Qifeng Guo^{1,2}, Yimin Liu⁴, Daji Zhang^{3*}

¹Institute of Exploration Technology, CGS, Chengdu, 611734, China

5 ²Technology innovation center for risk prevention and mitigation of geohazard, Ministry of Natural Resources, Chengdu 611734, China

³Chengdu Rail Transit Group Co., Ltd., Chengdu, 610036, China

⁴Chengdu Technological University, Chengdu, 611730, China

Correspondence to: Daji Zhang (77302709@qq.com)

10 **Abstract.** The multi-dimensional and multi-sliding surface measurement of deep-seated displacement on landslides poses a significant technical challenge in landslide monitoring and early warning. The fixed borehole inclinometer serves as an important measurement method based on drilling for this purpose. In this study, a novel flexible measurement array for deep-seated landslide displacement and its installation and measurement process were developed, enabling higher accuracy in full-hole multi-dimensional deformation measurement. The measurement array consists of individual measurement probes as
15 basic units, connected in series through coaxial cables and high-pressure rubber hoses, forming a flexible measurement array. Each probe is equipped with acceleration and magnetic field sensors, allowing for the measurement of borehole inclination and azimuth angles and providing a more comprehensive understanding of the deformation of deep-seated landslide. This flexible measurement array resolves the limitations of traditional fixed inclinometers, such as limited probe quantity or inaccurate installation positions that fail to reflect the deformation trend of the landslide body. Moreover, it eliminates the
20 need for auxiliary installation accessories like pulleys and inclinometer pipes, simplifying the mechanical structure and installation process, which represents an advancement in methodology and an improvement in measurement techniques. This array provides a more comprehensive and improved monitoring tool for disaster prevention and mitigation, thereby enhancing the level of geological hazard monitoring and early warning technology.

25 **KEY words:** Landslide monitoring, deep displacement, multi-dimensional, flexible measurement, disaster prevention and mitigation.

1 Introduction

China is a vast country with a complex geological structure, which is also characterized by its mountainous terrain, with mountainous areas accounting for approximately two-thirds of the total land area. (Li et al., 2004; Liu et al., 2022). Within these mountainous regions, the primary manifestations of natural disasters are landslides and slope failures. Due to their



30 unique characteristics and sudden occurrence, landslides and slope failures often result in significant losses to the natural environment, human lives and properties, as well as engineering infrastructure (Liu, 2012).

In China, for instance, an annual report (China Institute of Geo-Environment Monitoring 2022) shows that, Types of geological disasters in 2022, including 3919 landslides, 1366 collapses, 202 debris flows, 153 ground subsidences, 4 ground fissures, and 15 ground subsidences. A total of 90 people were killed, 16 were missing and 34 were injured, caused direct
35 economic losses of 1.5 billion yuan.

Therefore, the general monitoring method for mountain landslide and collapse involves placing measuring instruments or equipment for landslides and collapses at the field site and its surrounding area, and conducting continuous or periodic measurements (Zhou, 2004). The purpose of achieving measurements of landslides, collapses, and other phenomena through
40 field automation monitoring is to accurately determine the planar coordinates, elevation, or three-dimensional relative displacement values of the monitoring network and deformation monitoring points. By employing appropriate data processing, dynamic data such as horizontal displacement, vertical displacement, relative displacement of cracks and sliding zones are provided for the monitoring network and deformation monitoring points. These data serve the purpose of understanding the deformation patterns of landslides, predicting hazards, evaluating disaster prevention and control measures, and providing support for relevant departments and government decision-making. (Stark et al., 2005; Yin and Wu, 2012; Li
45 et al., 2016).

In terms of methods for monitoring deep-seated landslide displacement, the mainstream approaches both domestically and internationally primarily involve the use of automatic or fixed borehole inclinometers (Stark and Choi, 2008; Li et al., 2015; Giuseppe et al., 2020). These methods employ inclinometers installed in boreholes to monitor the sliding locations of deep-seated landslide bodies, capturing the horizontal displacement, sliding velocity, and intermittent sliding of the landslide
50 (Sarolkar et al., 2022). The deformation of deep-seated relative displacement precedes surface displacement, and the two are closely related. Monitoring the deformation of deep-seated relative displacement enables early prediction of landslide stability. The schematic diagram of the measurement is shown in Figure 1.




Figure 1: A measurement method for deep-seated landslide displacement based on fixed borehole inclinometers.

55 In academia, extensive research and practical work have been conducted by domestic and international scholars on the design of borehole inclinometers for measuring deep-seated landslide displacement. As early as 1992, the University of British Columbia (UBC) developed a prototype inclinometer that employs a three-component fluxgate magnetometer to obtain a compass bearing, presented a unified theory of data interpretation that can be applied to all inclinometers, discussed the application of the theory to the UBC inclinometer (Erik and Garry, 1992). Zhou et al. (Zhou et al, 2013) developed a



60 deep-seated landslide displacement monitoring instrument that measures torsional orientation. The instrument utilizes
triaxial accelerometers and magnetoresistive sensors to track and monitor the entire sliding process of landslides. Real-time
data transmission is achieved through GPRS technology. Giuseppe et al. (Giuseppe et al, 2020) presented a low-cost multi-
module fixed inclinometer for continuous landslide monitoring. The displacement measurement accuracy of the inclinometer
can reach 0.37% of its total length, and linear testing demonstrated a high linearity within a tilt angle range of $\pm 20^\circ$. Vassallo
65 et al (Vassallo et al ,2020) demonstrated long-term displacement monitoring using a fixed inclinometer and GPS integrated
system, comparing the results with PS-InSAR data to explore the relationship between deep-seated and surface
displacements of landslides.

Based on literature review and practical experience, several limitations of using borehole inclinometers for monitoring deep-
seated landslide displacement can be identified:

70 (1). Limited monitoring range: Traditional borehole inclinometers, due to their limited number of probes or inaccurate
installation positions, typically only capture localized displacement changes within the borehole, resulting in a relatively
small monitoring range. It may be challenging to comprehensively and accurately monitor large-scale landslides or internal
displacement within landslide bodies.

(2). Complex installation process: Traditional fixed borehole inclinometers require the assistance of inclinometer pipes for
75 measurements. The inclinometer pipes are fixed and installed inside the landslide body, often utilizing pulleys designed on
the inclinometer to position the probe by rolling in the positioning groove of the inclinometer pipe. This process demands
high precision during the connection of the positioning groove, significantly increasing the difficulty of instrument
installation.

(3). Insufficiency in azimuth measurement: Inevitably, inclinometer pipes introduce a torsional angle during the connection
80 process. Traditional inclinometers can only measure the inclination angle but not the torsional angle, leading to measurement
errors.

In conclusion, although borehole inclinometers have certain application value in monitoring deep-seated landslide
displacement, their limitations in terms of monitoring range, complex installation process, susceptibility to interference, and
difficulty in obtaining azimuth angle data necessitate upgrades and improvements to better meet the requirements of
85 geological hazard monitoring and early warning technology.

2 System Configuration

2.1 System composition

The flexible measurement array for deep-seated landslide displacement consists of individual measurement probes as the
basic units, connected to each other through cables and high-pressure rubber hoses (as shown in Figure 2). The high-pressure
90 rubber hoses ensure a significant degree of flexibility and bending capability between the probes, allowing for a better match
with the deformation of the borehole. The instrument cables of the nodes pass through hollow rubber hoses, maintaining a



single cable connection from start to finish. The nodes can be connected in series as needed to meet different measurement requirements at various depths. From an external perspective, it appears as a cable line connected to a long string of probes. The four-core cable consists of power supply lines and a 485 bus. The internal probes are all connected to the 485 bus for data transmission. Each probe is equipped with a three-axis accelerometer module and a geomagnetic module, connected to an STM32 series microcontroller through the SPI bus. The data acquisition host controls the STM32 microcontroller via the 485 bus to simultaneously collect incline and azimuth angle data.

This instrument serves as a flexible inclinometer array capable of obtaining full-hole incline data from the bottom to the top of the borehole. It can be customized according to the depth of the borehole to achieve a perfect match. With acceleration and magnetic field sensors installed in each probe, the incline angle and direction of the borehole can be measured, allowing users to gain a more comprehensive understanding of the deformation of deep-seated landslide displacement.



Figure 2: Schematic diagram of continuous full-hole inclinometer probe configuration.

2.2 Technical parameters

The main technical parameters of the flexible measurement array for deep-seated landslide displacement are shown in Table 1.

Table 1. Technical Specifications Table

technical indicators	parameter values
Accuracy	Vertical angle: 0.1%F·S, Azimuth angle: 1%F·S
Resolution	0.1°
Measuring Range	Vertical angle: ±90°, Azimuth angle: 0-360°
Power Supply Voltage	9~24V
Standby Current	50μA
Intelligent Data Acquisition Method	Adaptive encryption based on large deformation threshold
Probe Pressure	5Mpa

3 The measurement principle

110 3.1 Principle of deep displacement measurement

Based on the structural characteristics of the flexible measurement array described in Chapter 2, the measurement principle of deep-seated displacement is illustrated in Figure 3, as mentioned in the previous chapter.




Figure 3: The measurement principle.

115 As shown in Figure 3, the full-hole inclinometer measures the angle θ_i between the inclinometer casing and the vertical line at each section along the PVC pipe using the inclinometer spacing L . The horizontal displacement d_i at different elevations is then calculated using Equation (1):

$$d_i = L \sin \theta_i \quad (1)$$

By incrementally summing from the bottom measurement point of the inclinometer pipe, the actual horizontal displacement, 120 denoted as b_i , at any elevation can be obtained, as shown in Equation (2):

$$b_i = \sum_{j=1}^i d_j \quad (2)$$

The accumulated horizontal displacement at the mouth of the inclinometer pipe is denoted as B :

$$B = \sum_{i=1}^n d_i \quad (3)$$

125 Based on the angle and direction data obtained from each probe, the variation of horizontal displacement at different depths along the axis of the inclinometer pipe can be determined. In the above equation, d_i represents the horizontal displacement of the measurement section; L denotes the segmented length of the measurement point, which is the instrument spacing; θ_i represents the angle between the inclinometer pipe and the vertical line for the measurement section; b_i represents the



horizontal displacement of the i -th measurement point starting from the bottom of the hole; B represents the horizontal displacement at the mouth of the current measurement pipe; n represents the number of segments for the monitoring hole, where $n=H/L$, and H is the depth of the hole.

3.2 Calculation of crown footing and azimuth angles

The flexible inclinometer sensor adopts a triaxial accelerometer and a triaxial magnetic sensor, forming a dual triaxial (X , Y , Z) system. The axes of the accelerometer and magnetic sensor are parallel, with the Z -axis pointing downward along the instrument axis, while the X and Y axes lie in the plane perpendicular to the instrument axis. The coordinate system for top foot measurement is illustrated in Figure 4.




Figure 4: Vertex angle measurement coordinate system.

By using the components of gravity acceleration g sensed by the accelerometer and the components of the magnetic field sensed by the magnetic sensor, the values of borehole inclination and azimuth angles at the instrument's location can be calculated according to Equation (3) and (4) (Liu, 2016).

$$\alpha = \arctan \frac{g(\alpha_y H_x - \alpha_x H_y)}{H_z(\alpha_x^2 + \alpha_y^2) + \alpha_z(\alpha_x H_x + \alpha_y H_y)} \quad (3)$$

$$\theta = \arctan \frac{\sqrt{a_x^2 + a_y^2}}{a_z} \quad (4)$$



In the equation: a_x —The output value of the X-axis accelerometer ; a_y —The output value of the Y-axis
accelerometer ; a_z —The output value of the Z-axis accelerometer ; H_x —Magnetic flux gate (or magnetic resistance)
145 output value along the X-axis; ; H_y —Magnetic flux gate (or magnetic resistance) output value along the Y-axis ; H_z —
Magnetic flux gate (or magnetic resistance) output value along the Z-axis ; g —Value of gravitational acceleration ,
$$g = \sqrt{a_x^2 + a_y^2 + a_z^2} .$$

4 The production and installation process

The installation process of the measurement array mainly involves procedures such as indoor installation, adjustment,
150 performance testing, and assembly.

4.1 Sensor deployment

(1) First, prepare the installation equipment, tools, sensors, sensor mounting plates, flexible connectors, pressure-resistant
outer pipes, sealing rings, connecting wires, non-magnetic screws, etc. required for sensor installation (see Figure 5).



155 **Figure 5: Sensor installation accessories.**

(2) Stepwise installation of sensors


First, place the sealing ring on the connector, then attach the sensor mounting plate to the connector, and secure the sensors
to the mounting plate using screws. Finally, solder the four connecting wires (see Figure 6).



160 **Figure 6: Sensors installation.**

4.2 Sensor calibration

The sensors can be assembled into the configuration shown in Figure 7 for sensor calibration. As shown in Figure 8, the sensors are then clamped onto the HZT-60 inclinometer calibration table (Li et al., 2015), and calibration is performed for zenith angles and azimuth angles at 16 different positions.



165 **Figure 7: Assembled sensors.**



Figure 8: HZT-60 inclinometer calibration table.

4.3 The interconnection of sensors

- 170 After calibrating each sensor, the sensors are sequentially connected using high-strength flexible connectors to form a complete instrument assembly (as shown in Figure 9).




Figure 9: A complete instrument assembly.

5 Field experiment

175 5.1 Experimental objective

A demonstration site for monitoring deep-seated landslide displacement was established in Baiyan 3 Group, Lujiang Town, Baoshan City, Yunnan Province, using the flexible measurement array for deep-seated displacement. The main objectives of this field experiment were as follows:

(1) Testing the reliability of flexible joint connections:

180 In the field experiment, the flexible measurement array was installed in a borehole with a depth of 25.4 meters, and a $\varnothing 50$ PVC pipe was used for fixation inside the borehole. The instrument, consisting of 14 sensors, was connected through flexible high-strength joints. The first sensor was placed at a depth of 4 meters inside the borehole, while the fourteenth sensor was positioned at 11 meters. After the instrument was properly set up, the PVC pipe was filled with fine sand. The experiment confirmed the normal functioning of the instrument, demonstrating the feasibility of this connection method.

185 (2) Testing the installation orientation of the measurement array inside the borehole:



Due to the inherent connection errors, the orientations of the 14 sensors may not be perfectly aligned. However, once the sensors are fixed inside the borehole, their orientations remain fixed. Any deformation or displacement of the landslide will result in changes in the sensor readings and orientations. By analyzing these changes, the distance and direction of the landslide movement can be determined.

190 (3) Testing the reliability of the measurement array in a damp environment inside the borehole:


The borehole environment tends to be cool and humid, and although the instrument is sealed, there may still be moisture inside the instrument probe, which could potentially corrode electronic components. The reliability of the instrument in such conditions needs to be evaluated over time.

(4) Testing the stability and durability of the measurement array powered by a battery in the field:

195 Due to limitations in power supply options and safety considerations, the instrument cannot be powered by 220V AC electricity in the field. Instead, a 12V battery is used, which is charged by a solar panel. After a period of operation, the stability and durability of the instrument under battery power in the field are evaluated and assessed.

5.2 Installation method

200 In this field experiment, the installation schematic of the flexible measurement array is shown in Figure 10. The flexible measurement array is fixed at the predetermined depth position using wellhead steel wire ropes and then filled with drilling mud to achieve coupling between the measurement array and the rock wall. The measurement data is transmitted through cables to the wellhead data acquisition device, which packages and organizes the data before sending it to the server. The wellhead is equipped with a solar charger to provide power for the underground measurement array and the wellhead data acquisition device.



205

Figure 10: Schematic diagram of field experiment installation.

5.3 Data analysis




Figure 11: The data curves reveals that from March to May 2021.

210 After the installation and commissioning of the equipment, the project team initiated the automated monitoring and early warning work. The average value of the data transmitted by the equipment on the first day was taken as the initial data, and

subsequent data points were extracted at typical time intervals based on the deformation conditions for the purpose of constructing deformation curves.

As shown in Figure 11, analysis of the data curves reveals that from March to May 2021, there was minimal deformation in the deep-seated displacement of the landslide. However, during the flood season, a deformation of approximately 10mm occurred between depths of 5.5m and 8m on the slope. This was followed by an accumulated deformation of 23mm until September 11th. Subsequently, the deformation gradually converged. The increasing displacement observed between depths of 5.5m and 8m indicates movement along the main sliding direction of the landslide. Conversely, a decrease in displacement was observed between depths of 4m and 5.5m due to the shifting movement of the sliding zone at 5.5m. Below 5.5m, the sensors recorded movement along the main sliding direction, while above 5.5m, the sensors detected a reverse inclination caused by the movement of the sliding zone, leading to a decrease in measured displacement by the upper sensors. This method of analyzing the deep-seated displacement curve serves as a primary means to identify the position of the sliding zone.

Based on the deformation curve, it can be concluded that there is a distinct sliding zone between depths of 5.5m and 8m in the landslide. Additionally, notable displacement variations occurred during the flood season. This variation aligns with the concentrated rainfall in the region where the landslide is located, confirming that rainfall is the main triggering factor for the landslide. The deformation curve further demonstrates the accurate monitoring capability of the flexible measurement array for deep-seated landslide displacement, surpassing traditional devices with a limited number of sensors. It provides a more precise and comprehensive measurement of displacement variations throughout the entire borehole depth.

6 Conclusion

The multi-dimensional, multi-sliding surface measurement of deep-seated displacement on landslides poses a significant technical challenge in landslide monitoring and early warning. This study developed a flexible measurement array capable of measuring the deep-seated displacement of landslides in full boreholes. It incorporates an azimuth measurement module, eliminating the need for traditional inclinometer pipes and pulley components for auxiliary installation. This advancement greatly enhances cost-effectiveness and measurement accuracy. The maximum measuring range for inclination angle is $\pm 90^\circ$, with an accuracy of 0.1% F·S, while the accuracy for azimuth angle measurement is 1% F·S.

The flexible measurement array for deep-seated landslide displacement can be widely applied to the monitoring of slope stability, landslide bodies, embankments, highways, and impermeable walls, capturing inclinations, horizontal displacements, and settlement deformations. When combined with automated data acquisition equipment, continuous monitoring can be conducted automatically. Additionally, by installing multiple sensor arrays, the displacement magnitudes and displacement orientation curves of multiple measurement points can be obtained. This flexible measurement array overcomes the limitations of traditional fixed inclinometers, such as limited probe quantity or inaccurate installation positions that fail to reflect the deformation trend of the landslide body. Moreover, it eliminates the need for auxiliary installation accessories like



245 pulleys and inclinometer pipes, simplifying the mechanical structure and installation process. This advancement represents an improvement in both the technology and measurement methods, providing a more comprehensive and enhanced monitoring tool for disaster prevention and mitigation, thereby elevating the level of geological hazard monitoring and early warning technology.

Competing interests

The contact author has declared that none of the authors has any competing interests.

250 References

- Erik W.B. and Garry K.C.: Interpretation of borehole-inclinometer data: a general theory applied to a new instrument, *Journal of Glaciology*, 38(128):113-124, DOI: 10.3189/S002214300009655, 1992.
- Giuseppe R., Luigi G., Paola R., and Francesco M.: A Multi-Module Fixed Inclinometer for Continuous Monitoring of Landslides: Design, Development, and Laboratory Testing, *Sensors*, 20(11): 1-19, DOI: 10.3390/s20113318, 2020.
- 255 Li Y., Meng H., Dong Y., and Hu S.: Main Types and characteristics of geo-hazard in China —Based on the results of geo-hazard survey in 290 counties, *The Chinese Journal of Geological Hazard and Control*, 15(2): 29-34, DOI: 10.3969/j.issn.1003-8035.2004.02.005, 2004 (in Chinese with English abstract).
- Li Y.; Fu P.; Li Z., Li X., and Lin Z.: Biaxial angle sensor calibration method based on artificial neural network, *Chemical Engineering Transactions*, (46):361-366, DOI:10.3303/CET1546061, 2015.
- 260 Li Y.; Fu P.; Ji W.; Shi S.; Zhang Y.; and Zhang T.: Predictive method of nonlinear system based on artificial neural network and SVM, *Oxidation Communications*, 39(1A): 1226-1235, 2016;
- Liu C.: Theory and practice of prevention and control of major geological disasters, *The Chinese Journal of Geological Hazard and Control*, 23(1):126-126, DOI: CNKI:SUN:ZGDH.0.2012-01-028, 2012 (in Chinese with English abstract).
- Liu C., SHEN W., and Huang S.: Some Viewpoints on Strategies in Risk Reduction of Geological Disasters in China, *Journal of Catastrophology*, 37(3): 1-4, DOI: 10.17993/3comp.2023.120151.186-205, 2022 (in Chinese with English abstract).
- 265 Liu Y.: Design of the Drilling Trajectory Measurement Device in Ultra-high Temperature based on FOG and its Key Technologies Research, Sichuan university, 2016.
- Ministry of Natural Resources of the People's Republic of China.: China Institute of Geo-Environment Monitoring (2022)
- 270 Bulletin of geologic hazards from January to December in 2022. China Institute of Geo-Environment Monitoring, Beijing, 2022.
- Sarolkar, P.: Disasters and Hazards: Risk Reduction, Mitigation and Management, *Journal of Geosciences Research*. 7. 10.56153/g19088-022-0002-r, 2022.



- Stark T.D. and Choi H.: Slope inclinometers for landslides, *Landslides*, 2008(3):1-5, 2008.
- 275 Stark T.D., Arellano W.D., Hillman R.P., Hughes R.M., Joyal N., Hillebrandt D.: Effect of Toe Excavation on a Deep Bedrock Landslide, *Journal of Performance of Constructed Facilities*, 19(3):244-255, DOI: 10.1061/(ASCE)0887-3828(2005)19:3(244) , 2005.
- Vassallo R., Calcaterra S., Rosa J.D., Maio C.D., and Gambino P.: Long-Term Displacement Monitoring of Slow Earthflows by Inclinometers and GPS, and Wide Area Surveillance by COSMO-SkyMed Data, *Geosciences*, 10(5):171, DOI: 280 10.3390/geosciences10050171, 2020.
- Yin Y. and Wu S.: Research on landslide monitoring, early warning and emergency prevention technology, Beijing: Science Press, 2012 (in Chinese).
- Zhou C., Liu Y., and Chen W.: Development of Deep Landslide Displacement Monitoring Instrument with the Function of Torsion Direction Measurement, *Drilling Engineering*,40(7):5-7, DOI: 10.3969/j.issn.1672-7428.2013.07.003, 2013 (in 285 Chinese with English abstract).
- Zhou P.: Indicator system and techniques of landslide monitoring, *Journal of Geomechanics*, 10(1): 19-26, DOI: 10.3969/j.issn.1006-6616.2004.01.003, 2004 (in Chinese with English abstract).