



A hybrid data-driven approach to analyze the drivers of lake level dynamics

Márk Somogyvári¹, Dieter Scherer², Frederik Bart², Ute Fehrenbach², Akpona Okujeni^{1,3} and Tobias Krueger¹

5

¹Integrative Research Institute on Transformations of Human-Environment Systems (IRI THESys), Humboldt-Universität zu Berlin, Berlin, 12489, Germany

²Chair of Climatology, Institute of Ecology, Technische Universität Berlin, Berlin, 12165, Germany

³Earth Observation Lab, Geography Department, Humboldt-Universität zu Berlin, Berlin, 12489, Germany

10

Correspondence to: Márk Somogyvári (mark.somogyvari@hu-berlin.de)

Abstract. Lakes are directly exposed to climate variations, as their recharge processes are driven by precipitation and evapotranspiration, and indirectly via groundwater trends, changing ecosystems and changing water use.

In this study, we present a downward model development approach that uses models of increasing complexity to identify and quantify the dependence of lake level variations on climatic and other factors. The presented methodology uses high-resolution gridded weather data inputs that were obtained from dynamically downscaled ERA5 reanalysis data. Previously missing fluxes and previously unknown turning points in the system behavior are identified via a water balance model. The detailed lake level response to weather events is analyzed by calibrating data-driven models over different segments of the data timeseries. Changes in lake level dynamics are then inferred from the parameters and simulations of these models.

The methodology is developed and presented on the example of the Groß Glienicke Lake, a groundwater-fed lake in eastern Germany, that has been experiencing increasing water loss in the last half century. We show that lake dynamics were mainly controlled by climatic variations in this period, and we identified two different phases with systematic differences in behavior. The increasing water loss during the last decade, however, cannot be accounted for by climate change. Our analysis suggests that this alteration is caused by the combination of regional groundwater decline and vegetation growth in the catchment area, with some additional impact from changes in the local rainwater infrastructure.

25

1 Introduction

One of the most visible effects of climate change in recent years has been the decline of surface water levels, especially in lakes (Woolway et al., 2020). However, not all lakes react to changes in climate in the same way; some are more exposed to climate variations, while others are more exposed to anthropogenic effects (Mason et al., 1994). Understanding the drivers and their importance on lake level dynamics is thus essential for the development of mitigation measures or conservation strategies. The response of lake levels to changing meteorological conditions has been a focus of research for many decades, but in recent years an increased interest in water availability has broadened this research topic with more and more cases waiting for practical solutions (Kebede et al., 2006; Schulz et al., 2020; Getachew et al., 2021; Woolway et al., 2020). This broadened interest often comes with the challenge of limited data availability, especially in remote areas or at the beginning of research campaigns (Woolway et al., 2020; Altunkaynak, 2007; Solomatine and Ostfeld, 2008). Hence a practical approach that can work in such conditions is needed.

We here revisit the downward model development approach of (Sivapalan et al., 2003) as a way of tailoring hydrological models to the data availability. Downward model development starts from large scale, low complexity models and then progresses to the smaller-scale processes (Hrachowitz and Clark, 2017). We demonstrate that such downward model

40



development approach is suitable for lake system understanding, with the goal of identifying the key drivers of lake level dynamics. In our case, these drivers may be climatic variations, changes in natural water fluxes due to land cover changes or groundwater trends, but also changes in water use and water infrastructure. We propose a hybrid data-driven methodology, where the system understanding gained at a specific level of model complexity is used for the design of the higher-complexity
45 models. We start with a water balance model, which then informs the development of a linear regression model operating on higher temporal resolution. The development may then continue with nonlinear models (e.g. artificial neural networks) or with the higher resolution models of the catchment. The downward modeling can also fit organically into the development of process-based models, as will be shown.

Water balance modeling, as in our case, is often an initial step in understanding hydrological systems. Water balance models
50 do not require a complete system understanding to function properly (Xu and Singh, 1998), but can very well capture the macro-scale behavior of the system based on a set of in- and outfluxes. On a monthly timescale, these models only need a handful of hydrological variables, hence will often work in data-scarce cases.

(Mason et al., 1994) used water balance modeling to simulate the responses of the largest closed lakes around the globe and showed that lakes act as natural lowpass filters over any sudden variation in aridity. (Crapper et al., 1996) used such models
55 to predict future levels of the Goran lake in Australia by taking the cumulative sum of the predicted storage change from the model. (Kebede et al., 2006) used a monthly water balance model at Lake Tana and identified that the main driver of lake level change was the variation in rainfall and not human-induced activities. (Schulz et al., 2020) showed that variations in the levels of Lake Urmia were mainly driven by climate, while local agricultural water extraction had little effect on the overall trend. However, the authors also showed that even without affecting the trend or even some dynamic variations, the abstractions
60 weakened the resilience of the lake to climatic changes and the lake levels could be stabilized by limiting abstraction rates.

The main issue of water balance modeling comes from its highly simplified nature; while these models are robust and easy to model with, they are very general and can overlook some of the details that could be relevant for the hydraulic system. One such issue is how to handle any time-lag between the inputs and the lake level changes. This issue is well known, (Langbein, 1961) already suggested to incorporate the time lag with geometric weight functions into a water balance model. However,
65 most studies tend to overlook this issue by simply modeling on coarser timescales (e.g. monthly, yearly).

At the other end of the complexity spectrum, process-based models are constructed via simulating the individual hydrological (physical) processes that affect the lake dynamics, including spatially and temporally differentiated inflows and outflows, lake bathymetry, weather effects, thermal or chemical forcing (Beletsky et al., 2013; Laval et al., 2003; Valipour et al., 2023). Process-based models can resolve the behavior of the lakes at greater spatial and temporal resolution and can help to study and
70 predict the hydrological evolution of lakes even under complex environmental conditions. Lake models can be expanded to include further physical and biochemical processes such as water quality; hence their application range is very broad.

Lake Erie, for example, has been subject to extensive modeling work to support adaptive management (Arhonditsis et al., 2019). (Getachew et al., 2021) combined water balance and process-based modeling in a prediction framework for lake levels at Lake Tana. The process modeling of these studies focused on the recharge dynamics using the Soil Water Assessment Tool
75 (SWAT), but there is also extensive literature using groundwater modeling software such as MODFLOW, that can better handle lake-groundwater interactions (Lu et al., 2022; Dehghanipour et al., 2019). The downside of process-based models is their time-intensive setup, their large number of parameters requiring extensive data and their large computational costs. This is critical in situations where available data and prior knowledge are limited. In the absence of comprehensive data to run and parameterize process-based models, their theoretical superiority over simple water balance models vanishes.

80 As models of intermediate complexity, data-driven models are based on readily available observations of the investigated system, while the internal system mechanics are approximated using statistical methods. The underlying system behavior is thus approximated from the mathematical relations between the system input and output data (Souza et al., 2016).



In hydrology, data-driven methods are typically used for prediction or management, for which they are frequently embedded into a system dynamics model framework that goes beyond natural science hydrology (Hassanzadeh et al., 2012; Alifujiang et al., 2017). The term data-driven modeling is often used as an overarching term for a wide variety of novel machine learning methods (Zhu et al., 2020a; Elshorbagy et al., 2010a), but usually excludes methods such as time series analysis or regression that are also data-driven by design.

Time-series analyses methods often only consider the lake level timeseries themselves, predicting them based on their own past values. (Şen et al., 2000) analyzed the time-series of the Van Lake, Turkey with linear and non-linear trends, and combined them with a Markov model to predict future lake levels. (Ebtehaj et al., 2019) based a linear prediction on the spectral decomposition of timeseries. Multiple studies showed the applicability of Autoregressive Integrated Moving Average (ARIMA) models in the context of lake water management. ARIMA models use linear regression combined with moving averages and are suitable for short term time series predictions. Hence the approach is very popular for prediction applications in hydrology (Ghashghaie and Nozari, 2018; Irvine and Eberhardt, 1992; Montanari et al., 1997). Simple time-series approaches, however, are limited as they do not use any weather forcing as input as pointed out by (Kakahaji et al., 2013), for example. (Kakahaji et al., 2013) compared multiple prediction methods on the Urmia lake dataset, including water balance modeling, linear predictor models and different machine learning approaches (multi-layer perceptron and fuzzy networks). The authors concluded that in data-scarce scenarios linear approaches are preferred, while non-linear machine learning methods could only outperform them when properly trained.

Linear regression has been widely use to model the responses of hydrological systems to rainfall (Clarke, 1973; Tasker, 1980). Linear regression assumes a linear relationship between the model input and output, with the linear coefficients calibrated based on the misfit of the model (usually by the ordinary least squares method). As this is a very efficient and robust methodology, it has been the standard data-driven approach in geosciences for decades. Linear models are usually fitted deterministically, but they are also suitable to be implemented within Bayesian frameworks for sensitivity analysis and uncertainty quantification (Kroll and Song, 2013). In more recent studies, linear regression is still widely used as the reliable baseline to compare other more advanced methodologies. For example, (Elshorbagy et al., 2010a, 2010b) compared the predictive capabilities of six different methods using linear models as a baseline. Linear models were similarly used by several studies to show the advantages of machine learning methods (Heuvelmans et al., 2006; Sahoo and Jha, 2013).

Machine learning applications are gaining increasing popularity in hydrological practice, for example for rainfall-runoff modeling (Kratzert et al., 2019; Sahoo et al., 2019; Klotz et al., 2020), water resources management (Oyebode and Stretch, 2019), drought prediction (Li et al., 2021) or lake level prediction (Kisi et al., 2012; Demir and Yaseen, 2023). Machine learning methods provide black-box solutions with a non-linear internal mathematical structure. They can be used as predictors based on the lake level variation data only (Zhu et al., 2020b), or to predict dynamics based on forcing data (Páliz Larrea et al., 2021). Machine learning models typically have a very large number of parameters. Proper calibration of parameters requires large datasets, which again limits the applicability of these approaches. An even larger issue regarding the context of our study is the black-box nature of machine learning methods: it is very challenging to analyze individual processes when the black-box method is designed to mimic the overall behavior of the system (Amy McGovern et al., 2019). This is also true for most other data-driven approaches, as they are designed for prediction rather than understanding, but models of less complexity, e.g. regression-type models, could still be analyzed with relative ease.

120

In this paper we present a case of limited prior knowledge where a process-based model cannot (yet) be constructed, although predictions of lake level change and an assessment of potential drivers are increasingly demanded by policymakers and stakeholders. We use the case of the Groß Glienicker Lake, a groundwater-fed lake at the outskirts of Berlin, Germany, that has experienced drastic water losses over the last decades. This loss is not systematically observed in all lakes of the region



125 (Lischeid et al., 2021), hence further drivers beyond climatic changes need to be examined, e.g. water infrastructure and land use changes.

We follow the downward model development approach as follows: by a monthly water balance analysis, we identify and quantify missing water fluxes in the hydraulic system, and use it as a baseline to identify any turning points and changes over the investigated period. This informs a daily data-driven linear model that can unfold the lake level responses to specific events in more detail. By identifying the main drivers of the lake level dynamics and system changes, our study will support the development of a future process-based model, while the results can already be used in local water management initiatives.

2 Methodology

In this study, we propose a top-down model development approach (Sivapalan and Young, 2005; Hrachowitz and Clark, 2017) to understand the lake level dynamics, starting from simple water balance models to more complex data-driven approaches, with an outlook to what we can learn from these for even more complex physics-based modeling. We propose a hybrid data-driven modeling framework, consisting of the following steps:

1. Monthly water balance model to quantify fluxes
2. Identify main turning points in the system using the water balance residuals
- 140 3. Daily linear regression models between the turning points
4. Model response analysis to isolated weather forcings
5. Further analysis of step 3 and 4 with non-linear approaches of increasing complexity (if needed)
6. Triangulation of findings using independent data

Our proposed methodology requires the development of multiple models. First, a water balance model is created on the monthly scale, that helps quantifying the fluxes of the hydraulic system, and helps identifying any major turning points during the investigation periods. The evolution of the water balance residuals can indicate systematic changes, like increase in outflow from the catchment.

Next, daily-scale data-driven models calibrated over the periods between the turning points are compared in order to analyze the differences in their lake level response. We propose to start this analysis using linear regression models, due to their simplicity and transparency. The model responses to the different weather forcings (precipitation, evapotranspiration) are compared separately as well, to understand the system in detail.

If linear models cannot capture the system behavior sufficiently, we propose to increase the model complexity using non-linear models, such as artificial neural networks. In our study, the linear approach provided good fits, and enough insight for system understanding based on the available data - the fact the system seems to behave linearly is in itself an interesting result. As the last step, the findings are validated against independent information.

In the following, first we present the meteorological forcing data, and the way it was obtained. Then, we present the methodologies of the water balance and linear regression approaches.

2.1 Forcing meteorological data

The proposed methodology relies on local meteorological data from the investigated lake catchment, which is achieved by using data from the second version (v2) of the Central European Refined analysis (CER) (Jänicke et al., 2017), a gridded meteorological dataset for Central Europe with focus on the region of Berlin-Brandenburg. As its predecessor CER v1, the CER v2 dataset has been produced by an observation-based model approach. Global ERA5 reanalysis data has been dynamically downscaled using the Weather Research & Forecasting (WRF) model. The methodologically has been comprehensively described and successfully applied in different regions of the world, for instance in High Asia (Wang et al.,



165 2021; Maussion et al., 2014). The CER v2 data set covers the time period from 1980 to 2022 (with continuous update of most recent years) using a convection-resolving approach at the highest spatial resolution of 2 km horizontal grid spacing. Data from 2002 to 2022 have been used in this study since the CER v1 data set, which dates back only to 2002, was used to test the robustness of our methodology.

There are two advantages of using a dynamically downscaled gridded dataset instead of relying on interpolated station data. 170 First, such an approach provides an estimate of actual evapotranspiration for each grid point using land cover, vegetation and soil data, and dynamic data on soil moisture, while station-based observations are typically restricted to potential evapotranspiration (lysimeters or eddy flux towers would be available at only very few locations). Second, this approach explicitly takes account for meso-scale heterogeneity of weather systems, which is of particular importance for precipitation with its high variability at spatial scales of a few kilometers or less.

175 2.2 Water balance modeling

The water balance equation for a groundwater fed lake system can be formulated as:

$$\Delta S_{lake}(t) = P_{lake}(t) - E_{A,lake}(t) + F_{in}(t) - F_{out}(t) + \epsilon \quad (1)$$

where ΔS_{lake} is the change in water level (change in lake volume divided by the lake area), P_{lake} is the total precipitation over 180 the lake and $E_{A,lake}$ is the total lake evaporation. F_{in} and F_{out} are in this case the subsurface in- and outflow of water to the lake, which can be combined into the net water inflow (ΔF). The final term ϵ explains any remaining errors and uncertainties in the data.

Precipitation ($P_{catchment}$) and actual evapotranspiration ($ET_{A,catchment}$) over the catchment area, and not just the lake, strongly influence subsurface flow processes that feed the lake. However, these effects show some time delay. Therefore, the water 185 balance equation can be modified for the catchment as:

$$\Delta S(t) = \int_{t-\tau^*}^t P_{catchment}(\tau) d\tau - \int_{t-\tau^*}^t ET_{A,catchment}(\tau) d\tau + \Delta F^*(t) + \epsilon \quad (2)$$

Here, the first integral sums precipitation over the catchment back over time until a precipitation event ceases to cause an inflow into the lake at time t , while the second integral does the same for actual evapotranspiration. We denote this time 190 interval with τ^* which we can also call the hydraulic memory of the system, which is sometimes called lake response time in the literature (Mason et al., 1994; Gong et al., 2015). Here, ΔS denotes the change in storage over the whole catchment, which is mainly the change in groundwater storage. Using this formulation, lake levels act as an indicator for groundwater level changes. With this estimation, precipitation over the lake is included in the precipitation of the catchment and evaporation is included in the catchment evapotranspiration term. The modified water balance equation leaves ΔF^* to account for any 195 remaining net subsurface inflow unaffected by climatic forcing, for instance water abstractions in which case ΔF^* would be negative, or diverging regional groundwater flows. If these flows are approximately constant over the investigated time period, they will not appreciably affect the lake level dynamics.

Considering the discrete nature of daily input data, the integrals can be substituted by sums:

$$\Delta S(t) = \sum_{i=1}^{\tau^*} P_{catchment}(t-i) - \sum_{i=1}^{\tau^*} ET_{A,catchment}(t-i) + \Delta F^* + \epsilon \quad (3)$$

200

The complete water balance then can be used to estimate the lake level changes. In this study we assumed that lake level changes are linearly related to storage changes:



$$\Delta z(t) = \alpha \Delta S(t) + \beta \quad (4)$$

205 The slope (α) and intercept (β) can be estimated by optimizing the fit between the observed and modelled lake level changes. Note that under complex hydrological conditions this relation may be different, but this would be obviously seen if the observed and modelled timeseries would not come close during this optimization. In simpler hydrological systems (such as our case) α could equal 1, and β zero.

The water balance equation is closed by calibrating the ΔF value aiming to ensure the best fit between the observed and modelled lake level changes. To characterize the fit quality, we use the R^2 score metrics, the coefficient of determination. The calibration is done via a simple grid search, by testing a series of values with reasonably small intervals between them.

210 After the water balance equation is closed the remaining residuals (ϵ) are analyzed to identify any systematic trends or turning points in the system. Turning points can be identified where as the starting point of a continuous increase or decrease in the residual values (see Fig. 5 for example). To quantify these effects, transient fluxes can be introduced to the water balance, with constant values within certain time intervals. The calibration of such fluxes is done similarly, using a grid search.

2.3 Data-driven modeling

Data-driven models use the statistical relationship between the model input data and the observed outputs. Based on the modified discrete water balance equation (eq.3), we can frame the general modeling problem as:

$$\Delta z(t) = f(P(t - \tau^*), \dots, P(t), ET_A(t - \tau^*), \dots, ET_A(t)) + \epsilon \quad (5)$$

This means that we are looking for the functional relationship between the meteorological input data and the observed lake level changes. This equation can be amended by additional input data, like data on water abstraction (if such data is available). The simplest function that can be used in this model is a linear function, which would read as:

$$\begin{aligned} \Delta z(t) = & a + b_{P,-\tau}P(t - \tau^*) + b_{P,-\tau+1}P(t - \tau^* + 1) + \dots \\ & + b_{P,0}P(t) + b_{ET,-\tau}ET(t - \tau^*) + \dots + b_{ET,0}ET(t) + \epsilon \end{aligned} \quad (6)$$

220 Where a is the intercept of the linear function, $b_{P,-\tau+i}$ are the linear coefficients for precipitation for the timesteps $\tau + i$ in the past, $b_{ET,-\tau+i}$ are the same coefficients for actual evapotranspiration. Although this is a relatively simple formula, the function could have a high dimensionality, which increases with the memory τ^* and the number of input features F ($f: \mathbb{R}^{F\tau^*} \rightarrow \mathbb{R}$). This often referred to as a multilinear problem in the literature (Sahoo and Jha, 2013).

The linear model can be split into two sub-models, to investigate the individual responses to precipitation and evapotranspiration respectively:

$$\Delta z_P(t) = b_{P,-\tau}P(t - \tau^*) + \dots + b_{P,0}P(t) \quad (7)$$

$$\Delta z_{ET}(t) = b_{ET,-\tau}ET(t - \tau^*) + \dots + b_{ET,0}ET(t) \quad (8)$$

240 Optionally, input data might be filtered prior to the analysis, which would help with some more complex data driven modeling methods, such as neural networks. In this study we used a lowpass filter over the lake level data, with a cutoff frequency at 20 days to help with the visualization of the analysis. To make the linear model coefficients more comparable for the different input types, the input data may be standardized as well. Standardization rescales the input timeseries to have a zero mean and a standard deviation of 1. Standardization may also be necessary for non-linear machine learning approaches.



The linear model is fitted using ordinary least squares regression, from the scikit-learn python library (Pedregosa et al., 2011).

245 The method minimizes the sum of squared errors between observed and simulated data using an explicit formula of a projection matrix.

The lake response time/system memory can be estimated in multiple ways, in this study we used two separate methods. First the k-lag autocorrelation of the lake level data was calculated.

$$AC(\tau) = \text{corr}(z(x), z(x - \tau))$$

250 (9)

The k-lag autocorrelation shows the time dependence of the lake level data, and give a good indication of the ideal memory timeframe for the modeling. A second approach, which is often used in rainfall runoff models, is fitting and evaluating a series of linear regression models, with different memory windows. With this approach the fit qualities of the different models are compared to identify the lake response time.

3 Study site and data

We applied this method to the Groß Glienicker Lake, a groundwater fed lake system at the outskirts of Berlin, Germany. Like several lakes in the region, the Groß Glienicker Lake has shown a drastic loss in lake levels over the last half century, with an increasing rate over the last decade (Fig. 1b).

260 The lake catchment delineated from topographic data spans over 33 km², mainly consisting of forest (20 km²), cropland (6 km²) and urban area (4 km²). The main recharge area is the heathland west of the lake dominated by sandy soils. The regional groundwater flow direction points southeast, toward the river Havel, a major tributary of the river Elbe, but due to the lack of groundwater wells and low gradients, the exact groundwater flowsystem is currently not known.

265 Two lakes are located within the catchment, the Sacrower Lake and the Groß Glienicker Lake. The latter has been chosen for this study because it is a focus of the local concerns. The lake nevertheless is representative of declining lake levels that are widespread in the Berlin-Brandenburg region and beyond. Both lakes are groundwater fed, with no active surface water connections. A connection between the two lakes used to exist, but it has been closed in 1996 due to the declining levels in both lakes.

270 The Groß Glienicker Lake has been extensively studied from a hydrochemical point of view because between 1970 and 1990 a large amount of untreated sewage was regularly discharged into the lake from a nearby army base leading to eutrophication. To mitigate the effects of this pollution, a restoration campaign started in the early 1990s, which is well documented (Wolter, 2010; Kleeberg et al., 2012; Heinrich et al., 2022). There are, however, only a limited number of studies that focused on lake level dynamics, although the continuous decrease in lake levels has been a concern for the local communities and authorities for a while.

275 The lake is located on the administrative boundary of the German federal states of Berlin and Brandenburg. This makes the accessibility of infrastructural and water management data complicated. From the Berlin side, data regarding water supply, wastewater management and canalization maps are available on the city webpage for multiple years. From the Brandenburg side, geological and limited civil engineering information is available.

280




Figure 1: a) Catchment of the Groß Glienicke Lake (© OpenStreetMap contributors 2023. Distributed under the Open Data Commons Open Database License (ODbL) v1.0.), b) Overview of lake level changes of Groß Glienicke Lake together with concurrent timeseries of temperature and precipitation. Key events potentially impacting the lake system are shown as background colors.

285

Air temperature shows a very apparent increasing trend over this time period (Fig. 1). Precipitation does not show any long-term trends, only shorter-term variations. This is in line with the climate analysis of the German Weather Service, which forecasts a slow increase in precipitation in the region (DWD-Deutscher Wetterdienst, 2019). It is known, however, that extreme events have become more frequent and provided a larger fraction of the annual precipitation in later years.

290 *CER v2 input data*

The Central European Refined analysis (Jänicke et al., 2017) provides atmospheric data for the investigation region Berlin-Brandenburg on a spatial grid of 2 km, at a temporal resolution of hours. In this study, we used the daily aggregated data of precipitation and actual evapotranspiration, integrated over the catchment area of the lake. Actual evapotranspiration is calculated from atmospheric parameters using static land use data. The exact land use composition of the catchment was estimated from the 2015 remote sensing based land cover analysis of (Pflugmacher et al., 2019). Figure 2 shows an overview of the CER v2 data over the study timeframe of 2002-2023.

295




Figure 2: Weather forcing input data: a) investigation period, b) example year of 2009.

300

The plot shows how summer periods are dominated by the extreme rainfall events in the catchment. These events are isolated by drought periods, as seen during the example year of 2009 plotted in Fig.2b. The data also shows that actual evapotranspiration has a much more periodic and regular behavior, with similar patterns over the years. However, the downscaled actual evapotranspiration data do not show any increasing trend, which one might expect from the increasing air temperatures (Fig. 1b). This however would only happen in energy-limited systems with unlimited water availability (e.g. over




305 open water bodies). While potential evapotranspiration would follow such temperature trend, actual evapotranspiration in
water limited regimes does not depend on air temperature.

4 Results

In this section we apply the proposed methodology to the example of the Groß Glienicker Lake. After estimating the hydraulic
memory of the system, we construct a water balance model, and quantify its missing fluxes by fitting a linear model to the lake
310 level changes.

4.1 System memory (lake response time)

The memory of the hydraulic system is estimated by calculating the k-lag autocorrelation of the lake level data. A bandpass
filter is used over these data to remove the annual cycle, which dominates the lake level periodicity and could distort the
analysis. The result is shown in Fig. 3a.



315


Figure 3: Lake response time analysis: a) autocorrelation of lake levels, b) fit quality of linear models using different memory timeframes.

The autocorrelation plot in Fig. 3 shows a rapid decrease, it reaches zero around 15 days, and its minimum value around 30
days. Another method for estimating the optimal memory timeframe in hydrology (mainly in rainfall runoff modeling studies)
320 is to compare linear models with different memory lengths over the same data. This is shown in Fig. 3b, in a range from 1 to
250 days using the r^2 metric. The overall picture is very similar to the autocorrelation, with a rapid increase in fit quality until
about 30 days. Then the fit quality reaches a plateau until about 100 days when it starts to decrease again due to additional
cyclicality in the data.

Based on these analyses, we will use 30 days as the lake response time or hydraulic memory throughout this study. One might
325 link this time to the catchment size, as the distance travelled by the groundwater flow. However, this would be incorrect, as
the hydraulic pressure signals that cause the changes in water levels travel much faster than the water itself (due to hydraulic
continuity). The memory can be more related to the time that the rainwater needs to reach the groundwater table plus the time
the thus generated pressure anomaly needs to reach the lake water.

4.2 Water balance

330 The water balance model is built using eq. 1 on a monthly scale (30 days scale) – suggested by the system memory analysis.
The monthly precipitation and actual evapotranspiration timeseries are generated via summing up the daily values, and the
lake level timeseries (which is used for model validation) is averaged to monthly means. The monthly weather values are then
compared with the mean lake level of the next month.




335

Figure 4: Water balance modeling: a) cumulative sum of water availability, b) observed and estimated lake levels.

Figure 4 shows the two main steps of the water balance estimation. First, the water availability is calculated by subtracting actual evapotranspiration from precipitation monthly. By taking the cumulative sum of the water availability, we can see that if only these two processes would affect the lake, the lake levels would increase over the investigation period.

To obtain a more realistic picture of the water level changes an additional loss term needs to be introduced (ΔF in eq. 2). In this case, a constant outflow equivalent of 4.5 mm per month was necessary to bring the water balance curve as close to the lake levels as possible. This flux was estimated via a grid search via maximizing the r^2 score and can be attributed to the net groundwater outflow of the system. This means that the net precipitation is not enough to sustain the lake levels, an additional groundwater flow feeds the lake.

There is a clear breaking point between the modelled and the observed data around 2015, where the two curves diverge from each other. Before this turning point, the obtained fit was maximal at 0.76. This means that until this point in time, 76% of the lake level variations can be explained solely by the variations of the meteorological inputs. After this point in time, the difference between the curves significantly increases, as it is shown in the misfit curve in Fig. 5.



350

Figure 5. – Differences between the observations and the water balance model (non-climatic water balance anomaly). At positive values there is surplus water in the lake compared to the model, at negative values the lake shows a water deficit that is unaccounted for by the model.



It's clear from Fig. 5 that the residual variations cannot be explained by a single missing water balance component, but with
355 some system change. Until 2015, the model is in good agreement with the lake level observations, despite some short-term
variations in each direction.

Since 2015, the lake levels exhibit a downward trend (Fig. 4), which is not captured by the model. By 2015, we see a
systematically widening overestimation of the observed lake levels (Fig. 5). The difference is a rainfall equivalent of 10 mm
every month, which given the catchment size is around 4 million m³ yearly. Because this change in the water balance happens
360 very quickly, the time of change is very well identifiable at 2015 which is a strong turning point in the hydrological system.

4.3 Linear model

To investigate the changes in the hydrological system in more detail, two data-driven linear models were constructed. The two
models are set up identically, both taking daily standardized precipitation and actual evapotranspiration data as input, with a
30-day long memory into the past (eq. 6). The only difference is the calibration period used. The model 2004 uses a seven-
365 year period after 2004 for calibration, which is a relatively steady period according to the previous analysis, while the model
2015 uses the last 7 years of the dataset from 2015, after the previously identified turning-point. The calibrated models are
then run for the complete available timeseries, adjusting the start of each calibration period to the actual lake levels that day.
The results are shown in Fig. 6.




Figure 6: Daily lake levels modelled with a linear model using different time periods for calibration (marked by blue shading): a) model 2004, b) model 2015.


The results in Fig. 6 clearly show the different dynamics of the two investigated time periods. The model 2004, trained on the
earlier period depicts a very similar behavior to the water balance model. An overall good fit in the first 12 years, with some
375 larger deviations in more extreme years like 2007, which was exceptionally dry. After 2015, the model systematically
overestimates the lake level and hence an increasing gap opens between the observed and modelled lake levels. The gap is
very similar to the water balance model. As the linear model was calibrated independently from that model, its similar result
provides a validation for the chosen water balance parameters.

The output of the model 2015 is very much the opposite. It calibrates so as to capture relatively well the final steep decrease
380 of the lake levels (the fit is even better than the first model), but when this modelled trend is extrapolated over the first half of
the dataset as well, it overestimates the lake levels.

These results support the conclusion that the lake system behavior changes systematically around 2015. To diagnose these
changes further, we now look into the calibrated models, their mathematical structure and their response behavior. Note that
as these models are purely data driven; any missing process in the data is compensated for by adjusting the coefficients for P
385 and ET.



To make the estimated effects of the different input features comparable (the effects of different predictors), the input data are first standardized for this analysis. The model coefficients thus give a good indication of the importance of the different inputs over the model's memory framework. The results for the two investigated time periods are compared in Fig. 7.



390

Figure 7: Model coefficients for precipitation and actual evapotranspiration: a) model 2004, with calibration period of 2004-2011, b) model 2015, with calibration period of 2015-2022.

Figure 7 shows the coefficient values of the two models over different time lags. For example, the precipitation coefficient at time lag 5 is the weight with which the precipitation 5 days ago enters the calculation of today's lake level change (see eq. 6). This plot shows that the lake reacts to precipitation and evapotranspiration in a different manner, and that this difference changes depending on the calibration period due to the hypothesized system changes. The effect of precipitation is detectable immediately, and days in the past are becoming less and less relevant. In model 2004, the rainfall importance is generally higher than in model 2015, where it decreases rapidly after the first 10 days.

400 After rainfall, as rainwater reaches the groundwater table it creates a hydraulic gradient, and the hydraulic signal reaches the lake very rapidly. An event will affect the water table until the water seeps through the unsaturated soil. Actual evapotranspiration, on the other hand, has a delayed influence on lake level changes with a variable but on average constant importance of past days after 5-10 days in model 2004 and an increasing importance of past days after 10-15 days in model 2015. The overall importance of actual evapotranspiration is also higher in the second model (34% vs 42%).

405 To further analyze the model behavior, we created two sub-models according to eq. 7 and 8. Here, we separated the lake level response for the two input features, precipitation and actual evapotranspiration, i.e. simulating the lake level responses that would result from only precipitation or actual evapotranspiration as predictors. We used non-standardized inputs and outputs for this analysis. This way we can directly compare the differences between the two models in terms of the different effects of the two inputs. This is shown exemplary in Fig. 8.

410




Figure 8: Modelled hydraulic responses to different weather patterns: a) summer weather input with high intensity storms, b) spring weather input with light rain, c) model response to precipitation in summer, d) model response to precipitation in spring, e) model response to actual evapotranspiration in summer, f) model response to actual evapotranspiration in spring.

415 In this plot we zoom into two different parts of the dataset to compare the two models. The first time period in Fig. 8a is the late summer of 2006, which saw many days without precipitation but high evapotranspiration and single day rainfall events with relatively high amounts of rainfall. During this time period the model 2015 shows a systematically stronger response to actual evapotranspiration (Fig. 8e), which leads to a larger lake simulated level drop. The offset is not just vertical, there is a time lag of 5-10 days between the two responses (as expected based on the coefficients in Fig. 7).

420 The precipitation response is a bit more complex: the model 2004 gives a much stronger response to the larger rainfalls, but a weaker one to the lack of rain (Fig. 8c). This balances out the two curves over this time period – resulting in a similar precipitation response.

The models behave differently during the calmer spring season of 2016 (Fig. 8b). Here both the two evapotranspiration responses (Fig. 8f) and precipitation responses (Fig. 8d) run close to each other with small differences.

425 Therefore, the general offset between the two models is systematic. Between September and June, the models behave similarly – this is a period with regular rainfall without many dry days, or extreme rainfall events. The discrepancy in these periods however is usually not that high, hence the two models stay relatively close to each other.

This result shows that the main difference in the system between these two time periods is coming from the difference in evapotranspiration during the summer periods. The seasonality of the model differences is shown in more detail in Fig. 9,

430 where the median of the lake level response differences for the two inputs are plotted over the months of the year.




Figure 9: Yearly dynamics of the model discrepancies (model 2015-model 2004): a) median difference in precipitation response with confidence intervals, b) median difference in evapotranspiration response with confidence intervals.

435 The median difference in precipitation response in Fig. 9 shows that over the long run, the differences in rainfall response between the two models are cancelled out. We can see some small positive anomalies in the spring and fall, but this effect is much smaller than what is visible in evapotranspiration.

Evapotranspiration response also shows a small positive anomaly during these periods, keeping the two models close during the winter. Figure 9b nicely shows that the main difference between the two models originates from the summer evapotranspiration difference. This difference is very consistent over the years, indicated by the narrow confidence interval – which is not surprising as rainfall shows the bigger variability over the years.

5 Discussion

The water balance model shows a 4 million m³ yearly deficit to the climatic water balance since 2015. We take the two linear models as representing the system behavior during the relatively stable period between 2002-2015 and after 2015, respectively. The change in system behavior between these two periods is projected onto differences in responses to precipitation and actual evapotranspiration in these simple models while in reality a number of other processes will be responsible. However, the changes in the responses can still be analyzed to hypothesize about the actual processes at work. In this section we discuss some of these hypotheses.

450 5.1 Water management

A possible factor responsible for the accelerated decrease in lake water levels since 2015 that has been put forward by local stakeholders is an increase in water abstractions at the nearby water supply wells. Our analysis, however, does not support this hypothesis. There was no reported change in abstraction rate of the local waterworks in this period, and an increased abstraction rate would hardly explain the change in the short-term system dynamics – it would appear as a constant shift in water loss instead. Nevertheless, groundwater abstractions could affect the resilience of the lake to climate change effects as was shown by (Schulz et al., 2020) for Lake Urmia. Based on process-based modeling, their study did not find a direct correlation between abstractions and water level variability of Lake Urmia, as the lake could buffer the reduced inflow. However, in forecast scenarios, they achieved higher lake levels with reduced abstraction rates.



460 Abstractions by local households directly from the lake or from the groundwater could also have an effect, as people tend to
use these water sources for gardening. To calculate an upper bound for such private abstractions, we assume that all 5000
residents of Groß Glienicke (on the Brandenburg side of the lake) use 4% of the 200 l daily average water consumption for
gardening (OECD averages), which would amount to 15 000 m³ abstraction over the year. This is significantly less, than the
estimated water deficit.

465 Another local water utility is a former sewage farm (Rieselfeld Karolinenhöhe) north of the catchment. Here, large volumes
of untreated wastewater were infiltrated into the groundwater system up until 2010. The effects of this facility have been
extensively studied (Haacke et al. 2018; Liese et al. 2004) but no direct link has been found between the sewage farm and the
lake's catchment as the infiltrated water flew directly into the Havel river. The sewage farm stopped its operation in 2010, well
before the identified turning point.


470 Another infrastructural change that happened in the area was an upgrade of the sewage system. The most notable example is
the former British air force base (General Steinhoff Kaserne) east from the lake. Here, an almost 500 000m² area got connected
to the rainwater canalization system between 2012 and 2017, and the new system now leads the collected rainwater to the
Havel river, outside the catchment (Döllefeld et al., 2021). Assuming that 90% of this water would have previously reached
the groundwater or the lake (an assumption based on the urban evapotranspiration fraction of the CER dataset), this could
account for up to 225 000 m³ of the missing fluxes from the catchment.

475 Dialog with the local community also suggested that this canalization upgrade extended beyond the former airbase and it also
might have included the sewage system. Unfortunately, no reports or studies are available, but similarly to the private
abstractions, we can estimate the sewage production of the districts around the lake. Estimating 20 000 residents living in the
area, with an average sewage production of 120 l per year (Umweltbundesamt, 2023), we arrive at an estimate of 900 000 m³.
This could be used as an upper bound for the potential effect of the infrastructure change, if before all of this water had been
480 discharged in the catchment directly. This, however, is most likely a big overestimation, as the area is shown to be connected
to the Berlin canalization system in documents from 2012 and before (<https://www.berlin.de/umweltatlas/wasser/regen-und-abwasser/2012/literatur/>). The upgrade most likely affected the rainwater canalization only, which has a reported average
yearly flux of around 100 000 m³.

485 Still, this amount could have affected the hydrological system in some way (see Fig. 11), but cannot explain the observed
misfit. In particular, the lack of infiltrated water in the catchment would not explain the observed seasonality in the misfits
(Fig. 9). Further analysis of this issue is limited because the lake is located on the administrative boundary of the two German
states Berlin and Brandenburg, which means that some of the relevant information is only available on one side of the lake.



5.2 Vegetation increase



490 **Figure 10: Analysis of vegetation trends: a) yearly average NDVI values integrated over the catchment, b) comparison of the yearly non-climatic water balance anomaly and the cumulative NDVI anomaly of the catchment.**

A significant part of the lake catchment area west of the lake is covered by forests and heathlands (Fig. 1a). Satellite imagery reveals an increasing trend in the Normalized Difference Vegetation Index (NDVI) between 2002 and 2018 (Fig. 10a). This suggests a general increase in vegetation over the past decades within the catchment area, likely attributed to an increase in forest canopy density and an expansion of woody-vegetation.

495 Comparing this data with the water balance gap shows striking similarities. In Fig. 10b we calculated the cumulative sum of the NDVI anomaly relative to the period average, and obtained a similar trend to the water balance anomaly. This suggests a possible connection between the two trends.

A denser canopy intercepts more rainfall available for evaporation, and more mature trees have higher transpiration rates, hence a denser canopy reduces groundwater recharge. The model discrepancies in Fig. 8 are most pronounced in the growing season, where the tree canopies are most developed. This analysis supports the hypothesis that the forest in the catchment has a strong effect on the hydrological system.

The land cover analysis also shows that our modeling could be improved if we could account for the heterogeneous land cover in the catchment when calculating evapotranspiration. The observed 10% increase in NDVI, based on MODIS evapotranspiration data, could equal 5-15% increase in forest evapotranspiration. The impact of this change over the lake levels is equivalent to a yearly flux of 800 000m³.

505 This amount could partly explain the water balance deficit, and the increase in evapotranspiration would also explain why the two linear models differ most during the growing season. However, to gain a more precise understanding of the effects of vegetation cover changes, a more detailed process-based analysis would be required, including biophysical modeling of the trees, and detailed modeling of the recharge process.



5.3 Regional groundwater trends

Another hypothesis relates the change in lake dynamics to a larger scale, regional groundwater trend. (Lischeid, 2021) analyzed lake and groundwater level timeseries in the region with principal component analysis. The author's concluded that lakes situated on the higher parts of this lowland region are more sensitive to falling water levels than lakes in the valley bottoms

515 because lakes situated higher are prone to losing their direct connection with the groundwater.

The larger region of Brandenburg has a negative climatic water balance, with water flowing in from areas with a positive budget either as groundwater or surface water flow. This system however is currently under stress not only due to climate change, but also due to the reduced flows of the Spree river, which is caused by the closure of open pit mines in the Lausitz region (HABEL et al., 2023). Therefore, over the last decades, in multiple parts of the region decreasing groundwater levels are visible. As a result, multiple lakes that are mainly groundwater fed show similarly decreasing levels (e.g. Groß Seddiner Lake, Großer Wummsee).

520

The exact effect of groundwater trends cannot be quantified without groundwater modeling. Still some signs of deviation between the lake and groundwater levels can be seen after 2015, however not decisively clearly. We also cannot attribute the seasonality in the differences between the two periods to this explanation.

525 *Environmental tipping point*

Ultimately, it seems most plausible that the observed lake level behavior is the results of a combination of the above-mentioned explanations.




Figure 11: Potential impacts of the different explanations of the non-climatic water balance anomaly.

530 Figure 11 shows a comparison between the estimated impacts of all potential explanations of the non-climatic water balance anomaly considered here. It shows that none of the anthropogenic or ecological factors alone are enough to explain the water deficit completely (even when their maximum potential impact is considered). Note that the effect of regional groundwater trends cannot be estimated, hence we just used it to explain the missing water flux after the other explanations were applied.

Based on these results we could not single out one reason that could explain the sudden change in water balance in 2015, but we found multiple processes that probably all contribute to the loss of water. Due to their combined effect, the hydrological system could have reached a tipping point around 2015 that altered the water balance. This tipping point could have been a critical groundwater level that was reached due to the infrastructural and environmental changes, below which the surface water-groundwater connection got disrupted.

Another explanation is that the increase in vegetation on the west side of the catchment reduced the groundwater levels locally so that it altered the groundwater flow regime. The gradient of the groundwater table in this area is very small ($3 \times 10^{-4} m/m$),

540



hence a local decrease in recharge could divert the groundwater flow and modify the subsurface catchment size. This explanation is in line with our finding that the difference in the hydrological system appears mainly during the growing season. However, to analyze these explanations further, more detailed process-based modeling is required.

545 6 Conclusions

In this paper we have shown how a systematic downward model development approach, using water balance and data-driven models could help with the investigation of a relatively under-studied lake system.

545 With the help of high-resolution weather forcing data and lake level observations we have identified a relation between the climatic and lake level variations. Water balance modeling helped to estimate the inflows and outflows of the system and to reveal any long-term dynamics. Data-driven modeling could then give a more detailed picture of the short-term lake system behavior, including responses to different weather patterns. This set of methods provided an effective toolset for understanding lake level changes and their drivers.

555 Our results showed that the lake level variations of the Groß Glienicker Lake between 2002 and 2015 can be explained by the variations in net precipitation, i.e. by precipitation and actual evapotranspiration over the catchment. We have identified a change in the hydraulic system around 2015, which not just resulted in a loss of 4 million cubic meter of water per year, but also changed the hydraulic response of the lake to the climatic inputs.

560 We have analyzed multiple explanations of this change: changes in water infrastructure, increase in vegetation and regional groundwater trends. Changes in abstractions were ruled out as the local waterworks did not report an increase in production, and private abstractions could not explain the missing water volumes. The alteration of the local canalization system could have affected the water balance of the lake in some way, but this does not explain the changes in the seasonal dynamics of the lake.

Increased evapotranspiration from the maturation of a forest in the catchment could explain the altered system dynamics, and the change in the vegetation cover is well aligned with the observed hydrological trend. Therefore, the water loss can be at least partly attributed to the growth of the forest.

565 Another likely reason is the continuously sinking groundwater levels in Brandenburg due to climate change, which is suggested disrupt the connection of surface water bodies to the groundwater, increasing their outflow. Regional studies show similar lake level trends at several lakes of the area.

570 Ultimately, the most likely explanation is the combination of the aforementioned processes, which made the hydrological system cross a tipping point during the investigation period. Further analysis of this explanation requires more detailed modeling of the individual processes, and the development of a groundwater model.

The findings of this paper will be used to help the development of such a model. Our main recommendation is the need for a dynamic land cover model that can account for the changes in vegetation and the benefits of gridded meteorological forcing data. While we would still suggest including the water works wells into the model (for which data series are available), we have shown that the effect of private abstractions is negligible, while the effect of infrastructural changes can be significant.

575 Finally, we have emphasized the importance of the regionally observed changes of groundwater levels that need to be considered in any physically-based modelling effort.

Data availability

The CER v2 dataset is available from the website of the Chair of Climatology, TU Berlin under the link:

<https://www.tu.berlin/en/klima/research/regional-climatology/central-europe/cer>The lake level data of the Groß Glienicker

580 Lake can be accessed at the water portal of the Berlin Senate:



<https://wasserportal.berlin.de/start.php>

Author contributions

DS, FB and UF prepared and curated the forcing meteorological dataseries. MS did the modelling and the data analysis. OA provided the remote sensing data and did the analysis of the vegetation growth. TK and DS guided the conceptualization and the internal review process. The co-authors all contributed to the preparation of the manuscript.

Competing interests

The authors declare no competing interests.

Acknowledgments

This study was funded through the Einstein Research Unit ‘Climate and Water under Change’ from the Einstein Foundation Berlin and Berlin University Alliance under grant number ERU-2020-609.

References

- Alifujiang, Y., Abuduwaili, J., Ma, L., Samat, A., and Groll, M.: System Dynamics Modeling of Water Level Variations of Lake Issyk-Kul, Kyrgyzstan, *Water*, 9, 989, <https://doi.org/10.3390/w9120989>, available at: <https://www.mdpi.com/247154>, 2017.
- Altunkaynak, A.: Forecasting Surface Water Level Fluctuations of Lake Van by Artificial Neural Networks, *Water Resources Management*, 21, 399–408, <https://doi.org/10.1007/s11269-006-9022-6>, available at: https://idp.springer.com/authorize/casa?redirect_uri=https://link.springer.com/article/10.1007/s11269-006-9022-6&casa_token=36zlxfbwlt8aaaaa:r85hcs6q2fgbpassho_gqerlegiicyjemlyqrbw2iavjxcu-yh-dmhl6qyvt2itozb4nlxzz7bvfhurl, 2007.
- Amy McGovern, Ryan Lagerquist, David John Gagne, G. Eli Jergensen, Kimberly L. Elmore, Cameron R. Homeyer, and Travis Smith: Making the Black Box More Transparent: Understanding the Physical Implications of Machine Learning, *Bulletin of the American Meteorological Society*, 100, 2175–2199, <https://doi.org/10.1175/BAMS-D-18-0195.1>, available at: <https://journals.ametsoc.org/view/journals/bams/100/11/bams-d-18-0195.1.xml>, 2019.
- Arhonditsis, G. B., Neumann, A., Shimoda, Y., Kim, D.-K., Dong, F., Onandia, G., Yang, C., Javed, A., Brady, M., Visha, A., Ni, F., and Cheng, V.: Castles built on sand or predictive limnology in action? Part A: Evaluation of an integrated modelling framework to guide adaptive management implementation in Lake Erie, *Ecological Informatics*, 53, 100968, <https://doi.org/10.1016/j.ecoinf.2019.05.014>, available at: <https://www.sciencedirect.com/science/article/pii/S1574954118302486>, 2019.
- Beletsky, D., Hawley, N., and Rao, Y. R.: Modeling summer circulation and thermal structure of Lake Erie, *J. Geophys. Res. Oceans*, 118, 6238–6252, <https://doi.org/10.1002/2013JC008854>, available at: <https://agupubs.onlinelibrary.wiley.com/doi/full/10.1002/2013JC008854>, 2013.
- Clarke, R. T.: A review of some mathematical models used in hydrology, with observations on their calibration and use, *Journal of Hydrology*, 19, 1–20, [https://doi.org/10.1016/0022-1694\(73\)90089-9](https://doi.org/10.1016/0022-1694(73)90089-9), available at: <https://www.sciencedirect.com/science/article/pii/0022169473900899>, 1973.



- Crapper, P. F., Fleming, P. M., and Kalma, J. D.: Prediction of lake levels using water balance models, *Environmental Software*, 11, 251–258, [https://doi.org/10.1016/S0266-9838\(96\)00018-4](https://doi.org/10.1016/S0266-9838(96)00018-4), available at: <https://www.sciencedirect.com/science/article/pii/S0266983896000184>, 1996.
- 620 Dehghanipour, A. H., Zahabiyou, B., Schoups, G., and Babazadeh, H.: A WEAP-MODFLOW surface water-groundwater model for the irrigated Miyandoab plain, Urmia lake basin, Iran: Multi-objective calibration and quantification of historical drought impacts, *Agricultural Water Management*, 223, 105704, <https://doi.org/10.1016/j.agwat.2019.105704>, available at: <https://www.sciencedirect.com/science/article/pii/S0378377419304068>, 2019.
- Demir, V. and Yaseen, Z. M.: Neurocomputing intelligence models for lakes water level forecasting: a comprehensive review, *Neural Comput & Applic*, 35, 303–343, <https://doi.org/10.1007/s00521-022-07699-z>, available at: <https://link.springer.com/article/10.1007/s00521-022-07699-z>, 2023.
- Döllefeld, M., Haag, L., and Welsch, J.: Umweltatlas Berlin – planungsrelevante Umweltdaten für Berlin, *ZfV - Zeitschrift für Geodäsie, Geoinformation und Landmanagement*, <https://doi.org/10.12902/zfv-0341-2021>, available at: [https://geodaesie.info/zfv/zfv-archiv/zfv-146-jahrgang/zfv-2021-2/umweltatlas-berlin-planungsrelevante-umweltdaten-fuer-](https://geodaesie.info/zfv/zfv-archiv/zfv-146-jahrgang/zfv-2021-2/umweltatlas-berlin-planungsrelevante-umweltdaten-fuer-berlin)
- 630 [berlin](https://geodaesie.info/zfv/zfv-archiv/zfv-146-jahrgang/zfv-2021-2/umweltatlas-berlin-planungsrelevante-umweltdaten-fuer-berlin), 2021.
- DWD-Deutscher Wetterdienst: Klimareport Brandenburg. 1, Auflage, Deutscher Wetterdienst, Offenbach am Main, Deutschland, 2019.
- Ebtehaj, I., Bonakdari, H., and Gharabaghi, B.: A reliable linear method for modeling lake level fluctuations, *Journal of Hydrology*, 570, 236–250, <https://doi.org/10.1016/j.jhydrol.2019.01.010>, 2019.
- 635 Elshorbagy, A., Corzo, G., Srinivasulu, S., and Solomatine, D. P.: Experimental investigation of the predictive capabilities of data driven modeling techniques in hydrology - Part 1: Concepts and methodology, *Hydrol. Earth Syst. Sci.*, 14, 1931–1941, <https://doi.org/10.5194/hess-14-1931-2010>, available at: <https://hess.copernicus.org/articles/14/1931/2010/>, 2010a.
- Elshorbagy, A., Corzo, G., Srinivasulu, S., and Solomatine, D. P.: Experimental investigation of the predictive capabilities of data driven modeling techniques in hydrology - Part 2: Application, *Hydrol. Earth Syst. Sci.*, 14, 1943–1961,
- 640 <https://doi.org/10.5194/hess-14-1943-2010>, 2010b.
- Getachew, B., Manjunatha, B. R., and Bhat, H. G.: Modeling projected impacts of climate and land use/land cover changes on hydrological responses in the Lake Tana Basin, upper Blue Nile River Basin, Ethiopia, *Journal of Hydrology*, 595, 125974, <https://doi.org/10.1016/j.jhydrol.2021.125974>, available at: <https://www.sciencedirect.com/science/article/pii/S0022169421000214>, 2021.
- 645 Ghashghaie, M. and Nozari, H.: Effect of Dam Construction on Lake Urmia: Time Series Analysis of Water Level via ARIMA, *Journal of Agricultural Science and Technology*, 20, 1541–1553, available at: <http://jast.modares.ac.ir/article-23-16338-en.html>, 2018.
- Gong, Y., Liu, G., and Schwartz, F.: Quantifying the Response Time of a Lake–Groundwater Interacting System to Climatic Perturbation, *Water*, 7, 6598–6615, <https://doi.org/10.3390/w7116598>, available at: [https://www.mdpi.com/2073-](https://www.mdpi.com/2073-4441/7/11/6598)
- 650 [4441/7/11/6598](https://www.mdpi.com/2073-4441/7/11/6598), 2015.
- HABEL, M., Nowak, B., and Szadek, P.: Evaluating Indicators of Hydrologic Alteration to Demonstrate the Impact of Open-Pit Lignite Mining on the River Flow Regimes, 2023.
- Hassanzadeh, E., Zarghami, M., and Hassanzadeh, Y.: Determining the Main Factors in Declining the Urmia Lake Level by Using System Dynamics Modeling, *Water Resour Manage*, 26, 129–145, <https://doi.org/10.1007/s11269-011-9909-8>,
- 655 available at: <https://link.springer.com/article/10.1007/s11269-011-9909-8>, 2012.
- Heinrich, L., Dietel, J., and Hupfer, M.: Sulphate reduction determines the long-term effect of iron amendments on phosphorus retention in lake sediments, *J Soils Sediments*, 22, 316–333, <https://doi.org/10.1007/s11368-021-03099-3>, available at: <https://link.springer.com/article/10.1007/s11368-021-03099-3>, 2022.



- Heuvelmans, G., Muys, B., and Feyen, J.: Regionalisation of the parameters of a hydrological model: Comparison of linear regression models with artificial neural nets, *Journal of Hydrology*, 319, 245–265, <https://doi.org/10.1016/j.jhydrol.2005.07.030>, available at: <https://www.sciencedirect.com/science/article/pii/S0022169405003641>, 2006.
- Hrachowitz, M. and Clark, M. P.: HESS Opinions: The complementary merits of competing modelling philosophies in hydrology, *Hydrol. Earth Syst. Sci.*, 21, 3953–3973, <https://doi.org/10.5194/hess-21-3953-2017>, 2017.
- 665 Irvine, K. N. and Eberhardt, A. J.: MULTIPLICATIVE, SEASONAL ARIMA MODELS FOR LAKE ERIE AND LAKE ONTARIO WATER LEVELS, *JAWRA Journal of the American Water Resources Association*, 28, 385–396, <https://doi.org/10.1111/j.1752-1688.1992.tb04004.x>, 1992.
- Jänicke, B., Meier, F., Fenner, D., Fehrenbach, U., Holtmann, A., and Scherer, D.: Urban-rural differences in near-surface air temperature as resolved by the Central Europe Refined analysis (CER): sensitivity to planetary boundary layer schemes and urban canopy models, *Int. J. Climatol.*, 37, 2063–2079, <https://doi.org/10.1002/joc.4835>, 2017.
- 670 Kakahaji, H., Banadaki, H. D., Kakahaji, A., and Kakahaji, A.: Prediction of Urmia Lake Water-Level Fluctuations by Using Analytical, Linear Statistic and Intelligent Methods, *Water Resour Manage*, 27, 4469–4492, <https://doi.org/10.1007/s11269-013-0420-2>, available at: <https://link.springer.com/article/10.1007/s11269-013-0420-2>, 2013.
- Kebede, S., Travi, Y., Alemayehu, T., and Marc, V.: Water balance of Lake Tana and its sensitivity to fluctuations in rainfall, Blue Nile basin, Ethiopia, *Journal of Hydrology*, 316, 233–247, <https://doi.org/10.1016/j.jhydrol.2005.05.011>, 2006.
- 675 Kisi, O., Shiri, J., and Nikoofar, B.: Forecasting daily lake levels using artificial intelligence approaches, *Computers & Geosciences*, 41, 169–180, <https://doi.org/10.1016/j.cageo.2011.08.027>, available at: <https://www.sciencedirect.com/science/article/pii/S0098300411002950>, 2012.
- Kleeberg, A., Köhler, A., and Hupfer, M.: How effectively does a single or continuous iron supply affect the phosphorus budget of aerated lakes?, *J Soils Sediments*, 12, 1593–1603, <https://doi.org/10.1007/s11368-012-0590-1>, available at: <https://link.springer.com/article/10.1007/s11368-012-0590-1>, 2012.
- 680 Klotz, D., Kratzert, F., Gauch, M., Sampson, A., Klambauer, G., Hochreiter, S., and Nearing, G.: Uncertainty Estimation with Deep Learning for Rainfall-Runoff Modelling, 21 pp., 2020.
- Kratzert, F., Klotz, D., Shalev, G., Klambauer, G., Hochreiter, S., and Nearing, G.: Towards learning universal, regional, and local hydrological behaviors via machine learning applied to large-sample datasets, *Hydrol. Earth Syst. Sci.*, 23, 5089–5110, <https://doi.org/10.5194/hess-23-5089-2019>, 2019.
- 685 Kroll, C. N. and Song, P.: Impact of multicollinearity on small sample hydrologic regression models, *Water Res*, 49, 3756–3769, <https://doi.org/10.1002/wrcr.20315>, 2013.
- Langbein, W. B.: Salinity and hydrology of closed lakes: A study of the long-term balance between input and loss of salts in closed lakes, 412, US GovernmentPrint. Office, 1961.
- 690 Laval, B., Imberger, J., Hodges, B. R., and Stocker, R.: Modeling circulation in lakes: Spatial and temporal variations, *Limnol. Oceanogr.*, 48, 983–994, <https://doi.org/10.4319/lo.2003.48.3.0983>, 2003.
- Li, J., Wang, Z., Wu, X., Xu, C.-Y., Guo, S., Chen, X., and Zhang, Z.: Robust Meteorological Drought Prediction Using Antecedent SST Fluctuations and Machine Learning, *Water Res*, 57, e2020WR029413, <https://doi.org/10.1029/2020WR029413>, 2021.
- 695 Lischeid, G.: Abschätzung des mittelfristigen Niedrigwasserrisikos anhand der Daten des Grundwassermonitorings, *KW Korrespondenz Wasserwirtschaft*, 780–785, <https://doi.org/10.3243/kwe2021.12.004>, 2021.
- Lischeid, G., Dannowski, R., Kaiser, K., Nützmann, G., Steidl, J., and Stüve, P.: Inconsistent hydrological trends do not necessarily imply spatially heterogeneous drivers, *Journal of Hydrology*, 596, 126096, <https://doi.org/10.1016/j.jhydrol.2021.126096>, available at: <https://www.sciencedirect.com/science/article/pii/S0022169421001438>, 2021.



- Lu, C., He, X., Zhang, B., Wang, J., Kidmose, J., and Jarsjö, J.: Comparison of Numerical Methods in Simulating Lake–Groundwater Interactions: Lake Hampen, Western Denmark, *Water*, 14, 3054, <https://doi.org/10.3390/w14193054>, available at: <https://www.mdpi.com/2073-4441/14/19/3054>, 2022.
- 705 Mason, I. M., Guzkowska, M. A. J., Rapley, C. G., and Street-Perrott, F. A.: The response of lake levels and areas to climatic change, *Climatic Change*, 27, 161–197, <https://doi.org/10.1007/BF01093590>, available at: <https://link.springer.com/article/10.1007/BF01093590>, 1994.
- Maussion, F., Scherer, D., Mölg, T., Collier, E., Curio, J., and Finkelnburg, R.: Precipitation Seasonality and Variability over the Tibetan Plateau as Resolved by the High Asia Reanalysis*, *Journal of Climate*, 27, 1910–1927,
710 <https://doi.org/10.1175/JCLI-D-13-00282.1>, 2014.
- Montanari, A., Rosso, R., and Taqqu, M. S.: Fractionally differenced ARIMA models applied to hydrologic time series: Identification, estimation, and simulation, *Water Res*, 33, 1035–1044, <https://doi.org/10.1029/97WR00043>, 1997.
- Oyebode, O. and Stretch, D.: Neural network modeling of hydrological systems: A review of implementation techniques, *Natural Resource Modeling*, 32, e12189, <https://doi.org/10.1111/nrm.12189>, 2019.
- 715 Páliz Larrea, P., Zapata-Ríos, X., and Campozaño Parra, L.: Application of Neural Network Models and ANFIS for Water Level Forecasting of the Salve Faccha Dam in the Andean Zone in Northern Ecuador, *Water*, 13, 2011, <https://doi.org/10.3390/w13152011>, available at: <https://www.mdpi.com/2073-4441/13/15/2011>, 2021.
- Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., and Duchesnay, E.: Scikit-learn: Machine
720 Learning in Python, *Journal of Machine Learning Research*, 12, 2825–2830, 2011.
- Pflugmacher, D., Rabe, A., Peters, M., and Hostert, P.: Mapping pan-European land cover using Landsat spectral-temporal metrics and the European LUCAS survey, *Remote Sensing of Environment*, 221, 583–595, <https://doi.org/10.1016/j.rse.2018.12.001>, available at: <https://www.sciencedirect.com/science/article/pii/S0034425718305546>, 2019.
- 725 Sahoo, B. B., Jha, R., Singh, A., and Kumar, D.: Long short-term memory (LSTM) recurrent neural network for low-flow hydrological time series forecasting, *Acta Geophys.*, 67, 1471–1481, <https://doi.org/10.1007/s11600-019-00330-1>, available at: <https://link.springer.com/article/10.1007/s11600-019-00330-1>, 2019.
- Sahoo, S. and Jha, M. K.: Groundwater-level prediction using multiple linear regression and artificial neural network techniques: a comparative assessment, *Hydrogeol J*, 21, 1865–1887, <https://doi.org/10.1007/s10040-013-1029-5>, 2013.
- 730 Schulz, S., Darehshouri, S., Hassanzadeh, E., Tajrishy, M., and Schüth, C.: Climate change or irrigated agriculture - what drives the water level decline of Lake Urmia, *Sci Rep*, 10, 236, <https://doi.org/10.1038/s41598-019-57150-y>, 2020.
- Şen, Z., Kadioğlu, M., and Batur, E.: Stochastic Modeling of the Van Lake Monthly Level Fluctuations in Turkey, *Theor Appl Climatol*, 65, 99–110, <https://doi.org/10.1007/s007040050007>, available at: https://idp.springer.com/authorize/casa?redirect_uri=https://link.springer.com/article/10.1007/s007040050007&casa_token=yenp_r4onomaaaaa:l7zftnvd16eakkmmrdauzb5jz2rhxqfyck2jwi0nag_bkaol14e5-tvao2j3xcgednsvm0-m8z6y7vxe, 2000.
- 735 Sivapalan, M. and Young, P. C.: Downward Approach to Hydrological Model Development, in: *Encyclopedia of hydrological sciences*, edited by: Anderson, M. G., Wiley, Chichester, <https://doi.org/10.1002/0470848944.hsa141>, 2005.
- Sivapalan, M., Blöschl, G., Zhang, L., and Vertessy, R.: Downward approach to hydrological prediction, *Hydrol. Process.*, 17, 2101–2111, <https://doi.org/10.1002/hyp.1425>, 2003.
- 740 Solomatine, D. P. and Ostfeld, A.: Data-driven modelling: some past experiences and new approaches, *Journal of Hydroinformatics*, 10, 3–22, <https://doi.org/10.2166/hydro.2008.015>, 2008.
- Souza, F. A., Araújo, R., and Mendes, J.: Review of soft sensor methods for regression applications, *Chemometrics and Intelligent Laboratory Systems*, 152, 69–79, <https://doi.org/10.1016/j.chemolab.2015.12.011>, available at: <https://www.sciencedirect.com/science/article/pii/S0169743915003263>, 2016.



- 745 Tasker, G. D.: Hydrologic regression with weighted least squares, *Water Res*, 16, 1107–1113,
<https://doi.org/10.1029/WR016i006p01107>, 1980.
Umweltbundesamt: Sewage sludge disposal in Germany, <https://www.umweltbundesamt.de/en/topics/sewage-sludge-disposal-in-germany>, last access: 31 May 2023, 2023.
- Valipour, R., Fong, P., McCrimmon, C., Zhao, J., van Stempvoort, D. R., and Rao, Y. R.: Hydrodynamics of a large lake with
750 complex geometry and topography: Lake of the Woods, *Journal of Great Lakes Research*, 49, 82–96,
<https://doi.org/10.1016/j.jglr.2022.09.009>, available at:
<https://www.sciencedirect.com/science/article/pii/S0380133022002222>, 2023.
- Wang, X., Tolksdorf, V., Otto, M., and Scherer, D.: WRF-based dynamical downscaling of ERA5 reanalysis data for High
Mountain Asia: Towards a new version of the High Asia Refined analysis, *International Journal of Climatology*, 41, 743–762,
755 <https://doi.org/10.1002/joc.6686>, available at: <https://rmets.onlinelibrary.wiley.com/doi/full/10.1002/joc.6686>, 2021.
- Wolter, K.-D.: Restoration of Eutrophic Lakes by Phosphorus Precipitation, with a Case Study on Lake Gross-Glienicker, in:
Restoration of Lakes, Streams, Floodplains, and Bogs in Europe, Springer, Dordrecht, 85–99, https://doi.org/10.1007/978-90-481-9265-6_7, 2010.
- Woolway, R. I., Kraemer, B. M., Lenters, J. D., Merchant, C. J., O’Reilly, C. M., and Sharma, S.: Global lake responses to
760 climate change, *Nat Rev Earth Environ*, 1, 388–403, <https://doi.org/10.1038/s43017-020-0067-5>, available at:
<https://www.nature.com/articles/s43017-020-0067-5>, 2020.
- Xu, C.-Y. and Singh, V. P.: A Review on Monthly Water Balance Models for Water Resources Investigations, *Water Resour
Manage*, 12, 20–50, <https://doi.org/10.1023/A:1007916816469>, available at:
<https://link.springer.com/article/10.1023/A:1007916816469>, 1998.
- 765 Zhu, S., Lu, H., Ptak, M., Dai, J., and Ji, Q.: Lake water-level fluctuation forecasting using machine learning models: a
systematic review, *Environ Sci Pollut Res*, 27, 44807–44819, <https://doi.org/10.1007/s11356-020-10917-7>, available at:
<https://link.springer.com/article/10.1007/s11356-020-10917-7>, 2020a.
- Zhu, S., Hrnjica, B., Ptak, M., Choiński, A., and Sivakumar, B.: Forecasting of water level in multiple temperate lakes using
machine learning models, *Journal of Hydrology*, 585, 124819, <https://doi.org/10.1016/j.jhydrol.2020.124819>, available at:
770 <https://www.sciencedirect.com/science/article/pii/S0022169420302791>, 2020b.