

Multi-section reference value for the analysis of horizontally scanning aerosol lidar observations

Juseon Shin¹, Gahyeong Kim¹, Dukhyeon Kim², Matthias Tesche³, Gahyeon Park¹, and Youngmin Noh¹

¹Division of Earth Environmental System Science, Pukyong National University, Busan, Republic of Korea

²School of Basic Science, Hanbat National University, Daejeon, Republic of Korea

³Leipzig Institute for Meteorology (LIM), Leipzig University, Leipzig, Germany

Correspondence: Youngmin Noh (nym@pknu.ac.kr)

Abstract. The quantitative analysis of measurements with horizontally scanning aerosol lidar instruments faces two major challenges: the background correction can be affected by abnormal signal peaks and the choice of a reference extinction coefficient α_{ref} is complicated if aerosols are ubiquitous in the sampled volume. Here, we present the newly-developed multi-section method for the stable solution of extinction coefficient retrievals from horizontally scanning lidar measurements. The algorithm removes irregular peaks related to signal noise based on an experimentally derived fitting model. A representative value for α_{ref} is inferred from converging retrievals along different scan axes and over multiple scans of 10 to 15 min under the assumption that they are related only to ambient aerosols without distinct emission sources. Consequently, α_{ref} obtained through the multi-section method reflects typical atmospheric aerosols unaffected by emissions and noise. When comparing α_{ref} to the $PM_{2.5}$ mass concentrations at national monitoring stations near the measurement area, a significant correlation with an r-squared value exceeding 0.74 was observed. The presented case studies show that the new method allows for the retrieval and visualization of spatio-temporal aerosol distributions and subsequent products such as PM2.5 concentrations.

1 Introduction

Particulate matter (PM) has become a globally significant area of interest due to its implications for climate change and its impact on human health (Dockery et al., 1993; Doherty et al., 2017; Fang et al., 2013; Fiore et al., 2012; Isaksen et al., 2009; Jacob and Winner, 2009; Kaufman et al., 2002; McDonnell et al., 2000; Pope et al., 2009; Ren and Tong, 2008), and public awareness about air pollution has been on the rise. However, national-level PM concentration information is limited to point measurements, leading to constraints in observation locations and personnel for management. Consequently, providing real-time spatial distribution information of PM concentrations is not straightforward. Therefore, to meet the growing demand for real-time access to local PM information and fulfill the rights of citizens seeking such data, adopting remote sensing techniques for PM observation becomes essential.

Lidar measurements are a powerful tool for gaining insight into the sources, spatio-temporal distribution, and transport of atmospheric aerosols (Winker et al., 2010). Lidar instruments are mostly used for measurements at near-zenith elevations for vertically resolved aerosol detection (Lee and Wong, 2018; Noh et al., 2013, 2016). Scanning lidar system was developed in the 1980s to observe the horizontal distribution of aerosols, wind, and water vapour (Sasano et al., 1982; Nakane and Sasano,

25 1986; Eichinger et al., 1994; Palm et al., 1994; Papayannis et al., 1994; He et al., 2012). Initially, scanning technology was used to understand the atmospheric structure and dynamics at the micro- and meso-scale (De Wekker and Mayor, 2009; Doyle et al., 2009). More recently, scanning lidars have also been employed for time-resolved monitoring of horizontal aerosol distributions (Ma et al., 2019; Wang et al., 2020; Xie et al., 2015). Such observations allow for tracking the emission sources and movement of aerosols with high accuracy (Wang et al., 2020).

30 **As for any elastic backscatter lidar measurement, observations with horizontally scanning lidar are analysed with the Klett-Fernald method (Fernald et al., 1972; Klett, 1981) to infer aerosol extinction coefficients and, subsequently, information on aerosol concentrations. To retrieve aerosol backscatter and extinction coefficients, this methods assumes a reference value at a reference distance in which the detected signal can be considered to be of purely molecular origin, i.e., aerosol contributions are negligible. In the case of a near-zenith measurement, the reference height is usually set in the aerosol- and cloud-free upper troposphere and the molecular signal is calculated from a nearby sounding or model data. The selection of a reference distance and a reference value is less straightforward in measurements with higher elevation angles as all range bins might contain considerable aerosol contributions. The likelihood of measuring purely molecular signals is virtually zero in the case of horizontal measurements as the laser beam will always be within the planetary boundary layer that is full of aerosol sources. This is further complicated if the measurement range is decreased under heterogeneous, high aerosol load conditions (Xie et al., 2015). The main factors that affect retrieval stability in the analysis of horizontal lidar measurements are the uncertainty of the system constants, errors in the processing of the background signal, and horizontal inhomogeneities of the atmospheric aerosol field (He et al., 2012). The previously proposed combination of the Klett-Fernald method with the Collis slope method (Kunz and de Leeuw, 1993) for finding the most suitable reference distance was found to be of limited use under real-world atmospheric aerosol conditions (Ma et al., 2019). The consideration of the Pearson distribution based on the slope method was found to provide reasonable choices of the reference distance and value (Wang et al., 2020). However, all those methods fail to produce reliable results under inhomogeneous aerosol conditions.**

35
40
45

Here, we propose a new method for obtaining stable solutions of the Klett-Fernald method with horizontally scanning lidar in heterogeneous aerosol conditions. The paper starts with a description of the used scanning lidar system and the novel aerosol retrieval in Section 2. Results of the application of the retrieval to horizontally scanning lidar measurements are presented in Section 3. The paper ends with a summary and conclusion in Section 4.

50

2 Data and methods

2.1 Scanning lidar instrument

The instrument used in this study is a Smart Lidar Mk II developed by Samwoo TCS Co., Ltd in collaboration with Pukyong National University (<http://www.st-lidar.com/>). It is the two-wavelength system that emits laser pulses with an energy of <1 mJ at 532 and 1064 nm. Backscattered light is collected with an 8-inch Schmidt-Cassegrain telescope and led towards a three-channel detector. The signal at 1064 nm is detected with an Excelitas avalanche photo diode. Backscattering at 532 nm is split into a parallel and a perpendicular signal with respect to the linearly polarised emitted laser light. Signals at 532 nm are detected

55

with Hamamatsu photomultiplier tubes. Data are acquired with a maximum sampling rate of 30 MHz, which corresponds to a range-resolution of 4.5 m. Further details on the instruments are provided in Noh et al. (2020).

60 The instrument can be used for horizontal scans of the aerosol distribution with a maximum range (scan radius) of 5 km. A complete 360° scan with a spatial resolution of 28.8 m and 1° takes 30 min. The scanning range and measurement point can also be set manually. In this study, observations were performed at 22 horizontal angles: 0°, 7°, 17°, 27°, 37°, 47°, 57°, 67°, 77°, 90°, 97°, 107°, 117°, 124°, 140°, 147°, 157°, 167°, 176°, 188°, 197°, 207°. One such scan takes about 15 min. The real-time data visualisation includes the distributions of PM_{10} and $PM_{2.5}$ mass concentrations, which are based on the
65 inferred aerosol extinction coefficients.

The extinction coefficients obtained by lidar were converted to $PM_{2.5}$ and PM_{10} mass concentrations commonly used in point measurements by extinction coefficients and Ångström exponents at two wavelengths. This method assumes that the lidar-derived extinction coefficients correspond to the sum of fine particles for $PM_{2.5}$ and coarse particles for $PM_{2.5-10}$. By applying the Ångström exponent formula, which has wavelength dependence, it becomes possible to separate the extinction
70 coefficients of fine and coarse particles. By dividing the separated extinction coefficient values by the mass extinction efficiency, mass concentrations can be calculated. In previous research, mass extinction efficiencies of $7 \text{ m}^2/\text{g}$ for fine particles and $6 \text{ m}^2/\text{g}$ for coarse particles were applied, and a strong correlation was observed when compared to in-situ measurements Noh et al. (2020).

2.2 Extinction coefficient retrieval

75 The elastic lidar equation at a single wavelength λ (Fernald et al., 1972; Klett, 1985) can be expressed as

$$P(r) = P_0 \frac{c\tau}{2} A \frac{\beta(r)}{r^2} \exp \left[-2 \int_0^r \alpha(r') dr' \right], \quad (1)$$

where $P(r)$ is the power received from range r , P_0 is the intensity of the emitted light at time t_0 , $\alpha(r)$ is the extinction coefficient, $\beta(r)$ is the backscatter coefficient, c is the speed of light, τ is the laser pulse duration, and A is the area of the receiver telescope. The factor $c\tau/2A$ is the instrument constant (Klett, 1981).

80 The Klett-Fernald inversion estimates an initial extinction coefficient using the slope method (Fernald et al., 1972; Klett, 1981). To calculate the aerosol extinction coefficient, the reference extinction coefficient (α_{ref}) at the reference distance r_{ref} is substituted into the Klett equation (Klett, 1985) equation:

$$\alpha(r) = \frac{\exp \left[\frac{S(r) - S_{\text{ref}}}{k} \right]}{\alpha_{\text{ref}}^{-1} + \frac{2}{k} \int_r^{r_{\text{ref}}} \exp \left[\frac{S(r') - S_{\text{ref}}}{k} \right] dr'}. \quad (2)$$

Here, $S(r) = \ln[P(r)r^2]$ contains the range-corrected signal $P(r)r^2$ while k depends on the characteristics of the measured
85 aerosols and usually varies between 0.67 and 1.0 (Curcio and Knestrck, 1958).

Before the extinction coefficient retrieval, the distance resolution is decreased from 4.8 m to 28.8 m by summing up six range bins. Then, a background correction based on the signal-to-noise ratio (SNR) of the measurement is applied. Finally,

Please, put the letters (a), (b), (c) and (d) at the bottom of each figures




Figure 1. Steps of the improved background correction at 1064 nm for measurement at 1317 local time on 23 March 2022: (a) raw lidar signal, (b) range-corrected signal, (c) background-corrected signal with the common method, and (d) background-corrected signal with the improved method. Colour refers to profiles related to different scan angles.

signals are further smoothed with a moving average using a window length of 180 m. This pre-processing ideally reduces or eliminates signal fluctuations. ~~Through this process, fluctuations can be reduced or eliminated.~~ After successful retrieval, the inferred aerosol extinction coefficient is visualised through mapping.

Our horizontally scanning lidar observations are typically conducted at low altitudes of about 10 m above ground. Hence, finding suitable r_{ref} and α_{ref} form a major part of the analysis. This process is described in the next section.

2.3 Improved analysis of horizontal scans

We make two assumptions for inferring the horizontal aerosol distribution for scanning lidar measurements at different azimuth angles. First, aerosol is distributed homogeneously over the scanned area, i.e., in all directions, if there are no emission sources. While aerosol concentration generally decreases with height, similar aerosol concentration and a negligible molecular contribution can be expected in a horizontal plane. Second, as any point in the scanned area could be an emission source, it is more likely that the reference distance for the Fernald-Klett inversion is a function of scan angles. The latter complicated the analysis as horizontal measurements are often performed to identify emission sources and track their related aerosol plumes.

Please, put the letters (a) and (b) at the bottom of each figure




Figure 2. 1064-nm range-corrected signal from measurements at **1317** local time on 23 March 2022 (a) and spread of inferred α_{ref} over 50 iterations (b).

100 Here, we propose a method for stable and spatio-temporally consistent solutions of the Fernald-Klett inversion even in heterogeneous aerosol conditions. The new method consists of two steps: the background noise correction and the identification of r_{ref} and α_{ref} for application to a full planar scan. The first step screens the data for abnormal signals at larger distances from the instrument. Previous research suggests background correction based on equidistant designation (Cao et al., 2013; Manninen et al., 2016), but these methods are optimized for vertically-pointing lidar observations. To remove unreasonable peaks and noise from the horizontal measurements at distances where we would expect to see background values, i.e., towards the end of a profile, we exclude outliers that exceed 3σ (Hodge and Austin, 2004) and added a model-fitting process based on Eq. (3)

$$y = ae^{bx} + c \quad (3)$$

110 , which is an exponential function based on the lidar equation except for data on the near range. Here, x and y represent the measurement distance and the lidar signal, respectively, while a , b , and c are constant as calculated through model fitting as the primary background value. We compare c to the average signal in the background range and pick the **lower** of the two values as background noise.

The steps of the improved background correction are shown in Figure 1. Abnormal peaks between 6 and 9 km distance are visible in the 1064-nm raw lidar signal for scan angles of 146° , 163° , and 194° . Such peaks can occur in any measurement and might be the result of scattered sunlight or temporary optical path obstruction by moving objects. If included in the background correction, these individual peaks are strong enough to move the background-corrected signal to negative values (Figure 1c) and to inhibit the calculation of a range-corrected signal (Figure 1b). The new methods lead to positive background-corrected signals (Figure 1d) that allow for calculating a range-corrected signal.

The second part of the improved method is related to identifying the reference distance for the Fernald-Klett inversion. The reference value α_{ref} is derived as the distance slope of the logarithmic range-corrected signals as calculated after the new background correction. The reference distance is the range at which the retrieved aerosol backscatter coefficient equals α_{ref} . If

set correctly, the inferred extinction coefficient decreases with distance, except for ranges at which aerosols are present (Matisoff et al., 2008). The solution becomes unstable if r_{ref} is set incorrectly. In the case of near-zenith measurements, r_{ref} is usually set to somewhere between 5 and 10 km, which refers to the free troposphere where aerosol load is generally low or negligible. Following this approach, we initially set $r_{\text{ref}} = 5$ km. However, this fixed value cannot be universally applied in horizontal
125 measurements. Instead, r_{ref} and α_{ref} have to be set to regions where aerosol is relatively homogeneously distributed.

The steps for identifying α_{ref} are illustrated in Figure 2. At each scan angle, we consider 21 reference points for calculating α_{ref} starting at 1 km distance in intervals of 250 m and refer to the result as multi-section α_{ref} (Figure 2a). The total number of ~~thus~~ inferred values of α_{ref} is 21 times the number of scan angles (22 from 0° to 207° in this study). To converge in α_{ref} we iteratively remove outliers from the average slope calculation if they exceed one standard deviation σ . Routinely, 50 iterations
130 are performed but most outliers are already removed after ten iterations (Figure 2b). **Finally, the realistic α_{ref} is used in the Fernald-Klett inversion with $r_{\text{ref}} = 5$ km.**

The distinctive feature of this method is that the α_{ref} in the multi-section area replaces the value at 5 km, where the farthest distance has reliable signals. Therefore, the reference distance assumes all stable points without emissions or noise rather than pinpointing any specific point within the analysis area. Substituting the 5 km value with the α_{ref} obtained iteratively when
135 calculating using the Klett inversion method implies that we can calculate the reliable extinction coefficient, even if there was noise in the long-range region.

We refer to the new algorithm to calculate the extinction coefficient from horizontally scanning lidar measurements based on the Fernald-Klett method, as the multi-section method. An overview of the different steps of the data processing is presented in Figure 3.

140 2.4 Study area

The scanning lidar system was installed on the roof of Dangjin Port Center ($36^\circ 59' 07.7''\text{N}$ $126^\circ 44' 44.2''\text{E}$) to scan the Anseom port area (Godae-ri, Songak-eup, Dangjin-si Chungcheongnam-do, Republic of Korea). Dangjin has a developed steel industry, and many steelworks exist in the Seokmun National Industrial Complex. In addition, there are various large-scale industrial complexes, such as Bugok Industrial Complex and Songsan Commercial Complex. The location of the site and the scanned
145 area are illustrated in Figure 4.

3 Results and discussion

The multi-section method allows for retrieving values of α_{ref} in areas of homogeneous aerosol conditions that are consistent within individual scans. As these values are assumed to refer to ambient background conditions, it is expected that there is little variation between subsequent scans with 10 to 15 min distance.

150 Figure 5 shows that the fixed method, i.e. rigidly selecting α_{ref} at 5 km distance for each scan angle individually, leads to a large spread of values for single scan and between scans. Some of those values cannot be used to produce stable solutions of the Fernald-Klett inversion. In contrast, the multi-section method produces reference values that represent the entire scan and




Figure 3. Data processing flowchart of the multi-section method.

are also consistent between time steps. These results allow for always obtaining stable solutions of the Fernald-Klett inversion and, thus, an automated quantitative analysis of the measurements.

155 Aerosol extinction is a measure of aerosol load. As α_{ref} represents aerosol concentrations at homogeneous background conditions, one can expect it to correlate with other measures of aerosol load such as $PM_{2.5}$ mass concentrations. Such measurements are performed at the national air quality monitoring sites of the Korean Ministry of Environment. To verify the results of the multi-section method, inferred α_{ref} is compared to $PM_{2.5}$ mass concentrations measured at a site about 2.8 km away from the lidar's scan area (see Figure 4). Figure 6 presents a high correlation ($r^2 = 0.77$) between α_{ref} at 532 nm and
 160 with $PM_{2.5}$ mass concentrations with most points within the 95% prediction band. Outliers are likely related to the different time resolutions of the measurements with lidar data available in intervals of about 15 min and in-situ mass concentrations

Please, put the letters (a) and (b) at the bottom of each figures




Figure 4. Location (a) of the scanning lidar at Dangjin port center, South Korea, and (b) the scanned area with the locations of industrial sites. The location of a site of the national air quality monitoring network is marked by the yellow dot.




Figure 5. Temporal change in α_{ref} as inferred using the conventional fixed method (gray bars) and the new multi-section method (red) from scanning lidar measurements at 532 (right) and 1064 nm (left) for 45 planar scans between 0917 and 2053 on 23 March 2022.

are given as hourly averages. In contrast to the lidar measurements at 532 nm, α_{ref} at 1064 nm is less correlated to $PM_{2.5}$ concentration ($r^2 = 0.74$) and also shows a broader 95% prediction band. While the different temporal resolution is likely to

Please, put the letters (a) and (b) at the bottom of each figures





Figure 6. Comparison of α_{ref} as inferred by the multi-section method at 1064 nm (left) and 532 nm (right) at measures between 20 Feb and 29 Mar 2022 with $PM_{2.5}$ mass concentrations at a measurement site of the national observatory of the Korean Ministry of Environment. The linear regression is shown as a dashed line, while the colored area indicates the 95% prediction band.

165 affect the comparison at 1064 nm as well, it is well known from light-scattering theory that longer lidar wavelengths are less sensitive to fine particles.

For the purpose of monitoring air quality, the aerosol extinction coefficients inferred from our scanning lidar measurements are converted to $PM_{2.5}$ and PM_{10} mass concentrations using the wavelength-dependent Ångström exponent, lidar ratio, and aerosol extinction efficiency as mentioned in Section 2.1 (Liu et al., 2020; Noh et al., 2008, 2020). The lidar-derived PM mass distribution is interpolated by primary linear regression fitting for visualisation.

170 The impact of the improved method for the analysis of scanning lidar measurements on the retrieved aerosol extinction coefficient and the subsequently inferred PM_{10} mass concentration is presented in Figure 7. The use of a reference value derived at 5 km distance for different scan angles causes a strong overestimation of extinction coefficient maxima as it is strongly affected by signal noise at that distance. At the same time, individual profiles differ strongly in their baseline values. This is visible by a large spread in the profiles in Figure 7a. The spread is reduced to a consistent and stable background when
175 the multi-section method is applied. As a result, the PM_{10} field inferred from the multi-section analysis of the scanned plane is more homogeneous than the one obtained using the traditional method. It no longer contains exaggerated emission sources, increased values at the fringes of the covered area, or artificial features in close vicinity to the lidar's position. Consequently, the new analysis method is found very valuable for reliably and automatically obtaining secondary products for environmental monitoring by users without lidar expertise.



Please, put the letters (a), (b), (c) and (d) at the bottom of each figures

Figure 7. Angular resolved extinction coefficient at 532 nm (top row) and inferred PM_{10} concentration (bottom row) as obtained by using the fixed reference value method (left column) and the multi-section method (right column) from a lidar scan at 2014 local time at 27 February 2022. Colored lines in the upper panels refer to different scan angles while the chading in the lower panels marks PM_{10} concentration.

180 4 Conclusions

We have developed a horizontally scanning lidar for monitoring the spatio-temporal distribution of aerosol concentrations. The observations are used to obtain aerosol extinction coefficients as a function of scan angle, wavelength, and distance. To overcome difficulties in the application of the Fernald-Klett method to ~~our~~ horizontal measurements, we have developed a novel method for inferring the reference extinction coefficient. The new multi-section method first reduces background noise by dismissing signal peaks that exceed 3σ of the mean over individual scans of each angle. After the noise correction, an iterative approach is used for identifying a value of α_{ref} that is stable within full scan measurements and is, thus, likely to represent ambient background conditions. A comparison of lidar-inferred aerosol mass concentrations to independently measured $PM_{2.5}$ mass concentrations at Korean air-quality monitoring sites confirms α_{ref} can represent the concentration of ambient aerosols. The r^2 values of $PM_{2.5}$ mass concentration with α_{ref} on 1064 nm and 532 nm were 0.74 and 0.77, respectively. The application of the new method leads to a consistent picture of extinction coefficients and aerosol concentrations throughout the scanned

area. These improvements related to the new analysis method emphasize the applicability of horizontally scanning aerosol lidar measurements for quantitative source identification and air-quality monitoring.

Code and data availability. The dataset used in this study is available upon request from the corresponding author.

Author contributions. GK and GP performed the measurements. JS and DK designed conceptualization and methodology. JS, GK, and GP performed the data analysis. All authors contributed to the discussion of the methodology and results as well as to the preparation and revision of the manuscript.

Competing interests. The authors declare no competing interests .

Acknowledgements. This work was supported by the "Graduate school of Particulate matter specialization." of Korea Environmental Industry & Technology Institute grant funded by the Ministry of Environment, Republic of Korea

200 **References**

- Cao, N., Zhu, C., Kai, Y., and Yan, P.: A method of background noise reduction in lidar data, *Appl. Phys. B*, 113, 115-123, <https://doi.org/10.1007/s00340-013-5447-9>, 2013.
- Curcio, J. and Knestrick, G.: Correlation of atmospheric transmission with backscattering, *J. Opt. Soc. Am.*, 48, 686-689, <https://doi.org/10.1364/JOSA.48.000686>, 1958.
- 205 De Wekker, S. F. and Mayor, S. D.: Observations of atmospheric structure and dynamics in the Owens Valley of California with a ground-based, eye-safe, scanning aerosol lidar, *Journal of applied meteorology and climatology*, 48, 1483-1499, <https://doi.org/10.1175/2009JAMC2034.1>, 2009.
- Dockery, D. W., Pope, C. A., Xu, X., Spengler, J. D., Ware, J. H., Fay, M. E., Ferris Jr, B. G., and Speizer, F. E.: An association between air pollution and mortality in six US cities, *New England journal of medicine*, 329, 1753-1759, 1993.
- 210 Doherty, R. M., Heal, M. R., and O'Connor, F. M.: Climate change impacts on human health over Europe through its effect on air quality, *Environmental Health*, 16, 33-44, 2017.
- Doyle, J. D., Grubišić, V., Brown, W. O., De Wekker, S. F., Dörnbrack, A., Jiang, Q., Mayor, S. D., and Weissmann, M.: Observations and numerical simulations of subrotor vortices during T-REX, *J. Atmos. Sci.*, 66, 1229-1249, <https://doi.org/10.1175/2008JAS2933.1>, 2009.
- Eichinger, W. E., Cooper, D. I., Archuleta, F. L., Hof, D., Holtkamp, D. B., Karl, R. R., Quick, C. R., and Tiee, J.: Development of a scanning, solar-blind, water Raman lidar, *Appl. Opt.*, 33, 3923-3932, <https://doi.org/10.1364/AO.33.003923>, 1994.
- 215 Fang, Y., Mauzerall, D. L., Liu, J., Fiore, A. M., and Horowitz, L. W.: Impacts of 21st century climate change on global air pollution-related premature mortality, *Climatic Change*, 121, 239-253, 2013
- Fernald, F. G., Herman, B. M., and Reagan, J. A.: Determination of aerosol height distributions by lidar, *Journal of Applied Meteorology and Climatology*, 11, 482-489, 1972.
- 220 Fiore, A. M., Naik, V., Spracklen, D. V., Steiner, A., Unger, N., Prather, M., Bergmann, D., Cameron-Smith, P. J., Cionni, I., and Collins, W. J.: Global air quality and climate, *Chemical Society Reviews*, 41, 6663-6683, 2012
- He, T.-Y., Stanič, S., Gao, F., Bergant, K., Veberič, D., Song, X.-Q., and Dolžan, A.: Tracking of urban aerosols using combined LIDAR-based remote sensing and ground-based measurements, *Atmos. Meas. Tech.*, 5, 891-900, <https://doi.org/10.5194/amt-5-891-2012>, 2012.
- Hodge, V. and Austin, J.: A survey of outlier detection methodologies, *Artificial intelligence review*, 22, 85-126, <https://doi.org/10.1007/s10462-004-4304-y>, 2004.
- 225 Isaksen, I. S., Granier, C., Myhre, G., Berntsen, T., Dalsøren, S. B., Gauss, M., Klimont, Z., Benestad, R., Bousquet, P., and Collins, W.: Atmospheric composition change: climate-chemistry interactions, *Atmospheric Environment*, 43, 5138-5192, 2009.
- Jacob, D. J. and Winner, D. A.: Effect of climate change on air quality, *Atmospheric environment*, 43, 51-63, 2009.
- Kaufman, Y. J., Tanré, D., and Boucher, O.: A satellite view of aerosols in the climate system, *Nature*, 419, 215-223, 2002.
- 230 Klett, J. D.: Stable analytical inversion solution for processing lidar returns, *Appl. Opt.*, 20, 211-220, <https://doi.org/10.1364/AO.20.000211>, 1981.
- Klett, J. D.: Lidar inversion with variable backscatter/extinction ratios, *Appl. Opt.*, 24, 1638-1643, <https://doi.org/10.1364/AO.24.001638>, 1985.
- Kunz, G. J. and de Leeuw, G.: Inversion of lidar signals with the slope method, *Appl. Opt.*, 32, 3249-3256, <https://doi.org/10.1364/AO.32.003249>, 1993.
- 235

- Lee, K. H. and Wong, M. S.: Vertical Profiling of Aerosol Optical Properties From LIDAR Remote Sensing, Surface Visibility, and Columnar Extinction Measurements, in: *Remote Sensing of Aerosols, Clouds, and Precipitation*, Elsevier, 23-43, 2018.
- Liu, J., Ren, C., Huang, X., Nie, W., Wang, J., Sun, P., Chi, X., and Ding, A.: Increased aerosol extinction efficiency hinders visibility improvement in eastern China, *Geophys. Res. Lett.*, 47, <https://doi.org/10.1029/2020GL090167>, 2020.
- 240 Ma, X., Wang, C., Han, G., Ma, Y., Li, S., Gong, W., and Chen, J.: Regional Atmospheric Aerosol Pollution Detection Based on LiDAR Remote Sensing, *Rem. Sens.*, 11, <https://doi.org/10.3390/rs11202339>, 2019.
- McDonnell, W. F., Nishino-Ishikawa, N., Petersen, F. F., Chen, L. H., and Abbey, D. E.: Relationships of mortality with the fine and coarse fractions of long-term ambient PM10 concentrations in nonsmokers, *Journal of Exposure Science & Environmental Epidemiology*, 10, 427-436, 2000.
- 245 Manninen, A. J., O'Connor, E. J., Vakkari, V., and Petäjä, T.: A generalised background correction algorithm for a Halo Doppler lidar and its application to data from Finland, *Atmos. Meas. Tech.*, 9, 817–827, <https://doi.org/10.5194/amt-9-817-2016>, 2016.
- Mattis, I., Müller, D., Ansmann, A., Wandinger, U., Preißler, J., Seifert, P., and Tesche, M.: Ten years of multiwavelength Raman lidar observations of free-tropospheric aerosol layers over central Europe: Geometrical properties and annual cycle, *J. Geophys. Res.: Atmos.*, 113, <https://doi.org/10.1029/2007JD009636>, 2008.
- 250 Nakane, H. and Sasano, Y.: Structure of a Sea-breeze Front Revealed by Scanning Lidar Observation, *J. Meteorol. Soc. Japan. Ser. II*, 64, 787-792, https://doi.org/10.2151/jmsj1965.64.5_787, 1986.
- Noh, Y. M., Kim, Y. J., and Müller, D.: Seasonal characteristics of lidar ratios measured with a Raman lidar at Gwangju, Korea in spring and autumn, *Atmos. Environ.*, 42, 2208-2224, <https://doi.org/10.1016/j.atmosenv.2007.11.045>, 2008.
- Noh, Y. M., Lee, H., Mueller, D., Lee, K., Shin, D., Shin, S., Choi, T. J., Choi, Y. J., and Kim, K. R.: Investigation of the diurnal pattern of the vertical distribution of pollen in the lower troposphere using LIDAR, *Atmos. Chem. Phys.*, 13, 7619–7629, <https://doi.org/10.5194/acp-13-7619-2013>, 2013.
- 255 Noh, Y. M., Müller, D., Shin, S.-k., Shin, D., and Kim, Y. J.: Vertically-resolved profiles of mass concentrations and particle backscatter coefficients of Asian dust plumes derived from lidar observations of silicon dioxide, *Chemosphere*, 143, 24-31, <https://doi.org/10.1016/j.chemosphere.2015.03.037>, 2016.
- 260 Noh, Y. M., Kim, D., Choi, S., Choi, C., Kim, T., Kim, G., and Shin, D.: High resolution fine dust mass concentration calculation using two-wavelength scanning lidar system, *Korean J. Rem. Sens.*, 36, 1681-1690, <https://doi.org/10.7780/kjrs.2020.36.6.3.5>, 2020, in Korean.
- Palm, S. P., Melfi, S. H., Carter, D. L.: New airborne scanning lidar system: Applications for atmospheric remote sensing, *Appl. Opt.* 33, 5674-5681, <https://doi.org/10.1364/AO.33.005674>, 1994.
- Papayannis, A., Kambezidis, H. D., and Asimakopoulos, D. N.: Development of a mobile three-dimensional scanning lidar system for aerosol monitoring in rural areas in Greece, *Internat. J. Rem. Sens.*, 15, 361-368, <https://doi.org/10.1080/01431169408954079>, 1994.
- 265 Pope III, C. A., Ezzati, M., and Dockery, D. W.: Fine-particulate air pollution and life expectancy in the United States, *New England Journal of Medicine*, 360, 376-386, 2009.
- Ren, C. and Tong, S.: Health effects of ambient air pollution—recent research development and contemporary methodological challenges, *Environmental Health*, 7, 1-10, 2008.
- 270 Sasano, Y., Hirohara, H., Yamasaki, T., Shimizu, H., Takeuchi, N., and Kawamura, T.: Horizontal Wind Vector Determination from the Displacement of Aerosol Distribution Patterns Observed by a Scanning Lidar, *J. Appl. Meteor. Clim.*, 21, 1516-1523, [https://doi.org/10.1175/1520-0450\(1982\)021<1516:HWVDFT>2.0.CO;2](https://doi.org/10.1175/1520-0450(1982)021<1516:HWVDFT>2.0.CO;2), 1982.

- Wang, J., Liu, W., Liu, C., Zhang, T., Liu, J., Chen, Z., Xiang, Y., and Meng, X.: The Determination of Aerosol Distribution by a No-Blind-Zone Scanning Lidar, *Rem. Sens.*, 12, <https://doi.org/10.3390/rs12040626>, 2020.
- 275 Winker, D., Pelon, J., Coakley Jr, J., Ackerman, S., Charlson, R., Colarco, P., Flamant, P., Fu, Q., Hoff, R., and Kittaka, C.: The CALIPSO mission: A global 3D view of aerosols and clouds, *Bull. Am. Meteorol. Soc.*, 91, 1211-1230, <https://doi.org/10.1175/2010BAMS3009.1>, 2010.
- Xie, C., Zhao, M., Wang, B., Zhong, Z., Wang, L., Liu, D., and Wang, Y.: Study of the scanning lidar on the atmospheric detection, *J. Quantitative Spectr. Rad. Trans.*, 150, 114-120, <https://doi.org/10.1016/j.jqsrt.2014.08.023>, 2015.