

# Advances and Prospects of Deep Learning for Medium-Range Extreme Weather Forecasting

Leonardo Olivetti<sup>1</sup> and Gabriele Messori<sup>1,2</sup>

<sup>1</sup>Department of Earth Sciences and Centre of Natural Hazards and Disaster Science, Uppsala University, 75236 Uppsala, Sweden

<sup>2</sup>Department of Meteorology and Bolin Centre for Climate Research, Stockholm University, 10691 Stockholm, Sweden

**Correspondence:** Leonardo Olivetti (leonardo.olivetti@geo.uu.se)

**Abstract.** In recent years, deep learning models have rapidly emerged as a standalone alternative to physics-based numerical models for medium-range weather forecasting. Several independent research groups claim to have developed deep learning weather forecasts which outperform those from state-of-the-art ~~physies-basies~~ physics-based models, and operational implementation of data-driven forecasts appears to be drawing near. Yet, questions remain about the capabilities of deep learning models to provide robust forecasts of extreme weather. This paper provides an overview of recent developments in the field of deep learning weather forecasts, and scrutinises the challenges that extreme weather events pose to leading deep learning models. Lastly, it argues for the need to tailor data-driven models to forecast extreme events, and proposes a foundational workflow to develop such models.

## 1 Introduction

The very first deep learning models for weather applications date back to the 1990s (Schizas et al., 1991; Hall et al., 1999), and extensive research on the use of deep learning models for weather forecasting at a local scale (e.g. Zhu et al., 2017; Li et al., 2018; Haidar and Verma, 2018) and for short-term weather predictions (e.g. Klein et al., 2015; Qiu et al., 2017) has been ongoing since the mid-2010s. More recently, deep learning models have also been employed successfully as a nowcasting tool for precipitation (e.g. Ravuri et al., 2021; Espeholt et al., 2021) and as post-processing tools for numerical weather forecasts (e.g. Grönquist et al., 2021; Silini et al., 2022). However, it is only in the last few years that deep learning models have started to become competitive as self-standing medium-range and subseasonal large-scale forecasting tools. As late as 2021, in a popular review article Schultz et al. (2021) noted how deep learning research in the field of meteorology "is still in its infancy" and underscored that "a number of fundamental breakthroughs are needed" before deep learning applications may compete with physics-based weather forecasts.

20

Much has changed since then. From early 2022, at least ~~six~~ seven different research groups (Pathak et al., 2022; Bi et al., 2023; Keisler, 2022; Lam et al., 2023; Chen et al., 2023a; Nguyen et al., 2023; Chen et al., 2023b) claim to have developed deep learning models able to forecast key atmospheric variables with greater accuracy than deterministic forecasts from the European Centre for Medium-Range Weather Forecasts

25 (Pathak et al., 2022; Bi et al., 2023; Keisler, 2022; Lam et al., 2022; Chen et al., 2023a; Nguyen et al., 2023) (ECMWF), widely  
regarded as the leading global numerical weather predictions. In addition to technical advances, a key contextual enabler of this  
explosive development has been the contribution of "Big Tech" - major private actors in the field of information technology  
(Bauer et al., 2023). This has contributed to closing the gap between state-of-the-art deep learning, cutting-edge computational  
resources and weather practitioners, and has attracted a larger number of machine-learning experts to the field. Although only  
30 one of several developments within machine learning, we argue for a crucial role of Big Tech in the advent of the latest genera-  
tion of large-scale deep learning weather forecast models, which notably require larger computational resources and more spe-  
cialised knowledge than previous state-of-the-art models (Bi et al., 2023; Lam et al., 2022) (Bi et al., 2023; Lam et al., 2023).

Despite this astounding rise, deep learning models for weather forecasting still face a number of challenges. Some of these  
35 are well-known: deep learning approaches typically do not incorporate physical constraints (Ren et al., 2021), which may  
lead to unphysical forecasts. Furthermore, deep learning models usually produce deterministic forecasts, making it hard to  
compute reasonable estimates of the uncertainty around their predictions (Schultz et al., 2021). A less-studied challenge is  
that data-driven models have limited capabilities of extrapolating at the edge of their training range or beyond (Gutzwiller  
and Serno, 2023). These models may thus not be as helpful as numerical models for investigating future climates (Scher and  
40 Messori, 2019a) and, more prominently, might struggle with forecasting extreme weather events lying in the tails of a me-  
teorological variable's distribution (Watson, 2022). If unaddressed, the latter limitation is likely to hold back deep learning  
models from becoming a credible alternative to numerical, physics-driven forecasting models. Indeed, accurate predictions  
and early warnings of extreme weather play a key role in disaster prevention and mitigation (World Meteorological Organiza-  
tion, 2022; Merz et al., 2020), and are crucial for several economically prominent activities, including but not limited to the  
45 energy and insurance sectors (e.g. Kron et al., 2019). Nonetheless, the pace of development of deep learning weather predic-  
tion models continues to be rapid, and a number of promising approaches are being developed to address the above challenges  
(e.g. Bi et al., 2023; Zhang et al., 2023; Cisneros et al., 2023; Guastavino et al., 2022; Clare et al., 2021; Kashinath et al., 2021)  
(e.g. Hu et al., 2023; Bi et al., 2023; Zhang et al., 2023; Cisneros et al., 2023; Guastavino et al., 2022; Clare et al., 2021; Kashinath et al.,

50  
This article reflects on the rise of medium-range weather forecasting with deep learning, the challenges currently being faced  
when forecasting extreme weather, and the future perspectives opened by the latest research advances. We do not consider in  
detail issues related to computing forecast uncertainty estimates (Scher and Messori, 2021; Clare et al., 2021) or incorpo-  
rating physical reasoning in deep learning models (Kashinath et al., 2021; Beucler et al., 2020), for which we remand the  
55 reader to some recent review articles discussing these topics (Molina et al., 2023; de Burgh-Day and Leeuwenburg, 2023).  
We begin with a survey of recent developments in the field of large-scale deep learning weather prediction (DLWP), with a  
focus on the aforementioned models claiming to outperform deterministic state-of-the-art numerical weather prediction models  
(Pathak et al., 2022; Bi et al., 2023; Keisler, 2022; Lam et al., 2022; Chen et al., 2023a; Nguyen et al., 2023)  
(Pathak et al., 2022; Keisler, 2022; Bi et al., 2023; Lam et al., 2023; Chen et al., 2023a; Nguyen et al., 2023; Chen et al., 2023b)

60 . Then, we provide a technical justification of why those models might struggle with predictions in the tails of the distribution – namely weather extremes. Last, we outline alternative approaches which may be employed in order to design deep learning models specifically tailored to extreme weather forecasting.

## 2 Overview of DLWP models

### 2.1 Early DLWP efforts

65 The very first DLWP models were developed in the 1990s (Schizas et al., 1991; Hall et al., 1999) and followed a "feed-forward architecture" (Ivakhnenko and Lapa, 1965) (FNNs), a unidirectional, non-recurrent structure where the input is transmitted through the network sequentially. FNNs are limited in treating spatial data, due to their inability to leverage spatial patterns and their large computational burden, which makes them unsuitable for large datasets. Because of these reasons, FNNs were soon replaced by convolutional neural networks (LeCun and Bengio, 1995) (CNNs), which can learn spatial patterns and display  
70 better scalability. Early meteorological applications of CNNs had either a very local character (Zhu et al., 2017; Li et al., 2018; Haidar and Verma, 2018), or were aimed at producing nowcasts with lead times from a few minutes to a few hours (Klein et al., 2015; Qiu et al., 2017).

A further step in the direction of today's medium-range DLWP models was taken with the adoption of recurrent neural network architectures (Rumelhart et al., 1986; Bengio et al., 1994; Bengio and Gingras, 1995) (RNNs) and subsequently long-short term memory models (Hochreiter and Schmidhuber, 1997) (LSTMs). These follow the dynamical nature of time-series data by making current observations of the variable of interest depend on previous iterations of that same variable. They thus provide an effective framework for accounting for time-dependencies in the data, and produce predictions on multiple time-scales. However, due to their sequential, recursive nature, RNNs and LSTMs are hard to parallelise, preventing an effective  
80 exploitation of modern high-resolution climate reanalysis datasets, such as ERA 5 (Hersbach et al., 2020).

FNNs, CNNs, and RNNs/LSTMs are the cornerstones of deep learning, and were also the dominant supervised learning architectures within DLWP at the time the review by Schultz et al. (2021) was written. Since then, a number of new architectures have been developed, which address the limitations of the classical models through a number of creative innovations, often  
85 combining different elements of pre-existing architectures. Here, we focus primarily on those deep learning applications which are most relevant to medium-range, large-scale forecasting of weather extremes. We nonetheless acknowledge that data-driven nowcasting and subseasonal forecasting are both thriving fields of research with many potential applications, also for extreme events (e.g. Chkeir et al., 2023; Barnes et al., 2023; Civitarese et al., 2021).

## 2.2 State-of-the-art DLWP

90 A common element of current global medium-range DLWP models is the use of a large number of input variables ("features"),  
at high temporal and spatial resolution. This is in contrast to older models, which to a large extent relied on a theoretical un-  
derstanding of atmospheric dynamics and feature selection for the choice of a few atmospheric variables and pressure levels  
(e.g. Dueben and Bauer, 2018; Weyn et al., 2019). For example, [Lam et al. \(2022\)](#) [Lam et al. \(2023\)](#) include 6 input variables  
on 37 pressure levels, as well as 5 inputs at single levels and several constant masks. Similarly, Bi et al. (2023) make use of 4  
95 atmospheric variables at 13 pressure levels, 4 surface variables and 3 constant masks.

The fact that the latest DLWP models make use of a larger number of features than previously, may be partly ascribed to  
computational improvements and partly ascribed to deep learning architectural developments. A key one in this respect is the  
encoder-decoder architecture (Kramer, 1991; Cho et al., 2014). Encoders and decoders can be seen as two separate neural  
100 networks connected to each other through a latent encoding vector. Here, "latent" refers to quantities inferred indirectly from  
the input data. The aim of the first network is to identify and compress ("encode") into the encoding vector the most important  
features contained in the input data. The aim of the second network is to upscale ("decode") the information encoded in the  
encoding vector until it reaches the dimensionality of the desired output. The target output can then either be the same as the  
input, perhaps with some small variation (self-supervised problems—e.g. variational autoencoders), or different from the input  
105 in terms of time-scale, spatial resolution or even actual features.

In DLWP, the target output is usually different from the input, and encoders are mostly used to reduce the dimensionality  
of the input and identify the key latent features. This allows models to use very large input layers – namely many different at-  
mospheric variables at several pressure levels. Encoder-decoder architectures are used to this effect within cutting-edge global  
110 DLWP applications, such as Keisler (2022), [Lam et al. \(2022\)](#) [Lam et al. \(2023\)](#), Bi et al. (2023) and Chen et al. (2023a).

The encoder-decoder structure is also at the core of transformers (Vaswani et al., 2017), a recent architectural innovation  
allowing for efficient parallelisation of sequential data. Transformers use a so-called attention mechanism (Bahdanau et al.,  
2015), i.e. they compute a score for each element in the input sequence which determines its relevance for the associated de-  
115 coding step. This removes the need for sequential data intake, thus enabling an effective utilisation of modern GPUs and TPUs  
for time-series data. This represents a major improvement over classic RNNs, which instead rely on serial arrangement to learn  
key features and are therefore not easily parallelisable.

Recently, the use of transformers has been extended to computer vision tasks as an alternative, or complement, to CNNs.  
120 Dosovitskiy et al. (2020) propose the use of vision transformers, which adapt transformers to visual tasks by introducing an  
innovative pre-processing step: images are first divided into patches of fixed  $N \times N$  size, and then run through a flattening layer,  
so that each patch can be treated as a separate token. Then, transformers are applied just as in sequential tasks. This approach

is applied to weather forecasting for instance by Pathak et al. (2022) and Bi et al. (2023), who use flattened patches of  $4 \times 4$  pixels to apply transformers to gridded meteorological data.

125

A distinct approach featured by several global DLWP models is the use of graph neural networks [Searselli et al. \(2009\)](#) ([Scarselli et al., 2009](#)) (GNNs). Classic CNNs implicitly assume regular grids, in which the distance between points and the importance of each point is fixed (Thuemmel et al., 2023). This assumption is problematic in the case of global forecast models, as climate variables are often provided on regular latitude-longitude or reduced-Gaussian grids. Given that the Earth is quasi-  
130 spherical, the distance between degrees of latitude is greater at the equator than at the poles, and even the length of degrees of longitude varies slightly with latitude. GNNs, unlike CNNs, allow for complex, quasi-spherical shapes. A way to understand this is by drawing a parallel with cartesian and spherical coordinates. CNNs, similar to cartesian coordinates, assume a "flat" grid, and in the best case may introduce a weighting scheme not unlike the one of the  $\beta$ -plane, whereas GNNs can model the relation between the nodes as a complex polygon resembling a sphere.

135

The bearing of the architectural change from CNNs to GNNs on forecast performance is still object of debate, and it is likely it plays a larger role for global rather than local-to-regional applications, given the greater variation in the size of the grid cells in the former case. Yet, several recent deep learning weather forecasting models introduce the use of GNNs to good effect. For instance, Keisler (2022) and more prominently [Lam et al. \(2022\)](#) [Lam et al. \(2023\)](#) make use of GNNs to obtain  
140 accurate medium-range forecasts of several key atmospheric variables, managing to outperform the most accurate ECMWF deterministic forecasts available at the time of their publication.

Other current approaches look at ways of accounting for Earth's quasi-spherical nature within a CNN framework, without resorting to GNNs. Examples of this include spherical convolutions (Boomsma and Frellsen, 2017) and spherical cross-  
145 correlations (Cohen et al., 2018). Recent work by Scher and Messori (2023) showcases the advantages of spherical and hemispheric convolutions over classic CNNs. The authors compare models based on different architectures using the Weatherbench dataset (Rasp et al., 2020), and show that models incorporating spherical or hemispheric convolutions produce more accurate medium-range forecasts of 500 hPa geopotential height (Z500) and 850 hPa temperature (t850) than models featuring classic CNN architectures. However, feature-rich and high-resolution applications of this kind are still in development.

150


Finally, we outline how recent medium-range DLWP models treat temporal information. Instead of trying to incorporate the time aspect directly into the model in the form of extra features or channels, they account for the sequential nature of data through a dynamic approach, by using the predictions generated by a given model timestep as the input for the next model timestep. In other words, as clearly stated by Chen et al. (2023a), they approximate the forecast at time  
155  $t$ ,  $Y^t = f(Y^{t-1} + Y^{t-2} + \dots + Y^1)$  through an autoregressive approach of order 1 (AR 1), namely by using sequentially the forecasts at the previous time-steps:  $Y^t = f(Y^{t-1})$ ,  $Y^{t-1} = f(Y^{t-2})$ , ...,  $Y^2 = f(Y^1)$ . A similar approach is adopted by [Lam et al. \(2022\)](#) [Lam et al. \(2023\)](#), with the main difference being that the data generated by the previous two forecasts are

used as input for the latest forecast (AR 2).

160 If the focus is on a specific lead time, it is however not clear whether this iterative approach always outperforms training a model to make a single prediction at the chosen lead-time (Scher and Messori, 2019b). [In this regard, Chen et al. \(2023b\) show that producing a cascade of models finetuned on different time scales can lead to improvements in performance compared to a single model optimised on the whole forecasting window.](#)


165 An overview of the DLWP model developments over time is provided in Figures 1 and 2. Figure 1 summarises the evolution of model architectures described in this section, while Figure 2 outlines the continuous improvements in the spatial and temporal domains handled by DLWP models. The current leading global DLWP models are systematically presented in Table 1, where we provide information on the inputs, outputs, main architectural innovations and performance for extreme weather forecasts of each model.

## DLWP through time - architectures



**Figure 1.** Evolution of deep learning weather prediction (DLWP) through time: From feed-forward neural networks to graph neural networks and vision transformers.

## DLWP through time - temporal and geographical scale



**Figure 2.** Evolution of the largest geographical and temporal scales of deep learning weather prediction (DLWP) models over time.



**Table 1.** Overview of recent global medium-range DLWP applications. Abbreviations: lsm=land-sea mask, MSLP=mean sea-level pressure RH=relative humidity, Q=specific humidity, SP=surface pressure, T=temperature, ~~TCMWIWV~~=integrated total column water vapour, U=u-wind, V=v-wind, Z=geopotential, TP=total precipitation, lat=latitude, lon=longitude, hr=hour of the day, 2m=2m height, 10m=10m height, 500=500 hPa, 850=850hPa, HRES= ECMWF high resolution deterministic forecast.

Paper	Inputs	Tested outputs	Main innovation	Performance on extreme values
Pathak et al. (2022)	<del>Single-level</del> <u>Single level</u> : T2m, 10mU, 10mV, SP, MSLP, <del>integrated</del> — <del>TCWV</del> . <del>Multiple-level</del> <u>IWV</u> . <u>Multiple levels</u> : Z, U, V, Q, T.	Z500.	First paper with performance comparable to physics-based numerical models. Use of vision transformers (Dosovitskiy et al., 2020).	Model evaluation on extreme quantiles, tends to underestimate high quantiles of 10m zonal wind and total precipitation. Source code and trained models available.
Keisler (2022)	Static: lsm, orography. Single level: solar radiation. Multiple levels: Z,U,V,Q,T.	Z500, T850, wind-speed 500, RH700.	Use of GNNs (Battaglia et al., 2018).	Unknown. <a href="#">Source code available</a> .
Bi et al. (2022, 2023)	<del>Single-level</del> <u>Single level</u> : T2m, 10mU, 10mV, MSLP. <del>Multiple-level</del> <u>Multiple levels</u> : Z, U, V, Q, T.	Z500, T500, Q500, U500, V500, Z850, T850, T2m, 10mU, 10mV. MSLP for cyclone tracking example.	Three-dimensional vision transformer, hierarchical temporal aggregation to decrease computational burden.	Better than <del>ECMWF operational forecast</del> <u>HRES</u> in binary detection of T2m extremes at 6 days lead time despite tendency to underestimate their magnitude (Ben-Bouallegue et al., 2023). More precise tracking of tropical cyclones than HRES in a case study. <del>Can provide large ensemble forecast</del> . Source code and trained models available.
<del>Lam et al. (2022)</del> <u>Lam et al. (2022, 2023)</u>	Static: lsm, orography, <del>latitude</del> — <del>longitude</del> <u>lat, lon</u> . Single level: T2m, 10mU and 10mV, MSLP, <del>total</del> — <del>precipitation</del> <u>TP</u> , solar radiation, <del>time of the day</del> <u>hr</u> , elapsed year progress. Multiple levels: Z, U, V, W, Q, T.	Single level: T2m, 10mU and 10mV, MSLP. Multiple <del>level</del> <u>levels</u> : Z, U, V, Q, T.	Graphcast, <del>GNN-based</del> <u>GNN-based</u> architecture (Battaglia et al., 2018). Much larger set of inputs and outputs than predecessors.	More precise tracking of cyclones and atmospheric rivers than HRES at most lead times. Better or comparable to HRES in binary detection of T2m extremes at 5 days. Source code and trained models available.
Chen et al. (2023a)	Single level: T2m, 10mU, 10mV, MSLP. Multiple <del>level</del> <u>levels</u> : Z, U, V, RH, T.	Z500, T500, U500, V500, Z850, T850, U850, V850, T2m, 10mU, MSLP.	Transformer with encoder-fuse-decoder architecture.	Unknown. <a href="#">Trained model available</a> .
Nguyen et al. (2023)	Static: lsm, orography. Single level: T2m, 10mU and 10mV. Multiple <del>level</del> <u>levels</u> : Z, U, V, Q, RH, T.	Designed to allow for flexible outputs. Included example: Z500, T2m, T850, 10mU.	Variable-level embedding and variable aggregation to allow for heterogenous input datasets.	Unknown. Source code available.
<u>Chen et al. (2023b)</u>	<u>Single level: T2m, 10mU, 10mV, MSLP, TP. Multiple levels: Z, U, V, RH, T.</u>	<u>Z500, T500, U500, V500, T850, T2m, 10mU, 10mV, MSLP.</u>	<u>Cascade model architecture, with separate fine-tuning for different forecasting windows.</u>	<u>Source code and trained model available. Fuxi-extreme, a version of the model optimised for extreme weather, is in development (Zhong et al., 2023).</u>

**3.1 Current challenges in DLWP**

A common limitation of most large-scale DWLP applications introduced so far is that they are not targeted in any specific way to extreme weather events. Rather, their focus lies on maximising the average skill of the forecasts. Typically, machine learning models struggle to make accurate predictions of extreme values, partly due to the inherently limited training samples for extreme values, and partly due to intrinsic inferential challenges related to extrapolation. Given the key role of accurate prediction of and early warnings for extreme weather in disaster prevention and risk mitigation (World Meteorological Organization, 2022; Merz et al., 2020), it would be desirable for current DLWP applications to dedicate greater attention to forecast skill for extreme weather (Watson, 2022).

As highlighted in Table 1, this problem is further exacerbated by the fact that many global DLWP papers provide no or very limited diagnostics on the performance of their models for extreme weather scenarios (e.g. Keisler, 2022; Chen et al., 2023a; Nguyen et al., 2023), making it hard to assess their performance in those situations. Even those that do provide extreme weather diagnostics, mostly focus on selected variables and case studies, supplying no systematic overview of how the models perform in the prediction of high-impact surface extremes such as total precipitation or peak wind gusts. Indeed, some state-of-the-art DWLP models, such as ~~for instance~~ Bi et al. (2023), do not even produce forecasts for those variables.

Watson (2022) suggests some simple measures which authors could adopt to help readers evaluate whether or not a machine learning model can provide robust forecasts of extreme events: He suggests, for instance, that all papers should include scatterplots and quantile-quantile plots of forecasted vs. observed values, and that performance metrics computed only on extreme values should complement classic metrics of average skill. A positive note since the release of Watson (2022) is that several research groups have chosen to make the code of their global models publicly available, making it possible for third-party actors with enough computational resources to implement and further test their models. For instance, ECMWF has recently launched an experimental program running daily 10-day forecasts with 6-hourly time steps of the models introduced by Pathak et al. (2022), Bi et al. (2023) and ~~Lam et al. (2022)~~ Lam et al. (2023), whose forecasts are available to the general public (ECMWF, 2023). Similarly, the Weatherbench 2 (Rasp et al., 2024) provides additional scorecards and out-of-sample predictions for several models included in Table 1.

Some key "inductive biases", i.e. implicit assumptions of the employed estimation techniques (Battaglia et al., 2018), may also hamper the performance of current DLWP applications for extreme weather forecasting. Most global DLWP models choose to minimise the overall mean squared error (L2) of the forecast, averaging over all grid points and time-steps of interest ~~Pathak et al. (2022); Keisler (2022)~~ Pathak et al., 2022; Keisler, 2022). The minimisation thus uses the conditional mean of the dependent variable through space and time given the predictors, optimising forecasts for mean rather than extreme values. Furthermore, the use of L2 (and also L1, the mean absolute error, used for instance by Bi et al. (2023) and Chen et al. (2023b)),

implicitly assumes that for any given variable the distribution of the forecast error is symmetric, i.e. that it is possible to obtain  
205 both positive and negative errors of the same magnitude, and that deviations from the modelled value in the two directions are  
equally important. This is seldom the case in weather forecasting. Many weather variables display a high degree of autocorre-  
lation and follow highly asymmetric truncated distributions (e.g. peak windspeed or precipitation), which in combination tend  
to produce non-asymmetric error distributions (Hodson, 2022). Moreover, deviations of a variable from its mean in one of the  
two directions can have larger impacts on human societies than deviations in the other direction (e.g. one would expect that  
210 severely underestimating the amount of rain in a flash-flood event would be more harmful than incorrectly predicting rain on a  
dry day).

While the suggestions in Watson (2022), if implemented, would go a long way in ensuring greater transparency and credibil-  
ity for DLWP forecasts of extreme weather, the challenges related to the extrapolation issue and inductive biases still remain.  
215 The limited diagnostics provided by Pathak et al. (2022) and Bi et al. (2022) suggest that their models perform reasonably well  
on extremes, but also that they consistently tend to underestimate their magnitude. Similarly, Ben-Bouallegue et al. (2023), find  
that Pangu weather (Bi et al., 2023) can provide high-quality binary forecasts of moderately extreme temperatures, but that it  
also tends to oversmooth the prediction and underestimate the magnitude of the largest cold and hot extremes.

220 Thus, we argue for the need for DLWP models explicitly built to forecast extremes. These should make use of targeted loss  
functions and produce robust predictions of all relevant variables at or beyond the limits of their training range. In the next  
section, we propose a schematic framework on which to build such models. The aim here is to provide a general foundation  
for such approaches rather than discussing architectural details. Indeed, several of the architectures adopted by the models in  
Table 1 and Section 2.1 are in principle equally suitable for predictions of extreme weather as they are for average weather.  
225 The limiting factors are most likely the choice of optimisation problem and lack of specific treatment of the extremes rather  
than the architectures themselves.

### 3.2 A DLWP workflow for extreme weather

A simple way of shifting the focus from the average skill of a deep learning model to its performance in the tails of the  
230 distribution is by changing its loss function. Common loss functions, such as the mean absolute error (L1) and the mean  
squared error (L2), are minimised by taking the conditional median and mean of the dependent variable, respectively. An  
alternative loss function is given by the pinball loss, defined as follows (Koenker and Bassett, 1978):

$$L_{pinball} = \frac{1}{N} \sum_{i=1}^N \max(\tau \cdot (y_i - \hat{y}_i), (1 - \tau) \cdot (\hat{y}_i - y_i)), \quad (1)$$

where  $\tau$  is the target quantile,  $N$  is the number of training observations,  $i$  represents a specific observation,  $y_i$  is the actual  
235 value of the target variable for that observation and  $\hat{y}_i$  is the forecast generated by the model. This loss function punishes

predictions which are further away from the quantile of interest and is minimised by the conditional quantile of the dependent variable.<sup>1</sup> By choosing an extreme quantile of interest, it is possible to study in a regression setting how different predictors affect the tails of the distribution. Furthermore, models minimising the pinball loss could be used to set approximate confidence intervals around models maximising the average skill of the prediction.

240

Within a deep learning setting, models minimising the pinball loss often go under the name of deep quantile regression or quantile regression neural networks (Taylor, 2000). A limitation of deep quantile regression is that enough observations below and above the quantile of interest need to be available for the model to work properly. This can sometimes be an issue within a DLWP framework, given that the main interest can lie in very extreme quantiles, i.e. seldom-observed extreme events with long return periods.

245

A solution to this problem has recently been proposed by Pasche and Engelke (2023) who, building upon earlier work by Carreau and Bengio (2007), suggest using a two-step peak-over-threshold approach. First, a quantile regression-based estimator, such as linear or deep quantile regression, is used to estimate a conditional threshold of interest, and then the properties of the distribution of the exceedances are modelled with the help of extreme value theory (EVT). Pasche and Engelke (2023) assume that, in accordance with Balkema and De Haan (1974) and Pickands (1975), independent exceedances approximately follow a generalised Pareto distribution, with parameters depending on the value of the regressors. These parameters can then be estimated with the help of a neural network, and the resulting empirical distribution can be used to derive the properties of the distribution of any extreme event of interest, as is commonly done in EVT.

255

However, even the combination of quantile and EVT-based approaches suffers from a key limitation. Namely, it does not provide a deterministic forecast for a given time and place, but only return periods or values and a risk ratio of the probability of an event taking place compared to the climatology. In other words, it answers questions such as: "Is extreme event "X" more likely to occur than usual on day "Y"?" or: "How often does an event of a given severity occur given an initial set of atmospheric conditions?". It does not answer the question typically associated with deterministic weather forecasts, namely: "Is extreme event "X" going to take place on day "Y" at location "Z"?".

260

A possible alternative for cases where we are interested in answering the latter question, i.e. we want a deterministic forecast of a given extreme event at a specific time and place, is to use a binary classification model. This can, for instance, minimise a binary cross-entropy loss, defined as:

265

$$L_{\text{bincross}} = \frac{1}{N} \sum_{i=1}^N y_i \cdot \log(y_i) + (1 - y_i) \cdot \log(1 - y_i). \quad (2)$$

---

<sup>1</sup>Since the median is the 50th quantile, the pinball loss is equivalent to L1 when choosing  $\tau = 0.5$ .

By defining the extreme event on the base of a threshold or a given quantile of the climatology, and minimising Equation 2, we can then train a model to estimate the probability of an event of a given magnitude taking place at a specific time and location. The forecasted probability for a specific time and place can then easily be converted into a deterministic forecast by choosing a cutoff probability (e.g. 50%), where events above that probability are expected to take place, and events under that probability are not.

Whenever a heavy class imbalance is present, i.e. the interest lies in very extreme quantiles, training a classification neural network may be challenging, as the model may be prone to reverting to the trivial solution of never predicting an extreme event. In those cases, class weights may help: Weights are introduced in Equation 2, in order to give greater importance to the loss generated by training samples from the minority class, namely the extremes. In order words, the model is trained to minimise a weighted cross-entropy loss (Equation 3), defined as follows:


$$L_{weightedbincross} = \frac{1}{N} \sum_{i=1}^N -w_1 y_i \cdot \log(y_i) + w_0 (1 - y_i) \cdot \log(1 - y_i), \quad (3)$$

where  $w_1$  is the weight assigned to observations in the minority class, and  $w_0$  is the weight assigned to observations in the majority class.

Even after introducing class weights, this approach, like quantile regression, needs enough observations in each of the two classes for the model to work properly. Thus, it is not suitable in isolation for extremes with a very long return period, appearing no or very few times in the training sample. However, as in the previous case, we can build a two-step peak-over-threshold model which addresses this problem. First, we decide through a classification model whether or not an event above a certain not-too-extreme threshold is going to take place. Then, we model the tails of the distribution with the help of the Pickands-Balkema-De Haan theorem (Balkema and De Haan, 1974; Pickands, 1975), which allows to make inferences on very extreme cases potentially beyond the model's training range.

The different steps introduced above can be combined in order to obtain forecasts providing a rich set of information. For instance, one may implement jointly a classification-based and a quantile-based deep learning model to obtain time and location-specific forecasts of an extreme as well as information on its return period. Figure 3 summarises the approaches described in this section in a simple framework that can be used to tailor deep learning models to extreme weather forecasting.

# Extreme event prediction proposed workflow



**Figure 3.** Extreme event prediction model design workflow. The chosen approach should depend on the information one aims to gather and the return period of the extreme events of interest.

#### 4 Conclusions and Recommendations

295 Accurate prediction of extreme weather events is a central part of a high-quality medium-range weather forecast, and of great societal and economic relevance (World Meteorological Organization, 2022; Merz et al., 2020). In order for global end-to-end deep learning models to attain widespread operational use, we argue that achieving greater average skill than physics-based numerical weather prediction models is not sufficient. They additionally need to demonstrate skill for extreme weather events.

300 We identify two key limitations which constrain current state-of-the-art deep learning forecasts of extreme weather. First, current architectures are not optimised to make use of the limited training samples for extreme values. Second, the models are not optimised on extreme event forecasts, and make some simplistic assumptions on how the forecasting errors are distributed. These issues are compounded by the scant or missing validation of extreme weather forecasts provided by leading global DLWP models.

305

We argue for the urgency of a DLWP workflow targeted to extreme weather forecasts, whereby deep learning models specifically designed to handle extreme events should complement deep learning models maximising the average skill of the forecast. To enable rapid advances, the implementation of such a workflow should rest on adapting existing deep learning architectures, rather than developing radically new and untested approaches. This should be complemented by placing a greater emphasis on assessing the performance of existing and future models in the tails of the distributions of the forecasted variables (Watson, 2022).

Echoing the above recommendations, in this article we have proposed a foundational workflow to advance deep learning extreme weather forecasts, where the method of choice depends on the meteorological question to be answered – whether probabilistic or deterministic – and the return period of the extreme events of interest. The workflow is fully enabled by recent architectural advances in deep learning weather forecast models, and we thus envision it as functional to achieve robust deep learning forecasts of extreme weather in the near future.

*Code and data availability.* No code or data were used for this article. The authors of some of the global deep learning models presented in Table 1 have chosen to make the code used to build their models freely available - whenever this is the case, we mention this in Table 1. Most of these models are trained using the ERA 5 reanalysis dataset (Hersbach et al., 2020), which is freely available through the Copernicus Climate Change Service at <https://doi.org/10.24381/cds.adbb2d47> and <https://doi.org/10.24381/cds.bd0915c6>.

*Author contributions.* The authors are jointly responsible for the conceptualisation of this work including the visualisations, and all the revision and editing of the submitted manuscript. Additionally, L. Olivetti has researched existing literature on the topic, written most of the

original draft and created the visualisations. G.Messori has acquired the funding and other resources necessary to conduct the research and  
325 provided extensive supervision.

*Competing interests.* The authors declare no conflicts of interest relevant to this study.

*Acknowledgements.* The authors thankfully acknowledge the support of the European Research Council (ERC) under the European Union's  
Horizon 2020 research and innovation programme (project CENAE: compound Climate Extremes in North America and Europe: from  
dynamics to predictability, Grant Agreement No. 948309). The authors also wish to acknowledge the use of the online tool NN-SWG  
330 (LeNail, 2019) for plotting some of the neural networks included in Figure 1.



## References

- Bahdanau, D., Cho, K., and Bengio, Y.: Neural Machine Translation by Jointly Learning to Align and Translate, in: 3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings, edited by Bengio, Y. and LeCun, Y., <https://doi.org/10.48550/arXiv.1409.0473>, 2015.
- 335 Balkema, A. A. and De Haan, L.: Residual Life Time at Great Age, *The Annals of Probability*, 2, 792–804, <https://doi.org/10.1214/aop/1176996548>, publisher: Institute of Mathematical Statistics, 1974.
- Barnes, A. P., McCullen, N., and Kjeldsen, T. R.: Forecasting seasonal to sub-seasonal rainfall in Great Britain using convolutional-neural networks, *Theoretical and Applied Climatology*, 151, 421–432, <https://doi.org/10.1007/s00704-022-04242-x>, 2023.
- Battaglia, P. W., Hamrick, J. B., Bapst, V., Sanchez-Gonzalez, A., Zambaldi, V., Malinowski, M., Tacchetti, A., Raposo, D., Santoro, A.,  
340 Faulkner, R., Gulcehre, C., Song, F., Ballard, A., Gilmer, J., Dahl, G., Vaswani, A., Allen, K., Nash, C., Langston, V., Dyer, C., Heess, N., Wierstra, D., Kohli, P., Botvinick, M., Vinyals, O., Li, Y., and Pascanu, R.: Relational inductive biases, deep learning, and graph networks, <https://doi.org/10.48550/arXiv.1806.01261>, preprint at <https://arxiv.org/abs/1806.01261v3>, 2018.
- Bauer, P., Dueben, P., Chantry, M., Doblas-Reyes, F., Hoefler, T., McGovern, A., and Stevens, B.: Deep learning and a changing economy in weather and climate prediction, *Nature Reviews Earth & Environment*, 4, 507–509, <https://doi.org/10.1038/s43017-023-00468-z>, number:  
345 8 Publisher: Nature Publishing Group, 2023.
- Ben-Bouallegue, Z., Clare, M. C. A., Magnusson, L., Gascon, E., Maier-Gerber, M., Janousek, M., Rodwell, M., Pinault, F., Dramsch, J. S., Lang, S. T. K., Raoult, B., Rabier, F., Chevallier, M., Sandu, I., Dueben, P., Chantry, M., and Pappenberger, F.: The rise of data-driven weather forecasting, <https://doi.org/10.48550/arXiv.2307.10128>, preprint at arXiv:2307.10128, 2023.
- Bengio, Y. and Gingras, F.: Recurrent Neural Networks for Missing or Asynchronous Data, in: *Advances in Neural Information Processing Systems*, vol. 8, MIT Press, [https://papers.nips.cc/paper\\_files/paper/1995/hash/ffeed84c7cb1ae7bf4ec4bd78275bb98-Abstract.html](https://papers.nips.cc/paper_files/paper/1995/hash/ffeed84c7cb1ae7bf4ec4bd78275bb98-Abstract.html), 1995.
- 350 Bengio, Y., Simard, P., and Frasconi, P.: Learning long-term dependencies with gradient descent is difficult, *IEEE transactions on neural networks / a publication of the IEEE Neural Networks Council*, 5, 157–66, <https://doi.org/10.1109/72.279181>, 1994.
- Beucler, T., Pritchard, M., Gentine, P., and Rasp, S.: Towards Physically-Consistent, Data-Driven Models of Convection, in: *IGARSS 2020 - 2020 IEEE International Geoscience and Remote Sensing Symposium*, pp. 3987–3990,  
355 <https://doi.org/10.1109/IGARSS39084.2020.9324569>, ISSN: 2153-7003, 2020.
- Bi, K., Xie, L., Zhang, H., Chen, X., Gu, X., and Tian, Q.: Pangu-Weather: A 3D High-Resolution Model for Fast and Accurate Global Weather Forecast, <https://doi.org/10.48550/arXiv.2211.02556>, preprint at arXiv:2211.02556, 2022.
- Bi, K., Xie, L., Zhang, H., Chen, X., Gu, X., and Tian, Q.: Accurate medium-range global weather forecasting with 3D neural networks, *Nature*, pp. 1–6, <https://doi.org/10.1038/s41586-023-06185-3>, publisher: Nature Publishing Group, 2023.
- 360 Boomsma, W. and Frellsen, J.: Spherical convolutions and their application in molecular modelling, in: *Advances in Neural Information Processing Systems*, vol. 30, Curran Associates, Inc., [https://papers.nips.cc/paper\\_files/paper/2017/hash/1113d7a76ffceca1bb350bfe145467c6-Abstract.html](https://papers.nips.cc/paper_files/paper/2017/hash/1113d7a76ffceca1bb350bfe145467c6-Abstract.html), 2017.
- Carreau, J. and Bengio, Y.: A Hybrid Pareto Model for Conditional Density Estimation of Asymmetric Fat-Tail Data, in: *Proceedings of the Eleventh International Conference on Artificial Intelligence and Statistics*, pp. 51–58, PMLR, <https://proceedings.mlr.press/v2/carreau07a.html>, ISSN: 1938-7228, 2007.  
365

- Chen, K., Han, T., Gong, J., Bai, L., Ling, F., Luo, J.-J., Chen, X., Ma, L., Zhang, T., Su, R., Ci, Y., Li, B., Yang, X., and Ouyang, W.: FengWu: Pushing the Skillful Global Medium-range Weather Forecast beyond 10 Days Lead, <https://doi.org/10.48550/arXiv.2304.02948>, preprint at 10.48550/arXiv.2304.02948, 2023a.
- Chen, L., Zhong, X., Zhang, F., Cheng, Y., Xu, Y., Qi, Y., and Li, H.: FuXi: a cascade machine learning forecasting system for 15-day global weather forecast, *npj Climate and Atmospheric Science*, 6, 1–11, <https://doi.org/10.1038/s41612-023-00512-1>, number: 1 Publisher: Nature Publishing Group, 2023b.
- Chkeir, S., Anesiadou, A., Mascitelli, A., and Biondi, R.: Nowcasting extreme rain and extreme wind speed with machine learning techniques applied to different input datasets, *Atmospheric Research*, 282, 106 548, <https://doi.org/10.1016/j.atmosres.2022.106548>, 2023.
- Cho, K., van Merriënboer, B., Bahdanau, D., and Bengio, Y.: On the Properties of Neural Machine Translation: Encoder–Decoder Approaches, in: *Proceedings of SSST-8, Eighth Workshop on Syntax, Semantics and Structure in Statistical Translation*, pp. 103–111, Association for Computational Linguistics, Doha, Qatar, <https://doi.org/10.3115/v1/W14-4012>, 2014.
- Cisneros, D., Richards, J., Dahal, A., Lombardo, L., and Huser, R.: Deep graphical regression for jointly moderate and extreme Australian wildfires, <https://doi.org/10.48550/arXiv.2308.14547>, preprint at 10.48550/arXiv.2308.14547, 2023.
- Civitarese, D. S., Szwarcman, D., Zadrozny, B., and Watson, C.: Extreme Precipitation Seasonal Forecast Using a Transformer Neural Network, <https://doi.org/10.48550/arXiv.2107.06846>, preprint at 10.48550/arXiv.2107.06846, 2021.
- Clare, M. C., Jamil, O., and Morcrette, C. J.: Combining distribution-based neural networks to predict weather forecast probabilities, *Quarterly Journal of the Royal Meteorological Society*, 147, 4337–4357, <https://doi.org/10.1002/qj.4180>, 2021.
- Cohen, T. S., Geiger, M., Koehler, J., and Welling, M.: Spherical CNNs, <https://doi.org/10.48550/arXiv.1801.10130>, preprint at 10.48550/arXiv.1801.10130, 2018.
- de Burgh-Day, C. O. and Leeuwenburg, T.: Machine learning for numerical weather and climate modelling: a review, *Geoscientific Model Development*, 16, 6433–6477, <https://doi.org/10.5194/gmd-16-6433-2023>, publisher: Copernicus GmbH, 2023.
- Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., Uszkoreit, J., and Houlsby, N.: An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale, in: *International Conference on Learning Representations*, <https://openreview.net/forum?id=YicbFdNTTy>, 2020.
- Dueben, P. D. and Bauer, P.: Challenges and design choices for global weather and climate models based on machine learning, *Geoscientific Model Development*, 11, 3999–4009, <https://doi.org/10.5194/gmd-11-3999-2018>, publisher: Copernicus GmbH, 2018.
- ECMWF: Machine Learning model data, <https://www.ecmwf.int/en/forecasts/dataset/machine-learning-model-data>, <https://www.ecmwf.int/en/forecasts/dataset/machine-learning-model-data>, 2023.
- Espohlt, L., Agrawal, S., Sønderby, C., Kumar, M., Heek, J., Bromberg, C., Gazen, C., Hickey, J., Bell, A., and Kalchbrenner, N.: Skillful Twelve Hour Precipitation Forecasts using Large Context Neural Networks, <https://doi.org/10.48550/arXiv.2111.07470>, preprint at <https://arxiv.org/abs/2111.07470>, 2021.
- Grönquist, P., Yao, C., Ben-Nun, T., Dryden, N., Dueben, P., Li, S., and Hoefler, T.: Deep learning for post-processing ensemble weather forecasts, *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 379, 20200092, <https://doi.org/10.1098/rsta.2020.0092>, publisher: Royal Society, 2021.
- Guastavino, S., Piana, M., Tizzi, M., Cassola, F., Iengo, A., Sacchetti, D., Solazzo, E., and Benvenuto, F.: Prediction of severe thunderstorm events with ensemble deep learning and radar data, *Scientific Reports*, 12, 20 049, <https://doi.org/10.1038/s41598-022-23306-6>, number: 1 Publisher: Nature Publishing Group, 2022.

- Gutzwiller, K. J. and Serno, K. M.: Using the risk of spatial extrapolation by machine-learning models to assess the reliability of model predictions for conservation, *Landscape Ecology*, 38, 1363–1372, <https://doi.org/10.1007/s10980-023-01651-9>, 2023.
- 405 Haidar, A. and Verma, B.: Monthly Rainfall Forecasting Using One-Dimensional Deep Convolutional Neural Network, *IEEE Access*, 6, 69 053–69 063, <https://doi.org/10.1109/ACCESS.2018.2880044>, 2018.
- Hall, T., Brooks, H. E., and Doswell, C. A.: Precipitation Forecasting Using a Neural Network, *Weather and Forecasting*, 14, 338–345, [https://doi.org/10.1175/1520-0434\(1999\)014<0338:PFUANN>2.0.CO;2](https://doi.org/10.1175/1520-0434(1999)014<0338:PFUANN>2.0.CO;2), publisher: American Meteorological Society Section: Weather and Forecasting, 1999.
- 410 Hersbach, H., Bell, B., Berrisford, P., Hirahara, S., Horányi, A., Muñoz-Sabater, J., Nicolas, J., Peubey, C., Radu, R., Schepers, D., Simmons, A., Soci, C., Abdalla, S., Abellan, X., Balsamo, G., Bechtold, P., Biavati, G., Bidlot, J., Bonavita, M., De Chiara, G., Dahlgren, P., Dee, D., Diamantakis, M., Dragani, R., Flemming, J., Forbes, R., Fuentes, M., Geer, A., Haimberger, L., Healy, S., Hogan, R. J., Hólm, E., Janisková, M., Keeley, S., Laloyaux, P., Lopez, P., Lupu, C., Radnoti, G., de Rosnay, P., Rozum, I., Vamborg, F., Villaume, S., and Thépaut, J.-N.: The ERA5 global reanalysis, *Quarterly Journal of the Royal Meteorological Society*, 146, 1999–2049, <https://doi.org/10.1002/qj.3803>, dataset, 2020.
- 415 Hochreiter, S. and Schmidhuber, J.: Long Short-term Memory, *Neural computation*, 9, 1735–80, <https://doi.org/10.1162/neco.1997.9.8.1735>, 1997.
- Hodson, T. O.: Root-mean-square error (RMSE) or mean absolute error (MAE): when to use them or not, *Geoscientific Model Development*, 15, 5481–5487, <https://doi.org/10.5194/gmd-15-5481-2022>, publisher: Copernicus GmbH, 2022.
- 420 Hu, Y., Chen, L., Wang, Z., and Li, H.: SwinVRNN: A Data-Driven Ensemble Forecasting Model via Learned Distribution Perturbation, *Journal of Advances in Modeling Earth Systems*, 15, e2022MS003 211, <https://doi.org/10.1029/2022MS003211>, <https://onlinelibrary.wiley.com/doi/pdf/10.1029/2022MS003211>, 2023.
- Ivakhnenko, A. G. and Lapa, V. G.: Cybernetic Predicting Devices, Joint Publications Research Service [available from the Clearinghouse for Federal Scientific and Technical Information], 1965.
- 425 Kashinath, K., Mustafa, M., Albert, A., Wu, J.-L., Jiang, C., Esmailzadeh, S., Azizzadenesheli, K., Wang, R., Chattopadhyay, A., Singh, A., Manepalli, A., Chirila, D., Yu, R., Walters, R., White, B., Xiao, H., Tchelepi, H. A., Marcus, P., Anandkumar, A., Hassanzadeh, P., and Prabhat, n.: Physics-informed machine learning: case studies for weather and climate modelling, *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 379, 20200 093, <https://doi.org/10.1098/rsta.2020.0093>, publisher: Royal Society, 2021.
- 430 Keisler, R.: Forecasting Global Weather with Graph Neural Networks, <https://doi.org/10.48550/arXiv.2202.07575>, preprint at <http://arxiv.org/abs/2202.07575>, 2022.
- Klein, B., Wolf, L., and Afek, Y.: A Dynamic Convolutional Layer for short rangeweather prediction, in: 2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 4840–4848, <https://doi.org/10.1109/CVPR.2015.7299117>, iISSN: 1063-6919, 2015.
- Koenker, R. and Bassett, G.: Regression Quantiles, *Econometrica*, 46, 33–50, <https://doi.org/10.2307/1913643>, publisher: Wiley, Econometric Society, 1978.
- 435 Kramer, M. A.: Nonlinear principal component analysis using autoassociative neural networks, *AICHE Journal*, 37, 233–243, <https://doi.org/10.1002/aic.690370209>, 1991.
- Kron, W., Löw, P., and Kundzewicz, Z. W.: Changes in risk of extreme weather events in Europe, *Environmental Science & Policy*, 100, 74–83, <https://doi.org/10.1016/j.envsci.2019.06.007>, 2019.

- 440 Lam, R., Sanchez-Gonzalez, A., Willson, M., Wirnsberger, P., Fortunato, M., Pritzel, A., Ravuri, S., Ewalds, T., Alet, F., Eaton-Rosen, Z., Hu, W., Merose, A., Hoyer, S., Holland, G., Stott, J., Vinyals, O., Mohamed, S., and Battaglia, P.: GraphCast: Learning skillful medium-range global weather forecasting, <https://doi.org/10.48550/arXiv.2212.12794>, preprint at 10.48550/arXiv.2212.12794, 2022.
- Lam, R., Sanchez-Gonzalez, A., Willson, M., Wirnsberger, P., Fortunato, M., Alet, F., Ravuri, S., Ewalds, T., Eaton-Rosen, Z., Hu, W., Merose, A., Hoyer, S., Holland, G., Vinyals, O., Stott, J., Pritzel, A., Mohamed, S., and Battaglia, P.: Learning skillful medium-range  
445 global weather forecasting, *Science*, 382, 1416–1421, <https://doi.org/10.1126/science.adi2336>, publisher: American Association for the Advancement of Science, 2023.
- LeCun, Y. and Bengio, Y.: Convolutional networks for images, speech, and time series, *The handbook of brain theory and neural networks*, 3361, 1995, publisher: Citeseer, 1995.
- LeNail, A.: NN-SVG: Publication-Ready Neural Network Architecture Schematics, *Journal of Open Source Software*, 4, 747,  
450 <https://doi.org/10.21105/joss.00747>, 2019.
- Li, X., Du, Z., and Song, G.: A Method of Rainfall Runoff Forecasting Based on Deep Convolution Neural Networks, in: 2018 Sixth International Conference on Advanced Cloud and Big Data (CBD), pp. 304–310, <https://doi.org/10.1109/CBD.2018.00061>, 2018.
- Merz, B., Kuhlicke, C., Kunz, M., Pittore, M., Babeyko, A., Bresch, D. N., Domeisen, D. I. V., Feser, F., Koszalka, I., Kreibich, H., Pantillon, F., Parolai, S., Pinto, J. G., Punge, H. J., Rivalta, E., Schröter, K., Strehlow, K., Weisse, R., and Wurpts, A.: Impact Forecasting to Support  
455 Emergency Management of Natural Hazards, *Reviews of Geophysics*, 58, <https://doi.org/10.1029/2020RG000704>, publisher: John Wiley & Sons, Ltd, 2020.
- Molina, M. J., O'Brien, T. A., Anderson, G., Ashfaq, M., Bennett, K. E., Collins, W. D., Dagon, K., Restrepo, J. M., and Ullrich, P. A.: A Review of Recent and Emerging Machine Learning Applications for Climate Variability and Weather Phenomena, *Artificial Intelligence for the Earth Systems*, 2, <https://doi.org/10.1175/AIES-D-22-0086.1>, publisher: American Meteorological Society Section: Artificial In-  
460 telligence for the Earth Systems, 2023.
- Nguyen, T., Brandstetter, J., Kapoor, A., Gupta, J. K., and Grover, A.: ClimaX: A foundation model for weather and climate, <https://doi.org/10.48550/arXiv.2301.10343>, preprint at 10.48550/arXiv.2301.10343, 2023.
- Pasche, O. C. and Engelke, S.: Neural Networks for Extreme Quantile Regression with an Application to Forecasting of Flood Risk, <https://doi.org/10.48550/arXiv.2208.07590>, preprint at 10.48550/arXiv.2208.07590, 2023.
- 465 Pathak, J., Subramanian, S., Harrington, P., Raja, S., Chattopadhyay, A., Mardani, M., Kurth, T., Hall, D., Li, Z., Azizzadenesheli, K., Hassanzadeh, P., Kashinath, K., and Anandkumar, A.: FourCastNet: A Global Data-driven High-resolution Weather Model using Adaptive Fourier Neural Operators, <https://doi.org/10.48550/arXiv.2202.11214>, preprint at 10.48550/arXiv.2202.11214, 2022.
- Pickands, J.: Statistical Inference Using Extreme Order Statistics, *The Annals of Statistics*, 3, 119–131, publisher: Institute of Mathematical Statistics, 1975.
- 470 Qiu, M., Zhao, P., Zhang, K., Huang, J., Shi, X., Wang, X., and Chu, W.: A Short-Term Rainfall Prediction Model Using Multi-task Convolutional Neural Networks, in: 2017 IEEE International Conference on Data Mining (ICDM), pp. 395–404, <https://doi.org/10.1109/ICDM.2017.49>, iSSN: 2374-8486, 2017.
- Rasp, S., Dueben, P. D., Scher, S., Weyn, J. A., Mouatadid, S., and Thuerey, N.: WeatherBench: A Benchmark Data Set for Data-Driven Weather Forecasting, *Journal of Advances in Modeling Earth Systems*, 12, e2020MS002203, <https://doi.org/10.1029/2020MS002203>,  
475 2020.

- Rasp, S., Hoyer, S., Merose, A., Langmore, I., Battaglia, P., Russel, T., Sanchez-Gonzalez, A., Yang, V., Carver, R., Agrawal, S., Chantry, M., Bouallegue, Z. B., Dueben, P., Bromberg, C., Sisk, J., Barrington, L., Bell, A., and Sha, F.: WeatherBench 2: A benchmark for the next generation of data-driven global weather models, <https://doi.org/10.48550/arXiv.2308.15560>, preprint at arXiv:2308.15560, 2024.
- 480 Ravuri, S., Lenc, K., Willson, M., Kangin, D., Lam, R., Mirowski, P., Fitzsimons, M., Athanassiadou, M., Kashem, S., Madge, S., Prudden, R., Mandhane, A., Clark, A., Brock, A., Simonyan, K., Hadsell, R., Robinson, N., Clancy, E., Arribas, A., and Mohamed, S.: Skilful precipitation nowcasting using deep generative models of radar, *Nature*, 597, 672–677, <https://doi.org/10.1038/s41586-021-03854-z>, number: 7878 Publisher: Nature Publishing Group, 2021.
- Ren, X., Li, X., Ren, K., Song, J., Xu, Z., Deng, K., and Wang, X.: Deep Learning-Based Weather Prediction: A Survey, *Big Data Research*, 23, 100 178, <https://doi.org/10.1016/j.bdr.2020.100178>, 2021.
- 485 Rumelhart, D. E., Hinton, G. E., and Williams, R. J.: Learning representations by back-propagating errors, *Nature*, 323, 533–536, <https://doi.org/10.1038/323533a0>, number: 6088 Publisher: Nature Publishing Group, 1986.
- Scarselli, F., Gori, M., Tsoi, A. C., Hagenbuchner, M., and Monfardini, G.: The Graph Neural Network Model, *IEEE Transactions on Neural Networks*, 20, 61–80, <https://doi.org/10.1109/TNN.2008.2005605>, 2009.
- Scher, S. and Messori, G.: Generalization properties of feed-forward neural networks trained on Lorenz systems, *Nonlinear Processes in Geophysics*, 26, 381–399, <https://doi.org/10.5194/npg-26-381-2019>, publisher: Copernicus GmbH, 2019a.
- 490 Scher, S. and Messori, G.: Weather and climate forecasting with neural networks: using general circulation models (GCMs) with different complexity as a study ground, *Geoscientific Model Development*, 12, 2797–2809, <https://doi.org/10.5194/gmd-12-2797-2019>, publisher: Copernicus GmbH, 2019b.
- Scher, S. and Messori, G.: Ensemble Methods for Neural Network-Based Weather Forecasts, *Journal of Advances in Modeling Earth Systems*, 495 13, <https://doi.org/10.1029/2020MS002331>, 2021.
- Scher, S. and Messori, G.: Spherical convolution and other forms of informed machine learning for deep neural network based weather forecasts, <https://doi.org/10.48550/arXiv.2008.13524>, preprint at 10.48550/arXiv.2008.13524, 2023.
- Schizas, C., Michaelides, S., Pattichis, C., and Livesay, R.: Artificial neural networks in forecasting minimum temperature (weather), in: 1991 Second International Conference on Artificial Neural Networks, pp. 112–114, 1991.
- 500 Schultz, M. G., Betancourt, C., Gong, B., Kleinert, F., Langguth, M., Leufen, L. H., Mozaffari, A., and Stadtler, S.: Can deep learning beat numerical weather prediction?, *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 379, 20200 097, <https://doi.org/10.1098/rsta.2020.0097>, publisher: Royal Society, 2021.
- Silini, R., Lerch, S., Mastrantonas, N., Kantz, H., Barreiro, M., and Masoller, C.: Improving the prediction of the Madden–Julian Oscillation of the ECMWF model by post-processing, *Earth System Dynamics*, 13, 1157–1165, <https://doi.org/10.5194/esd-13-1157-2022>, publisher: 505 Copernicus GmbH, 2022.
- Taylor, J. W.: A quantile regression neural network approach to estimating the conditional density of multiperiod returns, *Journal of Forecasting*, 19, 299–311, [https://doi.org/10.1002/1099-131X\(200007\)19:4<299::AID-FOR775>3.0.CO;2-V](https://doi.org/10.1002/1099-131X(200007)19:4<299::AID-FOR775>3.0.CO;2-V), 2000.
- Thuemmel, J., Karlbauer, M., Otte, S., Zarfl, C., Martius, G., Ludwig, N., Scholten, T., Friedrich, U., Wulfmeyer, V., Goswami, B., and Butz, M. V.: Inductive biases in deep learning models for weather prediction, <https://doi.org/10.48550/arXiv.2304.04664>, preprint at 10.48550/arXiv.2304.04664, 2023.
- 510 Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, , and Polosukhin, I.: Attention is All you Need, in: *Advances in Neural Information Processing Systems*, edited by Guyon, I., Luxburg, U. V., Bengio, S., Wallach, H., Fer-

- gus, R., Vishwanathan, S., and Garnett, R., vol. 30, Curran Associates, Inc., [https://proceedings.neurips.cc/paper\\_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf), 2017.
- 515 Watson, P. A. G.: Machine learning applications for weather and climate need greater focus on extremes, *Environmental Research Letters*, 17, 111 004, <https://doi.org/10.1088/1748-9326/ac9d4e>, publisher: IOP Publishing, 2022.
- Weyn, J. A., Durran, D. R., and Caruana, R.: Can Machines Learn to Predict Weather? Using Deep Learning to Predict Gridded 500-hPa Geopotential Height From Historical Weather Data, *Journal of Advances in Modeling Earth Systems*, 11, 2680–2693, <https://doi.org/10.1029/2019MS001705>, 2019.
- 520 World Meteorological Organization: Early warnings for all: Executive action plan 2023-2027, <https://www.preventionweb.net/publication/early-warnings-all-executive-action-plan-2023-2027>, <https://www.preventionweb.net/publication/early-warnings-all-executive-action-plan-2023-2027>, 2022.
- Zhang, Y., Long, M., Chen, K., Xing, L., Jin, R., Jordan, M. I., and Wang, J.: Skilful nowcasting of extreme precipitation with NowcastNet, *Nature*, 619, 526–532, <https://doi.org/10.1038/s41586-023-06184-4>, number: 7970 Publisher: Nature Publishing Group, 2023.
- 525 Zhong, X., Chen, L., Liu, J., Lin, C., Qi, Y., and Li, H.: FuXi-Extreme: Improving extreme rainfall and wind forecasts with diffusion model, <https://doi.org/10.48550/arXiv.2310.19822>, preprint at arXiv:2310.19822, 2023.
- Zhu, A., Li, X., Mo, Z., and Wu, R.: Wind power prediction based on a convolutional neural network, in: 2017 International Conference on Circuits, Devices and Systems (ICCDs), pp. 131–135, <https://doi.org/10.1109/ICCDs.2017.8120465>, 2017.