

Layer-optimized SAR processing with a mobile phase-sensitive radar: a proof of concept for detecting the deep englacial stratigraphy of Colle Gnifetti, Switzerland/Italy

Falk M. Oraschewski¹, Inka Koch¹, M. Reza Ershadi¹, Jonathan Hawkins², Olaf Eisen^{3,4}, and Reinhard Drews¹

¹University of Tübingen, Department of Geosciences, Tübingen, Germany

²Cardiff University, School of Earth and Environmental Sciences, Cardiff, Wales, United Kingdom

³Alfred Wegener Institute, Helmholtz Centre for Polar and Marine Research, Bremerhaven, Germany

⁴University of Bremen, Department of Geosciences, Bremen, Germany

Correspondence: Falk M. Oraschewski (falk.oraschewski@uni-tuebingen.de)

Abstract. Radio-echo sounding is a standard technique for imaging the englacial stratigraphy of glaciers and ice sheets. In most cases, internal reflection horizons (IRHs) represent former glacier surfaces and comprise information about past accumulation, ice deformation and allow to link ice core chronologies. IRHs in the lower third of the ice column are often difficult to detect or coherently trace. In the polar ice sheets, progress in IRH detection has been made by using multistatic, phase-coherent radars, enabling focused synthetic-aperture radar (SAR) processing. However, these radar systems are often not suitable for deployment on mountain glaciers. We present a ~~proof-of-concept~~proof of concept study for a lightweight, phase-coherent, and ground-based radar system, based on the phase-sensitive radio echo-sounder (pRES). To improve the detectability of IRHs we additionally adapted a layer-optimized SAR (~~LO-SAR~~)-processing scheme to this setup. We showcase the system capability at Colle Gnifetti, Switzerland/Italy, ~~and detect significantly deeper and older IRHs compared to previously deployed pulsed radar systems.~~Continuous IRHs where specular reflections are now apparent down to the base of the glacier. Compared to previously deployed impulse radar systems, with the mobile pRES the age of the oldest continuously traceable IRH could be increased from 78 ± 12 a to 288 ± 35 a. Corresponding reflection mechanisms for this glacier are linked to ~~a stratified acidic impurity which was~~stratified acidic impurities which in the upper part were deposited at a higher rate due to increased industrial activity in the area. Possible improvements of the system are discussed. If successfully implemented, these may provide a new way to map the deep internal structure of Colle Gnifetti and other mountain glaciers more extensively in future deployments.

1 Introduction

Polar mid-latitude glaciers store information about past regional climate change (Wagenbach et al., 2012) and hold natural (Clifford et al., 2019) and anthropogenic (Gabrieli and Barbante, 2014; Sigl et al., 2018a) impurity records that can be extracted by ice coring. Being located in the vicinity of highly industrialized regions (Sigl et al., 2018a), these archives are an important complement to ice core records from the polar ice sheets spanning deep time (EPICA community members, 2004; NEEM community members, 2013). However, the interpretation of these records can be limited by uncertainties in ice core dating

(Jenk et al., 2009). Using radar surveys to laterally trace internal reflection horizons (IRHs) between multiple ice core sites, their chronologies can be compared to reduce uncertainties (Eisen et al., 2003; Bohleber, 2011; Licciulli et al., 2020). IRHs represent discontinuities of the dielectric permittivity or conductivity between different layers of ice. Permittivity is controlled through density and crystal-orientation fabric (COF), whereas conductivity is determined through acidity (Fujita et al., 2006). IRHs are isochronous when they are formed by seasonal snow-density variations or impurities that were initially deposited at the surface. Besides supporting the ice core dating, IRHs can be used to infer spatial accumulation patterns (~~Koeh et al., 2023~~) (Cavitte et al., 2018; Koch et al., 2023), past ice deformation (Drews, 2015; Koutnik et al., 2016), upstream effects for ice core records (Eisen et al., 2003), and for finding new ice-core sites with an intact stratigraphy (Lilien et al., 2021). In many of these applications the deep and old stratigraphy is of particular interest.

Both on mountain glaciers (Eisen et al., 2003; Konrad et al., 2013) and on polar ice sheets (Drews et al., 2009) the lowest third of the ice column is often difficult to image, for example due to increased radio-wave attenuation, weakening of density contrasts, or buckling and folding of reflection interfaces. For polar ice sheets, the emergence of phase-coherent radars and linked synthetic-aperture radar (SAR) processing have significantly improved the detection of the deep englacial stratigraphy (Hélière et al., 2007; Peters et al., 2007). These heavy and power-intensive systems are pulled by tracked vehicles (Paden, 2006), or mounted on aircrafts (Shi et al., 2010), ~~both of which is not neither of which are~~ applicable on many mountain glaciers. Instead, smaller, typically incoherent, ~~pulsed-impulse~~ ground penetrating radars (GPR) available in a variety of off-the-shelf products are used. Here, we address that a ~~light-weight~~lightweight, low-power, phase-coherent and ground-based system suitable for SAR processing is currently lacking.

SAR processing improves the along-track resolution and suppresses clutter in the radargram by coherently focusing the backscattered power of point targets illuminated across multiple traces (Peters et al., 2005; Kusk and Dall, 2010). Similar to migration, this will collapse along-track hyperbolas from off-nadir reflections, providing improved imaging of, e.g., basal structures. However, in the case of specular reflections from IRHs, the signal quality can also deteriorate during SAR processing due to destructive interference (Holschuh et al., 2014). Castelletti et al. (2019) addressed this shortcoming by introducing a ~~layer~~ optimized-layer-optimized SAR (LO-SAR) processing method that corrects for along-track phase shifts of specular reflections before coherent summation. Other approaches for improving the detection of IRHs are based on filtering the IRHs contribution in the azimuth frequency domain of the radargram (Heister and Scheiber, 2018) or on including spatial correlation information into SAR processing (Xu et al., 2022). In addition, most of these algorithms determine the slope of IRHs, which can support the automated tracing of IRHs (MacGregor et al., 2015) and provides an alternative metric for radar data-model comparison (Holschuh et al., 2017).

HereIn this study, we showcase a mobile, phase-coherent radar system that is suitable for SAR processing and can be deployed on mountain glaciers. We use the existing phase-sensitive radio echo-sounder (pRES, also ApRES for autonomous and stationary surveying), a ~~light-weight and lightweight~~, low-power and inexpensive frequency modulated continuous wave (FMCW) radar operating at 200–400 MHz (Brennan et al., 2014; Nicholls et al., 2015). This ~~technology-instrument~~ has been widely used, most prominently in determining basal melt rates beneath ice shelves (Vaňková et al., 2021; Zeising et al., 2022) ~~–However, for which it was originally designed and so far only used for static applications.–~~ Ershadi et al. (2024) presented

a mobile acquisition of polarimetric pRES data using an autonomous rover to measure the COF on large spatial scales with postings of several tens of meters. The feasibility of a mobile deployment using the pRES for profiling with sub-meter spacing has only theoretically been assessed by Kapai et al. (2022), who investigated artifacts that can arise from moving the pRES during data acquisition. Here, we present the first mobile deployment of the pRES in combination with a real-time kinematic (RTK)-GPS to achieve the high accuracy in positioning required for SAR processing.

We demonstrate that this enables the detection of deep IRHs invisible to for profiling and demonstrate its capability to detect deep IRHs that were unresolved in previous surveys. In the following we first present the study site (Section 4.1) and the outline the mobile pRES setup as well as the and the data acquisition approach (Section 2), before describing the applied FMCW signal and LO-SAR processing (Section 2.3). Collected radargrams are compared to GPR data from pulsed impulse systems and to available ice core data to interpret the imaged signatures in the glaciological context (Section 4.4). Finally, limitations of the mobile pRES are discussed including suggestions for improvements further developments (Section 5).

2 Study site Mobile pRES

Overview of Colle Gnifetti indicating the location of the collected pRES profiles. The thick part of the GPR profile marks the section that is compared to the across-saddle pRES profile in Fig. 5. Blue dots mark the drill locations of existing ice cores at the time of drilling. Source of orthophoto and elevation model: Federal Office of Topography swisstopo.

The Colle Gnifetti is located in the Monte Rosa massif (Swiss-Italian Alps) at an altitude of around 4450 m a.s.l. and forms the upper accumulation zone of Grenzgletscher. It is characterized by low accumulation rates due to wind driven snow erosion (Alean et al., 1983), englacial temperatures below 0°C (Hoelzle et al., 2011), and low horizontal flow velocities near the divide (Lüthi and Funk, 2000). In combination, these conditions favor the formation of the longest, still well-preserved, glacial climate record in the European Alps. Several ice cores have been drilled at the site (Fig. 1.), entailing over 1000 years long climate and environmental records (Bohleber et al., 2018). Using radiocarbon dating, Jenk et al. (2009) found indications of more than 10 ka old ice in the CG03 ice core, reaching potentially back into the last glacial period. In the KCC ice core, a discontinuity in the chronology was found by Hoffmann et al. (2018), perhaps because of englacial folding. Radar profiling was conducted to link the chronologies of several ice cores (Eisen et al., 2003; Konrad et al., 2013). However, these studies only detected IRHs in the upper 30–50 % of the glacier with a maximum layer age of 80 years at the time of data acquisition.

3 Methods

In September 2021, we collected 285 m of phase-coherent radar data at Colle Gnifetti using a mobile pRES (Fig. 1; a 166 m long profile across the saddle passing the CG03 ice core, and a second 119 m long profile upstream towards KCC/south). Coherent profiling with the pRES requires dm scale postings with a relative positioning accuracy on the cm level. Here, we first describe hardware related aspects for data acquisition with sub-decimeter positioning (Section 2.1). Then, we provide the linked FMCW signal and LO-SAR processing algorithms tailored to that specific measurement setup (Section 3). Finally, details about dating




Figure 1. Mobile pRES setup with (a) a schematic of its components and (b) a photograph of the deployment on Colle Gnifetti.

~~IRHs in the collected pRES data describe the hardware design and data acquisition approach for mobilizing the pRES, as applied in our proof of concept study (Section 3.34) and about ice core data for assessing the reflectivity decrease at Colle Gnifetti (Section 4.2) are given.~~

2.1 ~~Data acquisition with the mobile pRES~~ Hardware design

To mobilize the pRES for profiling, ~~we placed~~ the transmit and receive skeleton ~~antennas were placed~~ slot antennas in inflated tractor inner tubes with the antennas being separated by 2.7 m and elevated a few centimeters above the snow surface (Fig. 21). ~~The dipole axes of both antennas were oriented perpendicular~~ We oriented both antennas such that the E-plane was parallel to the profiling direction ~~, so that~~ (also denoted as HH orientation). In this configuration, the radiation pattern of the skeleton antennas extends further in along-track than in cross-track direction and ground targets are ~~consequently illuminated with more traces in the along-track direction.~~

~~Due to the long chirp time of the pRES (1 s in standard configuration), data were collected in stop-and-go mode. This suppresses incoherent backscatter, avoids the occurrence of Doppler blurring (Kapai et al., 2022), and reduces system noise which increases when cables move during data acquisition. To make data collection efficient despite this approach, we aimed to minimize the stopping time per point. In the beginning, two chirps were recorded per point/trace from which we only use the one with the lower noise floor. Later, this number was reduced to one chirp. Positioning was illuminated over more traces, however, the direct wave between the skeleton antennas is also stronger which can promote signal clipping (Vaňková et al., 2020). To suppress the direct wave, a perpendicular orientation of the E-plane to the profiling direction (VV orientation) might be advantageous.~~

In our survey, positioning was controlled by the Trimble R9s GNSS system, operated in RTK mode, real-time kinematic (RTK) mode with the baseline between the GNSS base station and rover being typically below 200 m. ~~SAR processing only requires relative positions~~ This setup provided the relative position of the pRES to the base station and we did not post-process the GPS data further. The positioning system was with centimeter accuracy in real-time. Both, the positioning system and the

110 pRES (operated in 'attended mode') were connected to a control station ~~which automatically triggered for automatic triggering~~
of radar signal acquisition ~~(with the pRES being operated in FÇÿattended mode FÇÖ)~~ based on the position. To build upon the
low-cost approach of the pRES, the system could alternatively be combined with low-cost GNSS instrumentation that achieves
a comparable accuracy (Still et al., 2023; Pickell and Hawley, 2024).

2.2 Data acquisition

115 The chirp time of the applied FMCW radar is the main limitation of the survey speed. Here, we used the standard configurations
of the pRES, including a chirp time of 1 s. This makes data collection in stop-and-go mode necessary, because moving the
pRES during signal recording can cause Doppler blurring (Kapai et al., 2022), promote incoherent backscatter and increase
system noise from cable movement. We therefore aimed to minimize the stopping time per point by first recording two and
later only one chirp per point/trace. When two chirps were recorded, only the one with the lower noise floor was selected for
120 further processing. Using the control station, chirping was triggered once the system was hand-towed by more than 9 cm and
~~gave the operator a signal~~ a signal indicated the operator to start/stop towing. With this approach, an average trace spacing of
approximately $\Delta d = 13$ cm and a median data acquisition time of 10 s per trace was achieved, giving a total survey speed of
around 3 h/100 m. To accelerate data acquisition further and potentially perform continuous profiling, a reduction of the chirp
time is needed. Section 5.1 discusses the software and hardware adaptations that are required for reducing the chirp time.




Figure 2. Overview of FMCW signal and LO-SAR processing scheme. Blue boxes represent the radar data at different processing stages. Gray blocks summarize the main processing steps, where a darker gray indicates that these are executed on the grid point level.

125 2.3 Radar processing

3 Data processing

This section outlines the ~~processing routine from the raw pRES data to the LO-SAR processed radargram (Fig. 3). We first present the LO-SAR processing routine (Fig. 2), starting with the~~ standard FMCW signal processing and ~~summarize~~ survey-specific ~~corrections. This provides adaptations which provide~~ the background for estimating ~~the slopes of englacial IRHs from the signal phase for IRH slopes from the phase signal during the~~ subsequent LO-SAR processing.

3.0.1 FMCW signal processing

3.1 FMCW signal processing

The description of the standard FMCW signal processing and the notation broadly follows Brennan et al. (2014). The pRES transmits a linearly frequency modulated chirp with a center frequency of $f_c = 300$ MHz and a bandwidth $B = 200$ MHz over a chirp time of $T = 1$ s. On the hardware side, the reflected signals are mixed with the transmitted signal and subsequently low-pass filtered. This results in the deramped waveform which, by using a fast Fourier transform (FFT), is decomposed into the deramped frequencies

$$f_d = \frac{2B\tilde{R}\sqrt{\varepsilon_{r,\text{ice}}}}{T_c}, \quad (1)$$

which relate to the reflection range \tilde{R} using the speed of light in vacuum c and the real-valued relative permittivity of ice $\varepsilon_{r,\text{ice}} = 3.17$ (Brennan et al., 2014). Note that this formulation does not allow the use of a variable relative permittivity and the reflection range does not consider the lower density of firm (indicated by \sim). A density correction will be described below and from here on, the general relative permittivity of firm or ice ε_r is used.

The range resolution δ_R of FMCW radars is determined by their bandwidth

$$\delta_R = \frac{c}{2B\sqrt{\varepsilon_r}}, \quad (2)$$

giving a resolution of the pRES of $\delta_R = 0.42$ m in ice (Brennan et al., 2014). For each frequency component, or range bin n , the FFT returns the amplitude a_n (Fig. 3c) and phase $\phi_{\text{raw},n}$ (Fig. 3a) in complex form:

$$A_{\text{raw},n} = a_n \exp(i\phi_{\text{raw},n}). \quad (3)$$

Prior to the FFT the deramped waveform is zero-padded, i.e. lengthened with zeros by a padding factor p . This increases the sampling rate of the FFT and reduces the range bin increment to $\Delta R_{\text{bin}} = \delta_R/p$, effectively corresponding to a sinc interpolation of the decomposed amplitude and phase signals. Brennan et al. (2014) suggest using $p \geq 2$ for resolving ambiguities in the phase because ~~otherwise, otherwise~~ the range bins ~~would be are~~ separated by more than a full phase cycle (or wavelength) at the center frequency of the pRES). Note, however, that because zero-padding is essentially an interpolation, the intermediate




Figure 3. An exemplary segment of the pRES profile over one synthetic aperture length. Phase signal before (a) and after (b) correcting it with a reference signal. Power before (c) and after (d) LO-SAR processing. The slope of the central reflection is indicated by a black line and obtained in (b) by fitting to a coherent section of the reference corrected phase.

phase cycles cannot be recovered. Nevertheless, the signal phase is typically interpreted relative to an idealized reference phase which, for the center of the n -th range bin, is given by

$$155 \quad \phi_{\text{ref},n} = n \frac{2\pi f_c}{Bp} - n^2 \frac{\pi}{Bp^2T} \quad (4)$$

(Brennan et al., 2014). The second term is negligible over the operation range of the pRES because $f_c \gg 1/T$, so that $\Delta\phi_{\text{ref},\text{bin}} = 2\pi f_c / (Bp)$. Therefore, $p \geq 2$ ensures that the phase variation of the reference phase between range bins is smaller than 2π . In addition, a high padding improves the representation of the reference phase, which is why we apply a padding factor of $p = 8$ for the subsequent LO-SAR processing.

160 Subtracting the reference phase ϕ_{ref} from the raw signal results in:

$$\begin{aligned} A_{\text{cor},n} &= a_n \exp(i(\phi_{\text{raw},n} - \phi_{\text{ref},n})) \\ &= a_n \exp(i\phi_{\text{cor},n}), \end{aligned} \quad (5)$$

~~We denote this where the phase difference between raw and reference phase is denoted as the corrected phase ϕ_{cor} and will exploit that it is.~~

165 We note that the corrected phase appears constant along sloped IRHs (Fig. 43b) for estimating these slopes which we will exploit during the following LO-SAR processing for estimating these slopes. The reason for this is that changes in the reflection range ΔR are directly related to changes in the raw phase (MacGregor et al., 2015):

$$\Delta\phi_{\text{raw}} = \frac{4\pi\Delta R}{\lambda_c}, \quad (6)$$

where $\lambda_c = c/(\sqrt{\epsilon_r}f_c)$ is the wavelength that corresponds to the center frequency. For sloped IRHs, this results in an along-track gradient of the raw phase between adjacent traces $\Delta\phi_{\text{trace}}$ (Fig. 3a) which is related to the IRH slope S by

$$170 \quad S = \arctan\left(\frac{-\Delta R_{\text{trace}}}{\Delta d}\right) = \arctan\left(\frac{-\lambda_c \Delta\phi_{\text{trace}}}{4\pi \Delta d}\right). \quad (7)$$

As the raw phase is approximately constant in the vertical (Fig. 3a), the horizontal phase gradient due to a change of an IRH range by ΔR_{bin} is exactly compensated by subtraction of the reference phase, causing the corrected phase to be constant along IRHs (Fig. 3b).

After In this study, we expand the standard FMCW signal processing ~~traces are cropped by cropping the traces~~ at the 175 airwave return and ~~shifted shifting the phase at zero travel time~~ to a uniform ~~phase value at zero travel time value~~. This accounts for spurious π -offsets which appear in some ~~of our~~ traces for unknown reasons.

Finally, the reflection range \tilde{R} , as given in Eq. (1), is ~~density corrected~~ Finally, we apply a density correction to account for faster ~~radar~~ wave propagation in firn, which ~~constitutes up to half~~ can constitute a significant portion of the thickness of ~~Colle Gnifetti. This is done by translating~~ mountain glaciers, whereas the reflection range \tilde{R} as given in Eq. (1) is computed 180 ~~by assuming a constant permittivity of $\epsilon_{r,\text{ice}}$. To allow for a variable permittivity, \tilde{R} is translated~~ into two-way travel time $\tau = 2\tilde{R}\sqrt{\epsilon_{r,\text{ice}}}/c$ and ~~converting them back into corrected ranges~~ then converted back into a density corrected range R by

$$R(\tau) = \int_0^\tau \frac{c}{2\sqrt{\epsilon_r}} d\tau', \quad (8)$$

using the ~~density data of the KCC ice core (Section 4.2, Freitag et al., 2018) and the relative permittivity~~ relative permittivity ϵ_r as given by the Looyenga (1965) mixture model ~~and density data from an ice core. This approach is justified, because the~~ 185 ~~permittivity of ice and air are approximately constant over the frequency range of the pRES (Bohleber et al., 2012).~~

3.1.1 Layer Optimized SAR (LO-SAR) processing

3.2 Layer-optimized SAR processing

Castelletti et al. (2019) introduced LO-SAR processing ~~optimizes to improve~~ the detection of inclined IRHs in a radargram. This method aims to enhance the signal strength of IRHs by coherently integrating their backscattered power (Fig. 4c) over 190 a fixed ~~aperture length. Our processing is motivated by Castelletti et al. (2019), but differs in the regard that we do not only correct for a phase change~~ synthetic aperture length L_{SAR} , where the signal-to-noise ratio (SNR) increases proportional to L_{SAR} (Castelletti et al., 2019). Because according to Eq. (6) the phase varies in the along-track direction for inclined IRHs, it is necessary to correct for this phase gradient before the coherent ~~summation. Instead, we explicitly sum along IRHs after extracting their slopes~~ integration to avoid destructive interference. In Castelletti et al.'s (2019) implementation of LO-SAR 195 ~~processing, for each grid point on the radargram the backscattered power is integrated along its range bin over L_{SAR} after applying an iteratively found optimal phase shift that maximizes the SNR. Following Eq. (7), this optimal phase shift then provides the local slope of IRHs as a byproduct.~~

Here, we tailor Castelletti et al.'s LO-SAR implementation to mobile pRES data, where we follow the different approach of first determining the englacial slopes, before using these to perform the coherent integration directly along the IRHs. This has the two advantages that the slopes can be filtered prior to the coherent summation to remove outliers and that the spurious integration of signal power from nearby IRHs is avoided for any grid point on the radargram. A comparison between our approach, the original implementation and moving averaging without correcting for the phase gradient is provided in Fig. S1.

In our implementation, the LO-SAR processed radargram is formed on an equidistant grid where the processed traces are located on a smoothed version of the observed profile line with a spacing of 10 cm. The processing is done grid point by grid point. In the following, we characterize these points (x, z) by their positions x and depths z . For every position, all M observed traces within a distance of $L_{\text{SAR}}/2$ are considered in the radargram formation, with the synthetic aperture length L_{SAR} . Following Castelletti et al. (2019) the Signal-to-Noise ratio (SNR) increases proportional to L_{SAR} . We use $L_{\text{SAR}} = 5$ m which gives a good improvement in radargram quality, while ensuring that IRHs can be assumed to be linearly sloped-linear over the full synthetic aperture length.

First, knowledge of the local The local englacial slopes S at all grid points is required. In theory are determined first. Following MacGregor et al. (2015), these can in theory be inferred from the unwrapped along-track phase gradient $\Delta\phi_{\text{trace}}$ between the neighboring observed traces which quantifies the local change in reflection depth ΔR_{IRH} (MacGregor et al., 2015) as given by the general relation between phase and range differences:-

$$\Delta R = \frac{\lambda_c \Delta\phi}{4\pi},$$

where $\lambda_c = c/(\sqrt{\epsilon_r} f_c)$ is the wavelength that corresponds to the center frequency. The local englacial slope is then:-

$$\begin{aligned} S(x, z) &= \arctan\left(\frac{-\Delta R_{\text{IRH}}(x, z)}{\Delta d(x)}\right) \\ &= \arctan\left(\frac{-\lambda_c \Delta\phi_{\text{trace}}(x, z)}{4\pi \Delta d(x)}\right). \end{aligned}$$

Eq. (7). However, this method directly translates uncertainties in the phase, e.g. due to occasional faulty traces and phase jumps at the transition between IRHs, into uncertainties in the slope, which in our data limits the accuracy of slope detection in this way in our data.

We circumvent this problem by not only considering the phase-gradient, but also the spatial coherence of the phase during slope estimation. For this we exploit that the corrected phase is constant along IRHs (Fig. 43b). In practice, we iterate for each grid point over a range of slopes s (from -30° to 30° in steps of 0.2° , a discussion of this range is provided in Section 5.2) to compute the coherence of the corrected phase along a line with length L_{SAR} and slope s , centered around (x, z) . Its depth range at the M observed traces within the synthetic aperture length is given by

$$R_m(x, z, s) = z + (x_m - x) \tan(s), \quad (9)$$

with the position of the observed traces x_m . The corrected signal of the m -th trace on that line $A_{\text{cor},m}(x, z, s)$ is then obtained by the weighting the values in the adjacent range bins above and below $R_m(x, z, s)$. Using these, we define the local phase

coherence at (x, z) along slope s :

$$C(x, z, s) = \left| \frac{1}{M} \sum_{m=1}^M \frac{A_{\text{cor},m}(x, z, s)}{|A_{\text{cor},m}(x, z, s)|} \right|$$

$$= \left| \frac{1}{M} \sum_{m=1}^M \exp(i\phi_{\text{cor},m}(x, z, s)) \right|. \quad (10)$$

230 The slope along which the coherence is largest then gives the local englacial slope S :

$$S(x, z) = \arg \max_s (C(x, z, s)). \quad (11)$$

This approach gives a more consistent slope estimate than the direct computation using Eq. (7), but still may provide **erroneously high-erroneous** values at the interface between different IRHs. To remove these, we apply a moving median filter to the slope field using a filtering window of $2 \text{ m} \times 2 \text{ m}$.

235 Finally, the LO-SAR processed **radar image radargram** is obtained by coherent summation of A_{cor} along the determined slope S :

$$A_{\text{LO-SAR}}(x, z) = \left| \frac{1}{M} \sum_{m=1}^M A_{\text{cor},m}(x, z, S(x, z)) \right| \quad (12)$$

This defines the LO-SAR processed amplitude $A_{\text{LO-SAR}}$ at each grid point (Fig. 43d).

3.3 Dating of internal reflection horizons

240 4 Proof of concept at Colle Gnifetti

~~Comparison of radargrams (a–d) across Colle Gnifetti and (e–f) upstream towards KCC. (a) Radar data of a pulsed GPR (Konrad et al., 2013); (b) IRH slopes relative to the surface derived from the corrected phase of the mobile pRES data; (c, e) mobile pRES data before and (d, f) after LO-SAR processing. Red lines mark picked IRHs. In the upstream profile (e–f), picking of deep IRHs is prevented by lower data quality due to technical problems and red dots only indicate the IRHs picked in the other profiles. The intersection points between the three profiles are marked by differently interrupted white lines. The CG03 and KCC ice core locations are marked by black dashed lines. The presented mobile pRES setup is tested in a proof of concept study which aims to image the deep englacial stratigraphy of Colle Gnifetti.~~

~~In the LO-SAR processed radargram, we picked and dated two IRHs and compare these with the deepest IRH from previous studies (Fig. 5). The age estimate of the newly picked IRHs is obtained from the model chronology of Jenk et al. (2009) for the CG03 ice core which is located on the profile (Fig. 6). For this, range values were converted into units of m.w.e. to match their formulation of the age–depth model. Uncertainties arise both, from dating of the ice core and from estimating the reflection range. To obtain ice core dating uncertainties, we computed the confidence limits of the age–depth model at both IRHs giving an uncertainty of 5 a in the upper and 27 a in the lower picked IRH. The range uncertainty is again attributed to two factors: To the inherent uncertainty associated with the width of radar reflections and to the uncertainty in the firn correction applied to the radar data. The latter was estimated as the given range difference between using the KCC or CG03 firn density data.~~




Figure 4. Overview of Colle Gnifetti indicating the location of the acquired mobile pRES profiles (red lines). The blue line marks a GPR profile from Konrad et al. (2013) that is used for comparison with the thick part indicating the section shown in Fig. 5a. The intersection points between the radar profiles are labeled (A–C) and blue dots mark ice core drill locations at the time of drilling. The inset shows the location of Colle Gnifetti within the European Alps. Source of orthophoto and local elevation model: Federal Office of Topography swisstopo.

4.1 Study site

The Colle Gnifetti is located in the Monte Rosa massif (Swiss–Italian Alps) at an altitude of around 4450 m a.s.l. and forms the upper accumulation zone of Grenzletscher. It is characterized by low accumulation rates due to wind driven snow erosion (Alean et al., 1983), englacial temperatures below 0°C (Hoelzle et al., 2011), and low horizontal flow velocities near the divide (Lüthi and Funk, 2000). In combination, these conditions favor the formation of the longest, still well-preserved, glacial climate record in the European Alps. Several ice cores have been drilled at the site (Section 4.2 Fig. 4) for density correction. In combination, both factoring in the low accumulation rates and the well-preserved nature of the ice, the site is ideal for obtaining over 1000 years long climate and environmental records (Bohleber et al., 2018).

4.2 Ice core data for radar signal interpretation

This study considers ice core data from the KCC ice core (Freitag et al., 2018), drilled in 2013, and in particular the CG03 ice core (Sigl et al., 2018b), drilled in 2003 and KCC ice cores (Fig. 14). The latter was measured in the upper 57.2 m and extended at the top by the shallow core CG15, drilled at the same location in 2015 (Sigl et al., 2018b) CG03 was drilled

in 2003 and analyzed by Sigl et al. (2018a) over its upper 57.2 m. Firn density data of CG03 were obtained by weighting ice core segments of ~ 70 cm length (M. Sigl, personal communication), and for KCC by X-ray computer tomography in ~ 2 mm resolution (Freitag et al., 2018). For CG03/CG15 we estimate the acidity by computing the ion balance between the (M. Sigl, personal communication; Sigl et al., 2018b). In addition, ion concentrations of Calcium, Sodium, Ammonium, Nitrate and Sulfate (Ca^{2+} , Na^+ , NH_4^+ , NO_3^- and SO_4^{2-}) measured in the cores. In addition, we compute the ion balance without Ca^{2+} to exclude its dominating contribution for the further interpretation. For comparison with the radar signal, were measured, with the record being extended at the top by the shallow core CG15, drilled at the same location in 2015 (Sigl et al., 2018a, b). Using radiocarbon dating, Jenk et al. (2009) found indications of more than 10 ka old ice at the base of the acidity records with a resolution of ~ 3 cm are smoothed by a Gaussian filter with a width of 48 cm, which is approximately the mean resolution of the pRES in firm CG03 ice core, reaching potentially back into the last glacial period. The KCC ice core was drilled in 2013 at the southern flank of Colle Gnifetti. Firn density data were obtained by X-ray computer tomography in ~ 2 mm resolution (Freitag et al., 2018). The deep stratigraphy at KCC is moreover interesting because of a discontinuity in its chronology near the base, perhaps caused by englacial folding (Hoffmann et al., 2018).

280 5 Results

4.1 Detection of deep englacial stratigraphy

4.2 Radar profiling at Colle Gnifetti

The transect from KCS to KCI previous ice core drilling efforts at Colle Gnifetti were supported by radar profiling surveys to reveal the englacial stratigraphic structure and to link the different ice core chronologies (Eisen et al., 2003; Konrad et al., 2013). These surveys used conventional impulse GPR system, for which the transect between KCS and KCI (Fig. 15a) from Konrad et al. (2013) is a representative example for numerous conventional pulsed GPR surveys conducted at Colle Gnifetti. These have mapped IRHs. In these studies, IRHs were mapped in the upper 30–50 % of the ice column, whereas the deeper ice appeared basically echo-free (Fig. 5a). (Eisen et al., 2003). The deepest IRH detectable in this radargram the KCS–KCI transect had an age of 78 ± 12 a at the time of recording data acquisition, which corresponds to the year 1930 CE. Note that Konrad et al. (2013) did not assign an age value to this IRH, and we repeated their approach for younger IRHs of averaging the KCS and KCI ages. In these data, the ice–bedrock interface is inconsistently detected and in some cases cannot be identified (e.g., Fig 3.8 in Bohleber, 2011).

Our pRES profile collected In this proof of concept study, we aim to expand the depth range over which IRHs can be detected. In September 2021, we acquired 285 m of phase-coherent radar data using the mobile pRES (Fig. 4). It is divided into a 166 m long profile across the saddle that passes the CG03 ice core and intersects with the GPR profile by Konrad et al. (2013) KCS–KCI transect by Konrad et al. (2013), and a second 119 m long upstream profile towards KCC/south. Already in the raw data, mobile pRES data ice and bedrock are clearly distinguishable and deeper IRHs are visible prior to the LO-SAR processing (Fig. 5e). However, than previously observed are visible (Fig. 5c). In parts these IRHs are yet difficult to trace in parts due to

300 persistent speckle noise ~~Moreover, IRH and because their~~ quality deteriorates in the flanks of the saddle where they are more inclined. ~~This~~ For these reasons, LO-SAR processing is applied as described in Section 3.2. In this process the IRH inclination relative to the surface is quantified ~~during the LO-SAR processing and attains and~~ values of about 10° ~~are attained~~ at both ends of the across-saddle profile (Fig. 5b). The LO-SAR processed data exhibits deep IRHs which were not apparent in the previous surveys (Fig. 5d and S1). ~~In the~~

305 ~~In the second~~ profile collected upstream towards KCC (Fig. 5e-f), LO-SAR processing also reveals the presence of deep specular reflections. However, ~~because of poorer data quality, our data does not show IRHs that are continuous over the whole upstream transect.~~

310 ~~We traced two~~ in this part the quality of our data got diminished by technical problems during data acquisition which might have arisen from overexerting the data writing capacity of the pRES after collecting > 1000 individual traces in a single folder. Thereby, various later recorded traces were lost or showed an enhanced noise level. In addition, this profile might have been affected by a less stable positioning of the mobile pRES system at each point due to the increased surface slope. As a consequence, deep IRHs in the ~~pRES radargram acquired across the saddle and linked them to the chronology of upstream profile are disturbed and not continuously traceable, which prevents studying the potentially complex deep stratigraphy at KCC and reduces the capability of our data to link the CG03 ice core (Jenk et al., 2009), and KCC ice cores.~~

315 For assessing the general potential of the mobile pRES, we therefore focus on the across-saddle profile. In this radargram, we trace two IRHs for comparison with the deepest IRH that was detectable in previous studies (Fig. 5). The first IRH matches the 78 a-horizon in the ~~pulsed-impulse~~ GPR data with respect to depth at the intersection between both profiles ~~It was independently dated to an~~ and the second one marks the deepest reflection that is continuously traceable in the LO-SAR processed across-saddle radargram.

320 The two IRHs are dated by converting their range into units of m water equivalent to link them with the age-depth model of Jenk et al. (2009) for the CG03 ice core that is located on the profile (Fig. 6). Uncertainties in the IRH dating arise both from dating of the ice core and from estimating the reflection range. To obtain ice core dating uncertainties, we computed the confidence limits of the age-depth model at both IRHs giving an uncertainty of 5 a in the upper and 27 a in the lower traced IRH. The range uncertainty is again attributed to two factors: To the inherent uncertainty associated with the width of radar reflections and to the uncertainty in the firn correction applied to the radar data. The latter was estimated as the given range difference between using the KCC or CG03 firn density data for the density correction, as these two ice cores represent the range of density variability in our study area. In combination, both factors give a range uncertainty on the order of 1 m (Fig. 6). The full dating uncertainty of both IRHs were computed by error propagation of all three contributing factors.

330 In this way, we assigned an age of 76 ± 7 a or the year 1945 CE ~~The second IRH with~~ to the upper IRH, that matches the deepest detectable horizon (78 ± 12 a) in the survey by Konrad et al. (2013). The lower traced IRH was dated to an age of 288 ± 35 a (i.e. the year 1733 CE) ~~marks the deepest reflection that is continuously traceable in the~~. As it represents the deepest continuously traceable IRH in our data, it demonstrates that LO-SAR processed radargram. ~~But even at greater depths mobile pRES data can be used to inter-compare ice-core chronologies at Colle Gnifetti for larger depth and age ranges than what was possible before. The system can in principle illuminate the englacial structure over the whole ice column. Even below~~

the 288 a-horizon IRHs are visible in parts in our data, which implies that older IRHs are potentially also preserved and might be traceable by further improvements in the acquisition and processing.

4.2 Comparison to ice core data

In summary, the data collected with the mobile pRES reproduces and expands the results of previous surveys. This can be attributed to a combination of accurate data acquisition and system hardware leading to a high SNR, and to the enhancement of signal coherence by the applied LO-SAR processing.

A caveat in interpreting deep IRHs and linking them to ice cores, lies in their associated depth-uncertainty and in potential interference by the bedrock reflector. At the location of the CG03 ice core, the ice-bed interface appears in our radar data at a range of 72 m (Fig. 6d), whereas the ice core itself has a length of 80.2 m (Jenk et al., 2009). This mismatch can be attributed to a potentially non-straight orientation of the borehole, and steep gradients in the bedrock topography of Colle Gnifetti, which affect the apparent position of the bedrock reflector in the radar data (Eisen et al., 2003; Bohleber, 2011). Following Moran et al. (2000), three-dimensional array processing and correspondingly dense profile grids are needed at steeply sloping topography to accurately measure the bedrock reflector depth. With only two-dimensional profiling, an accuracy on the order of 10 m is to be expected. Moreover, unlike traditional SAR processing methods, the LO-SAR processing does not provide a range migration, but merely aims at improving the SNR of specular reflections in the radargram.

Because of the complex basal topography, it is moreover possible that near-basal IRHs are masked by the 15 dB stronger cross-track bedrock reflections, if these IRHs are not similarly recorded from cross-track angles. Expanding our setup with a multi-channel cross-track antenna array (Castelletti et al., 2017; Holschuh et al., 2020; Scanlan et al., 2020) would allow to decipher the true origin of the near-basal IRH and bed returns and help in locating, separating and interpreting their signatures.

4.2 Origin of reduced radar backscatter

~~Similar to previous GPR surveys from Colle Gnifetti, the LO-SAR processed radar data shows a distinct contrast~~ By observing deep IRHs that are undisturbed and nearly flat, it can be excluded that their apparent absence in earlier surveys was caused by buckling or folding of reflectors, or a complete degradation of dielectric contrasts. Yet, a distinct transition in radio-backscatter between the upper and the lower part of the ice column ~~in the following, we investigate if available ice core data of firm density and acidity provides evidence as to why this is the case. Variations of both properties is also present in the LO-SAR processed~~ pRES data. The pRES power profile at CG03 (Fig. 6d) shows a highly reflective regime in the top 36 m, where reflections mostly attain values above -25 dB, and a low reflective regime below 45 m depth, where the returned power rarely exceeds -40 dB. In between these two regimes, the power level drops abruptly over less than 10 m. The bedrock reflections have a normalized power above -25 dB. Variations of density and acidity, together with COF, are ~~potential~~ reflection mechanisms that can form IRHs ~~and control the reflectivity~~. Here, we investigate if the dominant reflection mechanisms at Colle Gnifetti and the origin of the drop in backscattered power can be identified by direct comparison of the reflected power of observable IRHs with density and acidity records from ice cores.

Both at CG03 and KCC, firm compaction ~~occurs in is mostly confined to~~ the upper ~ 40 m (Fig. 6a). ~~Most variability in density is observed~~ Strong density variations occur particularly in the top 15 m, where melt layers ~~are can be~~ identified in the high-resolution record of the KCC core (Freitag et al., 2018). ~~These variations are likely causing near-surface IRHs. Further~~
370 ~~down, especially below 35 m depth, density contrasts are significantly weaker and show no correlation with the backscattered power. The reflectivity at depth is therefore not controlled by density.~~

~~Acidity is approximated by the~~ Accordingly, deep IRHs must be caused by impurities which determine the acidity and perhaps may induce localized gradients in the COF (Drews et al., 2012). By computing the ion balance between the ~~concentrations of~~ Ca^{2+} , Na^+ , NH_4^+ , NO_3^- and SO_4^{2-} ~~at concentrations measured in the CG03 (Fig. 6b). The /CG15 ice cores (Sigl et al., 2018a, b)~~
375 ~~, we obtained an estimate of the acidity with ~ 3 cm resolution (Fig. 6b). In addition, for comparison with the pRES signal we smoothed this estimate using a Gaussian filter with a width of 48 cm which corresponds to the mean resolution of the pRES data in firm.~~

The ion balance is dominated by alkaline peaks ~~, which are caused that are induced by~~ Ca^{2+} ~~and represent which is a proxy for Saharan dust. An example for a major Saharan dust deposition events (e.g., in 1936 CE/36.5 m depth, Sigl et al., 2018a).~~
380 ~~event is the 1936 CE peak in 36.5 m depth (Sigl et al., 2018a) that appears as a strong IRH in the radar data (Fig. 6d) and marks the onset of the power drop. Major Saharan dust deposition events occur on a decadal timescales, with an increasing frequency only in the last 4 decades, attributed to increasing drought conditions in northern Africa (Sigl et al., 2018a). In combination with other natural deposition, for example due to volcanic activity and forest fires, this sets the natural background for acidity variations at Colle Gnifetti.~~

By excluding Ca^{2+} from the ion balance, a trend from alkaline conditions in the pre-industrial to more acidic conditions during the 20th century ~~, which becomes apparent (Fig. 6c). This trend~~ initiates at a depth of 45 m, ~~becomes apparent (Fig. 6c). These~~ which corresponds to the year 1875 CE and the onset of industrialization in Western Europe (Sigl et al., 2018a). ~~Accordingly, the transition in acidity can be attributed to an increase in anthropogenic pollution. In particular, the deposition of~~
390 ~~NH_4^+ , NO_3^- and SO_4^{2-} is largely controlled by anthropogenic activity (Preunkert et al., 2003; Schwikowski et al., 1999) and correlates with other industrial emissions (e.g., refractory black carbon, Sigl et al., 2018a). Eisen et al. (2003) suggested that this acidity shift induces the change in reflectivity at Colle Gnifetti. A similar contrast in reflectivity at the glacial-interglacial transition is present across the Greenland Ice Sheet and is also thought to be induced by a transition in the amount of impurity deposition (Karlsson et al., 2013).~~

The more acidic conditions in the upper ice column are accompanied by a generally higher variability of the acidity ~~itself,~~
395 ~~which is most pronounced in the fine resolution record between 15–32 m depth. This high acidity variability strongly correlates with the strength of backscattered power. We conclude that it is not the general acidity level itself which induces the shift from a low- to a highly-reflective regime at Colle Gnifetti, but that it is caused by the associated higher rate at which deposition of anthropogenic pollution occurs.~~

In addition to altering the acidity, impurity layers might control the grain size (Kerch, 2016) and thereby induce localized
400 ~~changes of the COF (Drews et al., 2012). Potentially, this mechanism can additionally modulate the reflectivity at Colle Gnifetti. In a seismic profile collected across the KCI ice core, Diez et al. (2013) detected an englacial reflection 5 m above~~

~~the bedrock, which they attributed to changes in the crystal orientation. In our data, this reflection might correspond to the comparatively strong IRH at 67 m depth.~~

405 ~~The power profile of the recorded pRES data at CG03 shows a highly reflective regime in the top 36 m, where reflections mostly attain values above -25 dB, and a low reflective regime below 45 m depth, where the returned power rarely exceeds -40 dB. In between these two regimes, the power level drops abruptly over less than 10 m. The bedrock reflections have a normalized power above -25 dB, again.~~

5 Discussion

5.1 Feasibility assessment and system improvements

410 Our ~~proof-of-concept~~ proof of concept study demonstrates the capability of the pRES to expand the range over which englacial stratigraphy can be detected, which is a clear improvement over previous surveys that used ~~pulsed-impulse~~ GPRs. However, it comes at the cost of significantly slower data acquisition (Section 2.1) ~~, which that~~ takes several hours as opposed to several tens of minutes with ~~pulsed-GPRs~~ impulse systems. This results from the required high spatial sampling rate and the long chirp time of 1 s of the pRES (which is not a limiting factor for its intended stationary surveys). In combination, these factors make
415 data collection in stop-and-go mode necessary.

This raises the question whether ~~pulsed-impulse~~ GPRs can achieve similar detection ranges when being operated in stop-and-go mode and by applying high stacking rates, equivalent to the 1 s chirp time, to suppress incoherent backscatter. Although we cannot answer this question directly, we note that even if these GPRs can achieve a SNR comparative to the unprocessed pRES data (Fig. 5c), they will not be able to match the SNR potentially achievable by ~~phase-based radar processing~~ phase-coherent
420 radar processing (Fig. 5d).

~~Therefore, we suggest that the objective of further~~ We suggest that future research should not ~~be a more painstaking data collection using pulsed GPRs~~ focus on improving imaging with impulse GPRs by making data acquisition more painstaking but rather aim at accelerating the profiling capabilities of FMCW radars, ~~because the~~. The laborious data acquisition is the key limitation for mobile operation of the pRES ~~, restricting and restricts~~ the current applicability of the system to targeted small
425 scale surveys. In the following, we discuss how to accelerate data acquisition in future deployments.

The required spatial sampling rate for LO-SAR processing is set by the fact that reflections need to be traceable (Schroeder et al., 2019). The slope of IRHs can only be derived from the phase when it changes by less than π between neighboring traces, otherwise, spatial aliasing occurs. Thus, following Eq. (7) the minimal required trace spacing to resolve IRHs with a slope s is given by

$$430 \quad \Delta d < \frac{\lambda_c}{4 \tan(s)}. \quad (13)$$

In snow and firn-covered glacial ice, GPR can only record IRHs with a maximum slope of approximately 45° (Holschuh et al., 2014). Accordingly, a trace spacing of less than 14 cm is required to record IRHs of such slopes. This also suffices the threshold

of $\Delta d < \lambda_c/2$ to avoid the occurrence of grating lobes when imaging (basal) point reflectors (Kapai et al., 2022). A coarser trace spacing can be used, when only IRHs with a lower inclination are expected at the study site.

435 Nevertheless, if the requirement for stop-and-go measurements can be ~~loosened~~relaxed, a high spatial sampling rate is less of a problem. This can either be achieved by reducing the potential noise due to movement of the pRES during chirp acquisition or by reducing the chirp time. Electrical noise by cable motion can be reduced by using phase-stable cables ~~in future deployments~~ (Hati et al., 2009). However, increased noise by averaging signals of multiple reflections and the occurrence of Doppler blurring and grating lobes (Kapai et al., 2022) can only be avoided ~~when moving with~~ with the pRES when moving at very low speeds.

440 Fortunately, these problems are not of physical, but of technical nature and can again be avoided by reducing the chirp time.

The chirp time T of a FMCW radar ~~determines is set by its hardware design and operation range. This is because~~ the deramped frequency at a given range ~~(Eq. 1). The pRES is determined by T (Eq. 1). Thus, the sampling rate of a FMCW radar system's data logger sets a lower limit on T . The pRES, for example,~~ was designed to monitor up to 2 km thick polar ice, which for a chirp time of 1 s gives a maximum deramped frequency of 4.7 kHz. The build-in data logger ~~of the pRES with,~~

445 ~~which effectively operates at~~ a sampling rate of 40 kHz ~~was chosen accordingly (Brennan et al., 2014) and sets the lower limit of the chirp time. However, for,~~ was selected accordingly (Brennan et al., 2014). For deployment of the pRES on less thick ice ~~this means that~~ the chirp time ~~of the pRES~~ can be reduced. For example, for surveying less than 200 m thick ice, as we do in this study, a 90 % shorter chirp time could safely be selected without exceeding the sampling rate of the data logger. ~~Even faster chirp times in the~~ Yet, this reduction would also result in an increased noise level which might need to be compensated

450 by stacking. To completely avoid the stop-and-go requirement, redesigned FMCW system are desirable that similar to many airborne chirp systems operate in the μ s-range are desirable, but require a redesign of the hardware range.

A second limitation of the pRES lies in its range resolution, which is 2.5 times ~~higher, i.e. worse, coarser~~ compared to the previously used 250 MHz ~~pulsed-impulse~~ GPRs. The latter have a theoretical vertical resolution of 0.17 m as given by $\delta_{R,GPR} = \lambda_{GPR}/4 = c/(4\sqrt{\epsilon_r}f_{GPR})$. The resolution of FMCW radars is determined by their bandwidth, following Eq. (2):

455 $\delta_{R,FMCW} = c/(2\sqrt{\epsilon_r}B_{FMCW})$. For the pRES with $B = 200$ MHz this gives a vertical resolution of only 0.43 m. 250 MHz ~~pulsed-impulse~~ GPRs are consequently better at detecting shallower IRHs. ~~To achieve a comparable resolution with a FMCW system, Redesigned FMCW systems would require~~ a bandwidth of 500 MHz ~~is required to achieve a comparable resolution.~~

5.2 Slope estimation

The presented LO-SAR processing is also computationally expensive, primarily because of the slope estimation algorithm. For

460 short profiles, this is less of a problem (in the examples provided here the compute time was 12 hours on a normal performing ~~Desktop desktop~~ computer), but it might be a restriction for more extensive mobile pRES surveys ~~in the future.~~

Direct computation of englacial slopes from horizontal gradients of the phase, as introduced by MacGregor et al. (2015), is significantly faster. But it also gives a less accurate estimate, because it operates on a point-by-point (i.e. zero-dimensional) base and directly translates noise in the phase into noise in the slopes. For this reason, we derive the slopes of IRHs by matching

465 slope lines to the corrected phase. As this is a one-dimensional approach we combine the information from adjacent traces ~~and get,~~ which entails some horizontal averaging and thereby provides a more accurate slope estimate.

A third method to derive englacial slopes is based on the Radon transform, which operates on a two-dimensional window and computes line integrals over a range of possible slopes and intercepts (Holschuh et al., 2017). Similar to our approach, the Radon transform is computed for every grid point and the correct slope is selected as the one which gives the most coherent stack. Although this is even more computationally expensive, it does not improve the slope estimate further compared to our approach. This can be attributed to the fact that we essentially perform a one-dimensional Radon transform ~~–~~ which only considers an intercept of zero. This is possible because we obtain the coherence along the line integrals from the coherence of the phase and not from the coherence of structural patterns, as the two-dimensional Radon transform does.

~~It should be noted that our use of the corrected phase in fact contradicts with its intended purpose of indicating a fine rangeoffsets for each range bin, as suggested by Brennan et al. (2014). They introduced it as the phase differences between the raw and the reference phase, which following Eq. (6) would translate into range offsets. However, this approach relies on the assumption that the raw phase values in each range bin are independent. This would be expressed by a clear inter-bin variability of the raw phase, which cannot be observed (Fig. 4a). Instead, strong reflections spread out over several range bins, across which the raw phase tends to be stable and distinct jumps of the raw phase only occur at the transition between different reflections.~~

~~Under the assumption that the raw phase is constant in the vertical, it becomes clear why the corrected phase is constant along IRHs. The information about IRH slopes is entailed in the along-track gradient of the phase. The selection of the iteration range is based on two factors. Its boundaries must cover the range of slopes that are to be expected, and the step size needs to be sufficiently small to ensure that a mismatch does not result in destructive interference along the slope line. The limit for the occurrence of destructive interference can be estimated from the phase offset between range bins of $3\pi/p$ (Eq. 4). At a phase mismatch of π between the end points of the slope line, these will be completely out of phase, which for $p = 8$ equates to a mismatch of $8/3$ range bins. For an aperture length of 5 m this corresponds to a slope error of $\sim 2^\circ$. As the compute time was not a limiting factor in our proof of concept, we choose a wide slope range of an IRH has increased by $\phi_{\text{ref,bin}}$ in the horizontal, it will have moved down by one range bin. But as the raw phase of each reflection is approximately constant in the vertical, by subtracting exactly $\phi_{\text{ref,bin}}$ from the next range bin during phase correction, the value of the corrected phase at for example the center of an IRH will remain constant -30° to 30° in steps of 0.2° to not a priori prevent the detection of potential stronger inclined reflections in the near-basal ice and to sufficiently avoid the destructive interference limit of 2° .~~

Our final slope estimate shows some noticeable vertical bands (Fig. 5b). These are most likely ~~no~~ not englacial signals, but are caused by antenna tilt due to small-scale surface undulations. However, the slopes are only an intermediate product in our LO-SAR processing routine. In the subsequent coherent summation along IRHs, we specifically aim to follow IRHs, also across such undulations. For this reason, these artifacts are of no concern in our study, but might be relevant in other applications of the slope estimate.

5.3 Detection of deep IRHs

500 The data collected with the mobile pRES reproduces and expands the results of previous surveys. We identified an IRH with an age of 76 ± 7 a at the time of recording that with respect to depth matches the deepest detectable horizon (78 ± 12 a) in the survey by Konrad et al. (2013). By observing several deeper IRHs in our data, we demonstrate that LO-SAR processed mobile pRES data can be used to inter-compare ice-core chronologies at Colle Gnifetti for larger depth and age ranges than what was possible before. We shifted this limit to at least 288 ± 35 a. This can be attributed to a combination of accurate data acquisition and system hardware leading to a high SNR, and enhancement of signal coherence by the applied LO-SAR processing.

505 The system can in principle illuminate the glacial structure over the whole ice column. The data indicate the presence of a layered stratigraphy down to bedrock, which implies that older IRHs are potentially also preserved and might be traceable by further improvements in the processing and suppression of uncertainty sources. In particular, our data acquisition was affected by technical problems, which might have arisen from overexerting the data-writing capacity of the pRES after collecting > 1000 individual traces in a single folder. Thereby, various later recorded traces were lost or showed an enhanced noise level. This diminished the data quality of the second part of the pRES profile collected upstream towards KCC (Fig. 5)e-f. In addition, this part might have been affected by a less stable positioning of the mobile pRES system at each point due to the increased surface slope. As a consequence, deep IRHs in the upstream profile are disturbed and not continuously traceable. Finally, it should be noted that our use of the corrected phase during slope estimation contradicts with its intended purpose of providing a fine range offsets for each range bin, as suggested by Brennan et al. (2014). They introduced it as the phase difference between the raw and the reference phase, which prevents linking the CG03 and KCC ice cores with our data. following Eq. (6) would translate into a fine range offset to measure the absolute range of a reflection in a Vernier-like process (Brennan et al., 2014). However, this approach relies on the assumption that the raw phase values in each range bin are independent. This would be expressed by a clear inter-bin variability of the raw phase, which cannot be observed (Fig. 3a). Instead, strong reflections spread out over several range bins, across which the raw phase tends to be stable and distinct jumps of the raw phase only occur at the transition between different reflections. Therefore, the phase of a reflection is only representative for a specific point within its width, potentially its center, which needs to be taken into account for measuring the absolute range of a reflection. The interferometric measurement of the relative change of a reflection range between two measurements is not affected by its inter-bin spread and can be directly computed from phase changes at any range bin.

520 A caveat in interpreting deep IRHs and linking them to ice cores, lies in their associated depth-uncertainty and in potential interference by the bedrock reflector. At the location of the CG03 ice core, the ice-bed interface appears in our radar data at a range of 72 m (Fig. 6d), whereas the ice core itself has a length of 80.2 m (Jenk et al., 2009). This mismatch can be attributed to a potentially non-straight orientation of the borehole, and steep gradients in the bedrock topography of Colle Gnifetti, which affect the apparent position of the bedrock reflector in the radar data (Eisen et al., 2003; Bohleber, 2011). Following (Moran et al., 2000), three-dimensional array processing and correspondingly dense profile grids are needed at steeply sloping topography to accurately measure the bedrock reflector depth. With only two-dimensional profiling, an accuracy on the order of 10 m is to be expected. Moreover, unlike traditional SAR processing methods, the LO-SAR processing does not provide a range migration, but merely aims at improving the SNR of the radargram.

525 Because of the complex basal topography, it is moreover possible that near-basal IRHs are masked by

535 5.3 Future applications

The pRES is used in a broad range of glaciological applications. For example, by performing repeat visits at fixed locations, the 15 dB stronger cross-track bedrock reflections, if these IRHs are not similarly recorded from cross-track angles. Expanding our setup with a multi-channel cross-track antenna array (Castelletti et al., 2017; Holschuh et al., 2020; Seanlan et al., 2020) would allow to decipher the true origin of the near-basal IRH and bed returns and help in locating, separating and interpreting their signatures. pRES can measure ocean-induced melting at the base of ice shelves (Nicholls et al., 2015; Vaňková et al., 2021; Zeising et al., 2022), englacial vertical ice deformation (Gillet-Chaulet et al., 2011; Kingslake et al., 2014) and firn compaction (Case and Kingslake, 2022). With polarimetric techniques that screen the ice with differently polarized electromagnetic waves, the COF can be inferred (Jordan et al., 2020; Ershadi et al., 2022). Our mobile pRES setup expands this list by the enhanced detection of englacial stratigraphy, but also offers the potential to perform the above-mentioned survey types with larger spatial coverage.

545 5.4 **Origin of the reduced radar backscatter in the lower half of the ice column**

By observing deep IRHs that are undisturbed and nearly flat, it can be excluded that their apparent absence in earlier surveys was caused by buckling or folding of reflectors, or a complete degradation of dielectric contrasts. Direct comparison of the reflected power of observable IRHs with ice core records of density and acidity allows us to assess the dominant reflection mechanisms at Colle Gnifetti and the origin of the drop in backscattered power. Strong density variations due to melt layers are only present in Polarimetric pRES measurements can efficiently be conducted with multiple-input multiple-output (MIMO) antenna configurations in which the two transmitting and two receiving polarized radar antennas are orthogonally oriented, respectively. A mobile acquisition of COF data by towing a polarimetric MIMO setup with an autonomous rover was presented by Ershadi et al. (2024). MIMO setups can moreover be used for cross-track signal detection (Castelletti et al., 2017; Holschuh et al., 2020) or for density inversions (Arthern et al., 2013). However, the top 15 m and are likely causing near-surface IRHs. Further down, especially below 35 m depth, density contrasts are significantly weaker, show no correlation with the backscattered power, and, therefore, do not control the reflection mechanism. additional antenna weight restricts the extension of the here presented mobile pRES setup to MIMO configurations, because depending on the surface topography and snow conditions the system would become too heavy for hand-towed operation. For obtaining a lightweight FMCW MIMO system, the use of an FMCW radar that operates in a higher frequency range and, thus, with smaller and lighter antennas would be required.

Accordingly, deep IRHs are caused by impurities, determining the acidity and perhaps even promote changes in the COF. As noted by Eisen et al. (2003), the deep ice is more alkaline due to smaller emissions in the past, reducing its conductivity. However, for repeat-track surveys, it is not the general acidity level which induces reflections, but variations of it. By computing the ion balance between Ca^{2+} , Na^+ , NH_4^+ , NO_3^- and SO_4^{2-} , measured in the CG03 ice core (Sigl et al., 2018a), we obtained a high-resolution estimate of the acidity. It is dominated by prominent peaks in Ca^{2+} (Fig. 6b), which is a proxy for Saharan Dust (Sigl et al., 2018a). An example is the 1936 CE peak in 36 m depth which appears as a strong IRH in the radar data (Fig. 6d) that marks the onset of the power drop. Major Saharan dust deposition events occur on a decadal timescales, with an increasing frequency only in the last 4 decades, attributed to increasing drought conditions in northern Africa (Sigl et al., 2018a). In

combination with other natural deposition, for example due to volcanic activity and forest fires, this sets the natural background for acidity variations at Colle Gnifetti. to measure the spatio-temporal variability of firn compaction (Medley et al., 2015), no adaptations to our mobile pRES setup are needed. But the correlation of pRES repeat measurements to detect the vertical displacement of englacial reflections or the ice-ocean interface is thought to rely strongly on accurate repositioning of the system. We therefore suggest that future studies investigate which accuracy in the spatial and directional repositioning is required to develop corresponding acquisition and processing techniques.

By excluding Ca^{2+} from the ion balance, the impact of anthropogenic pollution is highlighted (Fig. 6e). In particular, the deposition of NH_4^+ , NO_3^- and SO_4^{2-} is largely controlled by anthropogenic activity (Preunkert et al., 2003; Schwikowski et al., 1999) and correlates with other industrial emissions (e.g., refractory black carbon, Sigl et al., 2018a). Starting in 1875 CE, which corresponds to 45 m depth at CG03 and the onset of industrialization in Western Europe (Sigl et al., 2018a), higher concentrations of these pollutants can be observed. These do not only shift the ice chemistry to more acidic conditions, but in particular correspond to an accelerated rate of impurity deposition events, most notable between 15 m and 32 m depth. This high acidity variability strongly correlates with the strength of backscattered power, because acidity contrast fosters IRH formation. Accordingly, the shift between a high- and a low-reflective regime at Colle Gnifetti, is caused by a shift from deposition of natural impurities at a low rate to anthropogenic pollution at a high rate.

In addition to altering the acidity, impurity layers might cause localized changes of the COF which additionally modulate the reflectivity at Colle Gnifetti. In a seismic profile collected across the KCI ice core, Diez et al. (2013) detected an englacial reflection 5 m above the bedrock, which they attributed to changes in the crystal orientation. In our data, this reflection might correspond to the comparatively strong IRH at 67 m depth

6 Conclusions

We present a phase-coherent ground-based radar system with low weight and power requirements by mobilizing the pRES. The setup facilitates coherent radar profiling in glaciated areas with low accessibility, as for example on remote mountain glaciers. A cm scale positioning accuracy at dm trace spacing is achieved by integration of a RTK GNSS. In combination, the coherence and positional accuracy enable the application of SAR processing techniques for enhancing the quality of the obtained radargrams. Here, we specifically focus on improving the imaging of the englacial stratigraphy by tailoring the LO-SAR processing technique by Castelletti et al. (2019) to mobile pRES data. In this process, we demonstrate that after subtraction of the reference phase the corrected phase signal is constant along IRHs. We exploit this characteristic in our implementation of LO-SAR processing by first detecting the slopes of IRHs to filter these before performing the coherent integration of power directly along IRHs.

We presented a proof-of-concept study for coherent radar profiling with a mobile pRES that is positioned using a RTK GPS. In combination with The capability of the mobile pRES system and LO-SAR processing, this enables the detection of implementation are demonstrated in a proof of concept study for detecting of the deep englacial stratigraphy of Colle Gnifetti. This is a clear step forward compared to previous GPR surveys where IRHs could only be detected Previous GPR surveys at

the site could detect IRHs only in the upper 30–50 % of the ice column. ~~Our study demonstrates the possibility to extensively map the deep structure of Colle Gnifetti in future deployments. Such a targeted survey could connect all previous ice core locations to inter-compare their chronologies and address open questions in the understanding of existing ice core records, such as the origin of the discontinuity in the chronology of the KCC ice core. Moreover, it can aid the selection of future ice~~
605 ~~core drilling sites, for example to find the deepest, and potentially oldest, preserved stratigraphically intact ice in the saddle, and therefore in the European Alps. As the applicability of our approach is however limited by time-intensive data acquisition due to the long chirp time of the pRES, we have provided suggestions on how to accelerate it in future deployments, whereas~~
with our approach the presence of a layered stratigraphy can essentially be detected down to the bedrock. Thereby, an IRH with an age of 288 ± 35 a could be traced continuously, which is a clear step forward compared to the detection of a 78 ± 12 a old
610 IRH achieved by previous surveys. By comparison to ice core data, we in addition identified that the ~~reflection pattern at Colle Gnifetti is controlled by acidity variations due to the deposition of impurities. The~~ presence of a highly reflective regime in the upper part of ~~the glacier (which was detectable in earlier~~ Colle Gnifetti (detectable in previous surveys) compared to a less reflective regime in the ~~bottom~~ lower part (which previously appeared echo-free) ~~;~~ is caused by acidic impurity layers that are deposited at a high rate since the onset of industrialization. ~~Only comparatively modest technical improvements are required~~
615 ~~to deploy this phase-coherent radar in other geoscientific settings, opening up new avenues for scientific applications based on FMCW radars. These improved imaging capabilities of the mobile pRES highlight the possibility to extensively map the deep stratigraphy of Colle Gnifetti and other mountain glaciers in the future. However, our study also demonstrates that the main limitation of the mobile pRES lies in the time-intensity of data acquisition due to its 1 s chirp time. We therefore encourage the development of faster ground-based FMCW radar systems suitable for profiling. Repeat-track surveys are a promising~~
620 application for the mobile pRES as they require no hardware adaptations. In addition to ongoing efforts of expanding the repeat-track capabilities of airborne chirp systems, this opens the avenue to detect englacial deformation, firm compaction and basal melt rates with the pRES with large spatial coverage and fine resolution.

Code and data availability. The raw and processed mobile pRES data are available at <https://doi.org/PANGAEA.965199> (Oraschewski et al., 2024a) and <https://doi.org/10.1594/PANGAEA.965194> (Oraschewski et al., 2024b). The LO-SAR processing code is available at
625 <https://github.com/oraschewski/pRocESsor>. A permanent release will be provided for the final published version of the manuscript.

Author contributions. FMO led the data acquisition, analysis and writing of the paper. FMO, RD and OE designed the study outline and FMO, RD, IK and MRE conducted the data acquisition. JH supported the analysis of the data and designed Fig. 1a. All authors contributed to the writing of the final paper.

Competing interests. RD and OE are members of the editorial board of The Cryosphere. The authors have no other competing interests to
630 declare.

Acknowledgements. We acknowledge ~~that the support of~~ Falk M. Oraschewski ~~was supported through a doctoral scholarship provided~~ by the German Academic Scholarship Foundation ~~with a doctoral scholarship~~. Reinhard Drews, Inka Koch and M. Reza Ershadi were supported by Deutsche Forschungsgemeinschaft (DFG) Emmy Noether grant (grant no. DR 822/3-1) and Jonathan Hawkins by the Royal Society Enhancement Award (grant no. RGF\EA\180173), awarded to Dr. Lai Bun Lok. We further acknowledge support from the Open Access
635 Publication Fund of the University of Tübingen.

References

- Alean, J., Haeberli, W., and Schädler, B.: Snow Accumulation, Firn Temperature and Solar Radiation in the Area of the Colle Gnifetti Core Drilling Site (Monte Rosa, Swiss Alps): Distribution Patterns and Interrelationships, *Zeitschrift für Gletscherkunde und Glazialgeologie*, 19, 131–147, 1983.
- 640 Arthern, R. J., J. Corr, H. F., Gillet-Chaulet, F., Hawley, R. L., and Morris, E. M.: Inversion for the Density-depth Profile of Polar Firn Using a Stepped-frequency Radar, *Journal of Geophysical Research: Earth Surface*, 118, 1257–1263, <https://doi.org/10.1002/jgrf.20089>, 2013.
- Bohleber, P.: Ground-Penetrating Radar Assisted Ice Core Research: The Challenge of Alpine Glaciers and Dielectric Ice Properties, Ph.D. thesis, Heidelberg University, <https://doi.org/10.11588/heidok.00012800>, 2011.
- Bohleber, P., Wagner, N., and Eisen, O.: Permittivity of Ice at Radio Frequencies: Part II. Artificial and Natural Polycrystalline Ice, *Cold Regions Science and Technology*, 83–84, 13–19, <https://doi.org/10.1016/j.coldregions.2012.05.010>, 2012.
- 645 Bohleber, P., Erhardt, T., Spaulding, N., Hoffmann, H., Fischer, H., and Mayewski, P.: Temperature and Mineral Dust Variability Recorded in Two Low-Accumulation Alpine Ice Cores over the Last Millennium, *Climate of the Past*, 14, 21–37, <https://doi.org/10.5194/cp-14-21-2018>, 2018.
- Brennan, P. V., Lok, L. B., Nicholls, K., and Corr, H.: Phase-sensitive FMCW Radar System for High-precision Antarctic Ice Shelf Profile Monitoring, *IET Radar, Sonar & Navigation*, 8, 776–786, <https://doi.org/10.1049/iet-rsn.2013.0053>, 2014.
- 650 Case, E. and Kingslake, J.: Phase-Sensitive Radar as a Tool for Measuring Firn Compaction, *Journal of Glaciology*, 68, 139–152, <https://doi.org/10.1017/jog.2021.83>, 2022.
- Castelletti, D., Schroeder, D. M., Hensley, S., Grima, C., Ng, G., Young, D., Gim, Y., Bruzzone, L., Moussessian, A., and Blankenship, D. D.: An Interferometric Approach to Cross-Track Clutter Detection in Two-Channel VHF Radar Sounders, *IEEE Transactions on Geoscience and Remote Sensing*, 55, 6128–6140, <https://doi.org/10.1109/TGRS.2017.2721433>, 2017.
- 655 Castelletti, D., Schroeder, D. M., Mantelli, E., and Hilger, A.: Layer Optimized SAR Processing and Slope Estimation in Radar Sounder Data, *Journal of Glaciology*, 65, 983–988, <https://doi.org/10.1017/jog.2019.72>, 2019.
- Cavitte, M. G. P., Parrenin, F., Ritz, C., Young, D. A., Van Liefferinge, B., Blankenship, D. D., Frezzotti, M., and Roberts, J. L.: Accumulation Patterns around Dome C, East Antarctica, in the Last 73 Kyr, *The Cryosphere*, 12, 1401–1414, <https://doi.org/10.5194/tc-12-1401-2018>, 2018.
- 660 Clifford, H. M., Spaulding, N. E., Kurbatov, A. V., More, A., Korotkikh, E. V., Sneed, S. B., Handley, M., Maasch, K. A., Loveluck, C. P., Chaplin, J., McCormick, M., and Mayewski, P. A.: A 2000 Year Saharan Dust Event Proxy Record from an Ice Core in the European Alps, *Journal of Geophysical Research: Atmospheres*, 124, 12 882–12 900, <https://doi.org/10.1029/2019JD030725>, 2019.
- Diez, A., Eisen, O., Hofstede, C., Bohleber, P., and Polom, U.: Joint Interpretation of Explosive and Vibroseismic Surveys on Cold Firn for the Investigation of Ice Properties, *Annals of Glaciology*, 54, 201–210, <https://doi.org/10.3189/2013AoG64A200>, 2013.
- 665 Drews, R.: Evolution of Ice-Shelf Channels in Antarctic Ice Shelves, *The Cryosphere*, 9, 1169–1181, <https://doi.org/10.5194/tc-9-1169-2015>, 2015.
- Drews, R., Eisen, O., Weikusat, I., Kipfstuhl, S., Lambrecht, A., Steinhage, D., Wilhelms, F., and Miller, H.: Layer Disturbances and the Radio-Echo Free Zone in Ice Sheets, *The Cryosphere*, 3, 195–203, <https://doi.org/10.5194/tc-3-195-2009>, 2009.
- 670 Drews, R., Eisen, O., Steinhage, D., Weikusat, I., Kipfstuhl, S., and Wilhelms, F.: Potential Mechanisms for Anisotropy in Ice-Penetrating Radar Data, *Journal of Glaciology*, 58, 613–624, <https://doi.org/10.3189/2012JoG11J114>, 2012.

- Eisen, O., Nixdorf, U., Keck, L., and Wagenbach, D.: Alpine Ice Cores and Ground Penetrating Radar: Combined Investigations for Glaciological and Climatic Interpretations of a Cold Alpine Ice Body, *Tellus B*, 55, 1007–1017, <https://doi.org/10.1034/j.1600-0889.2003.00080.x>, 2003.
- 675 EPICA community members: Eight Glacial Cycles from an Antarctic Ice Core, *Nature*, 429, 623–628, <https://doi.org/10.1038/nature02599>, 2004.
- Ershadi, M. R., Drews, R., Martín, C., Eisen, O., Ritz, C., Corr, H., Christmann, J., Zeising, O., Humbert, A., and Mulvaney, R.: Polarimetric Radar Reveals the Spatial Distribution of Ice Fabric at Domes and Divides in East Antarctica, *The Cryosphere*, 16, 1719–1739, <https://doi.org/10.5194/tc-16-1719-2022>, 2022.
- 680 Ershadi, M. R., Drews, R., Hawkins, J., Elliott, J., Lines, A. P., Koch, I., and Eisen, O.: Autonomous Rover Enables Radar Profiling of Ice-Fabric Properties in Antarctica, *IEEE Transactions on Geoscience and Remote Sensing*, pp. 1–1, <https://doi.org/10.1109/TGRS.2024.3394594>, 2024.
- Freitag, J., Kerch, J., Hoffmann, H., Spaulding, N., and Bohleber, P.: XCT Density from the Alpine Ice Core KCC (2013), <https://doi.org/10.1594/PANGAEA.887691>, 2018.
- 685 Fujita, S., Maeno, H., and Matsuoka, K.: Radio-Wave Depolarization and Scattering within Ice Sheets: A Matrix-Based Model to Link Radar and Ice-Core Measurements and Its Application, *Journal of Glaciology*, 52, 407–424, <https://doi.org/10.3189/172756506781828548>, 2006.
- Gabrieli, J. and Barbante, C.: The Alps in the Age of the Anthropocene: The Impact of Human Activities on the Cryosphere Recorded in the Colle Gnifetti Glacier, *Rendiconti Lincei*, 25, 71–83, <https://doi.org/10.1007/s12210-014-0292-2>, 2014.
- Gillet-Chaulet, F., Hindmarsh, R. C. A., Corr, H. F. J., King, E. C., and Jenkins, A.: *In-Situ* Quantification of Ice Rheology and Direct
690 Measurement of the Raymond Effect at Summit, Greenland Using a Phase-Sensitive Radar, *Geophysical Research Letters*, 38, L24503, <https://doi.org/10.1029/2011GL049843>, 2011.
- Hati, A., Nelson, C. W., and Howe, D. A.: Vibration-Induced PM and AM Noise in Microwave Components, *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, 56, 2050–2059, <https://doi.org/10.1109/TUFFC.2009.1288>, 2009.
- Heister, A. and Scheiber, R.: Coherent Large Beamwidth Processing of Radio-Echo Sounding Data, *The Cryosphere*, 12, 2969–2979,
695 <https://doi.org/10.5194/tc-12-2969-2018>, 2018.
- Hélière, F., Lin, C.-C., Corr, H., and Vaughan, D.: Radio Echo Sounding of Pine Island Glacier, West Antarctica: Aperture Synthesis Processing and Analysis of Feasibility from Space, *IEEE Transactions on Geoscience and Remote Sensing*, 45, 2573–2582, <https://doi.org/10.1109/TGRS.2007.897433>, 2007.
- Hoelzle, M., Darms, G., Lüthi, M. P., and Suter, S.: Evidence of Accelerated Englacial Warming in the Monte Rosa Area, Switzerland/Italy,
700 *The Cryosphere*, 5, 231–243, <https://doi.org/10.5194/tc-5-231-2011>, 2011.
- Hoffmann, H., Preunkert, S., Legrand, M., Leinfelder, D., Bohleber, P., Friedrich, R., and Wagenbach, D.: A New Sample Preparation System for Micro-¹⁴C Dating of Glacier Ice with a First Application to a High Alpine Ice Core from Colle Gnifetti (Switzerland), *Radiocarbon*, 60, 517–533, <https://doi.org/10.1017/RDC.2017.99>, 2018.
- Holschuh, N., Christianson, K., and Anandakrishnan, S.: Power Loss in Dipping Internal Reflectors, Imaged Using Ice-Penetrating Radar,
705 *Annals of Glaciology*, 55, 49–56, <https://doi.org/10.3189/2014AoG67A005>, 2014.
- Holschuh, N., Parizek, B. R., Alley, R. B., and Anandakrishnan, S.: Decoding Ice Sheet Behavior Using Englacial Layer Slopes, *Geophysical Research Letters*, 44, 5561–5570, <https://doi.org/10.1002/2017GL073417>, 2017.
- Holschuh, N., Christianson, K., Paden, J., Alley, R., and Anandakrishnan, S.: Linking Postglacial Landscapes to Glacier Dynamics Using Swath Radar at Thwaites Glacier, Antarctica, *Geology*, 48, 268–272, <https://doi.org/10.1130/G46772.1>, 2020.

- 710 Jenk, T. M., Szidat, S., Bolius, D., Sigl, M., Gäggeler, H. W., Wacker, L., Ruff, M., Barbante, C., Boutron, C. F., and Schwikowski, M.: A Novel Radiocarbon Dating Technique Applied to an Ice Core from the Alps Indicating Late Pleistocene Ages, *Journal of Geophysical Research: Atmospheres*, 114, 2009JD011 860, <https://doi.org/10.1029/2009JD011860>, 2009.
- Jordan, T. M., Schroeder, D. M., Elsworth, C. W., and Siegfried, M. R.: Estimation of Ice Fabric within Whillans Ice Stream Using Polarimetric Phase-Sensitive Radar Sounding, *Annals of Glaciology*, 61, 74–83, <https://doi.org/10.1017/aog.2020.6>, 2020.
- 715 Kapai, S., Schroeder, D., Broome, A., Young, T. J., and Stewart, C.: SAR Focusing of Mobile ApRES Surveys, in: *IGARSS 2022 - 2022 IEEE International Geoscience and Remote Sensing Symposium*, pp. 1688–1691, IEEE, Kuala Lumpur, Malaysia, ISBN 978-1-66542-792-0, <https://doi.org/10.1109/IGARSS46834.2022.9883784>, 2022.
- Karlsson, N. B., Dahl-Jensen, D., Gogineni, S. P., and Paden, J. D.: Tracing the Depth of the Holocene Ice in North Greenland from Radio-Echo Sounding Data, *Annals of Glaciology*, 54, 44–50, <https://doi.org/10.3189/2013AoG64A057>, 2013.
- 720 Kerch, J. K.: Crystal-Orientation Fabric Variations on the Cm-Scale in Cold Alpine Ice: Interaction with Paleo-Climature Proxies under Deformation and Implications for the Interpretation of Seismic Velocities, <https://archiv.ub.uni-heidelberg.de/volltextserver/22326/>, <https://doi.org/10.11588/heidok.00022326>, 2016.
- Kingslake, J., Hindmarsh, R. C. A., Aðalgeirsdóttir, G., Conway, H., Corr, H. F. J., Gillet-Chaulet, F., Martín, C., King, E. C., Mulvaney, R., and Pritchard, H. D.: Full-Depth Englacial Vertical Ice Sheet Velocities Measured Using Phase-Sensitive Radar: Measuring Englacial Ice
- 725 Velocities, *Journal of Geophysical Research: Earth Surface*, 119, 2604–2618, <https://doi.org/10.1002/2014JF003275>, 2014.
- Koch, I., Drews, R., Franke, S., Jansen, D., Oraschewski, F. M., Muhle, L. S., Višnjević, V., Matsuoka, K., Pattyn, F., and Eisen, O.: Radar Internal Reflection Horizons from Multisystem Data Reflect Ice Dynamic and Surface Accumulation History along the Princess Ragnhild Coast, Dronning Maud Land, East Antarctica, *Journal of Glaciology*, pp. 1–19, <https://doi.org/10.1017/jog.2023.93>, 2023.
- Konrad, H., Bohleber, P., Wagenbach, D., Vincent, C., and Eisen, O.: Determining the Age Distribution of Colle Gnifetti, Monte Rosa, Swiss Alps, by Combining Ice Cores, Ground-Penetrating Radar and a Simple Flow Model, *Journal of Glaciology*, 59, 179–189, <https://doi.org/10.3189/2013JoG12J072>, 2013.
- 730 Koutnik, M. R., Fudge, T. J., Conway, H., Waddington, E. D., Neumann, T. A., Cuffey, K. M., Buizert, C., and Taylor, K. C.: Holocene Accumulation and Ice Flow near the West Antarctic Ice Sheet Divide Ice Core Site, *Journal of Geophysical Research: Earth Surface*, 121, 907–924, <https://doi.org/10.1002/2015JF003668>, 2016.
- 735 Kusk, A. and Dall, J.: SAR Focusing of P-band Ice Sounding Data Using Back-Projection, in: *2010 IEEE International Geoscience and Remote Sensing Symposium*, pp. 4071–4074, IEEE, Honolulu, HI, USA, ISBN 978-1-4244-9565-8, <https://doi.org/10.1109/IGARSS.2010.5651038>, 2010.
- Licciulli, C., Bohleber, P., Lier, J., Gagliardini, O., Hoelzle, M., and Eisen, O.: A Full Stokes Ice-Flow Model to Assist the Interpretation of Millennial-Scale Ice Cores at the High-Alpine Drilling Site Colle Gnifetti, Swiss/Italian Alps, *Journal of Glaciology*, 66, 35–48, <https://doi.org/10.1017/jog.2019.82>, 2020.
- 740 Lilien, D. A., Steinhage, D., Taylor, D., Parrenin, F., Ritz, C., Mulvaney, R., Martín, C., Yan, J.-B., O’Neill, C., Frezzotti, M., Miller, H., Gogineni, P., Dahl-Jensen, D., and Eisen, O.: Brief Communication: New Radar Constraints Support Presence of Ice Older than 1.5 Myr at Little Dome C, *The Cryosphere*, 15, 1881–1888, <https://doi.org/10.5194/tc-15-1881-2021>, 2021.
- Looyenga, H.: Dielectric Constants of Heterogeneous Mixtures, *Physica*, 31, 401–406, [https://doi.org/10.1016/0031-8914\(65\)90045-5](https://doi.org/10.1016/0031-8914(65)90045-5), 1965.
- 745 Lüthi, M. and Funk, M.: Dating Ice Cores from a High Alpine Glacier with a Flow Model for Cold Firn, *Annals of Glaciology*, 31, 69–79, <https://doi.org/10.3189/172756400781820381>, 2000.

- MacGregor, J. A., Fahnestock, M. A., Catania, G. A., Paden, J. D., Prasad Gogineni, S., Young, S. K., Rybarski, S. C., Mabrey, A. N., Wagman, B. M., and Morlighem, M.: Radiostratigraphy and Age Structure of the Greenland Ice Sheet, *Journal of Geophysical Research: Earth Surface*, 120, 212–241, <https://doi.org/10.1002/2014JF003215>, 2015.
- 750 Medley, B., Ligtenberg, S., Joughin, I., Van Den Broeke, M., Gogineni, S., and Nowicki, S.: Antarctic Firn Compaction Rates from Repeat-Track Airborne Radar Data: I. Methods, *Annals of Glaciology*, 56, 155–166, <https://doi.org/10.3189/2015AoG70A203>, 2015.
- Moran, M. L., Greenfield, R. J., Arcone, S. A., and Delaney, A. J.: Delineation of a Complexly Dipping Temperate Glacier Bed Using Short-Pulse Radar Arrays, *Journal of Glaciology*, 46, 274–286, <https://doi.org/10.3189/172756500781832882>, 2000.
- NEEM community members: Eemian Interglacial Reconstructed from a Greenland Folded Ice Core, *Nature*, 493, 489–494, <https://doi.org/10.1038/nature11789>, 2013.
- 755 Nicholls, K. W., Corr, H. F., Stewart, C. L., Lok, L. B., Brennan, P. V., and Vaughan, D. G.: A Ground-Based Radar for Measuring Vertical Strain Rates and Time-Varying Basal Melt Rates in Ice Sheets and Shelves, *Journal of Glaciology*, 61, 1079–1087, <https://doi.org/10.3189/2015JoG15J073>, 2015.
- Oraschewski, F. M., Koch, I., Ershadi, M. R., Hawkins, J., Eisen, O., and Drews, R.: Raw Data of Mobile Phase-Sensitive Radio Echo Sounder (pRES) Profiling Data of Deep Radiostratigraphy of Colle Gnifetti (Swiss–Italian Alps), 2021, 2024a.
- 760 Oraschewski, F. M., Koch, I., Ershadi, M. R., Hawkins, J., Eisen, O., and Drews, R.: Mobile Phase-Sensitive Radio Echo Sounder (pRES) Profiling Data of Deep Radiostratigraphy of Colle Gnifetti (Swiss–Italian Alps), 2021, 2024b.
- Paden, J.: Synthetic Aperture Radar for Imaging the Basal Conditions of the Polar Ice Sheets, Ph.D. thesis, University of Kansas, 2006.
- Peters, M., Blankenship, D., Carter, S., Kempf, S., Young, D., and Holt, J.: Along-Track Focusing of Airborne Radar Sounding Data from West Antarctica for Improving Basal Reflection Analysis and Layer Detection, *IEEE Transactions on Geoscience and Remote Sensing*, 45, 2725–2736, <https://doi.org/10.1109/TGRS.2007.897416>, 2007.
- 765 Peters, M. E., Blankenship, D. D., and Morse, D. L.: Analysis Techniques for Coherent Airborne Radar Sounding: Application to West Antarctic Ice Streams, *Journal of Geophysical Research: Solid Earth*, 110, 2004JB003 222, <https://doi.org/10.1029/2004JB003222>, 2005.
- Pickell, D. J. and Hawley, R. L.: Performance Characterization of a New, Low-Cost Multi-GNSS Instrument for the Cryosphere, *Journal of Glaciology*, pp. 1–7, <https://doi.org/10.1017/jog.2023.97>, 2024.
- 770 Preunkert, S., Wagenbach, D., and Legrand, M.: A Seasonally Resolved Alpine Ice Core Record of Nitrate: Comparison with Anthropogenic Inventories and Estimation of Preindustrial Emissions of NO in Europe, *Journal of Geophysical Research: Atmospheres*, 108, 2003JD003 475, <https://doi.org/10.1029/2003JD003475>, 2003.
- Scanlan, K. M., Rutishauser, A., Young, D. A., and Blankenship, D. D.: Interferometric Discrimination of Cross-Track Bed Clutter in Ice-Penetrating Radar Sounding Data, *Annals of Glaciology*, 61, 68–73, <https://doi.org/10.1017/aog.2020.20>, 2020.
- 775 Schroeder, D. M., Castelletti, D., and Pena, I.: Revisiting the Limits of Azimuth Processing Gain for Radar Sounding, in: IGARSS 2019 - 2019 IEEE International Geoscience and Remote Sensing Symposium, pp. 994–996, IEEE, Yokohama, Japan, ISBN 978-1-5386-9154-0, <https://doi.org/10.1109/IGARSS.2019.8898737>, 2019.
- Schwikowski, B. M., Doscher, A., Gaggeler, H., and Schotterer, U.: Anthropogenic versus Natural Sources of Atmospheric Sulphate from an Alpine Ice Core, *Tellus B*, 51, 938–951, <https://doi.org/10.1034/j.1600-0889.1999.t01-4-00006.x>, 1999.
- 780 Shi, L., Allen, C. T., Ledford, J. R., Rodriguez-Morales, F., Blake, W. A., Panzer, B. G., Prokopiack, S. C., Leuschen, C. J., and Gogineni, S.: Multichannel Coherent Radar Depth Sounder for NASA Operation Ice Bridge, in: 2010 IEEE International Geoscience and Remote Sensing Symposium, pp. 1729–1732, IEEE, Honolulu, HI, USA, ISBN 978-1-4244-9565-8, <https://doi.org/10.1109/IGARSS.2010.5649518>, 2010.

- 785 Sigl, M., Abram, N. J., Gabrieli, J., Jenk, T. M., Osmont, D., and Schwikowski, M.: 19th Century Glacier Retreat in the Alps Preceded the Emergence of Industrial Black Carbon Deposition on High-Alpine Glaciers, *The Cryosphere*, 12, 3311–3331, <https://doi.org/10.5194/tc-12-3311-2018>, 2018a.
- Sigl, M., Abram, N. J., Gabrieli, J., Jenk, T. M., Osmont, D., and Schwikowski, M.: Black Carbon (rBC), Bismuth, Lead and Others from 1741 to 2015 AD from Colle Gnifetti Ice Core (Swiss/Italian Alps), <https://doi.org/10.1594/PANGAEA.894788>, 2018b.
- 790 Still, H., Odolinski, R., Bowman, M. H., Hulbe, C., and Prior, D. J.: Observing Glacier Dynamics with Low-Cost, Multi-GNSS Positioning in Victoria Land, Antarctica, *Journal of Glaciology*, pp. 1–18, <https://doi.org/10.1017/jog.2023.101>, 2023.
- Vaňková, I., Nicholls, K. W., Xie, S., Parizek, B. R., Voytenko, D., and Holland, D. M.: Depth-Dependent Artifacts Resulting from ApRES Signal Clipping, *Annals of Glaciology*, 61, 108–113, <https://doi.org/10.1017/aog.2020.56>, 2020.
- Vaňková, I., Cook, S., Winberry, J. P., Nicholls, K. W., and Galton-Fenzi, B. K.: Deriving Melt Rates at a Complex Ice Shelf Base Using in Situ Radar: Application to Totten Ice Shelf, *Geophysical Research Letters*, 48, e2021GL092692, <https://doi.org/10.1029/2021GL092692>, 2021.
- 795 Wagenbach, D., Bohleber, P., and Preunkert, S.: Cold, Alpine Ice Bodies Revisited: What May We Learn from Their Impurity and Isotope Content?, *Geografiska Annaler: Series A, Physical Geography*, 94, 245–263, <https://doi.org/10.1111/j.1468-0459.2012.00461.x>, 2012.
- Xu, B., Lang, S., Cui, X., Li, L., Liu, X., Guo, J., and Sun, B.: Focused Synthetic Aperture Radar Processing of Ice-Sounding Data Collected over East Antarctic Ice Sheet via Spatial-Correlation-Based Algorithm Using Fast Back Projection, *IEEE Transactions on Geoscience and Remote Sensing*, 60, 1–9, <https://doi.org/10.1109/TGRS.2022.3198432>, 2022.
- 800 Zeising, O., Steinhage, D., Nicholls, K. W., Corr, H. F. J., Stewart, C. L., and Humbert, A.: Basal Melt of the Southern Filchner Ice Shelf, Antarctica, *The Cryosphere*, 16, 1469–1482, <https://doi.org/10.5194/tc-16-1469-2022>, 2022.




Figure 5. Comparison of radargrams (a–d) across Colle Gnifetti and (e–f) upstream towards KCC. (a) Radar data of a impulse GPR (Konrad et al., 2013); (b) IRH slopes relative to the surface derived from the corrected phase of the mobile pRES data; (c, e) mobile pRES data before and (d, f) after LO-SAR processing. The CG03 and KCC ice core locations are marked by vertical black lines and the intersection points between the three profiles are denoted (A–C) and marked by black dashed lines. Red lines mark traced IRHs. In the upstream profile (e–f), the continuous tracing of deep IRHs is prevented by lower data quality and red dots only indicate traced IRHs in the intersecting profiles.

