



# Does stream remediation reduce phosphorus and sediment exports from agricultural catchments?

Lukas Hallberg<sup>1</sup>, Faruk Djodjic<sup>2</sup>, Magdalena Bieroza<sup>1</sup>

<sup>1</sup> Department of Soil and Environment, Swedish University of Agricultural Sciences, Uppsala, Box 7014, 750 07, Sweden

5 <sup>2</sup> Department of Aquatic Sciences and Assessment, Swedish University of Agricultural Sciences, Box 7050, 750 07, Uppsala, Sweden

*Correspondence to:* Lukas Hallberg (lukas.hallberg@slu.se)

10 **Abstract.** Agricultural headwater streams are important pathways for diffuse sediment and nutrient losses, requiring mitigation strategies beyond in-field measures to intercept the transport of pollutants to downstream freshwater resources. As such, floodplains can be constructed along existing agricultural streams and ditches to improve fluvial stability and promote deposition of sediments and particulate phosphorus. In this study, we evaluated 10 remediated agricultural streams in Sweden for their capacity to reduce sediment and particulate phosphorus export and investigated the interplay between fluvial processes and phosphorus dynamics. Remediated streams with different floodplain designs (either on one side or both sides of channel, with different width and elevation) were paired with upstream trapezoidal channels as controls. We used sedimentation plates to determine seasonal patterns in sediment deposition on channel beds and floodplains and monthly water quality monitoring. This was combined with continuous flow discharge measurements to examine suspended sediment and particulate phosphorus dynamics and reduction along reaches. Remediated streams with floodplains on both sides of the channel reduced particulate phosphorus concentrations and loads ( $-54 \mu\text{g L}^{-1}$ ,  $-0.21 \text{ kg ha}^{-1} \text{ yr}^{-1}$ ) along reaches, whereas increases occurred along streams with one-sided floodplains ( $27 \mu\text{g L}^{-1}$ ,  $0.09 \text{ kg ha}^{-1} \text{ yr}^{-1}$ ) and control streams ( $46.6 \mu\text{g L}^{-1}$ ). Sediment deposition in remediated streams was five times higher on channel beds compared to floodplains and there was no evident lateral distribution of sediments from channel to floodplains. There was no effect from sediment deposition on particulate phosphorus reduction, suggesting that bank stabilization was the key determinant for phosphorus mitigation in remediated streams, which can be realized with two-sided but not one-sided floodplains. Further, the overall narrow floodplain widths likely restricted reach-scale sediment deposition and its impact on P reductions. To fully understand remediated streams' potential for reductions in both nitrogen and different phosphorus species and avoid pollution swapping effects, there is a need to further investigate how floodplain design can be optimized to achieve a holistic solution towards improved stream water quality.



## 1 Introduction

30 Past and present inputs of bioavailable nutrients for agricultural production continue to negatively impact stream water quality and ecology across aquatic ecosystems globally (Sharpley et al., 2013; Smith, 2003). In particular, phosphorus (P) losses to surface waters play a key role in eutrophication since it often is the limiting element for algal and cyanobacterial growth in freshwater recipients (Correll, 1998). The transport of P from land to rivers and lakes is disproportionately influenced by headwater streams, representing entry points for sediments and nutrients to stream networks. Therefore, headwater streams' capacity for processing and removal of pollutants is critical for regulating downstream export (Wollheim et al., 2018). Headwaters in flat agricultural landscapes (< 2 % slopes) commonly comprise of straight and deep trapezoidal channels (Fig. 1b) that effectively drain excess water from fields and enable crop growth. However, their short water residence time and geomorphic instability also enhance downstream export of suspended sediments (SS) and associated P. Therefore, an improved understanding of the capacity for sediment and nutrient reductions within agricultural stream networks is critical, and increasingly so amidst a changing a climate with accelerated pollution to freshwaters (Ho et al., 2019; Ockenden et al., 2017).

High export of sediments and P from trapezoidal channels, either historically converted from natural streams or artificially introduced, results from altered transport capacity and an imbalance between catchment's supply and stream's transporting power (Magner et al., 2012; Simon and Rinaldi, 2006). Without recurring and costly maintenance, internal erosion from trapezoidal channels can therefore contribute with higher sediment and P loads compared to distal sediment sources in catchments. Closely interlinked with sediment conveyance in channels is the instream transport and storage of P, governed by fluvial processes (deposition/resuspension of sediment-bound P; Ballantine et al., 2009; Noe et al., 2019), redox processes (adsorption/desorption of reactive P to SS; Sandström et al., 2021) and geomorphic stability (streambank erosion; Fox et al., 2016). Channel bed sediments can store high amounts of P (Ballantine et al., 2009) and although deposition has been found to dominate in headwater reaches due to stream power limitation (Worrall et al., 2020), sediment-bound P becomes susceptible to remobilization during high flow events (Bowes et al., 2003). Streambank erosion due to bank failures in agricultural streams can also be a significant source of P export particularly in P-rich bank soils (Fox et al., 2016; Kronvang et al., 2013; Landemaine et al., 2015), but the efficacy of management strategies to counter this remains underexplored.

To reduce erosion and nutrient losses while maintaining drainage capacity, two-stage ditches with lateral floodplains excavated along existing channels have been tested as a stream remediation measure (Powell et al., 2007), with either two narrower or one single wider floodplain (Fig. 1). The purpose of two-stage designs is to establish a fluvial equilibrium by mimicking natural floodplain formation. Their design can support stable floodplains and banks, aid flood management and reduce the need for routine dredging and bank restoration (D'Ambrosio et al., 2015; Krider et al., 2017). During higher flows, stream power dissipates as water inundates vegetated floodplains, allowing for reductions in SS and P concentrations by sedimentation (Davis et al., 2015; Mahl et al., 2015), sediment adsorption of reactive P (Trentman et al., 2020) and nitrate removal through denitrification (Hallberg et al., 2022; Mahl et al., 2015; Speir et al., 2020). Reductions in SS and P concentrations and loads along remediated streams with a two-stage design are argued to be driven by lateral distribution of



sediments from inset channel onto floodplains during higher flows (Fig. 1), based on monitoring studies (D'Ambrosio et al., 2015; Krider et al., 2017; Mahl et al., 2015) and flume experiments (Bai and Zeng, 2019). To date, studies on sediment delivery in remediated streams have solely relied on either geometric survey data or grab water sampling, with emphasis on  
65 investigating its potential for improving geomorphic stability. Therefore, there is a need to explicitly link net P deposition rates and fluvial dynamics in field conditions with observed water quality impacts.

We measured net sedimentation rates and concentrations of P fractions in channel bed and floodplains of 10 remediated streams (Fig. 2a) with two-stage design (Fig. 1) with the aim to investigate spatial and temporal distribution of sediments and the effect on P export and long-term storage. Changes in stream water P concentrations along remediated streams and upstream  
70 trapezoidal control streams were compared to determine their reduction efficacy (Fig. 2b). Our objectives were to determine 1) if remediated streams with two-stage design can reduce SS and P export, 2) how floodplain designs (elevation and one- vs. two-sided floodplains) affects reduction capacity and 3) what factors of transport, erosion and deposition that control SS and P reductions. Two types of floodplain designs were compared: one-sided and two-sided floodplains along with a gradient in floodplain elevations and thus inundation frequencies.

## 75 2 Materials and methods

### 2.1 Site description

Ten study sites were selected with established two-stage ditches (referred to as remediated streams) in Central East (C1–5) and South Sweden (S6–S10; Fig. 2a). The study sites are located in low slope gradient and tile drained agricultural catchments, dominated by winter and spring sown cereal crops and ley grass. A control-impact design was used to compare  
80 remediated reaches (0.3 to 1.7 km reach lengths) with upstream, mostly trapezoidal reaches, hereafter referred to as control streams (see Fig. S6–9 for comparison of profiles). An exception is site C4 where the erosion of stream bank has created a natural floodplain (Fig. S7). Control stream reaches were selected with equivalent lengths (where this was possible) and similar channel slopes and agricultural land use % in sub-catchments (Table S1). For detailed monitoring design see Fig. S1–5. Site S7 was not paired with a control reach since the remediated stream originates from a wetland. Additionally, sites S7 and S8  
85 are nested in the same stream network (Fig 2a), with approximately 10 km stream length in between. Site C1 two tributaries draining to remediated stream reach.

In remediated streams, floodplains have been constructed either symmetrically on two sides (C1–3 and S8) or on one side (C4, S6–7 and S9–10) of the inset channel, site C5 being the exception with both designs along the reach. One-sided floodplains with double widths were constructed in streams where riparian obstructions (e.g., trees, boulders and high field elevation)  
90 restricted two-sided floodplain excavation. Floodplain elevations ranges between 0.25 and 0.96 m in relation to the lowest point of inset channel and the ratio of total flooded widths to channel top widths ranges between 1.3 and 2.9. Remediated streams were constructed between 2013 and 2019, with the purpose to prevent flooding of adjacent fields and to improve fluvial stability and downstream water quality (Brink et al., 2012; Wiström and Lindberg 2016; Hedin and Kivivuori 2015).



The sites are variable in their catchment characteristics and hydrology (Table 1). Central East catchments (C1–5) are generally characterized by lower agricultural land use density and higher clay content in soils compared to South catchments (S6–10). Overall, the remediated streams are dominated by base flows, with median discharge ranging between 0.01 to 0.32 m<sup>3</sup> s<sup>-1</sup>.

## 2.2 Sediment deposition rates: field sampling and analysis

To collect net sediment deposition rates, 0.16 m<sup>2</sup> square wooden fiber plates were installed in September 2020 and anchored with a 1 m metal rod through its center. Plates with a smooth surface coating were chosen to allow for resuspension of settled sediments but also to enable rapid *in situ* sediment collection. Sedimentation plates were installed on channel beds and on floodplains along each remediated ditch at the three locations upstream (US), mid (MS) and downstream (DS; Fig 2b), except at site S6 and S8–9, where no plates could be placed in channels due to impenetrable gravel and pebble bed substrates. Over the course of 21 months, deposited sediments were collected from the plates three times, approximately biannually (Fig. 2c) and with a total sample count of 41 (channel) and 73 (floodplains). To collect intact sediment samples from submerged plates in channels, a cylindrical frame was fitted onto plates before retrieval to prevent losses of sediments to water column. Before sampling, plates were lifted up from channel beds to dewater sediments and the sediments were then measured for depth to estimate the total volume. Sediments were only collected from the inner 0.04 m<sup>2</sup> square of the plates to avoid edge effects, and subsequently stored in airtight plastic bags. Sediment plates with high volumes (n = 32) were subsampled from the 0.04 m<sup>2</sup> square, with approximately 1 kg of fresh weight sediments collected after homogenization in field. The fresh weight per 0.04 m<sup>2</sup> of subsampled sediments was then estimated from the product of sediment volume on plate and bulk density of fresh sediments, measured per 100 ml. In case of missing sediment depth values in samples (n = 13), the depth was estimated based on a linear relationship between sediment fresh weight (kg m<sup>-2</sup>) and sediment depth (mm) of known samples (n = 90; r = 0.99, p < 0.01). All samples were oven dried at 105 °C to determine dry matter and then analyzed for TP with ICP-OES (Avio 200, PerkinElmer, USA). The TP content in sediments were normalized to deposition rates per area and six months as well as one year.

## 2.3 Composite sediment sampling and sequential P fractionation in sediments

Composite sediments, representing the integration of short- and long-term sediment deposition, were sampled in spring 2022 to determine P fractions. Sediments in channel bed and floodplains were sampled at US and DS for sequential P fractionation analysis (Fig. 2b, c). Sediments were sampled down to 5 cm depth with a trowel as 5 cm<sup>3</sup> cubes. At each channel location, five pseudo-replicates were sampled at 10 m distance along reaches and pooled into one sample. On floodplains, 10 pseudo-replicates were sampled at 5 m distance. Sediments were placed in airtight plastic bags and stored in coolers during field transportation and at 4 °C back at laboratory before dry matter was determined with oven drying at 105 °C.

To determine the forms of P present in composite sediment samples, a sequential P fractionation method was used, developed from Psenner and Puckso (1988) and Hupfer et al. (1995, 2009). The analyzed P species (as operationally defined)



were: water soluble P (H<sub>2</sub>O-P), redox-sensitive P adsorbed to iron and manganese (Fe-P), OH<sup>-</sup> exchangeable P adsorbed mainly to aluminum (Al-P), P bound in organic compounds (Org-P) and calcium-bound P (Ca-P). Here, H<sub>2</sub>O-P and Fe-P are also referred to as labile P and Al-P, Org-P and Ca-P as recalcitrant P. The residual non-reactive P after aforementioned fractionation (refractory P) was not determined; cumulative concentrations of analyzed P fractions are here referred to as TP.

130 Fresh sediment samples were sequentially extracted with Milli-Q water (H<sub>2</sub>O-P), buffered dithionate solution (Fe-P), NaOH (Al-P), NaOH after 30 min persulfate digestion at 120 °C, subtracted with NaOH (Org-P), and HCl (Ca-P). All extractions were analyzed for unfiltered soluble reactive P using the molybdenum blue method (Murphy and Riley, 1962). Concentrations of P fractions in sediments were calculated as g P kg<sup>-1</sup> DM for comparison with TP concentrations in newly deposited sediments.

#### 135 **2.4 Hydrological monitoring and stream power calculation**

Discharge was estimated by establishing stage-discharge rating curves from discharge measured manually at four to eight occasions and continuous water stage data from pressure sensors, as described in Hallberg et al. (2022). To minimize overestimation of high flows outside the range of flow measurements, out-of-range flows were estimated for all sites except C2 and C4, using the product of 1) polynomial regressions of stage-cross-section area and 2) logarithmic regressions of stage-  
140 mean velocity (Herschy, 2014). To determine the effect of floodplain inundation on sediment deposition, geometrical cross-section surveys were conducted and floodplain inundation events were subsequently estimated using stage data (Hallberg et al., 2022).

The power generated by a stream is a function of the amount of water that flows down a slope in a confined channel. To compare the stream power and its influence on bed sediments between streams of different sizes, the total stream power can  
145 be normalized by channel width to unit stream power ( $\omega$ ) at a given cross-section using:

$$\omega = \frac{\rho g Q S}{w} \quad (1)$$

where  $\rho$  is the density of the water (kg m<sup>-3</sup>),  $g$  is the acceleration due to gravity (m<sup>2</sup> s<sup>-1</sup>),  $Q$  is the flow discharge (m<sup>3</sup> s<sup>-1</sup>),  $S$  is the channel bed slope (%) and  $w$  is the channel width (m), here measured as the top width of the inset channel. With unit stream power, the force exerted per surface area and thus potential sediment transport can be derived, irrespective of system size. Unit  
150 stream power was calculated at point of floodplain overflow, using derived flow discharge and channel widths from geometrical survey, representing the maximum force of water when restricted to inset channel.

#### **2.5 Water quality sampling and vegetation survey**

Water grab samples were collected monthly between April 2020 to July 2022 to determine water chemistry at the four  
155 locations upstream control (TD), US, MS and DS (Fig. 2b). At site S9, sampling after June 2021 was excluded from analysis since the control stream was then converted into a remediated stream. Water samples were analyzed for TP (SS-EN ISO



6878:2005), with and without 0.45  $\mu\text{m}$  filtration, and suspended solids (SS; SS-EN 872:2005). Particulate P was calculated as the difference between unfiltered and filtered TP. In addition, vegetation cover was visually estimated on floodplains using three 1 m<sup>2</sup> (1 x 1 m) plots at each of the three locations US, MS and DS. Average percent vegetation cover was calculated from two surveys in May and June 2021.

## 2.6 Statistical data analysis

All statistical analyses were performed in R version 4.2.1 (RStudio Team, 2022). The packages hydrostats and leppott/ContDataQC were used to analyze the hydrological regimes. Base flow index (Gustard et al., 1992) were calculated using *baseflows* and flashiness index (Baker et al., 2004) using *RBlcalc*. Two outliers in TP and PP concentrations and one outlier in SS concentrations were removed from further analysis; these data points had exceptionally high concentrations (studentized residuals > 10, i.e., regression model residual divided by its adjusted standard error) and were measured in stagnant water during summer months, with minimal influence on total loads.

Annual loads of TP, PP and SS per ha were calculated at US and DS locations using flow-weighted mean concentration method (Elwan et al., 2018). Daily loads of TP at time of water sampling were also calculated by multiplying with daily flow. Changes in TP, PP and SS concentrations were calculated as the difference between US and TD (control streams) and the difference between DS and US (remediated streams), hence negative values represent reductions in concentrations along reaches. The sample distributions of changes in TP, PP and SS concentrations were non-normal, i.e., slightly right-skewed and with tails of outliers to both left and right. Therefore, when analyzing concentration data, we used the approach of non-parametric permutation of t-tests (R = 10,000), using *MKinfer* package. Permutation tests do not assume an underlying distribution and solely rely on the assumption of exchangeability, such as the absence of temporal autocorrelation (Good, 2000). To test for autocorrelation, concentration data was regressed against date and, if significant ( $p < 0.05$ ), it was excluded from subsequent permuted t-test. Differences in changes in TP, PP and SS concentrations between remediated and control streams as well as differences in P deposition rates across inundation classes and floodplain sides were tested with permuted unpaired two-tailed t-tests (*perm.t.test*). Seasonal differences in P deposition rates were tested with one-way ANOVA (*anova*, stats package).

The effects of P deposition and stream water P on labile P in composite sediments were quantified with Pearson correlation coefficients, using *cor.test* in stats package. No permutation of Pearson correlations was necessary due to met assumptions of homoscedasticity and normal distribution of residuals. To visualize the controls for P sedimentation, sample distribution of predictor variables (catchment and reach properties) was analyzed using scaled principal component analysis (PCA; *rda*) on two separate matrices for channels and floodplains, using the *Vegan* package. Vectors of P deposition rates were fitted to the PCAs using *envfit* with 10,000 permutations.



### 3 Results

#### 3.1 Suspended sediment and P reduction in stream water

Absolute concentrations of TP and PP in stream water were highly variable across both seasons and sites, peaking in  
190 summer months during low flows and ranging from below detection limit to 3940  $\mu\text{g TP L}^{-1}$  and 3557  $\mu\text{g PP L}^{-1}$ . Overall, the  
proportion of PP out of TP ranged from 28 % to 86 % but PP was the dominant form across seven sites (Table S2).  
Concentrations of SS ranged between  $< 1$  to 1200  $\text{mg SS L}^{-1}$  and were correlated to PP concentrations ( $r = 0.56$ ,  $p < 0.01$ ).  
Changes in TP concentrations along upstream control reaches correlated weakly with base flow index ( $r = 0.27$ ,  $p < 0.01$ ) and  
flashiness index ( $r = -0.25$ ,  $p < 0.01$ ), but there was no general correlation along remediated reaches and thus little influence  
195 of different hydrological regimes on P concentrations dynamics.

When grouping remediated streams by floodplain design, two-sided floodplains showed higher reductions in absolute TP  
and PP concentrations along reaches, compared to control streams (Fig. 3). Concentration changes along remediated streams  
with one-sided floodplains were not different compared to control streams. Correspondingly, there was a similar pattern to  
changes in TP and PP loads along remediated streams: two-sided floodplains retained on average  $0.17 \pm 0.26 \text{ kg TP ha}^{-1} \text{ yr}^{-1}$   
200 and  $0.22 \pm 0.21 \text{ kg PP ha}^{-1} \text{ yr}^{-1}$  while one-sided floodplains lost  $0.07 \pm 0.07 \text{ kg TP ha}^{-1} \text{ yr}^{-1}$  and  $0.09 \pm 0.10 \text{ kg PP ha}^{-1} \text{ yr}^{-1}$ .  
Reductions in daily TP loads with two-sided floodplains occurred during inundation events and not during base flows  
(permuted t-test,  $p < 0.01$ ), but inundation events did not affect TP loads along one-sided floodplains (permuted t-test,  $p =$   
 $0.78$ ). Incoming P loads also influenced changes in P loads along remediated streams; with two-sided floodplains, higher  
incoming loads led to reduced P loads but as for one-sided floodplains the opposite occurred (Fig. 4).

#### 205 3.2 Deposition of sediments and P in channels and on floodplains

Sediment deposition depth was five times higher on channel beds ( $86 \pm 72 \text{ mm yr}^{-1}$ ) compared to floodplains ( $16 \pm 23 \text{ mm}$   
 $\text{yr}^{-1}$ ) at sites C1–5, S7 and S10 (Fig. 5a), showing that sedimentation on floodplains, despite inundation frequencies up to 200  
days  $\text{yr}^{-1}$ , contributed little to the reaches' total sediment budgets. Deposition rates of P were correlated to sediment depth ( $r =$   
 $0.96$ ,  $p < 0.01$ ) and averaged  $29.9 \pm 29.3 \text{ g TP m}^{-2} \text{ yr}^{-1}$  on channel beds and  $7.0 \pm 10.4 \text{ g TP m}^{-2} \text{ yr}^{-1}$  on floodplains. Combined  
210 channel bed and floodplain deposition rates did not correlate with stream water P concentration changes, neither between  
remediated and control streams and irrespective of number of floodplain sides (Fig. S10). Ratios of deposited P:sediment mass  
did not differ between channel and floodplains (unpaired t-test,  $p = 0.83$ ). There was a seasonal pattern of higher P deposition  
rates on channel beds during the more hydrologically active winter and spring seasons, compared to summer and autumn  
(ANOVA,  $F_{2, 38} = 2.86$ ,  $p = 0.07$ ).

215 On channel beds, P deposition rates increased with lower unit stream power ( $r = -0.43$ ,  $p = 0.03$ ; Fig. S11), representing  
the maximum stream power per  $\text{m}^2$  bed surface area when flow was confined to the inset channel. Deposited P did not correlate  
with the average of stream water TP loads for each 6 month sampling period ( $r = -0.16$ ,  $p = 0.42$ ; Fig. S11) and neither with





the ratio of unit stream power:TP loads ( $r = 0.28$ ,  $p = 0.32$ ), indicating that unit stream power alone during lower flows was the primary driver for P sedimentation on channel beds.

220 On floodplains, P deposition rates fitted to a PCA of environmental predictors were primarily controlled by inundation frequency (Fig. S11b), in accordance with linear regression (Fig. 5c). Vegetation cover was also dependent on inundation frequency, but when excluding data points  $< 70$  inundation days  $\text{yr}^{-1}$ , there was an effect of higher P deposition rates with vegetation cover, independent of inundation (adj.  $R^2 = 0.05$ , Vegetation  $p = 0.05$ , Inundation  $p = 0.87$ ). In contrast to channel beds, unit stream power did not influence P deposition rates on floodplains. Grouping of sites by mean inundation frequency  
225 revealed that P deposition rates on floodplains increased with a magnitude of 1 during  $> 90$  inundation days  $\text{yr}^{-1}$  compared to  $< 20$  inundation days  $\text{yr}^{-1}$  (Fig. 5b). However, the process of lateral distribution from channel to floodplains could not be confirmed as P deposition rates on channel beds were not influenced by inundation.

### 3.3 Influence of sediment deposition on P stocks

There was an increase in TP content of composite sediments with construction age of remediated streams, both in channel  
230 beds ( $r = 0.48$ ,  $p = 0.04$ ) and floodplains ( $r = 0.54$ ,  $p = 0.02$ ), which was best explained by increases in Al-P fraction. Labile P fractions ( $\text{H}_2\text{O-P}$  and  $\text{Fe-P}$ ) accounted for on average 19 % of TP, hence the recalcitrant P fractions (Al-P, Org-P and Ca-P) were the dominant forms of P in sediments (Fig. S12). There was a trend in higher labile P content (paired t-test,  $p = 0.06$ ) in channel sediments compared to floodplain sediments but no differences for TP or recalcitrant P content (paired t-test, TP:  $p = 0.12$ , Recalcitrant P:  $p = 0.23$ ).

235 Total P in newly deposited sediments on plates was 1.6 times higher than in composite sediments. Deposited P further correlated with higher labile P content in composite sediments of channels but not floodplains (Fig. 6a). However, deposited P had no effect on recalcitrant P content, meaning that deposited P mainly contributed to the bioavailable P pool in channel sediments (Fig. 6b). Stream water concentrations of TP and PP predicted higher labile P content in channel and floodplain sediments equally well (Fig. 6c, d), indicating that P in water column supply bioavailable P on floodplains rather than sediment  
240 deposition.

## 4 Discussion

### 4.1 Floodplain design controls P reduction in remediated streams

The observed reductions in TP and PP concentrations and loads along remediated streams with two-sided floodplains show that this measure has the potential for improving downstream water quality when compared to control streams. The effect was  
245 exclusive to two-sided floodplain designs; one-sided floodplains did not differ from control streams, which implicates that a floodplain on only one side is unsuitable for P mitigation. Differences in P loads between the two floodplain designs were even more pronounced in sites with higher catchment P supply, where two-sided floodplains responded as active P sinks whereas one-sided floodplains behaved as passive conduits. Remediated streams with lower catchment P loads, due to less agricultural





land use, did not reduce P loads irrespective of floodplain design. Thus, to realize their P reduction potential, it is recommended  
250 to target implementation of remediated streams in areas with P loading exceeding  $0.25 \text{ kg P ha}^{-1} \text{ yr}^{-1}$ , corresponding to a  
considerable share of agricultural land within the contributing catchment.

Our results demonstrate that PP reductions can be substantial in these systems and lead to decreased TP loads, adding to  
previous body of research from the US (Davis et al., 2015; Kindervater and Steinman, 2019; Mahl et al., 2015). This is  
particularly important in clay-dominated catchments, associated with high PP delivery from soil erosion to streams (Sandström  
255 et al., 2020) as in site C2. The highest reductions in both TP (30 %) and PP (34 %) concentrations occurred along the remediated  
stream in site C2, characterized by silty clay loam soil texture. These reductions were in addition contributed by a perched  
culvert placed at the outlet, resulting in pre-dominantly stagnant water conditions at the lower end of the reach. In combination  
with little flow accumulation, this resulted in highly favourable conditions for P trapping, without the risk of bank overflow.  
Although the majority of the studied catchments were dominated by PP, site S8 which (in contrast to PP-dominated C2) was  
260 characterized by equal proportions of PP and reactive P and loam soil texture, also showed a tendency of reductions in both  
PP and TP. This implies that remediated streams can be effective across diverse catchments with contrasting soil textures and  
P forms, if the criteria of high P loading is met.

Our study confirmed that it was during inundation events that reductions in P loads occurred along streams with two-sided  
floodplains, consistent with previous research that have emphasized the importance of periodic floodplain inundation as master  
265 variable for reducing SS and P losses via flow dissipation (Bai and Zeng, 2019; D'Ambrosio et al., 2015; Krider et al., 2017).  
The lack of P reductions during inundation along streams with one-sided floodplains was likely connected to higher erosion  
from banks next to inset channels. These banks had higher slopes and resembled trapezoidal banks, compared to banks adjacent  
to floodplains (data not shown; Fig. 1). Higher bank slopes in loam and clay soils are known to reduce the cohesive strength  
and increase the vulnerability towards erosion of bank material to the water column (Thorne and Tovey, 1981). In one-sided  
270 designs, banks next to inset channels were also exposed to higher stream velocities; the greater water depth in channels  
compared to floodplains led to higher water velocities that exerted higher shear stress on banks adjacent to the channel.  
Accordingly, we suggest that these processes that drive bank erosion together can explain the lack of P reductions with one-  
sided floodplains, consistent with previous observations of increased scour and deposition with this floodplain design  
(D'Ambrosio et al., 2015).

#### 275 **4.2 Influence of sediment deposition on P dynamics and channel morphology**

Contrary to our initial assumption, higher P deposition rates on floodplains did not reduce P concentrations in stream water  
and could therefore not be confirmed as the sole process responsible for SS and P reduction in remediated streams. Instead,  
there was an average increase in TP concentrations of  $1.6 \mu\text{g TP L}^{-1}$  per deposited  $\text{g TP m}^{-2} \text{ yr}^{-1}$ , suggesting that floodplain  
deposition co-occurred with other processes contributing to P losses e.g., resuspension. Deposition rates of sediments and P  
280 on floodplains were controlled by inundation frequency and were substantially higher in this study compared to reported rates



from five US sites (0.5–13 mm sediment yr<sup>-1</sup>; D'Ambrosio et al., 2015) and three Swedish sites (0.04–1.2 g TP m<sup>-2</sup> yr<sup>-1</sup>; Lacoursière and Vought, 2020).

The relative importance of vegetation cover for trapping sediment-bound P on floodplains could only be assessed in locations with > 70 days of inundation yr<sup>-1</sup>, without collinearity between the two variables. Provision of water and nutrients from inundation events increases biomass growth on floodplains. It can therefore be assumed that sediment deposition is promoted directly by inundation, that provide sediments to be settled, and indirectly by its effect on vegetation that also traps sediments. However, the smooth surfaces of sediment plates that were used to measure deposition likely underestimated sediment trapping on densely vegetated floodplains.

Despite the relatively high sediment yields on floodplains, particularly at sites C4, S6 and S10, its lack of effect on P concentrations observed in our study contradicts previous findings, reporting floodplains as consistent P traps (D'Ambrosio et al., 2015; Davis et al., 2015; Mahl et al., 2015). An explanation for this could be that in our study sites, flooding to channel width ratios were significantly smaller than the recommended ratio of 3 to 5 (Powell et al., 2007) and therefore not contributing to sufficient reach-scale P deposition needed to impact P in the water column. The unexpected increase in P concentrations with floodplain deposition could be due to coinciding activation of erosion processes in either channel, banks, floodplains that override reductions from sedimentation. Total P losses during increasing floodplain deposition, were primarily explained by mobilization or increased transport of PP, accounting for 87 % of TP losses, and not reactive P. Overall, surface erosion in catchment soils did not drive stream sediment losses. Modelled maximum erosion rates of SS from surface runoff (Djodjic and Markensten, 2019) were generally low for all sites (10–50 kg ha<sup>-1</sup> yr<sup>-1</sup>), except for site S7 (100–250 kg ha<sup>-1</sup> yr<sup>-1</sup>), which likely contributed to SS and PP loading in that particular site. It is further possible that rapid resuspension of newly deposited sediments during higher flows lead to net losses of stream water P. As monitoring with sediment plates only accounted for net deposition, we could not quantify losses of sediments co-occurring with deposition.

Based on sediment deposition rates on plates, there was no indication of lateral sediment distribution from channel beds to floodplains in the seven sites (C1–5, S7, S10) where both channel beds and floodplains were evaluated. Instead, channel beds represented the dominant pool of sediment storage in remediated streams, independent of floodplain deposition rates. The ongoing aggradation on the channel beds indicate that these systems are still in fluvial disequilibrium, which is likely an indirect effect of floodplain inundation that also lower water velocities in channels. However, we could not show if this also occurred in control streams since no channel beds were monitored in these reaches. The lack of correlation between channel deposition and reductions in P concentrations in stream water could be explained by the bi-annual sediment sampling interval, being too coarse to capture periodic P reduction from sedimentation, which has been reported to occur during lower flow conditions (Bowes et al., 2003). In sites S6 and S8-9, where channel slopes ranged between 0.2 to 0.6 %, channel bed material was dominated by gravel and pebble substrates. Their impenetrable channel beds prevented plate installation and measurement of sedimentation rates but based on visual observations, no substantial deposition of fine sediments occurred over the study period. Hence these channels appeared to have sufficient stream power in relation to SS loads to transport SS, driven by their higher longitudinal channel slopes.



### 315 4.3 Variability in sediment P stock

The dominance of P deposition on channel beds compared to floodplains were also reflected in the higher labile P fractions (H<sub>2</sub>O-P and Fe-P) in composite channel bed sediments, which increased with P deposition rates. Although labile P fractions only accounted for 20 % of TP in composite sediments, Fe-P (the largest fraction of labile P) is sensitive to reducing conditions and subsequent re-release as reactive P into the water column (Jarvie et al., 2005). The contribution of labile P from sediment  
320 deposition can therefore have negative implications for P export, supplying the system with easily available P rather than providing a persistent P trap. Labile P in composite sediments also correlated with stream water P concentrations, but here the causation was less clear due to the reciprocity between sediment-bound P and stream water P; higher P concentrations in stream water can increase sediment P (deposition and sorption) while high sediment P also can lead to higher stream water P (resuspension and desorption).

325 The range of TP content in channel bed sediments was consistent with other agricultural streams in Sweden (0.07–1.57 g P kg<sup>-1</sup>, Lannergård et al., 2020; 0.35–1.85 g P kg<sup>-1</sup>, Sandström et al., 2021), indicating that remediated streams do not promote P enrichment in channel beds compared to streams without floodplains. However, the proportions of labile P fractions were overall lower in our study, either explained by less deposition of these fractions or a more rapid turnover of labile P. In a comparable system, sediments were also dominated by recalcitrant fractions that were shown to be stable over seasons  
330 (Kindervater and Steinman, 2019). The increase in Al-P with construction age was partly explained by higher clay content in catchment soils, which often are rich in Al silicates and hydroxides that increase the sorption of P to these surfaces (Gérard, 2016). However, the effect on TP with construction age was independent from clay content, suggesting a true accumulation of P in sediments over time in both channel and floodplain sediments. This post-construction maturation process indicate a system reset to low P content in sediments following construction, as previously shown for denitrification and microbial respiration  
335 rates in floodplain sediments (Speir et al., 2020).

The higher vegetation coverage on floodplains compared to channel beds was not reflected in higher organic P fraction in sediments. Although soil organic carbon have been found to accumulate more over time in floodplain sediments, compared to channel sediments (Hallberg et al., 2022; Speir et al., 2020), the lack of increase in organic P in floodplain sediments with  
340 construction age suggests that the build-up of organic P forms, despite presence of vegetation, is slow and require more time than 10 years to occur. In this study, P in vegetation biomass was not considered and although it could contribute as a seasonally active P sink, Kindervater and Steinman (2019) reported that channel and floodplain sediments on average held 18 times more P mass than biomass on reach-scale.

### 4.4 Floodplain management towards P reduction and fluvial equilibrium

Currently in Sweden, the recommended dimensions of remediated streams with two-stage design (1 km length, 3–5  
345 flooding to channel width ratio) are solely based on hydrology and do not take into account impact on sediment or nutrient reduction (Lindmark et al., 2013; Powell et al., 2007). Moreover, subsidies from Swedish authorities compensate for the stream



length when constructing remediated streams and there is no mechanism for incentivizing the implementation of wider floodplains, resulting in narrower than recommended widths in remediated streams. We suggest that wider floodplains and shorter lengths can have larger effects on P reductions by sedimentation, improving cost-efficiency while maintaining the same total area. It is therefore necessary to also evaluate this within a modelling framework that can isolate a range of dimensions from other confounding, site-specific factors.

A one-sided floodplain design is sometimes preferred among landowners when constructing floodplains due to lower cost, easier implementation and future maintenance accessibility, especially in locations where riparian obstructions (e.g., trees, boulders and high bank elevation) inhibit two-sided design. However, our results show clearly that this design is insufficient to enhance P reductions compared to control streams and therefore should be avoided. Instead, priority should be given to establish two-sided floodplains in critical source areas with high P loading, where riparian conditions as well as channel slope allow.

Reductions in P loads explicitly occurred during inundation events, but there was no correlation between P reductions, either in concentrations or loads, and annual inundation frequencies. Since higher inundation frequency (provided by lower floodplain elevations) increased P deposition, it is possible that lower and wider floodplains can increase reach-scale P trapping and thereby reduce P exports. However, lower floodplains can be exposed to higher shear stress and risk of toe erosion of floodplains that can explain the lack of observed P reductions with deposition. When choosing the optimal floodplain elevation, multiple pollutants (e.g., nitrogen; Hallberg et al, 2022) should be considered to avoid potential pollution swapping (Bierozza et al., 2019).

Combining floodplains with partial damming as in site C2, can lead to higher reductions in SS and P concentrations. Thus, raising culverts or installing low-grade weirs can complement remediated streams (Kröger et al., 2015). The increased bankfull volume with constructed floodplains reduces the risk of flooding when restricting outflows, however, hydraulic calculations should be made to ensure that large flood volumes are confined within the bankfull volume when installing impoundments.

Sediment accumulation on channel beds is widely perceived as negative by landowners, requiring routine channel dredging to avoid drainage impairment and to reduce the risk of flooding. However, in the absence of maintenance activities, natural formation of floodplains in agricultural streams have been observed to develop from sediment deposition in channels, facilitated by over-widened channels that limit stream power and bed load transport (Jayakaran and Ward, 2007; Landwehr and Rhoads, 2003). As such, the predominant accumulation of channel bed sediments in our studied sites could indicate that there is an ongoing adjustment towards floodplain formation, in addition to already existing floodplains. The room for allowing channel sedimentation before it puts conveyance capacity at risk is also higher in remediated streams and could motivate abstention from dredging to allow stabilization of fluvial equilibrium and adjustments of floodplains to the streams' fluvial conditions. Enhancing this potential by providing more space by designing wider floodplains is therefore important to effectively reduce P exports. As future climate will bring higher P exports and frequencies of flooding and drought, remediation of agricultural streams can therefore bring better flood and drought control together with enhanced water purification.



## 380 5 Conclusion

Human pressures on freshwater resources, exacerbated by climate change, require urgent adjustment in agricultural streams to improve their capacity to transport and process large water and pollution fluxes. To date, nutrient mitigation strategies focus largely on in-field and point measures (e.g., soil management and wetlands), ignoring the enormous potential of headwater agricultural streams and their corridors as interfaces for reducing multiple pollutants (SS, N and P) while also providing flood and drought control. Evaluating the capacity for stream remediation in agricultural landscapes to reduce SS and P export, as carried out in this study, is therefore a critical step for improving our understanding of how agricultural streams can be modified to reduce downstream water quality impacts.

In this study, we demonstrated that remediated streams reduce stream water P concentrations and loads while simultaneously increasing water conveyance capacity. Reductions in P were controlled by floodplain design, as floodplains constructed laterally on both sides reduced P exports during inundation events, compared to one-sided floodplains and control streams (trapezoidal channels). Higher catchment supply of P, driven by agricultural land use, also increased P reduction capacity in two-sided remediated streams. By linking fluvial dynamics with P storage and water quality impacts, our results showed that with narrow floodplains, PP reductions were controlled rather by protection against erosion than promotion of deposition. In this sense, remediated streams operate on a different principle than flow-through wetlands, with the focus on reducing erosion and near-stream P inputs rather than actively trapping upstream-derived sediments. However, by extending the width of floodplains, the importance of P deposition for PP reductions is expected to increase. The fact that heavily impacted catchments in this study delivered high loads of N and P, as is typical in agricultural streams, underscore the need for adopting management strategies that can maximize reductions of multiple pollutants and minimize the risk for pollution swapping. Although the optimal design for PP reduction also has the potential for promoting N removal, there is a further need for understanding the effect on reactive P dynamics when promoting high inundation frequencies and deposition of sediments with labile P.

### Data availability

The water and sediment chemistry and hydrology measurements from the studied sites are provided as Supplement.

### Supplement

405 The supplement related to this article is available online at: *DOI to be retrieved from HESS*



### Author contribution

Lukas Hallberg: Conceptualization, Methodology, Data curation, Formal analysis, Visualization, Writing – original draft, Writing - review and editing. Faruk Djodjic: Methodology, Formal analysis, Writing - review and editing. Magdalena Bieroza: Conceptualization, Methodology, Formal analysis, Writing - review and editing, funding acquisition.

### 410 Competing interests

The authors declare that they have no conflict of interest.

### Acknowledgements

This project was funded by Svenska Forskningsrådet Formas (2018-00890), Havs- och vattenmyndigheten (3280-2019) and Oscar och Lili Lamms Minne (DO2019-0021) awarded to M. Bieroza. The authors would like to thank private landowners  
415 and stakeholders in the study catchments for their help with collecting water and sediments samples and providing access to field sites, especially Christoffer Bonthron from Tullstorpsåprojektet, Anuschka Heeb from Lovang AB and Dennis Wiström from Västerviks kommun. We would like also to thank Sheryl Illao Åström for conducting the geometrical surveys and compiling GPS data and Emma Ryding for collecting sediments and performing sequential P fractionation.

### References

- 420 Bai, Y., and Zeng, Y.: Lateral distribution of sediment and phosphorus in a two-stage ditch with partial emergent vegetation on the floodplain. *Environmental Science and Pollution Research*, 26(28), 29351–29365, doi:10.1007/s11356-019-06118-6, 2019.
- Baker, D. B., Richards, R. P., Loftus, T. T., and Kramer, J. W.: A New Flashiness Index: Characteristics and Applications to Midwestern Rivers and Streams. *Journal of the American Water Resources Association*, 40(2), 503–522, doi:10.1111/j.1752-  
425 1688.2004.tb01046.x, 2004.
- Ballantine, D. J., Walling, D. E., Collins, A. L., and Leeks, G. J. L.: The content and storage of phosphorus in fine-grained channel bed sediment in contrasting lowland agricultural catchments in the UK. *Geoderma*, 151(3), 141–149, doi:10.1016/j.geoderma.2009.03.021, 2009.
- Bowes, M. J., House, W. A., and Hodgkinson, R. A.: Phosphorus dynamics along a river continuum. *Science of The Total Environment*, 313(1), 199–212, doi:10.1016/S0048-9697(03)00260-2, 2003.  
430
- Bieroza, M., Bergström, L., Ulén, B., Djodjic, F., Tonderski, K., Heeb, A., Svensson, J., and Malgeryd, J.: Hydrologic extremes and legacy sources can override efforts to mitigate nutrient and sediment losses at the catchment scale. *Journal of Environmental Quality*, 48(5), 1314–1324, doi:10.2134/jeq2019.02.0063, 2019.



- Brink, K., Juhlin, L., and Kuhlau, Å.: Svärtaåprojektet. 2010-2012: Erfarenheter av praktiskt åtgärdsarbete i samarbete med  
435 lantbrukare i Svärtaåns avrinningsområde. Länsstyrelsen Södermanlands län, Rapport 2013:23, 1-44, 2012.
- Correll, D. L.: The Role of Phosphorus in the Eutrophication of Receiving Waters: A Review. *Journal of Environmental Quality*, 27(2), 261–266, doi:10.2134/jeq1998.00472425002700020004x, 1998.
- D’Ambrosio, J. L., Ward, A. D., and Witter, J. D.: Evaluating Geomorphic Change in Constructed Two-Stage Ditches. *Journal of the American Water Resources Association*, 51(4), 910–922, doi:10.1111/1752-1688.12334, 2015.
- 440 Davis, R. T., Tank, J. L., Mahl, U. H., Winikoff, S. G., and Roley, S. S.: The Influence of Two-Stage Ditches with Constructed Floodplains on Water Column Nutrients and Sediments in Agricultural Streams. *Journal of the American Water Resources Association*, 51(4), 941–955, doi:10.1111/1752-1688.12341, 2015.
- Djordjic, F., and Markensten, H.: From single fields to river basins: Identification of critical source areas for erosion and phosphorus losses at high resolution. *Ambio*, 48(10), 1129–1142, doi:10.1007/s13280-018-1134-8, 2019.
- 445 Elwan, A., Singh, R., Patterson, M., Roygard, J., Horne, D., Clothier, B., and Jones, G.: Influence of sampling frequency and load calculation methods on quantification of annual river nutrient and suspended solids loads. *Environmental Monitoring and Assessment*, 190(2), 78, doi:10.1007/s10661-017-6444-y, 2018.
- Fox, G. A., Purvis, R. A., and Penn, C. J.: Streambanks: A net source of sediment and phosphorus to streams and rivers. *Journal of Environmental Management*, 181, 602–614, doi:10.1016/j.jenvman.2016.06.071, 2016.
- 450 Gérard, F.: Clay minerals, iron/aluminum oxides, and their contribution to phosphate sorption in soils—A myth revisited. *Geoderma*, 262, 213–226, doi:10.1016/j.geoderma.2015.08.036, 2016.
- Good, P.: *Permutation tests: a practical guide to resampling methods for testing hypotheses*. Springer Science & Business Media, 2nd edition, 2000.
- Gustard, A., Bullock, A., and Dixon, J. M.: *Low flow estimation in the United Kingdom*. Institute of Hydrology, 1992.
- 455 Hallberg, L., Hallin, S., and Bieroza, M.: Catchment controls of denitrification and nitrous oxide production rates in headwater remediated agricultural streams. *Science of The Total Environment*, 838(3), 156513, doi:10.1016/j.scitotenv.2022.156513, 2022.
- Hedin, J. and Kivivuori, H.: Tullstorpsåprojektet. Utvärdering. Tvåstegsdiken och kantavplaning sträckan Stora Markie-Stävesjö Ålholmens dikningsföretag. Naturvårdsingenjörerna AB, Rapport,1-22, 2015.
- 460 Herschy, R. W.: *Streamflow Measurement* (3rd ed.). CRC Press, doi:10.1201/9781482265880, 2014.
- Ho, J. C., Michalak, A. M., and Pahlevan, N.: Widespread global increase in intense lake phytoplankton blooms since the 1980s. *Nature*, 574(7780), Article 7780, doi:10.1038/s41586-019-1648-7, 2019.
- Hupfer, M., Gächter, R., and Giovanoli, R.: Transformation of phosphorus species in settling seston and during early sediment diagenesis. *Aquatic Sciences*, 57(4), 305–324, doi:10.1007/BF00878395, 1995.
- 465 Hupfer, M., Zak, D., Roßberg, R., Herzog, C., and Pöthig, R.: Evaluation of a well-established sequential phosphorus fractionation technique for use in calcite-rich lake sediments: Identification and prevention of artifacts due to apatite formation. *Limnology and Oceanography: Methods*, 7(6), 399–410, doi:10.4319/lom.2009.7.399, 2009.





- Jarvie, H. P., Jürgens, M. D., Williams, R. J., Neal, C., Davies, J. J. L., Barrett, C., and White, J.: Role of river bed sediments as sources and sinks of phosphorus across two major eutrophic UK river basins: The Hampshire Avon and Herefordshire Wye. *Journal of Hydrology*, 304(1), 51–74, doi:10.1016/j.jhydrol.2004.10.002, 2005.
- Jayakaran, A. D., and Ward, A. D.: Geometry of inset channels and the sediment composition of fluvial benches in agricultural drainage systems in Ohio. *Journal of Soil and Water Conservation*, 62(4), 296–307, 2007.
- Kindervater, E., and Steinman, A. D.: Two-Stage Agricultural Ditch Sediments Act as Phosphorus Sinks in West Michigan. *Journal of the American Water Resources Association*, 55(5), 1183–1195, doi:10.1111/1752-1688.12763, 2019.
- 475 Krider, L., Magner, J., Hansen, B., Wilson, B., Kramer, G., Peterson, J., and Nieber, J.: Improvements in Fluvial Stability Associated with Two-Stage Ditch Construction in Mower County, Minnesota. *Journal of the American Water Resources Association*, 53(4), 886–902, doi:10.1111/1752-1688.12541, 2017.
- Kröger, R., Prince Czarnecki, J. M., Tank, J. L., Christopher, S. F., and Witter, J. D.: Implementing Innovative Drainage Management Practices in the Mississippi River Basin to Enhance Nutrient Reductions. *Journal of the American Water Resources Association*, 51(4), 1020–1028, doi:10.1111/1752-1688.12342, 2015.
- 480 Kronvang, B., Andersen, H. E., Larsen, S. E., and Audet, J.: Importance of bank erosion for sediment input, storage and export at the catchment scale. *Journal of Soils and Sediments*, 13(1), 230–241, doi:10.1007/s11368-012-0597-7, 2013.
- Lacoursière, J. O. and Vought, L. B.: Field Evaluation of Two-Stage Channels Impact on Local Biodiversity and Nutrient Retention Potential. *Environmental Awareness International*, Report Number: 2020:06, 2020.
- 485 Landemaine, V., Gay, A., Cerdan, O., Salvador-Blanes, S., and Rodrigues, S.: Morphological evolution of a rural headwater stream after channelisation. *Geomorphology*, 230, 125–137, doi:10.1016/j.geomorph.2014.11.011, 2015.
- Landwehr, K., and Rhoads, B. L.: Depositional response of a headwater stream to channelization, East Central Illinois, USA. *River Research and Applications*, 19(1), 77–100, doi:10.1002/rra.699, 2003.
- Lannergård, E. E., Agstam-Norlin, O., Huser, B. J., Sandström, S., Rakovic, J., and Futter, M. N.: New Insights Into Legacy Phosphorus From Fractionation of Streambed Sediment. *Journal of Geophysical Research: Biogeosciences*, 125(9), e2020JG005763, doi:10.1029/2020JG005763, 2020.
- Lindmark, P., Karlsson, L. and Nordlund, J.: Tvåstegsdiken - ett steg i rätt riktning?. *Jordbruksverket, Rapport 2013:15*, 2013.
- 495 Magner, J., Hansen, B., Sundby, T., Kramer, G., Wilson, B., and Nieber, J.: Channel evolution of Des Moines Lobe till drainage ditches in southern Minnesota (USA). *Environmental Earth Sciences*, 8(67), 2359–2369, doi:10.1007/s12665-012-1682-3, 2012.
- Mahl, U. H., Tank, J. L., Roley, S. S., and Davis, R. T.: Two-Stage Ditch Floodplains Enhance N-Removal Capacity and Reduce Turbidity and Dissolved P in Agricultural Streams. *Journal of the American Water Resources Association*, 51(4), 923–940, doi:10.1111/1752-1688.12340, 2015.
- Murphy, J., and Riley, J. P.: A modified single solution method for the determination of phosphate in natural waters. *Analytica Chimica Acta*, 27, 31–36, doi:10.1016/S0003-2670(00)88444-5, 1962.
- 500



- Noe, G. B., Boomer, K., Gillespie, J. L., Hupp, C. R., Martin-Alciati, M., Floro, K., Schenk, E. R., Jacobs, A., and Strano, S.: The effects of restored hydrologic connectivity on floodplain trapping vs. Release of phosphorus, nitrogen, and sediment along the Pocomoke River, Maryland USA. *Ecological Engineering*, 138, 334–352, doi:10.1016/j.ecoleng.2019.08.002, 2019.
- Ockenden, M. C., Hollaway, M. J., Beven, K. J., Collins, A. L., Evans, R., Falloon, P. D., Forber, K. J., Hiscock, K. M.,  
505 Kahana, R., Macleod, C. J. A., Tych, W., Villamizar, M. L., Wearing, C., Withers, P. J. A., Zhou, J. G., Barker, P. A., Burke, S., Freer, J. E., Johnes, P. J., ... Haygarth, P. M.: Major agricultural changes required to mitigate phosphorus losses under climate change. *Nature Communications*, 8(1), 161, doi:10.1038/s41467-017-00232-0, 2017.
- Powell, G. E., Ward, A. D., Mecklenburg, D. E., and Jayakaran, A. D.: Two-stage channel systems: Part 1, a practical approach for sizing agricultural ditches. *Journal of Soil and Water Conservation*, 10, 2007.
- 510 Psenner, R., and Puckso, R.: Phosphorus fractionation: Advantages and limits of the method for the study of sediment P origins and interactions. *Arch Hydrobiol*, 30, 43–59, 1988.
- RStudio Team: RStudio: Integrated Development for R: <http://www.rstudio.com/>, last access: 25 October 2022.
- Sandström, S., Futter, M. N., Kyllmar, K., Bishop, K., O’Connell, D. W., and Djodjic, F.: Particulate phosphorus and suspended solids losses from small agricultural catchments: Links to stream and catchment characteristics. *Science of The*  
515 *Total Environment*, 711, 134616, doi:10.1016/j.scitotenv.2019.134616, 2020.
- Sandström, S., Futter, M. N., O’Connell, D. W., Lannergård, E. E., Rakovic, J., Kyllmar, K., Gill, L. W., and Djodjic, F.: Variability in fluvial suspended and streambed sediment phosphorus fractions among small agricultural streams. *Journal of Environmental Quality*, 50(3), 612–626, doi:10.1002/jeq2.20210, 2021.
- Sharpley, A., Jarvie, H. P., Buda, A., May, L., Spears, B., and Kleinman, P.: Phosphorus Legacy: Overcoming the Effects of  
520 Past Management Practices to Mitigate Future Water Quality Impairment. *Journal of Environmental Quality*, 42(5), 1308–1326, doi:10.2134/jeq2013.03.0098, 2013.
- Simon, A., and Rinaldi, M.: Disturbance, stream incision, and channel evolution: The roles of excess transport capacity and boundary materials in controlling channel response. *Geomorphology*, 79(3), 361–383, doi:10.1016/j.geomorph.2006.06.037, 2006.
- 525 Smith, V. H.: Eutrophication of freshwater and coastal marine ecosystems a global problem. *Environmental Science and Pollution Research*, 10(2), 126–139, doi:10.1065/espr2002.12.142, 2003.
- Speir, S. L., Tank, J. L., and Mahl, U. H.: Quantifying denitrification following floodplain restoration via the two-stage ditch in an agricultural watershed. *Ecological Engineering*, 155, 105945, doi:10.1016/j.ecoleng.2020.105945, 2020.
- Thorne, C. R., and Tovey, N. K.: Stability of composite river banks. *Earth Surface Processes and Landforms*, 6(5), 469–484,  
530 doi:10.1002/esp.3290060507, 1981.
- Trentman, M. T., Tank, J. L., Jones, S. E., McMillan, S. K., and Royer, T. V.: Seasonal evaluation of biotic and abiotic factors suggests phosphorus retention in constructed floodplains in three agricultural streams. *Science of The Total Environment*, 729, 138744, doi:10.1016/j.scitotenv.2020.138744, 2020.




535 Wiström, D. and Lindberg, G.: Havsmiljö Gamlebyviken del 3 Övergödningen som en resurs - Slutrapport. Västerviks kommun. 1-29, 2016.

Wollheim, W. M., Bernal, S., Burns, D. A., Czuba, J. A., Driscoll, C. T., Hansen, A. T., Hensley, R. T., Hosen, J. D., Inamdar, S., Kaushal, S. S., Koenig, L. E., Lu, Y. H., Marzadri, A., Raymond, P. A., Scott, D., Stewart, R. J., Vidon, P. G., and Wohl, E.: River network saturation concept: Factors influencing the balance of biogeochemical supply and demand of river networks. *Biogeochemistry*, 141(3), 503–521, doi:10.1007/s10533-018-0488-0, 2018.


540 Worrall, F., Burt, T. P., Hancock, G. R., Howden, N. J. K., and Wainwright, J.: The problem of underpowered rivers. *Earth Surface Processes and Landforms*, 45(15), 3869–3878, doi:10.1002/esp.5007, 2020.

545



550

**Fig. 1. Conceptual model of fluvial processes that determine particulate phosphorus (PP) export in remediated vs. control streams. Deposition of PP occur on channel beds predominantly during lower flows when transport capacity are lower than sediment delivery. During inundation, PP deposition dominates on floodplains, due to lower water velocities. In two-sided floodplains, streambanks are stabilized during higher flows due to their lower slopes and lower shear stress from water forces compared to the inset channel. In one-sided designs, one streambank is steeper and exposed to higher water velocities in the channel, resulting in higher mobilization and transport of PP.**



555 **Fig. 2.** Location of the 10 catchments with remediated streams in Central East (C1–C5) and South Sweden (S6–S10). **b)** Control-  
 impact monitoring design. Sediment samples and water grab samples were collected at start, middle and end of remediated reaches and water grab samples were also collected at start of control reaches. Water stage sensors were placed at start and end of remediated reaches. **c)** Sampling scheme over time of sediments deposited on plates and composite sediments for sequential P fractionation. Land use maps: ©Lantmäteriet.

560

565




570

**Table 1. Characteristics of catchment, hydrology, ditch geometry of remediated streams. Sites are ordered from North to South. Flow discharge and floodplain inundation were recorded in April 2020 to June 2022. Discharge in site C3 was recorded between 2018 and 2022, interrupted between December to March each year. Ditch and floodplains geometry were measured in March and April 2021 with a GPS levelling device (E600 GNSS Receiver, E-survey, China).**


Site	County	Catchment properties				Hydrology					Year of construction	Ditch geometry					
		Area (km <sup>2</sup> )	Precipitation (mm)*	Soil texture	Agricultural land use (%)	Q50 (m <sup>3</sup> s <sup>-1</sup> )	Baseflow Index (BFI)	Flashiness Index (RBI)	Unit stream power** (W/m <sup>2</sup> )	Floodplain inundation (day yr <sup>-1</sup> )		Two-stage length (m)	Floodplain Height (m)	Floodplain width (m)	Flooding-Channel ratio	Channel slope (%)	Floodplain design
<i>Central East</i>																	
C1	Södermanland	9.75	594	Silty clay	15	0.02	0.80	0.43	5	107	2012	340	0.55	3.1	1.6	0.04	2-sided
C2	Södermanland	7.91	594	Silty clay loam	27	0.03	0.93	0.13	17	17	2012	730	0.96	3.5	2.2	0.04	2-sided
C3	Östergötland	6.63	551	Clay loam	70	0.01	0.82	0.30	42	17	2014	1500	0.53	3.2	2.5	0.30	2-sided
C4	Kalmar	45.5	627	Clay loam	16	0.32	0.91	0.12	130	187	2019	320	0.65	1.7	1.3	0.10	1-sided
C5	Kalmar	16.3	627	Clay loam	38	0.06	0.83	0.30	110	53	2012	780	0.65	1.4	1.5	0.14	1-sided/2-sided
<i>South</i>																	
S6	Skåne	22.7	707	Loam	77	0.09	0.83	0.35	142	100	2016	400	0.48	5.7	2.9	0.17	1-sided
S7	Skåne	10.8	569	Loam	81	0.04	0.81	0.30	25	159	2013	1960	0.55/0.25	4.0	2.8	0.09	1-sided
S8	Skåne	42.4	569	Loam	81	0.22	0.86	0.23	1088	93	2013	1770	0.48	6.4	2.4	0.47	2-sided
S9	Skåne	31	569	Loam	86	0.11	0.90	0.09	1512	6	2019	630	0.71	4.6	2.3	0.44	1-sided
S10	Halland	16.4	823	Sandy loam	58	0.20	0.89	0.20	104	123	2014	1760	0.34	2.8	2.2	0.09	1-sided

\*Mean annual rainfall 2016-2021 (<https://www.smhi.se/data/meteorologi/nederbord>).

\*\*Unit stream power at the point of inset channel overflow




575 Fig. 3. Changes in TP, PP and SS concentrations (note log<sub>10</sub> y-axis) between start and end of control streams (red boxes) and start  
 and end of remediated streams (blue boxes) from April 2020 to June 2022. Changes in concentrations are shown a, c, e) by each site  
 (C1–5 and S6–10) and b, d, f) sites grouped by number of floodplain sides along inset channel. When comparing floodplain sides,  
 two sites were excluded due to lack of control stream (S7) and a combination of one- and two-sided floodplains along the reach (C5).  
 P-values of permuted unpaired t-tests are shown within the panels. Permuted t-test of TP for 2-sided floodplains is not applicable  
 580 due to temporal autocorrelation.




**Fig. 4.** Changes in a) TP and b) PP loads along remediated streams compared with P load supply loads at start of remediated streams. Remediated streams grouped as one-sided (yellow circles), one- and two-sided (gray circles) and two-sided floodplains (white circles). Size of circles denote average floodplain inundation days yr<sup>-1</sup>. Site C2 was excluded, due to lack of flow data at downstream location.





585

Fig. 5. a) Sediment deposition rate in depth on channel beds and floodplains across sites (C1–5 and S6–10) from sediment plates deployed between September 2021 and May 2022. b) Annual P deposition rate grouped by floodplain inundation frequency classes and c) biannual P deposition rate regressed against inundation frequency during each 6 month sampling occasion. P-values of permuted unpaired t-tests and permuted Pearson correlations are shown within panels.



590

595

Fig. 6. Linear regressions between deposited sediment TP and composite sediment a) labile P and b) recalcitrant P in channel sediments (blue circles) and floodplain sediments (red circles). Linear regressions of composite sediment labile P by c) stream water TP concentrations and d) stream water PP concentrations. Deposited sediments were collected between September 2021 to May 2022, composite sediments sampled in spring 2022 and monthly water grab samples from April 2020 to July 2022. Zero values from plates without deposited sediments were removed from analysis. Labile P represent P fractions H<sub>2</sub>O-P and Fe-P. Pearson r and p-values are shown within each panel and error bars show standard deviations of stream water P.