



Impact-based flood forecasting in the Greater Horn of Africa

Lorenzo Alfieri¹, Andrea Libertino¹, Lorenzo Campo¹, Francesco Dottori¹, Simone Gabellani¹, Tatiana Ghizzoni¹, Alessandro Masoero¹, Lauro Rossi¹, Roberto Rudari¹, Nicola Testa¹, Eva Trasforini¹, Ahmed Amdihun², Jully Ouma^{2,3}, Luca Rossi³, Yves Trambly⁴, Huan Wu^{5,6}, and Marco Massabò¹

¹ CIMA Research Foundation, University Campus of Savona, Via Armando Magliotto, 2, 17100 Savona - Italy

² IGAD Climate Prediction and Applications Centre (ICPAC), Nairobi, Kenya

³ United Nations Office for Disaster Risk Reduction (UNDRR), Regional Office for Africa, Nairobi, Kenya

⁴ HSM, University of Montpellier, CNRS, IRD, Montpellier, France

⁵ Southern Marine Science and Engineering Laboratory (Zhuhai), School of Atmospheric Sciences, Sun Yat-sen University, Zhuhai, 519082, China

⁶ Guangdong Province Key Laboratory for Climate Change and Natural Disaster Studies, Sun Yat-sen University, Guangzhou, 510275, China

Correspondence to: Lorenzo Alfieri (Lorenzo.Alfieri@cimafoundation.org)

20

Abstract. Every year Africa is hit by extreme floods which, combined with high levels of vulnerability and increasing population exposure, often result in humanitarian crises and population displacement. Impact-based forecasting and early warning for natural hazards is recognized as a step forward in disaster risk reduction, thanks to its focus on people, livelihoods and assets at risk. Yet, the majority of the African population is not covered by any sort of early warning system. This article describes the setup of Flood-PROOFS East Africa, an impact-based riverine flood forecasting and early warning system for the Greater Horn of Africa (GHA), with a forecast range of 5 days. The system is based on a modeling cascade relying on distributed hydrological simulations forced by ensemble weather forecasts, link to inundation maps for specific return period, and application of a risk assessment framework to estimate population and assets exposed to upcoming floods. The system is operational and supports the African Union Commission and the IGAD Disaster Operation Center in the daily monitoring and early warning from hydro-meteorological disasters in Eastern Africa. Results show a first evaluation of the hydrological reanalysis at 78 river gauging stations and a semi-quantitative assessment of the impact forecasts for the catastrophic floods in Sudan and in the Nile River Basin in Summer 2020.

35

Keywords

distributed hydrological modeling, model calibration, flood forecasting, early warning, inundation maps, impact assessment, Eastern Africa



5

1 Introduction

40 Globally, between 2000 and 2019 disasters caused approximately US\$ 2.97 trillion in economic losses, claimed
1.23 million lives, and affected a total of over 4 billion people (UNDRR and CRED, 2020). Out of those, floods
hold the largest share, with 1.65 billion people affected, on average over 82 million per year. While the
economic impacts are higher in absolute terms in high income countries, their toll in terms of casualties and
human displacement is usually larger in poorer countries, due to higher vulnerability and limited capacity to
45 cope with the disasters (Christian Aid, 2022). In the Greater Horn of Africa (GHA), the indirect impacts of
disasters such as floods and droughts often result in greater devastation than their direct impacts, yet this
association is frequently overlooked. These include water-borne disease spreading, failure of the crop season,
malnutrition, livelihood impoverishment, increase of infant mortality rates, severe food insecurity, large-scale
migration flows, ultimately increasing social inequality, political instability and civil conflicts (Maystadt et al.,
50 2015; FAO and WFP, 2022). Targeted flood risk profiling efforts confirm that over 2 million people are affected
on average every year in the GHA region, possibly becoming 2.7 millions under high-end future climate
scenarios in combination with socio economic projections for 2050 (UNDRR, 2021). Furthermore, an average
of 1.3 million people are estimated to be forcibly displaced each year (ICPAC, 2023).

Climate change is likely to increase the impacts of weather-related disasters in the GHA, by altering the regimes
55 of seasonal rainfalls which are key sources of water for the agricultural lands. Climate projections predict large
uncertainty in precipitation patterns across most of East Africa by 2050. Yet, there is high confidence for an
increase in seasonal rainfall over the Ethiopian highlands (Richardson et al., 2022). The variability in the
seasonal rainfalls is projected to increase, resulting in more frequent wetter and drier years and a higher risk of
flood and drought events. Advances in weather prediction models have enabled skillful early warning systems
60 for floods and other weather related hazards, also covering areas with very limited in situ measurements such as
Africa (e.g., Lienert et al., 2022; Sheffield et al., 2014; Arsenault et al., 2020; Alfieri et al., 2013; Wu et al.,
2019; Hales et al., 2022). The most common approach used in flood early warning systems is to force a
hydrological model with numerical weather predictions (NWP) and detect upcoming floods when predicted flow
peaks exceed warning thresholds derived from long-term statistics. Although such a method has demonstrated
65 its robustness in predicting potential flood occurrences, it has limitations in accurately identifying the full extent
of their impacts and the efforts required for emergency support and recovery in the aftermath of disasters. The
estimation of flood impacts requires the spatial characterization of the inundation extent, rather than mono-
dimensional information on discharge threshold exceedance. In addition, adding the information on the exposed
assets, vulnerability and coping capacity is crucial to shift the system from a purely hazard-based, to impact-
70 based forecasting. This is particularly important for developing countries as in Africa, which has high flood
exposure due to unplanned human settlements in flood-prone areas (Di Baldassarre et al., 2010; Douglas, 2017).
In addition, actual vulnerability to disasters has remarkably dynamic components, not only in space but also in
time. For instance, Matanó et al. (2022) found higher than expected drought and flood impacts in Kenya and
Ethiopia in 2017–2018, when government elections, crop pest outbreaks and ethnic conflicts increased the
75 countries vulnerability. Similarly, exposure to floods may experience rapid increase in the next few decades in
Africa if the planned population growth does not come with adequate land use planning (Alfieri et al., 2017;
Winsemius et al., 2016; Tabari et al., 2021).



This work describes the design, setup, operational implementation and first evaluation of an impact-based flood forecasting system for the GHA region named Flood-PROOFS East Africa. Flood-PROOFS (Flood
80 PROBABILISTIC OPERATIONAL FORECASTING SYSTEM) is designed to support decision makers during the operational phases of flood forecasting, flood monitoring, and water resource management. Its main goal is to protect the population and infrastructures from damage caused by intense hydro-meteorological events. The system is operational for the Italian National Civil Protection Department and other hydro-meteorological offices in various world countries (e.g., Bolivia, Caribbean, Mozambique). In the East African configuration, Flood-
85 PROOFS is based on a hydro-meteorological modeling chain including ensemble discharge forecasting forced by NWP, link to inundation scenarios, and application of a risk assessment framework to include all the relevant components to forecast disaster impacts. The activity is part of the development of an African Multi Hazard Early Warning System (AMHEWAS), a multi-year project funded by the Italian Government and implemented by CIMA Research Foundation through the United Nations Office for Disaster Risk Reduction (UNDRR), in
90 collaboration with national hydro-meteorological services, climate centers from different Regional Economic Communities (RECs) and the African Union Commission (AUC).

2 Material and Methods

2.1 The study region

95 The Greater Horn of Africa (GHA) region is composed of 11 countries (Figure 1), including Ethiopia, Eritrea, Djibouti, Sudan, South Sudan, Somalia, Uganda, Burundi, Rwanda, Kenya, and Tanzania, with a total population of 375 million in 2020, projected to exceed 700 million by 2050 (United Nations, 2022). The region experiences a highly variable climate, influenced by both oceanic and atmospheric processes. Precipitation patterns are particularly complex, with some areas receiving high amounts of rainfall and others experiencing
100 prolonged dry spells (Nicholson, 2017). The climate in the GHA ranges from dry to tropical, with temperatures that vary depending on elevation and proximity to water bodies.

The seasonal cycle of precipitation in the GHA is characterized by a bimodal pattern for the equatorial and southern parts and unimodal for the northern part. In the equatorial and southern part of the GHA region, the long rains occur from March to May, while the short rains fall between October and December. Differently, the
105 northern part of the region receives rainfall in the period June-September. The dry seasons, which are characterized by low rainfall and high temperatures, occur from June to September and from January to February in the equatorial and southern parts of the region. The climate of the GHA is characterized by large spatial heterogeneity, which can be largely attributed to the topographic differences that can be found throughout the region as well as the oscillation of the intertropical convergence zone (ITCZ) (Lyon, 2014).
110 Despite the variability in precipitation patterns, the region has significant water resources, including lakes, rivers, and underground aquifers. However, the variability of the climate, together with other factors such as population growth and land use changes, pose significant challenges to the sustainable management of these resources.

The economy of GHA countries is highly dependent on rain-fed agriculture, thus it is extremely sensitive to
115 weather and climate variability. The GHA region is already experiencing changes in temperature and precipitation patterns due to climate change, which exacerbates the region's vulnerability to extreme weather



events. Climate projections point towards more severe river flooding in the White Nile, Kenya and southern Somalia by the end of the century (Hirpa et al., 2019). On the other hand, the northern part of the GHA is likely to experience in the coming decades further drying and reduction of low flows, partly linked to a higher warming rate than the global average (Osima et al., 2018).

2.2 Static data

2.2.1 Hydrological modeling

The setup of Flood-PROOFS East Africa required the collection of several static and dynamic data, which are described in the following. The Digital Elevation Model (DEM) is taken from the Hydrologic Derivatives for Modeling and Applications (HDMA) database (Verdin, 2017), with spatial resolution of 3 arc-second (~90 m at the equator). HDMA comes with a pre-computed and corrected set of hydrological derivatives, including channel network and basin partitioning. Ancillary data including flow accumulation and drainage direction were extracted from the DEM with GRASS GIS (<https://grass.osgeo.org/>). The DEM was upscaled at the chosen domain resolution and carved using the 90 m stream network.

Land use and land cover information at 300 m resolution are taken from the ESA-CCI Land Cover map v2 (ESA, 2017), which was used to estimate the soil characteristics and the vegetation cover. Further, we applied the USDA method for soil texture identification and hydrologic soil type classification (Shirazi and Boersma, 1984) by combining the ISRIC SoilGrids (Hengl et al., 2017) maps of soil fraction in sand and clay at 250 m spatial resolution.

2.2.2 Impact modeling

Inundation maps are taken from the set of global flood hazard maps produced by the European Commission, Joint Research Centre (JRC, Dottori et al., 2016) and distributed through its Data Catalog service. Maps are provided at 30 arc-second resolution (~1000m) for rivers with drainage area above 5000 km² and for six return periods, i.e., the 1 in 10, 20, 50, 100, 200 and 500 years. These represent the maximum flood extent and depth assuming an unprotected scenario, i.e., assuming the failure of flood defenses. Maps are produced with a bi-dimensional hydrodynamic model forced by flood hydrographs taken from the GloFAS reanalysis (Alfieri et al., 2020), and come with a set of Areas of Influence maps, which define the links between portions of inundated areas and the corresponding pixel of the GloFAS river network at 0.1 degree resolution (Alfieri et al., 2017).

Exposure maps were collected for the following classes: Population, Crop land, Grazing land, Gross Domestic Product (GDP), Livestock units, and Road network. Maps cover the entire GHA region and were chosen as the best tradeoffs between data quality, year of release and homogeneous coverage in the region. Additional details on exposure layers are reported in the Supplement material.

Country-based lack of coping capacity (Lcc) values were taken from the latest version of the INFORM Risk Index (De Groeve et al., 2015) available at the time of development (i.e., year 2022). Lcc ranges between 0 and 10, with largest values for countries with lowest coping capacity, hence needing more support in case of disasters. East African countries ranks the highest in the global ranking of INFORM, with South Sudan having the largest value (Lcc=9.5) among all world countries, Somalia ranking 3rd (Lcc=8.8), Eritrea 8th (Lcc=7.8), and Uganda and Ethiopia in the top 25 countries.

Vulnerability is defined as the conditions determined by physical, social, economic and environmental factors or processes which increase the susceptibility of an individual, a community, assets or systems to the impacts of hazards. In particular, vulnerability to riverine flooding is linked to the probability of being affected by the



160 inundation in the flood-prone areas, hence it depends on the flood protection level, probability of a levee failure,
early warning systems in place, and other impact-reduction measures. In this work we use vulnerability
information from Alfieri et al. (2022a) which values range between 0 and 1 depending on the hazard magnitude,
and were tuned on the basis of reported affected impacts in past disasters in Africa.

165

2.3 Dynamic data

Variables needed by Continuum, the hydrologic model underpinning the Flood-PROOFS flood forecasting
system, are 10m wind speed, relative humidity, 2m temperature, downward short-wave radiation, and
precipitation. Hydrological model runs for historical simulations over 2001-2022 are forced by the gauge-
170 adjusted GSMaP precipitation (Kubota et al., 2020) and by surface air temperature, relative humidity, wind
speed and incoming solar radiation taken from the ERA5 atmospheric reanalysis (Hersbach et al., 2020) from
the European Centre for Medium-Range Weather Forecasts (ECMWF). GSMaP has a resolution of 0.1° and 1
hour. It relies on a Dual-frequency Precipitation Radar (DPR) onboard GPM core satellites, other GPM
constellation satellites, Geostationary satellites, and a bias correction based on CPC Unified Gauge-based
175 Analysis of Global Daily Precipitation. The near real time version of the product, with a nominal latency of 4
hours, has been selected to feed the operational runs of the flood forecasting chain.

ERA5 is produced on regular latitude-longitude grids at 0.25° x 0.25° hourly resolution, with daily updates
being available 5 days behind real time. Data from both GSMaP and ERA5 were downscaled from the original
to the respective domain resolutions through a natural neighbor interpolation method.

180 Weather forecasts are taken from the Global Forecast System (GFS) of the United States National Centers for
Environmental Prediction (NCEP), together with the corresponding 30-member ensemble product GEFS. Both
products have 0.25° resolution and are acquired up to 120 hour forecast range at hourly resolution for GFS and
3-hourly for GEFS.

Daily discharge data was collected at ~200 gauging stations in the GHA region. Data sources are the Global
185 Runoff Data Centre (GRDC), the African Database of Hydrometric Indices (ADHI, Trambly et al., 2020), and
the national hydrometeorological services of Burundi, Sudan, South Sudan, Tanzania and Uganda. After a
screening for data quality, period of record and minimum record length of 3 years, we selected 56 stations to use
for calibration and 78 for model validation.

190 2.4 Methods

2.4.1 Modeling setup

Hydrological processes in the study region are simulated with the Continuum model (Silvestro et al., 2013).
Continuum is a semi-physically based rainfall-runoff-routing distributed hydrological model, which completely
solves the mass and energy balance at the land surface. It relies on a morphological approach placing the Digital
Elevation Model (DEM) as the key element, from which the drainage network and other hydrological
195 derivatives are computed (Giannoni et al., 2000). Continuum reproduces the spatio-temporal evolution of runoff,
soil moisture, energy fluxes, surface soil temperature, snow accumulation and melting, by reproducing all main
processes of the hydrological cycle. For the implementation in the GHA region, Continuum was set up over 17
independent and hydrologically coherent domains (Figure 1), to cover 11 countries and additional land portions
200 located upstream, for a total simulated area of 6.8 million km². The model setup has variable grid resolution



depending on the domain, with D01 and D02 (including the Nile River Basin) at 0.03° (~3.3 km), D15 (including the Juba-Shabelle river basin) at 0.02° (~2.2 km), D13a, D13b and D13c (the three main Tanzanian islands) at 250 m, and all the other domains at 0.01° (~1.1 km) resolution. Point features implemented include the largest 19 reservoirs and 20 lakes, extracted from the Global Dam Watch (Mulligan et al., 2021), the FAO-AQUASTAT-Dams (<https://www.fao.org/aquastat/en/databases/dams>) and the HydroLAKES (Messenger et al., 2016) datasets. Both lakes and reservoirs were selected among those having total storage larger than 300 Mm^3 . An additional lake was inserted to model the Sudd swamps in South Sudan. To estimate its two model parameters (emptying constant and volume with zero outflow discharge) we took the maps of minimum and maximum flood extent in 2001-2018 from Di Vittorio and Georgakakos (2021) and estimated the corresponding water storage using the procedure by Peter et al. (2022) and the Shuttle Radar Topography Mission (SRTM) DEM at 30m resolution.




Figure 1: GHA region with dams, lakes and calibration stations included in the model (left). The 17 simulation domains implemented (right). Map data from © OpenStreetMap.

2.4.2 Parameter calibration

We performed a multi-site calibration of the model parameters over 7 domains using 56 daily discharge time series resulting after the data screening. The calibration strategy follows the procedure described by Alfieri et al. (2022), yet using the normalized Root Mean Square Error (nRMSE) in place of the Kling Gupta Efficiency (KGE), which is then weighted by the logarithm of their upstream area, to give a comparable but higher weight to stations located downstream. For each domain we calibrated four parameters, chosen through a global sensitivity analysis (GSA) on eight Continuum parameters to investigate their sensitivity and the most influential ones for each output variable. GSA was based on the SAFE Toolbox (Pianosi et al., 2015), using the Elementary Effects Test (EET) (or method of Morris) and One-at-a-time (OAT) sampling using Latin Hyper-cubes. Additional details on the GSA and on the calibration strategy are reported in the Supplement material.



25

Multi-site calibrations are known to give on average lower performance than cascading calibrations in the calibration period, though they improve and stabilize basin-wide performance, with noticeable skill gain in uncalibrated rivers and overall in validation (Wi et al., 2015). The calibration period was chosen to include three years of observed discharge data in the most recent period of availability, considering the quality of the data and possibly including both periods of high and low flows. Each calibration run has a 4-year duration, to include a 1-year warm up period at the start of each run.

In most of the calibrated domains the entire calibration process was repeated more than once to fine tune the choice of the parameter set, the calibration stations and the calibration period. Overall, the entire calibration procedure required over 2000 model runs. Parameter regionalization was performed on those domains with no calibration stations, according to criteria of proximity and climatic conditions. Calibrated parameters were then used in a set of long-term hydrological simulations over 2001-2022, having three key functions. First, to estimate suitable initial conditions to initialize the operational forecasts. This is particularly useful for large river basins (e.g., Nile, Juba-Shabelle) with long memory (i.e., more than 1 year), thus requiring long initialization periods to adequately characterize their water balance conditions. Second, to serve as an evaluation dataset to be compared with observed discharges. Third, long term simulations are analyzed statistically to extract discharge annual maxima and estimate extreme value distributions at each pixel of the river network. Analytical functions were estimated with the 3-parameter Generalized Extreme Value (GEV) distribution based on L-moments (e.g., Hosking, 1990). Maps of discharge peaks corresponding to the 1 in 2, 5, and 20 year return periods were chosen as medium, high and severe warning thresholds for the operational forecasting chain, thus identifying three hazard classes (Hc). Performance of the hydrological model was assessed over the maximum extent of discharge data availability at the validation stations over the period 2002-2022, using the long term simulations described above. Validation was performed over 78 river gauges, hence including some that were not used in the calibration phase. Validation skills are key predictors of the model skills of the operational model runs and are thus more representative than the skills obtained in the calibration phase.

2.5 The impact-based forecasting chain

The operational forecasting chain is composed of three main components: hydrological runs and threshold exceedance detection, composite of the corresponding inundation depth and extent, and impact forecast. These are activated every day as soon as new weather forecasts are available.

2.5.1 Hydrological runs and event detection

GFS deterministic forecasts with a 5-day horizon are downloaded and pre-processed to be taken as input by Continuum. Hydrological states are updated to the 00 UTC of the current day through a 1-day run starting from the previous day conditions and taking as input the GSMaP 24-hour precipitation and the other atmospheric variables of the last 24 hours from the same global forecasting model. Continuum is run in forecast mode for the subsequent 5 days and the maximum discharge at each pixel of the river network is compared with the three warning thresholds extracted from the long-term runs, to detect high-flow events.

A similar exceedance analysis is performed versus a threshold corresponding to the 20-th percentile of the analytical cumulative distribution function of the GEV distribution at each pixel (i.e., the 1 in 1.25 year return period). When such exceedance is detected at any point, the ensemble forecast is triggered for the same domain, which consist of 5-day hydrological forecasts based on the 30-member GEFS as forcing input. The 30 output



discharge scenarios at each reporting point are then shown in the visualization platform, enabling the forecaster on duty to evaluate the range of variability of predicted flows (see example in the Supplement material).

270

2.5.2 Impact forecasts

Impact forecasts are triggered when the forecast deterministic discharge exceeds the 1 in 2 year warning threshold at any section of the river network. First, an unprotected inundation scenario (i.e., assuming that all flood defenses fail) is produced by linking the grid points where the highest discharge threshold is exceeded to the JRC inundation map with the closest return period. To this aim, each pixel of the GloFAS river network was mapped to one or more pixels of the Continuum network, using automated criteria of proximity and similarity between the drainage areas, followed by manual fitness check. In addition to the three warning thresholds used for early warning (i.e., annual frequencies of 1 in 2, 5 and 20 years), we extracted four additional threshold maps with the same annual frequencies as those of the JRC inundation maps (i.e., 1 in 50, 100, 200 and 500 years), to enable impact assessments for a wider spectrum of event magnitude. Finally, the inundation scenario of each forecast is produced by mosaicking together all the portions of flooded area (with variable return period along the river network).

275

Absolute (I) and relative (RI) impacts are calculated as aggregate values for each administrative region (GADM level 1, see <https://gadm.org>) according to the following formulas:

$$I_{AR} = \sum_{AR} \sum_{Hc=1}^3 (H \cdot E \cdot V) Lcc \quad (1)$$

285

$$RI_{AR} = \frac{I_{AR}}{E_{AR}} \quad (2)$$

where: H is the hazard, i.e., the mask of maximum inundated area in the forecast range;

E is the exposure of the considered class (Population, Crop land, Grazing, Gross Domestic Product (GDP), Livestock units, and Road network);

290 V is the vulnerability;

Lcc is the lack of coping capacity.

I_{AR} is the potential impact for any considered administrative region (AR), obtained as a double summation over all pixels within AR and over each of the three considered hazard classes (Hc), where Lcc is a constant value for each country and the product (H E V) is computed at the pixel level for each Hc and then added to the sum. For each forecast run, eq. (1) and (2) are evaluated for all 227 administrative regions in the GHA and for the seven exposure categories. Results of flood impacts are displayed in the myDewetra web interface on average at 6:30 UTC, typically within 1 hour from the availability of the weather forecast data. Ensemble simulations, if triggered, are produced afterwards and progressively displayed on the interface when available.

295

3 Results and Discussions

3.1 Hydrological model evaluation

300 Long term runs of the calibrated model domains over 2002-2022 are evaluated at 78 quality controlled river gauges for the available period of record of each station. Four summary performance scores are reported in Figure 2: the Kling-Gupta Efficiency (KGE) and its three decomposition terms, i.e., correlation (r), bias rate, and variability rate. Note that all four scores have their optimum at 1. Figure 3 shows a comparison of observed



305 versus simulated discharges at 10 sample validation stations while a table with the scores of all validation
stations is reported in the Supplement material. Median scores taken from the validation sample include
 $KGE_{VAL}=-0.76$, $correlation_{VAL}=0.35$, $bias\ rate_{VAL}=0.33$ and $variability\ rate_{VAL}=2.33$. For comparison, the same
scores in the calibration period are $KGE_{CAL}=-0.37$, $correlation_{CAL}=0.47$, $bias\ rate_{CAL}=0.51$ and $variability$
 $rate_{CAL}=2.03$. Best KGE are generally found along the main rivers: Blue Nile, White Nile, Jubba, Shabelle and
310 Awash, while poorest performances are seen particularly in Tanzania and regions south of the Equator, in river
sections with smaller basin area and faster runoff dynamics. The reduction in performance in this area is largely
attributed to a significant negative bias and large variability rates. Those results are supported by the work of
Awange et al. (2016), who found that GSMaP precipitation severely underestimates rainfall in Tanzania and to a
lesser extent also in the Equatorial part of the GHA. This results in model parameters tuned to minimize
315 infiltration and favor a quick runoff, which increase the variability rate of the output discharges. The issue of
bias in hydrological simulations in Africa was already pointed out in various previous works, yet with a trend of
overestimating discharges when atmospheric reanalyses are used as input. Hirpa et al. (2019) found an average
bias rate of 3.50 while comparing the output of a global hydrological model with 29 observed river gauges in the
GHA. Similarly, the GloFAS Reanalysis v3 (Alfieri et al., 2020) produces average bias rates of 4.12 (1.97) in an
320 evaluation exercise versus 7 (89) discharge stations in the GHA (entire African continent). However, it is known
that bias does not deteriorate the performance of systems based on threshold exceedance detection, if warning
thresholds are consistent with the discharge time series.

Correlations generally denote larger skills, with 75% of stations having values larger than 0.25. Stations best
correlated with observations are in line with those having best KGE. Worst correlations are mostly located in
325 stations immediately downstream large reservoirs (i.e. Victoria Nile downstream Lake Victoria and Lake
Kyoga; White Nile downstream Lake Albert and Jebel Aulia dam; Awash River at Tendaho dam), which release
rules are not easily predictable, as well as in small headwater catchments. Correlation is better linked to the
performance in detecting rise or decrease in discharge levels without being penalized by multiplicative or
additive errors, hence it is a suitable indicator to measure the capability in event detection and in turn of flood
330 early warning based on threshold exceedance.





Figure 2: Validation skills at 78 river gauges: KGE and its decomposition terms correlation (r), bias rate, and variability rate. Numeric values are reported in the Supplement material. Map data: © Google 2019.



335

Figure 3: Comparison of simulated versus available observed discharges at 10 stations sampled from all 8 validation domains for the period 2002-2021.

3.2 Case study - the Nile floods in summer 2020

Here we illustrate an example of the system output for the floods in the Nile River Basin in Summer 2020, based on the analysis of hazard and impact forecasts, screenshots from the myDewetra visualization platform, qualitative and quantitative comparison with reported data.

Between July and September 2020, continuous rainfall in Sudan and upstream countries in the Nile Basin caused devastating floods across 17 out of the 18 Sudanese states, with the Blue Nile exceeding water level records set in 1946 and 1988¹. The flood event killed over 100 people in Sudan, affected nearly one third of cultivated land and about 3 million people from agricultural households, worsening already acute levels of food insecurity (FAO, 2020). The dynamics of the event and of the resulting flood impacts is particularly challenging

1 <https://floodlist.com/africa/sudan-floods-update-september-2020>



to simulate through a modeling chain, due to the superposition of different drivers. The first one are the exceptional seasonal rainfalls recorded in the Ethiopian Highlands, contributing to extreme levels in the Blue Nile and its tributaries. Second are the slow yet persistent rise of the flows in the White Nile, resulting from exceptionally high-water levels in upstream lakes, including Lake Victoria, Lake Albert and Lake Kyoga. This dynamic triggered the well known floods in South Sudan, causing the expansion of the Sudd Swamps which affected over a million people and lasted over two years before starting to recede in 2022 (FAO and WFP, 2022). The third driver is the series of short-lived and intense rainfall events causing flash floods and pluvial flooding in various areas of Sudan during summer 2020. Those events usually affect relatively small areas, yet their poor predictability coupled with their rapid evolution and destructive power causes on average the largest death toll by catching people unprepared.

In Flood-PROOFS East Africa (FPEA), the Nile basin was calibrated using observed discharges at 22 gauging stations. The 20-year hydrological reanalysis forced by GSMaP satellite precipitation correctly identifies the flow peak of September 2020 in the lower Blue Nile as the largest in the available simulation record (see Supplement material). The hydrological and impact forecasts were simulated using initial conditions and input weather forecasts available at the time of the event. We ran one 5-day forecast every 4 days for the three months July-September 2020 and visualized the output in myDewetra as in operational mode. According to the Sudanese Ministry of Irrigation and Water Resources, on 7 September 2020 the Blue Nile River at Khartoum reached 17.67 meters², the highest level on record, before starting to decrease on the following day. FPEA forecast run of 2 September 2020 predicted a flow peak well above the 1 in 20 year return period in the Blue Nile at the same location in the evening of the 5 September, less than 2 day difference with the observed peak (see Supplement material). The same forecast shows return periods in the Blue Nile generally above the 1 in 5 year return period, then exceeding the 1 in 20 years after the confluence with the Dinder River, all the way downstream beyond Khartoum till the Merowe Reservoir in the Nile River. Flooding is worsened also by high discharges from the Atbara River joining the Nile River in Atbara and forecast to exceed the 1 in 5 year return period of peak flows. At the same time, flows in the White Nile are forecast to exceed the 1 in 2 year return period in the entire Sudanese portion down to Khartoum, with a slight but persistent increasing trend resulting from the lamination of flood volumes released by the Sudd Swamps in South Sudan (Figure 4a). Each river reach exceeding the 1 in 2 year flood threshold in the 5-day forecast is then assigned with the corresponding inundation scenario taken from the JRC flood hazard maps (Figure 4b). The figure shows the large potential extent of the flooding along the White Nile, Blue Nile and Atbara River. Differently, the extensive threshold exceedance visible in the western part of the country occurs in an ephemeral river in a desert area, where the 1 in 20 year peak flow corresponds to moderate discharges and limited or no flooding outside the river bed. The forecast map of inundation extent is then used as the hazard component in the subsequent estimation of flood impacts.




Figure 4: FPEA forecast on 2 September 2020 from the myDewetra web platform. (a) Reporting points and 5-day discharge forecast at four sample points. (b) 5-day forecast of flood hazard levels and maximum inundation extent. Map data: © Google 2019.

385 5-day impact forecasts for the seven exposure categories listed in Sect. 2.2.2 are produced at each model run (see, e.g., Figure 5). In the FPEA forecasts of 2 September 2020, most regions of Sudan and South Sudan have considerable impacts in all considered categories, together with parts of Uganda, Ethiopia and Eritrea. 5-day forecasts of population affected are also displayed as time series in Figure 6, to show the evolution of impact forecasts by country and by Sudanese state in the period July-September 2020. The same figures for the six

390 other exposure categories are provided in the Supplement. These figures show that most of the impacts were forecast in Sudan, starting towards the end of July 2020 and then sharply increasing towards the end of August. The peak of total population affected was predicted in the run of 2 September 2020, when the most severe flood wave in the Blue Nile was about to transit by Khartoum, the largest city in the affected region. Maximum forecast population affected was 3.9 millions in Sudan (Table 1), of which 1.9 in the country capital. The peak

395 of impacts of the floods in South Sudan was forecast on 10 September 2020, with 0.9 million people affected. Forecasts compare well in magnitude with recorded impacts in Sudan, South Sudan and Uganda, from the EMDAT database (EM-DAT, 2023). For comparison, estimates by GloFAS are one order of magnitude lower, with about 224,000 people affected in the three countries and only 40,000 in Sudan. In FPEA, people affected in Khartoum and in the states along the Nile and Blue Nile River are generally above the figures reported by UN-

400 OCHA (<https://www.unocha.org/sudan>, see comparison in Figure 7). This is partly attributed to a considerable overestimation of the inundated area for all flood scenarios in the JRC flood hazard maps (Dottori et al., 2016). For instance, in those maps, most of the city of Khartoum is inundated even with a flood return period as low as 1 in 10 years, due to the coarse map resolution, and the simplified representation of flood defenses and river channels in the modeling framework. In addition, the definition of affected population by floods is non univocal and may lead to very different estimates depending on the approach used, such as the one by UN-FAO reporting

405 up to 3 million people affected in Sudan in the 2020 event³. In FPEA we count population as affected for any flood depth, while estimates by governments are likely to consider higher levels of impact. On the other hand, impact estimates are generally underestimated in smaller flash flood-prone catchments (e.g., in Darfur), due to

3 <https://www.theguardian.com/world/2020/sep/05/sudan-declares-state-of-emergency-record-flooding>



410 the poor predictability of those events by global atmospheric models and to the lower limit of 5,000 km² below which the JRC flood hazard maps are not defined.




Figure 5: FPEA forecast on 2 September 2020 from the myDewetra web platform. Absolute (left) and relative (right) 5-day forecasts of affected cropland aggregated at 1st level sub-national administrative regions in the Nile Basin. Map data: © Google 2019.





Figure 6: 5-day forecast of population affected in the Nile Basin for the period July-September 2020 from FPEA. Country totals (left) and aggregations for the Sudanese states (right).

Table 1: Impacts recorded by EMDAT for the floods in 2020 and comparison with FPEA and GloFAS forecasts.

	Population Affected [1,000]			Damage [million USD]	
	EMDAT	FPEA	GloFAS	EMDAT	FPEA
Sudan	875	3920	39.7	250	243
South Sudan	1042	891	184	NA	69
Uganda	8.7	49	0	NA	6.7
Total	1925.7	4860	223.7		318.7



60



420

Figure 7: Maximum forecast population affected for the 2020 floods by FPEA and comparison with figures by UN-OCHA. Aggregations by Sudanese states.

4 Conclusions

This work describes the status of implementation of Flood-PROOFS East Africa, a novel medium-range impact-based system for ensemble flood forecasting and early warning in the Greater Horn of Africa. The system is based on a hydro-meteorological modeling chain coupled with impact predictions at sub-national administrative level, taking into account all elements of the risk assessment formula: hazard, exposure, vulnerability, and coping capacity. Being an operational system, it runs within an automated daily scheduling including data acquisition, model runs, archiving of the model output, creation of visualization products, display in the web interface myDewetra, process monitoring, service status notification and backup operations. Flood-PROOFS East Africa is one of the key activities of the UNDRR “Programme for a continental coordination, early warning and action system in Africa” currently being performed in collaboration with the African Union Commission (AUC) and relevant African partners working in the field of climate prediction and disaster management. The system operations started in December 2022 and foresee to provide continuous support ahead of major floods during the rainy seasons in the GHA: March–May and October–December in the equatorial region, June–September in the northern sub-region including most of the Nile river Basin, and December-May in Tanzania. To maximize the system’s value, impact forecasts must be translated into clear and concise warning messages and reach emergency operators, including national civil defense forces and humanitarian organizations. Achieving such a full operating status involves identifying some additional steps, including: i) setting up a team of duty officers composed by hydro-meteorological experts and disaster risk managers, working in shifts to monitor daily forecasts; ii) establishing a network of national and regional focal points in the GHA region, to contact ahead of major events; iii) ensure that warning messages are correctly interpreted, together with their key strengths and limitations, and propose a set of advisories and suggested actions; iv) collect feedback on predicted impacts to improve the future system performance. Currently, model results are available through the password-protected web interface myDewetra, and dedicated accounts have already been shared with the Disaster Operation Centers of the AUC, in Addis Ababa - Ethiopia, the Climate Center of the IGAD region (ICPAC), based in Nairobi - Kenya, and at national level with the Sudanese National Council of Civil Defence



NCCD and its members, including early warning units from different institutions: Ministry of Irrigation and Water Resources, Sudan Meteorological Authority, Ministry of Agriculture and Forests.

450 Future activities include a more extensive evaluation of the model output in flood prediction, specifically targeted to achieving robust quantification of expected flood impacts. Such an approach has multiple advantages. First, it focuses on relevant metrics for disaster mitigation and preparedness, which can be directly linked to the amount of resources needed for emergency support and recovery. Second, validation data is independent from in situ hydrological measurements, which are particularly difficult to obtain in near-real time

455 in this region. Model evaluation is instead performed on data which is of higher interest for emergency operations and thus is collected promptly, including people affected and damage to infrastructures. Similarly, forecasts of inundation extent can be benchmarked to satellite acquisitions, which improved latency and availability currently enable almost daily coverage of flood disasters globally, even in cloud conditions (Salamon et al., 2021). In addition, being based on a full hydrological modeling system, the model output can be

460 evaluated both in wet and dry conditions, to understand if it generates skillful results that can be of use also for drought and water resources monitoring.

Code availability

Continuum is an open source hydrological model. Its code is available at <https://github.com/c-hydro/hmc-lib>. Meteorological data was downloaded with the open source package “door”, available at <https://github.com/c-hydro/door>.

465

Data availability

GSMaP precipitation data is available from <ftp://hokusai.eorc.jaxa.jp>. Operational GFS forecasts are downloaded through the NOAA Nomads grib filter (https://nomads.ncep.noaa.gov/gribfilter.php?ds=gdas_0p25) while historical GFS data were downloaded from the NCAR Data Archive (<https://rda.ucar.edu/thredds/catalog/files/g/ds084.1/catalog.html>). ERA5 atmospheric reanalysis were downloaded from the Copernicus Climate Data Store (<https://cds.climate.copernicus.eu/>) through the dedicated python api. ESA-CCI land cover can be downloaded from <https://www.esa-landcover-cci.org/>. The SoilGrids map are available from the ISRIC data hub at <https://data.isric.org/geonetwork/srv/ita/catalog.search#/home>.

470

475 Lakes and dams data were downloaded respectively from <https://www.hydrosheds.org/products/hydrolakes> and <https://www.globaldamwatch.org/directory>. Observed discharges from the GRDC database are freely available for download at <https://www.bafg.de/GRDC>. Global flood hazard maps from Dottori et al. (2016) can be downloaded from <https://data.jrc.ec.europa.eu/collection/id-0054>. Lack of coping capacity values were taken from the INFORM Risk Index at <https://drmkc.jrc.ec.europa.eu/inform-index/INFORM-Risk>.

480 Author contribution

LA, AL, LC and SG, designed the hydrological experiments. AL developed the model code. LA and AL performed the formal analysis and produced the figures. TG and ET supported the development of the impact assessment framework. AM and NT supported the assessment of the Sudan floods 2020. YT, HW, FD, JO and AL supported the data collection. LR, RR, LR, AA and MM supported the funding acquisition and the

485 definition of the project strategies. LA prepared the manuscript with contributions from all co-authors.

Competing interests

The authors declare that they have no conflict of interest.

Financial support

The research leading to these results has received funding from the Italian Ministry of Foreign Affairs, the

490 Italian Agency for Development Cooperation and is implemented through the United Nations Office for



Disaster Risk Reduction (UNDRR) contract n. UNDRR/GR/2022/009 “Programme for a Continental Coordination, Early Warning and Action System in Africa”.

Special issue statement

495 This article is part of the special issue “Reducing the impacts of natural hazards through forecast-based action: from early warning to early action”.

References

500 Alfieri, L., Burek, P., Dutra, E., Krzeminski, B., Muraro, D., Thielen, J., and Pappenberger, F.: GloFAS – global ensemble streamflow forecasting and flood early warning, *Hydrol. Earth Syst. Sci.*, 17, 1161–1175, <https://doi.org/10.5194/hess-17-1161-2013>, 2013.

Alfieri, L., Bisselink, B., Dottori, F., Naumann, G., de Roo, A., Salamon, P., Wyser, K., and Feyen, L.: Global projections of river flood risk in a warmer world, *Earth’s Future*, 5, 171–182, <https://doi.org/10.1002/2016EF000485>, 2017.

505 Alfieri, L., Lorini, V., Hirpa, F. A., Harrigan, S., Zsoter, E., Prudhomme, C., and Salamon, P.: A global streamflow reanalysis for 1980–2018, *Journal of Hydrology X*, 6, 100049, <https://doi.org/10.1016/j.hydroa.2019.100049>, 2020.

510 Alfieri, L., Avanzi, F., Delogu, F., Gabellani, S., Bruno, G., Campo, L., Libertino, A., Massari, C., Tarpanelli, A., Rains, D., Miralles, D. G., Quast, R., Vreugdenhil, M., Wu, H., and Brocca, L.: High-resolution satellite products improve hydrological modeling in northern Italy, *Hydrology and Earth System Sciences*, 26, 3921–3939, <https://doi.org/10.5194/hess-26-3921-2022>, 2022.

515 Arsenault, K. R., Shukla, S., Hazra, A., Getirana, A., McNally, A., Kumar, S. V., Koster, R. D., Peters-Lidard, C. D., Zaitchik, B. F., Badr, H., Jung, H. C., Narapusetty, B., Navari, M., Wang, S., Mocko, D. M., Funk, C., Harrison, L., Husak, G. J., Adoum, A., Galu, G., Magadzire, T., Roningen, J., Shaw, M., Eylander, J., Bergaoui, K., McDonnell, R. A., and Verdin, J. P.: The NASA Hydrological Forecast System for Food and Water Security Applications, *Bulletin of the American Meteorological Society*, 101, E1007–E1025, <https://doi.org/10.1175/BAMS-D-18-0264.1>, 2020.

520 Awange, J. I., Ferreira, V. g., Forootan, E., Khandu, Andam-Akorful, S. a., Agutu, N. o., and He, X. f.: Uncertainties in remotely sensed precipitation data over Africa, *International Journal of Climatology*, 36, 303–323, <https://doi.org/10.1002/joc.4346>, 2016.

Christian Aid: Counting The Cost 2022: A year of climate breakdown, 2022.

De Groeve, T., Poljansek, K., and Vernaccini, L.: Index for risk management-INFORM, *JRC Sci Policy Reports —Eur Comm*, 96, 636388, 2015.

525 Di Baldassarre, G., Montanari, A., Lins, H., Koutsoyiannis, D., Brandimarte, L., and Blöschl, G.: Flood fatalities in Africa: From diagnosis to mitigation, *Geophysical Research Letters*, 37, <https://doi.org/10.1029/2010GL045467>, 2010.

Di Vittorio, C. A. and Georgakakos, A. P.: Hydrologic Modeling of the Sudd Wetland using Satellite-based Data, *Journal of Hydrology: Regional Studies*, 37, 100922, <https://doi.org/10.1016/j.ejrh.2021.100922>, 2021.

530 Dottori, F., Salamon, P., Bianchi, A., Alfieri, L., Hirpa, F. A., and Feyen, L.: Development and evaluation of a framework for global flood hazard mapping, *Advances in Water Resources*, 94, 87–102, <https://doi.org/10.1016/j.advwatres.2016.05.002>, 2016.

Douglas, I.: Flooding in African cities, scales of causes, teleconnections, risks, vulnerability and impacts, *International Journal of Disaster Risk Reduction*, 26, 34–42, <https://doi.org/10.1016/j.ijdr.2017.09.024>, 2017.

535 EM-DAT: The OFDA/CRED International Disaster Database – www.emdat.be, Université Catholique de Louvain, Brussels (Belgium), 2023.

ESA: Land Cover CCI Product User Guide Version 2. Tech. Rep., 2017.



- FAO: “The Sudan | 2020 Flood Impact Rapid Assessment.” Food and Agriculture Organization of the United Nations, September 2020. <https://www.fao.org/3/cb1463en/CB1463EN.pdf>, 2020.
- 540 FAO and WFP: Special Report - 2021 FAO/WFP Crop and Food Security Assessment Mission (CFSAM) to the Republic of South Sudan. 9 June 2022, Rome, 2022.
- Hales, R. C., Nelson, E. J., Souffront, M., Gutierrez, A. L., Prudhomme, C., Kopp, S., Ames, D. P., Williams, G. P., and Jones, N. L.: Advancing global hydrologic modeling with the GEOGloWS ECMWF streamflow service, *Journal of Flood Risk Management*, e12859, 2022.
- 545 Hengl, T., Jesus, J. M. de, Heuvelink, G. B. M., Gonzalez, M. R., Kilibarda, M., Blagotić, A., Shangquan, W., Wright, M. N., Geng, X., Bauer-Marschallinger, B., Guevara, M. A., Vargas, R., MacMillan, R. A., Batjes, N. H., Leenaars, J. G. B., Ribeiro, E., Wheeler, I., Mantel, S., and Kempen, B.: SoilGrids250m: Global gridded soil information based on machine learning, *PLOS ONE*, 12, e0169748, <https://doi.org/10.1371/journal.pone.0169748>, 2017.
- 550 Hersbach, H., Bell, B., Berrisford, P., Hirahara, S., Horányi, A., Muñoz-Sabater, J., Nicolas, J., Peubey, C., Radu, R., Schepers, D., Simmons, A., Soci, C., Abdalla, S., Abellan, X., Balsamo, G., Bechtold, P., Biavati, G., Bidlot, J., Bonavita, M., De Chiara, G., Dahlgren, P., Dee, D., Diamantakis, M., Dragani, R., Flemming, J., Forbes, R., Fuentes, M., Geer, A., Haimberger, L., Healy, S., Hogan, R. J., Hólm, E., Janisková, M., Keeley, S., Laloyaux, P., Lopez, P., Lupu, C., Radnoti, G., de Rosnay, P., Rozum, I., Vamborg, F., Villaume, S., and Thépaut, J.-N.: The ERA5 global reanalysis, *Quarterly Journal of the Royal Meteorological Society*, 146, 1999–2049, <https://doi.org/10.1002/qj.3803>, 2020.
- 555 Hirpa, F. A., Alfieri, L., Lees, T., Peng, J., Dyer, E., and Dadson, S. J.: Streamflow response to climate change in the Greater Horn of Africa, *Climatic Change*, <https://doi.org/10.1007/s10584-019-02547-x>, 2019.
- Hosking, J. R. M.: L-Moments: Analysis and Estimation of Distributions Using Linear Combinations of Order Statistics, *Journal of the Royal Statistical Society. Series B (Methodological)*, 52, 105–124, 1990.
- 560 ICPAC: Flood Displacement Risk Profile, 2023.
- Kubota, T., Aonashi, K., Ushio, T., Shige, S., Takayabu, Y. N., Kachi, M., Arai, Y., Tashima, T., Masaki, T., Kawamoto, N., Mega, T., Yamamoto, M. K., Hamada, A., Yamaji, M., Liu, G., and Oki, R.: Global Satellite Mapping of Precipitation (GSMaP) Products in the GPM Era, in: *Satellite Precipitation Measurement: Volume 1*, edited by: Levizzani, V., Kidd, C., Kirschbaum, D. B., Kummerow, C. D., Nakamura, K., and Turk, F. J., Springer International Publishing, Cham, 355–373, https://doi.org/10.1007/978-3-030-24568-9_20, 2020.
- 565 Lienert, J., Andersson, J. C. M., Hofmann, D., Silva Pinto, F., and Kuller, M.: The role of multi-criteria decision analysis in a transdisciplinary process: co-developing a flood forecasting system in western Africa, *Hydrology and Earth System Sciences*, 26, 2899–2922, <https://doi.org/10.5194/hess-26-2899-2022>, 2022.
- 570 Lyon, B.: Seasonal Drought in the Greater Horn of Africa and Its Recent Increase during the March–May Long Rains, *Journal of Climate*, 27, 7953–7975, <https://doi.org/10.1175/JCLI-D-13-00459.1>, 2014.
- Matanó, A., de Ruyter, M. C., Koehler, J., Ward, P. J., and Van Loon, A. F.: Caught Between Extremes: Understanding Human-Water Interactions During Drought-To-Flood Events in the Horn of Africa, *Earth’s Future*, 10, e2022EF002747, <https://doi.org/10.1029/2022EF002747>, 2022.
- 575 Maystadt, J.-F., Calderone, M., and You, L.: Local warming and violent conflict in North and South Sudan, *Journal of Economic Geography*, 15, 649–671, <https://doi.org/10.1093/jeg/lbu033>, 2015.
- Messenger, M. L., Lehner, B., Grill, G., Nedeva, I., and Schmitt, O.: Estimating the volume and age of water stored in global lakes using a geo-statistical approach, *Nat Commun*, 7, 13603, <https://doi.org/10.1038/ncomms13603>, 2016.
- 580 Mulligan, M., Lehner, B., Zarfl, C., Thieme, M., Beames, P., Soesbergen, A. van, Higgins, J., Januchowski-Hartley, S. R., Brauman, K. A., Felice, L. D., Wen, Q., Leaniz, C. G. de, Belletti, B., Mandle, L., Yang, X., Wang, J., and Mazany-Wright, N.: Global Dam Watch: curated data and tools for management and decision making, *Environ. Res.: Infrastruct. Sustain.*, 1, 033003, <https://doi.org/10.1088/2634-4505/ac333a>, 2021.
- Nicholson, S. E.: Climate and climatic variability of rainfall over eastern Africa, *Reviews of Geophysics*, 55, 590–635, <https://doi.org/10.1002/2016RG000544>, 2017.



- 585 Osima, S., Indasi, V. S., Zaroug, M., Endris, H. S., Gudoshava, M., Misiani, H. O., Nimusiima, A., Anyah, R. O., Otieno, G., Ogwang, B. A., Jain, S., Kondowe, A. L., Mwangi, E., Lennard, C., Nikulin, G., and Dosio, A.: Projected climate over the Greater Horn of Africa under 1.5 °C and 2 °C global warming, *Environ. Res. Lett.*, 13, 065004, <https://doi.org/10.1088/1748-9326/aaba1b>, 2018.
- 590 Peter, B. G., Cohen, S., Lucey, R., Munasinghe, D., Raney, A., and Brakenridge, G. R.: Google Earth Engine Implementation of the Floodwater Depth Estimation Tool (FwDET-GEE) for Rapid and Large Scale Flood Analysis, *IEEE Geoscience and Remote Sensing Letters*, 19, 1–5, <https://doi.org/10.1109/LGRS.2020.3031190>, 2022.
- Pianosi, F., Sarrazin, F., and Wagener, T.: A Matlab toolbox for Global Sensitivity Analysis, *Environmental Modelling & Software*, 70, 80–85, <https://doi.org/10.1016/j.envsoft.2015.04.009>, 2015.
- 595 Richardson, J., Calow, R., Pichon, F., New, S., and Osborne, R.: Climate risk report for the East Africa region. Met Office, ODI, FCDO., 2022.
- Salamon, P., Mctormick, N., Reimer, C., Clarke, T., Bauer-Marschallinger, B., Wagner, W., Martinis, S., Chow, C., Böhnke, C., Matgen, P., Chini, M., Hostache, R., Molini, L., Fiori, E., and Walli, A.: The New, Systematic Global Flood Monitoring Product of the Copernicus Emergency Management Service, in: 2021
600 IEEE International Geoscience and Remote Sensing Symposium IGARSS, 2021 IEEE International Geoscience and Remote Sensing Symposium IGARSS, 1053–1056, <https://doi.org/10.1109/IGARSS47720.2021.9554214>, 2021.
- Sheffield, J., Wood, E. F., Chaney, N., Guan, K., Sadri, S., Yuan, X., Olang, L., Amani, A., Ali, A., and Demuth, S.: A drought monitoring and forecasting system for sub-Saharan African water resources and food
605 security, *Bulletin of the American Meteorological Society*, 95, 861–882, 2014.
- Shirazi, M. A. and Boersma, L.: A Unifying Quantitative Analysis of Soil Texture, *Soil Science Society of America Journal*, 48, 142–147, <https://doi.org/10.2136/sssaj1984.03615995004800010026x>, 1984.
- Tabari, H., Hosseinzadehtalaei, P., Thiery, W., and Willems, P.: Amplified Drought and Flood Risk Under
610 Future Socioeconomic and Climatic Change, *Earth's Future*, 9, e2021EF002295, <https://doi.org/10.1029/2021EF002295>, 2021.
- Tramblay, Y., Rouché, N., Paturel, J.-E., Mahé, G., Boyer, J.-F., Amoussou, E., Bodian, A., Dacosta, H., Dakhlaoui, H., Dezetter, A., Hughes, D., Hanich, L., Peugeot, C., Tshimanga, R., and Lachassagne, P.: The African Database of Hydrometric Indices (ADHI), *Earth System Science Data Discussions*, 1–21, <https://doi.org/10.5194/essd-2020-281>, 2020.
- 615 UNDRR: Towards an IGAD regional flood risk profile: preliminary results of the regional flood risk assessment, 2021.
- UNDRR and CRED: The human cost of disasters: an overview of the last 20 years (2000-2019), 2020.
- United Nations: World Population Prospects 2022: Data Sources. (UN DESA/POP/2022/DC/NO. 9), Department of Economic and Social Affairs, Population Division, 2022.
- 620 Verdin, K. L.: Hydrologic Derivatives for Modeling and Analysis—A new global high-resolution database, *Hydrologic Derivatives for Modeling and Analysis—A new global high-resolution database*, U.S. Geological Survey, Reston, VA, <https://doi.org/10.3133/ds1053>, 2017.
- Wi, S., Yang, Y. C. E., Steinschneider, S., Khalil, A., and Brown, C. M.: Calibration approaches for distributed hydrologic models in poorly gaged basins: implication for streamflow projections under climate change,
625 *Hydrology and Earth System Sciences*, 19, 857–876, <https://doi.org/10.5194/hess-19-857-2015>, 2015.
- Winsemius, H. C., Aerts, J. C. J. H., van Beek, L. P. H., Bierkens, M. F. P., Bouwman, A., Jongman, B., Kwadijk, J. C. J., Ligtoet, W., Lucas, P. L., van Vuuren, D. P., and Ward, P. J.: Global drivers of future river flood risk, *Nature Clim. Change*, 6, 381–385, <https://doi.org/10.1038/nclimate2893>, 2016.
- 630 Wu, H., Kimball, J. S., Zhou, N., Alfieri, L., Luo, L., Du, J., and Huang, Z.: Evaluation of real-time global flood modeling with satellite surface inundation observations from SMAP, *Remote Sensing of Environment*, 233, 111360, <https://doi.org/10.1016/j.rse.2019.111360>, 2019.