

Characterization of Gas and Particle Emissions from Open Burning of Household Solid Waste from South Africa

Xiaoliang Wang¹, Hatef Firouzkouhi¹, Judith C. Chow¹, John G. Watson¹, Warren Carter², Alexandra S.M. De Vos²

5 ¹ Division of Atmospheric Sciences, Desert Research Institute, Reno, NV 89512, U.S.A.

² SASOL Research and Technology, Sasolburg, South Africa

Correspondence to: Xiaoliang Wang (xiaoliang.wang@dri.edu)

Abstract. Open burning of household and municipal solid waste is a frequent practice in many developing countries. Due to limited resources for collection and proper disposal, solid waste is often disposed of in neighborhoods and open burned in piles to reduce odors and create space for incoming waste. Emissions from these ground-level and low-temperature burns cause air pollution, leading to adverse health effects among community residents. This study conducted laboratory combustion experiments to characterize gas and particle emissions from ten waste categories representative of those burned in South Africa: paper, leather/rubber, textiles, plastic bottles, plastic bags, vegetation (with three different moisture content levels), food discards, and combined materials. Carbon dioxide (CO₂) and carbon monoxide (CO) were measured in real-time to calculate modified combustion efficiencies (MCE). MCE is used along with video observations to determine fuel-based emission factors (EFs) during flaming and smoldering phases as well as the entire combustion process. Fuel elemental composition and moisture content have strong influences on emissions. Plastic bags have the highest carbon content and the highest combustion efficiency, leading to the highest EFs for CO₂. Textiles have the highest nitrogen and sulfur contents, resulting in the highest EFs for nitrogen oxides (NO_x) and sulfur dioxide (SO₂). Emissions are similar for vegetation with 0% and 20% moisture contents; however, EFs for CO and particulate matter (PM) from the vegetation with 50% moisture content are 3 and 20–30 times, respectively, those from 0% and 20% moisture contents. This study also shows that neglecting carbon in the ash and PM can lead to significant overestimation of EFs. Results from this study are applicable to emission inventory improvements as well as air quality management to assess the health and climate effects of household waste open burning.

1 Introduction

Solid waste management is a global environmental challenge. Approximately two billion metric tons per year of municipal solid waste (MSW) are generated globally (Wilson and Velis, 2015). Even though high-income countries have higher per capita MSW generation, waste generation in middle- and low-income countries is growing rapidly due to population growth and economic development (Ferronato and Torretta, 2019). Waste disposal practices include collection, recycling, land filling, incineration, and open burning (Wilson and Velis, 2015; Wiedinmyer et al., 2014). In contrast to the near 100% collection and controlled disposal rates in high and upper-middle income countries, low-income countries often have less than 50% collection rates, with near 0% controlled disposal common in rural areas. It is estimated that at least two billion people worldwide still lack access to solid waste collection, treatment, or disposal services and infrastructure (Cook and Velis, 2021; Wilson et al., 2015).

In rural communities of developing countries, particularly regions where waste collection service is expensive, unavailable, or infrequent, uncontrolled open burning of household solid waste is a common practice for decreasing MSW mass and volume, reducing unpleasant odors from decomposing materials, fueling heating and cooking activities, and destroying pathogens (Cook and Velis, 2021). Globally, about half of the household waste (i.e., about one billion tons) is burned in open, uncontrolled fires every year. Open burning is conducted not only by community members, but also by municipal authorities. Although perceived as a cost-effective method of waste disposal, uncontrolled solid waste open burning generates a wide range of hazardous substances that pose threats to human health and contribute to climate change (Wiedinmyer et al., 2014; Lemieux et al., 2004). These air contaminants include criteria pollutants, such as carbon monoxide (CO), nitrogen dioxide (NO₂), sulfur dioxide (SO₂), particulate matter with aerodynamic diameter $\leq 2.5 \mu\text{m}$ (PM_{2.5}) and $\leq 10 \mu\text{m}$ (PM₁₀), and lead. Burning also emits other air toxics, such as heavy metal elements, polychlorinated and polybrominated dioxins and furans, and polycyclic aromatic hydrocarbons (PAHs) (Velis and Cook, 2021; Wiedinmyer et al., 2014). Many of these pollutants are carcinogenic or mutagenic; they may cause immunological and developmental impairments and lead to respirable and cardiovascular diseases. It is estimated that exposure to PM_{2.5} from open burning of solid waste causes at least 270,000 premature deaths in the world every year (Williams et al., 2019; Kodros et al., 2016). In addition, open burning emits large amounts of carbon dioxide (CO₂) and light absorbing carbon (including black carbon [BC]), two of the largest climate forcers to global warming (Bond et al., 2013; IPCC, 2013).

Despite the global health crisis and potential climate impacts caused by uncontrolled solid waste open burning, the quantity of pollutant emissions is uncertain. Due to lack of data, household solid waste open burning emissions are not often included in regional, national, or global emission inventories (Wiedinmyer et al., 2014). Estimating household waste burning emissions faces two challenges: 1) it is difficult to estimate when, where, and how much burning occurs (activities); and 2) few studies have systematically quantified representative open burning emission factors (EFs; i.e., amount of pollutant emitted per kg of fuel burned).

Several approaches have been used to derive EFs. The Intergovernmental Panel on Climate Change (IPCC, 2006) calculates CO₂ EFs from carbon content in several categories of solid waste fuels. Bond et al. (2004) used a single PM₁₀ EF value of 30 g kg⁻¹ to represent all solid waste open burning when establishing a global inventory of black and organic carbon emissions. The U.S. Environmental Protection Agency (U.S. EPA) tested solid waste emissions

when compiling and validating EFs in its AP-42 Compilation of Air Emissions Factors (U.S. EPA, 1992; Gerstle and
65 Kemnitz, 1967; Lemieux, 1997, 1998). However, many of the fuels do not represent modern waste materials and the
applied measurement technologies are outdated. Other studies acquired laboratory emissions for several waste
categories, such as shredded tires, plastic bags, and mixed garbage (Stockwell, 2016; Yokelson et al., 2013; Cheng et
al., 2020) and several field measurements were conducted in Nepal and China (Stockwell et al., 2016; Jayarathne et
al., 2018; Wu et al., 2021). While EFs for biomass burning are available, data for other waste categories, particularly
70 those in Africa, are scant (Rabaji, 2019; Kwatala et al., 2019). Developing more reliable EFs that represent open
burning conditions has been identified as a research priority to reduce harm from solid waste open burning (Cook and
Velis, 2021).

To improve emission inventories, this study conducted comprehensive laboratory combustion experiments to
determine household solid waste burning emissions. The tested waste materials were collected from a Waste
75 Collection Interventions (WCI) program implemented by SASOL, a petrochemical and energy company in South
Africa, to assist the Zamdela local community in MSW collection and disposal in landfills to minimize open burning
and improve air quality in communities near SASOL facilities. EFs for criterial pollutants from smoldering and
flaming phases as well as the entire combustion process are reported for ten waste materials representing commonly
disposed of in South Africa.

80 **2 Method**

2.1 Waste Materials

The mass distribution of common waste material categories that are burned in South Africa townships is shown
in Fig. 1. Vegetation had the highest weight percent (33.3%), followed by plastics (20%) and paper (19.5%). Examples
of major waste categories included in this study are illustrated in Supplemental Fig. S1. Due to difficulties in
85 preserving and importing food discards and vegetation, local substitutes (Nevada, USA) were used. Food waste was
represented by a mixture of bread, potato and banana peels, lettuce, cucumbers, and tomatoes (Cronje et al, 2018).
Vegetation samples were collected in Nevada to represent similar species in South Africa, including basin wild rye,
Sandberg bluegrass, crested wheat grass, red willows, and creeping wild rye, typical of African bunch grasses, African
sumac, and crab grass. EFs for glass, metals, and ceramics were not separately measured as they do not combust or
90 degrade at open burning temperatures. However, to simulate their potential effects on combustion, these discards were
included in the laboratory testing with combined waste materials. Ten types of waste categories/conditions were tested:
1) paper; 2) leather/rubber; 3) textile; 4) plastic bottles and food containers (hard plastics); 5) plastic bags (soft
plastics); 6) dry vegetation (0% moisture content); 7) natural vegetation (20% moisture content); 8) damp vegetation
(50% moisture content); 9) food discards; and 10) combined materials. The combined materials were mixtures of all
95 categories based on their mass fractions in Fig. 1. Each category was tested at least three times, except that the
vegetations with 20% and 50% moisture content were each tested twice.




Figure 1: Mass fraction of municipal solid waste categories collected by Sasol’s Waste Collection Interventions (WCI) program in Zamdela, South Africa.

100 Because fuel moisture content affects combustion behavior and emissions (Rein et al., 2008; Chen et al., 2010), the moisture contents of waste materials were measured right after field collection, ranging 0.5–35% (Table S1). To account for moisture changes during shipping and storage, all materials (except food discards) were oven dried at 90 °C for 24 hours. A calculated amount of distilled deionized water (DDW) was then added to the dried materials to achieve the natural moisture levels shown in Table S1. These moisturized materials were sealed in airtight bags to
 105 equilibrate for at least 24 hours before testing. Fresh food discards were tested without drying/re-moisturizing to avoid irreversible changes. The moisture content for the combined waste was calculated as the sum of the mass-weighted moisture content in individual waste category.

Table S2 shows the major elemental compositions (i.e., carbon [C], hydrogen [H], nitrogen [N], sulfur [S], and oxygen [O]) of the waste materials measured by an elemental analyzer (Model Flash EA1112, Thermo Scientific).
 110 Plastic bags (84%) and plastic bottles (64%) have higher carbon contents than other materials (33–48%). These carbon contents fall within the IPCC (2006) range for all materials except the leather/rubber category: 33% (this study) vs. 67% (IPCC, 2006). The single synthetic leather/rubber piece (a car floor mat) measured in this study may not be representative of all such materials available elsewhere. Unlike other waste categories, IPCC (2006) does not give a range of carbon content for leather/rubber, indicating a need for a wider range of testing for this category. The textile
 115 category contained the highest nitrogen (8%) and sulfur (0.71%) contents, while most other materials yielded sulfur contents below the minimum detection limit. The paper category had the highest oxygen content (44%), followed by vegetation and food discards (41–42%). The lowest (~3%) oxygen was found for soft plastic bags.

After combustion, the ash was weighed to calculate its mass fraction related to the original dry material mass, ranging from 2% to 58% (Table S3). The C, H, N, and S content of the ash was also measured by the elemental analyzer, and the ash carbon content was used in the EF calculation.

2.2 Combustion Experiments

The experimental setup is shown in Fig. 2, similar to the ones used in previous studies (Chen et al., 2010; Chow et al., 2019; Tian et al., 2015; Wang et al., 2019, 2020b). Key specifications for gas and particle measurement instruments are listed in Table S4. For each experiment, a small amount (0.5 – 20 g) of waste material was placed in a ceramic crucible inside a woodstove, then quickly heated to and maintained at 450 °C by a temperature-controlled heater to simulate large scale open burning. The heater accounts for open burning temperatures surrounding the fuel materials that could be much higher than those produced by laboratory fuels (Chen et al., 2010; Chow et al., 2019). Flammable waste materials (i.e., paper, textile, plastic bags, dry and natural moist vegetations, and combined wastes) were ignited by an electric heat gun or a butane lighter. For nonflammable materials (i.e., leather/rubber, plastic bottles, damp vegetation, and food discards), smoldering emissions were measured when the materials were heated to 450 °C. Each test started with about 5-minute sampling of background concentrations and ended when pollutant concentrations returned to baselines. Elapsed time varied from 1000 to 4000 s for each burn, with typical run times of 30 min per sample. An exhaust fan drew fresh air through the stove inlet and vented the smoke above the roof via the stack. Temperature and relative humidity (RH) of the exhaust air were monitored by a hygrometer (Model HH314A, Omega). A web camera inside the stove recorded the combustion process.

During combustion, major fuel components of C, H, N, and S are oxidized to generate carbon dioxide (CO₂), carbon monoxide (CO), water (H₂O), oxides of nitrogen (NO_x), sulfur dioxide (SO₂), volatile organic compounds (VOCs), and particulate matter (PM) (Akagi et al., 2011). The air sample was extracted from the stack through a sampling line and directed to a suite of gas and particle analyzers (Table S4). CO₂ was measured by a CO₂ analyzer (Model 840A; Li-Cor). CO was measured by a CO analyzer (Model 48i, ThermoFisher Scientific), which is designated as a federal equivalent method (FEM) by the U.S. Environmental Protection Agency (U.S. EPA). SO₂ was measured by a FEM SO₂ analyzer (Model 43i, ThermoFisher Scientific). Nitric oxide (NO), nitrogen dioxide (NO₂), and NO_x were measured by a FEM NO/NO₂/NO_x analyzer (Model APNA-360, Horiba Ltd). An emission analyzer (Model 350 XL, Testo Inc.) provided redundant measurements of CO₂, CO, SO₂, NO, and NO₂, in order to accommodate high concentrations in the event that the FEM analyzers were saturated. In addition, the Testo also measured oxygen (O₂), temperature (T), and pressure (P). Size segregated PM mass concentrations were acquired every second by an aerosol monitor (Model DustTrak DRX, TSI Inc.) in five size fractions (i.e., PM₁, PM_{2.5}, PM₄, PM₁₀, and PM₁₅) (Wang et al., 2009). Gas and particle analyzers were calibrated before and after experiments. All analyzer responses were quality checked to ensure readings were within their measurement ranges.




Figure 2: Experimental setup for solid waste combustion.

PM_{2.5} and PM₁₀ samples were collected on Teflon-membrane and quartz-fiber filters. The gravimetric mass concentrations were used to calibrate the real-time mass concentrations by the DRX. Organic and elemental carbon (OC and EC) were analyzed from the quartz-fiber filters using the DRI Model 2015 Multiwavelength Carbon Analyzer following the IMPROVE_A protocol (Chow et al., 2007; Chen et al., 2015). Detailed chemical composition of PM_{2.5} analyzed from the filters, particle size distribution by the Electrical Low Pressure Impactor (ELPI⁺), and particle light scattering and absorption by the Photoacoustic Soot Spectrometer (PASS-3) will be reported in future publications.

2.3 Data Analysis

Data from real-time gas and particle analyzers were assembled and mapped to a common time stamp with one-second time resolution. Time series of gas and particle concentrations were aligned to account for their different transport and response times. Calibration factors were applied to each analyzer. Modified combustion efficiency (MCE) was calculated as

$$MCE = \frac{\Delta CO_2}{\Delta CO_2 + \Delta CO} \quad (1)$$

165 where ΔCO_2 and ΔCO are CO_2 and CO concentrations above background concentrations. MCE provides a real-time indicator of the combustion phase (i.e., $MCE \geq 0.9$ for flaming and $MCE < 0.9$ for smoldering) (Reid et al., 2005; Yokelson et al., 1996; Wang et al., 2020a).

Fuel-based emission factors ($EF_{p,i}$) were calculated based on carbon mass balance as (Wang et al., 2019; Chen et al., 2007; Moosmüller et al., 2003):

$$170 \quad EF_{p,i} = \left(CMF_{fuel} - \frac{m_{ash}}{m_{fuel}} CMF_{ash} \right) \frac{C_p}{C_{CO_2} \left(\frac{M_C}{M_{CO_2}} \right) + C_{CO} \left(\frac{M_C}{M_{CO}} \right) + C_{PM}} \times 1000 \quad (2)$$

where $EF_{p,i}$ is the emission factor of pollutant p from waste material i in g per kg of fuel. CMF_{fuel} is the carbon mass fraction of the fuel in g carbon per g of fuel (Table S2), and CMF_{ash} is the carbon mass fraction of the ash in g carbon per g of ash (Table S3). m_{ash} and m_{fuel} are the mass of ash and fuel in g, respectively. C_p is the mean plume concentration of pollutant p in $g\ m^{-3}$ averaged over the calculation period (i.e., flaming, smoldering, or entire combustion process); and C_{CO} and C_{CO_2} are the mean concentrations of CO_2 and CO in $g\ m^{-3}$, respectively. C_{PM} is the mean total carbon (TC = OC + EC) concentration in PM_{10} in $g\ m^{-3}$. M_C , M_{CO_2} and M_{CO} are the atomic or molecular weights of carbon, CO_2 , and CO in g per mole, respectively. The factor of 1000 converts mass from kilograms to grams. Eq. (2) assumes that the carbon mass in emissions other than CO_2 , CO , and PM_{10} is negligible, which is a reasonable assumption for such burns. However, it is recognized that some carbon will be emitted as methane (CH_4) and VOCs, causing the EFs determined by Eq. (2) slightly overestimated. For waste materials that had both flaming and smoldering combustions, the split points between the two phases were determined from the burn video recording and MCE. $EF_{p,i}$ for flaming, smoldering, and the entire burning process were calculated. Means and standard deviations of $EF_{p,i}$ for each waste category and/or burn condition were calculated from repeated tests.


3 Results and Discussion

185 3.1 Evolution of Air Pollutants during Combustion

Time series plots of criteria pollutant concentrations, along with photographs of the waste materials, ash, and sample filters for each waste category are presented in Supplementary Section S3 to provide more details on the emission evolution, flaming vs. smoldering phases, ash contents, and potential light absorption properties for each fuel. Results for plastic bottles and bags are presented below to illustrate experimental findings from smoldering- and flaming-dominated combustions, respectively.

195 Trial burns with ~5 g of mixed plastic bottles generated very high PM concentrations that clogged filters and overloaded real-time particle sampling instruments. The final tests utilized 0.5 g of this material moisturized to 0.54% water content (Fig. S13a). As shown in Fig. 3, smoldering started ~100 s after initial heating with low CO_2 and CO concentrations. PM emissions were the highest among all the waste materials, likely formed from condensation of semivolatile thermal decomposition products, such as carboxylic acids and hydroxyl esters including phthalates (Sovová et al., 2008; Holland and Hay, 2002). The MCE was only ~0.6 during most duration of the burn, indicating low combustion efficiencies. NO_x concentrations were only slightly above the background levels during the peak

emission period, likely due to the low combustion temperatures, low nitrogen content of the plastic bottles (Table S2), and a small quantity of materials burned.



200


Figure 3: Time series of emissions during a plastic bottle burning experiment.

For the plastic bag experiment, 5 g of mixed soft plastic bags (Fig. S16a) were prepared with 0.54% moisture content. Flaming started at ~150 s after ignition, causing all pollutant concentrations to increase (Fig. 4). In contrast to the smoldering-only plastic bottle combustion, flaming dominated the soft plastics combustion, generating ~20 times higher CO₂ and CO concentrations. The shaded area in Fig. 4 shows the period during which flame was visible from the video camera. The MCE was high (> 0.94) during most parts of burn, indicating high combustion efficiencies. Plastic bags produced the highest CO₂ and the lowest CO EF_s among all test materials, consistent with the high MCEs due to their high C and H content (Table S2). Due to the higher combustion temperatures, NO_x concentrations during plastic bag burning were also higher than those in plastic bottles burning. Only a small amount of ash (3.4%) remained after combustion (Fig. S16b).

210

Among the ten waste types, paper, textile, soft plastic bags, vegetations with dry and natural moisture contents, and combined waste had both flaming and smoldering phases. Leather/rubber, plastic bottles, damp vegetation, and food discards only smoldered. Ash residues were the highest for rubber (~58%) (Table S3), consistent with its high fraction of elements other than C, H, N, S, and O (Table S2). Similar flaming-dominated burns were found for vegetations with 0% and 20% moisture content (Figs. S20 and S21), in contrast to the smoldering dominated 50% moist vegetation that charred but did not flame (Fig. S22). The mean MCEs for 0%, 20%, and 50% moisture content vegetations were ~0.92, 0.9, and 0.8, respectively, signifying the role of the moisture in the combustion efficiency (Chen et al., 2010).

215




220 **Figure 4: Time series of emissions during a plastic bag burning experiment. The shaded areas indicate flaming stage.**

3.2 PM_{2.5}, PM₁₀, and Particulate Carbon

Figure 5 shows high correlations ($R^2 = 1$) between PM_{2.5} and PM₁₀ mass for 30 sample sets. The linear regression slopes indicate that PM_{2.5} constituted ~93% of PM₁₀, consistent with findings for combustion emissions reported in the literature (e.g., U.S. EPA, 1992; Lemieux, 1997).

225 Since the DRX measures PM concentration based on light scattering and its conversion from the scattering signal to mass concentration depends on particle refractive index, density, and size distribution, the DRX concentrations need to be calibrated with gravimetric concentrations (Wang et al., 2009). The mean DRX and gravimetric PM_{2.5} and PM₁₀ mass concentrations are highly correlated with R^2 of 0.95–0.96 (Fig. S2). The DRX measured mass concentrations were about twice of those by gravimetry (slopes of 1.88 for PM_{2.5} and 1.82 for PM₁₀). The DRX had
 230 an internal custom photometric calibration factor (PCF) of 1.0 and size calibration factor (SCF) of 1.7. The higher DRX reported concentrations are expected because the standard calibration uses Arizona Road Dust (ARD) with a density of 2.65 g cm⁻³ (Wang et al., 2009) while the major compositions of the combustion particles are OC and EC, which have lower densities (~1.8 and 1.1–1.4 g cm⁻³, respectively) (Schmid et al., 2009). The DRX concentrations are normalized to the gravimetric PM_{2.5} and PM₁₀ concentrations for EF calculations.




235

Figure 5: Comparison of PM_{2.5} and PM₁₀ mass concentrations measured from the Teflon-membrane filters.

Carbon is the most abundant PM_{2.5} component. As shown in Fig. 6, TC contributed 70±11% (ranging 51–94%) of PM_{2.5} mass, with higher OC found in smoldering dominated materials (i.e., rubber, plastic bottles, damp vegetation, and food discards). The EC fraction increased during flaming combustion, particularly for plastic bags and combined materials. Since PM₁₀ is only ~7% higher than PM_{2.5} (Fig. 5), it is reasonable to assume that PM_{2.5} and PM₁₀ have comparable TC fractions. The C_{PM} in Eq. (2) was calculated from the TC fraction in PM_{2.5} (Fig. 6) multiplied by the PM₁₀ mass concentration.

The properties and abundances of OC and EC affect the optical properties of PM emissions. Photographs of sample filters in the insert of Fig. 6 and in Section S3 show that particles from flaming-dominated combustion of textiles, plastic bags, and combined materials have grey to black coloration due to high EC abundances. Some OC-abundant filters do not show colors (e.g., rubber and plastic bottles) or show yellow/brown colors (e.g., paper, damped vegetation, and food discards), suggesting the presence of different amount of brown carbon (Andreae and Gelencsér, 2006; Chen et al., 2021). Quantitative analysis of particle optical properties will be reported in a separate publication.



250 **Figure 6: Mass percent of organic carbon (OC) and elemental carbon (EC) in PM_{2.5}. The error bar indicates the uncertainty of total carbon (TC = OC + EC), calculated as the larger of the analytical uncertainty and standard deviation of multiple runs. The top row insert shows photographs of representative PM_{2.5} quartz-fiber filters collected from burning of each material.**

3.3 Emission Factors (EF) for Criteria Pollutants

255 The percentages of consumed waste materials and emissions during flaming and smoldering phases for each category are listed in Table 1. Mean EFs for criteria pollutants are reported in Table 2 for flaming and smoldering phases, as well as for the entire combustion process. The relative standard deviations (RSD) of total EFs from multiple tests of each material were within 50% of the mean, showing reproducibility. Except for plastic bags that have high EFs due to high carbon fuel content, total CO₂ EFs are relatively consistent for materials that have both flaming and smoldering phases (i.e., paper, textile, dry and natural vegetation, and combined waste), with an RSD of 3% and an ANOVA test p-value of 0.20, in part due to similar fuel carbon contents as shown in Table S2 (RSD = 6%). Several exceptions with high RSD (e.g., NO_x for textile and plastic bottles) were due to fuel material heterogeneity or low emission levels. The RSD for the flaming phases and smoldering phases were higher than those for the entire burns due to a somewhat subjective split between the two phases. Table 3 compares EFs from this study with those reported in the literature for similar fuel materials.

260

265

For paper, most of the fuel (76%) was consumed in the flaming phase (Table 1), consistent with elevated CO₂ concentrations (Fig. S4). Approximately 65–85% of pollutants were emitted in the flaming phase except for CO, which was emitted about equally in both phases. EFs for CO in the smoldering phase were ~4 times of those in flaming phase. EFs for paper combustion are scarce in the literature (Table 3). Results from this study are close to these reported by Cheng et al. (2020). The EFs for PM_{2.5} and PM₁₀ are higher than other studies; Park et al. (2013) reported an order of magnitude lower EFs than this study. Paper briquettes used in the Marshall Islands (Thai et al., 2016; Xiu

270

et al., 2018) likely have different combustion behaviors compared to the open burning of loose paper; therefore, and the EFs are not considered to be comparable.

275 The car floor mat synthetic rubber sample only smoldered without flaming, leading to low CO₂ and high PM EFs (Table 2). A large fraction (58%) of material was unburned as ash with a 13% carbon content (Table S3). Field and laboratory studies of tire burning emissions (Ryan, 1989; Downard et al., 2015; Stockwell, 2016) report higher EFs than those found here for most pollutants, but PM₁₀ EFs are similar.

280 Textile burning consumed 78% of the mass and emitted 60–90% pollutants in the flaming phase except for ~20% more CO emissions in the smoldering phase (Table 1). While EFs for CO₂ and SO₂ were higher in the flaming phase, EFs for CO and PM were higher in the smoldering phase (Table 2). Textile burning had the highest EFs for NO_x and SO₂ among all tested materials, consistent with higher nitrogen and sulfur contents (Table S1). Wesolek and Kozlowski (2002) measured gas emissions during thermal decomposition of natural and synthetic fabrics at 450, 550, and 750 °C. The EFs for CO₂ and CO from this study fall within the ranges of those reported for different fabrics (Table 3). EFs for NO_x and SO₂ are higher in this study, likely due to differences in material compositions. EFs from this study are also higher than those reported by Cheng et al. (2020).

290 The plastic bottles only smoldered, yielding the lowest CO₂ EFs and among the highest CO and PM EFs (Table 2). Most fuel carbon was turned into PM and volatile organics (strong odor). In contrast, flaming dominated plastic bag combustion, consuming ~99% of the fuel mass and contributing to over 90% of emissions (Table 1). Among all waste materials, plastic bags had the highest CO₂ EFs due to their high carbon content (Table S1) and high combustion efficiencies. Similar high efficiency combustion of plastic bags is reported by Stockwell (2016). Plastic bag EFs are in the same range as literature values. Note that the literature has a wide range of PM EFs (Table 3), likely due to different plastic materials and burning conditions (Park et al., 2013; Lemieux et al., 2004; Oberacker et al., 1992; Stockwell et al., 2016; Jayarathne et al., 2018; Stockwell, 2016; Wu et al., 2021).

300 The flaming phase for vegetations with 0% and 20% moisture content consumed ~70% of the fuel mass and emitted over 70% of pollutants, except that ~60–75% of the CO was emitted during smoldering (Table 1). The damp 50% moisture content vegetation emitted 26% less CO₂, but a factor of 3 and 20–30 higher CO and PM, respectively, as compared to the drier vegetations. Most of the published vegetation emissions lack information on moisture content. Some studies with fuels relevant to South Africa are compared in Table 3 (Christian et al., 2010; Akagi et al., 2011; Santiago-De La Rosa et al., 2018; Yokelson et al., 2009; Ni et al., 2015; EMEP/EEA, 2019). The EFs are consistent with those of low moisture contents measured in this study. In particular, EFs for CO₂, CO, and SO₂ derived here are in good agreement with those derived for Savanna vegetation (Akagi et al., 2011). The EFs for PM from damp vegetation burning were about one order of magnitude higher than literature values.

305 Food discards did not flame due to high moisture contents in fresh vegetables and fruits, resulting in lower EFs for CO₂ and higher EFs for CO and PM (Table 2). Food discards are often included in municipal/household waste, but no separate EFs for food discard burning have been found in the literature.

Flaming-dominated combustion of the combined materials consumed 81% of the fuel mass and emitted over 75% of the pollutants, except that 62% of the CO was emitted during smoldering (Table 1). Combined waste combustion was efficient and MCE for most of the burn period was higher than 0.90 (Fig. S29). The EFs for combined waste fall

310 within the EF ranges of the individual waste categories, but with lower EFs for PM (Table 2). Considering the wide
variety of waste materials and burn practices, EFs are expected to vary over a wide range. Interestingly, as shown in
Table 3, with the exception of an old (1967) test in the USA (U.S. EPA, 1992; Gerstle and Kemnitz, 1967) with a
“below average” data quality rating and the study by Park et al. (2013) which showed consistently lower EFs than
other studies, most other studies show reasonable consistency in EFs (Lemieux, 1997, 1998; Christian et al., 2010;
Stockwell et al., 2016; Jayarathne et al., 2018; Akagi et al., 2011; Reyna-Bensusan et al., 2018; Wiedinmyer et al.,
315 2014; Yokelson et al., 2013; Stockwell, 2016; Cheng et al., 2020). EFs for CO₂ and CO from this study agree
remarkably well with data suggested for global emission inventory development (Akagi et al., 2011; Reyna-Bensusan
et al., 2018; Wiedinmyer et al., 2014).

Table 2 shows that CO₂ EFs are 10–25% higher for flaming compared to smoldering and are lowest for smoldering
only combustions, while CO EFs are 4–9 times higher for smoldering than for flaming. Figure S3a and b show that
320 overall, CO₂ increased with MCE while CO decreased with MCE, although there were large variations among fuel
materials. Among the tested materials, textile has the highest nitrogen and sulfur contents, resulting in the highest EFs
for NO_x and SO₂. EFs for NO_x are generally higher in the smoldering phase (except for vegetation), probably due to
the time required for fuel nitrogen to be oxidized and released. Due to larger fuel influences, NO_x emissions do not
show a strong pattern as a function of MCE (Fig. S3c). EFs for SO₂ are generally higher in the flaming phase (except
325 for plastic bags). Figure S3d shows that EFs for PM_{2.5} do not show a strong correlation with MCE. Over two-fold
higher EFs are found in smoldering than flaming of textile and plastic bags, with less variations between the two
phases for paper, vegetation, and combined materials (Table 2).

Table 1: Percentage of consumed fuel and emissions during flaming and smoldering phases.

Fuel	Burn Type	Relative Fraction of Fuel Burned and Emissions in Flaming and Smoldering Phases (%)								
		Burned Fuel Mass	CO ₂	CO	NO	NO ₂	NO _x	SO ₂	PM _{2.5}	PM ₁₀
Paper	Flaming	76 ± 8	77 ± 7	46 ± 18	72 ± 12	64 ± 16	68 ± 14	84 ± 5	69 ± 22	69 ± 22
	Smoldering	24 ± 8	23 ± 7	54 ± 18	28 ± 12	36 ± 16	32 ± 14	16 ± 5	31 ± 22	31 ± 22
Leather/ Rubber	Flaming	No Flaming Phase								
	Smoldering	100								
Textile	Flaming	78 ± 8	81 ± 6	41 ± 19	75 ± 19	76 ± 18	75 ± 19	90 ± 2	61 ± 23	60 ± 23
	Smoldering	22 ± 8	19 ± 6	59 ± 19	25 ± 19	24 ± 18	25 ± 19	10 ± 2	39 ± 23	40 ± 23
Plastic Bottles	Flaming	No Flaming Phase								
	Smoldering	100								
Plastic Bags	Flaming	99 ± 0	99 ± 0	93 ± 2	96 ± 2	93 ± 2	94 ± 2	96 ± 2	97 ± 3	97 ± 3
	Smoldering	1 ± 0	1 ± 0	7 ± 2	4 ± 2	7 ± 2	6 ± 2	4 ± 2	3 ± 3	3 ± 3
Vegetation (0% mc*)	Flaming	72 ± 4	75 ± 4	26 ± 1	80 ± 3	77 ± 5	80 ± 3	94 ± 1	87 ± 8	87 ± 8
	Smoldering	28 ± 4	25 ± 4	74 ± 1	20 ± 3	23 ± 5	20 ± 3	6 ± 1	13 ± 8	13 ± 8
Vegetation (20% mc*)	Flaming	70 ± 3	72 ± 1	43 ± 18	77 ± 0	81 ± 1	79 ± 0	94 ± 2	91 ± 4	91 ± 4
	Smoldering	30 ± 3	28 ± 1	57 ± 18	23 ± 0	19 ± 1	21 ± 0	6 ± 2	9 ± 4	9 ± 4
Vegetation (50% mc*)	Flaming	No Flaming Phase								
	Smoldering	100								
Food Discards	Flaming	No Flaming Phase								
	Smoldering	100								
Combined	Flaming	81 ± 0	83 ± 1	38 ± 2	75 ± 2	83 ± 3	78 ± 2	97 ± 1	82 ± 8	82 ± 8
	Smoldering	19 ± 0	17 ± 1	62 ± 2	25 ± 2	17 ± 3	22 ± 2	3 ± 1	18 ± 8	18 ± 8

*mc: fuel moisture content

Table 2: Measured emission factors (mean ± standard deviation) for waste materials tested in this study.

Fuel	Burn Type	Mean MCE	Emission Factor (g kg ⁻¹ fuel)									
			CO ₂	CO	NO (as NO ₂)	NO ₂	NO _x (as NO ₂)	SO ₂	PM _{2.5}	PM ₁₀		
Paper	Flaming	0.96 ± 0.03	1530 ± 24	26.2 ± 6.9	0.58 ± 0.04	0.42 ± 0.15	1.00 ± 0.15	0.68 ± 0.58	12.05 ± 3.28	12.19 ± 3.70		
	Smoldering	0.87 ± 0.04	1406 ± 22	101.2 ± 13.3	0.81 ± 0.51	0.86 ± 0.53	1.66 ± 1.00	0.33 ± 0.08	15.21 ± 6.96	15.16 ± 6.67		
	Total	0.90 ± 0.02	1498 ± 7	44.9 ± 3.2	0.63 ± 0.16	0.52 ± 0.19	1.14 ± 0.31	0.57 ± 0.41	13.31 ± 0.77	13.42 ± 1.21		
Rubber	Flaming	0.92 ± 0.02	456 ± 41	28.1 ± 3.9	0.31 ± 0.15	2.75 ± 4.44	3.06 ± 4.59	0.16 ± 0.04	141.34 ± 23.01	153.19 ± 20.26		
	Smoldering	0.92 ± 0.02	456 ± 41	28.1 ± 3.9	0.31 ± 0.15	2.75 ± 4.44	3.06 ± 4.59	0.16 ± 0.04	141.34 ± 23.01	153.19 ± 20.26		
	Total	0.92 ± 0.02	456 ± 41	28.1 ± 3.9	0.31 ± 0.15	2.75 ± 4.44	3.06 ± 4.59	0.16 ± 0.04	141.34 ± 23.01	153.19 ± 20.26		
Textile	Flaming	0.97 ± 0.01	1540 ± 129	27.3 ± 8.9	9.53 ± 1.95	1.17 ± 0.19	10.70 ± 5.58	4.43 ± 2.12	37.20 ± 22.65	42.78 ± 31.32		
	Smoldering	0.86 ± 0.03	1227 ± 59	149.5 ± 34.5	11.57 ± 8.73	1.19 ± 0.53	12.76 ± 9.87	1.68 ± 0.45	75.56 ± 15.33	87.55 ± 24.71		
	Total	0.87 ± 0.03	1467 ± 104	54.9 ± 7.4	10.37 ± 3.72	1.21 ± 0.15	11.58 ± 6.57	3.72 ± 1.48	47.04 ± 16.83	53.95 ± 26.96		
Plastic Bottles	Flaming	0.56 ± 0.05	182 ± 42	90.4 ± 10.6	0.22 ± 0.26	0.12 ± 0.08	0.35 ± 0.34	0.22 ± 0.02	651.00 ± 38.45	722.47 ± 17.98		
	Smoldering	0.56 ± 0.05	182 ± 42	90.4 ± 10.6	0.22 ± 0.26	0.12 ± 0.08	0.35 ± 0.34	0.22 ± 0.02	651.00 ± 38.45	722.47 ± 17.98		
	Total	0.56 ± 0.05	182 ± 42	90.4 ± 10.6	0.22 ± 0.26	0.12 ± 0.08	0.35 ± 0.34	0.22 ± 0.02	651.00 ± 38.45	722.47 ± 17.98		
Plastic Bags	Flaming	0.98 ± 0.00	2938 ± 26	21.0 ± 5.1	0.70 ± 0.17	0.72 ± 0.04	1.42 ± 0.14	0.08 ± 0.01	33.48 ± 9.22	36.01 ± 9.62		
	Smoldering	0.89 ± 0.01	2506 ± 247	183.9 ± 13.7	3.74 ± 0.82	6.87 ± 2.62	10.61 ± 3.15	0.36 ± 0.17	85.75 ± 76.56	89.47 ± 76.47		
	Total	0.94 ± 0.01	2934 ± 24	22.4 ± 5.4	0.72 ± 0.17	0.77 ± 0.06	1.50 ± 0.12	0.08 ± 0.01	34.00 ± 8.55	36.55 ± 8.88		
Vegetation (0% mc ^a)	Flaming	0.97 ± 0.01	1573 ± 11	21.0 ± 3.6	2.94 ± 0.42	0.40 ± 0.15	3.34 ± 0.21	0.72 ± 0.14	3.80 ± 1.07	3.60 ± 0.83		
	Smoldering	0.84 ± 0.02	1366 ± 18	156.2 ± 13.6	1.87 ± 0.16	0.29 ± 0.03	2.17 ± 0.12	0.12 ± 0.02	1.70 ± 1.68	1.57 ± 1.48		
	Total	0.88 ± 0.01	1515 ± 12	58.5 ± 4.8	2.64 ± 0.32	0.37 ± 0.12	3.01 ± 0.11	0.54 ± 0.08	3.20 ± 1.25	3.02 ± 1.01		
Vegetation (20% mc ^a)	Flaming	0.93 ± 0.04	1549 ± 14	34.7 ± 8.1	2.42 ± 0.13	0.74 ± 0.12	3.16 ± 0.24	0.76 ± 0.10	5.40 ± 1.00	5.56 ± 1.14		
	Smoldering	0.87 ± 0.02	1390 ± 7	135.5 ± 15.2	1.43 ± 0.08	0.47 ± 0.09	1.90 ± 0.01	0.20 ± 0.08	5.88 ± 7.27	6.18 ± 7.68		
	Total	0.91 ± 0.03	1505 ± 1	63.9 ± 3.3	2.17 ± 0.07	0.64 ± 0.07	2.82 ± 0.13	0.56 ± 0.07	4.80 ± 1.98	4.97 ± 2.16		
Vegetation (50% mc ^a)	Flaming	0.79 ± 0.00	1124 ± 0	183.6 ± 0.7	1.64 ± 0.15	0.25 ± 0.04	1.88 ± 0.19	0.28 ± 0.05	87.57 ± 6.83	92.66 ± 7.24		
	Smoldering	0.79 ± 0.00	1124 ± 0	183.6 ± 0.7	1.64 ± 0.15	0.25 ± 0.04	1.88 ± 0.19	0.28 ± 0.05	87.57 ± 6.83	92.66 ± 7.24		
	Total	0.79 ± 0.00	1124 ± 0	183.6 ± 0.7	1.64 ± 0.15	0.25 ± 0.04	1.88 ± 0.19	0.28 ± 0.05	87.57 ± 6.83	92.66 ± 7.24		
Food	Flaming	0.89 ± 0.01	955 ± 30	76.1 ± 7.6	1.71 ± 0.34	0.27 ± 0.01	1.98 ± 0.34	0.16 ± 0.02	82.97 ± 18.36	87.23 ± 20.76		
	Smoldering	0.89 ± 0.01	955 ± 30	76.1 ± 7.6	1.71 ± 0.34	0.27 ± 0.01	1.98 ± 0.34	0.16 ± 0.02	82.97 ± 18.36	87.23 ± 20.76		
	Total	0.89 ± 0.01	955 ± 30	76.1 ± 7.6	1.71 ± 0.34	0.27 ± 0.01	1.98 ± 0.34	0.16 ± 0.02	82.97 ± 18.36	87.23 ± 20.76		
Combined	Flaming	0.98 ± 0.00	1443 ± 8	14.9 ± 0.7	1.66 ± 0.14	0.63 ± 0.03	2.29 ± 0.16	1.13 ± 0.15	6.94 ± 2.32	7.34 ± 2.36		
	Smoldering	0.88 ± 0.02	1302 ± 28	105.1 ± 11.0	2.40 ± 0.19	0.55 ± 0.09	2.95 ± 0.26	0.17 ± 0.06	6.55 ± 3.01	6.95 ± 3.22		
	Total	0.91 ± 0.01	1417 ± 8	31.6 ± 1.8	1.80 ± 0.11	0.61 ± 0.00	2.41 ± 0.11	0.95 ± 0.13	6.86 ± 2.08	7.26 ± 2.12		

^amc: fuel moisture content

Table 3: Comparison of emission factors from this study with those reported in the literature.

Ref.	Region	Fuel	Emission Factor (g kg ⁻¹ fuel)					Method	
			CO ₂	CO	NO _x (as NO ₂)	SO ₂	PM _{2.5}		PM ₁₀
			Paper						
This study	South Africa	Paper	1498 ± 7	44.9 ± 3.2	1.14 ± 0.31	0.57 ± 0.41	13.31 ± 0.77	13.42 ± 1.21	Lab
(Park et al., 2013)	South Korea	Paper					0.6 (0.25–0.8)	0.93 (0.73–1.13)	Lab
(Thai et al., 2016; Xiu et al., 2018)	Marshall Islands	Paper brquettes		112	5.7		2.0		Lab
(Cheng et al., 2020)	China	Paper	1400±100	66.6±11.5	3.3±0.3	0.30±0.07	10.56±1.52		Barrel
(Cheng et al., 2020)	China	Paper	1000±100	34.1±6.7	2.3±0.2	0.20±0.08	5.81±0.39		Pile
(Wu et al., 2021)	China	Paper packaging					4.90±1.12		Field
			Leather/Rubber/Tires						
This study	South Africa	Car floor mat	456 ± 41	28.1 ± 3.9	3.06 ± 4.59	0.16 ± 0.04	141.34 ± 23.01	153.19 ± 20.26	Lab
(Ryan, 1989)	USA	Chunk tire						108–119	Lab
(Ryan, 1989)	USA	Shredded tire						119–179	Lab
(Downard et al., 2015)	USA	Shredded tires				7.1±8.3	5.35±5.39		Field
(Stockwell, 2016)	USA	Shredded tire	2882±14	70.6±6.4	7.81	26.2±2.2			Lab
			Textile/fabric						
This study	South Africa	Mixed fabrics	1467 ± 104	54.9 ± 7.4	11.58 ± 6.57	3.72 ± 1.48	47.04 ± 16.83	53.95 ± 26.96	Lab
(Wesolek and Kozlowski, 2002)	Poland	Natural fabrics	850–1300	50–215	0.15–0.43	0.1–1.1			Lab
(Wesolek and Kozlowski, 2002)	Poland	Synthetic fabrics	1000–1750	21–139	0.1–0.33	0.06–0.07			Lab
(Cheng et al., 2020)	China	Textile	1200±98	37.5±7.4	2.1±0.1	0.10±0.03	9.27±0.61		Barrel
(Cheng et al., 2020)	China	Textile	800±68	19.6±3.0	0.6±0.1	0.10±0.02	5.56±0.42		Pile
			Plastics						
This study	South Africa	Plastic bottles	182 ± 42	90.4 ± 10.6	0.35 ± 0.34	0.22 ± 0.02	651.00 ± 38.45	722.47 ± 17.98	Lab
This study	South Africa	Plastic bags	2934 ± 24	22.4 ± 5.4	1.50 ± 0.12	0.08 ± 0.01	34.00 ± 8.55	36.55 ± 8.88	Lab

Ref.	Region	Fuel	Emission Factor (g Kg ⁻¹ fuel)						Method		
			CO ₂	CO	NO _x (as NO ₂)	SO ₂	PM _{2.5}	PM ₁₀			
(Park et al., 2013)	South Korea	Plastics						0.5		Lab	
(Lemieux et al., 2004; Oberncker et al., 1992)	USA	Agricultural plastic film						(0.1–0.85)	1.5	Lab	
(Stockwell et al., 2016; Jayaramne et al., 2018)	Nepal	Chip bags	2249	15.9	4.30	bdl ^a		50±9	(0.6–2.4)	5.7	Field
(Stockwell et al., 2016; Jayaramne et al., 2018)	Nepal	Plastics	2473–2695	16.6–62.2	5.31	bdl ^a		84±13			Field
(Stockwell, 2016)	USA	Plastic bag	3127	11.7	2.69						Lab
(Wu et al., 2021)	China	Plastic woven bags						2.60±0.46			Field
(Wu et al., 2021)	China	Plastic packaging						2.61±0.45			Field
(Wu et al., 2021)	China	Plastic foam						34.8±4.5			Field
Vegetation											
This study	South Africa	Vegetation (0% mc³)	1515 ± 12	58.5 ± 4.8	3.01 ± 0.11	0.54 ± 0.08		3.20 ± 1.25	3.02 ± 1.01		Lab
This study	South Africa	Vegetation (20% mc³)	1505 ± 1	63.9 ± 3.3	2.82 ± 0.13	0.56 ± 0.07		4.80 ± 1.98	4.97 ± 2.16		Lab
This study	South Africa	Vegetation (50% mc³)	1124 ± 0	183.6 ± 0.7	1.88 ± 0.19	0.28 ± 0.05		87.57 ± 6.83	92.66 ± 7.24		Lab
(Christian et al., 2010)	Mexico	Barley stubble	1602	118							Field
(Akagi et al., 2011)	Africa	Savanna vegetation	1686±38	63±17	6.0±1.2	0.48±0.27		7.17±3.42			Data synthesis
(Akagi et al., 2011)	Global	Crop residue	1585±100	102±33	4.8±2.4			6.26±2.36			Data synthesis
(Santiago-De La Rosa et al., 2018)	Mexico	Alfalfa	1052±144	65.23±5.38				9.98 ± 0.71	11.11±0.91		Lab
(Santiago-De La Rosa et al., 2018)	Mexico	Barley	1693±84	33.31±2.33				1.19 ± 0.10	1.77±0.19		Lab
(Santiago-De La Rosa et al., 2018)	Mexico	Bean	1230±38	65.92±3.5				2.24 ± 0.19	2.75±0.18		Lab
(Santiago-De La Rosa et al., 2018)	Mexico	Cotton	1690±76	75.81±4.1				8.22 ± 0.54	13.37±1.9		Lab
(Santiago-De La Rosa et al., 2018)	Mexico	Maize	1748±81	34.61±2.04				2.70 ± 0.28	3.3±0.42		Lab
(Santiago-De La Rosa et al., 2018)	Mexico	Rice	1651±54	81.12±3.25				3.04 ± 0.24	4.95±0.52		Lab
(Santiago-De La Rosa et al., 2018)	Mexico	Sorghum	1851±58	155.71±4.77				11.30 ± 1.05	21.56±2.26		Lab

Ref.	Region	Fuel	Emission Factor (g Kg ⁻¹ fuel)						Method
			CO ₂	CO	NO _x (as NO ₂)	SO ₂	PM _{2.5}	PM ₁₀	
(Santiago-De La Rosa et al., 2018)	Mexico	Wheat	1812±103	28.85±1.79			2.54 ± 0.39	4.07±0.51	Lab
(Yokelson et al., 2009)	Mexico	Crop residues	1676±50	75.04±25.81	7.21±2.69				Field
(Yokelson et al., 2009)	Mexico	Deforestation	1656±38	82.68±14.21	7.20±2.72				Field
(Ni et al., 2015)	China	Wheat straw	1311±181	47.9±13.5			11.4±4.9		Lab
(Ni et al., 2015)	China	Rice straw	1393±91	57.2±26.0			8.5±6.7		Lab
(Ni et al., 2015)	China	Corn stalk	1363±154	52.1±17.7			12.0±5.4		Lab
(EMEP/EEA, 2019)	USA	Agricultural waste		55.83	3.18	0.11	4.19	4.51	Lab
			Mixed household/municipal waste						
This study	South Africa	Combined waste	1417 ± 8	31.6 ± 1.8	2.41 ± 0.11	0.95 ± 0.13	6.86 ± 2.08	7.26 ± 2.12	Lab
(U.S. EPA, 1992; Gersfle and Kemnitz, 1967)	USA	Municipal refuse	615	42	3	0.5		8 (TSP) ^c	Lab
(Lemieux, 1997, 1998)	USA	Household waste (no recycle)					14.8–20.07	16.23–21.28	Barrel
(Lemieux, 1997, 1998)	USA	Household waste (recycle)					3.58–6.93	4.18–7.46	Barrel
(Christian et al., 2010)	Mexico	Landfill garbage	1367±65	45.3±22.8			10.5±8.8		Field
(Park et al., 2013)	South Korea	Household solid waste					0.78 (0.48–0.98)	1.2 (0.3–1.9)	Lab
(Stockwell et al., 2016; Jayarathne et al., 2018)	Nepal	Mixed garbage	1602±142	84.7±55.5	3.39±0.21	bdl ^b	7.37±1.22		Field
(Jayarathne et al., 2018)	Nepal	Damp mixed garbage					124±23 82±13		Field
(Akagi et al., 2011; Reyna-Bensusan et al., 2018; Wiedimyer et al., 2014)	Global	Mixed garbage	1453±69	38±19	5.7±2.3	0.5	9.8±5.7	11.9	Data synthesis
(Yokelson et al., 2013)	USA	Mixed garbage	1341	28.7	1.35	0.77	10.8		Lab
(Stockwell, 2016)	USA	Mixed household refuse	1793±28	31.5±6.9	1.57±0.41	0.897			Lab
(Cheng et al., 2020)	China	Mixed waste	1230±95	55.1±10.5	2.4±0.3	0.50±0.08	10.53±1.24		Barrel
(Cheng et al., 2020)	China	Mixed waste	1000±70	25.9±4.9	1.2±0.1	0.20±0.05	6.04±0.91		Pile

^anc: moisture content^bddl: below detection limit^cTSP: total suspended particulate

3.4 Effects of Ash and Particulate Carbon Content on EF Calculation

Carbon contents in the ash or PM emissions (Eq. (2)) are rarely included in fuel-based EF calculations (Stockwell et al., 2016; Christian et al., 2010; Jayarathne et al., 2018; Wang et al., 2019; Chen et al., 2007). Their impacts are assumed to be negligible but have not been systematically evaluated. Table 4 demonstrates the importance of carbon in ash
 345 $\left(\frac{m_{ash}}{m_{fuel}} CMF_{ash}/CMF_{fuel}\right)$ and PM $\left(C_{PM}/\left[C_{CO_2}\left(\frac{M_c}{M_{CO_2}}\right) + C_{CO}\left(\frac{M_c}{M_{CO}}\right) + C_{PM}\right]\right)$ in EF calculations using Eq. (2). Without including ash and/or PM carbon, changes in EFs are <5% for flaming dominated combustion of paper, plastic bags, vegetation with 0% and 20% moisture content, and combined materials. These fuels had <5% fuel carbon in ash and <5% emitted carbon in PM.

350

Table 4: Emission factor changes relative to Eq. (2) when the carbon in the PM (C_{PM}) or ash (CMF_{ash}) are not included.

Fuel	Fuel Carbon in Ash	Emitted Carbon in PM ₁₀	EF Changes relative to Eq. (2)		
			With Ash Without C _{PM}	Without Ash With C _{PM}	Without Ash Without C _{PM}
Paper	1.1 ± 0.3%	1.9 ± 0.3%	1.9%	1.1%	3.1%
Rubber	22.6 ± 1.0%	46.5 ± 4.5%	87.0%	29.1%	141.4%
Textile	2.1 ± 0.4%	9.4 ± 6.6%	10.4%	2.2%	12.8%
Plastic Bottle	6.4 ± 3.8%	85.2 ± 1.9%	576.6%	6.9%	623.1%
Plastic Bag	0.4 ± 0.1%	3.7 ± 0.6%	3.8%	0.4%	4.3%
Vegetation (0% mc ^a)	1.2 ± 0.4%	0.5 ± 0.1%	0.5%	1.2%	1.7%
Vegetation (20% mc ^a)	1.2 ± 0.2%	0.7 ± 0.3%	0.7%	1.2%	1.9%
Vegetation (50% mc*)	1.0 ± 0.2%	12.7 ± 0.1%	14.5%	1.1%	15.7%
Food	2.5 ± 0.6%	13.6 ± 2.8%	15.7%	2.5%	18.7%
Combined	1.1 ± 0.5%	1.5 ± 0.5%	1.5%	1.2%	2.7%

^amc: fuel moisture content

The consequences of not including ash or PM carbon are larger for smoldering fuels. Due to their high EFs of carbonaceous PM, the errors caused by not including PM carbon are over 10%. Rubber had the highest fuel carbon (22.6%) in the ash, and
 355 excluding ash in Eq. (2) results in a 29.1% overestimation of EFs. Rubber had 46.5% carbon emitted as TC in PM; excluding C_{PM} causes an EF overestimation of 87%. If neither ash nor PM carbon is included, the EFs are overestimated by 141%. The hard plastic bottle EFs are also affected by carbon contents. Because of the very high EFs for carbonaceous PM and relatively

low EFs for CO and CO₂, 85% of the carbon was emitted as PM. Not including C_{PM} results in an EF overestimation of 577%; in addition, if ash carbon is not included, the EFs are overestimated by 623%.

360 This result shows that ash and PM carbon cannot be neglected in EF calculations, particularly for smoldering combustion with high carbon contents in ash and/or PM emissions. Carbon can also be emitted as gaseous hydrocarbons and excluding it in Eq. (2) may result in some overestimation of the EFs. While it is expected that the hydrocarbon carbon content is lower than that in CO and CO₂ in most cases, it may not be negligible when their emissions are high. Future studies should measure total hydrocarbons for more accurate EF determination.

365 3.5 Discussion: Emission Factors for Solid Waste Open Burning Emission Inventories

One application of EFs is to estimate emission rates for establishing emission inventories (U.S. EPA, 1992). These inventories are used to conduct air quality modeling, track long-term trends, evaluate control strategy effectiveness, and provide offsets for other emitters. For example, emissions avoided by trucking the normally open burned household solid waste to landfill by Sasol's WCI can be estimated as:

$$370 E_p = AR \times EF_p = \sum_{i=1}^n AR_i \times EF_{p,i} \quad (3)$$

where E_p is total avoided emission of pollutant p (in metric tons per year); AR is the activity rate, i.e., the amount of burned waste avoided in a year (in tons per year); and EF_p is the emission factor (in grams of emissions per gram of waste) of pollutant p from the waste that would otherwise be burned. The subscript i corresponds to values for each waste material (e.g., paper, textile, plastics, and vegetation). EF_p corresponds to the measured EFs from the combined waste materials; it can also be estimated by summing $EF_{p,i}$ for individual waste materials, weighted by their mass fractions (Fig. 1). $EF_{p,i}$ can be determined from laboratory testing under controlled conditions, and the heterogeneity of waste materials can be accounted for by examining the waste refuse. The separation of flaming and smoldering EFs offers additional flexibility in accounting for burning condition changes. However, it should be cautioned that the burning behaviors differ between separated and combined waste materials, causing emissions to change. Table S5 compares the measured EFs for the combined materials and the values calculated from $EF_{p,i}$. The calculated EFs agree with the measured values within 10% for CO₂ and NO_x; however, the calculated EFs for CO and PM are over 50% and 600% higher, respectively. It is possible that more efficient combustion in the combined materials lowered CO and PM emissions as compared to less efficient individual burns, particularly for materials that only smoldered and had high EFs for CO and PM. Additionally, laboratory measured $EF_{p,i}$ or EF_p might differ from field values given the complex waste mixtures and burning conditions. Adjustments to laboratory $EF_{p,i}$ might be needed when estimating real-world EF_p . Future studies comparing in situ measurement from a variety of representative real-world burns with laboratory data would assist in establishing adjustment factors.

385

4 Conclusions

This study measured criteria pollutant emissions from simulated combustion of different household solid waste materials representative of those in open burnings in South Africa. EFs vary with waste composition and combustion conditions. Data
390 from this study fill EF gaps for paper, leather/rubber, textile, and food discards burning that have been scarcely reported in the literature. EFs for vegetation and mixed waste materials from this study are within the ranges reported in the literature. These EFs can be used to improve emission inventories for household and municipal solid waste open burning emissions in South Africa and other countries.

Emissions are closely related fuel elemental compositions. Among the tested materials, plastic bags have the highest
395 carbon content and the highest combustion efficiency, leading to the highest EFs for CO₂. Textiles have the highest abundances of nitrogen and sulfur, resulting in the highest EFs for NO_x and SO₂. Combustion behaviors and emissions are also affected by fuel moisture content. EFs for vegetation with three moisture content: dry (0%), natural (20%), and damp (50%) were measured. Emissions were similar for 0% and 20% moisture content; however, EFs for CO and PM from the vegetation with 50% moisture content are 3 and 20–30 times, respectively, those from 0% and 20% moisture content.

This study reports three sets of EF_s (i.e., flaming, smoldering, and entire combustion), which can be applied to estimate
400 emissions based on waste burning characteristics. It also reports EFs for individual and combined waste categories. These data offer flexibility in calculating emission rates depending on waste composition and burning characteristics. However, caution should be exerted when using mass weighted sum of individual waste category EFs to calculate combined waste EFs as the combustion behavior might be different between individual and combined waste materials. This study shows that neglecting
405 the carbon in ash and/or PM may lead to significant overestimation of EFs.

EF data from this study were obtained from controlled laboratory tests simulating real-world open burning conditions. Real-world open burning emissions vary with waste material composition, pile size, packing structure, moisture content, ambient temperature, and wind speed. Such variations are reflected in the wide range of EFs reported in the literature. Although this and past studies agree within reported extremes, laboratory tests are an approximation of real-world variations. The EFs
410 derived from laboratory experiments represent the values obtained under the specific conditions in laboratory tests; adjustment might be needed when real-world burning conditions are very different from laboratory test conditions.

Data availability. Data are available at: Wang, X., 2023, "Data for: Air Pollutant Emissions from Open Burning of Household Solid Waste from South Africa", <https://doi.org/10.7910/DVN/QTV9YW>, Harvard Dataverse, V1. Additional data is available upon request.

415 **Author contributions.** XW, JCC, and JGW designed the study; HF conducted the combustion experiments; XW and HF performed the data analyses and prepared the original paper draft; WC and SDV provided waste materials and resources; all authors reviewed and edited the paper.

Competing interests. None.

420 **Financial support.** This research was partially funded by SASOL and partially by the Desert Research Institute internal funding.

Acknowledgements: The authors thank Matthew Claassen of DRI for collecting vegetations for testing.

References

- Akagi, S. K., Yokelson, R. J., Wiedinmyer, C., Alvarado, M. J., Reid, J. S., Karl, T., Crounse, J. D., and Wennberg, P. O.: Emission factors for open and domestic biomass burning for use in atmospheric models, *Atmos. Chem. Phys.*, 11, 4039-4072, 10.5194/acp-11-4039-2011, 2011.
- 425 Andreae, M. O. and Gelencsér, A.: Black carbon or brown carbon? The nature of light-absorbing carbonaceous aerosols, *Atmos. Chem. Phys.*, 6, 3131-3148, 2006.
- Bond, T. C., Streets, D. G., Yarber, K. F., Nelson, S. M., Woo, J.-H., and Klimont, Z.: A technology-based global inventory of black and organic carbon emissions from combustion, *J. Geophys. Res.*, 109, D14203, 10.1029/2003jd003697, 2004.
- 430 Bond, T. C., Doherty, S. J., Fahey, D. W., Forster, P. M., Berntsen, T., DeAngelo, B. J., Flanner, M. G., Ghan, S., Kärcher, B., and Koch, D.: Bounding the role of black carbon in the climate system: A scientific assessment, *Journal of geophysical research: Atmospheres*, 118, 5380-5552, 2013.
- Chen, L.-W. A., Chow, J. C., Wang, X., Cao, J., Mao, J., and Watson, J. G.: Brownness of Organic Aerosol over the United States: Evidence for Seasonal Biomass Burning and Photobleaching Effects, *Environ. Sci. Technol.*, 55, 8561-8572, 10.1021/acs.est.0c08706, 2021.
- 435 Chen, L.-W. A., Verburg, P., Shackelford, A., Zhu, D., Susfalk, R., Chow, J. C., and Watson, J. G.: Moisture effects on carbon and nitrogen emission from burning of wildland biomass, *Atmos. Chem. Phys.*, 10, 6617-6625, doi:10.5194/acp-10-6617-2010, 2010.
- Chen, L.-W. A., Chow, J. C., Wang, X. L., Robles, J. A., Sumlin, B., Lowenthal, D. H., Zimmermann, R., and Watson, J. G.: Multi-wavelength optical measurement to enhance thermal/optical analysis for carbonaceous aerosol, *Atmos. Meas. Tech.*, 8, 451-461, doi:10.5194/amt-8-451-2015, 2015.
- 440 Chen, L.-W. A., Moosmüller, H., Arnott, W. P., Chow, J. C., Watson, J. G., Susott, R. A., Babbitt, R. E., Wold, C. E., Lincoln, E. N., and Hao, W. M.: Emissions from Laboratory Combustion of Wildland Fuels: Emission Factors and Source Profiles, *Environ. Sci. Technol.*, 41, 4317-4325, 10.1021/es062364i, 2007.
- 445 Cheng, K., Hao, W., Wang, Y., Yi, P., Zhang, J., and Ji, W.: Understanding the emission pattern and source contribution of hazardous air pollutants from open burning of municipal solid waste in China, *Environ. Pollut.*, 263, 114417, <https://doi.org/10.1016/j.envpol.2020.114417>, 2020.
- Chow, J. C., Watson, J. G., Chen, L.-W. A., Chang, M. C. O., Robinson, N. F., Trimble, D., and Kohl, S.: The IMPROVE_A temperature protocol for thermal/optical carbon analysis: maintaining consistency with a long-term database, *Journal of the Air & Waste Management Association*, 57, 1014-1023, 2007.
- 450

- Chow, J. C., Cao, J. J., Chen, L.-W. A., Wang, X. L., Wang, Q. Y., Tian, J., Ho, S. S. H., Watts, A. C., Carlson, T. N., Kohl, S. D., and Watson, J. G.: Changes in PM_{2.5} peat combustion source profiles with atmospheric aging in an oxidation flow reactor, *Atmos. Meas. Tech.*, 12, 5475-5501, <https://doi.org/10.5194/amt-2019-198>, 2019.
- 455 Christian, T. J., Yokelson, R. J., Cárdenas, B., Molina, L. T., Engling, G., and Hsu, S. C.: Trace gas and particle emissions from domestic and industrial biofuel use and garbage burning in central Mexico, *Atmos. Chem. Phys.*, 10, 565-584, 10.5194/acp-10-565-2010, 2010.
- Cook, E. and Velis, C.: Global review on safer end of engineered life, Royal Academy of Engineering, London, UK, <https://doi.org/10.5518/100/58>, 2021.
- 460 Cronjé, N., Van der Merwe, I., and Müller, I.-M.: Household food waste: A case study in Kimberley, South Africa, *Journal of Consumer Sciences*, 46, 2018.
- Downard, J., Singh, A., Bullard, R., Jayarathne, T., Rathnayake, C. M., Simmons, D. L., Wels, B. R., Spak, S. N., Peters, T., Beardsley, D., Stanier, C. O., and Stone, E. A.: Uncontrolled combustion of shredded tires in a landfill – Part 1: Characterization of gaseous and particulate emissions, *Atmos. Environ.*, 104, 195-204, <https://doi.org/10.1016/j.atmosenv.2014.12.059>, 2015.
- 465 EMEP/EEA: EMEP/EEA air pollutant emission inventory guidebook 2019, European Environmental Agency, Copenhagen, Denmark, 2019.
- Ferronato, N. and Torretta, V.: Waste Mismanagement in Developing Countries: A Review of Global Issues, *Int J Environ Res Public Health*, 16, 10.3390/ijerph16061060, 2019.
- 470 Gerstle, R. W. and Kemnitz, D. A.: Atmospheric Emissions from Open Burning, *Journal of the Air Pollution Control Association*, 17, 324-327, 10.1080/00022470.1967.10468988, 1967.
- Holland, B. J. and Hay, J. N.: The thermal degradation of PET and analogous polyesters measured by thermal analysis–Fourier transform infrared spectroscopy, *Polymer*, 43, 1835-1847, [https://doi.org/10.1016/S0032-3861\(01\)00775-3](https://doi.org/10.1016/S0032-3861(01)00775-3), 2002.
- IPCC: 2006 IPCC guidelines for national greenhouse gas inventories, National Greenhouse Gas Inventories Programme Japan; Intergovernmental Panel on Climate Change (IPCC): Geneva, Switzerland, 2006.
- 475 IPCC: Climate change 2013: The physical science basis. Working Group I Contribution to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change, Cambridge University Press Cambridge, UK, and New York 2013.
- Jayarathne, T., Stockwell, C. E., Bhave, P. V., Praveen, P. S., Rathnayake, C. M., Islam, M. R., Panday, A. K., Adhikari, S., Maharjan, R., Goetz, J. D., DeCarlo, P. F., Saikawa, E., Yokelson, R. J., and Stone, E. A.: Nepal Ambient Monitoring and Source Testing Experiment (NAMaSTE): emissions of particulate matter from wood- and dung-fueled cooking fires, garbage and crop residue burning, brick kilns, and other sources, *Atmos. Chem. Phys.*, 18, 2259-2286, 10.5194/acp-18-2259-2018, 2018.
- 480 Kodros, J. K., Wiedinmyer, C., Ford, B., Cucinotta, R., Gan, R., Magzamen, S., and Pierce, J. R.: Global burden of mortalities due to chronic exposure to ambient PM 2.5 from open combustion of domestic waste, *Environ. Res. Lett.*, 11, 124022, 10.1088/1748-9326/11/12/124022, 2016.
- 485 Kwatala, N., Naidoo, M., Naidoo, S., and Garland, R. M.: Estimated emissions of domestic waste burning in South Africa, 2019 Conference of the National Association for Clean Air, Western Cape, October 3-4, 2019,
- Lebreton, L. and Andrady, A.: Future scenarios of global plastic waste generation and disposal, *Palgrave Communications*, 5, 6, 10.1057/s41599-018-0212-7, 2019.
- 490 Lemieux, P. M.: Evaluation of emissions from the open burning of household waste in barrels - Volume 1. Technical Report, National Risk Management Research Laboratory, US Environmental Protection Agency, Cincinnati, OHEPA-600/R-97-134a, 1997.
- Lemieux, P. M.: Evaluation of emissions from the open burning of household waste in barrels - Project Summary, National Risk Management Research Laboratory, US Environmental Protection Agency, Cincinnati, OH EPA/600/SR-97/134, 1998.
- 495 Lemieux, P. M., Lutes, C. C., and Santoianni, D. A.: Emissions of organic air toxics from open burning: a comprehensive review, *Prog. Energy Combust. Sci.*, 30, 1-32, <https://doi.org/10.1016/j.pecs.2003.08.001>, 2004.
- Moosmüller, H., Mazzoleni, C., Barber, P., Kuhns, H., Keislar, R., and Watson, J.: On-road measurement of automotive particle emissions by ultraviolet lidar and transmissometer: Instrument, *Environ. Sci. Technol.*, 37, 4971-4978, 2003.
- Ni, H., Han, Y., Cao, J., Chen, L.-W. A., Tian, J., Wang, X. L., Chow, J. C., Watson, J. G., Wang, Q., Wang, P., Li, H., and Huang, R.-J.: Emission characteristics of carbonaceous particles and trace gases from open burning of crop residues in China, *Atmos. Environ.*, 123, Part B, 399-406, <http://dx.doi.org/10.1016/j.atmosenv.2015.05.007>, 2015.
- 500

- Oberacker, D. A., Lin, P. C., Shaul, G. M., Ferguson, D. T., Engleman, V. S., Jackson, T. W., Chapman, J. S., Evans, J. D., Martrano, R. J., and Evey, L. L.: Characterization of Emissions Formed from Open Burning of Pesticide Bags, in: Pesticide Waste Management, ACS Symposium Series, 510, American Chemical Society, 78-94, doi:10.1021/bk-1992-0510.ch007 10.1021/bk-1992-0510.ch007, 1992.
- 505 Park, Y. K., Kim, W., and Jo, Y. M.: Release of Harmful Air Pollutants from Open Burning of Domestic Municipal Solid Wastes in a Metropolitan Area of Korea, *Aerosol Air Qual. Res.*, 13, 1365-1372, 10.4209/aaqr.2012.10.0272, 2013.
- Rabaji, O. P.: Waste dumping in Sharpeville (Emfuleni Municipality): an investigation of the characteristics and the potential impacts on air quality, M.S., Environmental Management, North-West University, Potchefstroom, South Africa, 2019.
- 510 Reid, J. S., Koppmann, R., Eck, T. F., and Eleuterio, D. P.: A review of biomass burning emissions part II: intensive physical properties of biomass burning particles, *Atmos. Chem. Phys.*, 5, 799-825, 10.5194/acp-5-799-2005, 2005.
- Rein, G., Cleaver, N., Ashton, C., Pironi, P., and Torero, J. L.: The severity of smouldering peat fires and damage to the forest soil, *CATENA*, 74, 304-309, <https://doi.org/10.1016/j.catena.2008.05.008>, 2008.
- Reyna-Bensusan, N., Wilson, D. C., and Smith, S. R.: Uncontrolled burning of solid waste by households in Mexico is a significant contributor to climate change in the country, *Environ. Res.*, 163, 280-288, 515 <https://doi.org/10.1016/j.envres.2018.01.042>, 2018.
- Ryan, J. V.: Characterization of emissions from the simulated open burning of scrap tires, Acurex Corp., Research Triangle Park, NCEPA-600/2-89-054, 1989.
- Santiago-De La Rosa, N., González-Cardoso, G., Figueroa-Lara, J. d. J., Gutiérrez-Arzaluz, M., Octaviano-Villasana, C., Ramírez-Hernández, I. F., and Mugica-Álvarez, V.: Emission factors of atmospheric and climatic pollutants from crop residues 520 burning, *J. Air Waste Manage. Assoc.*, 68, 849-865, 10.1080/10962247.2018.1459326, 2018.
- Schmid, O., Chand, D., Karg, E., Guyon, P., Frank, G. P., Swietlicki, E., and Andreae, M. O.: Derivation of the density and refractive index of organic matter and elemental carbon from closure between physical and chemical aerosol properties, *Environ Sci Technol*, 43, 1166-1172, 10.1021/es800570p, 2009.
- 525 Sovová, K., Ferus, M., Matulková, I., Španěl, P., Dryahina, K., Dvořák, O., and Civiš, S.: A study of thermal decomposition and combustion products of disposable polyethylene terephthalate (PET) plastic using high resolution fourier transform infrared spectroscopy, selected ion flow tube mass spectrometry and gas chromatography mass spectrometry, *Mol. Phys.*, 106, 1205-1214, 10.1080/00268970802077876, 2008.
- Stockwell, C. E.: Advanced measurements of undersampled globally significant biomass burning sources, Chemistry, The University of Montana, Missoula, MT, 2016.
- 530 Stockwell, C. E., Christian, T. J., Goetz, J. D., Jayarathne, T., Bhawe, P. V., Praveen, P. S., Adhikari, S., Maharjan, R., DeCarlo, P. F., Stone, E. A., Saikawa, E., Blake, D. R., Simpson, I. J., Yokelson, R. J., and Panday, A. K.: Nepal Ambient Monitoring and Source Testing Experiment (NAMaSTE): emissions of trace gases and light-absorbing carbon from wood and dung cooking fires, garbage and crop residue burning, brick kilns, and other sources, *Atmos. Chem. Phys.*, 16, 11043-11081, 10.5194/acp-16-11043-2016, 2016.
- 535 Thai, P., Rahman, M. M., Pourkhesalian, A. M., and Stevanovic, S.: Comparative investigations of combustion emissions from paper briquettes, International Laboratory for Air Quality and Health (ILAQH) at Queensland University of Technology (QUT), 2016.
- Tian, J., Chow, J. C., Cao, J., Han, Y., Ni, H., Chen, L.-W. A., Wang, X. L., Huang, R., Moosmüller, H., and Watson, J. G.: A Biomass Combustion Chamber: Design, Evaluation, and a Case Study of Wheat Straw Combustion Emission Tests, *Aerosol 540 Air Qual. Res.*, 15, 2104-2114, 2015.
- U.S. EPA: Compilation of Air Pollutant Emissions Factors AP-42, Fifth Edition Section 2.5 Open Burning, U.S. Environmental Protection Agency, Research Triangle Park, NCEPA AP-42, 1992.
- Velis, C. A. and Cook, E.: Mismanagement of Plastic Waste through Open Burning with Emphasis on the Global South: A Systematic Review of Risks to Occupational and Public Health, *Environ. Sci. Technol.*, 55, 7186-7207, 545 10.1021/acs.est.0c08536, 2021.
- Wang, Q., Wang, L., Li, X., Xin, J., Liu, Z., Sun, Y., Liu, J., Zhang, Y., Du, W., Jin, X., Zhang, T., Liu, S., Liu, Q., Chen, J., Cheng, M., and Wang, Y.: Emission characteristics of size distribution, chemical composition and light absorption of particles from field-scale crop residue burning in Northeast China, *Sci. Total Environ.*, 710, 136304, <https://doi.org/10.1016/j.scitotenv.2019.136304>, 2020a.

- 550 Wang, X. L., Chancellor, G., Evenstad, J., Farnsworth, J. E., Hase, A., Olson, G. M., Sreenath, A., and Agarwal, J. K.: A Novel Optical Instrument for Estimating Size Segregated Aerosol Mass Concentration in Real Time, *Aerosol Sci. Technol.*, 43, 939-950, 2009.
- Wang, X. L., Zhou, H., Arnott, W. P., Meyer, M. E., Taylor, S., Firouzkhohi, H., Moosmüller, H., Chow, J. C., and Watson, J. G.: Characterization of smoke for spacecraft fire safety, *J. Aerosol Sci.*, 136, 36-47, 555 <https://doi.org/10.1016/j.jaerosci.2019.06.004>, 2019.
- Wang, X. L., Zhou, H., Arnott, W. P., Meyer, M. E., Taylor, S., Firouzkhohi, H., Moosmüller, H., Chow, J. C., and Watson, J. G.: Evaluation of Gas and Particle Sensors for Detecting Spacecraft-Relevant Fire Emissions *Fire Saf. J.*, 113, 1-12, <https://doi.org/10.1016/j.firesaf.2020.102977>, 2020b.
- Wesolek, D. and Kozłowski, R.: Toxic gaseous products of thermal decomposition and combustion of natural and synthetic fabrics with and without flame retardant, *Fire Mater.*, 26, 215-224, 10.1002/fam.800, 2002.
- Wiedinmyer, C., Yokelson, R. J., and Gullett, B. K.: Global Emissions of Trace Gases, Particulate Matter, and Hazardous Air Pollutants from Open Burning of Domestic Waste, *Environ. Sci. Technol.*, 48, 9523-9530, 10.1021/es502250z, 2014.
- Williams, M., Gower, R., Green, J., Whitebread, E., Lenkiewicz, Z., and Schröder, P.: No time to waste: Tackling the plastic pollution crisis before it's too late, Tearfund, London, UK, 2019.
- 565 Wilson, D. C. and Velis, C. A.: Waste management – still a global challenge in the 21st century: An evidence-based call for action, *Waste Management & Research*, 33, 1049-1051, 10.1177/0734242X15616055, 2015.
- Wilson, D. C., Rodic, L., Modak, P., Soos, R., Carpintero, A., Velis, K., Iyer, M., and Simonett, O.: Global waste management outlook, United Nations Environment Programme (UNEP)2015.
- Wu, D., Li, Q., Shang, X., Liang, Y., Ding, X., Sun, H., Li, S., Wang, S., Chen, Y., and Chen, J.: Commodity plastic burning as a source of inhaled toxic aerosols, *J. Hazard. Mater.*, 416, 125820, <https://doi.org/10.1016/j.jhazmat.2021.125820>, 2021.
- 570 Xiu, M., Stevanovic, S., Rahman, M. M., Pourkhesalian, A. M., Morawska, L., and Thai, P. K.: Emissions of particulate matter, carbon monoxide and nitrogen oxides from the residential burning of waste paper briquettes and other fuels, *Environ. Res.*, 167, 536-543, <https://doi.org/10.1016/j.envres.2018.08.008>, 2018.
- Yokelson, R. J., Griffith, D. W. T., and Ward, D. E.: Open-path Fourier transform infrared studies of large-scale laboratory biomass fires, *Journal of Geophysical Research: Atmospheres*, 101, 21067-21080, 10.1029/96jd01800, 1996.
- 575 Yokelson, R. J., Burling, I. R., Gilman, J. B., Warneke, C., Stockwell, C. E., de Gouw, J., Akagi, S. K., Urbanski, S. P., Veres, P., Roberts, J. M., Kuster, W. C., Reardon, J., Griffith, D. W. T., Johnson, T. J., Hosseini, S., Miller, J. W., Cocker III, D. R., Jung, H., and Weise, D. R.: Coupling field and laboratory measurements to estimate the emission factors of identified and unidentified trace gases for prescribed fires, *Atmos. Chem. Phys.*, 13, 89-116, 10.5194/acp-13-89-2013, 2013.
- 580 Yokelson, R. J., Crouse, J. D., DeCarlo, P. F., Karl, T., Urbanski, S., Atlas, E., Campos, T., Shinozuka, Y., Kapustin, V., Clarke, A. D., Weinheimer, A., Knapp, D. J., Montzka, D. D., Holloway, J., Weibring, P., Flocke, F., Zheng, W., Toohey, D., Wennberg, P. O., Wiedinmyer, C., Mauldin, L., Fried, A., Richter, D., Walega, J., Jimenez, J. L., Adachi, K., Buseck, P. R., Hall, S. R., and Shetter, R.: Emissions from biomass burning in the Yucatan, *Atmos. Chem. Phys.*, 9, 5785-5812, 10.5194/acp-9-5785-2009, 2009.

585