



Spatio-temporal patterns and trends of streamflow in water-scarce Mediterranean basins

Laia Estrada^{1,2}, Xavier Garcia^{1,2}, Joan Saló^{1,2}, Rafael Marcé^{1,2,3}, Antoni Munné⁴, Vicenç Acuña^{1,2}

¹Catalan Institute for Water Research (ICRA - CERCA). Carrer Emili Grahit 101, 17003 Girona (Spain)

5 ²University of Girona. Plaça de Sant Domènec 3, 17004 Girona (Spain)

³Current address: Integrative Freshwater Ecology, Centre for Advanced Studies of Blanes (CEAB-CSIC), Blanes (Spain)

⁴Catalan Water Agency (ACA). Carrer Provença 260, 08008 Barcelona (Spain)

Correspondence to: Laia Estrada (lestrada@icra.cat)

10 **Abstract.** The issue of water scarcity, exacerbated by climate change and demographic increase, has become a growing concern in many regions throughout the world. Understanding hydrological behaviour to promote resilient and sustainable water management is paramount. Hydrological models that integrate natural processes and anthropogenic alterations of the basin's hydrology are a powerful tool to support decision-making. We developed a SWAT+ hydrological model including stakeholder expert knowledge on water management and introducing a novel calibration and validation approach suitable for
15 heterogeneous basins in space and / or time. We also assessed spatio-temporal patterns and trends of streamflow during the first two decades of the 21st century in the Catalan River Basin District, in the western Mediterranean, using a wide variety of indicators to fully characterize the hydrological regime. We calibrated and validated the model using data from 50 gauging stations, verifying the usefulness of the new calibration and validation strategy. Co-development with stakeholders and the integration of expert knowledge, most notably on reservoir operations, helped improve model performance. Results revealed
20 a generalized streamflow reduction, as well as increased dominance of streamflow flashiness and zero-flows recurrence. We also observed differences in seasonal trends, with autumn being the most affected season. These results provide insights into how climate change and anthropogenic pressures are going to keep affecting water resources availability in the future, thus raising the need for sustainable management practices in the Catalan River Basin District, as well as other regions vulnerable to water scarcity.

25 1 Introduction

Water scarcity, a situation in which freshwater demands exceed its availability due to climatic or non-climatic factors, is a growing concern in many regions, with half the world's population being subject to severe water scarcity (Caretta et al., 2022). The Mediterranean region is already prone to water scarcity due to its intrinsic high inter-annual rainfall variability, but rising demands and climate change, which includes warming at faster rates than the global mean as well as reduced
30 rainfall, will exacerbate this issue (Cramer et al., 2018).



Promoting sustainable water resources management is thus of great importance to address the challenges brought on by the combined effects of climate change, demographic growth, and overexploitation of resources (Zribi et al., 2020). Using hydrological models to predict water resources availability under different climate and/or management scenarios is thus necessary to identify efficient adaptation measures and support decision-making (Loucks and van Beek, 2017).

35 Despite the potential contribution of hydrological models to the water management sector, their practical implementation remains a challenge (Pezij et al., 2019). In some cases, the main issue is the lack of active involvement from end-users (i.e., stakeholders and water managers) during the model's implementation process, which can lead to the actual management needs not being addressed by the model, or the model's capabilities not being effectively conveyed (Loucks and van Beek, 2017). Co-development with end-users can significantly improve the model through the inclusion of first-hand expert
40 knowledge (e.g., addressing specific needs or simulating more accurate management operations). Additionally, this collaborative approach increases the likelihood of the model being used in the planning and management processes, as end-users become aware of its capabilities and limitations (Højberg et al., 2013; Bots et al., 2011).

Many studies have successfully applied hydrological modelling in watersheds susceptible to water scarcity to characterize streamflow dynamics and evolution (e.g., Swain et al., 2020; Tanner et al., 2022), including in the Mediterranean region
45 (e.g., Brouziyne et al., 2021; De Girolamo et al., 2022). While many studies focus on basins with natural or near-natural flow regimes, it is important to note that larger regulated basins, typically more relevant to water management, are often excluded. Some studies include regulated basins with coupled hydrological-water allocation models (Haro-Monteagudo et al., 2020) or a specific reservoir module (Eekhout et al., 2020). However, these studies perform separate calibrations for the hydrological and the water allocation/reservoir models. Moreover, hydrological calibration is either performed upstream of the reservoirs
50 or using naturalized streamflow data. To our knowledge, there are no studies yet involving an integrated model (i.e., a single model including both hydrological and water allocation processes) calibrated in a single process using both natural and altered flow regimes.

In relation to the calibration process, most model applications rely on streamflow data from one or few gauging stations within the basin. This practice, however, constrains the accuracy and practicality of the calibrated model, especially in larger
55 case studies with heterogeneous rainfall regimes, varying elevation, and diverse land uses (i.e., where spatial and often temporal variability are pronounced). Despite the importance of multi-site calibration for large and/or highly heterogeneous basins being noted, most studies use a limited number of gauging stations, most likely due to data availability (e.g., Pandey et al., 2020; Wang et al., 2012; Wi et al., 2015).

Moreover, the division of data into calibration and validation periods can significantly affect model results. This highlights
60 the importance of selectively choosing those periods, despite the fact that in most studies it is done arbitrarily (Myers et al., 2021), allocating either the first or last recorded years for calibration, and the rest for validation. Although generally it is recommended that both periods are statistically similar (Abbaspour et al., 2018; Dakhlaoui et al., 2019), using distinctly different periods can also be interesting depending on the intended use of the calibrated model. Specifically, when the model is to be applied to future climate and/or land use change scenarios (Daggupati et al., 2015). An alternate approach is to



65 randomize the data splitting to obtain a calibrated model that can be accurately used under conditions that are both similar
and different from those of the calibration period, as well as to ensure that the model performance is not biased by the
allocation of data (Daggupati et al., 2015; Bennett et al., 2013). This is of particular interest for watersheds with spatio-
temporally heterogeneous gauging data, as each individual record presents different lengths and hydrological characteristics.
Selectively choosing the calibration and validation period for each gauging station may be challenging, but the random
70 approach effectively ensures that all spatio-temporal variability is captured across all stations provided that enough data is
available. However, this has not been explored before in large-scale applications with many gauging stations, as generally
only calibration is performed (Chawanda et al., 2020), or the last years of the record are arbitrarily chosen for validation
without considering the statistical similarity (or dissimilarity) between the two periods (Abbaspour et al., 2015; Piniewski
and Okruszko, 2011).

75 As previously stressed, hydrological models can be used to support water managers, but also to identify and analyse
streamflow patterns and trends in ungauged basins, which is of great interest to understand the evolution of hydrologic
dynamics under both natural and anthropogenic pressures. However, many studies addressing this topic only use observed
flows, which can constrain the spatial interpretation of trends. Hydrological models, on the other hand, can bridge this gap
by providing spatially coherent patterns and trends of streamflow (Stahl et al., 2012). At the global level, Gudmundsson et al.
80 (2019) used streamflow observations to identify trends in low, mean and high flows, and Gudmundsson et al. (2021) verified
that observed trends were only reproducible with models if anthropogenic climate change was considered. Both observations
and models show a strong and significant decreasing trend of streamflow in the Mediterranean region, while the opposite is
observed in northern Europe. This fact is also confirmed in studies at the European level using observations (Blöschl et al.,
2019; Masseroni et al., 2021; Stahl et al., 2010) and models (Gudmundsson et al., 2017; Stahl et al., 2012). Local studies
85 have also identified this decreasing trend in the Mediterranean using observations (Folton et al., 2019; Lutz et al., 2016) and
models (Llanos-Paez et al., 2023). Many of these studies only focus on trends in annual streamflow, with some also
evaluating trends on low, high, and monthly flows. However, none delve into trends informing of other key hydrological
regime characteristics than magnitude (i.e., timing, duration, frequency, and rate of change), excluding Folton et al. (2019)
and Llanos-Paez et al. (2023), where trends on the duration and timing of low flows and on the duration, timing and
90 frequency of zero-flows are evaluated, respectively.

The objective of this research is to develop a hydrological model that can serve as a valuable tool in the water management
sector by integrating both physical and anthropogenic processes, including expert knowledge of management operations. We
also introduce a novel calibration and validation strategy, which overcomes the limitations of conventional approaches,
particularly when dealing with relatively large modelling studies involving numerous and spatio-temporal heterogenous
95 gauging stations. Moreover, this new approach can deal with records differing in length and/or with significant gaps, as it
determines calibration and validation periods for each gauging station individually. The widely employed hydrological
modelling Soil Water and Assessment Tool (SWAT) is used, more particularly its revised version SWAT+ (Bieger et al.,
2017). Another objective is to identify and characterize spatio-temporal patterns and trends of streamflow in Mediterranean



basins during the first two decades of the 21st century. This research provides valuable insights into modelling improvements
100 achieved by promoting co-development with end-users and introducing a novel calibration and validation approach. It also
contributes to deepen our understanding of how water-scarce Mediterranean basins behave under changing climatic
conditions and anthropogenic pressures.

2 Material and methods

2.1 Study site

105 The study was performed in the Catalan River Basin District (CRBD), located in the northeastern part of the Iberian
Peninsula (western Mediterranean). It covers an area of over 16,000 km², comprising of several small/medium-sized river
basins, and it is managed as a single River Basin District by the Catalan Water Agency. However, for this study only part of
the CRBD is considered, including the Llobregat, Ter, Fluvià, Besòs, Tordera and Foix basins (Figure 1). This selection was
based on data availability and the overall significance of these basins, as they host most of the water resources and demand
110 in the region.




Figure 1: Location of the CRBD in the Western Mediterranean. The study area has been divided into five SWAT+ models, named after its main river basin.

The elevation within the CRBD ranges from 0 to 2910 m a.s.l. Almost 60% of the area is covered by forests, mainly
115 coniferous, although in the eastern basins broad-leaved forests are dominant, especially sclerophyll forests. Crops are mainly
found in the medium and lower parts of the basins, the most common being barley, wheat, and grape vines. The majority is
rain-fed, with only 3.2% irrigated.



For the period 2001-2022, the CRBD received on average 660 mm of annual precipitation. However, as is characteristic of the Mediterranean climate, there is a high interannual variability, ranging between 480 and 990 mm. There is also a high spatial variability within the CRBD, with annual averages ranging from 900 mm in the Pyrenees to 450 mm in coastal regions.

Water demand within the CRBD exceeds 1000 hm³/year, of which 42 % is for agricultural use, 32 % for domestic use, 10 % for industrial use, and the remaining 15 % for other urban uses (ACA, 2021). Over 7.1 million people live in the CRBD, of which 91 % live within the basins chosen for this study.

2.2 Hydrological modelling with SWAT+

SWAT is a semi-distributed and physically-based ecohydrological model widely used worldwide (Abbaspour et al., 2015; Gassman et al., 2014; Samimi et al., 2020), including many applications in Mediterranean basins (Boithias et al., 2017; Brouziyne et al., 2021; De Girolamo et al., 2022). The upgraded SWAT+ offers an improved spatial representation of hydrological processes and interactions within a watershed (Bieger et al., 2017, 2019), as well as more flexibility in defining management schedules and operations using decision tables (Arnold et al., 2018). SWAT+ has also been successfully used in Mediterranean basins (Pulighe et al., 2021; Castellanos-Osorio et al., 2023; Llanos-Paez et al., 2023).

SWAT+ divides the basin into several sub-basins, which can be further divided into landscape units (LSUs: floodplain and upland), and those into hydrological response units (HRUs), the smallest unit at which hydrological processes are simulated. Each HRU consists of the area within a LSU with a unique combination of land use, soil type and topographic slope (Bieger et al., 2017). Connectivity between spatial objects, including HRUs and LSUs as well as channels, aquifers and reservoirs, can be adjusted by the user to realistically represent the basin's physical characteristics (Bieger et al., 2019).

2.3 Co-development with end-users

We involved end-users (i.e., water managers from the Catalan Water Agency) in the development and implementation of the SWAT+ model for the CRBD. This co-development led to the inclusion of valuable expert knowledge on actual management practices in the CRBD, resulting in a more accurate hydrological model. Notably, we incorporated expert knowledge on actual reservoir release operations into custom-built decision tables. We also included expert knowledge on irrigation, inter-basin water transfers, urban abstractions and point source discharges.

We conducted several meetings to discuss progress on model development, as well as SWAT+ training sessions, in order to help end-users familiarize themselves with the model and its capabilities as a tool to support decision making.

2.4 SWAT+CRBD inputs and configuration

The basic inputs needed to set up a SWAT+ model are a digital elevation model (DEM), land use map, soil map, and weather data. The weather data consists of daily measurements of precipitation, maximum and minimum temperatures, relative humidity, wind speed and solar radiation, as well as a database of monthly statistics to fill in null values. A



150 floodplain map is also required if the LSUs floodplain and upland within a sub-basin are to be separated. The basic inputs used for the SWAT+CRBD model are listed in Table 1. Additional input data, including reservoir operations, cropland management, and point source discharges and abstractions, were also used to enhance the SWAT+CRBD model.

Table 1. SWAT+ input data, resolution, and sources. Weather data include precipitation, maximum and minimum temperature, relative humidity, wind speed, and solar radiation.

SWAT+ inputs	Resolution	Source
Digital Elevation Model	70 m	Cartographic and Geological Institute of Catalonia. Modified to improve stream delineation and adjust resolution. https://www.icgc.cat/en/Downloads/Elevations
Land use map	100 m	CORINE Land Cover 2018. https://land.copernicus.eu/pan-european/corine-land-cover/clc2018
	1 m	Land use map of Catalonia 2018, Cartographic and Geological Institute of Catalonia. https://www.icgc.cat/Descarregues/Mapes-en-format-d-imatge/Cobertes-del-sol
Soil map	250 m	Digital Soil OpenLand Map, WaterITech. https://www.wateritech.com/data
Floodplain map	20 m	Floodable area for T=10y, Catalan Water Agency. https://sig.gencat.cat/visors/VISOR_ACA.html
Weather data	1 day	Meteorological Service of Catalonia (Meteocat) https://www.meteo.cat
	Monthly statistics	Spain weather generator database for SWAT+. https://swat.tamu.edu/data/spain/

2.4.1 Digital elevation model

155 The original DEM had a resolution of 15 m but was modified to improve the delineation of the river network through plain terrain, as well as resampled to a 70 m resolution. The lower resolution is more reasonable to the extent of the CRBD. A threshold of 5 km² of drainage area was used for the channel delineation, however the river network was then manually modified by merging or splitting default river reaches generated by the automatic delineation. The criteria used were the official body masses defined by the Catalan Water Agency, as well as other constraints (i.e., gauging stations, WWTP and
160 industrial point source discharges).

2.4.2 Land use data

The land use map was based on the CORINE Land Cover (CLC) 2018 (EEA, 2018) and adapted to SWAT+ nomenclature. We also used the land cover map of Catalonia (ICGC, 2018) to differentiate between deciduous and sclerophyll broad-leaved forests, as well as more specific crop land uses.

165 2.4.3 Soil data

We used the Digital Soil OpenLand Map (DSOLMap), a newly developed soil map at 250 m resolution, with a detailed six-horizons soil profile, specifically tailored to use with the SWAT+ model (López-Ballesteros et al., 2023).



2.4.4 Floodplain map

We used a floodplain map to differentiate between the LSUs floodplain and upland within a subbasin. We used the floodable
170 area for a return period of 10 years, and we complemented it by using geomorphological criteria in the sections of the river
network where this area was not defined.

2.4.5 Weather data

We have used daily data from 141 meteorological stations spread out across the CRBD for the simulation period 2000-2022.
We used a one-year warmup, as it is the SWAT+ default. Most of the data was provided by the Catalan Water Agency, who
175 previously gathered data from different sources, including the Meteorological Service of Catalonia (SMC), the Spanish
Meteorological Agency (AEMET), and the Ebro Basin Water Authority (CHE). Data for the years 2021-2022 is exclusively
from the SMC (Table 1).

Not all stations have complete records for the period 2000-2022, therefore, the Spain weather generator dataset for SWAT+
was used to fill daily missing values with monthly statistics (Senent-Aparicio et al., 2021).

180 2.4.6 Additional data

We included five reservoirs in the SWAT+CRBD model. Each reservoir has its own decision table where the release
operations are defined according to actual release rules provided by the Catalan Water Agency. There are five possible
release scenarios depending on the reservoir level: water excess, normality, drought alert, exceptional drought, and
emergency. In the first case, the reservoir is full and all daily inputs through the river network are then released. During
185 normality, a fixed daily release rate for every month is defined according to the mean releases from the last five years. For
the rest of the scenarios, the fixed release rate is decreased according to the drought restrictions defined by the Catalan Water
Agency. When possible, the performance of the decision tables was tested in R using real daily inputs and water level, and
the estimated fixed release rates for every scenario/month were calibrated to the median value instead.

WWTP and industrial discharges were included in the SWAT+CRBD model by means of point source objects to account for
190 the added volumes to the river network, as in some smaller rivers their influence is considerable. Abstractions for urban use
were also accounted for with negative point sources.

We have implemented decision tables to manage crop schedules and operations based on plant growth and soil water content
for most of the crops, except for orchards, grape vines, and olive trees, which have a manual harvest operation. Irrigation is
also managed by decision tables as well as the water allocation routines native to SWAT+. Irrigated HRUs are grouped into
195 irrigation districts with its own irrigation source (either a channel, a reservoir, or an aquifer) and a threshold to only allow
water abstraction if this is exceeded (respectively, environmental flow, minimum volume, and minimum water table). On
each simulation day, if water stress in a HRU exceeds a threshold, irrigation demand is defined. We modified the SWAT+
source code so that the irrigation demand is the difference between the potential evapotranspiration and the real

evapotranspiration instead of a fixed volume. If an HRU has an irrigation demand and there is enough water in the irrigation district's source, then this HRU is irrigated.

2.5 Sensitivity analysis

We performed a global sensitivity analysis using the variance-based Fourier amplitude sensitivity test (FAST) method (Cukier et al., 1973) using the R packages Fast (Fast: Implementation of the Fourier Amplitude Sensitivity Test (FAST)) and SWATplusR (Schürz, 2022). Variance-based methods are widely used for parameter sensitivity analysis in hydrological models (Song et al., 2015), including SWAT (Guse et al., 2014) and SWAT+ (Llanos-Paez et al., 2023) applications. For the Llobregat and Ter models, we performed the sensitivity analysis with 30 parameters (Table 2), while for the rest of the SWAT+ models we used 28 as the last two parameters are related to reservoirs, and these models either do not include reservoirs (Besòs-Tordera, Fluvià) or gauging stations are located upstream (Foix). We ran 5763 simulations for the Llobregat and Ter models and 4795 for the rest, as the number of iterations required to determine the sensitivity indices is related to the number of parameters. We used the objective function Kling-Gupta Efficiency (KGE) (Gupta et al., 2009) and considered a parameter sensitive if their partial variance accounted for more than 1 % of the total (Table 2).

Table 2. Parameters used in the sensitivity analysis. For ‘pctchg’ the parameter is altered by a percentage of the default value, while for ‘absval’ the absolute value is replaced. For each sub-model, bolded variances indicate that a parameter is sensitive. Llob.: Llobregat; B-T: Besòs-Tordera.

Parameter	Description	Change	Range		FAST variance (%)				
			Min	Max	Llob.	Ter	B-T	Fluvià	Foix
cn2	Condition II curve number	pctchg	-50	50	786.2	815.8	899.1	755.1	950.9
cn3_swf	Soil water adjustment factor for CN3	absval	0	1	3.0	59.9	30.5	34.9	14.3
ovn	Overland flow Manning's n	pctchg	-50	50	<1	<1	<1	<1	<1
lat_ttime	Lateral flow travel time (days)	absval	0.5	180	2.4	<1	1.9	3.8	<1
latq_co	Lateral flow coefficient	absval	0	1	5.0	20.8	3.0*	25.5	<1
canmx	Maximum canopy storage (mm)	absval	0	100	116.3	2.3	18.6	5.1	24.5
esco	Soil evaporation compensation factor	absval	0	1	<1	<1	<1	1.0	<1
epco	Plant uptake compensation factor	absval	0	1	<1	1.4*	1.3*	1.3*	<1
perco	Percolation coefficient	absval	0	1	1.1	2.1	<1	5.8	<1
z	Depth from soil surface to bottom of layer (mm)	pctchg	-50	50	7.0	19.4	1.5	30.3	<1
bd	Moist bulk density of soil layer (g/cm ³)	pctchg	-50	50	29.9	38.9	26.4	84.4	1.3
awc	Available water capacity of soil layer (mm H ₂ O/mm soil)	pctchg	-50	50	2.1	2.7*	4.0	<1	2.7
k	Saturated hydraulic conductivity of soil layer (mm/hr)	pctchg	-50	50	<1	1.1	<1	3.3	<1
plaps	Precipitation lapse rate (mm/km)	absval	0	200	<1	<1	<1	<1	<1
tlaps	Temperature lapse rate (deg C/km)	absval	-10	10	<1	<1	<1	<1	<1
surlag	Surface runoff lag coefficient	absval	0.05	24	<1	<1	<1	<1	<1
evrch	Reach evaporation adjustment factor	absval	0.5	1	1.2	<1	<1	<1	<1



evlai	Leaf area index at which no evaporation occurs from water surface	absval	0	10	<1	<1	<1	<1	<1
ffcb	Initial soil water storage (fraction)	absval	0	1	1.4	<1	<1	<1	<1
chn	Channel Manning's n	absval	0	0.3	5.9*	1.5	7.8*	2.0*	<1
chk	Channel bottom conductivity (mm/day)	absval	0	1	41.9	34.7	15.9	46.6	4.7
k_res	Hydraulic conductivity of the reservoir bottom (mm/hr)	absval	0	1	<1	<1	-	-	-
evrsv	Lake evaporation coefficient	absval	0	500	<1	<1	-	-	-
alpha	Alpha factor for groundwater recession curve (1/days)	absval	0	1	<1	<1	<1	<1	<1
bf_max	Baseflow rate when the entire area is contributing to baseflow (mm)	absval	0.1	2	<1	<1	<1	<1	<1
deep_seep	Recharge to deep aquifer (fraction)	absval	0.001	0.4	<1	<1	<1	<1	<1
sp_yld	Specific yield for shallow aquifer (m ³ /m ³)	absval	0	0.5	<1	<1	<1	<1	<1
flo_min	Water table depth for return flow to occur (m)	absval	0	50	<1	<1	<1	<1	<1
revap_co	Groundwater revap coefficient (fraction)	absval	0.02	0.2	<1	<1	<1	<1	<1
revap_min	Water table depth for revap to occur (m)	absval	0	50	<1	<1	<1	<1	<1

* Variance assessed for monthly streamflow. These parameters are considered sensitive even though the daily variance is less than 1‰

215 2.6 Calibration and validation

We conducted the model calibration with daily streamflow data obtained from 50 gauging stations distributed across the study area. We calibrated each of the five SWAT+ models independently, respectively using 23, 14, 9, 3 and 1 gauging station for the Llobregat, Ter, Besòs-Tordera, Fluvià, and Foix models (Figure 1). The simulation period is from 2001 to 2022, however, many gauging stations present significant gaps in their records. These gaps in data are characterized by variability in terms of record length and temporal distribution throughout the simulation period. Traditional methods to determine calibration and validation periods involve either discretionarily using a period at the beginning or end for validation and the rest for calibration or selecting statistically similar periods. However, due to the spatial and temporal heterogeneity in our gauged data, these methods are not suitable for our study. To address this, we randomly selected the calibration and validation periods for each station independently. Specifically, we allocated 70% of the records for calibration and reserved 30% for validation. To prevent numerous alternating periods, we introduced the constraint of a single validation window, which can randomly occur at any point within the station's record. Consequently, this approach resulted in one or two calibration periods and one validation period. We assume that with the random approach all spatiotemporal variability is captured. Besides, all bias that might arise during the selection is removed.

For each SWAT+ model and its corresponding sensitive parameters (Table 2), we used Latin hypercube sampling to generate 2000 parameters combinations. Only one calibration iteration was performed, as during the sensitivity analysis we already ran many simulations and further iterations were not expected to yield better results. The model performance was assessed by the objective functions KGE and percent bias (PBIAS). We considered that results were “satisfactory” if KGE > 0.5 and -



25% < PBIAS < 25%, “good” if KGE > 0.65 and -15% < PBIAS < 15%, and “very good” if KGE > 0.75 and -10% < PBIAS < 10% (Moriasi et al., 2007; Odusanya et al., 2021).

235 **2.7 Data analysis**

To identify and characterize spatio-temporal patterns and trends of streamflow in the CRBD, we calculated 40 annual hydrological indicators for each of the 999 SWAT+CRBD river reaches, as well as the annual percentage of reaches that dry at least once for the whole river network (Table 3). We used indicators characterizing low, medium and high flows in relation of their magnitude, frequency, duration, timing and rate of change (Richter et al., 1996; Alcaraz-Hernández et al., 240 2023), as well as several zero-flow indicators to characterize flow intermittency (Llanos-Paez et al., 2023).

Table 3: Hydrological indicators used for the analysis of flow patterns and trends.

Hydrological indicator	Units	Regime characteristics
<u>Medium flows</u>		
Median of daily flow for each month	m ³ /s	Magnitude, timing
Median of annual daily flow	m ³ /s	Magnitude
<u>High flows</u>		
90th percentile of annual daily flow	m ³ /s	Magnitude
Annual maximum daily flow	m ³ /s	Magnitude, duration
3, 7, 30 and 90-day means of maximum daily flow	m ³ /s	Magnitude, duration
Julian date of maximum daily flow	Julian day	Timing
Number of high pulses	Events/year	Frequency
Mean duration of high pulses	Days	Duration
<u>Low flows</u>		
10th percentile of annual daily flow	m ³ /s	Magnitude
Annual minimum daily flow	m ³ /s	Magnitude, duration
3, 7, 30 and 90-day means of minimum daily flow	m ³ /s	Magnitude, duration
Julian date of minimum daily flow	Julian day	Timing
Number of low pulses	Events/year	Frequency
Mean duration of low pulses	Days	Duration
<u>Zero-flows</u>		
Total number of days with zero-flow	Days/year	Duration
Number of periods of consecutive zero-flow days	Events/year	Frequency
Mean duration of zero-flow events	Days	Duration
Julian date of first zero-flow event	Julian day	Timing
Median julian date of zero-flow events	Julian day	Timing
Percentage of river network that dries at least once per year	%	Frequency
<u>General</u>		
Rise rate: means of all positive differences between consecutive days	m ³ /s	Magnitude, rate of change
Fall rate: mean of all negative differences between consecutive days	m ³ /s	Magnitude, rate of change



Number of flow reversals	Reversals/year	Frequency, rate of change
Sum of all annual flow	hm ³	Magnitude

We applied a modified Mann-Kendall test (Yue and Wang, 2004) to identify statistically significant temporal trends with a *p-value* lower than 0.05 while accounting for serial autocorrelation. The Theil-Sen estimator (Theil, 1950; Sen, 1968), hereby referred to as only Sen’s slope, was employed to assess the magnitude of trends. Sen’s slopes for indicators with units of flow (m³/s) were standardized to remove the stronger influence of river segments with higher streamflow, and thus avoid a skewed interpretation of spatial patterns. Both methods have been widely used in hydrology to identify and quantify trends, as demonstrated in prior studies (e.g., Clavera-Gispert et al., 2023; Gudmundsson et al., 2017; Khorchani et al., 2021).

3 Results

3.1 Sensitivity analysis

The FAST sensitivity analysis identified in each SWAT+ model between 6 and 13 sensitive parameters (Table 2). Most of the sensitive parameters are identified in multiple models, and they are mostly related to surface and plant processes (cn2, cn3_swf, canmax, epco), soil processes (latt_ttime, lat_co, esco, perco, z, bd, awc, k) and channel processes (chn, chk).

3.2 Calibration and validation

The comparisons between observed and simulated daily streamflow for representative gauging stations of the main rivers of the CRBD demonstrate good model performance (Figure 2), and the values of the objective functions overall indicate satisfactory results for both the calibration and validation periods (Table 4). For the validation period, KGE values are satisfactory or above both for the daily and monthly timestep, and PBIAS values are good or very good.

Table 4. Kling-Gupta Efficiency (KGE) and percent bias (PBIAS) results for each of the five SWAT+ models that configure SWAT+CRBD, assessed at a daily and monthly timestep for the calibration and validation period.

SWAT+ model	Daily timestep				Monthly timestep			
	Calibration		Validation		Calibration		Validation	
	KGE	PBIAS	KGE	PBIAS	KGE	PBIAS	KGE	PBIAS
Llobregat	0.46	-19.1	0.53	-14.5	0.63	-19.3	0.68	-14.6
Ter	0.48	-8.7	0.51	-10.7	0.77	-9.2	0.82	-10.6
Besòs-Tordera	0.66	0.5	0.70	-5.1	0.87	0.3	0.85	-4.9
Fluvià	0.53	-12.6	0.59	-14.9	0.59	-12.6	0.58	-14.6
Foix	0.55	-5.1	0.74	-13.2	0.76	-3.9	0.71	-13





Figure 2: Observed and simulated daily streamflow for the period 2001-2022 in the six main rivers of SWAT+CRBD. Individual KGE and PBIAS values for both the calibration and validation periods are also shown.



3.3 Analysis of spatial and temporal patterns

265 The analysis of the simulated streamflow for the period 2001-2022 in the CRBD revealed several spatio-temporal patterns and trends (Figures 3-7). The advantage of using simulated streamflow instead of observed is working with 999 values for each indicator instead of only 50 (gauging stations), which allows us to better observe spatial patterns. Moreover, some gauging stations present gaps for the period 2001-2022, so simulated streamflow also provides a complete temporal series.

270 The evolution of the percent of river segments that dry at least once a year for the period 2001-2022 indicates a drying tendency in the CRBD (Figure 3a), which can be positively correlated to an increase in mean annual temperature. While individual annual percentages correlate directly with mean annual rainfall, there is no apparent decreasing trend in the latter. We observe a general decrease in total annual flow, except for the headwaters of the Llobregat basin (Figure 3b). However, this region shows a poorer model adjustment (see discussion on section 4.1), which compromises the reliability of this result.



275 **Figure 3: a) Evolution of annual percentage of river segments that dry at least once a year and mean annual rainfall and temperature. b) Spatial distribution of standardized Sen's slope for the hydrological indicator total annual flow.**

Significant trends in median flow are most generally negative, both in annual (Figure 4a) and seasonal (Figure 4b-e) median flows, being the Llobregat basin the most clearly affected. Autumn is the season with the most widespread negative trends (4e). Positive trends are not as dominant and are generally located in the headwaters, while lower regions of the Ter basin

280 also show positive trends during winter (Figure 4b).




Figure 4: Spatial distribution of standardized Sen's slope for the hydrological indicators annual Q50 (a) and Q50 in January (b), in April (c), in July (d), and in October (e), representative of the different seasonal flow patterns.

285 Negative trends in the magnitude of high flows (90th percentile) are also consistently dominant, although some significant positive trends can also be found mainly in the headwaters of the Llobregat basin (see discussion on section 4.1), as well as some other river segments in the Ter and Fluvià basins (Figure 5a). However, for low flows (10th percentile) most river segments do not present significant trends (Figure 5b), primarily because the 10th percentile threshold is zero in many of these segments. The few significant trends are mostly negative and located in the lower sections of the Llobregat basin and the Besòs basin. Conversely, positive trends can be observed in the headwaters of the Fluvià basin and downstream of the reservoirs in the Ter basin.

290



Concerning the frequency of high and low-flow events, we observe a distinct spatial pattern for the number of high-flow events per year, with positive trends in the north (Pyrenees headwaters) and negative trends in the southern/coastal regions (Figure 5c). Trends for the number of low-flow events are generally non-significant, but segments with significant trends show an increase of annual episodes (Figure 5d). Mean duration of high-flow events generally decreases across the entire study area (Figure 5e), while significant trends for mean duration of low-flow events show a decrease in the Pyrenees/northern regions and an increase in the Besòs, Foix and lower Llobregat basins (Figure 5f).





Figure 5: Spatial distribution of Sen's slope for the hydrological indicators Q90 (a), Q10 (b), number of high and low flow pulses (c, d), and their mean duration (e, f). The Sen's slope for Q90 and Q10 is standardized, while the units for the other indicators are number of events/year (c, d) and days/year (e, f).

300



Despite the general decrease in high flows in the Llobregat basin, the annual maximum daily flow shows an overall positive trend. In other basins, trends vary, with some displaying mixed patterns (Besòs, Foix) and others primarily characterized by non-significant trends or limited negative trends.

Zero-flow indicators complement and expand the information that is not captured with low-flow indicators, as most of the river network shows some degree of intermittency. The number of days with zero-flow per year has notably increased, with Sen's slopes of up to 11 days/year in many segments in the Llobregat and Besòs basins (Figure 6a). There are very few segments, all tributaries of the Ter River, with a decrease of zero-flow days. Trends in the mean duration of zero-flow events show mixed results, but a slight tendency towards shorter and longer zero-flow events can be observed in the southern and northeastern regions respectively (Figure 6b). We observe a general tendency towards an earlier onset of zero-flows, in the scale of several days and up to a week per year (Figure 6c), while more mixed results can be observed for the central point of zero-flows (Figure 6d).




315

Figure 6: Spatial distribution of Sen's slope for the hydrological indicators total annual days with zero-flow (a), mean duration of zero-flow pulses (b), julian day of first zero-flow (c), and median julian day of zero-flows (d). Sen's slope units for all indicators are days/year.



Regarding trends in hydrological indicators informing of the rate of change, there is a clear tendency towards increased rise (Figure 7a) and fall (Figure 7b) rates, except for the Besòs basin. The number of reversals tend to increase in the Pyrenees/northern regions, while they decrease in the Besòs and Foix basins, as well as some notable tributaries in the Llobregat basin (Figure 7c).



320

Figure 7: Spatial distribution of Sen's slope for the hydrological indicators rise rate (a), fall rate (b) and number of flow reversals (c). The former's units are number of reversals/year for the last indicator, while the Sen's slope is standardized for the rise and fall rates indicators.

4 Discussion

325 4.1 Shifting integrative hydrological modelling

Before proceeding with the discussion of the results, several considerations concerning the followed approach should be discussed. As highlighted in the introduction, the incorporation of anthropogenic activities in hydrological modelling plays a crucial role in accurately capturing watershed dynamics and supporting decision-making. We integrated anthropogenic activities in our SWAT+ model such as crop scheduling, irrigation, urban water abstractions, discharges from wastewater treatment plants and industries, water transfers between basins, and reservoir release operations. The last one is especially

330



important due to the profound impact of reservoirs on natural flow regimes both regarding timing and magnitude. We used expert knowledge on how releases are managed to construct custom decision tables for each reservoir. However, actual releases depend on other factors besides the ones that can be included in decision tables, such as hydropower demand and preventive releases for flood risk mitigation. As a result, our approach approximates real management operations, much like
335 the other anthropogenic factors in our model, which are also based on estimations and generalizations. Another consideration on model inputs is the fact that land use change during the simulation period is not considered in our study, assessing instead only the climatic and direct anthropogenic effect on streamflow.

We introduced a novel approach to unbiasedly determine the calibration and validation periods suitable for case studies where gauging data is abundant but spatio-temporally heterogenous. We consider that, given the high number of gauging
340 stations in our study, randomly determining the calibration and validation periods for each station effectively captures all spatio-temporal variability in both periods. Thus, a bootstrapping method to repeatedly resample the calibration and validation periods, which is time consuming and would imply running many more iterations, is not necessary. However, the validity of this consideration could be further explored in future applications, as well as other approaches based on statistically similarities in cases where gauging data is less abundant and a random split would not be sufficient.
345 Hydrological indicators, such as the ones used in this research to identify trends, or techniques such as persistent homology (Musa et al., 2022), could be used to characterize hydrological behaviour or gauged data and define statistically similar calibration and validation periods. Even though we explored using such methods in our study, it would have required analyses for each individual gauging station, as well as developing a more complex methodology with uniform selecting criteria, and ultimately, we assumed that for our study the random approach would be sufficient to capture the spatio-
350 temporal variability.

The calibration and validation results are satisfactory overall (Table 4) and for many of the gauging stations, however, some gauging stations show poorer results. This might be due to the quality/length of the recorded data and the spatio-temporal distribution of weather stations within the draining area. Some gauging stations present periods with incongruous data, which have been removed, but some less evidently inconsistent data may remain and affect model performance. Moreover, in
355 stations with shorter records the calibration and validation periods might end up being too different from each other due to the random approach, and this could also affect the performance of individual gauging stations, despite their reduced weight in determining overall results. Another important factor affecting local model performance is the inaccuracy of the default SWAT+ aquifer module in accurately representing hydrogeological processes. The integration of complex hydrogeological processes and their interaction with surface water in hydrological is required to more accurately simulate watershed
360 dynamics (Frey et al., 2021). Future studies should prioritize the refinement of models to better capture these intricate processes, using for example the more advantageous gwflow module for SWAT+ (Bailey et al., 2020). One region with poorer performance, as it has been noted in the results section, is the headwaters of the Llobregat basin, due to it being a mountainous heterogenous area with complex karstic geology, as well as not having enough coverage of meteorological stations to properly capture the complex rainfall distribution.



365 The last consideration does not concern the model but rather the spatio-temporal analysis of streamflow patterns and trends. A modified Mann-Kendall test was used to account for temporal autocorrelation, but spatial autocorrelation (i.e., the effect that upstream segments have on downstream segments) was not considered in the analysis. We explored the possibility of removing spatial autocorrelation (e.g., using spectral clustering), as it could provide insights into factors influencing streamflow aside from network connectivity, but ultimately, we deemed it non-relevant for the purpose of this paper's analysis. However, further studies could expand on removing spatial autocorrelation as complementary information to conventional analysis.

4.2 Patterns and trends of streamflow

The analysis of patterns and trends of streamflow for the first two decades of the 21st century in the CRBD has revealed an overall trend indicating a reduction of water resources availability, which is consistent with other Mediterranean case studies (Clavera-Gispert et al., 2023; Masseroni et al., 2021). Three main messages can be derived from this research's results: 1) we identified a reduction in streamflow as well as an increase in intermittency; 2) streamflow flashiness has been intensified; and 3) monthly trends reveal that all seasons have not been evenly affected by recent climate change.

4.2.1 Streamflow reduction and increased intermittency

Significant decreasing trends over the CRBD have been identified for medium and high flows (Figure 4a & 5a), as well as total annual streamflow (Figure 3b). There has also been a reduction in high-flow events, except in the Pyrenees/northern region (Figure 5c), as well as in their duration (Figure 5e). The regional positive trend in high-flow events is most probably due to complex spatio-temporal patterns of rainfall distribution (Lana et al., 2021) which produce high-flow events, but the rest of the indicators reveal a decreasing trend in water resources availability, and this decreasing tendency has been predicted to continue during the 21st century (Caretta et al., 2022; Marx et al., 2018). Most trends on low-flow and number of low-flow events are not significant (Figure 5b,d), mainly because the 10th percentile which defines the low-flow threshold is zero in many river segments, but the few significant trends also reveal a decreasing tendency. Zero-flow indicators are more informative, showing an increase in number of days with zero-flow (Figure 6a) and in the percentage of river segments that dry at least once a year (Figure 3a), as well as an earlier annual onset of zero-flow (Figure 6c). This increase in flow intermittency has also been identified in other Mediterranean case studies (Llanos-Paez et al., 2023; Trambly et al., 2021). Precipitation in the Mediterranean region is projected to decrease over the following decades, which is expected in turn to decrease water resources availability (Dai et al., 2018; MedECC, 2020). However, in this study we identified a tendency towards flow reduction and increased intermittency while no decreasing trend in precipitation is observed for the period 2001-2022 (although there is a clear inter-annual correlation, see Figure 3a). Khorchani et al. (2021), Peña-Angulo et al. (2020), and Vicente-Serrano et al. (2022) have reported similar findings. This implies that other factors than precipitation affect streamflow, such as temperature (and consequently evaporative demand), which in our study does in fact follow an increasing tendency and it is also projected to increase in the following decades (Ali et al., 2022; MedECC, 2020).



Land use change has also been identified as an important factor influencing streamflow (Dennedy-Frank and Gorelick, 2020), and numerous studies in the Mediterranean region have explored the impact of these land use changes on streamflow (Buendia et al., 2016; Gallart et al., 2011; Gallart & Llorens, 2004; Khorchani et al., 2021). These studies report a correlation
400 between afforestation in the headwaters and decreases in streamflow. Rural exodus during the second half of the 20th century in the CRBD resulted in the expansion of forests on abandoned cropland and pasture land (Cervera et al., 2019). During the first two decades of the 21st century this trend has continued, with forested area going from 46% of our study area in 2000 to 56% in 2018 (EEA, 2000, 2018). To simplify the modelling exercise, we did not account for land use changes, although we did include the effects of increased evaporation due to warming, which may be more relevant (Buendia et al., 2016).
405 However, the fact that we did not include direct land use changes means that we cannot attribute exact changes in streamflow to climate change, land use change or other factors.

To sum up, the reduction in streamflow during the following decades can be expected to be even more severe due to the combined effects of climate change, land use change, and rising anthropogenic demands, thus reinforcing the need for sustainable water resources management.

410 **4.2.2 Increased streamflow flashiness**

An increase in streamflow flashiness has also been observed. Flashiness refers to the frequency, rapidity, and magnitude of short-term changes in streamflow (daily changes in this study).

Despite the overall tendency towards a reduction in streamflow, the annual maximum daily flow has increased in the Llobregat, Besòs and Foix basins. Similar results have been found by Bouadila et al. (2020) and Varlas et al. (2023). This
415 trend might be due to increased precipitation extremes events (Ali et al., 2022), which are projected to keep increasing in the following decades in spite of total precipitation reduction (Zittis et al., 2021). Therefore, Mediterranean basins will suffer from both water scarcity and from increased flood risk, making the role of water management even more prominent to defend vulnerable regions.

Changes in annual maximum are not the only evidence of intensified streamflow flashiness. Trends in median rise and fall
420 rate indicate a generalized increase in daily streamflow changes (Figure 7a-b), and the annual number of reversals also shows a positive trend in most regions (Figure 7c). All this implies that day-to-day changes in streamflow are both more significant and more frequent, thus increasing flashiness, which can have severe impacts on ecosystem function (Pletterbauer et al., 2018).

4.2.3 Uneven seasonal response to climate change

425 Most hydrological indicators are calculated and assessed at an annual scale. However, the Mediterranean climate is characterized by marked seasonality with hot, dry summers and mild winters, with most rainfall occurring in autumn and spring. Therefore, in this study we also analysed trends for monthly median flow to characterize intra-annual dynamics and different seasonal patterns.



430 The most relevant tendency is that of autumn median flows (Figure 5e), where most significant trends are negative. The Llobregat basin, of especial interest for water management, is particularly affected. Trends in winter flows also reveal a notable decrease in the Llobregat basin, but positive trends are observed in northeastern basins (Figure 5b), which might be a result of reduced snowfall in the Pyrenees due to increasing temperature (Döll and Schmied, 2012). Many spring and summer trends are non-significant, but negative trends prevail (Figure 5c-d).

435 Although decreasing trends in streamflow are prevalent for all seasons, their extent and magnitude differ. Autumn is the most affected season, followed by winter and summer, while spring remains almost neutral. The marked reduction in autumn flows, which has traditionally been the wettest season in CRBD, has also been observed in Clavera-Gispert et al. (2023). The extension of summer conditions into autumn, which were exceptionally anomalous in 2022 (Meteocat, 2023), is projected to continue (Spinoni et al., 2018). Delayed or lack of autumn rains put significant pressure on reservoirs and aquifers, already depleted after dry summers with higher demands, and exacerbates water scarcity.

440 **4.3 Hydrological modelling in water-scarce regions and implications for water management**

Process-based hydrological modelling is a useful tool to characterize and predict water resources availability within a watershed, which then has the potential to support decision-making in the water sector, especially if management operations and infrastructures are integrated into the modelling framework. Climatic and/or management scenarios can be implemented and assessed to determine the best measures to implement to support sustainable and resilient societies and ecosystems. 445 Integrating the management factor is especially important when modelling water-scarce regions, characterized by both an intrinsic limitation on water resources availability, which can be exacerbated by climate change, and growing demographic pressures.

The Mediterranean has been identified as one of the most critical regions where the issue of water scarcity will be aggravated by climate change (Cramer et al., 2018), to the point of being described as a climate emergency (Bremberg et al., 2022). 450 Therefore, the importance of hydrological modelling to support water resources management will continue to grow, and modelers and managers need to communicate effectively so that hydrological modelling can be successfully integrated into the planning and management processes.

Our approach led to successfully simulating hydrological and anthropogenic processes in water-scarce Mediterranean basins. During model development there was collaboration with water managers from the Catalan Water Agency, the CRBD's 455 authority, who provided valuable first-hand expert knowledge on actual management operations to include in the SWAT+ modelling framework, as well as participated in several follow-up meetings and SWAT+ training sessions. This co-development with water managers improves the quality of the hydrological model in simulating management operations and helps address specific problems and concerns of water managers, while also allowing water managers to get more familiarized with the model's capabilities and its use during planning and management. In particular, the inclusion of expert 460 knowledge on reservoir operations in custom decision tables allows us to simulate real reservoir releases more accurately, and it also provides water managers with an intuitive tool to test different management scenarios and thus support decision-



making on this topic. Past applications of decision tables for reservoir release operations based on generic rules, which cannot reproduce complex reservoir-specific management guidelines (Chawanda et al., 2020; Arnold et al., 2018), thus limiting their application and reinforcing the need to integrate this expert knowledge to better simulate releases.

465 The good model performance achieved for the validation period corroborates our assumption that the new strategy proposed to define the calibration and validation periods randomly for each individual gauging station captures all spatio-temporal variability and it is a good approach when dealing with spatio-temporally heterogeneous basins. However, as discussed in section 4.1, this strategy could be improved by using some other criteria to replace the random selection and accounting for statistical similarity between periods.

470 Future developments should also focus on further improving the integration of anthropogenic pressures and processes into hydrological modelling. Moreover, as already discussed in section 4.2.1, land use changes can have a profound impact on water resources availability and distribution and their integration into the modelling framework can be of great interest, especially when considering future management scenarios. Another interesting path for future research is the development of more easily accessible and operable hydrological models, such as on-line tools and river basin digital twins which allow for

475 the continuous estimation of streamflow using easily available meteorological forecasts.

5 Conclusions

There is a pressing need to promote sustainable water management, especially in regions vulnerable to water scarcity, such as the Mediterranean, where rising anthropogenic demands and increased severity of droughts due to climate change are expected to exacerbate water scarcity in the following decades. In this context, hydrological modelling that can accurately

480 simulate both natural and anthropogenic processes to assess water resources availability stands as a useful tool to support efficient decision-making in such water-scarce regions. In this research, we integrated first-hand expert knowledge on management operations into the hydrological model SWAT+ and applied it in the CRBD, located in the western Mediterranean.

We used the SWAT+CRBD model to characterize and identify spatio-temporal patterns and trends of streamflow for the

485 period 2001-2022, to deepen our understanding of how climate change and anthropogenic dynamics impact water-scarce basins. We identified a tendency towards flow reduction and increased streambed drying throughout the study region despite not observing a decreasing trend in mean annual rainfall, which indicates that other factors such as increasing temperature and anthropogenic pressures have a profound impact on water resources availability.

The integration of first-hand expert knowledge from water managers into our modelling framework, along with the

490 introduction of a novel random calibration and validation approach, have resulted in notable improvements in hydrological modelling and its potential use to support decision-making in the water management sector. The spatio-temporal analysis of streamflow patterns and trends have also provided insights into the evolution of hydrological dynamics under climate change and increasing anthropogenic pressures in basins vulnerable to water scarcity.



Code and data availability

495 The modified SWAT+ source code is available from the repository <https://doi.org/10.5281/zenodo.10362245>. All data used and presented in this paper are available upon request.

Author contribution

LE: Conceptualization, Data curation, Formal analysis, Methodology, Visualization, Writing – original draft preparation, Writing – review & editing. XG: Data curation, Writing – review & editing. JS: Software, Writing – review & editing. RM: 500 Supervision, Writing – review & editing. AM: Data curation, Project Administration, Writing - review & editing. VA: Conceptualization, Funding acquisition, Project Administration, Supervision, Writing – review & editing.

Competing interests

The authors declare that they have no conflict of interest.

Acknowledgements

505 This research was funded by the Catalan Water Agency under the contract CTN20A0533, titled “Analysis of the potential urban sanitation improvements and industrial point source contaminants traceability”. L. Estrada acknowledges funding from the Secretariat of Universities and Research of Generalitat de Catalunya and the European Social Fund for her FI fellowship (2023 FI-2 00168). Authors acknowledge the support from the Economy and Knowledge Department of the Catalan Government through Consolidated Research Groups (ICRA-ENV 2021 SGR 01282), as well as from the CERCA program.

510 References

- Abbaspour, K., Rouholahnejad, E., Vaghefi, S., Srinivasan, R., Yang, H., and Kløve, B.: A continental-scale hydrology and water quality model for Europe: Calibration and uncertainty of a high-resolution large-scale SWAT model, *J. Hydrol.*, 524, 733–752, <https://doi.org/10.1016/J.JHYDROL.2015.03.027>, 2015.
- Abbaspour, K., Vaghefi, S. A., and Srinivasan, R.: A Guideline for Successful Calibration and Uncertainty Analysis for Soil 515 and Water Assessment: A Review of Papers from the 2016 International SWAT Conference, *Water*, 10, 6, <https://doi.org/10.3390/W10010006>, 2018.
- Alcaraz-Hernández, J. D., Soler, J., Mezger, G., Corrochano Codornú, A., Calleja Arriero, B., and Magdaleno, F.: Hydrological classification of non-perennial Mediterranean rivers and streams: A new insight for their management within the water framework directive, *River Res. Appl.*, 39, 675–691, <https://doi.org/10.1002/RRA.4095>, 2023.



- 520 Ali, E., Cramer, W., Carnicer, J., Georgopoulou, E., Hilmi, N. J. M., Le Cozannet, G., and Lionello, P.: Cross-Chapter Paper 4: Mediterranean Region, in: *Climate Change 2022: Impacts, Adaptation and Vulnerability. Contribution of Working Group II to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change*, edited by: Pörtner, H.-O., Roberts, D. C., Tignor, M., Poloczanska, E. S., Mitenbeck, K., Alegría, A., Craig, M., Langsdorf, S., Löschke, S., Möller, V., Okem, A., and Rama, B., Cambridge University Press, Cambridge, UK and New York, NY, USA, 2233–2272, 525 <https://doi.org/10.1017/9781009325844.021>, 2022.
- Arnold, J. G., Bieger, K., White, M. J., Srinivasan, R., Dunbar, J. A., and Allen, P. M.: Use of Decision Tables to Simulate Management in SWAT+, *Water*, 10, 713, <https://doi.org/10.3390/W10060713>, 2018.
- Bailey, R. T., Bieger, K., Arnold, J. G., and Bosch, D. D.: A New Physically-Based Spatially-Distributed Groundwater Flow Module for SWAT+, *Hydrology*, 7, 75, <https://doi.org/10.3390/HYDROLOGY7040075>, 2020.
- 530 Bennett, N. D., Croke, B. F. W., Guariso, G., Guillaume, J. H. A., Hamilton, S. H., Jakeman, A. J., Marsili-Libelli, S., Newham, L. T. H., Norton, J. P., Perrin, C., Pierce, S. A., Robson, B., Seppelt, R., Voinov, A. A., Fath, B. D., and Andreassian, V.: Characterising performance of environmental models, *Environ. Model. Softw.*, 40, 1–20, <https://doi.org/10.1016/J.ENVSOFT.2012.09.011>, 2013.
- Bieger, K., Arnold, J. G., Rathjens, H., White, M. J., Bosch, D. D., Allen, P. M., Volk, M., and Srinivasan, R.: Introduction 535 to SWAT+, A Completely Restructured Version of the Soil and Water Assessment Tool, *J. Am. Water Resour. Assoc.*, 53, 115–130, <https://doi.org/10.1111/1752-1688.12482>, 2017.
- Bieger, K., Arnold, J. G., Rathjens, H., White, M. J., Bosch, D. D., and Allen, P. M.: Representing the Connectivity of Upland Areas to Floodplains and Streams in SWAT+, *J. Am. Water Resour. Assoc.*, 55, 578–590, <https://doi.org/10.1111/1752-1688.12728>, 2019.
- 540 Blöschl, G., Hall, J., Viglione, A., Perdigão, R. A. P., Parajka, J., Merz, B., Lun, D., Arheimer, B., Aronica, G. T., Bilibashi, A., Boháč, M., Bonacci, O., Borga, M., Čanjevac, I., Castellarin, A., Chirico, G. B., Claps, P., Frolova, N., Ganora, D., Gorbachova, L., Gül, A., Hannaford, J., Harrigan, S., Kireeva, M., Kiss, A., Kjeldsen, T. R., Kohnová, S., Koskela, J. J., Ledvinka, O., Macdonald, N., Mavrova-Guirguinova, M., Mediero, L., Merz, R., Molnar, P., Montanari, A., Murphy, C., Osuch, M., Ovcharuk, V., Radevski, I., Salinas, J. L., Sauquet, E., Šraj, M., Szolgay, J., Volpi, E., Wilson, D., Zaimi, K., 545 and Živković, N.: Changing climate both increases and decreases European river floods, *Nature*, 573, 108–111, <https://doi.org/10.1038/S41586-019-1495-6>, 2019.
- Boithias, L., Sauvage, S., Lenica, A., Roux, H., Abbaspour, K. C., Larnier, K., Dartus, D., and Sánchez-Pérez, J. M.: Simulating Flash Floods at Hourly Time-Step Using the SWAT Model, *Water*, 9, 929, <https://doi.org/10.3390/W9120929>, 2017.
- 550 Bots, P. W. G., Bijlsma, R., Von Korff, Y., Van Der Fluit, N., and Wolters, H.: Supporting the Constructive Use of Existing Hydrological Models in Participatory Settings: a Set of “Rules of the Game,” *Ecol. Soc.*, 16, 2011.
- Bouadila, A., Tzoraki, O., and Benaabidate, L.: Hydrological modelling of three rivers under Mediterranean climate in Chile, Greece, and Morocco: study of high flow trends by indicator calculation, *Arab. J. Geosci.*, 13, 1–17,



<https://doi.org/10.1007/S12517-020-06013-2/TABLES/6>, 2020.

- 555 Bremberg, N., Cramer, W., Dessì, A., Philippe, D., Fusco, F., Guiot, J., Pariente-David, S., and Raineri, L.: Climate Change and Security in the Mediterranean: Exploring the Nexus, Unpacking International Policy Responses, edited by: Dessì, A. and Fusco, F., Nuova Cultura, Rome, 146p pp., 2022.
- Brouziyne, Y., De Girolamo, A. M., Aboubdillah, A., Benaabidate, L., Bouchaou, L., and Chehbouni, A.: Modelling alterations in flow regimes under changing climate in a Mediterranean watershed: An analysis of ecologically-relevant hydrological indicators, *Ecol. Inform.*, 61, 101219, <https://doi.org/10.1016/j.ecoinf.2021.101219>, 2021.
- 560 Buendia, C., Batalla, R. J., Sabater, S., Palau, A., and Marcé, R.: Runoff Trends Driven by Climate and Afforestation in a Pyrenean Basin, *L. Degrad. Dev.*, 27, 823–838, <https://doi.org/10.1002/LDR.2384>, 2016.
- Caretta, M. A., Mukherji, A., Arfanuzzaman, M., Betts, R. A., Gelfan, A., Hirabayashi, Y., Lissner, T. K., Liu, J., Lopez Gunn, E., Morgan, R., Mwanga, S., and Supratid, S.: Water, in: Climate Change 2022: Impacts, Adaptation, and Vulnerability. Contribution of Working Group II to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change, edited by: Pörtner, H.-O., Roberts, D. C., Tignor, M., Poloczanska, E. S., Mitenbeck, K., Alegría, A., Craig, M., Langsdorf, S., Löschke, S., Möller, V., Okem, A., and Rama, B., Cambridge University Press, Cambridge, UK and New York, NY, USA, 551–712, <https://doi.org/10.1017/9781009325844.006>, 2022.
- Cobertes del sòl: <https://www.icgc.cat/Descarregues/Mapes-en-format-d-imatge/Cobertes-del-sol>.
- 570 Castellanos-Osorio, G., López-Ballesteros, A., Pérez-Sánchez, J., and Senent-Aparicio, J.: Disaggregated monthly SWAT+ model versus daily SWAT+ model for estimating environmental flows in Peninsular Spain, *J. Hydrol.*, 623, 129837, <https://doi.org/10.1016/j.jhydrol.2023.129837>, 2023.
- Catalan Water Agency (ACA): Pla de gestió del districte de conca fluvial de Catalunya 2022-2027, 2021.
- Cervera, T., Pino, J., Marull, J., Padró, R., and Tello, E.: Understanding the long-term dynamics of forest transition: From deforestation to afforestation in a Mediterranean landscape (Catalonia, 1868–2005), *Land use policy*, 80, 318–331, <https://doi.org/10.1016/J.LANDUSEPOL.2016.10.006>, 2019.
- Chawanda, C. J., Arnold, J., Thiery, W., and van Griensven, A.: Mass balance calibration and reservoir representations for large-scale hydrological impact studies using SWAT+, *Clim. Change*, 163, 1307–1327, <https://doi.org/10.1007/s10584-020-02924-x>, 2020.
- 580 Clavera-Gispert, R., Quintana-Seguí, P., Palazón, L., Zabaleta, A., Cenobio, O., Barella-Ortiz, A., and Beguería, S.: Streamflow trends of the Pyrenees using observations and multi-model approach (1980–2013), *J. Hydrol. Reg. Stud.*, 46, 101322, <https://doi.org/10.1016/J.EJRH.2023.101322>, 2023.
- Cramer, W., Guiot, J., Fader, M., Garrabou, J., Gattuso, J. P., Iglesias, A., Lange, M. A., Lionello, P., Llasat, M. C., Paz, S., Peñuelas, J., Snoussi, M., Toreti, A., Tsimplis, M. N., and Xoplaki, E.: Climate change and interconnected risks to sustainable development in the Mediterranean, *Nat. Clim. Chang.*, 8, 972–980, <https://doi.org/10.1038/s41558-018-0299-2>, 2018.
- 585 Cukier, R. I., Fortuin, C. M., Shuler, K. E., Petschek, A. G., and Schaibly, J. H.: Study of the sensitivity of coupled reaction



- systems to uncertainties in rate coefficients. *I Theory, J. Chem. Phys.*, 59, 3873–3878, <https://doi.org/10.1063/1.1680571>, 1973.
- 590 Daggupati, P., Pai, N., Ale, S., Douglas-Mankin, K. R., Zeckoski, R. W., Jeong, J., Parajuli, P. B., Saraswat, D., and Youssef, M. A.: A Recommended Calibration and Validation Strategy for Hydrologic and Water Quality Models, *Trans. ASABE*, 58, 1705–1719, <https://doi.org/10.13031/TRANS.58.10712>, 2015.
- Dai, A., Zhao, T., and Chen, J.: Climate Change and Drought: a Precipitation and Evaporation Perspective, *Curr. Clim. Chang. Reports*, 4, 301–312, <https://doi.org/10.1007/S40641-018-0101-6>, 2018.
- 595 Dakhlaoui, H., Ruelland, D., and Trambly, Y.: A bootstrap-based differential split-sample test to assess the transferability of conceptual rainfall-runoff models under past and future climate variability, *J. Hydrol.*, 575, 470–486, <https://doi.org/10.1016/J.JHYDROL.2019.05.056>, 2019.
- Dennedy-Frank, P. J. and Gorelick, S. M.: Insights on expected streamflow response to land-cover restoration, *J. Hydrol.*, 589, 125121, <https://doi.org/10.1016/j.jhydrol.2020.125121>, 2020.
- 600 Döll, P. and Schmied, H. M.: How is the impact of climate change on river flow regimes related to the impact on mean annual runoff? A global-scale analysis, *Environ. Res. Lett.*, 7, <https://doi.org/10.1088/1748-9326/7/1/014037>, 2012.
- Eekhout, J. P. C., Boix-Fayos, C., Pérez-Cutillas, P., and De Vente, J.: The impact of reservoir construction and changes in land use and climate on ecosystem services in a large Mediterranean catchment, *J. Hydrol.*, 590, 125208, <https://doi.org/10.1016/j.jhydrol.2020.125208>, 2020.
- 605 Corine Land Cover (CLC) 2000, Version 2020_20u1: <https://land.copernicus.eu/pan-european/corine-land-cover/clc-2000>.
Corine Land Cover (CLC) 2018, Version 2020_20u1: <https://land.copernicus.eu/pan-european/corine-land-cover/clc2018>, last access: 10 April 2022.
- Folton, N., Martin, E., Arnaud, P., L’Hermite, P., and Tolsa, M.: A 50-year analysis of hydrological trends and processes in a Mediterranean catchment, *Hydrol. Earth Syst. Sci.*, 23, 2699–2714, <https://doi.org/10.5194/HESS-23-2699-2019>, 2019.
- 610 Frey, S. K., Miller, K., Khader, O., Taylor, A., Morrison, D., Xu, X., Berg, S. J., Hwang, H. T., Sudicky, E. A., and Lapen, D. R.: Evaluating landscape influences on hydrologic behavior with a fully-integrated groundwater – surface water model, *J. Hydrol.*, 602, 126758, <https://doi.org/10.1016/J.JHYDROL.2021.126758>, 2021.
- Gallart, F. and Llorens, P.: Observations on land cover changes and water resources in the headwaters of the Ebro catchment, Iberian Peninsula, *Phys. Chem. Earth*, 29, 769–773, <https://doi.org/10.1016/j.pce.2004.05.004>, 2004.
- 615 Gallart, F., Delgado, J., Beatson, S. J. V., Posner, H., Llorens, P., and Marcé, R.: Analysing the effect of global change on the historical trends of water resources in the headwaters of the Llobregat and Ter river basins (Catalonia, Spain), *Phys. Chem. Earth, Parts A/B/C*, 36, 655–661, <https://doi.org/10.1016/J.PCE.2011.04.009>, 2011.
- Gassman, P. W., Sadeghi, A. M., and Srinivasan, R.: Applications of the SWAT Model Special Section: Overview and Insights, *J. Environ. Qual.*, 43, 1–8, <https://doi.org/10.2134/JEQ2013.11.0466>, 2014.
- 620 De Girolamo, A. M., Barca, E., Leone, M., and Lo Porto, A.: Impact of long-term climate change on flow regime in a Mediterranean basin, *J. Hydrol. Reg. Stud.*, 41, 101061, <https://doi.org/10.1016/J.EJRH.2022.101061>, 2022.



- Gudmundsson, L., Seneviratne, S. I., and Zhang, X.: Anthropogenic climate change detected in European renewable freshwater resources, *Nat. Clim. Chang.*, 7, 813–816, <https://doi.org/10.1038/NCLIMATE3416>, 2017.
- Gudmundsson, L., Leonard, M., Do, H. X., Westra, S., and Seneviratne, S. I.: Observed Trends in Global Indicators of Mean and Extreme Streamflow, *Geophys. Res. Lett.*, 46, 756–766, <https://doi.org/10.1029/2018GL079725>, 2019.
- Gudmundsson, L., Boulange, J., Do, H. X., Gosling, S. N., Grillakis, M. G., Koutroulis, A. G., Leonard, M., Liu, J., Schmied, H. M., Papadimitriou, L., Pokhrel, Y., Seneviratne, S. I., Satoh, Y., Thiery, W., Westra, S., and Zhang, X.: Globally observed trends in mean and extreme river flow attributed to climate change, *Science (80-.)*, 371, 1159–1162, <https://doi.org/10.1594/PANGAEA.887470>, 2021.
- Gupta, H. V., Kling, H., Yilmaz, K. K., Martinez, G. F., and Kling, H.: Decomposition of the mean squared error and NSE performance criteria: Implications for improving hydrological modelling, *J. Hydrol.*, 377, 80–91, <https://doi.org/10.1016/j.jhydrol.2009.08.003>, 2009.
- Guse, B., Reusser, D. E., and Fohrer, N.: How to improve the representation of hydrological processes in SWAT for a lowland catchment - temporal analysis of parameter sensitivity and model performance, *Hydrol. Process.*, 28, 2651–2670, <https://doi.org/10.1002/HYP.9777>, 2014.
- Haro-Montegudo, D., Palazón, L., and Beguería, S.: Long-term sustainability of large water resource systems under climate change: A cascade modelling approach, *J. Hydrol.*, 582, 124546, <https://doi.org/10.1016/j.jhydrol.2020.124546>, 2020.
- Højberg, A. L., Trolborg, L., Stisen, S., Christensen, B. B. S., and Henriksen, H. J.: Stakeholder driven update and improvement of a national water resources model, *Environ. Model. Softw.*, 40, 202–213, <https://doi.org/10.1016/J.ENVSOFT.2012.09.010>, 2013.
- Khorchani, M., Nadal-Romero, E., Lasanta, T., and Tague, C.: Natural revegetation and afforestation in abandoned cropland areas: Hydrological trends and changes in Mediterranean mountains, *Hydrol. Process.*, 35, e14191, <https://doi.org/10.1002/HYP.14191>, 2021.
- Lana, X., Casas-Castillo, M. C., Rodríguez-Solà, R., Serra, C., Martínez, M. D., and Kirchner, R.: Rainfall regime trends at annual and monthly scales in Catalonia (NE Spain) and indications of CO₂ emissions effects, *Theor. Appl. Climatol.*, 146, 981–996, <https://doi.org/10.1007/S00704-021-03773-Z>, 2021.
- Llanos-Paez, O., Estrada, L., Pastén-Zapata, E., Boithias, L., Jorda-Capdevila, D., Sabater, S., and Acuña, V.: Spatial and temporal patterns of flow intermittency in a Mediterranean basin using the SWAT+ model, *Hydrol. Sci. J.*, <https://doi.org/10.1080/02626667.2022.2155523>, 2023.
- López-Ballesteros, A., Nielsen, A., Castellanos-Osorio, G., Trolle, D., and Senent-Aparicio, J.: DSOLMap, a novel high-resolution global digital soil property map for the SWAT + model: Development and hydrological evaluation, *CATENA*, 231, 107339, <https://doi.org/10.1016/J.CATENA.2023.107339>, 2023.
- Loucks, D. P. and van Beek, E.: Water Resource Systems Modelling: Its Role in Planning and Management, in: *Water Resource Systems Planning and Management*, Springer, Cham, 51–72, https://doi.org/10.1007/978-3-319-44234-1_2, 2017.



- Lutz, S. R., Mallucci, S., Diamantini, E., Majone, B., Bellin, A., and Merz, R.: Hydroclimatic and water quality trends across three Mediterranean river basins, *Sci. Total Environ.*, 571, 1392–1406, <https://doi.org/10.1016/J.SCITOTENV.2016.07.102>, 2016.
- Marx, A., Kumar, R., Thober, S., Rakovec, O., Wanders, N., Zink, M., Wood, E. F., Pan, M., Sheffield, J., and Samaniego, L.: Climate change alters low flows in Europe under global warming of 1.5, 2, and 3°C, *Hydrol. Earth Syst. Sci.*, 22, 1017–1032, <https://doi.org/10.5194/HESS-22-1017-2018>, 2018.
- Masseroni, D., Camici, S., Cislighi, A., Vacchiano, G., Massari, C., and Brocca, L.: The 63-year changes in annual streamflow volumes across Europe with a focus on the Mediterranean basin, *Hydrol. Earth Syst. Sci.*, 25, 5589–5601, <https://doi.org/10.5194/hess-25-5589-2021>, 2021.
- MedECC: Climate and Environmental Change in the Mediterranean Basin – Current Situation and Risks for the Future. First Mediterranean Assessment Report, edited by: Cramer, W., Guiot, J., and Marini, K., Union for the Mediterranean, Plan Bleu, UNEP/MAP, Marseille, France, 632pp pp., <https://doi.org/10.5281/ZENODO.7224821>, 2020.
- Moriasi, D. N., Arnold, J. G., Van Liew, M. W., Bingner, R. L., Harmel, R. D., and Veith, T. L.: Model Evaluation Guidelines for Systematic Quantification of Accuracy in Watershed Simulations, *Trans. ASABE*, 50, 885–900, <https://doi.org/10.13031/2013.23153>, 2007.
- Musa, S. M. S. S., Noorani, M. S. M., Razak, F. A., Ismail, M., and Alias, M. A.: Streamflow Data Analysis for Flood Detection using Persistent Homology, *Sains Malaysiana*, 51, 2211–2222, <https://doi.org/10.17576/jsm-2022-5107-22>, 2022.
- Myers, D. T., Ficklin, D. L., Robeson, S. M., Neupane, R. P., Botero-Acosta, A., and Avellaneda, P. M.: Choosing an arbitrary calibration period for hydrologic models: How much does it influence water balance simulations?, *Hydrol. Process.*, 35, <https://doi.org/10.1002/HYP.14045>, 2021.
- Odusanya, A. E., Schulz, K., Biao, E. I., Degan, B. A. S., and Mehdi-Schulz, B.: Evaluating the performance of streamflow simulated by an eco-hydrological model calibrated and validated with global land surface actual evapotranspiration from remote sensing at a catchment scale in West Africa, *J. Hydrol. Reg. Stud.*, 37, 100893, <https://doi.org/10.1016/J.EJRH.2021.100893>, 2021.
- Pandey, V. P., Dhaubanjhar, S., Bharati, L., and Thapa, B. R.: Spatio-temporal distribution of water availability in Karnali-Mohana Basin, Western Nepal: Hydrological model development using multi-site calibration approach (Part-A), *J. Hydrol. Reg. Stud.*, 29, 100690, <https://doi.org/10.1016/J.EJRH.2020.100690>, 2020.
- Peña-Angulo, D., Vicente-Serrano, S. M., Domínguez-Castro, F., Murphy, C., Reig, F., Trambly, Y., Trigo, R. M., Luna, M. Y., Turco, M., Noguera, I., Aznárez-Balta, M., García-Herrera, R., Tomas-Burguera, M., and El Kenawy, A.: Long-term precipitation in Southwestern Europe reveals no clear trend attributable to anthropogenic forcing, *Environ. Res. Lett.*, 15, <https://doi.org/10.1088/1748-9326/AB9C4F>, 2020.
- Pezij, M., Augustijn, D. C. M., Hendriks, D. M. D., and Hulscher, S. J. M. H.: The role of evidence-based information in regional operational water management in the Netherlands, *Environ. Sci. Policy*, 93, 75–82,



- 690 <https://doi.org/10.1016/J.ENVSCL.2018.12.025>, 2019.
- Piniewski, M. and Okruszko, T.: Multi-Site Calibration and Validation of the Hydrological Component of SWAT in a Large Lowland Catchment, in: *Modelling of Hydrological Processes in the Narew Catchment*, edited by: Świątek, D. and Okruszko, T., Springer, Berlin, Heidelberg, 15–41, https://doi.org/10.1007/978-3-642-19059-9_2, 2011.
- Pletterbauer, F., Melcher, A., and Graf, W.: Climate Change Impacts in Riverine Ecosystems, in: *Riverine Ecosystem Management*, edited by: Schmutz, S. and Sendzimir, J., Springer, Cham, 203–223, https://doi.org/10.1007/978-3-319-73250-3_11, 2018.
- 695 Pulighe, G., Lupia, F., Chen, H., and Yin, H.: Modelling Climate Change Impacts on Water Balance of a Mediterranean Watershed Using SWAT+, *Hydrology*, 8, 157, <https://doi.org/10.3390/hydrology8040157>, 2021.
- Fast: Implementation of the Fourier Amplitude Sensitivity Test (FAST): <https://cran.r-project.org/package=fast>.
- 700 Richter, B. D., Baumgartner, J. V, Powell, J., Braun, D. P., and Braunt, D. P.: A Method for Assessing Hydrologic Alteration within Ecosystems, *Conserv. Biol.*, 10, 49–49, 1996.
- Samimi, M., Mirchi, A., Moriasi, D., Ahn, S., Alian, S., Taghvaeian, S., and Sheng, Z.: Modelling arid/semi-arid irrigated agricultural watersheds with SWAT: Applications, challenges, and solution strategies, *J. Hydrol.*, 590, 125418, <https://doi.org/10.1016/j.jhydrol.2020.125418>, 2020.
- 705 Schürz, C.: SWATplusR: Running SWAT2012 and SWAT+ Projects in R, <https://doi.org/10.5281/zenodo.6517027>, 2022.
- Sen, P. K.: Estimates of the Regression Coefficient Based on Kendall’s Tau, *J. Am. Stat. Assoc.*, 63, 1379, <https://doi.org/10.2307/2285891>, 1968.
- Senent-Aparicio, J., Jimeno-Sáez, P., López-Ballesteros, A., Giménez, J. G., Pérez-Sánchez, J., Cecilia, J. M., and Srinivasan, R.: Impacts of swat weather generator statistics from high-resolution datasets on monthly streamflow simulation over Peninsular Spain, *J. Hydrol. Reg. Stud.*, 35, 100826, <https://doi.org/10.1016/J.EJRH.2021.100826>, 2021.
- 710 Servei Metereològic de Catalunya (Meteocat): *Butlletí Anual d’Indicadors Climàtics 2022*, 2023.
- Song, X., Zhang, J., Zhan, C., Xuan, Y., Ye, M., and Xu, C.: Global sensitivity analysis in hydrological modelling: Review of concepts, methods, theoretical framework, and applications, *J. Hydrol.*, 523, 739–757, <https://doi.org/10.1016/j.jhydrol.2015.02.013>, 2015.
- 715 Spinoni, J., Vogt, J. V., Naumann, G., Barbosa, P., and Dosio, A.: Will drought events become more frequent and severe in Europe?, *Int. J. Climatol.*, 38, 1718–1736, <https://doi.org/10.1002/JOC.5291>, 2018.
- Stahl, K., Hisdal, H., Hannaford, J., Tallaksen, L. M., Van Lanen, H. A. J., Sauquet, E., Demuth, S., Fendekova, M., and Jodar, J.: Streamflow trends in Europe: Evidence from a dataset of near-natural catchments, *Hydrol. Earth Syst. Sci.*, 14, 2367–2382, <https://doi.org/10.5194/HESS-14-2367-2010>, 2010.
- 720 Stahl, K., Tallaksen, L. M., Hannaford, J., and Van Lanen, H. A. J.: Filling the white space on maps of European runoff trends: estimates from a multi-model ensemble, *Hydrol. Earth Syst. Sci.*, 16, 2035–2047, <https://doi.org/10.5194/hess-16-2035-2012>, 2012.
- Swain, S. S., Mishra, A., Sahoo, B., and Chatterjee, C.: Water scarcity-risk assessment in data-scarce river basins under



- 725 decadal climate change using a hydrological modelling approach, *J. Hydrol.*, 590, 125260, <https://doi.org/10.1016/j.jhydrol.2020.125260>, 2020.
- Tanner, J., Mantel, S., Paxton, B., Slaughter, A., and Hughes, D.: Impacts of climate change on rivers and biodiversity in a water-scarce semi-arid region of the Western Cape, South Africa, *Front. Water*, 4, 949901, <https://doi.org/10.3389/FRWA.2022.949901/BIBTEX>, 2022.
- 730 Theil, H.: A Rank Invariant Method of Linear and Polynomial Regression Analysis, i, ii, iii, in: Proceedings of the Royal Netherlands Academy of Arts and Sciences, 386–392, 521–525, 1397–1412, 1950.
- Tramblay, Y., Rutkowska, A., Sauquet, E., Sefton, C., Laaha, G., Osuch, M., Albuquerque, T., Alves, M. H., Banasik, K., Beaufort, A., Brocca, L., Camici, S., Csabai, Z., Dakhlaoui, H., DeGirolamo, A. M., Dörflinger, G., Gallart, F., Gauster, T., Hanich, L., Kohnová, S., Mediero, L., Plamen, N., Parry, S., Quintana-Seguí, P., Tzoraki, O., and Datry, T.: Trends in flow intermittence for European rivers, *Hydrol. Sci. J.*, 66, 37–49, <https://doi.org/10.1080/02626667.2020.1849708>, 2021.
- 735 Varlas, G., Papadaki, C., Stefanidis, K., Mentzafou, A., Pechlivanidis, I., Papadopoulos, A., and Dimitriou, E.: Increasing Trends in Discharge Maxima of a Mediterranean River during Early Autumn, *Water*, 15, 1022, <https://doi.org/10.3390/W15061022>, 2023.
- Vicente-Serrano, S. M., Peña-Angulo, D., Beguería, S., Domínguez-Castro, F., Tomás-Burguera, M., Noguera, I., Gimeno-Sotelo, L., and El Kenawy, A.: Global drought trends and future projections, *Philos. Trans. R. Soc. A*, 380, <https://doi.org/10.1098/RSTA.2021.0285>, 2022.
- 740 Wang, S., Zhang, Z., Sun, G., Strauss, P., Guo, J., Tang, Y., and Yao, A.: Multi-site calibration, validation, and sensitivity analysis of the MIKE SHE Model for a large watershed in northern China, *Hydrol. Earth Syst. Sci.*, 16, 4621–4632, <https://doi.org/10.5194/HESS-16-4621-2012>, 2012.
- Wi, S., Yang, Y. C. E., Steinschneider, S., Khalil, A., and Brown, C. M.: Calibration approaches for distributed hydrologic models in poorly gaged basins: implication for streamflow projections under climate change, *Hydrol. Earth Syst. Sci.*, 19, 857–876, <https://doi.org/10.5194/hess-19-857-2015>, 2015.
- 745 Yue, S. and Wang, C. Y.: The Mann-Kendall test modified by effective sample size to detect trend in serially correlated hydrological series, *Water Resour. Manag.*, 18, 201–218, <https://doi.org/10.1023/B:WARM.0000043140.61082.60/METRICAL>, 2004.
- 750 Zittis, G., Bruggeman, A., and Lelieveld, J.: Revisiting future extreme precipitation trends in the Mediterranean, *Weather Clim. Extrem.*, 34, 100380, <https://doi.org/10.1016/j.wace.2021.100380>, 2021.
- Zribi, M., Brocca, L., Tramblay, Y., and Molle, F.: Water Resources in the Mediterranean Region, Elsevier, Amsterdam, Netherlands, <https://doi.org/10.1016/C2018-0-02971-0>, 2020.