

# Modelling subglacial fluvial sediment transport with a graph-based model, GraphSSeT

Alan R.A. Aitken<sup>1,2</sup>, Ian Delaney<sup>3</sup>, Guillaume Pirot<sup>1,4</sup>, and Mauro A. Werder<sup>5,6</sup>

<sup>1</sup>School of Earth Sciences, The University of Western Australia, Perth Western Australia, Australia

<sup>2</sup>Australian Center of excellence for Antarctic Science, The University of Western Australia, Perth Western Australia, Australia

<sup>3</sup>Institut des dynamiques de la surface terrestre (IDyST), Université de Lausanne, Lausanne, Switzerland

<sup>4</sup>Mineral Exploration Cooperative Research Centre, Centre for Exploration Targeting, School of Earth Sciences, The University of Western Australia, Perth, Australia

<sup>5</sup>Swiss Federal Institute for Forest, Snow and Landscape Research (WSL), Birmensdorf, Switzerland

<sup>6</sup>Laboratory of Hydraulics, Hydrology and Glaciology (VAW), ETH Zurich, Zurich, Switzerland

**Correspondence:** Alan Aitken (alan.aitken@uwa.edu.au)

**Abstract.** A quantitative understanding of how sediment discharge from subglacial fluvial systems varies in response to glacio-hydrological conditions is essential for understanding marine systems around Greenland and Antarctica and for interpreting sedimentary records of cryosphere evolution. Here we develop a graph based approach, GraphSSeT, to model subglacial fluvial sedimentary transport using subglacial hydrology model outputs as forcing. GraphSSeT includes glacial erosion of bedrock and a dynamic sediment model with exchange between the active transport system and a basal sediment layer. Sediment transport considers transport-limited and supply-limited regimes and includes stochastically-evolving grain size, network scale flow management and tracking of detrital provenance. GraphSSeT satisfies volume balance and sediment velocity and transport capacity constraints on flow. GraphSSeT is demonstrated for synthetic scenarios that probe the impact of variations in hydrological, geological and glaciological characteristics on sediment transport over multi-diurnal to seasonal timeframes. For steady-state hydrology scenarios on seasonal timescales we find a primary control from the scale and organisation of the channelised hydrological flow network. The development of ~~grain-size-dependant~~grain-size-dependant selective transport is identified as the major secondary control. Non-steady-state hydrology is tested on multi-diurnal timescales, for which sediment discharge scales with peak water input leading to increased sediment discharge compared to steady state. ~~With increasing application of subglacial hydrology models,~~Subglacial hydrology models are being applied more broadly and GraphSSeT extends this capacity to ~~define quantitatively~~quantitatively define the volume, grain size distribution and detrital characteristics of sediment discharge, ~~and enables a stronger connection of models of the glacio-hydrological system with constraints from that, through comparison with~~ the sediment record~~and impacts,~~may enable improved knowledge of the glacio-hydrological system and its impact on marine systems.

## 1 Introduction

20 Discharge of sediments from subglacial fluvial systems is an important component of the ocean system and impacts ~~on~~ the delivery of nutrients (Wadham et al., 2013; Meire et al., 2017; Cape et al., 2019; Overeem et al., 2017), ice-shelf cavity processes (Smith et al., 2019) and marine geomorphology (Dowdeswell et al., 2016, 2015). Turbid sediment plumes provide a means to observe subglacial fluvial inputs into the ocean that are ~~otherwise unobservable~~ difficult to observe in-situ (Schild et al., 2017; Chu et al., 2009). Furthermore, marine sediments from currently or formerly glaciated margins are a primary record  
25 of past cryosphere change, and are crucial to ~~establishing pinning points in~~ develop knowledge of global climate evolution (Lepp et al., 2022; Hogan et al., 2020, 2011; Witus et al., 2014; Hogan et al., 2012; Andresen et al., 2024). ~~Subglacial-~~

~~In sub-ice sheet settings, subglacial~~ fluvial systems comprise a ~~long-term evolution with superimposed multi-scale system with flow varying on timescales spanning from hours to centuries or more. Of particular interest are~~ events of short duration but with high flow (Dow, 2022; Dow et al., 2022; Chu, 2014; Ashmore and Bingham, 2014). ~~These are~~ associated with seasonal  
30 to diurnal surface melting cycles (Ehrenfeucht et al., 2023) and flood events, including jökulhlaups (Roberts, 2005). Ice stream ‘water piracy’, involving the re-routing of subglacial water from one ice stream to another, may ~~occur in response to relatively~~ rapidly reorganise the drainage regime even with small changes in glacial mass-balance or bed conditions (McCormack et al., 2023; Alley et al., 1994; Vaughan et al., 2008). It is likely that ongoing changes in cryosphere systems will increase the frequency and intensity of high-flow events in the future, and so ~~increased~~ increase sediment flux to the ocean (Delaney and  
35 Adhikari, 2020)

To ~~express~~ realize the consequences of cryosphere change on marine systems, and to fully comprehend the implications of sedimentary records of the past and present cryosphere ~~there is a need for a~~ quantitative understanding of subglacial fluvial sediment transport systems is needed (Delaney and Adhikari, 2020). Here we describe a new graph-based approach ; ~~GraphSSeT, with capacity to model~~ to modeling subglacial fluvial sediment transport, Graphical Subglacial Sediment Transport  
40 (GraphSSeT). ~~The approach is demonstrated~~ for glacio-hydrological ~~models~~ scenarios across a range of time- and length-scales ~~The approach is demonstrated for using~~ subglacial hydrology model outputs ~~from synthetic scenarios (De Fleurian et al., 2018) for which we~~ (De Fleurian et al., 2018). ~~We~~ assess the most important ~~key~~ hydrological, geological, and glaciological controls on the sediment transport system.

## 2 Background

45 GraphSSeT seeks to provide a versatile environment for modelling subglacial sediment transport, including the efficient delineation of channelised hydrology networks, a dynamic sediment model (Delaney et al., 2019), and network scale flow management. GraphSSeT outputs the key information used to constrain sedimentary systems include the volume, concentration and grain size distribution of sediment and its detrital characteristics. The model is stochastic and is particularly well suited to developing a representative understanding of the sediment transport system for specific glacio-hydrological scenarios.

## 50 2.1 Conceptual Background

### 2.1.1 Subglacial hydrology

Under ~~glaciers and ice sheets~~ ice, water transport occurs in response to hydraulic potential gradients that drive flow towards lower potential areas (Shreve, 1972). The subglacial hydrology system ~~involves numerous components, but fundamentally includes~~ comprises input, storage, flow and output (Ashmore and Bingham, 2014). Water enters the subglacial hydrology ~~system~~ flow network by the melting of basal ice, groundwater discharge, subglacial lake discharge, and surface melt transported to the bed through moulins. In the context of the modeling to come we make a distinction between ~~a distributed input~~ distributed inputs, occurring over a substantial area ~~relative to the model resolution e.g. from basal melt~~, and focused input(s) inputs with a high volume ~~input at a specific location(s)~~ input at specific locations e.g. from surface water input via moulins. Water may be stored englacially (Fountain et al., 2005) and in subglacial lakes, which may be 'active' lakes that fill and empty in a cyclical to episodic fashion, or stable lakes ~~which indicate balanced flow or closed systems~~ (Livingstone et al., 2022). Water may also be stored in sediments and sedimentary rocks (Christoffersen et al., 2010; Flowers and Clarke, 2002).

Subglacial water flow may be characterised by a distributed, or so-called 'sheet flow', along the bed interface, which is relatively inefficient, and flow concentrated into subglacial channels, so-called 'channelised flow' which is relatively efficient. Distributed flow may be accommodated by several mechanisms including linked-cavity systems (Kamb, 1987), distributed 'canals' eroded into underlying sediment (Walder and Fowler, 1994), thin patchy films (Alley, 1989; Creyts and Schoof, 2009), or flow through permeable basal sediments (Boulton et al., 2007); more generally the bed may be viewed as a permeable interface (Hewitt, 2011; Flowers et al., 2004). Channels may be incised into the overlying ice, forming so-called Röthlisberger or 'R' channels (Röthlisberger, 1972) that evolve dynamically in response to water and ice flow, ~~or alternatively by~~ Classical R-channels are semi-circular in section (Röthlisberger, 1972), but may be more generally viewed as circle segments, with a geometry defined by the so-called Hooke angle, allowing for broad, low conduits (Hooke et al., 1990). Alternatively, channels may form by incision into the bed forming so-called Nye or 'N' channels (Nye, 1976). Outputs from the subglacial hydrology system include discharge to the ocean, re-freezing to the bed (Alley et al., 1998), filling of lakes and englacial reservoirs, or recharge of groundwater aquifers.

The hydrology system is strongly influenced by quasi-stable basal boundary conditions including bed topography, bed roughness, subglacial geology and geothermal heat flux, ~~but also and~~ is intrinsically linked to ~~dynamic changes to the ice that can occur much more rapidly. These ice-dynamics~~, including changes in ice thickness and surface slope as well as the thermal state and flow-dynamics of the ice. Particularly important are the temporal and spatial variations in hydrological inputs that may occur over timescales from hours to millenia.

### 2.1.2 Subglacial sediment transport

80 Glaciers can transport sediment ~~coupled with ice flow including as sediment~~ entrained within the basal ice (Licht and Hemming, 2017) and ~~by basal sliding occurring within subglacial till, causing the material above the shear interface~~ through basal sliding causing sediment to move with the ice (Evans et al., 2006; Christoffersen et al., 2010). These transport processes have

previously been represented in ice sheet models (Pollard and DeConto, 2020) and ~~-, although undoubtedly important,~~ are not the focus here. Subglacial fluvial transport is the other major component of sediment discharge ~~at glaciated margins~~ (Overeem et al., 2017; Andresen et al., 2024), and is more sensitive to changes in glacial-hydrologic state. This highly dynamic spatio-temporal transport system is the focus of our model. Important considerations include the dual limits on transport ~~by from~~ transport capacity and ~~by~~ sediment supply, and the interaction of changing hydrology with an evolving basal interface.

The dynamics of subglacial fluvial sediment transport are not well constrained by observations, ~~however,~~. However, they share similarities with fluvial transport in rivers for which the governing processes are better established (Rijn and C, 2007a, b; Ancey, 2020a, b). ~~Although the~~ The physical description of fluvial transport processes is often uncertain with respect to satisfying empirical data, but several classes of transport law are well established. One major family of such laws uses the shear stress at the bed to establish transport capacity, using either stochastic or deterministic criteria for sediment mobilisation (Engelund and Hansen, 1967; Meyer-Peter and Müller, 1948; Einstein, 1950). These laws have been applied to ~~model develop~~ the first dedicated model for subglacial fluvial sediment transport in the SUGSET-SubGlacial SEDiment Transport (SUGSET) model, with formulations in one-dimension (Delaney et al., 2019) and recently in two dimensions (Delaney et al., 2023). Network-based models are developed for riverine fluvial systems (Czuba, 2018; Wilkinson et al., 2006) but no network-based formulation exists for subglacial fluvial systems.

## 2.2 Modelling Background

### 2.2.1 Subglacial hydrology models

Subglacial hydrology may be described by models with varying degrees of complexity ~~and correspondingly varying computational cost and ease of use~~ (Flowers, 2015). The simplest models use the so-called Shreve potential (Shreve, 1972) to define the direction and relative magnitude of water flow (equation 1).

$$\varphi = \rho_i g z_s + (\rho_w - \rho_i) g z_b + N \quad (1)$$

where  $\varphi$  is the hydraulic potential at the bed for ~~a given an~~ ice-surface elevation  $z_s$  and bed elevation  $z_b$ .  $\rho_i$  and  $\rho_w$  are the densities of ice and water respectively,  $g$  is gravitational acceleration.  $N$  is effective pressure, being defined as ice overburden pressure minus the basal water pressure. Assuming constant  $N$ , the hydraulic potential gradient may be defined as

$$\nabla \varphi = \rho_i g \nabla z_s + (\rho_w - \rho_i) g \nabla z_b \quad (2)$$

With ~~the inclusion of basal water input~~ water input applied to the bed, flow can be accumulated to define regions of enhanced flow. ~~For example, Le Brocq et al. (2009) model the spatially variable drainage system as a sheet, the thickness of which is varied to accommodate potential gradient driven laminar flow.~~ (Le Brocq et al., 2009). Shreve potential approaches have the benefit of low computational cost, simplicity, and ease of application ~~to large-scale examples~~. However, with the assumption of constant  $N$ , they do not represent well the dynamic interactions of distributed and channelised flow on short timescales nor on length scales of individual channels (De Fleurian et al., 2018).

~~One more advanced formulation is~~ [More advanced formulations include](#) a network-based approach that considers flow to represent both channels and linked cavities in a unified form as conduits ~~∴ conduits that exceed a critical discharge represent channels and are spontaneously enhanced due to instabilities between opening and closure rate (Schoof, 2010); the remainder represents the distributed flow system. Other approaches develop~~ (Schoof, 2010) and [approaches that involve](#) a coupled model of ~~the~~ channelised and distributed flow regimes, considering the development of each and the transfer of water between them ~~. Several such models have been developed including descriptions of distributed flow with a so-called ‘macroporous sheet’ for which thickness varies in-line with effective pressure (Flowers et al., 2004), or by a linked cavity drainage system (Hewitt, 2011). In the latter, cavity height varies dynamically with an opening rate typically defined from ice-sliding rate and bed roughness, and a closure rate typically defined by ice creep (Hewitt, 2011). R-channels are most commonly represented as circle segments, classically as semi-circles (Röthlisberger, 1972), but also as broad low conduits with a geometry defined by the so-called Hooke angle (Hooke et al., 1990). The channel sectional area evolves dynamically with a closing rate typically defined by ice creep, and an opening rate typically defined by ice melt at the channel walls. For our new approach~~ (Flowers et al., 2004; Hewitt, 2011). [For GraphSST](#) (Fig. 1), any model for which channelised flow can be described on a set of connected edges could be used as input, but ~~perhaps the most widely used approach in recent times, and the~~ [the](#) one used as forcing here, is the Finite Element Method (FEM) ~~model~~ [GlaDS-based Glacier Drainage System \(GlaDS\) model](#) (Werder et al., 2013).

## 2.2.2 The GlaDS model

130 For sheet flow we begin with the conservation of mass

$$\frac{\partial h_w}{\partial t} + \nabla \cdot \mathbf{q} = m_b \quad (3)$$

where  $h_w$  represents the water sheet thickness, and  $m_b$  describes water input to the sheet.  $\mathbf{q}$  is the sheet discharge and is defined as a Darcy-Weisbach turbulent flow parameterization  $\mathbf{q} = -kh_w^\alpha |\nabla \varphi|^{\beta-2} \nabla \varphi$ , where  $k$ ,  $\alpha$  and  $\beta$  are defined appropriately for the flow law (Werder et al., 2013). The evolution of the sheet thickness is modelled on elements and is formulated using a

135 linked cavity approach (Hewitt, 2011)

$$\frac{\partial h_w}{\partial t} = \omega - v \quad (4)$$

where  $\omega$  represents the cavity opening rate as

$$\omega(h_w) = \begin{cases} u_b(h_r - h_w)/l_r & \text{if } h_w < h_r \\ 0 & \text{otherwise} \end{cases} \quad (5)$$

with  $u_b$  the basal sliding velocity of ice,  $h_r$  and  $l_r$  are the typical bedrock bump height and horizontal cavity spacing respectively. In equation 4,  $v$  represents the cavity closing rate as

140

$$v(h_w, N) = \tilde{A} h_w |N|^{\eta-1} N \quad (6)$$

where  $\tilde{A}$  is the ice flow constant scaled for cavities and  $\eta$  is the Glen’s flow law exponent, typically 3.



**Figure 1.** a) schematic of a GraphSSeT model edge showing its structure (open arrows) and key model components. Hydrology model components in black, ice sheet model components in grey, sediment model components in white. Variables and quantities for GlaDS and SUGSET are as in sections 2.2.2 and 2.2.3 respectively. b) schematic illustrating the network transport model (see [Section section 2.2.4](#)). This example shows three interconnected channels each with flow from the head node to the outlet node. The ‘northern’ and ‘southern’ channels have supply-limited conditions, where all sediment is able to leave the edge ( $V_{s_{out}}$  is sediment leaving the edge). The central channel and connecting edges have transport-capacity limited conditions, and sediment will only leave the edge from below the critical point  $x_{crit}$ . Furthermore, the edges downstream from node B cannot transport the sediment supplied from upstream. The consequence is for residual sediment volume (as flux density,  $K'$ ) to accumulate on the downstream edges, and ultimately for reduced flow ( $V_{s_{in}}$ ) into the downstream edges, balanced by a back-flow ( $V_{s_{back}}$ ) on the upstream edges: an excessive flux density causes an edge to ‘jam’. Jammed edges cannot receive incoming sediment volume, but sediment can flow out to the downstream edges allowing the jam to clear.

Channelised flow is modelled on element edges, with each edge representing a potential channel that can open and close according to the balance between ice creep and melting of the channel walls. Again we begin with the conservation of mass

$$145 \quad \frac{\partial S}{\partial t} + \frac{\partial Q_w}{\partial x} = \frac{\Xi - \Pi}{\rho_w L} + m_c \quad (7)$$

where  $x$  is the coordinate along the edge,  $\Xi$  the potential energy dissipated per unit length and time and  $\Pi$  the sensible heat exchange of water due to melting or refreezing (see Werder et al. (2013) for definition of  $\Xi$  and  $\Pi$ ).  $L$  is the latent heat of fusion.  $Q_w$  is defined as a Darcy-Weisbach turbulent flow parameterization  $Q_w = -k_c S \alpha_c \left| \frac{\partial \varphi}{\partial x} \right|^{\beta_c - 2} \frac{\partial \varphi}{\partial x}$ , with  $k_c$ ,  $\alpha_c$  and  $\beta_c$  not necessarily the same as those for sheet flow.  $m_c$  is the water entering the channel from the adjacent sheet. The time evolution of channel area  $S$  is given by the balance of opening rate and closing rate

$$\frac{\partial S}{\partial t} = \frac{\Xi - \Pi}{\rho_i L} - v_c \quad (8)$$

The closing rate  $v_c$  is defined similarly to eq. 6 replacing  $h_w$  with  $S$ , and with potentially a different scaling for  $\tilde{A}$ .

The sheet and the channel model are coupled by requiring that the pressure is continuous, i.e. the pressure in the sheet and an adjacent channel are equal. The continuity is assured by fixing the water exchange between the sheet and the channels accordingly (via  $m_c$  for the channels and via boundary conditions for the sheet).

### 2.2.3 Subglacial sediment dynamics model

For sediment transport in GraphSSeT, we ~~consider~~ discretise the one-dimensional form of the SUGSET model (Delaney et al., 2019) to apply to individual graph edges (Figure 1). ~~SUGSET uses an R-channel geometry for which the dimensions of the channel and the channelised~~ The channel dimensions and flux may be calculated from water inputs. ~~Alternatively, the channel dimensions and flux, or~~ may be obtained a-priori from an input hydrology model, which is the approach we use here. With knowledge of the channel sectional area and channelised water flux, the basal shear stress from water flow is

$$\tau = \frac{1}{8} f_r \rho_w u_w^2 \quad (9)$$

where  $u_w$  is the mean water velocity defined from  $Q_w/S$  and  $f_r$  the Darcy-Weisbach friction factor. Once  $\tau$  is defined the sediment transport capacity may be determined using one of several sediment transport laws. In this case we use the formulation for total sediment flux of Engelund and Hansen (1967).

$$Q_{sc} = \frac{0.4}{f_r} \frac{1}{d_{50} \left( \frac{\rho_s}{\rho_w} - 1 \right)^2 g^2} \left( \frac{\tau}{\rho_w} \right)^{\frac{5}{2}} w_c \quad (10)$$

where  $d_{50}$  is the median sediment grain size ~~and~~,  $\rho_s$  the sediment grain density ~~and~~  $w_c$  ~~is~~ the width of the channel floor, ~~defined for a given~~. ~~Here,  $w_c$  is defined from the channel area  $S$  by the using a~~ Hooke angle of ~~the channel~~ (Delaney et al., 2019; Hooke et al., 1990) ~~Here we use  $\pi$~~  (Delaney et al., 2019; Hooke et al., 1990), consistent with the semi-circular R-channel geometry in GlADS.

~~In the SUGSET model sediment may be~~ The SUGSET model defined sediment as either in active transport, or stored in a basal sediment layer, from which sediment can be remobilised. For a channel segment, the amount of sediment in active transport may be limited either by transport capacity (eq. 10) or by a lack of available sediment. SUGSET ~~applies~~ applied a dynamic bed-evolution that accommodates both transport-capacity-limited and supply-limited regimes with provision for a) the generation of new sediment due to glacial erosion of bedrock, b) mobilisation of existing sediment from the basal sediment layer and c) deposition of excess sediment to the basal sediment layer. In GraphSSeT, glacial erosion potential  $\dot{e}$  may be defined

either as a power-law of the sliding velocity at the bed (Herman et al., 2018), or, if the basal shear stress of the ice is also known, as a linear function of the work done by basal sliding (Pollard and DeConto, 2003):

$$\dot{\epsilon} = \kappa u_b^\gamma \text{ or } \dot{\epsilon} = \varkappa \tau_b u_b \quad (11)$$

where  $\kappa$  is generally between  $1 \times 10^{-4}$  and  $1 \times 10^{-7} \text{ m}^{1-\gamma}/\text{a}^{1-\gamma}$  for  $\gamma$  between 1 and 2 (Herman et al., 2018); scaling factor  $\varkappa$  may be defined  $\approx 2^{-10} \text{ Pa m/s}$  (Pollard and DeConto, 2003; Golledge and Levy, 2011). Importantly, new sediment generation is restricted by the capacity of the ice to access the bedrock through the basal sediment layer and the following formulation is used ~~to define the source term:~~

$$m_t = \dot{\epsilon} \left( 1 - \frac{h_s}{h_{max}} \right) w_{edge} \quad (12)$$

where  $h_{max}$  is a limit on the depth to which glacial erosion may penetrate through sediment, ~~typically considered between 0.5 to 2 m~~. This value should not be deeper than the expected depth of deformation in subglacial till, which is observed to vary from  $\sim 0.2$  to  $\sim 2$  m (Pollard and DeConto, 2003; Golledge and Levy, 2011; Delaney et al., 2019). Here (Evans et al., 2006). Previous modelling studies have used values between 0.5 and 2 m (Pollard and DeConto, 2003; Golledge and Levy, 2011), and here we use 0.75 m following Delaney et al. (2019).  $w_{edge}$  is the width of the bed accessible by the channel segment. For this we set  $w_{edge} \times l_{edge}$  as one-third the area of an equilateral triangle with side length  $l_{edge}$ . The mobilisation of sediment ~~from at~~ the ice sheet bed is defined as

$$\frac{\partial Q_s}{\partial x} = \begin{cases} \frac{Q_{sc} - Q_s}{l} & \text{if } \frac{Q_{sc} - Q_s}{l} \leq m_t & \text{(a)} \\ 0 & \text{if } h_s \geq h_{lim} \text{ \& } \frac{Q_{sc} - Q_s}{l} < 0 & \text{(b)} \\ \frac{Q_{sc} - Q_s}{l} \sigma(h_s) + m_t (1 - \sigma(h_s)) & \text{otherwise} & \text{(c)} \end{cases} \quad (13)$$

In equation 13 the first case describes the mobilisation of sediment according using a sediment-uptake e-folding length  $l$ , here taken equal to  $l_{edge}$ . If transport capacity ( $Q_{sc}$ ) exceeds the influx of sediment from upstream ( $Q_s$ ) mobilisation will be positive and sediment will enter the transport system from the basal sediment layer; in the opposing situation, mobilisation is negative and sediment will be deposited to the basal sediment layer. ~~In the first case mobilisation to transport capacity is realised where  $(Q_{sc} - Q_s)/l$  is less than the capacity for erosion to supply sediment (equation 13 a). In the~~ The second case, ~~we seek describes a need~~ to deposit sediment, but already the basal sediment layer has reached the maximum permitted thickness  $h_{lim}$  and so mobilisation is set to 0 (equation 13 (b)). ~~This~~  $h_{lim}$  prevents ‘runaway’ accumulations of sediment from occurring in areas such as overdeepenings, as the model has no feedback between sediment deposition and hydraulics (Creys et al., 2013). Equation 13 (c) describes a more general case where existing sediment may be mobilised to or from the bed and new sediment may be derived through glacial erosion, depending on the function  $\sigma(h_s)$ .

$$\sigma(h_s) = \left( 1 + \exp \left( 10 - 5 \frac{h_s}{\Delta\sigma} \right) \right)^{-1} \quad (14)$$

where  $\Delta\sigma$  provides a smooth transition between the two terms over the range  $h_s = 2\Delta\sigma \pm \Delta\sigma$ ; for discussion of the influence of  $\Delta\sigma$  see Delaney et al. (2019, 2023). Finally, from the net sediment mobilisation the change in the thickness of the basal



205 sediment layer over time is calculated using the Exner equation

$$\frac{\partial h_s}{\partial t} w_{edge} = -\frac{\partial Q_s}{\partial x} \frac{1}{1-\lambda} + m_t \quad (15)$$

In GraphSSeT we consider porosity as part of the Exner equation with in this case  $\lambda = 0.3$  ~~used for the runs performed~~ heretypical for subglacial tills (Evans et al., 2006). In GraphSSeT, as well as the conditions in eq. 13, sediment mobilisation  $\frac{\partial Q_s}{\partial x}$  is further limited as part of the network transport model such that the condition  $0 \leq h_s \leq h_{lim}$  is maintained.

## 210 2.2.4 Network transport model

The preceding describes the local co-evolution of the basal sediment layer and active transport. ~~In GraphSSeT these are calculated discretely for~~ calculated discretely on each graph edge. At network-scale we construct the transport model on the basis of an evolving flux density defined from the sediment volume in active transport on the edge:

$$K = \frac{V_s}{l_{edge}} \quad (16)$$

215 A limit on flux density that we cannot exceed is defined from the sediment transport capacity as  $K_{max} = Q_{sc} dt / l_{edge}$ , where  $dt$  is the model-time elapsed since the last timestep for that edge, which need not be constant. For each timestep ~~for each edge~~ we define  $V_s$  for each edge, considering the flow of sediment through the network.

$$V_s = K' l_{edge} + Q_s dt + \frac{\partial Q_s}{\partial x} l_{edge} dt \quad (17)$$

220 where  $K'$  is the residual flux density from the end of the last timestep on that edge,  $\frac{\partial Q_s}{\partial x}$  is the mobilisation of sediment on the edge (eq. 13) and  $Q_s$  is the influx to the edge from its upstream node.

In GraphSSeT we control the network-scale flow using three founding principles:

1. Sediment transport can not involve excessive ~~velocities implied particle velocities for the median grain size~~
2. Sediment transport capacity can not be exceeded for any edge
3. Sediment volume must be conserved except for addition through erosion and discharge at the outlets

225 The first criterion is important in situations where relatively coarse grains are transported on relatively long edges, in which case not all the active sediment is able to leave the edge. To constrain this, we apply an unsteady virtual velocity limit for bedload transport  $u_s$  using the empirically-defined relationships of Klösch and Habersack (2018). Empirical relationships with grain size are defined for formula types  $u_s = a(\tau^* - \tau_c^*)(\sqrt{\tau^*} - \sqrt{\tau_c^*})$  and  $u_s = a(\tau^* - \tau_c^*)^{\frac{3}{2}}$ . Each of these is available in GraphSSeT. In the model runs presented in this study we use the former realised as:

$$230 \quad u_s = a \sqrt{\frac{\rho_s - \rho_w}{\rho_w} g d_{50}} (\tau^* - \tau_c^*) (\sqrt{\tau^*} - \sqrt{\tau_c^*}), \tau^* > \tau_c^* \quad (18)$$

where  $a$  is a dimensionless coefficient, for which Klösch and Habersack (2018) derive the value 2.30.  $\tau^*$  is the dimensionless Shields stress  $\frac{\tau}{(\rho_s - \rho_w) g d_{50}}$  and  $\tau_c^*$  the dimensionless critical Shields stress  $\tau_c^* = b \left( \frac{d_{50}}{d_{mean}} \right)^c$  with  $b$  and  $c$  empirically constrained as 0.052 and -0.82 respectively.  $d_{mean}$  is the mean grain size of the population distribution input to the model. For the datasets in Klösch and Habersack (2018) both this formulation and the alternative formulation generated similar results.

235 From  $u_s$  we define the critical point  $x_{crit}$  on the edge (Fig.1) as the point below which the sediment is able to reach the downstream node in timestep length  $dt$ . All active sediment below  $x_{crit}$  is assigned to leave the edge in the current timestep. A lower limit on  $x_{crit}$ ,  $l_{min}$ , is set to avoid stagnant edges, here it is set at  $0.1 \times l_{edge}$ .

$$x_{crit} = \begin{cases} l_{edge} & \text{if } u_s dt > l_{edge} \\ u_s dt & \text{if } l_{min} \leq u_s dt \leq l_{edge} \\ l_{min} & \text{if } u_s dt < l_{min} \end{cases} \quad (19)$$

For each edge we define the sediment volume flowing out as  $V_{s_{out}} = V_s \frac{x_{crit}}{l_{edge}}$ .

240 The second criterion is important for both controlling the active sediment on the edge and the interactions at nodes where several edges meet. The situation may occur where the maximum flux density for an edge is exceeded by due to sediment influx from upstream. The edge cannot receive more sediment without violating condition 2, and is designated as ‘jammed’ (Fig. 1) meaning that neither sediment influx from upstream nodes nor the mobilisation of sediment are permitted. A jammed status does not imply a physical restriction to sediment flow, and outflux to downstream nodes can occur as well as deposition  
245 of sediment to the basal sediment layer; therefore the jammed status is inherently transient.

The third criterion is considered at nodes, where we must take the influx from several upstream edges and distribute it between several downstream edges. No volume is stored on nodes, and so to manage the flow distribution we use a kinematic wave approach (Newell, 1993). Total influx to the node may exceed the combined transport capacity of the downstream edges, in which case a ‘back-flow’ is defined for each node as

$$250 \quad v_{s_{back}} = \begin{cases} v_{s_{node}} - v_{s_{c_{out}}} & \text{if } v_{s_{node}} - v_{s_{c_{out}}} > 0 \\ 0 & \text{if } v_{s_{node}} - v_{s_{c_{out}}} \leq 0 \end{cases} \quad (20)$$

and the corresponding ‘out-flow’ from the node is defined as  $v_{s_{out}} = v_{s_{node}} - v_{s_{back}}$

Transient volume components defined on the nodes include the total incoming sediment volume from upstream edges  $v_{s_{node}}$ , the combined transport capacity of downstream edges  $v_{s_{c_{out}}}$ , the total back flow to upstream edges  $v_{s_{back}}$  and the resulting out-flow to downstream edges  $v_{s_{out}}$ . While the back-flow is unphysical, the desired outcome is to limit downstream transport where  
255 it is not permissible under criterion 2, while also preserving volume balance under criterion 3. The distribution of outflow  $v_{s_{out}}$  between the downstream edges is proportional to each edge’s contribution to volumetric sediment transport capacity  $v_{s_{c_{out}}}$ , defined as

$$V_{s_{in}} = v_{s_{out}} \frac{V_{s_c}}{v_{s_{c_{out}}}} \quad (21)$$

260 where  $V_{s_c} = Q_{s_c} dt$  for the edge. Similarly, the back-flow  $v_{s_{back}}$  is distributed between upstream edges proportional to their contributions to total volumetric sediment input to the node.

$$V_{s_{back}} = v_{s_{back}} \frac{V_{s_{out}}}{v_{s_{node}}} \quad (22)$$

From these volumes, the flux density  $K = (V_s - V_{s_{out}} + V_{s_{back}})/l_{edge}$  and the incoming flux to the edge  $Q_s = V_{s_{in}}/dt$  are updated, ready for the next timestep in which that edge is analysed.

The grain size distribution is a critical factor for the sediment transport system and is also a key observable for sedimentary records from the ocean and in the subglacial environment. We consider grain size to be a stochastic variable defined by samples from a log-normal population distribution. Studies of till exposures suggest a typical central value on Krumbein's  $\phi$  scale ( $\phi = -\log_2 d$ ) of  $\approx 2.2$  with standard deviation between 1 and 2  $\phi$  (Peterson et al., 2018; Haldorsen, 1981), so defining the population distribution. ~~This~~The stochastic formulation allows spatial and temporal variability of grain size to be accommodated in the model, but also generates variations in sediment transport capacity and virtual velocity, causing time-variable transport conditions.

In the event that new sediment is required, i.e. at the beginning of the model run and due to erosion, we draw a sample from the population distribution and define for that sample a log-normal sample distribution as

$$\ln(d) \sim \mathcal{N}(\mu, \varsigma^2) \quad (23)$$

where  $\mu$  and  $\varsigma$  are the mean and standard deviation of the sample.

At several times in the transport model it is necessary to mix sediment volumes, for example, when newly mobilised sediment is added to existing sediment on the edge, their respective grain size distributions must be combined. For simplicity, the mixture is defined as a new sample composed from the union of volume-weighted samples drawn from each component distribution:

$$\mathbb{R}_{mixture} = \mathbb{R}_{residual} \cup \mathbb{R}_{influx} \cup \mathbb{R}_{mobilised} \cup \mathbb{R}_{bedrock} \quad (24)$$

with

$$\mathbb{R}_{residual} \sim e^{\mathcal{N}_{edge}}, \mathbb{R}_{influx} \sim e^{\mathcal{N}_{node}}, \mathbb{R}_{mobilised} \sim e^{\mathcal{N}_{sediment}}, \mathbb{R}_{bedrock} \sim e^{\mathcal{N}} \quad (25)$$

Each component is defined by a sub-sample drawn from the sample distribution for that component, with a size proportional to the relative component volume, i.e. for a desired sample size  $n$ , the sub-sample for a component that provides half the volume has size  $n/2$ , or the closest integer value. The sub-sample for sediment coming from upstream  $\mathbb{R}_{influx}$  is drawn from the distribution for the upstream node  $e^{\mathcal{N}_{node}}$ , this in turn being defined by the union of volume-weighted samples from the distributions of all incoming edges to the node. The sub-sample for residual sediment  $\mathbb{R}_{residual}$  on the edge is drawn from the distribution for that edge  $e^{\mathcal{N}_{edge}}$  at the start of the timestep; the sub-sample for sediment mobilised from the basal sediment layer  $\mathbb{R}_{mobilised}$  is drawn from its distribution  $e^{\mathcal{N}_{sediment}}$ ; finally, for sediment eroded from bedrock  $\mathbb{R}_{bedrock}$  the sub-sample is drawn from the population distribution  $e^{\mathcal{N}}$ . From ~~the union of these,~~  $\mathbb{R}_{mixture}$ , an updated  $\mu$ ,  $\varsigma$  and  $d_{50}$  are defined for the edge. In the case of deposition to the basal sediment layer the new distribution for the basal sediment layer is defined as the volume-weighted union of the depositional component  $\mathbb{R}_{deposition}$  sampled from the distribution for that edge at the start of the timestep and the residual component  $\mathbb{R}_{sediment}$  sampled from the distribution for the basal sediment layer.

## 2.2.6 Detrital provenance tracking

295 In addition to the grain size, the network transport model can track mixtures of detrital properties, which may represent the  
source(s) of sediment and its characteristics such as bedrock geology, so yielding a provenance distribution at the outlet.  
Detritus tracking is entirely passive and can be omitted to save computational cost. Two modes are enabled in GraphSSEt;  
the ‘normal’ mode keeps track of the sediment source when sediment last joined the active transport system. Three source  
classes are defined: ‘init’ describes active sediment generated in the first timestep; ‘basal’ describes sediment mobilised from  
300 the basal sediment layer and ‘bedrock’ describes sediment derived ~~from erosion that~~ directly from erosion - that is it has never  
been deposited. These properties do not persist through cycles of deposition and remobilisation, hence sediment that has been  
eroded from bedrock, deposited and later remobilised will have ‘basal’ class.

Bedrock tracers such as isotopic data are important fingerprints of glacial erosion that can be reliably recovered from sed-  
iment cores (Licht and Hemming, 2017). Quantitative model-based approaches using these data can constrain cryosphere  
305 processes more reliably, but transport is a source of ambiguity in the detrital provenance problem (Aitken and Urosevic, 2021).  
Supporting this, the second ‘bedrock’ mode tracks a set of detrital ~~source classes~~ classes linked to bedrock erosion, for example,  
bedrock geology classes. In contrast to the ‘normal’ mode, these classes persist through sediment cycles and the characteris-  
tics of the basal sediment layer also becomes defined by its constituent classes. In this mode, ~~there is no distinction between~~  
~~multiply remobilised sediment and fresh bedrock erosion~~ the detrital class is persistent through mobilisation and deposition,  
310 hence sediment that has been eroded from bedrock, deposited and later remobilised will retain its original class.

## 3 Numerical Implementation

Following from the model formulations of Werder et al. (2013) and Delaney et al. (2019), this work considers dynamically  
evolving R-channels as the predominant mode of channelised flow, and only channelised flow is considered to have sufficient  
flux to mobilise sediment and to transport it significant distances over the timescales of interest. Consequently, for a graph  
315 representation of the hydrology system we use the network of channels and their attributes derived from subglacial hydrology  
models. Sediment entrainment into the ice, englacial sediment transport and deposition via glacial-hydrological processes are  
not considered here; glacial transport could be defined to evolve in parallel to the subglacial fluvial transport using a multi-graph  
representation.

### 3.1 Graph representations of subglacial hydrology

320 GraphSSEt is based on ~~representations~~ the representation of the channelised hydrology as a set of connected edges in a  
directed graph. Directionality for each edge is derived from the hydraulic potential gradient direction. In this work, all graphs  
are constructed and manipulated using the NetworkX module in Python (Hagberg et al., 2008). We build the graph directly  
from the GlADS FEM mesh. ~~From the FEM element edges several~~ edges and nodes. Several different types of edges are  
defined including perimeter edges, perimeter-contacting edges, and internal edges. Outlet edges are defined ~~either from the~~

325 ~~FEM boundary conditions, if the flow reaches the model boundary as grounded ice, or where~~ for edges where ice becomes  
ungrounded (hydraulic potential is zero at either node, but not both-), so representing a virtual grounding line, or where edges  
reach the downstream model boundary. Entirely floating edges, where hydraulic potential is zero at both nodes, are excluded  
from the graph. ~~Directionality for each edge is derived from the hydraulic potential gradient direction~~ The examples studied  
here do not include any lakes or hydraulic sinks, however, these are automatically handled as follows: lakes with ice at flotation  
330 will be ringed by outlet nodes and edges, no sediment transport can occur across the lake and sediment will leave the model.  
Hydraulic sinks with grounded ice do not form part of any viable pathways to the outlet nodes, and they are implicitly excluded  
from the network. Edges are populated with properties ~~required~~ for the dynamic sediment model including spatial coordinates,  
edge type, edge length, edge direction flag, hydraulic potential gradient magnitude, channel sectional area, and channelised  
water flux.

335 Graph nodes contain the characteristics of the ice and distributed water sheet flow. Several node types are defined, including  
floating nodes (hydraulic potential of zero), perimeter nodes, and predefined ‘moulin’ nodes where focused water input is to  
be applied. Head nodes are defined at nodes with no predecessor edges, outlet nodes are defined ~~either~~ at the downstream  
~~domain boundary or at the downstream~~ node of outlet edges. Nodes are populated with ~~required~~ properties including spatial  
coordinates, node type, surface and bed elevation, hydraulic potential, effective pressure, basal ice velocity magnitude, and the  
340 thickness of basal water layer. An example of a graph representing a hydrological model scenario is shown in Figure 2.

~~Key to our approach is~~ Our approach includes the definition, from this main graph, ~~targeted of flow-defined~~ subgraphs that  
enable a flexible and sparse representation of the channelised flow network and ~~therefore~~ allow more efficient computation, and  
variable return time to edges. Subgraphs are views of the main graph, and so define a hierarchical set of graphs that capture the  
most essential components of the network without sacrificing generality. For steady-state model runs, with no variation in the  
345 hydrology conditions, we define these subgraphs only once, however for non-steady-state model runs, in which the hydrology  
conditions vary, a fresh subgraph view is generated every timestep.

### 3.1.1 Graph connectivity measures for effective hydrology representation

Subgraphs may be defined according to several criteria, but our principal goal is to define for a given hydrology model scenario  
the most important edges to represent the channelised drainage system effectively, and so to reduce the magnitude and com-  
350 plexity of the model. Edge weights are assigned according to the channel area, which is a robust feature of the GlaDS model  
(equation 8) and is closely linked to the magnitude of water flux and the channel width. For the weighted graph we calculate  
edge betweenness centrality which represents the relative frequency that each edge is found on the shortest-paths between all  
source node-target node pairs (Brandes, 2001). For the problems here we use the formulation

$$c_B(e) = \sum_{s,t \in V} \frac{\sigma(s,t|e)}{\sigma(s,t)} \quad (26)$$

MainImages/Figure2\_v2.png

**Figure 2.** a) The level 0 graph representation of the SHMIP model scenario A5 comprising edges on all valid paths. Head nodes are nodes with no predecessor nodes, outlet nodes are defined at the 'grounding line'. Input nodes are a randomly selected subset of **other**-nodes, used to define the network geometry. This model scenario has no moulin nodes. b) the hydraulic potential gradient defined on edges c) the effective pressure defined on nodes, d) the thickness of the sheet  $h_w$  defined on nodes and e) the channelised water flux defined on edges

355 where  $V$  is the set of all nodes,  $s$  is the set of source nodes and  $t$  the set of target nodes.  $\sigma(s, t)$  is the number of shortest paths for that node-pair while  $\sigma(s, t|e)$  is the number that pass through the edge  $e$ . In this work we normalise edge-betweenness centrality as  $1/(|s|(|t|-1))$  where  $|s|$  and  $|t|$  are the total number of source and target nodes respectively. Therefore, a normalised edge betweenness centrality  $> 0$  means the edge was on at least one shortest path, while an edge betweenness centrality of 1 implies the edge is on every shortest path.

360 To define transport on the graph it is necessary to have enough node pairs to represent the extent of valid flow paths. For maximal precision all nodes can be used, but to reduce computation time a sub-selection is used instead. Source nodes include all head nodes and moulin nodes and a ~~randomly selected random~~ set of  $n$  input nodes ~~representing the distributed hydrological inputs; target to represent a spatially distributed hydrological input.~~ Target nodes are the outlet nodes. In this case  $n = 100$  and with 37 head nodes and 24 outlet nodes, gives  $\sim 3000$  shortest paths. A directed graph will be less well sampled upstream  
365 relative to downstream.

~~From~~ For a more focused representation of the high-flux channels, using edge betweenness centrality we define hierarchical subgraphs as views of the ~~main graph (level 0)~~ for a more focused representation of the high-flux channels subgraph (Fig. 3). In this case we define two further subgraph levels, with edge betweenness centrality  $\geq 0$  (level 1) ~~and  $\geq$~~ , comprising all edges on at least one shortest path and  $> 0.005$  (level 2). ~~For the~~, comprising edges on 16 or more shortest paths. For example, in model  
370 scenario A5 (see section 4), the level 1 subgraph includes 98% of total channelised flow on 31% of the edges, while the level 2 subgraph includes 97% of total channelised flow on 20% of the edges. Crucially, the high-flux edges are evolving dynamically with much higher sediment transport capacity and so we may analyse these subgraphs more frequently than the main graph, so reducing the computation cost without loss of precision. Besides computational benefit, the graphs for different model scenarios show a diversity of network characteristics that define how water (and sediment) are transported, with significant  
375 implications for understanding the sensitivity of sediment flow-organisation to changes in the hydrological system.

### 3.2 Sediment modelling approach

In line with section 2.2, we run the sediment transport model in several steps. For each model run we initialise the graph ~~in the first timestep with required properties not defined by the input hydrology model scenario including initial~~ with the grain-size distribution,  $d_{50}$ , and the basal sediment thickness as stochastic variables, grain density ~~which is a constant here~~, and erosion  
380 potential. For each edge we calculate local transport capacity as in eq. 10 and sediment mobilisation as in eq. 13. The network-scale transport model is applied, and we update the bed elevation and basal sediment thickness as defined in eq. 15. The final, optional, stage of the GraphSSeT model is to apply the detrital provenance tracking (section 2.2.6).

For the grain size distribution we use a stochastic sampling procedure. For steady-state model runs, the grain size distribution is seeded with a random number array that has, for each edge (or node) at each timestep a sample of size  $n = 1000$  drawn from  
385 the standard normal distribution (mean = 0, standard deviation = 1). The input seed array spans the first two-weeks of the model time period, after which samples are drawn from a shuffled array. For non-steady-state model runs, every timestep we draw a new sample for every edge (or node) from the standard normal distribution. To generate the real valued distributions, each sample is scaled by  $\varsigma$  and offset by  $\mu$  for the relevant ~~distributions~~ distribution.

## 4 Model scenarios and model inputs for this study

390 To define controls on the subglacial fluvial sediment transport system, a series of experiments were conducted with synthetic model scenarios derived from the Subglacial Hydrology Model Intercomparison Project, SHMIP (De Fleurian et al., 2018).

MainImages/Figure3ab\_V2.png

MainImages/Figure3cd\_V2.png

**Figure 3.** a) edge betweenness centrality (EBC) for the SHMIP model scenario A5 [computed](#) on the L0 graph, source nodes include moulins, head nodes and randomly selected input nodes, while target nodes are the outlet nodes b) L1 and L2 hierarchical subgraphs derived from EBC thresholds of  $> 0$  and  $\geq 0.005$  respectively. c) and d) show the same as a) and b) for model scenario A6. These examples do not have any moulin nodes

We do not wish to study here the hydrology model differences and we ~~model-only examples from the ‘mw’ series of models~~ [consider only the examples](#) computed with GlADS.

395 Three series of SHMIP models were used. The A-series represent hydrologic steady-state with a distributed water input to the sheet ( $m_b$ ) applied at a constant rate and distributed equally across all nodes in the domain. The B-series represents a hydrologic steady-state with both distributed and focused water inputs. Only a small distributed water input to the sheet is included, while focused water input ( $m_s$ ) is applied through moulin nodes, at a constant rate, but with differing intensity between scenarios. For these model scenarios, the hydrology network was developed dynamically over a time period of ca. 21 years. The C-series represents a hydrologic non-steady-state and involves time-varying water input to moulins on a diurnal



400 cycle from  $\frac{1}{4}$  to 2 times the base input. The C-series models build on the final state of the model scenario B5, with 100 moulins, and the hydrology network was developed over an additional time period of 50 days.

The base scenario ~~for all experiments~~ is the model scenario A5, with water input to the ice sheet bed at a moderate level ( $4.5 \times 10^{-8}$  m/s or ~~ea.~~  $\approx 3.93$  mm/day). Default experimental parameters and properties for our experiments are presented in table 1. For steady-state model scenarios the last timestep of the hydrology model scenario was used to force the sediment model.  
405 Most model runs were conducted over time period of 26 weeks, analogous to a summer season. The model run comprised daily cycles of 8 three-hour timesteps: the first and last use the level 0 subgraph, and in between a cycle of six timesteps alternating between the level 1 and level 2 subgraphs. This cycle captures the potential for higher-flux channels to evolve more rapidly, while ensuring the whole network is covered sufficiently often. For non steady-state model runs the sediment model is a down-sampling of the original hydrology model scenario timesteps. This sampling need not be linear, but in this case, the hydrology  
410 model state was reported every hour and we ran the sediment models at this sample interval.

Experiment set 1 was conducted for the A-series model scenarios with default parameters to demonstrate the effect of increasing basal water supply to the model. Experiment set 2 was conducted with the model scenario A5 and establishes the sensitivity to major parameters including the initial basal sediment layer thickness, the erosion scaling,  $\Delta\sigma$ , the grain size distribution, and grain density. Experiment set 3 considers the effect of focused water input using the B-series model  
415 scenarios, while experiment set 4 considers diurnally time-varying water input using the C-series model scenarios. Finally, we demonstrate several model runs with the ‘bedrock’ detrital provenance tracking mode enabled ~~using a graticule bedrock classification.~~

#### 4.1 Reference and default models

For each hydrology model scenario, we ran ~~at least two default model runs and~~ a reference model scenario with no grain  
420 size variation and two model runs with default parameters. The default model has an initial randomly defined basal sediment thickness of  $0.25 \pm 0.125$  m; and erosion scaling as  $2.07 \times 10^{-7} u_b^{2.02}$  (Herman et al., 2018). The mean grain size is  $\phi = 2.2 \approx 0.218$  mm and  $\varsigma = 1.5$ , corresponding to typical grain size distributions of subglacial till (Peterson et al., 2018; Haldorsen, 1981). The reference model scenario has the same variables as the default except for  $\varsigma$  is ~~set to zero, and so the outcome indicates the sediment model with no variation in grain size~~ zero.

425 The hydrology model scenario A5 generates two major channels, one in the ‘south’ of the model and the other more central, which has greater ~~channel~~ flux (Fig. 2e). Edge betweenness centrality subgraphs define a linear-dendritic network geometry comprising numerous minor channels convergent with the major channels along their length and a divergent network near the outlet nodes. This divergent network accommodates the ~~potential pathways~~ for flow to all outlet nodes (Fig. 3a). The reference model run generates a nearly constant sediment discharge rate at the outlet nodes (Fig. 4) representing the combined transport-  
430 capacity of the outlet edges. Total sediment discharge over 26 weeks for the reference model is  $2.75 \times 10^4$  m<sup>3</sup>, the vast majority from the central subglacial channel. The default models show significant variations in sediment discharge rate occurring in line with the grain size distribution (Fig. 4). In these model runs the initial basal sediment layer is rapidly removed along the major

MainImages/Figure4\_colsafe.png

**Figure 4.** The reference run and two ~~default separate~~ runs ~~for with default parameters all using~~ the hydrology model ~~setup scenario~~ A5. ~~Solid~~ For each, ~~solid~~ lines show the cumulative ~~volume-of-total~~ sediment discharge, dashed lines show cumulative ~~volume-of-bedrock~~ sediment discharge, ~~derived directly~~ from erosion of bedrock. ~~The difference is the cumulative sediment discharge from remobilised basal sediments.~~ Dotted lines show cumulative mean grain-size relative to the initial mean.

channels, which subsequently remain largely sediment free, but more widespread mobilisation of sediment does not occur. The proportion of bedrock-derived sediment consistently increases from ca. 5 weeks on.

#### 435 4.2 Experiment Set 1

In experiment set 1 we compare the impact of ~~increasing steady-state GlaDS scenarios with variable~~ basal water input ~~for steady-state models~~, run with default ~~settings parameters SHMIP~~ Model scenario A4 considers a low-level of basal water input of 2.16 mm/day, and represents threshold conditions for channelised flow. SHMIP model scenario A6 has a much greater input of 50 mm/day representing peak water discharge driven by surface melt in Greenland-like conditions (De Fleurian et al.,  
440 2018). Two additional GlaDS models were run in between A5 and A6 with flux rates of 21.6 mm/day (A7) and 39.3 mm/day (A8). The network geometry of all these models is linear-dendritic with, as flux increases, the development of closer-spaced and longer channels (Fig. 5).


These model scenarios generate substantially different conditions for sediment transport with total sediment discharge for the default A4 model just  $1.79 \times 10^3 \text{ m}^3$ , for A5  $2.55 \times 10^4 \text{ m}^3$  and for A6  $4.60 \times 10^5 \text{ m}^3$ ; the intermediate models A7 and  
445 A8 generate discharge of  $1.01 \times 10^5 \text{ m}^3$  and  $3.72 \times 10^5 \text{ m}^3$ . Grain-size evolutions for the higher flux model runs show a consistent pattern of initially flat or increasing grain size for 5-10 weeks, followed by a systematic reduction in grain size. These variations in grain size are associated with variations in sediment discharge (Fig. 6). The interpretation is that for higher flux model runs the selective transport of finer-grained material from upstream comes to increase discharge rates by increasing sediment transport capacity. Lower flux model runs show no such grain size reduction indicating that selective transport is not  
450 as significant in low-flux conditions.

MainImages/Figure5.png

**Figure 5.** a) sedimentary layer thickness and b) median grain size at the end of the A5 default model run. c) and d) show the same for the A6 default model run. Note the selective transport for model A6 with finer-grained sediment in the major channels

**Table 1.** Tested parameters in Experiment Set 2, conducted with the model scenario A5

Parameter	Default value	Test values
Mean grain size $\phi$	<u>2.2 (0.218 mm)</u>	<del>0.218</del> <u>3.2 (0.109 mm)</u> ; <u>1.2 (0.436 mm)</u>
Grain size $\varsigma$	1.5	1;2
Grain density (kg/m <sup>3</sup> )	2650	2550; 2750
Initial sediment thickness (m)	0.25 ± 0.125	0.05 ± 0.025; 0.5 ± 0.25
$\Delta\sigma$ (m)	0.001	0.005;0.01
Erosion scaling	$2.7e^{-7}u_b^{2.02}$	$1e^{-4}u_b$ ; $2e^{-4}u_b$ ; $1e^{-7}u_b^{2.02}$



MainImages/Figure6\_colsafe.png

**Figure 6.** Sedimentary output for all the models of experiment set 1-Solid-1 with default settings. For each, solid lines show the cumulative total sediment discharge and dotted lines show cumulative mean grain size relative to the initial mean.


## 4.3 Experiment Set 2

### 4.3.1 Grain size distribution and its variance


In experiment set 2 we vary selected input parameters from the default parameters (Table 1) ~~from the default settings~~ to gauge their importance for sediment transport. Grain size is fundamental to both transport capacity (equation 10) and transport velocity (equation 18) and also varies naturally across several orders of magnitude (Peterson et al., 2018; Haldorsen, 1981). Here we test the impact of this parameter, varying both  $\mu$  and  $\varsigma$  of the population distribution. In the former case (Fig. 7a) we see the profound impact of the value of  $\mu$ : overall discharge for a mean of  $\phi = 1.2$  (grain size 0.436 mm) is  $7.96 \times 10^3 \text{ m}^3$ , but with a mean of  $\phi = 3.2$  (grain size 0.109 mm) discharge is  $6.25 \times 10^4 \text{ m}^3$ . Changes in the grain size distribution during the model run indicate that selective transport occurs for the finer-grained model runs, causing a reduction in grain size from 10-15 weeks, however the coarser-grained model run does not show evidence of selective transport developing (Fig. 7a).

The variability of grain size is also significant with higher variance associated with increased discharge and finer at-outlet grain size, while lower variance is associated with reduced discharge and coarser at-outlet grain size (Fig. 7b). The interpretation is that samples with a coarser median grain size will reduce transport capacity and the associated sediment volume can be transported only slowly. In contrast, samples with finer median grain size, should be transported rapidly through the graph. Consequently, while higher variance will develop coarse and fine grained samples equally, only the fine-grained samples will propagate ~~to the~~ through the graph and influence discharge at the outlet. In Figure 7b with  $\varsigma = 2$  strong selective transport reduces the grain size markedly from ca. 10 weeks onwards, while for  $\varsigma = 1$  the grain size increases steadily.

Grain density is in principle a very important factor for sediment transport capacity (eq 10), but due to a relatively limited range, its effect is minor in comparison to the grain size. The influence of a higher and lower grain density was tested, and showed that the model run with lower grain density is not associated with increased discharge overall, while the model run



MainImages/Figure7a\_colSAFE.png



MainImages/Figure7b\_colSAFE.png

**Figure 7.** Sediment output with variations in a) grain size distribution mean and b) grain size distribution standard deviation, using scenario A5. For each, solid lines show the cumulative total sediment discharge volume, dashed lines show cumulative bedrock sediment volume discharge, derived directly from erosion of bedrock (never deposited), and dotted lines show cumulative mean grain-size relative to the initial mean

with higher grain density is associated with a moderately reduced discharge. This deviation may be explained by changes in grain size, rather than necessarily a direct impact of grain density. Overall, grain density does not lead to large variations in either the sediment discharge volume or grain size at the outlet nodes.

#### 4.3.2 Basal sedimentary layer thickness and $\Delta\sigma$

475 The thickness of the initial basal sediment layer is important for sediment transport because this material is available to be mobilised whenever transport capacity exceeds supply from erosion. We tested the impact of this initial condition with a reduced initial thickness of  $5 \pm 2.5\text{cm}$  and an increased initial thickness of  $50 \pm 25\text{cm}$  (Figure 8). For these model runs, higher initial sediment thickness has increased total discharge (Figure 8). Although we may expect an enhanced supply for a greater

MainImages/Figure8\_colsafe.png

**Figure 8.** Sedimentary output with variable initial basal sediment layer thickness,  $h_s$  using scenario A5. For each, solid lines show the cumulative total sediment volume discharge, dashed lines show cumulative bedrock sediment volume discharge, derived directly from erosion of bedrock (never deposited), and dotted lines show cumulative mean grain-size relative to the initial mean

initial thickness, the effect is in-line with the expected impact of grain-size variations. More significant are the delay in the onset of bedrock erosion to 15 weeks in the high initial thickness run, and a much lower proportion of bedrock-derived sediment (Figure 8).

Sediment mobilisation is modulated by the parameter  $\Delta\sigma$ , which controls the transition between the supply-limited and transport-capacity limited regimes (eq. 13c). Increases to  $\Delta\sigma = 0.005$  m and  $\Delta\sigma = 0.01$  m caused little variation in the overall sediment discharge, but had a marked effect in reducing the proportion derived from the bedrock.

The importance of the basal sediment layer is not only increased supply, but also protection of the bedrock from erosion. With  $h_s$ ,  $h_{max}$  and  $\Delta\sigma$  control access to the bed and higher values for these bedrock. Higher values for  $h_s$  and  $\Delta\sigma$  sustain the basal sediment layer for longer. This enhances potential sediment supply and reduces the proportion of bedrock-derived sediment. Higher values for  $h_{max}$  will tend to increase the proportion of bedrock-derived sediment. Furthermore, in the case of deposition and remobilisation, a greater volume of basal sediment acts as a ‘buffer’ in grain size mixing calculations, which may influence grain size evolution and selective transport. Although important, the basal sediment layer had, for this model scenario, a small overall effect on the volume and grain size of sediment discharge.

### 4.3.3 Erosion law scaling

The supply-limited regime, and its distinction from the transport-capacity limited regime, is fundamentally constrained by the rate of bedrock erosion (eq. 12), which in GraphSSEt is controlled first by the protective effect of the basal sediment layer, and second by the basal ice velocity (in this case, a constant at  $1 \times 10^{-06}$  m/s in this case), and third by the choice of erosion scaling law. Velocity-based erosion scaling laws with linear and ‘velocity-squared’ laws are both common, although other exponents are possible (Herman et al., 2018, 2021; Cook et al., 2020). For our model scenario, with a ‘velocity-squared’ scaling, reducing

MainImages/Figure9\_colsafe.png

**Figure 9.** Sedimentary output with different erosion scaling laws using scenario A5. Scaling laws are for velocities expressed in m/a. **Solid** For each, solid lines show the cumulative total sediment volumedischarge, dashed lines show cumulative bedrock sediment volumedischarge, derived directly from erosion of bedrock (~~never-deposited~~) and dotted lines show cumulative mean grain-size relative to the initial mean.

the pre-exponent had little effect on the model (Fig. 9). The linear scaling, in general, provided additional discharge and showed greater sensitivity to the scaling parameter (Fig. 9). However, the effect is much less marked than the variation in the erosion potential itself, which is a factor of ~~ea-~~ ~ 30-60 times greater. The interpretation is that the effects of basal sediment thickness and capacity limited transport restricted the influence of erosion potential. More generally, if the system is transport capacity-limited and has an extensive basal sediment layer, then erosion potential will have a limited impact on sediment discharge. The effect on supply is seen in the ~~basement-derived~~ bedrock-derived sediment which has a greater volume proportion and earlier onset with the linear scaling law (Fig. 9).

#### 505 4.4 Experiment Set 3

In experiment set 3 we ~~investigate~~ investigated the influence of concentrated hydrological inputs with a scattered distribution (De Fleurian et al., 2018). In this experiment set the volumetric water input is identical to the A5 model scenario but comprises only a small distributed basal input (0.006 mm/day), with the remainder split between  $n$  randomly selected input nodes representing moulins. Models B1 through B5 investigate this flow for  $n = 1$  to  $n = 100$ , with a corresponding volumetric water input for each of  $90 \text{ m}^3/\text{s}$  to  $0.9 \text{ m}^3/\text{s}$ . For each of these model scenarios we ran four sediment transport model runs. The results indicate that the distribution and intensity of focused water inputs are significant for sediment flux. The least sediment discharge occurs for the model scenario B1 with total discharge consistently below  $5000 \text{ m}^3$ . B1 has a single moulin that yields a single channel, but is not effective in accessing the bed more broadly. The other model runs return variable sediment discharge, but in general the greatest discharge occurs for model B2, while B4 tends to have the least ~~-(Fig. 10)~~. These model runs have typically lower discharge than the runs for model scenario A5.

MainImages/Figure10\_colsafe.png

**Figure 10.** Sedimentary output for the default models of experiment set 3. **Solid** For each, solid lines show the cumulative total sediment discharge and dotted lines show cumulative mean grain-size relative to the initial mean. **Basement** **Bedrock** components are not shown

These model scenarios have only small **difference** **differences** in water flux at the outlet and in total channel volume, but they do have significant differences in the distribution and extents of channels and these are interpreted to dictate the sediment transport. First, relative to model runs for scenario A5, the channel geometry is less well connected from the outlets to the inland areas of the domain, so limiting the area exposed to channelised flow. Second the main channels have typically reduced water flux. These combined effects lead to generally lower and more variable sediment discharge for a given total water input.

#### 4.4.1 Experiment Set 4

For experiment set 4 we investigate the influence of non-steady state hydrology with a diurnal time-variable input over a period of 50 days. The total volumetric input, and the locations of the moulins, are identical to the model scenario B5 but the input is varied according to a diurnal sinusoidal cycle

$$R(t, R_a) = \max\left(0, m_s \left[1 - R_a \sin\left(\frac{2\pi t}{s_d}\right)\right]\right) \quad (27)$$

where  $t$  is the time in seconds,  $s_d$  the number of seconds per day and  $m_s = 0.9 \text{ m}^3/\text{s}$ . The amplification factor  $R_a$  is tested across a range from 0.25 (C1) to 2 (C4), noting that for  $R_a > 1$  it is necessary to truncate the function to remain non-negative (eq. 27). This leads to a slight increase in total flux volume for the model scenario C4. We run in addition to these a C0 model which uses the same run procedure but without any diurnal variation.

For these runs, the sediment model is run with some modifications to the approach. With variable hydrology, edges may change status during the run (e.g. by becoming ungrounded) or flow-directions may be reversed. This demands that a fresh graph is constructed for each timestep, and from this graph we recompute edge betweenness centrality and generate the desired subgraph. In this way the network geometry dynamically evolves with the hydrology model. We run the model with a one-hour



MainImages/Figure11\_colSAFE.png

**Figure 11.** Sedimentary output for the models of experiment set 4. ~~Solid~~ For each, solid lines show the cumulative total sediment ~~output~~ discharge and dotted lines show cumulative mean grain-size relative to the initial mean.

timestep, in line with the hydrology model outputs and run in each day 8 cycles of three iterations, these being run on the L2,  
535 L1 and L0 graphs in that order.

The results (Fig. 11) indicate that the magnitude of the diurnal cycle impacts on sediment flux such that higher intensity in the diurnal cycle is associated with increased sediment discharge during periods of peak water input, while the corresponding reduction during low-input periods is limited. The increased discharge is due to increased sediment concentration during daily peak flow, which reaches 60-100 ppm in the C4 runs versus peaks of 10-30 ppm for the C1 runs. The relationship is consistent  
540 with increased transport capacity at peak flow due to increased basal shear stress from fast water flow, in line with eq 10.

#### 4.4.2 Detrital examples

For these model runs we track ~~bedrock classes~~ the detrital property of 'bedrock class' through the network. For our bedrock ~~classes we use a graticule with~~ classification we use here a graticule (Figure 12a) with five classes from the front to the back (0,1,2,3,4) and three classes across the model width ~~and five classes from the front to the back (Figure 12a(L, C and R)).~~ These  
545 classes represent spatial areas of the same size, but in principle could be any property the user wishes to track (for example bedrock geology). Material eroded from nodes ~~located within the graticule element~~ possessing the detrital property are assigned the associated class for the purpose of detritus tracking.

The distribution of detritus for these model runs indicates significant differences in the erosion, mobilisation and transport of detritus. Systematic changes are seen in the degree of access to inland classes between models (Fig 12). For these model  
550 scenarios, erosion potential is uniform throughout and so the differences seen are due to bed access through sediment cover, and the effectiveness of the transport system.

In all cases the early part of the model run is dominated by mobilisation of basal sediment, the volume of which reduces significantly during the model run as the initial basal sediment is depleted. For model run A4D the hydrology network is limited

MainImages/Figure12a\_colsafe.png

MainImages/OutletCumulativeVolumeDetritus\_A4D\_A5D\_A8D\_A6D.png

**Figure 12.** a) Map of graticule classes. b) to e) stackplots of cumulative volume by class as a proportion of total volume for the model runs A4D, A5D, A8D, and A6D. The class 'init' represents initial active sediment on edges, 'basal' represents the initial basal sediment layer; neither of these is associated with spatial location.

555 in inland extent and bedrock-derived detritus is dominated by classes '000L', '010C' and '020R', reflecting transport at the margin, but with some class '411C' due to the central channel. For model run A5D, the detrital signature is different, with the classes '22' '412R' '1C' and '010C' dominant. These classes underlie the main channel where bedrock is exposed (Fig. 5). Moreover, the dominant class is '222R' transported from the upstream catchment: as is expected from eq. 13, transport of

incoming active sediment is prioritised over eroded or remobilised sediment and so the downstream classes '11C' and '00C' are subordinate to class '22'. (Fig. 12). High flux model runs A8D and A6D are markedly different to the preceding, with first a greater proportion of detritus from basal sediment, and second a much more uniform sampling of bedrock classes. This indicates a much broader sampling of the bed, extending across almost the whole domain. Model run A6D has an especially enhanced contribution-enhanced pulse of detritus from class '20L' from weeks 15 to 20. This corresponds to a period of low grain size, suggesting a strong grain-size driven selective transport event stemming from that region, and propagating to the outlet.

## 565 5 Discussion

### 5.1 Geological controls on sediment flux

The dominant geological factor is grain size distribution, which controls transport capacity variations and in particular drives the evolution of selective transport. The transport system self-organises in response to stochastic variations in grain size: coarser grain sizes are not transported efficiently and tend to move slowly through the network; smaller grain sizes are preferentially transported and will tend to progress rapidly through the network. A tendency is seen in many of the model runs for increasing grain size early in the run (up to ca. 10 weeks) and then, for most higher-flux runs a systematic reduction in grain size. In contrast most of the lower-flux model runs do not show any decrease in grain size. The evolution may be explained by the ice-sheet geometry, with a region of high potential gradient from 5 to 20 km upstream (Fig. 2) in which relatively coarse-grained sediment can be transported. The coarser-grained sediment can be transported off the network only slowly. In model runs with higher flux, finer-grained sediment is transported from further upstream due to selective transport, leading to a significant increase in transport capacity through time.

The thickness of the basal sediment layer is a key factor for sustained sediment supply and controls access to the bedrock (Delaney and Adhikari, 2020). A further effect of basal sediment thickness occurs during the mixing of sediment, as this layer is an important buffer for the evolving grain-size distribution and through this exerts further control on sediment transport dynamics. Particularly, the onset of volumetrically-abundant bedrock derived detritus is in many model runs coincident with significant reductions in the at-outlet grain-size distribution. This is a consequence of the feedback between transport capacity, mobilisation, and grain size buffering. Under selective transport, sediment flowing into an edge will often have a finer grain size distribution than the residual sediment which will increase the transport capacity and is likely to cause remobilisation of basal sediment. In most cases this will be coarser-grained and so partially offset the increased transport capacity, but as basal sediment is lost the buffering effect of this layer is reduced and so the selectivity of the transport system is enhanced. For coarser-grained incoming sediment the reverse effect is expected and the drop in transport capacity will lead to deposition and coarsening of the basal sediment leading to inhibited flow through the edge until sufficient finer-grained sediment arrives.

## 5.2 Glaciological controls on sediment flux

In our experiments, varying the erosion potential scaling law had a limited impact on sediment flux, as this factor is subordinate to the effects of the basal sediment layer, and because the model runs are transport-capacity limited. As a consequence, the composition of detritus reflects variations in transport rather than supply. This suggests that, for correct representation of the detrital signatures of glaciers and ice sheets it is ~~important~~ critical to understand the transport as well as erosion (Aitken and Urosevic, 2021). Our input model scenarios have ~~everywhere the same basal velocity, have~~ no topography, and no ~~variation in spatial variations in ice-sheet basal velocity,~~ bed roughness or bedrock erosive properties, and therefore no variation in erosion potential. In the general case, variable erosion rates may occur due to variations in basal sliding velocity, in bedrock roughness and in erodability of the bedrock (Alley et al., 2019). A secondary effect is the potential impact of variations in bedrock lithology, joint frequency and structure orientation on at-source grain size distribution (Krabbendam and Glasser, 2011; Hooyer et al., 2012). ~~Variable~~ Variations in erosion rates and at-source grain size distributions would cause both sediment supply and transport capacity to vary in ways that might significantly impact network-scale transport dynamics.

## 5.3 Hydrological controls on sediment flux

### 5.3.1 Water input controls on sediment flux

Experiment set 1 assessed the effect of basal water input on the discharge of sediment. For lower amounts of basal water input, the channel system is less extensive but with higher amounts of basal water input these channels become more numerous and extend further inland. With no topography or other constraints in these model scenarios, the network geometry self-organises to form linear-dendritic channel networks, with little interaction between channels (Hewitt, 2011). In the model scenarios, the overall relation of sediment discharge to basal water input scaled linearly with the total channel volume. Across all model runs, the best fit scaling per unit width was  $Q_s \approx 0.042 \sum S l_{edge} - 1.28 \text{ m}^3/\text{a}$ . While low flux model scenarios have minimal channelisation and low sediment discharge, higher-flux scenarios have extensive and well-formed hydrology networks. These networks have a much greater capacity to access the bed and to mobilise sediment across the broader domain (Figs. 5 and 12), leading to an increase in sediment discharge.

Experiment set 4 tested the effect of diurnal variations in water input via moulins. The model runs in this suite typically generated additional sediment flux relative to an identical series run without temporal variation. Furthermore, the greater the variability the greater the sediment discharge, in particular for model C4 (Fig. 11). Due to a limited capacity for the channel geometry to adjust to short-term variations in water input, water velocity within the channels will increase, causing transient peaks and troughs in sediment transport capacity, and therefore, discharge. Furthermore, while the discharge peaks may be significantly higher than the background level, the corresponding troughs have little influence on total sediment discharge and so a systematically higher total sediment discharge is seen.

### 5.3.2 Network geometry controls on sediment flux

Experiment set 3 tested the effect of different configurations of moulins on the sediment flux, from broadly scattered inputs (100 moulins) to highly focused inputs (1 moulin), with the same overall flux distributed between them in each case. The single moulin model provided an exceptional result that one major high volume channel develops, but with little capacity to access the bed outside of this channel, and sediment discharge is always small. Sediment discharge for the other results were highly varied, but were reduced relative to the model runs for the scenario A5. The configuration of moulin inputs is accompanied by significant changes in the network flow configuration, with less extensive channel distributions, and less well connected networks. The interpretation is that the extent and connectivity of channels is a limiting factor for efficient sediment transport at network scale. In the absence of other constraining factors, a completely distributed input will naturally self-organise with respect to forming regularly spaced channels and flow discrimination into ‘catchments’ within which flow-connectivity is high (Hewitt, 2011), generating an efficient sediment transport network. With a network involving higher-flux at predefined input locations, network geometries must adjust to hydrological inputs that may not be well located with respect to the development of a channelised flow network (Gulley et al., 2012) and so the capacity to mobilise and transport sediment effectively at network scale is inhibited.

### 5.4 Comparison with observational data

We may compare our sediment discharge to estimates of total sediment flux from glacial systems around the margins of Greenland, for which estimates exist for Petermann Glacier of between 1080 and 1420  $\text{m}^3\text{a}^{-1}\text{m}^{-1}$  (Hogan et al., 2012) and Jakobshavn Isbrae of 1030-2300  $\text{m}^3\text{a}^{-1}\text{m}^{-1}$  (Hogan et al., 2011), and more generally estimates of sediment transport-rates in the range of hundreds to thousands of  $\text{m}^3\text{a}^{-1}\text{m}^{-1}$ . In contrast, total sediment discharge from our model runs is typically below 50  $\text{m}^3\text{a}^{-1}\text{m}^{-1}$ , substantially less than observed volumes. We infer the low volumetric output of these model scenarios to be due to a very small catchment size relative to natural systems, being only 2000  $\text{km}^2$  versus tens of thousands of  $\text{km}^2$  for the catchments above.

Looking to sediment concentration, in the steady-state models the mean volumetric sediment concentration varied between 0.5 to 90 ppm, and was in the range ca. 20-30 ppm for most model runs. For a grain density of 2650  $\text{kg}/\text{m}^3$  these concentrations correspond to a range of ca. 1.3 to 240  $\text{mg}/\text{l}$ , but typically in the range of 50 to 80  $\text{mg}/\text{l}$ . Concentrations during high-flux periods were potentially much higher, often in the range of 200 to 400 ppm (or 500 to 1000  $\text{mg}/\text{l}$ ). Overall the sediment concentrations are within expected ranges for subglacial meltwater plumes reported in the literature (Chu et al., 2009; Schild et al., 2017; Overeem et al., 2017)

## 5.5 Model performance and development

### 5.5.1 Limitations and further development

The model runs presented here have addressed the main drivers of subglacial fluvial sediment transport ~~-.The model runs do not cover-~~ with multi-diurnal to seasonal synthetic scenarios. We do not include any long-term ~~evolutions, which may~~ involve new drivers that runs, for which new drivers are superimposed on the above, ~~for.~~ For example, sustaining ongoing sediment supply becomes a more critical condition (Delaney and Adhikari, 2020) while seasonal to ~~multiannual~~ multi-annual variations in hydrology superimpose additional variability to model forcing that may cause systematically different sediment transport conditions. Furthermore, we do not include topography, which is critical for hydrological flow organisation and will significantly control hydrology network geometry and flow-routing (Hiester et al., 2016). Variable ice sheet flow through space and time also will impact on channelisation and erosion, and may be a significant driver of variable sediment supply. Application to subglacial hydrology models of real systems carries some additional challenges, including greater model size and complexity, multi-catchment structure, and the potential presence of hydraulic sinks, lakes and diffuse, time variable grounding zones. The current model design is sufficient to address all the above ~~scenarios with different input scenarios.~~ and these are being addressed further in applications of GraphSSeT to systems in Greenland and Antarctica.

In the preceding, GraphSSeT has used a semi-circular R-channel geometry consistent with the GlaDS hydrology model, and therefore assumes a flat-bedded channel to calculate basal shear stress and sediment transport capacity (Eqs. 9 10). In addition, the mean water velocity is used. In principle, GraphSSeT may accommodate any channel geometry for which the basal shear stress can be determined, potentially including rectangular, U-shaped and V-shaped incisions into the sediment layer, should these be compatible with the subglacial hydrology model used as forcing.

Grain size dependent transport has emerged as a key component of the transport model, with high sensitivity to changes in the grain size distribution causing selective transport and non-linear behavior. A more tightly-constrained grain size may in principle allow more consistent results, but this is unrealistic for glacial sediments that are generally unobserved due to ice cover, and in any case are characterised by highly variable grain size (Haldorsen, 1981). Alternatively, model ensembles are needed to mitigate the impact of the stochastic grain-size variations and to define with greater accuracy the expected sediment volume and characteristics for the glacial-hydrological scenario of interest. One limitation of the model presented here is that, although multimodal grain size distributions are likely to develop through mixing processes, these will be poorly represented by the unimodal grain size distributions used in this implementation. A Gaussian mixture model or a cumulative probability distribution approach could allow multi-modal distributions to be accommodated within the model design.

### 5.5.2 Computational considerations

Model development has not yet emphasised computational performance, however some discussion is warranted. All model runs were conducted on a laptop with a 1.7 GHz processor (AMD Ryzen 7 PRO 4750U) and 32 Gb RAM, without parallelisation implemented. Run times were between ca. 1.5 and ca. 4.5 hours. Average ~~timestep times~~ compute times per timestep were ca. 4 seconds for steady-state hydrology runs with ‘normal’ detritus tracking ~~were ca. 4 seconds~~, increasing to ca. 4.5 seconds with

‘bedrock’ detritus tracking. For non-steady state models an average timestep took ca. 9 seconds, increasing to ca. 10.5 seconds  
680 with ‘bedrock’ detritus tracking.

The largest factor in run times was the size of the samples in the grain-size mixture calculations, for which a conservative  
choice of  $n = 1000$  was used here to mitigate against excessive non-linear behaviour. A smaller sample size will yield signifi-  
cantly reduced run times but with a greater variability in model outcomes. Significant potential exists for this performance to be  
improved upon through parallelisation and optimising the procedure for large-scale ensemble models run on high performance  
685 computing infrastructure.

## 6 Conclusions

We have developed a graph-based model, GraphSSeT, to represent subglacial hydrology networks and to calculate subglacial  
fluvial sediment transport on those networks. The model uses the output of a subglacial hydrology model, for example GlaDS  
(Werder et al., 2013) as forcing, from which the channelised flow network is defined as a directed graph. The graph accommo-  
690 dates the definition of local sediment transport capacity and dynamic sediment evolution and the management of the flow of  
sediment at network-scale. GraphSSeT uses a stochastically-varying grain size which enables the evolution of the key process  
of selective transport. Grain size is tracked on the network as a distribution, and detrital properties may be tracked [passively](#)  
through the network.

Using a set of synthetic model scenarios from SHMIP (De Fleurian et al., 2018), four experiment sets were run to investigate  
695 the impact of key factors in the model on sediment discharge volume, detrital characteristics and grain size. These include  
1) the scale, degree of development and organisation of the subglacial hydrology network; 2) grain-size dependant transport  
generating an evolving selective transport and non-linear flow dynamics at network scale; 3) the effects of short-term variations  
in water input for enhanced sediment output relative to steady state and 4) the evolving thickness of the basal sediment layer  
controlling sediment supply, access to the bedrock and buffering of grain size mixing processes. Overall, the results from  
700 these models generate sedimentary characteristics that are in-line with observations of sediment plumes and glacial sediments,  
although discharge volumes are very low compared to real examples, due to the small size of the model catchment. [A remaining  
goal is to test the influence of these key factors for sediment transport in real glacial systems of Greenland and Antarctica, which  
involve greatly increased scale and complexity.](#)

*Code and data availability.* Code and model input data for these examples is on GitHub <https://github.com/al8ken/GraphSSeT>. Additional  
705 input data are available at Zenodo (doi:10.5281/zenodo.12570097)

## Appendix A: Appendix A

**Table A1.** Summary of [SHMIP](#) hydrology model runs referred to in this paper ([De Fleurian et al., 2018](#))

<del>Input hydrology scenario</del> Scenario	Variable	Total water input rate	Total channel volume	Outlet flux % channelised	Supp. s
-	-	$\text{m}^3 \text{a}^{-1} \text{m}^{-1}$	$\text{km}^3$	-	
A4	<a href="#">water input 2.16 mm/d</a>	78840	0.349	81	<a href="#">S1.1.</a>
A5	<a href="#">water input 3.93 mm/d</a>	143445	1.291	91	<a href="#">S1.1.</a>
A7	<a href="#">water input 21.6 mm/d</a>	788400	9.540	100	<a href="#">S1.1.</a>
A8	<a href="#">water input 39.3 mm/d</a>	1434450	17.426	100	<a href="#">S1.1.</a>
A6	<a href="#">water input 50 mm/d</a>	1825000	21.795	100	<a href="#">S1.1.</a>
B1	<a href="#">1 moulin</a>	142162	1.978	92	<a href="#">S1.2.</a>
B2	<a href="#">10 moulins</a>	142162	0.906	91	<a href="#">S1.2.</a>
B3	<a href="#">20 moulins</a>	142162	0.981	92	<a href="#">S1.2.</a>
B4	<a href="#">50 moulins</a>	142162	0.841	92	<a href="#">S1.2.</a>
B5	<a href="#">100 moulins</a>	142162	0.858	91	<a href="#">S1.2.</a>
C1	<a href="#">relative amplitude 1/4</a>	142162	0.893	92	<a href="#">S1.3.</a>
C2	<a href="#">relative amplitude 1/2</a>	142162	0.906	92	<a href="#">S1.3.</a>
C3	<a href="#">relative amplitude 1</a>	142162	0.912	92	<a href="#">S1.3.</a>
C4	<a href="#">relative amplitude 2</a>	173081	1.073	91	<a href="#">S1.3.</a>



**Table A2.** Summary of Experiment Set 1 model runs. Bedrock-derived sediment values for 'D' models with bedrock detritus tracking are higher: these values indicate the total erosion-derived component regardless of sediment recycling

Model run	Detritus mode	Total <u>sediment sed.</u> $\text{m}^3\text{a}^{-1}\text{m}^{-1}$	Bedrock-derived <u>sediment sed.</u> $\text{m}^3\text{a}^{-1}\text{m}^{-1}$	Mean grainsize mm	Mean <u>sediment concentration sed. conc.</u> ppm
A4 Reference	normal	0.553	0.144	0.218	8.68
A4 default	normal	0.240	0.015	0.212	5.46
A4 default_r	normal	0.179	0.024	0.244	4.12
A4D default	bedrock	0.257	0.164	0.193	10.0
A4D default_r	bedrock	0.321	0.207	0.265	6.25
A5 Reference	normal	2.75	1.02	0.218	21.3
A5 default	normal	2.55	0.614	0.214	22.0
A5 default_r	normal	1.70	0.356	0.309	15.7
A5D default	bedrock	1.99	1.46	0.267	17.7
A5D default_r	bedrock	3.91	3.04	0.145	36.7
A6 Reference	normal	35.7	4.39	0.218	19.5
A6 default	normal	49.7	4.11	0.136	34.7
A6 default_r	normal	46.0	3.46	0.139	33.6
A6D default	bedrock	41.6	18.3	0.163	25.9
A6D default_r	bedrock	40.9	23.1	0.162	28.9
A7 Reference	normal	6.91	1.45	0.218	9.09
A7 default	normal	8.23	1.04	0.161	11.8
A7 default_r	normal	10.1	1.32	0.156	16.4
A7D default	bedrock	6.05	3.12	0.246	8.12
A7D default_r	bedrock	6.21	2.80	0.204	8.37
A8 Reference	normal	27.7	3.86	0.218	19.5
A8 default	normal	55.2	5.06	0.090	56.8
A8 default_r	normal	37.2	3.05	0.149	29.9
A8D	bedrock	41.8	17.7	0.123	34.4
A8D_r	bedrock	53.2	17.1	0.090	54.6

**Table A3.** Summary of Experiment Set 2 model runs, all with model scenario A5

Variable	Value	Total sed.	Bedrock-derived sed.	Mean grainsize	Mean <del>sediment conc.</del> <u>sed. conc.</u>	Supp. sec
-	-	$\text{m}^3\text{a}^{-1}\text{m}^{-1}$	$\text{m}^3\text{a}^{-1}\text{m}^{-1}$	mm	ppm	-
Mean grain size (mm)	0.109	6.25	1.79	0.091	60.2	<a href="#">S2.2.1</a>
Mean grain size (mm)	0.436	0.80	0.16	0.477	7.67	<a href="#">S2.2.2</a>
Grain size $\varsigma$	1	2.37	0.50	0.244	19.2	<a href="#">S2.2.3</a>
Grain size $\varsigma$	2	6.55	1.91	0.084	92.2	<a href="#">S2.2.4</a>
Grain density ( $\text{kg}/\text{m}^3$ )	2550	2.63	0.56	0.239	21.7	<a href="#">S2.2.5</a>
Grain density ( $\text{kg}/\text{m}^3$ )	2750	4.13	0.89	0.124	37.9	<a href="#">S2.2.6</a>
Initial sediment thickness (m)	$0.05 \pm 0.025$	2.18	0.83	0.257	17.9	<a href="#">S2.2.7</a>
Initial sediment thickness (m)	$0.5 \pm 0.25$	2.86	0.29	0.202	24.6	<a href="#">S2.2.8</a>
$\Delta\sigma$ (m)	0.005	2.98	0.24	0.188	28.8	<a href="#">S2.2.9</a>
$\Delta\sigma$ (m)	0.01	2.39	0.096	0.239	19.8	<a href="#">S2.2.10</a>
Erosion scaling	$1e^{-7}u_b^{2.02}$	2.61	0.55	0.196	28.2	<a href="#">S2.2.11</a>
Erosion scaling	$1e^{-4}u_b$	3.23	1.25	0.200	27.2	<a href="#">S2.2.12</a>
Erosion scaling	$2e^{-4}u_b$	2.81	0.98	0.220	24.3	<a href="#">S2.2.13</a>

**Table A4.** Summary of Experiment Set 3 model runs. Bedrock-derived sediment values for 'D' models indicate the total erosion-derived component regardless of sediment recycling

Model run	Detritus mode	Total <u>sediment_sed.</u> m <sup>3</sup> a <sup>-1</sup> m <sup>-1</sup>	Bedrock-derived <u>sediment_sed.</u> m <sup>3</sup> a <sup>-1</sup> m <sup>-1</sup>	Mean grainsize mm	Mean <u>sediment-concentration_sed_conc.</u> ppm
B1 Reference	normal	0.478	0.311	0.218	3.63
B1 default	normal	0.381	0.090	0.215	4.24
B1 default_r	normal	0.315	0.072	0.228	3.69
B1D default	bedrock	0.363	0.225	0.239	3.41
B2 Reference	normal	2.36	0.775	0.218	18.2
B2 default	normal	1.69	0.270	0.265	15.3
B2 default_r	normal	12.2	1.72	0.039	23.9
B2D default	bedrock	2.66	1.35	0.187	22.0
B3 Reference	normal	1.58	0.556	0.218	12.2
B3 default	normal	2.05	0.385	0.146	20.0
B3 default_r	normal	1.30	0.257	0.207	13.4
B3D default	bedrock	1.46	1.06	0.192	16.3
B4 Reference	normal	0.796	0.213	0.218	6.12
B4 default	normal	0.224	0.013	0.235	2.77
B4 default_r	normal	2.83	0.204	0.061	34.2
B4D default	bedrock	0.51	0.288	0.245	4.73
B5 Reference	normal	1.25	0.365	0.218	9.62
B5 default	normal	1.53	0.171	0.170	13.7
B5 default_r	normal	1.05	0.141	0.230	9.49
B5D default	bedrock	0.780	0.587	0.241	8.26

**Table A5.** Summary of Experiment Set 4 model runs. Bedrock-derived sediment values for 'D' models indicate the total erosion-derived component regardless of sediment recycling

Model run	Detritus mode	Total <u>sediment sed.</u> $\text{m}^3\text{a}^{-1}\text{m}^{-1}$	Bedrock-derived <u>sediment sed.</u> $\text{m}^3\text{a}^{-1}\text{m}^{-1}$	Mean grainsize mm	Mean <u>sediment concentration sed. conc.</u> ppm
C0 Reference	normal	0.091	0.004	0.218	0.700
C0 default	normal	0.288	0.003	0.184	3.02
C0D default	bedrock	0.196	0.096	0.196	2.76
C1 Reference	normal	0.098	0.003	0.218	0.833
C1 default	normal	0.237	0.003	0.201	2.96
C1D default	bedrock	0.947	0.054	0.038	11.2
C2 Reference	normal	0.173	0.004	0.218	2.29
C2 default	normal	0.245	0.041	0.206	3.24
C2D default	bedrock	0.240	0.143	0.208	3.28
C3 Reference	normal	0.275	0.023	0.218	4.21
C3 default	normal	0.255	0.005	0.204	4.31
C3D default	bedrock	0.269	0.169	0.208	4.27
C4 Reference	normal	2.74	0.129	0.218	37.1
C4 default	normal	3.06	0.145	0.182	42.2
C4D default	bedrock	3.66	1.63	0.166	48.8

*Author contributions.* Aitken ARA: Conceptualization, Methodology, Software, Investigation, Writing- Original draft, Writing - Review and Editing, Funding acquisition; Delaney IA: Methodology, Writing - Review and Editing; Pirot G: Methodology, Writing - Review and Editing; Werder M: Methodology, Writing - Review and Editing; Funding acquisition

710 *Competing interests.* One or more co-authors is a member of The Cryosphere editorial board.

*Acknowledgements.* This research was supported by the Australian Research Council Special Research Initiative, Australian Centre for Excellence in Antarctic Science (SR200100008). I. Delaney was supported by SNSF Project No. PZ00P2\_202024. G. Pirot was supported by the Mineral Exploration Cooperative Research Centre whose activities are funded by the Australian Government's Cooperative Research Centre Programme.

## 715 **References**

- Aitken, A. R. A. and Urosevic, L.: A probabilistic and model-based approach to the assessment of glacial detritus from ice sheet change, *Palaeogeography, Palaeoclimatology, Palaeoecology*, 561, 110–118, <https://doi.org/10.1016/j.palaeo.2020.110053>, 2021.
- Alley, R. B.: Water-Pressure Coupling of Sliding and Bed Deformation: I. Water System, *Journal of Glaciology*, 35, 108–118, <https://doi.org/10.3189/002214389793701527>, 1989.
- 720 Alley, R. B., Anandakrishnan, S., Bentley, C. R., and Lord, N.: A water-piracy hypothesis for the stagnation of Ice Stream C, Antarctica, *Annals of Glaciology*, 20, 187–194, <https://doi.org/10.3189/1994AoS20-1-187-194>, 1994.
- Alley, R. B., Lawson, D. E., Evenson, E. B., Strasser, J. C., and Larson, G. J.: Glaciohydraulic supercooling: a freeze-on mechanism to create stratified, debris-rich basal ice: II. Theory, *Journal of Glaciology*, 44, 563–569, <https://doi.org/10.3189/S0022143000002070>, 1998.
- Alley, R. B., Cuffey, K. M., and Zoet, L. K.: Glacial erosion: status and outlook, *Annals of Glaciology*, 60, 1–13, <https://doi.org/10.1017/aog.2019.38>, 2019.
- 725 Ancey, C.: Bedload transport: a walk between randomness and determinism. Part 2. Challenges and prospects, *Journal of Hydraulic Research*, 58, 18–33, <https://doi.org/10.1080/00221686.2019.1702595>, 2020a.
- Ancey, C.: Bedload transport: a walk between randomness and determinism. Part 1. The state of the art, *Journal of Hydraulic Research*, 58, 1–17, <https://doi.org/10.1080/00221686.2019.1702594>, 2020b.
- 730 Andresen, C. S., Karlsson, N. B., Straneo, F., Schmidt, S., Andersen, T. J., Eidam, E. F., Bjørk, A. A., Dartigumalle, N., Dyke, L. M., Vermassen, F., and Gundel, I. E.: Sediment discharge from Greenland’s marine-terminating glaciers is linked with surface melt, *Nature Communications*, 15, 1332, <https://doi.org/10.1038/s41467-024-45694-1>, 2024.
- Ashmore, D. W. and Bingham, R. G.: Antarctic subglacial hydrology: current knowledge and future challenges, *Antarctic Science*, 26, 758–773, <https://doi.org/10.1017/S0954102014000546>, 2014.
- 735 Boulton, G. S., Lunn, R., Vidstrand, P., and Zatzepin, S.: Subglacial drainage by groundwater–channel coupling, and the origin of esker systems: part II—theory and simulation of a modern system, *Quaternary Science Reviews*, 26, 1091–1105, <https://doi.org/10.1016/j.quascirev.2007.01.006>, 2007.
- Brandes, U.: A faster algorithm for betweenness centrality\*, *The Journal of Mathematical Sociology*, 25, 163–177, <https://doi.org/10.1080/0022250X.2001.9990249>, 2001.
- 740 Cape, M. R., Straneo, F., Beaird, N., Bundy, R. M., and Charette, M. A.: Nutrient release to oceans from buoyancy-driven upwelling at Greenland tidewater glaciers, *Nature Geoscience*, 12, 34–39, <https://doi.org/10.1038/s41561-018-0268-4>, 2019.
- Christoffersen, P., Tulaczyk, S., and Behar, A.: Basal ice sequences in Antarctic ice stream: Exposure of past hydrologic conditions and a principal mode of sediment transfer, *Journal of Geophysical Research: Earth Surface*, 115, <https://doi.org/10.1029/2009JF001430>, 2010.
- Chu, V. W.: Greenland ice sheet hydrology: A review, *Progress in Physical Geography: Earth and Environment*, 38, 19–54, <https://doi.org/10.1177/0309133313507075>, 2014.
- 745 Chu, V. W., Smith, L. C., Rennermalm, A. K., Forster, R. R., Box, J. E., and Reeh, N.: Sediment plume response to surface melting and supraglacial lake drainages on the Greenland ice sheet, *Journal of Glaciology*, 55, 1072–1082, <https://doi.org/10.3189/002214309790794904>, 2009.
- Cook, S. J., Swift, D. A., Kirkbride, M. P., Knight, P. G., and Waller, R. I.: The empirical basis for modelling glacial erosion rates, *Nature Communications*, 11, 759, <https://doi.org/10.1038/s41467-020-14583-8>, 2020.
- 750

- Creys, T. T. and Schoof, C. G.: Drainage through subglacial water sheets, *Journal of Geophysical Research: Earth Surface*, 114, <https://doi.org/10.1029/2008JF001215>, 2009.
- Creys, T. T., Clarke, G. K. C., and Church, M.: Evolution of subglacial overdeepenings in response to sediment redistribution and glaciohydraulic supercooling, *Journal of Geophysical Research: Earth Surface*, 118, 423–446, <https://doi.org/10.1002/jgrf.20033>, 2013.
- 755 Czuba, J. A.: A Lagrangian framework for exploring complexities of mixed-size sediment transport in gravel-bedded river networks, *Geomorphology*, 321, 146–152, <https://doi.org/10.1016/j.geomorph.2018.08.031>, 2018.
- De Fleurian, B., Werder, M. A., Beyer, S., Brinkerhoff, D. J., Delaney, I. A. N., Dow, C. F., Downs, J., Gagliardini, O., Hoffman, M. J., and Hooke, R. L.: SHMIP The subglacial hydrology model intercomparison Project, *Journal of Glaciology*, 64, 897–916, <https://doi.org/10.1017/jog.2018.78>, 2018.
- 760 Delaney, I. and Adhikari, S.: Increased Subglacial Sediment Discharge in a Warming Climate: Consideration of Ice Dynamics, Glacial Erosion, and Fluvial Sediment Transport, *Geophysical Research Letters*, 47, e2019GL085672, <https://doi.org/10.1029/2019GL085672>, 2020.
- Delaney, I., Werder, M. A., and Farinotti, D.: A Numerical Model for Fluvial Transport of Subglacial Sediment, *Journal of Geophysical Research: Earth Surface*, 124, 2197–2223, <https://doi.org/10.1029/2019JF005004>, 2019.
- 765 Delaney, I., Anderson, L., and Herman, F.: Modeling the spatially distributed nature of subglacial sediment transport and erosion, *Earth Surface Dynamics*, 11, 663–680, <https://doi.org/10.5194/esurf-11-663-2023>, 2023.
- Dow, C. F.: The role of subglacial hydrology in Antarctic ice sheet dynamics and stability: a modelling perspective, *Annals of Glaciology*, 63, 49–54, <https://doi.org/10.1017/aog.2023.9>, 2022.
- Dow, C. F., Ross, N., Jeffrey, H., Siu, K., and Siegert, M. J.: Antarctic basal environment shaped by high-pressure flow through a subglacial river system, *Nature Geoscience*, 15, 892–898, <https://doi.org/10.1038/s41561-022-01059-1>, 2022.
- 770 Dowdeswell, J. A., Hogan, K. A., Arnold, N. S., Mugford, R. I., Wells, M., Hirst, J. P. P., and Decalf, C.: Sediment-rich meltwater plumes and ice-proximal fans at the margins of modern and ancient tidewater glaciers: Observations and modelling, *Sedimentology*, 62, 1665–1692, <https://doi.org/10.1111/sed.12198>, 2015.
- Dowdeswell, J. A., Canals, M., Jakobsson, M., Todd, B. J., Dowdeswell, E. K., and Hogan, K. A.: The variety and distribution of submarine glacial landforms and implications for ice-sheet reconstruction, *Geological Society, London, Memoirs*, 46, 519–552, <https://doi.org/10.1144/M46.183>, 2016.
- 775 Ehrenfeucht, S., Morlighem, M., Rignot, E., Dow, C. F., and Mouginot, J.: Seasonal Acceleration of Petermann Glacier, Greenland, From Changes in Subglacial Hydrology, *Geophysical Research Letters*, 50, e2022GL098009, <https://doi.org/10.1029/2022GL098009>, 2023.
- Einstein, H. A.: The Bed-load Function for Sediment Transportation in Open Channel Flows, *Technical Bulletin*, U.S. Department of Agriculture, 1950.
- 780 Engelund, F. and Hansen, E.: A monograph on sediment transport in alluvial streams, Technical University Denmark, Copenhagen Denmark, <https://repository.tudelft.nl/islandora/object/uuid%3A81101b08-04b5-4082-9121-861949c336c9>, 1967.
- Evans, D. J. A., Phillips, E. R., Hiemstra, J. F., and Auton, C. A.: Subglacial till: Formation, sedimentary characteristics and classification, *Earth-Science Reviews*, 78, 115–176, <https://doi.org/10.1016/j.earscirev.2006.04.001>, 2006.
- 785 Flowers, G. E.: Modelling water flow under glaciers and ice sheets, *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 471, 20140907, <https://doi.org/10.1098/rspa.2014.0907>, 2015.
- Flowers, G. E. and Clarke, G. K. C.: A multicomponent coupled model of glacier hydrology 1. Theory and synthetic examples, *Journal of Geophysical Research: Solid Earth*, 107, ECV 9–1–ECV 9–17, <https://doi.org/10.1029/2001JB001122>, 2002.

- Flowers, G. E., Björnsson, H., Pálsson, F., and Clarke, G. K. C.: A coupled sheet-conduit mechanism for jökulhlaup propagation, *Geophysical Research Letters*, 31, <https://doi.org/10.1029/2003GL019088>, 2004.
- 790 Fountain, A. G., Jacobel, R. W., Schlichting, R., and Jansson, P.: Fractures as the main pathways of water flow in temperate glaciers, *Nature*, 433, 618–621, <https://doi.org/10.1038/nature03296>, 2005.
- Golledge, N. R. and Levy, R. H.: Geometry and dynamics of an East Antarctic Ice Sheet outlet glacier, under past and present climates, *Journal of Geophysical Research: Earth Surface*, 116, <https://doi.org/10.1029/2011JF002028>, 2011.
- 795 Gulley, J. D., Grabiec, M., Martin, J. B., Jania, J., Catania, G., and Glowacki, P.: The effect of discrete recharge by moulins and heterogeneity in flow-path efficiency at glacier beds on subglacial hydrology, *Journal of Glaciology*, 58, 926–940, <https://doi.org/10.3189/2012JoG11J189>, 2012.
- Hagberg, A., Swart, P. J., and Schult, D. A.: Exploring network structure, dynamics, and function using NetworkX, in: *Proceedings, Pasadena, California, USA*, [https://conference.scipy.org/proceedings/SciPy2008/SciPy2008\\_proceedings.pdf](https://conference.scipy.org/proceedings/SciPy2008/SciPy2008_proceedings.pdf), 2008.
- 800 Haldorsen, S.: Grain-size distribution of subglacial till and its relation to glacial crushing and abrasion, *Boreas*, 10, 91–105, <https://doi.org/10.1111/j.1502-3885.1981.tb00472.x>, 1981.
- Herman, F., Braun, J., Deal, E., and Prasicek, G.: The Response Time of Glacial Erosion, *Journal of Geophysical Research: Earth Surface*, 123, 801–817, <https://doi.org/10.1002/2017JF004586>, 2018.
- Herman, F., De Doncker, F., Delaney, I., Prasicek, G., and Koppes, M.: The impact of glaciers on mountain erosion, *Nature Reviews Earth & Environment*, 2, 422–435, <https://doi.org/10.1038/s43017-021-00165-9>, 2021.
- 805 Hewitt, I. J.: Modelling distributed and channelized subglacial drainage: the spacing of channels, *Journal of Glaciology*, 57, 302–314, <https://doi.org/10.3189/002214311796405951>, 2011.
- Hiester, J., Sergienko, O. V., and Hulbe, C. L.: Topographically mediated ice stream subglacial drainage networks, *Journal of Geophysical Research: Earth Surface*, 121, 497–510, <https://doi.org/10.1002/2015JF003660>, 2016.
- 810 Hogan, K. A., Dix, J. K., Lloyd, J. M., Long, A. J., and Cotterill, C. J.: Seismic stratigraphy records the deglacial history of Jakobshavn Isbræ, West Greenland, *Journal of Quaternary Science*, 26, 757–766, <https://doi.org/10.1002/jqs.1500>, 2011.
- Hogan, K. A., Dowdeswell, J. A., and Ó Cofaigh, C.: Glacimarine sedimentary processes and depositional environments in an embayment fed by West Greenland ice streams, *Marine Geology*, 311, 1–16, <https://doi.org/10.1016/j.margeo.2012.04.006>, 2012.
- Hogan, K. A., Jakobsson, M., Mayer, L., Reilly, B. T., Jennings, A. E., Stoner, J. S., Nielsen, T., Andresen, K. J., Nørmark, E., and Heirman, K. A.: Glacial sedimentation, fluxes and erosion rates associated with ice retreat in Petermann Fjord and Nares Strait, north-west Greenland, *The Cryosphere*, 14, 261–286, <https://doi.org/10.5194/tc-14-261-2020>, 2020.
- 815 Hooke, R. L., Laumann, T., and Kohler, J.: Subglacial Water Pressures and the Shape of Subglacial Conduits, *Journal of Glaciology*, 36, 67–71, <https://doi.org/10.3189/S0022143000005566>, 1990.
- Hooyer, T. S., Cohen, D., and Iverson, N. R.: Control of glacial quarrying by bedrock joints, *Geomorphology*, 153–154, 91–101, <https://doi.org/10.1016/j.geomorph.2012.02.012>, 2012.
- 820 Kamb, B.: Glacier surge mechanism based on linked cavity configuration of the basal water conduit system, *Journal of Geophysical Research: Solid Earth*, 92, 9083–9100, <https://doi.org/10.1029/JB092iB09p09083>, 1987.
- Klösch, M. and Habersack, H.: Deriving formulas for an unsteady virtual velocity of bedload tracers, *Earth Surface Processes and Landforms*, 43, 1529–1541, <https://doi.org/10.1002/esp.4326>, 2018.
- 825 Krabbendam, M. and Glasser, N. F.: Glacial erosion and bedrock properties in NW Scotland: Abrasion and plucking, hardness and joint spacing, *Geomorphology*, 130, 374–383, <https://doi.org/10.1016/j.geomorph.2011.04.022>, 2011.



- Le Brocq, A. M., Payne, A. J., Siegert, M. J., and Alley, R. B.: A subglacial water-flow model for West Antarctica, *Journal of Glaciology*, 55, 879–888, <https://doi.org/10.3189/002214309790152564>, 2009.
- 830 Lepp, A. P., Simkins, L. M., Anderson, J. B., Clark, R. W., Wellner, J. S., Hillenbrand, C.-D., Smith, J. A., Lehrmann, A. A., Totten, R., Larter, R. D., Hogan, K. A., Nitsche, F. O., Graham, A. G. C., and Wacker, L.: Sedimentary Signatures of Persistent Subglacial Meltwater Drainage From Thwaites Glacier, Antarctica, *Frontiers in Earth Science*, 10, <https://doi.org/https://doi.org/10.3389/feart.2022.863200>, 2022.
- Licht, K. J. and Hemming, S. R.: Analysis of Antarctic glacial sediment provenance through geochemical and petrologic applications, *Quaternary Science Reviews*, 164, 1–24, <https://doi.org/10.1016/j.quascirev.2017.03.009>, 2017.
- 835 Livingstone, S. J., Li, Y., Rutishauser, A., Sanderson, R. J., Winter, K., Mikucki, J. A., Björnsson, H., Bowling, J. S., Chu, W., Dow, C. F., Fricker, H. A., McMillan, M., Ng, F. S. L., Ross, N., Siegert, M. J., Siegfried, M., and Sole, A. J.: Subglacial lakes and their changing role in a warming climate, *Nature Reviews Earth & Environment*, 3, 106–124, <https://doi.org/10.1038/s43017-021-00246-9>, 2022.
- McCormack, F. S., Roberts, J. L., Kulesa, B., Aitken, A., Dow, C. F., Bird, L., Galton-Fenzi, B. K., Hochmuth, K., Jones, R. S., Mackintosh, A. N., and McArthur, K.: Assessing the potential for ice flow piracy between the Totten and Vanderford glaciers, East Antarctica, *The Cryosphere*, 17, 4549–4569, <https://doi.org/10.5194/tc-17-4549-2023>, 2023.
- 840 Meire, L., Mortensen, J., Meire, P., Juul-Pedersen, T., Sejr, M. K., Rysgaard, S., Nygaard, R., Huybrechts, P., and Meysman, F. J. R.: Marine-terminating glaciers sustain high productivity in Greenland fjords, *Global Change Biology*, 23, 5344–5357, <https://doi.org/10.1111/gcb.13801>, 2017.
- Meyer-Peter, E. and Müller, R.: Formulas for Bed-Load transport, in: IAHSR 2nd meeting, Stockholm, appendix 2, IAHR, Stockholm, Sweden, <https://repository.tudelft.nl/islandora/object/uuid%3A4fda9b61-be28-4703-ab06-43cdc2a21bd7>, 1948.
- 845 Newell, G. F.: A simplified theory of kinematic waves in highway traffic, part I: General theory, *Transportation Research Part B: Methodological*, 27, 281–287, [https://doi.org/10.1016/0191-2615\(93\)90038-C](https://doi.org/10.1016/0191-2615(93)90038-C), 1993.
- Nye, J. F.: Water Flow in Glaciers: Jökulhlaups, Tunnels and Veins, *Journal of Glaciology*, 17, 181–207, <https://doi.org/10.3189/S002214300001354X>, 1976.
- 850 Overeem, I., Hudson, B. D., Syvitski, J. P. M., Mikkelsen, A. B., Hasholt, B., van den Broeke, M. R., Noël, B. P. Y., and Morlighem, M.: Substantial export of suspended sediment to the global oceans from glacial erosion in Greenland, *Nature Geoscience*, 10, 859–863, <https://doi.org/10.1038/ngeo3046>, 2017.
- Peterson, G., Johnson, M. D., Dahlgren, S., Pässe, T., and Alexanderson, H.: Genesis of hummocks found in tunnel valleys: an example from Hörda, southern Sweden, *GFF*, 140, 189–201, <https://doi.org/10.1080/11035897.2018.1470199>, 2018.
- 855 Pollard, D. and DeConto, R. M.: Antarctic ice and sediment flux in the Oligocene simulated by a climate–ice sheet–sediment model, *Palaeogeography, Palaeoclimatology, Palaeoecology*, 198, 53–67, [https://doi.org/10.1016/S0031-0182\(03\)00394-8](https://doi.org/10.1016/S0031-0182(03)00394-8), 2003.
- Pollard, D. and DeConto, R. M.: Continuous simulations over the last 40 million years with a coupled Antarctic ice sheet-sediment model, *Palaeogeography, Palaeoclimatology, Palaeoecology*, 537, 109–374, <https://doi.org/10.1016/j.palaeo.2019.109374>, 2020.
- Rijn, V. and C, L.: Unified View of Sediment Transport by Currents and Waves. II: Suspended Transport, *Journal of Hydraulic Engineering*, 860 133, 668–689, [https://doi.org/10.1061/\(ASCE\)0733-9429\(2007\)133:6\(668\)](https://doi.org/10.1061/(ASCE)0733-9429(2007)133:6(668)), 2007a.
- Rijn, V. and C, L.: Unified View of Sediment Transport by Currents and Waves. I: Initiation of Motion, Bed Roughness, and Bed-Load Transport, *Journal of Hydraulic Engineering*, 133, 649–667, [https://doi.org/10.1061/\(ASCE\)0733-9429\(2007\)133:6\(649\)](https://doi.org/10.1061/(ASCE)0733-9429(2007)133:6(649)), 2007b.
- Roberts, M. J.: Jökulhlaups: A reassessment of floodwater flow through glaciers, *Reviews of Geophysics*, 43, <https://doi.org/10.1029/2003RG000147>, 2005.

- 865 Röthlisberger, H.: Water Pressure in Intra- and Subglacial Channels, *Journal of Glaciology*, 11, 177–203, <https://doi.org/10.3189/S0022143000022188>, 1972.
- Schild, K. M., Hawley, R. L., Chipman, J. W., and Benn, D. I.: Quantifying suspended sediment concentration in subglacial sediment plumes discharging from two Svalbard tidewater glaciers using Landsat-8 and in situ measurements, *International Journal of Remote Sensing*, 38, 6865–6881, <https://doi.org/10.1080/01431161.2017.1365388>, 2017.
- 870 Schoof, C.: Ice-sheet acceleration driven by melt supply variability, *Nature*, 468, 803–806, <https://doi.org/10.1038/nature09618>, 2010.
- Shreve, R. L.: Movement of Water in Glaciers, *Journal of Glaciology*, 11, 205–214, <https://doi.org/10.3189/S002214300002219X>, 1972.
- Smith, J. A., Graham, A. G. C., Post, A. L., Hillenbrand, C.-D., Bart, P. J., and Powell, R. D.: The marine geological imprint of Antarctic ice shelves, *Nature Communications*, 10, 5635, <https://doi.org/10.1038/s41467-019-13496-5>, 2019.
- Vaughan, D. G., Corr, H. F. J., Smith, A. M., Pritchard, H. D., and Shepherd, A.: Flow-switching and water piracy between Rutford Ice Stream and Carlson Inlet, West Antarctica, *Journal of Glaciology*, 54, 41–48, <https://doi.org/10.3189/002214308784409125>, 2008.
- 875 Wadham, J. L., De'Ath, R., Monteiro, F. M., Tranter, M., Ridgwell, A., Raiswell, R., and Tulaczyk, S.: The potential role of the Antarctic Ice Sheet in global biogeochemical cycles, *Earth and Environmental Science Transactions of the Royal Society of Edinburgh*, 104, 55–67, <https://doi.org/10.1017/S1755691013000108>, 2013.
- Walder, J. S. and Fowler, A.: Channelized subglacial drainage over a deformable bed, *Journal of Glaciology*, 40, 3–15, <https://doi.org/10.3189/S0022143000003750>, 1994.
- 880 Werder, M. A., Hewitt, I. J., Schoof, C. G., and Flowers, G. E.: Modeling channelized and distributed subglacial drainage in two dimensions, *Journal of Geophysical Research: Earth Surface*, 118, 2140–2158, <https://doi.org/10.1002/jgrf.20146>, 2013.
- Wilkinson, S. N., Prosser, I. P., and Hughes, A. O.: Predicting the distribution of bed material accumulation using river network sediment budgets, *Water Resources Research*, 42, <https://doi.org/10.1029/2006WR004958>, 2006.
- 885 Witus, A. E., Braneky, C. M., Anderson, J. B., Szczuciński, W., Schroeder, D. M., Blankenship, D. D., and Jakobsson, M.: Meltwater intensive glacial retreat in polar environments and investigation of associated sediments: example from Pine Island Bay, West Antarctica, *Quaternary Science Reviews*, 85, 99–118, <https://doi.org/10.1016/j.quascirev.2013.11.021>, 2014.