

The ZiCOS-M CO_2 sensor network: measurement performance and CO_2 variability across Zürich

Stuart K. Grange^{1,2}, Pascal Rubli¹, Andrea Fischer¹, Dominik Brunner¹, Christoph Hueglin¹, and Lukas Emmenegger¹

¹Empa, Swiss Federal Laboratories for Materials Science and Technology, Laboratory for Air Pollution/Environmental Technology, Überlandstrasse 129, 8600 Dübendorf, Switzerland

²Wolfson Atmospheric Chemistry Laboratories, University of York, York, YO10 5DD, United Kingdom

Correspondence: Stuart K. Grange (stuart.grange@empa.ch); Christoph Hueglin (christoph.hueglin@empa.ch)

Abstract.

As a component of the ICOS Cities project, a “mid-cost” NDIR (nondispersive infrared) CO_2 sensor network was deployed across Zürich city (Switzerland), known as ZiCOS-M. The network was operational between July 2022 and July 2024 and consisted of 26 monitoring sites, 21 of which were located in or around Zürich city with five sites outside the urban area.

5 Daily calibrations using two reference gas cylinders and corrections of the sensors’ spectroscopic response to water vapour were performed to reach a high level of measurement accuracy. The hourly mean root mean squared error (RMSE) was 0.98 ppm (range of 0.46 and 1.5 ppm) while the mean bias was ~~-0.09 ppm (range of ranged between~~ -0.72 and 0.66 ppm ~~)~~ when undergoing parallel measurements with a high-precision reference gas analyser ~~-for a period of two weeks or more.~~

CO_2 concentrations (technically, dry air mole fractions), were highly variable with site means in Zürich ranging from 434 to

10 460 ppm and Zürich’s mean urban CO_2 dome was 15.4 ppm above the regional background. Some of the highest CO_2 levels were found at two sites exposed to a combination of strong plant respiration into a very confined nocturnal boundary layer. High CO_2 episodes were detected outside Zürich’s urban area demonstrating that processes acting on a variety of scales drove CO_2 levels. The ZiCOS-M network offered significant insights at an order of magnitude lower cost compared to reference instruments and the observations generated by ZiCOS-M will be used in additional ICOS Cities activities to conduct CO_2

15 emission inventory validation with inversion modelling systems.

1 Introduction

1.1 Background

Urban areas are very significant sources of atmospheric pollutants and greenhouse gases (GHGs) including carbon dioxide (CO_2). In 2020, it was estimated that urban areas were responsible for approximately 70 % of global CO_2 emissions (Lwasa et al., 2022). The increased population densities and intensive energy consumption can result in CO_2 urban domes, where CO_2 is enhanced by a few parts per million (ppm) to tens of ppm in and around the urban extent (Xueref-Remy et al., 2023). The importance of reducing CO_2 emissions and the decoupling of carbon emissions from economic growth is a priority for most

national and subnational governments, in order to avoid some of the worst negative consequences of anthropogenic climate change (IPCC, 2023). The importance of CO₂ emissions from urban areas has driven top-down analysis methods, where
25 observations of CO₂ are combined with atmospheric inversion modelling systems to validate bottom-up emission inventory-based estimates. These two approaches are ~~complimentary~~ complementary and their reconciliation is expected to yield the most reliable emission estimates to allow for potential management.

The monitoring of CO₂ in urban areas has ~~generally not been a priority, unlike~~ been a lesser priority when compared to traditional air pollutants, because of the lack of legal standards. ~~High-quality for CO₂. Therefore, high-quality CO₂~~ time
30 series are generally confined to isolated or remote locations where immediate emission sources are absent. These sites are suitable to capture long-term and large-scale processes, but they are unable to resolve the dynamics of CO₂ sources and sinks within urban areas (Hernández-Paniagua et al., 2015). In addition, the technology used for high-accuracy monitoring of CO₂ measurement remains expensive (Mao et al., 2012; Martin et al., 2017) and, therefore, the deployment of several CO₂ analysers in a city is usually considered cost prohibitive. An alternative approach is to deploy lower cost CO₂ sensors and
35 several research groups have deployed monitoring networks in this context (Maag et al., 2018). Although such sensors have lower measurement performance, their poorer accuracy can be offset by being deployed in a larger number and thus, offer the possibility of resolving spatial and temporal patterns at a smaller scale (Peltier et al., 2021). Therefore, the utility of lower-cost sensors can still be high (Bart et al., 2014; Casey and Hannigan, 2018).

Prominent urban CO₂ monitoring networks include the Berkeley Environmental Air-quality and CO₂ Network (BEACO₂N)
40 located across the San Francisco Bay area (Shusterman et al., 2016; Turner et al., 2016; Kim et al., 2018; Delaria et al., 2021), the Indianapolis (INFLUX) Urban Test Bed (Turnbull et al., 2015; Davis et al., 2017), the Los Angeles Megacity Carbon Project (Verhulst et al., 2017), the Northeast Corridor tower network (Karion et al., 2020), networks in Paris (Arzoumanian et al., 2019; Lian et al., 2024), and the Carbosense network across Switzerland (Müller et al., 2020). The nomenclature regarding the cost points for these networks is inconsistent because the definition of what a lower-cost sensor is varies among
45 operators. Here, we discuss a CO₂ sensor network that has been defined as “mid-cost” and is in a price range that is comparable to the BEACO₂N and Paris networks. The Carbosense network, in contrast, used sensors at a significantly lower price point, and therefore, would be defined as a low-cost CO₂ sensor network.

1.2 Switzerland and Zürich

Switzerland is a small country located in Western Europe with a population of approximately 9 million. It is highly developed
50 with a GDP per capita among the highest in the world (International Monetary Fund, 2023). Switzerland has been successful at decreasing its production-based CO₂ emissions, especially since 2010 (Ritchie et al., 2020; Federal Office for the Environment (FOEN), 2023). Consumption-based per capita CO₂ emissions have not decreased in the same way and remain high reflecting the wealth of the country’s residents.

Zürich is Switzerland’s largest city and has a population of 430 000 inhabitants in the city proper and another 1 million in
55 the surrounding agglomerations (Stadt Zürich, 2023a). Zürich is located on the Swiss plateau at about 410 m above sea level in an area of complex terrain. Zürich’s city centre is situated around Lake Zürich’s main northern outflow – the Limmat River

– flowing in a northwest direction, which has formed the Limmat Valley where much of the urban area is located. The Limmat Valley is bound to the west by the Albis range and to the east by the discontinuous Pfannenstiel–Altberg hill chain. Zürich’s urban area extends beyond the Limmat Valley in all directions, but notably, Districts 11 and 12 are located north of the eastern
60 hill range and form a continuous urban area over a saddle between Zürichberg and Käferberg. These topographic features of the urban area are relevant for pollutant transport and dispersion processes (Berchet et al., 2017).

Zürich city’s local government has legal obligations to be net zero by 2040 regarding direct CO₂ emissions and has targets for the reduction of per capita emissions (Stadt Zürich, 2023b). These net zero laws were a result of a Zürich canton referendum in September 2022. The latest emission inventory compiled for 2022 indicates that half of the city’s CO₂ emissions (51 %) are
65 sourced from stationary combustion, mostly residential and commercial heating emissions with a small contribution from waste incineration (Stadt Zürich, 2024). Public power generation and road transportation are the two other large emission sources (32 and 12 % respectively), and all other sources make up the outstanding 5 %.

1.3 ICOS Cities

ICOS Cities¹ is a European Horizon 2020 project that acts as a pilot to test and evaluate different CO₂ measurement approaches
70 that provide value for the scientific, policy, and citizen communities within urban areas. Three European cities ranging from large to small – Paris (France), Munich (Germany), and Zürich (Switzerland) are included in the pilot project and all three cities have CO₂ sensor networks that form one component of the urban observatories that have been or are deployed in the cities. By design, the three different sensor networks in the three cities differ in their monitoring focus, hardware, and software, but not in their primary objectives. In the Zürich case, the ZiCOS-M network greatly benefited from the experiences gained
75 from the earlier Swiss-wide Carbosense CO₂ network (Klose, 2017; Empa, 2019; Müller et al., 2020), but the Carbosense and ICOS Cities activities were separate.

The ZiCOS-M network was designed to supply observations for atmospheric inversion modelling systems, in order to allow for comparisons between top-down estimates of CO₂ emissions (natural and anthropogenic) and bottom-up estimates. However, once the sensor network was deployed, it was clear that the network was providing observations at a sufficiently high data
80 quality that were of use for observational analyses of CO₂ across Zürich’s region and urban area.

1.4 Objectives

This work has two overarching objectives. The first is to describe the ZiCOS-M CO₂ sensor network’s design, deployment, and data processing strategies, and to document what measurement performance was achieved with the sensors. The second is to present the spatial and temporal patterns of CO₂ across the network’s monitoring domain. The first objective will satisfy two
85 communities: the inversion modelling groups that use the observations generated by the sensor network to evaluate and verify the city’s emission inventory, and those who are operating or designing environmental gas sensing networks because many of the data processing approaches are generic and are portable to other networks in other areas and/or networks that target other quantities, such as other greenhouse gases or air pollutants.

¹<https://www.icos-cp.eu/projects/icos-cities>

The CO_2 sensor network deployed across Zürich city for the ICOS Cities project contained two sensor tiers – so-called low- and mid-cost. Here, only the mid-cost sensors’ activities and results will be discussed, while the low-cost sensor network (called ZiCOS-L) will be discussed in a future companion paper because the differing data quality gives rise to challenges when making direct comparisons across the different sensor types, due to their different measurement performances.

At the time of writing, the ZiCOS-M network is still in operation, but imminently, the network will be reconfigured, whereby half of the monitoring sites will be decommissioned. Therefore, we refer to the ZiCOS-M’s operations, sites, and data set in the past tense, except for the more distant background sites that are run by other monitoring activities, because these sites can be considered permanent features.

2 Methods

2.1 Sensors

The ZiCOS-M network used three different models of NDIR CO_2 sensors from three different manufacturers. Most of the sensors (21) were an integration based on the Senseair HPP (high-performance platform) (Senseair, 2016, 2018) sensor (Table 1). The Senseair HPP sensor is a prototype sensor and is no longer in production. These sensors have seen use in similar past ambient monitoring activities in Switzerland (Müller et al., 2020) and related sensors have undergone characterisation elsewhere (Kunz et al., 2018; Arzoumanian et al., 2019; Lian et al., 2024). In addition to the Senseair HPPs, five Vaisala GMP343 (Vaisala, 2013) sensor units were also used, and finally, one Licor LI-850 (LI-COR Biosciences, 2018) was operated in the network. The cost of the sensor units themselves was between CHF/EUR/USD 3000 and 5000, but after integration into a measurement system, the price point was approximately CHF/EUR/USD 5000–10000. The counts of sensors in Table 1 do not include the replacement of the actual CO_2 sensors themselves within the sensor packages (which were referred to as sensing elements). Additionally, more sensors were operated than the number of monitoring sites because some sensors failed and were replaced during the monitoring period.

Table 1. The number (n) of different sensors or monitors used in the ZiCOS-M sensor network.

Sensor type	Sensor group	n
Senseair HPP	CO_2 sensor	21
Vaisala GMP343	CO_2 sensor	5
Licor LI-850	CO_2 sensor	1
Picarro G1301 or G2401	High-precision gas analyser	4
Decentlab DL-ATM22	Wind sensor	14

All three sensor models were integrated into a very similar monitoring package by Decentlab GmbH (Decentlab GmbH, 2022), a commercial project partner. Figure 1 shows the main components and configuration of the measurement system. The sensor package included three-way valves for the switching between ambient sampling and two gas cylinders with demand-

flow regulators, filters, a sample pump, boards for data acquisition and transmission, temperature and relative humidity sensors installed in the sample gas stream, and for some integrations, ambient air pressure sensors. Table A1 [contains the make and models of the principle parts or components of the sensor packages](#). All hardware, except for the gas cylinders and demand-flow regulators, was contained in a weatherproof housing (Figure 1; Figure A1). In the case of the Vaisala GMP343 and Licor LI-850 sensors, the ancillary sensors in the gas stream and the ambient pressure sensors were connected to the sensor and onboard compensations for sample temperature, humidity, and ambient pressure were enabled. Originally, it was planned that a consistent data processing approach could be used for the three sensor types, but due to their differing measurement performance (especially concerning water vapour), different logic was required. Full details of these processes are available in Section 2.3.




Figure 1. Schematic of the sensor measurement system showing the major components of the system and their configuration. Table A1 [contains the make and models of the principle parts or components](#).

In addition to the CO_2 sensors, fourteen sonic wind sensors (Decentlab DL-ATM22) were installed at rooftop sites to provide auxiliary information on air flow and temperatures in the city (Table 1). The sensors' data were transmitted via Swisscom's LoRaWAN network which is a wide area network (WAN) designed for low power applications and small data volumes (LoRa® Alliance, 2015). The four high-precision gas analysers included in the network's data set were cavity ring-down spectrometers of different generations manufactured by Picarro (Rella, 2010; Rella et al., 2013; Zellweger et al., 2016) that were operated by following routine calibration and data quality control processes.

2.2 CO_2 monitoring sites

The ZiCOS-M sensor network was composed of a total of 26 monitoring sites with 21 sites in or around the immediate area of Zürich city and five sites in more distant locations. Three of these more distant sites were included in the dataset as they provide critical information on CO_2 levels surrounding the city (Figure 2; Table 2) while the other two sites provided CO_2 observations from other locations that could be contrasted with CO_2 measurements across the Zürich region.

Table 2. Basic monitoring site information for the ZiCOS-M sensor network. The elevation represents the elevation above sea level of the monitoring site and the measurement height is the height above ground. The five more distant and background sites outside Zürich are at the bottom of the table.

Site	Site type	Monitor type	Installation	Measurement height (m)	Latitude	Longitude	Elevation (m)
Albisgüetli	Urban	Mid-cost sensor	Rooftop	22.1	47.353	8.513	4
Badenerstrasse Farbhof	Urban	Mid-cost sensor	Rooftop	22.5	47.390	8.480	4
Bankenviertel Bleicherweg	Urban	Mid-cost sensor	Rooftop	26.5	47.369	8.538	4
Dübendorf-Empa	Urban	High-precision analyser	Near-ground	5	47.405	8.608	4
Güterbahnhof	Urban	Mid-cost sensor	Rooftop	29.4	47.382	8.518	4
Hardau II	Urban	Mid-cost sensor	Rooftop (high)	114	47.381	8.510	4
Hardturmstrasse Förlibuck	Urban	Mid-cost sensor	Rooftop	40.6	47.392	8.515	4
Heubeerbüel	Urban	Mid-cost sensor	Near-ground	1.5	47.381	8.566	6
Kantonaes Labor Zürich	Urban	Mid-cost sensor	Rooftop	20.4	47.371	8.558	4
Letzigraben Telefonzentrale	Urban	Mid-cost sensor	Rooftop	24	47.379	8.501	4
Limmattalstrasse Höngg	Urban	Mid-cost sensor	Rooftop	13.5	47.404	8.488	4
Reckenholz	Urban	Mid-cost sensor	Near-ground	4.2	47.428	8.517	4
Schule Milchbuck	Urban	Mid-cost sensor	Rooftop	35.3	47.396	8.538	4
Stauffacherstrasse Werdplatz	Urban	Mid-cost sensor	Rooftop	48	47.372	8.529	4
Tiefenbrunnen Wildbachstrasse	Urban	Mid-cost sensor	Rooftop	38.8	47.353	8.559	4
Universität Zürich Irchel	Urban	Mid-cost sensor	Rooftop	29	47.399	8.551	4
Wollishofen	Urban	Mid-cost sensor	Rooftop	40.6	47.347	8.533	4
Zürich Kaserne	Urban	Mid-cost sensor	Near-ground	3.3	47.378	8.530	4
Rosengartenstrasse	Urban traffic	Mid-cost sensor	Near-ground (kerbside)	2.8	47.395	8.526	4
Schimmelstrasse	Urban traffic	Mid-cost sensor	Near-ground (kerbside)	4.2	47.371	8.524	4
Stampfenbachstrasse	Urban traffic	Mid-cost sensor	Near-ground (kerbside)	4.2	47.387	8.540	4
Beromünster	Rural background	High-precision analyser	Tower	212	47.190	8.176	7
Birchwil Turm	Rural background	Mid-cost sensor	Tower	54	47.467	8.649	5
Lägern Hochwacht	Rural background	High-precision analyser	Elevated	28	47.482	8.397	8
Sottens	Rural background	Mid-cost sensor	Tower	46	46.656	6.736	7
Jungfrauoch	High-alpine background	High-precision analyser	High-alpine	13.9	46.548	7.985	35




Figure 2. Location of the ZICOS-M sensor network and the more distant locations where CO_2 observations were available and used as part of the study's dataset in Switzerland. The internal lines indicate Switzerland's cantonal boundaries and substantial water bodies are also shown.

The network's testing site, Dübendorf-Empa, is also an air quality morning site that is part of the National Air Pollution Monitoring Network (NABEL) (Empa, 2024). Dübendorf-Empa was used for intercomparison exercises and model training by using the reference CO_2 time series provided at this site. The intercomparisons conducted at Dübendorf-Empa allowed for the CO_2 sensors to be run in parallel with a high-precision gas analyser in ambient conditions for at least two weeks for a representative and robust testing procedure. Therefore, the measurement performance presented in Section 3.1 is highly representative of what was achieved during operational monitoring. Three of the four more distant sites were equipped with high-precision gas analysers while the fourth site, Sottens (160 kilometres to the south-west of Zürich city), had a sensor that was operated identically to those sensors in Zürich city. The predominant wind directions across the Zürich region are west-south-west and east-north-east, reflecting the orientation of the Swiss plateau. The three background monitoring sites surrounding Zürich city (Figure 2) were positioned in locations that, depending on the wind behaviour, would be down- or up-wind of the city.

The Beromünster background monitoring site is located southwest of Zürich city (Figure 2). It is a tall tower where the sampling system cycles among five different measurement heights. For the dataset presented here, only observations from the highest sampling point at 212 m were used. Lägern Hochwacht is northwest of Zürich city and is located on the forested Lägern hill that is orientated in an east-west direction. Lägern Hochwacht is on the hill's ridge or crest. The sampling height

is 32 m above ground which is above the forest's canopy height. For additional details about these two monitoring sites, see [Oney et al. \(2015\)](#). Birchwil Turm (a telecommunication tower) is another background site located 12.8 km from Zürich's city centre in a north-east direction next to an electrical substation in the Zürcher Unterland (Table 2; Figure 3). Birchwil Turm is approximately halfway between Zürich city and Winterthur, Canton Zürich's second largest city. Jungfrauoch in the Bernese Alps, 102 km from Zürich at an altitude of 3572 m, was used as the study's European or hemispheric background site (Figure 2). Jungfrauoch is an observatory that includes NABEL and ICOS activities. The CO_2 time series from this location serves as a reference to represent background European CO_2 with an absence of any immediate significant emission sources ([Pieber et al., 2022](#)).


The monitoring sites within and around Zürich city were classified further by their installation or siting types. The majority of sensors (14 of the 22 sensor sites) were deployed with inlets sampling at rooftop level (Table 2; Figure 3; Figure A1). The sensors were generally installed in maintenance rooms reserved for mobile phone infrastructure, and for most installations, these rooms were temperature-controlled. The focus on rooftop installations was done to represent CO_2 emission sources in the city without being primarily forced by immediate emission sources as would occur with sampling points at ground level in street canyon environments. The rooftop sites offer spatial representativeness across the city at a resolution that was optimised to the mesoscale model systems' spatial resolution. The sites were carefully selected out of a large number of potential locations by requiring minimal impact from nearby ventilation or heating stacks that were present on many roofs.

Hardau II is a central monitoring site of the network, which not only features a mid-cost sensor but also an Eddy covariance system to directly measure the CO_2 fluxes in a central part of the city. Measurements are conducted at 114 m above ground on a 95.3 m tall building, which is much higher than other rooftop sites. Several extra monitoring activities were conducted at this site during an intensive campaign between September 2022 and March 2023 within the ICOS Cities project. Details on the other monitoring activities at Hardau II are available in [Stagakis et al. \(2023\)](#).

2.3 Data

The principal steps of the extensive data processing for the ZiCOS-M network are outlined and explained below. The data processing logic was dependent on the sensor type (Section 2.1) because of their variable performances relating to what onboard correction algorithms were activated. A schematic of data processing steps is shown in Figure A2 and the main equations are presented in the appendix. The final set of observations was classified as Level-2A following the processing levels proposed by [Schneider et al. \(2019\)](#).

At a high level, the data processing steps can be grouped into three operations: (i) the collection and formatting of data from different sources to conform to a formal data model and framework for convenient access and interaction, (ii) the application of various adjustment strategies to improve the measurement quality (*i.e., to increase their agreement with observations generated by reference instrumentation*) without moving to outright model predictions ([Schneider et al., 2019](#)), and (iii) the handling and integration of metadata units such as when and where sensors were located, calibration gas information, and what observations have been invalidated and why. All data processing was conducted with the R programming language ([R Core Team, 2023](#)). The database technology used was PostgreSQL ([PostgreSQL Global Development Group](#)), and the formal time series relational data



© OpenStreetMap contributors 2024.
 Distributed under the Open Data Commons Open Database License (ODbL) v1.0
 Elevation data from swisstopo's DHM25

Installation ● Rooftop ● Near-ground ● Near-ground (kerbside)

Figure 3. The ZICOS-M CO_2 sensor sites (additional details can be found in Table 2) in and around the vicinity of Zürich city. Vegetated areas, terrain, and substantial water bodies are also shown.

model was an extended **smonitor** data model previously developed for air quality applications that overlaps with greenhouse gas monitoring almost completely (Grange et al., 2017; Grange, 2018, 2019a, b).

2.3.1 Transmission and storage

185 All sensor data were transmitted through the LoRaWAN network to Decentlab's cloud storage infrastructure (Decentlab GmbH, 2022) where the data packets were decoded and made accessible via a simple application programming interface (API) (Grange, 2024b). Depending on the sensor type, diagnostic variables along with raw measurement values (the IR signal in the specific case of NDIR sensors), ancillary data such as temperature, relative humidity, and pressure from other sensors integrated into the sensor product as well as onboard calculated CO_2 concentration were transmitted and stored. In the **smonitor** nomenclature, 190 the CO_2 calculated by onboard algorithms (that are generally proprietary) and coefficients determined by factory calibration

was called *reported* CO_2 . The sensors reported observations approximately every 60 seconds; however, because of limitations of the LoRaWAN protocol, usually 57–58 measurements were successfully transferred and stored per hour.

Several other data sources were accessed in an automated or semi-automated fashion. These data sources include: observations from a CO_2 analyser installed at the Dübendorf-Empa NABEL monitoring site (Figure 3), which was the facility used for field testing and parallel measurements, observations for two additional high-precision CO_2 analysers in Switzerland but outside Zürich city (Lägern Hochwacht and Beromünster; Figure 2), observations for three NABEL monitoring sites that hosted meteorological instrumentation, two MeteoSwiss data sources – the VQEA33 data product that contains MeteoSwiss’s ‘core’ sites or stations that host a full suite of meteorological sensors (five sites in and around Zürich were available), and observations sourced from the IDAWEB portal (MeteoSwiss, 2009) for five additional meteorological sites in and around Zürich city, and finally Jungfrauoch’s high-alpine (at 3572 m altitude; Figure 2) validated and near-real time CO_2 observations from the ICOS Carbon Portal (Emmenegger et al., 2023, 2024). All of these data sources were integrated into the common data model and stored for uniform access and interaction.

2.3.2 Water dilution effect correction and dry air mole fractions

Atmospheric CO_2 is usually reported as dry air mole fraction (in units of $\mu\text{mol mol}^{-1}$ or parts per million, ppm), because this quantity is preserved, not only during atmospheric transport, but also under processes changing the moisture content of the air (Tans and Thoning, 2020). Here, we often use the more generic term “concentration” interchangeably, but in all cases beyond reported CO_2 , the more accurate definition of dry air mole fraction is correct.

All NDIR CO_2 sensors used in the network reported CO_2 in moist air. To convert to dry air mole fractions, an estimate of the water vapour in the gas sample was required, which was obtained from the ancillary temperature and relative humidity sensors installed in the gas stream and the ambient pressure sensors installed within the sensors’ waterproof box. The vapour pressure of water was calculated from the relative humidity and the saturation vapour pressure according to the August-Roche-Magnus equation (Alduchov and Eskridge, 1997; Lawrence, 2005). This conversion to dry air mole fractions is referred to as water dilution correction in the following text.

The Senseair HPP sensors also required their reported CO_2 to be explicitly normalised to standard atmospheric pressure (1013.25 hPa) before the dilution correction. This was necessary because a clear CO_2 dependence on ambient pressure was observed during testing, which indicated that the integrated pressure sensor was not properly used for onboard pressure normalisation. This extra transformation was not required for the two other sensor types as they did not show a dependence on air pressure during the same tests.

2.3.3 Reference gas cylinder calibrations

The sensors were integrated with three inlets, an inlet for ambient air sampling and two inlets for the connection of two reference gas cylinders containing known CO_2 traceable to the WMO CO_2 X2019 calibration scale (Hall et al., 2021). Across the network, the sensors were deployed with 5 or 10 L ‘high’ and ‘low’ reference gas cylinders (≈ 400 and ≈ 600 ppm, respectively; Figure 1). The inlets were switched from ambient to low and high inlets (in that order) every 25 hours for 10 minutes. The

first preceding and four subsequent minutes before and after the gas tests were handled as a non-ambient sample to ensure the
225 sample system was flushed of cylinder-sourced gases and did not contaminate the ambient samples.

For each gas test, the period was isolated, the first and final three minutes were discarded and the median was taken to
represent the sensor's CO_2 for the cylinder test. This trimming and summary logic robustly captured the CO_2 concentration in
the gas stream from the cylinder after the sensor had reached stability and the gas stream's flow, pressure, and humidity had the
opportunity to equilibrate during the test period. Because the calibration gases were nearly dry, a gas sample humidity criterion
230 of less than 10 % relative humidity was applied to determine whether the test was valid. A moist sample indicated a leak or an
empty cylinder. All test summaries were stored for later use.

The high and low test summaries were used to compute a slope and offset with simple linear regression – albeit (usually)
with only two points. The final calibrated dry air mole fraction was then computed from the reported dilution-corrected dry air
mole fraction (Figure A2).

235 Infrequently, a gas test summary was correctly calculated, but the result was a clear outlier. This was usually driven by poor
data capture or bad valve articulation during the gas test. Therefore, the gas test summaries were passed through an interquartile
range filter to remove these outliers. Three-day rolling means of the slope and offset coefficients were calculated to slightly
smooth the coefficients and to avoid a relatively large change in a coefficient occurring when traversing the midnight boundary
during the moving from one calendar day to the next (Figure A3). If a daily test was missing due to operational issues, the
240 application of a last observation carried forward process was applied to the coefficients.

All sensors were able to be successfully corrected for their relatively constant change in baseline and sensitivity over the
monitoring period with the daily reference gas tests (an example is shown in Figure A3). The remaining variability may be
partly explained by spectroscopic effects driven by various changes in environmental conditions, such as temperature and
pressure. When there is access to two-cylinder gas tests for such an adjustment, other strategies are also possible; for example,
245 to use the low gas for an offset adjustment and the high gas as a target gas for quality control purposes. However, since the
sensors did not only reveal a drift in offset but also gradual changes in sensitivity, it was necessary to calibrate both offset and
slope to meet the performance objectives of an uncertainty of about 1 ppm.

2.3.4 Correction of the water-induced response

During intercomparison exercises, a measurement performance issue was uncovered with some of the sensors, specifically the
250 Senseair HPP sensors, the sensor model that was most frequently used in the network (Table 1). The issue was identified as
a response to water vapour that was not related to the dilution effect. For NDIR measurement technologies and especially for
the measurement of CO_2 , this feature is known and can be potentially corrected for by the sensor-internal data processing
(McDermitt et al., 1993; LI-COR Biosciences, 2023). We labelled the effect as a generic *water-induced response* because
the exact mechanism was not confirmed, but will most likely include a combination of spectroscopic features including band
255 broadening, crosstalk, and/or interference. This issue manifested not only in suboptimal performance in ambient monitoring
but also as a positive bias of a few ppm, despite the reference gas calibrations. A bias of this magnitude was problematic and

was caused by the reference gases in use being dry. The reference gases were thus completely absent of the interferent that was present during ambient monitoring.

260 The water-induced response was quantified for each sensor using the following laboratory setup. A spiral sampling line with a length of one metre complete with fittings to allow for connections with cylinders containing known CO_2 and water injections. The gas cylinder was connected to the sampling line and after a settling period, 0.5 mL of Milli-Q water was injected into the sampling line and sealed. The gas was sampled at a flow rate of 0.5 L min^{-1} . The experiment lasted for about 90 minutes, during which the humidity decreased from approximate saturation to nearly zero. This test was repeated with three reference gases containing 418, 492, and 614 ppm CO_2 . The obtained data were used to train a multiple linear regression model with two terms, 265 absolute humidity and CO_2 , which was later used to correct for the water-induced response. The humidity tests showed that the factory correction for the water-induced response was adequate in the case of the Vaisala GMP343 sensor type (Figure A4); hence, this correction was not implemented for the five sensors that were used in the network. The water-induced response is not necessarily a linear function of humidity and CO_2 (Wu et al., 2023). However, our tests showed that a linear fit was sufficient and consistent with the overall performance of the sensors (presented and discussed in Section 3.1).

270 2.3.5 Flagging observations for possible local contamination

A challenging issue was the handling of possible contamination from sources in the immediate vicinity of the sensors' sample inlets. This is a general difficulty for monitoring in urban areas with their numerous sources, and it was especially clear for some rooftop monitoring locations where the inlets were located in close proximity to stacks for heating and/or hot water gas-fired boilers and ventilation shafts. Although an observation taken in such a situation is valid in an operational sense, for 275 some analyses, such measurements need to be removed or handled in another way. Therefore, an algorithm was implemented to detect potential local contamination. The Hampel identifier was used, which is a windowed median absolute deviation (MAD) filter where a value's distance from the median is evaluated (Pearson et al., 2016), and if that value is outside a threshold, then it is identified as an outlier. The Hampel identifier works in the same manner as other windowed filters, such as those documented and defined as 'despiking' algorithms by El Yazidi et al. (2018), and it was very effective at identifying local contamination 280 events in the rooftop-sampled CO_2 time series as in, for example, Figure A5.

The flagging was applied to all 14 sites that were classed as rooftop sites (Table 2). The median potential local contamination fraction among these sites was 0.9 % but one site, Limmattalstrasse Höngg, had a much greater fraction of 5.1 % (Table A2). For the analyses presented here, all observations that were classed as potentially contaminated were removed. All time series were also manually inspected as part of the network operations. Erroneous measurement spikes and observations taken during 285 maintenance activities were also flagged to ensure that downstream data users had information on the validity of any given observation.

3 Results and discussion

3.1 Sensor CO_2 measurement performance

Measurement performance of all sensors was assessed during ambient measurements carried out at the Dübendorf-Empa air quality monitoring site (Table 2; Figure 3), which was equipped with a calibrated high-precision CO_2 analyser (a Picarro G1301) and produced the reference CO_2 time series that was considered a ground truth. The objective of the intercomparisons was to independently test the sensor system in conditions that were very similar to what the sensors experienced in field deployment. In our case, this was with an inlet sampling ambient air and the sensor installed inside, usually in an air-conditioned room. The analyser and sensors were run independently of one another, and their observations were only compared after the monitoring period. Therefore, the intercomparisons were classed as independent, parallel measurements.

The targeted minimum duration of the parallel measurements was two weeks (336 hours), but generally, this period was longer. The data processing was undertaken in the way it would be conducted in the field, with the same logic being applied for dry air mole fraction transformation, the subtraction of water-induced response if required, and the calibration of observations based on the daily cylinder tests (Section 2.3). The facility did not have the physical space to test all sensors at the same time, so the sensors were tested sequentially or in pairs over a period of 12 months. Therefore, the sensors experienced different environmental conditions from one another during testing, which could explain some of the inter-sensor variation observed. Standard pairwise performance statistics were computed. The equations and descriptions of these statistics can be found in Peters et al. (2022).

The sensors' average hourly mean root mean squared error (RMSE) was 0.98 ppm and ranged between 0.46 and 1.5 ppm, depending on which sensor was under test (Figure 4; Table A3). The average mean bias was -0.09 ppm, but the average mean bias also demonstrated values between -0.72 and 0.66 ppm due to sensor variation. The calculation of the RMSE error statistic, which covers both systematic (bias) and random components, can be interpreted as the average uncertainty of the estimators' (the sensors') predictions. The measurement uncertainty of approximately 1 ppm, as determined during testing, can be confidently translated to field conditions because of the design of the testing procedure.

The discontinued Senseair HPP sensor often performed poorer than the commercially available Vaisala GMP343 and Licor LI-850 sensors. The inter-sensor variability of the Senseair HPP sensors was also higher, with some sensors displaying more measurement uncertainty than others (Table A3). This variation may have been partially caused by the variability of age or uptime because some of these sensors had been used previously for monitoring in other studies (see Müller et al., 2020) or differing environmental conditions during the testing period. Furthermore, the Senseair HPP sensor was a prototype, possibly resulting in larger variations in the product. However, because of the irregular number of each sensor type, additional sensor units would need to be used to confirm these apparent patterns and not over interpret the rather small differences observed among the different sensor models.

Scatterplots of hourly means (Figure 5) demonstrated that all three sensor types displayed excellent CO_2 measurement quality and linearity across the detected ambient CO_2 range. The scatterplots also show the importance of data processing and the improvements in measurement performance in both bias and dispersion dimensions, that were achieved due to the




Figure 4. Hourly CO_2 error statistics of the sensors that were exposed to parallel measurements with a high-precision reference gas analyser at the Dübendorf-Empa monitoring site.

application of correction and calibration processes (moving sequentially from the top to bottom panels in Figure 5). In general, the Senseair HPP sensors displayed more dispersion around the reference observations, and therefore, a larger measurement error than the other two sensor models. A somewhat surprising observation was that, despite the Licor LI-850 measuring and reporting water vapour directly, a small water-induced response was still experimentally confirmed. Achieving the measurement performance shown in Figure 4, Table A3, and Figure 5 was only possible with these NDIR sensors with the utilisation and careful handling of reference gases, which is not feasible for many other atmospheric gases – including the family of reactive gases (and particulates) that are important for air quality.

The use of reference gases increased the complexity of the measurement system and the maintenance required for the operation of the network. However, the gases were critical for achieving the reported measurement performance (Figure 5). An alternative strategy would be to use a single gas and apply only an offset correction. A sensitivity analysis exploring this approach was conducted by withholding the ‘high’ gas tests and only using the ‘low’ CO_2 cylinder (≈ 400 ppm) for an offset correction. The mean RMSE and bias penalties of this approach were 1.7 and 0.8 ppm and the corresponding medians were 0.17 and 0.12 ppm (compared to the two-gas calibration discussed above). The median penalties of using a single reference gas were rather low and may be acceptable for some monitoring applications, but the larger means demonstrate that for some of the sensors (three in this case) the sensitivities altered during the testing procedure, and thus, the second gas test was required to address this robustly. This sensitivity analysis showed that an offset correction strategy could be used in some scenarios, but the sensors’ sensitivity stability should be regularly tested to ensure that large measurement performance penalties do not arise.




Figure 5. Hourly CO_2 means for selected sensors for the three sensor models used in the ZiCOS-M network during [intercomparison](#) at the Dübendorf-Empa monitoring site. The improvements in measurement performance can be seen when moving from top to bottom as the data processing adjustments are applied. The Vaisala GMP343 sensors did not require a water-induced adjustment, therefore, this was not calculated and is not shown.

The intercomparison periods were also used to evaluate the effectiveness of the water vapour correction that was determined in laboratory tests under real conditions. Figure 6 shows the response of the three CO_2 sensor types to absolute humidity during their intercomparison periods. Without correcting for the water dilution effect, the values were biased low in comparison to the reference because the sensors reported CO_2 in moist air. In the case of the Senseair HPP, converting from moist to dry mole fractions (*i.e.* correcting for the water dilution), led to an overestimation of CO_2 . Additionally, correcting for the water-induced response brought the residuals close to zero, demonstrating the importance of this additional correction.




Figure 6. CO_2 residuals by sample absolute humidity (in 0.5 g kg^{-1} bins) during parallel measurements with a high-precision reference gas analyser at the Dübendorf-Empa monitoring site. The clear influence of dilution (negative) and water-induced response (positive) can be observed in the Senseair HPP example, as can the efficacy of the post-measurement adjustments or corrections.

An hourly CO_2 measurement uncertainty of 1 ppm is comparable to other studies that report such results for CO_2 NDIR sensors (Shusterman et al., 2016; Martin et al., 2017; Kunz et al., 2018; Arzoumanian et al., 2019; Müller et al., 2020; Delaria et al., 2021; Lian et al., 2024). Direct comparisons among the various studies are difficult due to the different endpoints that were defined, variable testing or intercomparison designs, and if the stated uncertainty or error truly represents field conditions. However, because many studies have reported rather similar results, it is likely that measurement uncertainties of ≈ 1 ppm can be expected with the current generation of CO_2 NDIR sensor products. In contrast, the World Meteorological Organization has set compatibility goals of 0.1 and 0.05 ppm for background monitoring sites in the northern and southern hemispheres, respectively, when using state-of-the-art monitors (World Meteorological Organization, 2014). Clearly, these types of sensors are unsuitable for background monitoring sites at this time.

3.2 CO_2 variation in and around Zürich city

3.2.1 Site means

355 The ZICOS-M sensor network that included 26 monitoring sites demonstrated that CO_2 was highly variable across time and the Zürich area during the monitoring period between July 2022 and July 2024. The sensor network's urban background site for the Zürich region, Birchwil Turm (Figure 3), experienced a mean CO_2 of 434 ppm while the highest mean CO_2 concentration of 460 ppm was found at Rosengartenstrasse (Table 3; Figure 7). Reckenholz observed the second highest mean CO_2 and notably was a rural, near-ground monitoring site with an inlet height of 4.2 m (Table 3). The high levels of CO_2 were not driven
360 by anthropogenic emission activities, but by strong biogenic respiration in the early hours of the morning. Dübendorf-Empa, the network's testing site was also exposed to strong biogenic forcing with peak CO_2 occurring in the early morning during the growing seasons including spring, summer, and autumn. The processes governing these features are further explored in Section 3.2.2. Beromünster suffered an observation gap between late August 2023 and early February 2024 due to instrument failure and therefore, had a lower data capture rate compared to the other sites.




Figure 7. Mean CO_2 for ZICOS-M's 26 monitoring sites between July 2022 and July 2024.

365 Rosengartenstrasse was the most enhanced monitoring site with respect to CO_2 . Rosengartenstrasse is in Zürich city proper and is located in a kerbside environment next to an uphill and northbound section of an arterial road. It displayed a clear,

Table 3. Summary statistics for the CO_2 monitoring sites between July 2022 and July 2024. CO_2 unit ppm representing dry air mole fractions and the sites are ordered by their mean CO_2 .

Site	Site type	Installation	Mean	Median	Min.	Max.	Data capture (%)
Jungfrauojoch	High-alpine background	High-alpine	421.4	421.9	407.0	460.5	94.0
Beromünster	Rural background	Tower	423.4	423.5	401.8	466.1	60.9
Lägern Hochwacht	Rural background	Elevated	427.7	427.7	401.0	473.4	93.3
Sottens	Rural background	Tower	427.8	427.5	404.6	477.4	96.5
Birchwil Turm	Rural background	Tower	433.6	432.4	401.4	496.8	91.9
Albisgüetli	Urban	Rooftop	438.4	433.9	399.0	562.3	96.8
Heubeeribüel	Urban	Near-ground	438.7	436.5	400.6	577.9	94.9
Hardau II	Urban	Rooftop (high)	441.0	435.3	404.1	603.7	98.1
Universität Zürich Irchel	Urban	Rooftop	442.2	436.3	402.8	627.8	95.3
Tiefenbrunnen Wildbachstrasse	Urban	Rooftop	444.2	438.4	400.6	649.8	96.3
Kantonaes Labor Zürich	Urban	Rooftop	444.4	440.2	402.5	649.1	94.3
Wollishofen	Urban	Rooftop	444.8	439.3	403.2	611.4	95.8
Letzigraben Telefonzentrale	Urban	Rooftop	446.7	439.4	401.7	603.9	98.4
Schule Milchbuck	Urban	Rooftop	447.4	440.7	402.6	616.1	86.0
Stauffacherstrasse Werdplatz	Urban	Rooftop	447.5	440.4	402.3	646.8	97.5
Hardturmstrasse Förrlibuck	Urban	Rooftop	449.0	440.6	402.6	599.6	87.8
Güterbahnhof	Urban	Rooftop	449.7	441.8	405.9	624.5	96.6
Zürich Kaserne	Urban	Near-ground	449.8	443.0	403.3	636.3	97.1
Bankenviertel Bleicherweg	Urban	Rooftop	449.9	443.4	407.9	638.4	88.9
Limmattalstrasse Höngg	Urban	Rooftop	450.7	443.8	403.3	599.3	84.5
Badenerstrasse Farbhof	Urban	Rooftop	451.3	444.1	402.2	615.3	79.3
Stampfenbachstrasse	Urban traffic	Near-ground (kerbside)	451.6	444.4	405.2	647.9	94.1
Dübendorf-Empa	Urban	Near-ground	457.6	443.2	400.9	646.3	98.3
Schimmelstrasse	Urban traffic	Near-ground (kerbside)	458.6	450.8	407.7	646.3	97.4
Reckenholz	Urban	Near-ground	459.4	441.4	399.0	732.4	94.4
Rosengartenstrasse	Urban traffic	Near-ground (kerbside)	460.3	453.4	409.7	643.7	92.5

traffic-forced diurnal cycle of CO_2 during the day, as observed in other cities (Shusterman et al., 2018). The two other traffic sites located in kerbside environments – Schimmelstrasse and Stampfenbachstrasse – also experienced some of the highest CO_2 of the network (Table 3; Figure 7).

370 Site means for the daytime hours (local time between 10:00 and 16:00) are also provided in Figure A6. The gradient between background and rooftop sites was, on average, about 25 ppm for daily means but only 15 ppm for daytime means. For the kerbside locations Rosengartenstrasse and Schimmelstrasse the gradient was about 30 ppm in both cases suggesting that their concentrations are primarily determined by their proximity to traffic, and less so by atmospheric dispersion dynamics.

375 When considering only the rooftop sites with measurement heights between 13.5 and 114 m (Table 2), the daily means ranged from 438 ppm at Albisgüetli to 451 ppm at Badenerstrasse Farbhof (Table 3), a mean gradient within the city of 13 ppm. For daytime means the gradients were only about half this magnitude, but they were still sufficiently large to be reliably

captured by the sensors, given their measurement uncertainty of 1 ppm (Section 3.1). Jungfraujoch, the high-alpine monitoring site located in the distant Bernese Alps at an elevation of 3572 m, experienced a daily mean of 421 ppm which represented European background CO_2 during the period of monitoring. Another interesting observation is that the distant sensor site in
 380 Sottens in Vaud (western Switzerland; Figure 2) had lower mean and median CO_2 than Zürich's regional background site Birchwil Turm, despite their comparable installation and sampling height, which suggests the source-sink dynamics across the Swiss plateau were variable during the monitoring period.

3.2.2 Diurnal cycles and ranges

The diurnal cycle of CO_2 at the 26 sites in the ZiCOS-M network formed three broad groups reflecting different source and sink dynamics that can be classified as background, anthropogenic-influenced, and biogenically forced. Background sites demonstrated minor changes in mean hourly CO_2 throughout the year but, except for Jungfraujoch, small amounts of morning
 385 CO_2 enhancement and afternoon reduction were present in all seasons (Figure 8). The magnitudes of the morning CO_2 peaks were higher than those experienced in the afternoon or evening. Three-monthly definitions of seasons were used, where summer refers to the months of June, July, and August.




Figure 8. Seasonal CO_2 diurnal cycles for selected monitoring sites with different site type classifications between July 2022 and July 2024.

390 Most sensor sites were located in or around Zürich's urban area, and they showed an anthropogenic-influenced diurnal cycle. These anthropogenic-influenced sites were distinguished by CO_2 levels peaking in the morning (usually between 06:00 and 10:00), driven by traffic and other anthropogenic emission processes at these times. A combination of increased atmospheric dispersion and biogenic uptake in the early and mid-afternoon reduced CO_2 to the daily minima (Figure 8). During summer afternoons, many of the anthropogenic-influenced sites' mean CO_2 were below the European background at Jungfraujoch, due
 395 to uptake by the local and regional biosphere, reflecting the ground-level acting as a net sink in this season (Stephens et al.,

2007). Outside the growing season, *i.e.*, winter, the anthropogenic-influenced sites showed a clear second peak in the afternoon or evening due to traffic and heating emissions. This was reminiscent of the diurnal cycles observed for primary air pollutants because they are co-emitted from the same sources (West et al., 2013; Fiore et al., 2015; The Royal Society, 2021), and due to the lack of strong active CO_2 sinks at this time of the year.

400 The Reckenholz and Dübendorf-Empa sites formed the third, biogenically forced, diurnal cycle group. This group was strikingly distinct from the other groups and was identified by peak CO_2 being reached in the early hours of the morning (04:00–06:00) during the growing seasons (Figure 8). These early morning CO_2 peaks could exceed 730 ppm which was higher than peak CO_2 observed at the three kerbside monitoring sites. A combination of CO_2 emissions from ecosystem respiration processes into an extremely confined nocturnal boundary layer with no or very little advection caused these rather
405 extreme CO_2 levels. These observations were clear demonstrations of what is known as the rectifier effect where boundary layer dynamics and CO_2 fluxes are temporally correlated, which amplifies the diurnal variability of CO_2 beyond the magnitude expected from source-sink dynamics alone (Denning et al., 1999; Shi et al., 2020). Similar observations, such as those captured by ZiCOS-M, have been made previously, albeit somewhat less pronounced, in Switzerland (Gimmiz) (Oney et al., 2015) and
410 Canada (Vancouver) (Crawford and Christen, 2014). Both Reckenholz and Dübendorf-Empa have significant amounts of forest and crop fields in the surrounding area and furthermore, Reckenholz is located in a shallow depression. For all three diurnal cycle groups, the daily CO_2 minima were always reached in the afternoon (between 14:00–16:00 local time) and showed little temporal variation among the different seasons.

To further characterise the diurnal variability across the network, the amplitude of the mean differences between daily minimum and maximum hourly means were calculated for each season and all sites. The two biogenically forced Reckenholz
415 and Dübendorf-Empa sites showed large diurnal ranges in all seasons, apart from winter, with diurnal ranges peaking at 106 and 81 ppm in the summer months (Figure 9). Diurnal ranges of this magnitude were greater than those reported in previous studies, for example, Vogt et al. (2006). The extremely high values in the early morning hours are responsible for these two sites' high mean CO_2 values, presented in Figure 7 and Table 3. The high-alpine Jungfrauoch site is largely isolated from localised CO_2 sources and sinks, and thus showed almost no diurnal range throughout all four seasons. This contrasted with all
420 other sites in the network, which experienced their most pronounced diurnal cycle in summer, followed by spring or autumn due to the correlated diurnal variation in boundary layer depth and natural and anthropogenic sources and sinks during these seasons. The low diurnal ranges observed in winter can be mostly explained by only anthropogenic sources being active, because the climate of Zürich is such (Köppen-Geiger climate classification: *Cfb* (Beck et al., 2018)) that plant respiration and photosynthesis drops to near-zero for much of this period (Zubler et al., 2014).

425 3.2.3 Quantification of Zürich's urban CO_2 dome

The ZiCOS-M network was used to calculate overall and seasonal environmental increments, notably the regional CO_2 enhancement of the Swiss Plateau compared to European background mole fractions represented by Jungfrauoch and the magnitude of Zürich city's urban CO_2 dome, with respect to the regional background. Between July 2022 and July 2024, Zürich's regional background was on average 9.3 ppm larger than the European background and Zürich's urban CO_2 dome was enhanced




Figure 9. Mean diurnal ranges of CO_2 of minimum and maximum hourly means for four seasons for ZiCOS-M monitoring sites between July 2022 and July 2024.

430 by an additional 15.4 ppm above its regional background (Figure 10). There was, however, a 12.1 ppm inter-site gradient among the rooftop monitoring sites, (Figure 7; Table 3) and this resulted in CO_2 enhancements ranging from 7.9 to 20 ppm depending on what site was considered in isolation. Urban CO_2 enhancements of such magnitudes are comparable to other urban areas where similar analyses have been conducted and reported, for example, [Briber et al. \(2013\)](#); [Xueref-Remy et al. \(2023\)](#).

In Zürich's roadside environments, the proximity to the principal CO_2 emission source of traffic elevated CO_2 levels by an additional 26.4 ppm enhancement above Zürich's urban dome (Figure 10). This roadside enhancement, relative to other urban environments, remained relatively constant during winter, spring, and summer, but it did increase in autumn. This suggests that the extra roadside loading of CO_2 remained mostly unchanged throughout the year and the regional background CO_2 was generally a more important driver of observed CO_2 in Zürich and, in turn, indicated that larger European scale source-sink processes drive much of the variability of CO_2 observed in Zürich's urban area. On average, the biogenic forced environments 440 experienced higher CO_2 increments (28.5 ppm) than all other environments, including those located next to the roadside (Figure 10). However, the large increments were only present in Zürich's growing seasons, especially in summer and autumn (34 and 36.4 ppm, respectively), and only in daily means, but not in daytime means as previously discussed.





Figure 10. Daily CO_2 increments for different environments in Zürich between July 2022 and July 2024. The points indicate the groups' mean while the error bars show the minimum and maximum of the sites within the groups.

3.2.4 Zürich's regional CO_2 background

A striking feature of the network behaviour was that Zürich's regional background CO_2 was highly variable. Figure 11 shows daily means of CO_2 for the Birchwil Turm and Lägern Hochwacht regional background monitoring sites and the high-alpine site of Jungfraujoch. The figure shows the large dynamic range and pronounced temporal variability of the regional background enhancement relative to Jungfraujoch. Enhanced CO_2 was generally experienced in episodes with durations between four and 25 days, the longest of which was experienced in November and December 2022 (episode 6 in Figure 11). Here, an episode was defined as CO_2 being at least 14 ppm higher than Jungfraujoch for at least four sequential days. In total, 20 such episodes were identified during the monitoring period. CO_2 depletion events also occurred where Zürich's daily mean background CO_2 dropped below Jungfraujoch's, but this was rather rare and did not persist for longer than two days.

The 20 high CO_2 episodes, that were objectively classified, were explored and these episodes were not clearly related to wind speeds or wind conditions that would result in Zürich's or Winterthur's urban plumes nor emissions from Zürich's international airport being transported to the monitoring site. This suggested that Zürich's episodic high CO_2 background was driven by larger synoptic-scale processes when sink- and source-laden air masses pass over the region, as has been observed elsewhere (Hurwitz et al., 2004; Pal et al., 2020; Davis et al., 2021). Furthermore, a key observation from this analysis is that Zürich's



Dashed line indicates 415 ppm
 Labelled shaded zones show the identified episodes

Figure 11. Daily CO_2 for two of ZiCOS-M’s regional background sites and a high-alpine monitoring site between July 2022 and July 2024. High regional CO_2 episodes are indicated and labelled.

CO_2 is not driven by a simple anthropogenic loading on top of the hemispheric (or European) background, but rather it is a function of processes acting on different scales, all of which interact to produce ambient concentrations.

To investigate these 20 episodes further, FLEXible PARTicle dispersion model (FLEXPART) (Pisso et al., 2019) footprints
 460 for a European domain were run using Birchwil Turm as the receptor site for the time when the sensor network was operational. This was done to determine where air masses were sourced from during the high CO_2 episodes. To clearly visualise the origin of the air masses experienced for each episode, each episode’s surface was normalised by the entire period’s mean in the same way as described in Sturm et al. (2013).

The FLEXPART footprints indicated that episodes occurred in most circulation regimes, with the exception of strong flows
 465 sourced from the Atlantic Ocean (six example episodes shown in Figure 12). Examples of northerly, southerly, western, and eastern flows are present, as are conditions that are consistent with extended calm conditions. These footprints and the lack of clear correlation in wind behaviour demonstrate that high background CO_2 was influenced by larger scale processes, but high CO_2 episodes can occur in almost any circulation regime in Zürich.




Figure 12. Normalised FLEXPART footprints (as described in [Sturm et al. \(2013\)](#)) for Birchwil Turm for six selected high CO_2 episodes experienced at the sensor network's regional background sites during the network's monitoring period.

3.2.5 A low urban CO_2 event case study

470 The measurement performance of the sensors in the ZiCOS-M network was high enough to resolve local CO_2 source-sink processes. An example of this was when CO_2 dropped below regional background concentrations across the city on March 3 2024. In Zürich on March 3, the highest temperatures of the year to that date were experienced, peaking at 18°C . It represented one of the first days, if not the first day of 2024, when the biogenic uptake of CO_2 was strong due to photosynthesis. In the early afternoon, most sensor sites in the urban area experienced CO_2 levels well below those that were reported at the network's regional background monitoring sites, especially for five hours between 13:00 and 19:00 (Figure 13). The site that demonstrated this plunge in CO_2 levels the clearest with a difference of 17 ppm was Universität Zürich Irchel, a rooftop monitoring site

475

located in the northeast corner of the city (Table 3) and on the western border of the Zürichberg forest and hill (Figure 3). An analysis of the wind behaviour at the time of low CO_2 concentrations revealed that the episode coincided with a wind direction shift to an east-southeast direction with wind speeds above 2 m s^{-1} (Figure 13). This strongly suggested that air from the Zürichberg forest that was depleted of CO_2 on the first growing day of the year was being transported over the Universität

480




Figure 13. Time series of CO_2 and meteorological variables on March 3 and 4, 2024 demonstrating an episode where CO_2 at Universität Zürich Irchel dropped well below regional background levels due to forest air depleted of CO_2 passing over the monitoring site.

Zürich Irchel site, and the city in general. The depleted CO_2 air over the city took another 24 hours to revert to the normal situation where CO_2 in the urban area was higher than the regional background location. The Birchwil Turm monitoring site experienced CO_2 reduction too during the afternoon of March 3 because of biogenic uptake, but the specific and local process identified around Zürich's urban area did not affect this more distant location in the same way. This case study shows that the sensor network could provide insight into very specific and local-scale processes.

4 Conclusions

The ZICOS-M CO_2 network's sensor performance and the insights gained into atmospheric processes influencing CO_2 while the network was operational have been presented and discussed. The measurement performance of the sensors was assessed through parallel measurements with a high-precision instrument under representative field conditions. After addressing ambient

490 pressure, water vapour, and reference gas tests, the mean uncertainty was quantified at 0.98 ppm of RMSE for hourly mean values. This level of measurement performance was high enough to confidently disentangle CO_2 gradients across Zürich's regional and urban areas.

During the monitoring period between July 2022 and July 2024, the sites' CO_2 means ranged from 433 to 460 ppm, reflecting their different surrounding environments. The sites that experienced some of the highest CO_2 were strongly influenced by
495 biogenic respiration with peak hourly CO_2 exceeding 730 ppm in the early hours of the morning. These levels were higher than those found in Zürich's roadside environments but only reflected biogenic respiration in certain conditions and did not reflect the full CO_2 source-sink dynamics at these biogenic sites. Zürich's urban CO_2 dome was quantified, on average, as 15.4 ppm above the regional background and ranging between 7.9 and 20 ppm when considering the individual monitoring sites. Furthermore, the sensor network showed that the processes which drove CO_2 levels acted on multiple scales with synoptic-scale transport of
500 CO_2 -depleted or CO_2 -enhanced air masses being especially important, and resulted in a very dynamic regional background that experienced several high CO_2 episodes during the monitoring period. This illustrates that the observed CO_2 across the Zürich region was not a simple anthropogenic loading on top of a stable regional background, and emphasises the importance of measurement sites placed in the surroundings of the city to characterise this background. These observations support previous studies, such as [Turnbull et al. \(2015\)](#).

505 The ZiCOS-M network provided important insights in its own right, but the observations will be used further in downstream activities utilising atmospheric inversion modelling systems, including the ICON-ART ([Schröter et al., 2018](#); [Steiner et al., 2024](#)) and GRAMM/GRAL models ([Berchet et al., 2017](#)), to determine the city's CO_2 emissions and compare them to the established approach based on the emission inventory ([Stadt Zürich, 2023b, 2024](#)). The sensor network also contained low-cost sensors that have not been presented here. However, details and the results gleaned from the low-cost sensors are in
510 preparation. The ZiCOS-M network acts as a good example of an environmental gas sensing monitoring network in which the measurement performance was adequate to answer a number of scientific research questions at an order of magnitude lower cost than would be possible with contemporary state-of-the-art CO_2 reference instruments.

Appendices

Figures



Figure A1. Examples of the CO_2 sensor's typical installations in the CARIN-ZH sensor network in Zürich city. The photograph on the left was taken by Pekka Pelkonen from ICOS RI.




Figure A2. Schematic of the data handling steps for the sensors' CO_2 observations in the ZiCOS-M sensor network.




Figure A3. Slope and offset coefficients calculated from daily reference gas cylinder tests for an example sensor between July 2022 and July 2024. When applying the adjustment calculations, the three-day rolling mean coefficients were used. This particular sensor demonstrated a decline in baseline and sensitivity during the monitoring period.




Figure A4. Examples of the water-induced response for three different types of CO_2 sensors during the decaying humidity tests. The Senseair HPP sensors strongly demonstrated the effect.




Figure A5. An example of the potential local contamination identification for a CO_2 sensor rooftop monitoring site between October 2022 and July 2024 where heating periods can be visually identified (this site is a school). The observations that were identified as contaminated by local contamination were flagged for optional handling by downstream data users.




Figure A6. Mean daytime (local time hours between 10:00 and 16:00) CO_2 for ZiCOS-M's 26 monitoring sites between July 2022 and July 2024.

Table A1. Mid-cost sensors' parts or components makes and models.

<u>Sensor part</u>	<u>Make and model</u>	<u>Notes</u>
<u>External sample inlet filter</u>	<u>Solberg FS 1/4"</u>	<u>With steel mesh & no filter insert used</u>
<u>Sample inlet tubing</u>	<u>SynFlex 1/4"</u>	
<u>Inlet particulate filter</u>	<u>Swagelok SS-4TF-05</u>	
<u>Sample valve</u>	<u>IMI Norgren Bacosol 3-way Valve</u>	
<u>Internal tubing</u>	<u>Thermoplastic Processes Bev-A-Line VHT 1/4"</u>	
<u>Sample pump</u>	<u>KNF NMP015B</u>	
<u>Ancillary temperature and relative humidity sensor</u>	<u>Sensirion SHT21</u>	
<u>Ancillary pressure sensor</u>	<u>Bosch BMP380</u>	
<u>Demand-flow regulator</u>	<u>Calgaz DFR 2003</u>	
<u>Control board</u>	<u>Decentlab Custom integration</u>	

Table A2. Fraction of observations that were identified as potentially locally contaminated with an outlier detector for 14 rooftop monitoring sites.

Site	Installation	Fraction of potentially locally contaminated observations (%)
Hardturmstrasse Förrlibuck	Rooftop	0.5
Stauffacherstrasse Werdplatz	Rooftop	0.5
Hardau II	Rooftop (high)	0.7
Kantonales Labor Zürich	Rooftop	0.7
Letzigraben Telefonzentrale	Rooftop	0.8
Universität Zürich Irchel	Rooftop	0.8
Güterbahnhof	Rooftop	0.9
Bankenviertel Bleicherweg	Rooftop	1.0
Albisgüetli	Rooftop	1.0
Badenerstrasse Farbhof	Rooftop	1.3
Schule Milchbuck	Rooftop	1.3
Tiefenbrunnen Wildbachstrasse	Rooftop	2.2
Wollishofen	Rooftop	2.6
Limmattalstrasse Höngg	Rooftop	5.1

Table A3. Hourly CO_2 dry air mole fraction error statistics of the CO_2 sensors when undergoing parallel measurements in field conditions with a high-precision gas analyser acting as a ground truth. The three error statistics units are ppm. The air temperature and absolute humidity are the means for the testing duration. Sensors 438 and 445 suffered from poor data transmission during testing so n is significantly lower than the target of 336 hours (two weeks). The last row shows the means of the statistics.

Sensor type	Sensor ID	Sensing element ID	Air temp. ($^{\circ}\text{C}$)	Abs. hum. (g kg^{-1})	n	Mean bias	RMSE	MAE	R^2
Senseair HPP	429	3429	20.6	8.5	368	0.66	0.87	0.69	1.000
Senseair HPP	430	1430	16.8	10.9	406	-0.23	1.49	1.13	0.999
Senseair HPP	433	433	19.6	11.7	649	-0.18	0.82	0.66	1.000
Senseair HPP	434	1434	10.0	6.3	605	-0.03	0.77	0.57	1.000
Senseair HPP	436	436	19.6	11.7	636	-0.28	0.94	0.73	1.000
Senseair HPP	437	1429	13.3	8.9	339	-0.04	0.89	0.69	1.000
Senseair HPP	438	437	5.0	6.2	127	0.01	0.46	0.34	1.000
Senseair HPP	439	439	6.0	6.3	320	0.19	1.48	1.08	0.997
Senseair HPP	441	429	6.0	6.3	315	0.07	1.36	1.03	0.998
Senseair HPP	443	443	9.2	7.5	531	0.22	1.33	1.01	0.998
Senseair HPP	444	2444	9.9	6.6	655	-0.14	1.01	0.71	0.999
Senseair HPP	445	445	21.2	11.1	211	-0.45	0.83	0.69	1.000
Senseair HPP	446	2429	9.0	7.5	489	-0.20	1.03	0.80	0.999
Vaisala GMP343	450	450	21.2	10.1	531	-0.72	1.14	0.91	0.999
Vaisala GMP343	451	451	5.2	6.0	1394	-0.41	0.69	0.57	1.000
Vaisala GMP343	452	452	5.9	5.7	311	-0.67	0.94	0.80	1.000
Vaisala GMP343	4060	4060	7.0	6.4	633	-0.02	0.49	0.39	1.000
Licor LI-850	4057	4057	16.8	10.9	415	0.60	1.07	0.95	1.000
Mean			12.3	8.3	496	-0.09	0.98	0.76	0.999

Equations

The spectroscopic correction to address the sensors' water-induced response was conditionally applied to some sensor types in the following way:

$$CO_{2w} = \begin{cases} CO_{2reported} - (CO_{2reported} \cdot \beta_{CO_2} + w \cdot \beta_w) & \text{if sensor type was Senseair HPP or Licor LI-850} \\ CO_{2reported} & \text{else} \end{cases} \quad (1)$$

520 Where β_{CO_2} and β_w represent slopes of multiple linear regression models that were trained on observations during humidity tests (Section 2.3.4). The Senseair HPP sensors' reported CO_2 required transformation to standard pressure and was done using standard atmospheric pressure (atm):

$$CO_{2p} = \begin{cases} CO_{2w} \cdot \left(\frac{1013.25}{P_o}\right) & \text{if sensor type was Senseair HPP} \\ CO_{2w} & \text{if sensor type was Licor LI-850} \\ CO_{2reported} & \text{else} \end{cases} \quad (2)$$

To compute CO_2 dry air mole fractions, water partial pressure (P) was calculated with the August-Roche-Magnus equation (Alduchov and Eskridge, 1997; Lawrence, 2005) using temperature (T) and relative humidity (RH) observations from the sensors' sample stream and, in turn, the water vapour mixing ratio was calculated, and the sensors' CO_2 moist air mole fractions were transformed using observed air pressure (P_o):

$$P = \frac{RH}{100} \cdot 6.1078 \cdot \exp\left(\frac{17.08085 \cdot T}{234.175 + T}\right) \quad (3)$$

$$CO_{2dry} = \frac{CO_{2p}}{\left(1 - \frac{P}{P_o}\right)}, \quad (4)$$

530 Finally, CO_2 dry air mole fractions were calibrated with slopes ($\beta_{cylinder}$) and offsets ($\alpha_{cylinder}$) calculated from reference gas tests conducted every 25 hours:

$$CO_{2dry\,cal} = CO_{2dry} \cdot \beta_{cylinder} + \alpha_{cylinder}. \quad (5)$$

The product of these transformations was CO_2 dry air mole fractions calibrated to the WMO X2019 calibration scale (Hall et al., 2021).

535 *Data availability.* The data sources used in this work are described and the observations are available via the ICOS Cities data portal (<https://citydata.icos-cp.eu/portal>). The hourly field and intercomparison observations used for the analysis are also publicly accessible in a persistent data repository (Grange, 2024a, <https://doi.org/10.5281/zenodo.13759332>). Additional data and information are available from the authors upon reasonable request.

Author contributions. SKG conceived the research questions, conducted the data analysis, and wrote the manuscript with assistance from all authors. PR, AF, DB, CH, and LE designed the sensor network, were project managers, and contributed to data analysis activities. PR led the sensor network's installation and on-site maintenance. All authors contributed to revising and improving the manuscript.

Competing interests. The authors declare no competing interest.

Acknowledgements. This work was funded by the European Union's Horizon 2020 research and innovation programme, grant agreement number 101037319, named Pilot Applications in Urban Landscapes - towards integrated city observatories for greenhouse gases (PAUL) and is known as ICOS Cities. The project team thanks the collaborators from Umwelt- und Gesundheitsschutz Zürich (UGZ; the environmental department of Zürich city) and Swisscom for their help regarding sensor sites and installations. Decentlab GmbH is thanked for their development of sensor hardware and for developing reliable data transmission and storage infrastructure. Simone Baffelli and Lucas Fernandez Vilanova are thanked for their contributions to legacy software systems as is Nikolai Ponomarev for providing feedback on the sensors' observations. Beat Schwarzenbach and Stephan Henne are thanked for allowing easy access to three additional sites' CO_2 observations from the NABEL and [ICOS Switzerland \(ICOS-CH\)](#) monitoring networks. [ICOS-CH is supported by the Swiss National Science Foundation \(grant 20F120_198227\)](#). Stephan Henne is thanked for a second time for his running of the FLEXPART footprints. The sensor network maintenance was only possible with the help of civil servants (*Zivis*) when the network was in operation. The *Zivis* were Wisnu Lang, Simon Rohrbach, Davide Bernasconi, Hannes Wäckerlig, Michael Kovac, Josua Stoffel, Urban Brunner, Ulysse Schaller, Leonardo Beltrami (not a civil servant but a visiting student), Stefan Lampart, Yann von der Weid, Jan Krummenacher, and Quirin Beck; many thanks for your contributions. Finally, the two other ICOS Cities sensor network groups in Munich and Paris are thanked for their fruitful collaboration.

References

- Alduchov, O. A. and Eskridge, R. E.: Improved Magnus' form approximation of saturation vapor pressure, <https://doi.org/https://doi.org/10.2172/548871>, OSTI ID: 548871, 1997.
- Arzoumanian, E., Vogel, F. R., Bastos, A., Gaynullin, B., Laurent, O., Ramonet, M., and Ciais, P.: Characterization of a commercial lower-cost
560 medium-precision non-dispersive infrared sensor for atmospheric CO₂ monitoring in urban areas, *Atmospheric Measurement Techniques*, 12, 2665–2677, <https://doi.org/10.5194/amt-12-2665-2019>, 2019.
- Bart, M., Williams, D., Ainslie, B., Ian McKendry, Salmond, J., Grange, S., Maryam Alavi Shoshtari, Steyn, D., and Henshaw, G.: High Density Ozone Monitoring using Gas Sensitive Semi-Conductor Sensors in the Lower Fraser Valley, British Columbia, *Environmental Science & Technology*, 48, 3970–3977, <https://doi.org/10.1021/es404610t>, 2014.
- 565 Beck, H. E., Zimmermann, N. E., McVicar, T. R., Vergopolan, N., Berg, A., and Wood, E. F.: Present and future Köppen-Geiger climate classification maps at 1-km resolution, *Scientific Data*, 5, 180 214, <https://doi.org/10.1038/sdata.2018.214>, 2018.
- Berchet, A., Zink, K., Oetl, D., Brunner, J., Emmenegger, L., and Brunner, D.: Evaluation of high-resolution GRAMM–GRAL (v15.12/v14.8) NO_x simulations over the city of Zürich, Switzerland, *Geoscientific Model Development*, 10, 3441–3459, <https://doi.org/10.5194/gmd-10-3441-2017>, 2017.
- 570 Briber, B. M., Hutyra, L. R., Dunn, A. L., Raciti, S. M., and Munger, J. W.: Variations in Atmospheric CO₂ Mixing Ratios across a Boston, MA Urban to Rural Gradient, *Land*, 2, 304–327, <https://doi.org/10.3390/land2030304>, 2013.
- Casey, J. G. and Hannigan, M. P.: Testing the performance of field calibration techniques for low-cost gas sensors in new deployment locations: across a county line and across Colorado, *Atmospheric Measurement Techniques*, 11, 6351–6378, <https://doi.org/10.5194/amt-11-6351-2018>, 2018.
- 575 Crawford, B. and Christen, A.: Spatial variability of carbon dioxide in the urban canopy layer and implications for flux measurements, *Atmospheric Environment*, 98, 308–322, <http://www.sciencedirect.com/science/article/pii/S1352231014006542>, 2014.
- Davis, K. J., Deng, A., Lauvaux, T., Miles, N. L., Richardson, S. J., Sarmiento, D. P., Gurney, K. R., Hardesty, R. M., Bonin, T. A., Brewer, W. A., Lamb, B. K., Shepson, P. B., Harvey, R. M., Cambaliza, M. O., Sweeney, C., Turnbull, J. C., Whetstone, J., and Karion, A.: The Indianapolis Flux Experiment (INFLUX): A test-bed for developing urban greenhouse gas emission measurements, *Elementa: Science of the Anthropocene*, 5, 21, <https://doi.org/10.1525/elementa.188>, 2017.
- 580 Davis, K. J., Browell, E. V., Feng, S., Lauvaux, T., Obland, M. D., Pal, S., Baier, B. C., Baker, D. F., Baker, I. T., Barkley, Z. R., Bowman, K. W., Cui, Y. Y., Denning, A. S., DiGangi, J. P., Dobler, J. T., Fried, A., Gerken, T., Keller, K., Lin, B., Nehrir, A. R., Normile, C. P., O'Dell, C. W., Ott, L. E., Roiger, A., Schuh, A. E., Sweeney, C., Wei, Y., Weir, B., Xue, M., and Williams, C. A.: The Atmospheric Carbon and Transport (ACT)-America Mission, *Bulletin of the American Meteorological Society*, 102, E1714 – E1734, <https://doi.org/https://doi.org/10.1175/BAMS-D-20-0300.1>, 2021.
- 585 Decentlab GmbH: Decentlab Data Access User Guide, <https://docs.decentlab.com/decentlab-data-access/v8/>, 2022.
- Delaria, E. R., Kim, J., Fitzmaurice, H. L., Newman, C., Wooldridge, P. J., Worthington, K., and Cohen, R. C.: The Berkeley Environmental Air-quality and CO₂ Network: field calibrations of sensor temperature dependence and assessment of network scale CO₂ accuracy, *Atmospheric Measurement Techniques*, 14, 5487–5500, <https://doi.org/10.5194/amt-14-5487-2021>, 2021.
- 590 Denning, A. S., Takahashi, T., and Friedlingstein, P.: Can a strong atmospheric CO₂ rectifier effect be reconciled with a “reasonable” carbon budget?, *Tellus B*, 51, 249–253, <https://doi.org/https://doi.org/10.1034/j.1600-0889.1999.t01-1-00010.x>, 1999.

- El Yazidi, A., Ramonet, M., Ciais, P., Broquet, G., Pison, I., Abbaris, A., Brunner, D., Conil, S., Delmotte, M., Gheusi, F., Guerin, F., Hazan, L., Kachroudi, N., Kouvarakis, G., Mihalopoulos, N., Rivier, L., and Serça, D.: Identification of spikes associated with local sources in continuous time series of atmospheric CO, CO₂ and CH₄, *Atmospheric Measurement Techniques*, 11, 1599–1614, <https://doi.org/10.5194/amt-11-1599-2018>, 2018.
- Emmenegger, L., Leuenberger, M., and Steinbacher, M.: ICOS ATC CO₂ Release, Jungfraujoch (13.9 m), 2016-12-12–2023-03-31, <https://hdl.handle.net/11676/G1YsR1DxkD-DaG3R6bgyHvom>, 2023.
- Emmenegger, L., Leuenberger, M., and Steinbacher, M.: ICOS ATC NRT CO₂ growing time series, Jungfraujoch (13.9 m), 2023-04-01, <https://hdl.handle.net/11676/Tx80un9N4jzNzdOp4VqsYHPr>, 2024.
- Empa: Carbosense – Swiss Low Power Network For Carbon Dioxide Sensing, <http://carbosense.wikidot.com/main:project>, 2019.
- Empa: Technischer Bericht zum Nationalen Beobachtungsnetz für Luftfremdstoffe (NABEL) 2024, https://www.empa.ch/documents/56101/246436/Technischer_Bericht_2024/0d7b63e5-70a1-4fba-ad3a-599347447a32, prepared for BAFU, 2024.
- Federal Office for the Environment (FOEN): Switzerland’s greenhouse gas inventory, <https://www.bafu.admin.ch/bafu/en/home/topics/climate/state/data/greenhouse-gas-inventory.html>, 11.04.2023, 2023.
- Fiore, A. M., Naik, V., and Leibensperger, E. M.: Air Quality and Climate Connections, *Journal of the Air & Waste Management Association*, 65, 645–685, <https://doi.org/10.1080/10962247.2015.1040526>, 2015.
- Grange, S. K.: **smonitor**: A Framework and a Collection of Functions to Allow for Maintenance of Air Quality Monitoring Data, <https://github.com/skgrange/smonitor>, 2018.
- Grange, S. K.: Development of Data Analytic Approaches for Air Quality Data, Ph.D. thesis, Chemistry, The University of York, <http://etheses.whiterose.ac.uk/23306>, 2019a.
- Grange, S. K.: **saqgetr**: Import Air Quality Monitoring Data in a Fast and Easy Way, <https://cran.r-project.org/web/packages/saqgetr/index.html>, r package, 2019b.
- Grange, S. K.: Data for publication “The ZICOS-M CO₂ sensor network: measurement performance and CO₂ variability across Zürich”, <https://doi.org/10.5281/zenodo.13759332>, 2024a.
- Grange, S. K.: **decentlabr**: An R Interface to the Decentlab API, <https://github.com/skgrange/decentlabr>, R package, 2024b.
- Grange, S. K., Lewis, A. C., Moller, S. J., and Carslaw, D. C.: Lower vehicular primary emissions of NO₂ in Europe than assumed in policy projections, *Nature Geoscience*, 10, 914–918, <https://doi.org/10.1038/s41561-017-0009-0>, 2017.
- Hall, B. D., Crotwell, A. M., Kitzis, D. R., Mefford, T., Miller, B. R., Schibig, M. F., and Tans, P. P.: Revision of the World Meteorological Organization Global Atmosphere Watch (WMO/GAW) CO₂ calibration scale, *Atmospheric Measurement Techniques*, 14, 3015–3032, <https://doi.org/10.5194/amt-14-3015-2021>, 2021.
- Hernández-Paniagua, I. Y., Lowry, D., Clemittshaw, K. C., Fisher, R. E., France, J. L., Lanoisellé, M., Ramonet, M., and Nisbet, E. G.: Diurnal, seasonal, and annual trends in atmospheric CO₂ at southwest London during 2000–2012: Wind sector analysis and comparison with Mace Head, Ireland, *Atmospheric Environment*, 105, 138–147, <https://doi.org/https://doi.org/10.1016/j.atmosenv.2015.01.021>, 2015.
- Hurwitz, M. D., Ricciuto, D. M., Bakwin, P. S., Davis, K. J., Wang, W., Yi, C., and Butler, M. P.: Transport of Carbon Dioxide in the Presence of Storm Systems over a Northern Wisconsin Forest, *Journal of the Atmospheric Sciences*, 61, 607 – 618, [https://doi.org/https://doi.org/10.1175/1520-0469\(2004\)061<0607:TOCDIT>2.0.CO;2](https://doi.org/https://doi.org/10.1175/1520-0469(2004)061<0607:TOCDIT>2.0.CO;2), 2004.
- International Monetary Fund: World Economic Outlook (WEO) database, <https://www.imf.org/en/Publications/WEO/weo-database/2023/October/download-entire-database>, October 2023 Edition, 2023.

- IPCC: Synthesis Report of the IPCC Sixth Assessment Report (AR6), <https://www.ipcc.ch/report/sixth-assessment-report-cycle/>, IPCC AR6
630 SYR, 2023.
- Karion, A., Callahan, W., Stock, M., Prinzivalli, S., Verhulst, K. R., Kim, J., Salameh, P. K., Lopez-Coto, I., and Whetstone, J.: Greenhouse gas observations from the Northeast Corridor tower network, *Earth System Science Data*, 12, 699–717, <https://doi.org/10.5194/essd-12-699-2020>, 2020.
- Kim, J., Shusterman, A. A., Lieschke, K. J., Newman, C., and Cohen, R. C.: The BERkeley Atmospheric CO₂ Observation Network: field calibration and evaluation of low-cost air quality sensors, *Atmospheric Measurement Techniques*, 11, 1937–1946, <https://doi.org/10.5194/amt-11-1937-2018>, 2018.
635
- Klose, R.: Carbosense 4D – High-res CO₂ observation over Switzerland, <https://www.empa.ch/web/s604/carbosense4d>, Dec 7, 2017, 2017.
- Kunz, M., Lavric, J. V., Gerbig, C., Tans, P., Neff, D., Hummelgård, C., Martin, H., Rödjegård, H., Wrenger, B., and Heimann, M.: COCAP: a carbon dioxide analyser for small unmanned aircraft systems, *Atmospheric Measurement Techniques*, 11, 1833–1849,
640 <https://doi.org/10.5194/amt-11-1833-2018>, 2018.
- Lawrence, M. G.: The Relationship between Relative Humidity and the Dewpoint Temperature in Moist Air: A Simple Conversion and Applications, *Bulletin of the American Meteorological Society*, 86, 225–233, <https://doi.org/10.1175/BAMS-86-2-225>, 2005.
- LI-COR Biosciences: LI-830 and LI-850 Gas Analyzers. For Continuous Monitoring Applications, <https://www.licor.com/documents/tl6v2vsim8y6wpqcilkxm38zimjboea>, 2018.
- 645 LI-COR Biosciences: The Importance of Water Vapor Measurements and Corrections, <https://www.licor.com/env/support/TechTips/irg4110-h2o-measurement.html>, IRG4-110. 02/2023, 2023.
- Lian, J., Laurent, O., Chariot, M., Lienhardt, L., Ramonet, M., Utard, H., Lauvaux, T., Bréon, F.-M., Broquet, G., Cucchi, K., Millair, L., and Ciais, P.: Development and deployment of a mid-cost CO₂ sensor monitoring network to support atmospheric inverse modeling for quantifying urban CO₂ emissions in Paris, *Atmospheric Measurement Techniques*, 17, 5821–5839, <https://doi.org/10.5194/amt-17-5821-2024>, 2024.
650
- LoRa® Alliance: LoRaWAN™—What is it?, a technical overview of LoRa® and LoRaWAN™. Technical Marketing Workgroup 1.0, 2015.
- Lwasa, S., Seto, K. C., Bai, X., Blanco, H., Gurney, K. R., Kılıç, Ş., Lucon, O., Murakami, J., Pan, J., Sharifi, A., and Yamagata, Y.: Chapter 8: Urban systems and other settlements, in: IPCC, 2022: Climate Change 2022: Mitigation of Climate Change. Contribution of Working Group III to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change, edited by Shukla, P. R., Skea, J., Slade, R., Khourdajie, A. A., van Diemen, R., McCollum, D., Pathak, M., Some, S., Vyas, P., Fradera, R., Belkacemi, M., Hasija, A., Lisboa, G., Luz, S., and Malley, J., Cambridge University Press, Cambridge, UK and New York, NY, USA, <https://doi.org/10.1017/9781009157926.010>, 2022.
- Maag, B., Zhou, Z., and Thiele, L.: A Survey on Sensor Calibration in Air Pollution Monitoring Deployments, *IEEE Internet of Things Journal*, 5, 4857–4870, <https://doi.org/10.1109/JIOT.2018.2853660>, 2018.
- 660 Mao, X., Miao, X., He, Y., Li, X.-Y., and Liu, Y.: CitySee: Urban CO₂ monitoring with sensors, in: 2012 Proceedings IEEE INFOCOM, pp. 1611–1619, <https://doi.org/10.1109/INFCOM.2012.6195530>, 2012.
- Martin, C. R., Zeng, N., Karion, A., Dickerson, R. R., Ren, X., Turpie, B. N., and Weber, K. J.: Evaluation and environmental correction of ambient CO₂ measurements from a low-cost NDIR sensor, *Atmospheric Measurement Techniques*, 10, 2383–2395, <https://doi.org/10.5194/amt-10-2383-2017>, 2017.
- 665 McDermitt, D. K., Welles, J. M., and Eckles, R. D.: Effects of Temperature, Pressure and Water Vapor on Gas Phase Infrared Absorption by CO₂, https://www.licor.com/env/pdf/photosynthesis/co2_abs.pdf, LI-COR, Inc., 1993.

- MeteoSwiss: Accessing Data with IDAWEB, https://www.meteoswiss.admin.ch/dam/jcr:f79051a0-9240-4a5c-b42c-9fe1b916f655/E_idaweb_order_examples.pdf, Bundesamt für Meteorologie und Klimatologie, 2009.
- Müller, M., Graf, P., Meyer, J., Pentina, A., Brunner, D., Perez-Cruz, F., Hüglin, C., and Emmenegger, L.: Integration and calibration of non-dispersive infrared (NDIR) CO₂ low-cost sensors and their operation in a sensor network covering Switzerland, *Atmospheric Measurement Techniques*, 13, 3815–3834, <https://doi.org/10.5194/amt-13-3815-2020>, 2020.
- Oney, B., Henne, S., Gruber, N., Leuenberger, M., Bamberger, I., Eugster, W., and Brunner, D.: The CarboCount CH sites: characterization of a dense greenhouse gas observation network, *Atmospheric Chemistry and Physics*, 15, 11 147–11 164, <https://doi.org/10.5194/acp-15-11147-2015>, 2015.
- 675 Pal, S., Davis, K. J., Lauvaux, T., Browell, E. V., Gaudet, B. J., Stauffer, D. R., Obland, M. D., Choi, Y., DiGangi, J. P., Feng, S., Lin, B., Miles, N. L., Pauly, R. M., Richardson, S. J., and Zhang, F.: Observations of Greenhouse Gas Changes Across Summer Frontal Boundaries in the Eastern United States, *Journal of Geophysical Research: Atmospheres*, 125, e2019JD030 526, <https://doi.org/10.1029/2019JD030526>, 2020.
- Pearson, R. K., Neuvo, Y., Astola, J., and Gabbouj, M.: Generalized Hampel Filters, *EURASIP Journal on Advances in Signal Processing*, 2016, 87, <https://doi.org/10.1186/s13634-016-0383-6>, 2016.
- 680 Peltier, R. E., Castell, N., Clements, A. L., Dye, T., Hüglin, C., Kroll, J. H., Lung, S.-C. C., Ning, Z., Parsons, M., Penza, M., Reisen, F., and von Schneidmesser, E.: An Update on Low-cost Sensors for the Measurement of Atmospheric Composition, December 2020, World Meteorological Organization (WMO), WMO-No. 1215 edn., https://library.wmo.int/index.php?lvl=notice_display&id=21508#.YwTDbtLMKuA, 2021.
- 685 Peters, D. R., Popoola, O. A. M., Jones, R. L., Martin, N. A., Mills, J., Fonseca, E. R., Stidworthy, A., Forsyth, E., Carruthers, D., Dupuy-Todd, M., Douglas, F., Moore, K., Shah, R. U., Padilla, L. E., and Alvarez, R. A.: Evaluating uncertainty in sensor networks for urban air pollution insights, *Atmospheric Measurement Techniques*, 15, 321–334, <https://doi.org/10.5194/amt-15-321-2022>, 2022.
- Pieber, S. M., Tuzson, B., Henne, S., Karstens, U., Gerbig, C., Koch, F.-T., Brunner, D., Steinbacher, M., and Emmenegger, L.: Analysis of regional CO₂ contributions at the high Alpine observatory Jungfraujoch by means of atmospheric transport simulations and $\delta^{13}\text{C}$, *Atmospheric Chemistry and Physics*, 22, 10 721–10 749, <https://doi.org/10.5194/acp-22-10721-2022>, 2022.
- 690 Pisso, I., Sollum, E., Grythe, H., Kristiansen, N. I., Cassiani, M., Eckhardt, S., Arnold, D., Morton, D., Thompson, R. L., Groot Zwaafink, C. D., Evangeliou, N., Sodemann, H., Haimberger, L., Henne, S., Brunner, D., Burkhardt, J. F., Fouilloux, A., Brioude, J., Philipp, A., Seibert, P., and Stohl, A.: The Lagrangian particle dispersion model FLEXPART version 10.4, *Geoscientific Model Development*, 12, 4955–4997, <https://doi.org/10.5194/gmd-12-4955-2019>, 2019.
- 695 PostgreSQL Global Development Group: PostgreSQL: Version 16, <https://www.postgresql.org/>.
- R Core Team: R: A Language and Environment for Statistical Computing, R Foundation for Statistical Computing, Vienna, Austria, <https://www.R-project.org/>, 2023.
- Rella, C.: Accurate Greenhouse Gas Measurements in Humid Gas Streams Using the Picarro G1301 Carbon Dioxide / Methane / Water Vapor Gas Analyzer, Picarro, Inc. White Paper, 2010.
- 700 Rella, C. W., Chen, H., Andrews, A. E., Filges, A., Gerbig, C., Hatakka, J., Karion, A., Miles, N. L., Richardson, S. J., Steinbacher, M., Sweeney, C., Wastine, B., and Zellweger, C.: High accuracy measurements of dry mole fractions of carbon dioxide and methane in humid air, *Atmospheric Measurement Techniques*, 6, 837–860, <https://doi.org/10.5194/amt-6-837-2013>, 2013.
- Ritchie, H., Roser, M., and Rosado, P.: CO₂ and Greenhouse Gas Emissions, <https://ourworldindata.org/co2-and-greenhouse-gas-emissions>, our World in Data, 2020.

- 705 Schneider, P., Bartonova, A., Castell, N., Dauge, F. R., Gerboles, M., Hagler, G. S. W., Hüglin, C., Jones, R. L., Khan, S., Lewis, A. C., Mijling, B., Müller, M., Penza, M., Spinelle, L., Stacey, B., Vogt, M., Wesseling, J., and Williams, R. W.: Toward a Unified Terminology of Processing Levels for Low-Cost Air-Quality Sensors, *Environmental Science & Technology*, 53, 8485–8487, <https://doi.org/10.1021/acs.est.9b03950>, 2019.
- Schröter, J., Rieger, D., Stassen, C., Vogel, H., Weimer, M., Werchner, S., Förstner, J., Prill, F., Reinert, D., Zängl, G., Giorgetta, M., Ruhnke, R., Vogel, B., and Braesicke, P.: ICON-ART 2.1: a flexible tracer framework and its application for composition studies in numerical weather forecasting and climate simulations, *Geoscientific Model Development*, 11, 4043–4068, <https://doi.org/10.5194/gmd-11-4043-2018>, 2018.
- Senseair: Application Note – Reading data from and writing parameters to HPP_CO₂, high resolution CO₂ sensor on HPP platform for environmental monitoring., 2016.
- 715 Senseair: Senseair LP8 CO₂ sensor module for integration into battery-powered applications. Sensor specification and integration guideline, document TDE2712. Revision 7, 2018.
- Shi, T., Ma, X., Han, G., Xu, H., Qiu, R., He, B., and Gong, W.: Measurement of CO₂ rectifier effect during summer and winter using ground-based differential absorption LiDAR, *Atmospheric Environment*, 220, 117097, <https://doi.org/https://doi.org/10.1016/j.atmosenv.2019.117097>, 2020.
- 720 Shusterman, A. A., Teige, V. E., Turner, A. J., Newman, C., Kim, J., and Cohen, R. C.: The BERkeley Atmospheric CO₂ Observation Network: initial evaluation, *Atmospheric Chemistry and Physics*, 16, 13 449–13 463, <https://doi.org/10.5194/acp-16-13449-2016>, 2016.
- Shusterman, A. A., Kim, J., Lieschke, K. J., Newman, C., Wooldridge, P. J., and Cohen, R. C.: Observing local CO₂ sources using low-cost, near-surface urban monitors, *Atmospheric Chemistry and Physics*, 18, 13 773–13 785, <https://doi.org/10.5194/acp-18-13773-2018>, 2018.
- Stadt Zürich: Über Zürich, https://www.stadt-zuerich.ch/portal/de/index/portraet_der_stadt_zuerich.html, data from 13 April 2022, 2023a.
- 725 Stadt Zürich: Klimaschutzziel Netto-Null, https://www.stadt-zuerich.ch/gud/de/index/departement/strategie_politik/umweltstrategie/klimapolitik/netto-null.html, 2023b.
- Stadt Zürich: Emissionskataster, https://www.stadt-zuerich.ch/gud/de/index/umwelt_energie/luftqualitaet/schadstoffquellen/emissionskataster.html, Reporting year 2022, 2024.
- Stagakis, S., Vogt, R., Hashemi, J., Hillard, R., and Christen, A.: Hardau II site description, IRGASON and meteorology metadata, ICOS Cities. PAUL Pilot Applications in Urban Landscapes. WP3: Observations. Task 3.4: Eddy Covariance flux observations., 2023.
- Steiner, M., Peters, W., Luijkx, I., Henne, S., Chen, H., Hammer, S., and Brunner, D.: European CH₄ inversions with ICON-ART coupled to the CarbonTracker Data Assimilation Shell, *Atmospheric Chemistry and Physics*, 24, 2759–2782, <https://doi.org/10.5194/acp-24-2759-2024>, 2024.
- Stephens, B. B., Gurney, K. R., Tans, P. P., Sweeney, C., Peters, W., Bruhwiler, L., Ciais, P., Ramonet, M., Bousquet, P., Nakazawa, T., Aoki, S., Machida, T., Inoue, G., Vinnichenko, N., Lloyd, J., Jordan, A., Heimann, M., Shibistova, O., Langenfelds, R. L., Steele, L. P., Francey, R. J., and Denning, A. S.: Weak northern and strong tropical land carbon uptake from vertical profiles of atmospheric CO₂, *Science*, 316, 1732–5, <https://doi.org/10.1126/science.1137004>, 2007.
- 735 Sturm, P., Tuzson, B., Henne, S., and Emmenegger, L.: Tracking isotopic signatures of CO₂ at the high altitude site Jungfraujoch with laser spectroscopy: analytical improvements and representative results, *Atmospheric Measurement Techniques*, 6, 1659–1671, <https://doi.org/10.5194/amt-6-1659-2013>, 2013.
- 740 Tans, P. and Thoning, K.: How we measure background CO₂ levels on Mauna Loa, https://gml.noaa.gov/ccgg/about/co2_measurements.html, NOAA Global Monitoring Laboratory, 2020.

- The Royal Society: Effects of net-zero policies and climate change on air quality, <https://royalsociety.org/topics-policy/projects/air-quality-climate-change>, 2021.
- 745 Turnbull, J. C., Sweeney, C., Karion, A., Newberger, T., Lehman, S. J., Tans, P. P., Davis, K. J., Lauvaux, T., Miles, N. L., Richardson, S. J., Cambaliza, M. O., Shepson, P. B., Gurney, K., Patarasuk, R., and Razlivanov, I.: Toward quantification and source sector identification of fossil fuel CO₂ emissions from an urban area: Results from the INFLUX experiment, *Journal of Geophysical Research: Atmospheres*, 120, 292–312, <https://doi.org/https://doi.org/10.1002/2014JD022555>, 2015.
- Turner, A. J., Shusterman, A. A., McDonald, B. C., Teige, V., Harley, R. A., and Cohen, R. C.: Network design for quantifying urban
750 CO₂ emissions: assessing trade-offs between precision and network density, *Atmospheric Chemistry and Physics*, 16, 13465–13475, <https://doi.org/10.5194/acp-16-13465-2016>, 2016.
- Vaisala: Vaisala CARBOCAP® Carbon Dioxide Probe GMP343, <https://www.vaisala.com/en/products/instruments-sensors-and-other-measurement-devices/instruments-industrial-measurements/gmp343>, User's Guide. M210514EN-E, 2013.
- 755 Verhulst, K. R., Karion, A., Kim, J., Salameh, P. K., Keeling, R. F., Newman, S., Miller, J., Sloop, C., Pongetti, T., Rao, P., Wong, C., Hopkins, F. M., Yadav, V., Weiss, R. F., Duren, R. M., and Miller, C. E.: Carbon dioxide and methane measurements from the Los Angeles Megacity Carbon Project – Part 1: calibration, urban enhancements, and uncertainty estimates, *Atmospheric Chemistry and Physics*, 17, 8313–8341, <https://doi.org/10.5194/acp-17-8313-2017>, 2017.
- Vogt, R., Christen, A., Rotach, M. W., Roth, M., and Satyanarayana, A. N. V.: Temporal dynamics of CO₂ fluxes and profiles over a Central
760 European city, *Theoretical and Applied Climatology*, 84, 117–126, <https://doi.org/10.1007/s00704-005-0149-9>, 2006.
- West, J. J., Smith, S. J., Silva, R. A., Naik, V., Zhang, Y., Adelman, Z., Fry, M. M., Anenberg, S., Horowitz, L. W., and Lamarque, J.-F.: Co-benefits of mitigating global greenhouse gas emissions for future air quality and human health, *Nature Climate Change*, 3, 885–889, <https://doi.org/10.1038/nclimate2009>, 2013.
- World Meteorological Organization: 17th WMO/IAEA Meeting on Carbon Dioxide, Other Greenhouse Gases and Related Tracers Measure-
765 ment Techniques (GGMT-2013, <https://library.wmo.int/idurl/4/51479>, GAW Report No. 213, 2014.
- Wu, Z., Pang, X., Xing, B., Shang, Q., Wu, H., Lu, Y., Wu, H., Lyu, Y., Li, J., Wang, B., Ding, S., Chen, D., and Chen, J.: Development of a Portable and Sensitive CO₂ Measurement Device with NDIR Sensor Clusters and Minimizing Water Vapor Impact, *Sustainability*, 15, <https://doi.org/10.3390/su15021533>, 2023.
- 770 Xueref-Remy, I., Milne, M., Zoghbi, N., Lelandais, L., Riandet, A., Armengaud, A., Gille, G., Lanzi, L., Oppo, S., Brégonzio-Rozier, L., Blanc, P.-E., Yohia, C., Piazzola, J., and Delmotte, M.: Analysis of atmospheric CO₂ variability in the Marseille city area and the north-west Mediterranean basin at different time scales, *Atmospheric Environment: X*, 17, 100208, <https://doi.org/https://doi.org/10.1016/j.aeoa.2023.100208>, 2023.
- Zellweger, C., Emmenegger, L., Firdaus, M., Hatakka, J., Heimann, M., Kozlova, E., Spain, T. G., Steinbacher, M., van der Schoot, M. V., and Buchmann, B.: Assessment of recent advances in measurement techniques for atmospheric carbon dioxide and methane observations,
775 *Atmospheric Measurement Techniques*, 9, 4737–4757, <https://doi.org/10.5194/amt-9-4737-2016>, 2016.
- Zubler, E. M., Scherrer, S. C., Croci-Maspoli, M., Liniger, M. A., and Appenzeller, C.: Key climate indices in Switzerland; expected changes in a future climate, *Climatic Change*, 123, 255–271, <https://doi.org/10.1007/s10584-013-1041-8>, 2014.