

Multi-objective calibration and evaluation of the ORCHIDEE land surface model over France at high resolution

Peng Huang¹, Agnès Ducharne¹, Lucia Rinchioso¹, Jan Polcher², Laure Baratgin², Vladislav Bastrikov³, and Eric Sauquet⁴

¹Sorbonne Université/CNRS/EPHE, METIS-IPSL, Paris, France

²CNRS/Sorbonne Université/École Polytechnique, LMD-IPSL, Palaiseau, France

³Science Partners, Paris, France

⁴INRAE, UR RiverLy, Villeurbanne, France

Correspondence: Peng Huang (peng.huang@sorbonne-universite.fr)

Abstract. We present here a strategy to obtain a reliable hydrological simulation over France with the ORCHIDEE land surface model. The model is forced by the Safran atmospheric reanalysis at 8-km resolution and hourly time steps from 1959 to 2020, and by a high-resolution DEM (around 1.3 km in France). Each Safran grid cell is decomposed into a graph of hydrological transfer units (HTUs) based on the higher resolution DEM to better describe lateral water movements. In particular, it is possible to accurately locate 3507 stations among the 4081 stations collected from the national hydrometric network HydroPortail (filtered to drain an upstream area larger than 64 km²). A simple trial-and-error calibration is conducted by modifying selected parameters of ORCHIDEE to reduce the biases of the simulated water budget compared to the evapotranspiration products (the GLEAM and FLUXCOM datasets) and the HydroPortail observations of river discharge. The simulation that is eventually preferred is extensively assessed with classic goodness-of-fit indicators complemented by trend analysis at 1785 stations (filtered to have records for at least 8 entire years) across France. For example, the median bias of evapotranspiration is -0.5% against GLEAM (-4.3% against FLUXCOM), the median bias of river discharge is 6.3%, and the median KGE of square-rooted river discharge is 0.59. These indicators, however, exhibit a large spatial variability, with poor performance in the Alps and the Seine sedimentary basin. The spatial contrasts and temporal trends of river discharge across France are well represented with an accuracy of 76.4% for the trend sign and an accuracy of 62.7% for the trend significance. Although it does not yet integrate human impacts on river basins, the selected parameterization of ORCHIDEE offers a reliable historical overview of water resources and a robust configuration for climate change impact analysis at the nationwide scale of France.

1 Introduction

1.1 Land surface models for high-resolution hydrological simulations

Land surface models (LSMs) are the land surface components of Earth system models (ESMs) and simulate water, energy and carbon fluxes across continents. The offline use of LSMs as independent physically-based distributed hydrological models has

emerged in the recent decades for evaluating water resources and investigating climate change impacts at both regional and global scales (e.g., Cai et al., 2014; Pokhrel et al., 2021; Telteu et al., 2021).

Since LSMs provide the lower boundary to atmosphere circulation in ESMs, the spatial discretization of LSMs is usually consistent with the atmospheric component or atmospheric forcing (in offline mode) so that spatial discontinuity can be averted during land-atmosphere coupling. However, the spatial resolution of the atmosphere component, typically 0.5° (IPCC, 2023), or the atmospheric forcing, typically tens of kilometres (e.g., EuroCORDEX at 11 km in Jacob et al. 2014 and ERA-5 at 31 km in Hersbach et al. 2020), are too coarse to represent topographic details. In addition, river flows are much more constrained by topographic conditions than by the atmosphere. Thus, accurate hydrological simulations for flood risk assessment, drought monitoring and human impact assessment (e.g., dam regulation and irrigation) are difficult to achieve, especially for local-scale implementations. Hence, incorporating high-resolution river routing systems in LSMs is necessary to improve hydrological simulations by better characterizing the morphological conditions of river basins with high-resolution digital elevation models (DEMs) (Bierkens et al., 2015).

The conventional approach to computing river basin discharges relies on independent runoff routing models (RRMs) that interpolate the lateral water flows simulated by the LSM to the grid cells of the RRM and cascade river discharges along the drainage network. The RRM represents the horizontal movements of water fluxes while their vertical movements are kept in LSMs. There are many different RRM in the literature, such as the TRIP at 0.5° resolution (Oki and Sud, 1998; Oki et al., 1999; Vergnes and Decharme, 2012), the RiTHM at 0.25° resolution (Ducharne et al., 2003), and the HYDRA at $5'$ resolution (Coe, 2000). To bridge the gap between high-resolution hydrological simulations and coarse LSM grid cells, the concept of constructing hydrological transfer units (HTUs) in LSM grid cells with high-resolution DEMs was proposed to better represent natural river systems (Nguyen-Quang et al., 2018; Polcher et al., 2023). These hydrologically consistent units within each atmospheric grid cell are connected to horizontally transfer the simulated lateral flows so that the generated river flows in one atmospheric grid cell can flow into neighbouring grid cells (HTU to HTU and then grid cell to grid cell) (Polcher et al., 2023). The vertical and horizontal movements of water fluxes can be maintained within the LSM instead of separating these two movements by two models (i.e., LSMs and RRM) at different resolutions, which facilitates the representation of human impacts on hydrological processes (Zhou et al., 2021; Baratgin et al., 2024).

1.2 How to calibrate land surface models?

When using LSMs to simulate realistic water fluxes, including river discharge, a calibration step is often necessary: even if LSMs are designed to be as physical as possible, they inevitably contain parameters that are hard to measure directly, such as vegetation water stress (Ruiz-Vásquez et al., 2023), or soil properties at different depths (Yang et al., 2016). Traditional hydrologic calibration is primarily conducted against river discharge observations (e.g., Troy et al., 2008; Gou et al., 2020; Cho and Kim, 2022; Rummler et al., 2022), which is considered to be a well-suited benchmark (Prentice et al., 2015). However, calibrating physically-based LSMs to discharge alone does not guarantee the realistic representation of hydrological processes and the accurate simulation of other LSM outputs, such as soil moisture (Sutanudjaja et al., 2014) and evapotranspiration (Rajib et al., 2018a, b). Over the recent decades, the advancement of reanalysis and remote-sensing data quality at fine scales, such as snow

55 cover (Hall et al., 2002), evapotranspiration (Martens et al., 2017) and soil moisture (Dorigo et al., 2017) products, provides new opportunities to investigate and improve the effectiveness of LSMs in representing water fluxes. Multi-objective calibration works that combine discharge observations with these data products have shown an overall improvement on hydrological simulation performance (e.g., López López et al., 2017; Jiang et al., 2020; Yang et al., 2021).

The complexity of LSMs makes their calibration extremely difficult in practice because their large number of parameters
60 induces high degrees of freedom (Fisher and Koven, 2020). Two kinds of methods are mostly used to adjust the parameter set of LSMs: automatic (i.e., optimization techniques) and manual (i.e., trial-and-error procedure). Numerous efforts have been put into optimization algorithms (e.g., Müller et al., 2015; Yang et al., 2021; Cheng et al., 2023), with the major challenge being the computational burden, especially for high-resolution applications (Bierkens et al., 2015; Sun et al., 2020). Another limitation of the automatic calibration method, especially if applied to large parameter sets, stems from the equifinality issue that many
65 different parameter sets lead to equally good results (Beven, 2006; Fisher and Koven, 2020). In manual calibration practice, modelers select a few parameter sets, apply them to run the LSM, and choose the best parameter set based on evaluations. Albeit highly dependant on expert judgement, this method can be efficient in saving model run time compared to the hundreds of model runs required by automatic methods (Schaperow et al., 2021). Either way, a perfect calibration is always impossible to achieve due to inherent uncertainties in forcing data (e.g., Gelati et al., 2018; Kabir et al., 2022), benchmark observations
70 (e.g., Zeng and Cai, 2018) and model structure (e.g., van Kempen et al., 2021).

1.3 How to evaluate the performance of land surface models?

Hydrological model performance is typically evaluated with goodness-of-fit indicators, such as Kling-Gupta (Kling et al., 2012) or Nash-Sutcliffe (Nash and Sutcliffe, 1970) efficiencies. In doing so, discharge is often transformed for performance evaluation, such as with logarithm to emphasize on low flows (Santos et al., 2018) or with square-root to balance low/high
75 flows (Song et al., 2019). Hydrological signatures that characterize statistical or dynamic features of discharge (e.g., annual discharge and low flow duration) can also be used to evaluate simulation performance (see the review by McMillan (2021)). These traditional indicators implicitly assume stationary conditions and are no longer sufficient since "stationarity is dead" (Milly et al., 2008). As shown by Todorović et al. (2022), the traditional indicators do not guarantee the reproduction of streamflow trends with hydrological models. Thus, trend analyses are important to evaluate the robustness of hydrological
80 models over the long term, which is essential to subsequent applications for climate change assessment (Fowler et al., 2020).

1.4 Aim and novelty of the study

At the nationwide scale of France, the first distributed LSM for hydrological applications has been proposed by Habets et al. (2008). It couples the Safran atmospheric reanalysis system (Vidal et al., 2010a) and the ISBA LSM (Decharme and Douville, 2006), both at a spatial resolution of 8 km x 8 km, and the MODCOU model (Ledoux et al., 1989) for groundwater and river
85 flow, with a variable resolution down to 1 km along rivers. This model, called SIM for Safran-ISBA-MODCOU, was validated by comparison to hundreds of hydrometric stations with a focus on the Seine, Loire, Garonne, and Rhône River basins, the four major river basins in France from 1995 to 2005. Observations of piezometric head and snow depth at several sites are

also used to evaluate the SIM model. Since then, it was used to assess drought risks in the atmosphere, soils and rivers, and to investigate the impact of climate change for future adaptation at the national scale (e.g., Quintana Seguí et al., 2009; Vidal et al., 2010b; Boé et al., 2009), and recently improved to better describe the water and energy budgets in France from 1958 to 2018, providing an extensive historical analysis (Le Moigne et al., 2020).

The main goal of the present study is to obtain a reliable and robust hydrological simulation over France with another LSM, the Organising Carbon and Hydrology in Dynamic Ecosystems (ORCHIDEE) LSM, using a high-resolution HTU-based routing scheme (Nguyen-Quang et al., 2018; Polcher et al., 2023). This approach allowed us to simulate river discharge at thousands of hydrometric stations across French rivers, supporting a thorough performance evaluation. In doing so, we combined traditional indicators implicitly assuming stationary conditions, and indicators about trend accuracy because "stationarity is dead" (Milly et al., 2008). Another novelty stems from a multi-objective calibration focused on the water budget, benefiting from river discharge observations at 1785 hydrometric stations, and evapotranspiration products. The parameterization selected in this study has been used to project the impact of climate change on French water resources, which contributes to the national Explore2 project (<https://professionnels.ofb.fr/fr/node/1244>) for future adaptation design. Here, we only present the simulation results from 1959 to 2020 to assess the performance of the ORCHIDEE LSM. In section 2, the ORCHIDEE LSM is presented, followed by a summary of the input data, the benchmark datasets, and the calibration strategy. In section 3, we detail the calibration procedure that was conducted step by step to improve the overall simulated water budget and evaluate the simulation which was eventually chosen with classic goodness-of-fit measures and trend analysis; finally, a discussion and conclusions are presented.

2 Materials

2.1 The ORCHIDEE LSM

The ORCHIDEE model is a physically-based LSM developed at the Institut Pierre Simon Laplace (IPSL) as the land component of the IPSL climate model, which is used for all the past and future climate simulation exercises carried out for the IPCC reports as part of the Coupled Model Intercomparison Project (CMIP) (IPCC, 2023). Here, we use ORCHIDEE version 2.2 (with revision 7738), which is very close to the version used as the land component of the IPSL-CM6 climate model (Boucher et al., 2020; Cheruy et al., 2020). In this study, the ORCHIDEE model is not coupled to the IPSL climate model (off-line simulation) but is instead fed by an atmospheric forcing (section 2.2.1). The ORCHIDEE model couples the SECHIBA (water and energy budgets in Ducoudré et al., 1993) and STOMATE (carbon budget and phenology in Krinner et al., 2005) modules. This coupling describes the hydrological processes (e.g., soil moisture diffusion, evapotranspiration, and river discharge) and their interactions with vegetation and the carbon cycle so that the simulated variables depend on the atmospheric CO₂ concentration. The water, energy and carbon fluxes are calculated on a 30-minute time step within each atmospheric grid cell, and the river discharges are then deduced by aggregating the lateral flows of each grid cell along the river routing network. It must be noted that this version of ORCHIDEE does not include any human impact, with the exception of the presence of crops among the possible vegetation types.

The vegetation in a grid cell is not uniform but rather comprises a mosaic of several plant function types (PFTs, section 2.2.2). Table S1 summarizes the 15 PFTs used in the ORCHIDEE LSM. Each PFT is characterized by different morphological, physiological, phenological and radiative properties, mainly based on specialized literature. The root density profile of each PFT in the ORCHIDEE model is assumed to decrease exponentially with depth and is modulated by a decay factor c , as shown in Figure S9. The root density of each PFT can be increased (decreased) by decreasing (increasing) c . Crop and grass PFTs have higher c values than forest PFTs; the roots of crop and grass PFTs are concentrated in surface soil layers while the roots of forest PFTs can pass through deep soil layers.

The soil is 2 m deep, and each grid cell is characterized by the dominant soil texture (section 2.2.2). The soil water retention properties (including porosity θ_s , field capacity θ_c and wilting point θ_w) depend on the texture as detailed in Table S2. The soil hydraulic conductivity at saturation K_s is not vertically constant, as shown in Figure S5: ORCHIDEE assumes an exponential decrease with depth due to soil compaction, ruled by a decay factor f , combined with an increase towards the soil surface due to the presence of roots, which enhances infiltration capacity (de Rosnay et al., 2002; d'Orgeval et al., 2008). This effect depends on the root density profile. At each time step, soil moisture is redistributed vertically according to the Richards equation (flow in an unsaturated medium) taking into account surface boundary conditions by infiltration and soil evaporation, withdrawals by roots through the entire soil depth to supply transpiration, and gravitational drainage at the bottom of the soil (Campoy et al., 2013; Tafasca et al., 2020). For accurate computation, soil moisture and vertical water fluxes are discretized across 22 layers over 2 m, with 7 soil layers of increasing depth in the top 20 cm to capture the strong soil moisture gradients, then soil layers of constant thickness (12.5 cm) down to the soil bottom (Campoy et al., 2013). In this framework, transpiration depends on soil moisture and a factor p , which represents the soil moisture content above which transpiration is maximal, i.e., not limited by water stress. Figure S7 shows how the parameter p constrains transpiration.

Evapotranspiration (ET) is calculated as the sum of plant transpiration, evaporation of intercepted water, soil evaporation and snow sublimation. This calculation does not depend on potential evapotranspiration, but it is coupled to the surface energy balance, which requires a sub-hourly time step (here, 30 minutes) to describe the diurnal radiation cycle. The four ET fluxes in ORCHIDEE are described by a bulk aerodynamic formulation, in which the roughness length for momentum z_{0m} and for heat z_{0h} control the aerodynamic resistance. z_{0m} and z_{0h} in ORCHIDEE can be calculated by prescribed parameters: z_{0m} is calculated by a first-order approximation of vegetation height, i.e., multiplied by a factor f_z (e.g., 1/10 in Brutsaert, 2005); z_{0m}/z_{0h} is parameterized as 1 in CMIP5 to compensate for forcing errors (Dufresne et al., 2013). Note that z_{0m}/z_{0h} should be larger than 1; for example, $z_{0m}/z_{0h} = 10$ was proposed by Brutsaert (2005). z_{0m} and z_{0h} in the ORCHIDEE can also be calculated as a function of leaf area index (LAI) by the dynamic (dyn) method proposed by Su et al. (2001), as implemented in CMIP6 (Boucher et al., 2020). The formulation of the method as well as its application is detailed in Su et al. (2001) and Su (2002). This dynamic method generally decreases ET simulation for the CMIP6 configuration of ORCHIDEE compared with the CMIP5 configuration.

Snowpack and its dynamics are described by a 3-layer model, which makes it possible to account for variations in albedo, density and thus the insulating properties of the snowpack as a function of the age of the snow and the nature of the underlying vegetation (Wang et al., 2013). Rainfall not intercepted by vegetation cover and meltwater can infiltrate or runoff when the

rainfall exceeds the surface hydraulic conductivity. The two runoff terms, surface runoff and gravitational drainage at the bottom of the soil, are summed as the total runoff.

Eventually, river flows are calculated by a high-resolution routing model (Nguyen-Quang et al., 2018; Polcher et al., 2023), which aggregates the total runoff of HTUs within each atmospheric grid cell along the river routing network (section 2.2.3).
160 The routing model contains 3 linear reservoirs in each HTU: the river reservoir allows horizontal flow to transfer from HTU to HTU along the high-resolution river network; the groundwater and surface water reservoirs are used to compute the mean transit time of groundwater drainage and surface runoff, respectively, and their contribution to the outflow from the river reservoir (Schrapffer et al., 2020). The groundwater reservoir is simplified as a free aquifer, and thus the outflow is the base flow. The resident time of each reservoir depends on the length and slope of the HTU, modulated by a time constant specific
165 for each reservoir (Polcher et al., 2023), which leads to a duration of resident time from long to short according to the order of groundwater, surface water, and river reservoirs. In this context, the flow velocity at each HTU in the river reservoir does not vary with discharge and does not depend on flooding, which is not explicitly described.

2.2 Input data over France

2.2.1 Atmospheric forcing

170 The near-surface meteorological Safran reanalysis with a spatial resolution of 8 km and a temporal resolution of hourly time steps (Vidal et al., 2010a) is used in this study to drive the ORCHIDEE simulations over France. The Safran grid cell is thus the horizontal resolution of the ORCHIDEE simulations. To cover the complete drainage area of French rivers, especially in the Eastern alpine parts of France, the Safran reanalysis was extended to some parts of neighbouring countries, especially Switzerland (Figure 1). The Safran reanalysis is available from 08/1958 onwards and contains atmospheric data for ORCHIDEE:
175 air temperature, air pressure, air specific humidity, wind speed, liquid and solid precipitation, and downwards longwave and shortwave radiation. In addition, annual CO₂ concentration observations in the atmosphere are sourced from Lurton et al. (2020).

2.2.2 Boundary conditions: soil, vegetation and land use

The annual vegetation and land use maps for France used in this study are sourced from Lurton et al. (2020) and derived
180 from two products (see <https://orchidas.lsce.ipsl.fr/dev/lccci/> for further data aggregation information): the global ESA CCI vegetation distribution (Harper et al., 2023) at 300 m spatial resolution is used to generate 15 generic PFTs gridded at 0.25° spatial resolution for the ORCHIDEE model (bare soil, 2 crop PFTs, 4 grass PFTs, and 8 forest PFTs as detailed in Table S1) to represent land cover distribution; the generic 15 PFT distribution is then combined with the Land-Use Harmonization 2 (LUH2) dataset (Hurtt et al., 2020) at 0.25° spatial resolution to produce the temporal evolution of 15 PFTs for CMIP6
185 simulations over the historical and future periods (850-2100). This information is ultimately reaggregated into Safran grid cells to account for the spatial distribution of the PFTs across France (Figure S1). The harvested wood biomass is also sourced from the LUH2 dataset.




Figure 1. The topography and hydrography of Metropolitan France (including Corsica), delineated in black contours, extended to neighbouring countries based on the upscaled MERIT hydro DEM. The river networks in blue are represented by the pixels with a flow accumulation larger than 200 pixels. Four major river basins, the Seine, the Loire, the Rhône and the Garonne, and three major mountain ranges, the Alps, the Massif central and the Pyrenees, in France are marked on the map. The gray points represent the central points of the Safran reanalysis grid cells.

The sensitivity of the ORCHIDEE model to global and regional soil texture maps was tested in the literature (e.g., Tafasca et al., 2020; Kilic et al., 2023). The global soil texture map of Reynolds et al. (2000) shows a better hydrological performance for the Seine River basin (Kilic et al., 2023). Therefore, the soil texture data for France used in this study are based on the global soil texture map of Reynolds et al. (2000) at a $1/12^\circ$ spatial resolution, which classifies soil textures into 12 USDA types. The soil texture information over France is then rescaled into Safran grid cells by keeping the dominant soil texture type for each grid cell (Figure S2). The dominant soil textures in France are loam and clay loam according to the Reynolds soil texture map.

2.2.3 River routing network

The construction of the river routing network across France for the ORCHIDEE model is based on the DEM at $1/60^\circ$ resolution (approximately 1.3 km over France) built by upscaling the MERIT Hydro global hydrography map at 3-arc sec resolution (Yamazaki et al., 2019) with the Iterative Hydrography Upscaling (IHU) method (Eilander et al., 2021). The DEM incorporates the following topographic and hydrologic information from the MERIT Hydro dataset: elevation, flow direction, flow accumulation and distance to the ocean for each pixel, as shown in Figure 1; this information is used to construct the river routing network connected by the HTUs of Safran grid cells as detailed in Polcher et al. (2023). In this study, we selected 15 truncations to construct HTUs (nbmax = 15, i.e., the maximum number of HTUs within each atmospheric grid cell) given the spatial resolutions of the DEM and Safran. Within this framework, the hydrometric stations collected from the Explore2 project are positioned on the constructed high-resolution river routing network to comply with the following criteria: the distance between the real station and the modelled station must be less than 5 km and the error of the upstream surface at the modelled station must be less than 20%. Of the 4081 hydrometric stations collected, 3507 stations are within the above tolerance (86% of the total stations). Finally, ORCHIDEE can monitor the flow out of the HTU associated with the station during the simulation.

2.3 Evaluation strategy

2.3.1 Evaluation datasets

Three evaluation datasets are used in this study to assess the performance of the ORCHIDEE simulation.

The GLEAM dataset (Martens et al., 2017) provides daily ET data at a 0.25° resolution at the global scale from 1980 to 2020; these data were derived from the Priestley and Taylor (1972) evaporation model with satellite-based products (net radiation, precipitation, surface soil moisture, skin and air temperatures, vegetation optical depth, and snow water equivalent) as inputs. The FLUXCOM dataset (Jung et al., 2019) provides daily ET at a 0.5° resolution from 2001 to 2015 based on machine learning algorithms that merge global FLUXNET measurements with remote sensing and meteorological observations. Both ET benchmarks are aggregated to Safran grid cells at monthly time steps. GLEAM and FLUXCOM provide independent ET estimates, both of them with large uncertainties (Liu et al., 2023). They are used in combination to approach the plausible range of observed ET.

The Explore2 project provides records of daily river discharge (Q) across France extracted from the French national hydrometric HydroPortail (Leleu et al., 2014; Delaigue et al., 2020). Of the 3507 hydrometric stations placed across the constructed

220 river routing network, 1785 stations have Q records for at least 8 entire years over the simulation period of 1959-2020; these records were used to calibrate and evaluate the ORCHIDEE simulation. Stations with Q records for at least 8 entire years were chosen because (1) the simulation performance was shown to be rather insensitive to the length of evaluation period above 8 years (Section S10 in supplementary material), and (2) these stations offer a large coverage of French rivers.

225 Although the version of ORCHIDEE used in this study does not include any human impact, the 1785 selected hydrometric stations were all used in the evaluation process, whether human influenced or not. This enables a more comprehensive assessment of ORCHIDEE, as natural or weakly influenced stations are few in number (only 536, see Section S9 in supplementary material) and exclude the stations along the main streams of the four major French rivers (Seine, Loire, Garonne, and Rhône).

2.3.2 Performance criteria

230 The criteria bias, Pearson correlation, Kling-Gupta efficiency (KGE, Kling et al., 2012) and time lag are used to quantitatively evaluate the goodness-of-fit of the simulated ET (at grid cell level over France) and Q against the above datasets. The square-root transformation of Q is applied when calculating the KGE criterion to capture both high and low flows (Song et al., 2019). The time lag calculation is based on auto-correlation with various lags, and determined by the lag t giving the maximum correlation (a positive t means that the simulated Q time series lags the observed time series by t days; a negative t means that the simulated Q time series leads the observed time series by $-t$ days). The ideal time lag value is 0.

235 In addition, to verify the ability of the ORCHIDEE LSM to reproduce the observed trends of ET (at station level as the spatial averages of grid cells in the basins upstream the stations) and Q, the trends of the 1785 selected stations were calculated using the Sen's slope estimator (Sen, 1968). The nonparametric Mann-Kendall test (Mann, 1945; Kendall, 1948) was used to determine the significance of the calculated trends. The significance level in this study is set to 5%. Split sample tests were also performed and showed stable performances if the Q time series are split in two halves (Section S11 in supplementary material).

240 We used a confusion matrix and associated metrics to summarize the trend results: the "Accuracy" indicates the proportion of correct simulations among all observations; the "PPV" (positive predictive value) and "NPV" (negative predictive value) indicate how many positive/negative simulations are actually correct; and the "TPR" (true positive rate) and "TNR" (true negative rate) indicate how many positive/negative observations are correctly represented by the model. How these classic metrics are calculated are detailed in Ting (2010). Besides, to focus on the accuracy of the simulated trend significance, two metrics "PTSA" (positive trend significance accuracy) and "NTSA" (negative trend significance accuracy) are used to indicate the proportions of accurate trend significance (either significant or not) among all the accurate positive or negative trends. Stations with accurate trend sign but incorrect significance are considered inaccurate in this framework.

2.4 Calibration design

250 LSMs are complex models, integrating many coupled processes related to hydrology, soils, vegetation, but also to the radiative transfer or the boundary layer. They are also distributed models designed to be applied over wide and contrasted domains (Clark et al., 2015), in which every grid-point could be regarded as one 1D model. Therefore, their calibration is challenging and a full optimization of LSM's parameters is practically intractable, due to the computational burden (Bierkens et al., 2015),

the equifinality (Fisher and Koven, 2020), and the uncertainty of input and benchmark datasets (Best et al., 2015). The most common solutions are to rely on transfer functions to derive the spatial variations of model parameters from maps of physical parameters (e.g. Samaniego et al., 2010), and to accept sub-optimal but satisfactory performance (Best et al., 2015).

In this line, we chose here to calibrate selected parameters of the ORCHIDEE LSM based on an iterative trial-and-error procedure to gradually improve simulations by manually adjusting some parameters. The simulation period is from 1959 to 2020, with a warm-up from 1959 to 1968 to provide reasonable initial conditions, and the output variables (e.g., ET and Q) are aggregated to daily time steps. The starting experiment of this calibration procedure is called STD and uses the "standard" parameter set sourced from CMIP6 (Boucher et al., 2020), according to which the roughness heights z_{0m} and z_{0h} are calculated by the dynamic method of Su et al. (2001). STD forced with Safran reanalysis significantly underestimates ET and overestimates Q compared with the evaluation datasets detailed in Section 2.3. The calibration is therefore aimed at increasing ET and decreasing Q. According to expert knowledge on the parameter sensitivity of ORCHIDEE and previous calibration exercises (Kilic et al., 2023; Raoult et al., 2021; MacBean et al., 2020; Dantec-Nédélec et al., 2017; Campoy et al., 2013), we focused on parameters that control surface roughness, soil hydraulics and vegetation morphology (detailed in Section 2.1) to improve the simulations of ET and Q.

A hundred parameter sets were tested in this iterative evaluation process, summarized in Table 1 by a selection of 6 calibration experiments that show a gradual decrease of ET and Q biases on average over France. Each parameter set in Table 1 is applied uniformly over the entire simulation area. EXP1a and EXP1b calculate ET using the prescribed z_{0m}/z_{0h} and f_z , respectively, with values suggested by Brutsaert (2005). EXP2 increases the decay factor f , and the soil hydraulic conductivity decreases more rapidly with depth so that the soil drainage decreases (Q decreases) and ET increases. EXP3 decreases the soil water threshold for transpiration from 0.8 to 0.5, and transpiration (thus, ET) increases. EXP4 changes the root profiles of the PFTs present in France by increasing the c parameter of tree and boreal grass PFTs to decrease their root density, while decreasing the c parameter of crop PFTs to increase crop root density. As such, the transpiration of trees and boreal grasses decreases, while the transpiration of crops increases.

3 Results

3.1 Evaluation of simulated basin area

Figure 2 shows the good performance of the high-resolution river routing model in simulating the basin areas across France, with $R^2 = 0.999$ across the 3507 stations compared to the information from HydroPortail. Classically, the performance increases with increasing river basin area, with R^2 ranging from 0.992 for basins less than 10^3 km² to 0.998 for basins larger than 10^4 km². However, the routing model tends to overestimate basin areas for basins less than 10^4 km² but tends to slightly underestimate basin areas for basins larger than 10^4 km². There is no significant positive or negative bias in the simulated basin area for the 4 major river basins (the Seine, the Loire, the Rhône, and the Garonne), and the biases of most of the simulated basins are less than 5%. For basins larger than 10^3 km², most of the biases are larger than 5% are located in the mountainous regions, especially in the Alps, given the complicated topography.




Figure 2. The comparison between the simulated upstream basin area and the reference area in HydroPortail for the 3507 stations located in the high-resolution river networks: (a) scatter plot of simulated area to reference area, (b) boxplot of simulated area bias and (c) spatial map of simulated area bias for basins less than 10^3 km², between 10^3 km² and 10^4 km², and larger than 10^4 km².

Table 1. Parameter sets applied to the calibration experiments of the ORCHIDEE LSM. The means of daily evapotranspiration (ET), surface runoff (R_s), drainage (R_d) and total runoff (R) are calculated over the extended Safran coverage and the 1959-2020 simulation period. The medians of ET bias are calculated for all Safran grid cells of the extended Safran coverage with GLEAM dataset over the 1980-2020 period and with FLUXCOM dataset over the 2001-2015 period. The median of river discharge (Q) bias is calculated with the 1785 selected French hydrometric stations over the 1959-2020 period.

	Roughness		Hydraulics	Vegetation		ET	R_s	R_d	R	Bias ET to G.	Bias ET to F.	Bias Q	
	$\frac{z_{0m}}{z_{0h}}$	f_z	f	p	c	[mm/d]	[mm/d]	[mm/d]	[mm/d]	[%]	[%]	[%]	
Calibrations	STD	dyn	1/15	2	0.8	ref	1.350	0.330	0.933	1.263	-11.6	-14.9	28.4
	EXP1a	10	-	-	-	-	1.453	0.314	0.847	1.161	-5.6	-9.2	16.7
	EXP1b	10	1/10	-	-	-	1.471	0.318	0.824	1.143	-4.4	-8.0	13.6
	EXP2	10	1/10	4	-	-	1.490	0.916	0.208	1.124	-3.3	-6.8	11.7
	EXP3	10	1/10	4	0.5	-	1.498	0.910	0.206	1.116	-2.7	-6.2	10.7
	EXP4	10	1/10	4	0.5	new	1.526	0.893	0.195	1.089	-0.5	-4.3	6.3

- same as STD; dyn as dynamic; G. as GLEAM; F. as FLUXCOM;

ref = [5.0, 0.8, 0.8, 1.0, 0.8, 0.8, 1.0, 1.0, 0.8, 4.0, 4.0, 4.0, 4.0, 4.0, 4.0] in Table S1;

new = [5.0, 0.8, 0.8, 1.0, 0.8, 1.5, 2.0, 2.0, 1.5, 4.0, 4.0, 2.0, 2.0, 4.0, 6.0] in Table S1.

3.2 Performance of the different experiments

Figure 3 illustrates how the performance criteria of the simulated ET and Q improve during the calibration experiments. The first three calibration experiments show the impact of two different methods in calculating ET. STD applies a dynamic physically-based model that calculates z_{0m} and z_{0h} with the variables simulated by ORCHIDEE (e.g., canopy height, LAI, and fractional coverage for 15 PFTs). EXP1a and EXP1b prescribe $\frac{z_{0m}}{z_{0h}}$ and f_z values to approximate z_{0m} and z_{0h} only with the simulated variable of canopy height. Compared with STD, EXP1a decreases the negative ET bias against FLUXCOM by 5.7% by greatly increasing z_{0h} from 1.10×10^{-4} to 1.43×10^{-2} m over the extended simulation domain and simulation period (z_{0m} decreases from 0.385 to 0.255 m). Compared with EXP1a, EXP1b decreases the negative ET bias by 1.2% by increasing f_z from 1/15 to 1/10: z_{0m} increases from 0.255 to 0.482 m, and z_{0h} increases from 1.43×10^{-2} to 2.28×10^{-2} m. Figures S3 and S4 show the spatial and temporal changes of the z_{0h} , z_{0m} and ET values for the first three calibration experiments. Q is thus decreased due to the water budget of ORCHIDEE when ET is increased, and the positive Q bias against HydroPortail decreases by 11.7% and 3.1%, respectively. For the first three calibration experiments, the biases of simulated ET and Q against observation datasets are gradually decreased and EXP1a decreases the biases of the simulated ET and Q the most. In addition, the KGE values of square-rooted Q against observations are slightly increased. However, the correlation values of the simulated Q against observations are slightly decreased, and the simulated Q tends to gradually lag behind the observations for the first three calibrations.




Figure 3. Performance criteria of calibration experiments: (a) bias of the simulated ET to GLEAM dataset; (b) bias of the simulated ET to FLUXCOM dataset; (c) bias of the simulated Q; (d) Pearson correlation coefficient of the simulated Q; (e) KGE of the square-rooted simulated Q; (f) time lag of the simulated Q. The calculation of biases for the simulated ET is applied to all Safran grid cells of the extended domain over the 1980-2020 period against GLEAM dataset and over the 2001-2015 period against FLUXCOM dataset, respectively. The calculation of criteria for the simulated Q is applied to the 1785 hydrometric stations in the HydroPortail dataset with records for at least 8 entire years. For each boxplot, the lower and upper hinges are the first and third quartiles; the minimum and maximum values extend from the first/third hinge to 1.5 times of the inter-quartile range.

To improve the goodness-of-fit of the simulated Q, EXP2 increases the decay factor f from 2 to 4 compared to EXP1b, which decreases the hydraulic conductivity for soil layers below 0.3 m, while the hydraulic conductivity for soil layers above 0.3 m remains unchanged (Figure S6a-b). A decrease of hydraulic conductivity in deep soil layers leads to a decrease of drainage at the soil bottom. Since less water drains from deep soil layers while the surface soil layers maintain the same infiltration capacity, the latter can saturate more easily, and more surface runoff is produced (Table 1). Eventually, the total runoff is decreased from EXP1b to EXP2 as the surface runoff increase is smaller than the decrease of gravitational drainage at the soil bottom. EXP2 thus decreases the positive Q bias against HydroPortail (by 1.9%), as well as the negative ET bias against FLUXCOM (by 1.2%). In addition, the ratio of surface runoff to total runoff is greatly increased from 27.9% in EXP1b to 81.5% in EXP2, which results in more "fast" surface flow and less "slow" groundwater, leading to more responsive Q to precipitation events. The correlation and KGE criteria of the simulated Q are improved from 0.59 to 0.69 and from 0.54 to 0.59, respectively (Figure 3). The time lag criterion of the simulated Q is also greatly improved from a range of -11 to 27 days to a range of -3 to 5 days. Similar improvements in streamflow dynamics could be obtained by changing the time constant of the fast and slow routing reservoirs without improving the Q and ET biases.

Two additional simulations, EXP3 and EXP4, were conducted to further improve the bias criteria by changing the vegetation parameters in ORCHIDEE to potentially increase transpiration (thus ET): EXP3 reduced the soil moisture stress for transpiration, while EXP4 changed the vegetation root profile. Transpiration is conveyed by the factor U_s in ORCHIDEE, which is negatively related to the water stress factor F and positively related to root density.

The factor F depends on soil moisture and on a threshold parameter p , as illustrated in Figure S7: there is no soil moisture stress if $F = 1$, which occurs when the soil moisture exceeds $\theta_w + p \times (\theta_c - \theta_w)$. By decreasing p from 0.8 in EXP2 to 0.5 in EXP3, a wider range of soil moisture leads to $F = 1$ and thus unstressed transpiration. As shown in Figure S8, transpiration (U_s) is increased for all PFTs and the effect is more pronounced for crop PFTs (PFTs 12 and 13) than for forest PFTs (PFTs 7 and 8). However, this general decrease of soil water stress to favour transpiration is weak, as it decreases the negative ET bias against FLUXCOM by only 0.6% (1.0% for the positive Q bias against HydroPortail).

The change in the root density profile from EXP3 to EXP4 further modifies transpiration but also changes the hydraulic conductivity of the shallow soil layers. In EXP4, we increased the root density of the crop PFTs (PFTs 12 and 13) by decreasing c , and decreased the root density of the forest and boreal grass PFTs (PFTs 6, 7, 8, 9, and 15) by increasing c (Table S1; Figure S9). Given the major spatial distribution of the crop PFTs in France (Figure S1), the general effect of EXP4 compared to EXP3 increases transpiration (thus ET), which also reduces drainage at the soil bottom. In addition, the hydraulic conductivity of the shallow soil layers in France is slightly increased but with some spatial differences, as shown in Figure S6c-d, which generally reduces surface runoff. The negative ET bias against FLUXCOM is decreased by 1.9% (4.4% for the positive Q bias against HydroPortail). Both EXP3 and EXP4 barely improve the correlation and KGE criteria of simulated Q against observations, while EXP4 slightly degrades the time lag due to the change in infiltration capacity in surface soils.

In summary, by successively adjusting the surface roughness, hydraulic, and vegetation parameters, the goodness-of-fit measures of the simulated ET and Q are gradually improved. A considerable improvement in the bias criteria for the simulated ET and Q comes from the method of calculating ET by prescribing the surface roughness parameters (EXP1a and EXP1b). The

correlation, KGE and time lag criteria performance for the simulated Q are considerably increased by calibrating the hydraulic parameter (EXP2) due to a better adjustment of the surface runoff and drainage ratios to total runoff. Calibrations of vegetation parameters (EXP3 and EXP4) also improve the simulation performance but with minor sensitivity compared to the previous
340 calibrations. Generally, EXP4 shows the most satisfactory simulation performance among the calibration experiments.

3.3 Preferred experiment: Spatial evaluation of the simulated water fluxes

The simulation is evaluated using the EXP4 calibration experiment, which yields the overall best performance criterion values in terms of the simulated ET and Q.

3.3.1 ET simulation performance

345 Both the GLEAM and FLUXCOM datasets are used to evaluate the ET simulation by ORCHIDEE in this study. Both datasets show more ET in the southern part (except for the high Alps) and less ET in the northern part of the simulation domain (Figure 4a-b). However, compared with that in the GLEAM dataset, the ET of the FLUXCOM dataset is much greater in the north-western part of the domain (i.e., the Seine and Loire River basins) and lower in the mountainous regions (i.e., the Alps, the Massif central and the Pyrenees).

350 Figure 4c shows that the spatial distributions of the simulated ET biases are distinctly contrasted from those of the GLEAM dataset over the entire simulated domain: the simulated ET is generally underestimated in the mountainous regions (except for the high Alps, where a considerable overestimation occurs) and the Gascogne region (alluvial plain of the Pyrenees) but is significantly overestimated in the north-western part (notably the Seine River basin). On the other hand, compared to the FLUXCOM dataset, Figure 4d shows that the simulated ET bias is generally underestimated but overestimated in the south-
355 eastern part of the entire simulation domain (notably the Mediterranean mountainous regions). Although the median bias of the simulated ET against GLEAM (-0.5%) is better than that against FLUXCOM (-4.3%), as illustrated in Figure 3, the simulated ET is more spatially consistent with FLUXCOM.

3.3.2 Q simulation performance

Figure 5 shows the spatial distribution of the simulated Q criteria evaluated by the 1785 selected hydrometric stations in the HydroPortail dataset. The Q simulated by ORCHIDEE is mainly underestimated in Mediterranean river basins and overestimated elsewhere, which is consistent with the overestimation of the simulated ET in the Mediterranean region and the underestimation elsewhere against the FLUXCOM dataset. The biases of the simulated Q for most basins larger than 10^3 km² are less than 10%. In general, the river discharges in the Saône (a major tributary contributing to the Rhône River basin), Garonne, and Loire River basins along the main river networks are satisfactorily represented by ORCHIDEE, with the Pearson correlation
365 and KGE criteria mostly larger than 0.8 and 0.75, respectively. Subbasins with areas less than 10^3 km² in these river basins are also fairly well simulated with Pearson correlation and KGE criteria broadly larger than 0.6 and 0.5, respectively. In terms of the time lag criterion, most simulated Q with large time lag errors correspond to catchments smaller than 10^4 km², with




Figure 4. The spatial distributions of the ET datasets and the simulated ET biases against them for all the Safran grid cells over the entire simulation domain: (a) the mean ET of the GLEAM dataset and (c) the bias of the simulated ET against it from 1980 to 2020; (b) the mean ET of the FLUXCOM dataset and (d) the bias of the simulated ET against it from 2001 to 2015. The mean ET of the GLEAM dataset from 2001 to 2015 is not shown here but is very similar to that of the 1980-2020 period.




Figure 5. The spatial distribution of the Q simulation performance evaluated by the (a) bias, (b) Pearson correlation coefficient, (c) KGE of the square-rooted Q, and (d) time lag for the 1785 selected French hydrometric stations in the HydroPortail dataset over the entire simulation domain.

M5300010: Loire at Montjean-sur-Loire




Figure 6. The simulation performance of the Loire River at the hydrometric station Montjean-sur-Loire (M5300010): (a) the simulated river basin area with the legend of the proportion of Safran grids contributing to the basin area; (b) the annual regime of simulated Q compared to the observation in the HydroPortail dataset at daily time steps from 1959 to 2020; (c) the annual regime of simulated ET compared to the GLEAM dataset at monthly time steps from 1980 to 2020; (d) the annual regime of simulated ET compared to the FLUXCOM dataset at monthly time steps from 2001 to 2015; and (e) the simulated Q compared to the observation at monthly time steps from 1959 to 2020. The regime plots of ET and Q are presented with the colour bands as the range between the 25% and 75% quantiles and the solid lines as the medians.

H8110020: Seine at Vernon




Figure 7. The same as in Figure 6 but for the Seine River at the hydrometric station Vernon (H8110020).

simulated Q leading the observations by 2 to 6 days in the Seine River basin, but lagging the observations by 2 to 4 days in the Loire River basin. The simulated Q in the Garonne and Rhône River basins generally reveal no obvious leading or lagging results.

Human impacts on water that are not explicitly taken into account in this study lead to the degradation of goodness-of-fit indicators. An example of the simulation results for the Loire River basin is illustrated in Figure 6. The variability and seasonality of the Q and ET fluxes are well represented by ORCHIDEE while the simulated Q of the Loire River during the summer period is overestimated. This difference may be attributed to the irrigation extraction of maize crops by upstream reservoirs (Janin, 1996). The Seine River basin is influenced by upstream reservoirs that store high winter flows and release them during summer to meet environmental and navigational needs and by groundwater pumping mostly for drinking water in Paris (Flipo et al., 2020). These human interventions are not described in the ORCHIDEE LSM, which probably explains in a large part why river discharge downstream of Paris is strongly underestimated, especially in summer (Figure 7). In addition, the mountainous basins in the Alps (e.g. the Isère and Durance River basins, contributing to the Rhône River) and the Pyrenees (e.g. the Neste River basin, contributing to the Garonne River) show unsatisfactory simulation performance (Figures S10-11) because these river basins are significantly perturbed by dams and reservoirs for winter hydropower production, spring refill and summer irrigation (e.g. the Serre-Ponçon reservoir in the Durance River basin, one of the largest dams in Europe) (François et al., 2014; Andrew and Sauquet, 2017; Huang et al., 2022; Baratgin et al., 2024). Figure S14 shows that ORCHIDEE performs better on natural or weakly influenced river basins than on influenced river basins, especially for correlation and KGE criteria.

Other model imperfections degrade the quality of simulated river discharge. In the mountains, these poor results could also be related to poor snow simulation. Groundwater is also known to strongly influence streamflow, especially in river basins embedded in sedimentary basins (e.g., the Seine River basin). Groundwater is simply represented in ORCHIDEE by the slow reservoir of the routing scheme as a free aquifer. However, ORCHIDEE does not account for the difference between large aquifers, which significantly buffer river discharge variability (Gascoïn et al., 2009), and smaller aquifers with shallow and very reactive water tables. This degrades the ORCHIDEE's performance (e.g., bias and time lag) in the sedimentary basins. This problem could be approached by assigning larger residence times to the slow reservoirs of grid cells in sedimentary basins. However, it is difficult in practice because parameters are applied uniformly over France in ORCHIDEE.

3.4 Preferred experiment: Evaluation of river discharge trends

Figure 8 shows that the calibrated ORCHIDEE LSM satisfactorily represents the observed Q trend of the 1785 selected French hydrometric stations. In general, both the observed and simulated Q trends exhibit similar spatial patterns, with a decreasing trend (significant) in the south-eastern part of France and an increasing trend (not significant) in the north-western part of France, which is consistent with the findings of previous studies (e.g., Gudmundsson et al., 2017; Vicente-Serrano et al., 2019). Most basins with significant observed and simulated decreasing trends are located in the Garonne River, upstream of the Loire River, and upstream of the Rhône River. However, compared with the observed Q trends over France, the simulated Q trends tend to alleviate the decreasing trend and to enhance the increasing trend. For example, there is a general decreasing trend, usually not significant, for the basins located on the Mediterranean coast (including Corsica) from the observed Q, while the




Figure 8. The spatial distribution of the observed Q trend (a), the simulated Q trend (b), and the ratio between the simulated Q trend and observed Q trend for the 1785 selected French hydrometric stations in the HydroPortail dataset from 1959 to 2020. The trends of the simulated and observed Q are calculated with the yearly mean Q time series for the common period of two time series. The confusion matrix (d) between the observed Q trend and the simulated Q trend is presented at 4 dimensions as colourful boxes (significant positive, not significant positive, not significant negative, and significant negative) and at 2 dimensions as white boxes (positive and negative).

simulated trends are more variant. In the north-western part of France (such as in the middle part of the Seine River and the Brittany Peninsula), the increasing trends of the simulated Q are more pronounced than in the observations. To summarize, the simulated trends tend to be more positive than the observed trends over France, which might be attributed to the fact that intensified water withdrawals (for irrigation, industry, and drinking water) are not considered in the simulation from 1959 to 2020. This period corresponds to the expansion of agricultural and water infrastructure projects across France (Janin, 1996), and human activities are inferred to be the dominant drivers of river flow decreases and drought aggravation (e.g., García-Ruiz et al., 2011; Loon et al., 2022; Greve et al., 2023). Nonetheless, climate variability and land use and land cover changes are taken into account in the simulations of this study, which partially explain the south-east (dry)/north-west (wet) contrast across France.

Table 2. The confusion matrix metrics (detailed in Section 2.3) that evaluate the performance of the ORCHIDEE LSM in representing the Q trend sign and significance over France from 1959 to 2020 calculated from Figure 8d.

		Trend sign			
Metric	Accuracy	PPV	NPV	TPR	TNR
Value [-]	76.4%	66.8%	81.7%	66.7%	81.8%
		Trend significance			
Metric	Accuracy	PTSA	NTSA		
Value [-]	62.7%	87.9%	79.4%		

To further advance the information obtained from the confusion matrix of Figure 8d, Table 2 summarizes the performance of the simulated Q trend sign and its significance with accuracy of trend sign = $(941+423)/1785$, PPV = $423/(423+210)$, NPV = $941/(941+211)$, TPR = $423/(423+211)$, NPR = $941/(941+210)$, accuracy of trend significance = $(143+604+357+15)/1785$, PTSA = $(357+15)/423$, and NTSA = $(143+604)/941$. Generally, the ORCHIDEE LSM satisfactorily reproduces the past trends of French river discharge from 1959 to 2020 with an accuracy of 76.4% for the trend sign and an accuracy of 62.7% for the trend significance. Compared to the observed Q trend sign over France, the negative Q trend is relatively better simulated than the positive Q trend despite the inadequate consideration of human perturbations. However, in terms of the simulation performance of trend significance, the positive Q trend significance is slightly better than the negative Q trend significance.

Figures 9 and 10 show the water flux trends in the Loire and Seine River basins, respectively, as two examples. The decreasing trends of the annual streamflow for both river basins are well simulated by the ORCHIDEE LSM. Nevertheless, the simulated decreasing trend of the Loire River is weakened with the underestimation of wet years, while that of the Seine River is aggravated with the overestimation of wet years and the underestimation of dry years. The simulated increasing trends of ET for both river basins are more consistent with those of the GLEAM dataset than those of the FLUXCOM dataset given its longer records. More examples of the water flux trends are provided in supplementary material (Figures S12-13).

This study presents the development of a high-resolution of approximately 1.3 km hydrological simulation over France with the ORCHIDEE LSM to quantify water resources at the nationwide scale, either retrospectively, as shown here to evaluate the set up, or prospectively, as planned for the Explore2 project to deliver climate change projections. After several calibration steps to improve the simulated water budget and hydrological performance, the simulation results over the 1959-2020 period are evaluated via comparison with the ET products (the GLEAM and FLUXCOM datasets) at monthly steps and with the French national hydrometric networks (the HydroPortail dataset) at daily time steps. Generally, the selected parametrization of the ORCHIDEE LSM provided satisfactory results in terms of the simulated basin areas and water fluxes.

This study emphasizes the ability of this version of ORCHIDEE to reproduce the temporal and spatial patterns of Q trends, with an accuracy of the trend sign of 76.4% and that of the trend significance of 62.7% over France. The decreasing trend in south-eastern France with marked significance and the increasing trend in north-western France with minor significance are adequately represented by the ORCHIDEE LSM. To a greater extent, this diagnosis is necessary for climate change impact studies because adaptation strategies are grounded in the statistical analysis of the projections, potential trends of future river discharge in particular. Therefore, hydrological models must be able to accurately reproduce trends under current climate conditions. However, in most climate change impact studies, this investigation of hydrological model performance has been rarely analysed but has been found to depend primarily on traditional goodness-of-fit indicators (e.g., KGE). A recent study revealed that these traditional indicators do not ensure the reproduction of trends (Todorović et al., 2022). An inadequate representation of vegetation dynamics can explain why some hydrological models fail to accurately reproduce river discharge trends (e.g., the HBV conceptual hydrological model; Duethmann et al., 2020). On the other hand, the incorporation of vegetation dynamics in hydrological models often improves their hydrological simulation performance (e.g., Jiao et al., 2017; Bai et al., 2018). The ORCHIDEE LSM accounts for the interactions between the biosphere (15 PFTs in this study) and hydrosphere (e.g., transpiration, precipitation interception, and photosynthesis) by coupling the SECHIBA and STOMATE modules to explicitly simulate the phenomena of the terrestrial carbon and water cycles (Ducoudré et al., 1993; Krinner et al., 2005).

The limitations of the modelling framework proposed in this study and the prospects to improve ORCHIDEE simulations are analyzed from these three major aspects: parameter calibration, input and evaluation datasets, and ORCHIDEE model structure.

First, uncertainties remain in the selected parameter set. In this study, we applied the trial-and-error calibration method (no parameter optimization procedure) to reduce the computational burden. The general principle of calibration is to decrease the biases of water fluxes across France by increasing ET and decreasing Q simulations starting from the CMIP6 configuration; the calibration experiments follow this principle by changing the parameters employed for all the grid cells across France. This procedure indeed simplifies the calibration of such sophisticated physically based LSMs to obtain generally accepted performance criteria over the entire simulation domain. However, improvements in simulation performance in some areas remain limited. For example, calibrating the hydraulic conductivity influenced by both soil and vegetation (EXP2 and EXP4) to adjust infiltration and surface runoff have improved the overall performance criteria except for those of the Seine River basin.

In reality, the characteristics of the Seine River basin, such as its relief and lithology, allow more predominant infiltration than surface runoff, especially in the upstream region of the Seine basin (e.g., Schneider et al., 2017; Mardhel et al., 2021). The calibration of soil hydraulic conductivity at the basin scale (i.e., different parameter values for the grid cells over the simulation domain) could improve the simulation results (e.g., Quintana Seguí et al., 2009). Another challenge is the parameterization of the 15 PFTs in terms of their transpiration capacity when facing water stress and root profiles (EXP3 and EXP4) due to the lack of observations, notwithstanding their importance to terrestrial carbon and water cycles.

Second, uncertainties concerning the input and evaluation datasets should also be considered. For instance, heterogeneity regarding the radiation data of the Safran reanalysis (i.e., the break of homogeneity in time series with an abrupt increase in the profile of incident solar radiation after the late 1980s) has been reported, which could be attributed to the improvement of the assimilation system over time, the variation of the in-situ observations and the darkening-lightening effect (e.g., Le Moigne et al., 2020). This directly impacts the ET simulation results. There are also large uncertainties in the Safran reanalysis on precipitation in high elevation areas in France (e.g., Birman et al., 2017; Baratgin et al., 2024). The uncertainties of other input datasets, such as the Reynolds soil texture map and the LUH2 land use and land cover maps applied to the ORCHIDEE LSM has been discussed in other studies (e.g., Kilic et al., 2023; Lurton et al., 2020; Tafasca et al., 2020). Besides, Q records of the selected 1785 stations are not fully checked because identifying Q anomalies is extremely time-consuming and subjective. The remaining observational Q errors might influence model evaluation.

Third, some perspectives concerning better representations of land surface processes can be proposed to improve the simulation performance of the ORCHIDEE LSM. Given the inadequate performance of basins where drainage plays an important role in river discharge (e.g., the Seine River basins), the introduction of a groundwater module in the ORCHIDEE LSM is necessary to describe the interactions between aquifers and rivers in these basins. Moreover, mountainous basins are not adequately simulated; indeed, the Safran reanalysis is deficient in these regions, and there is still room for improvement in the 3-layer snow model, especially for the snow thermal conductivity, which is crucial for snow dynamics (Wang et al., 2013). Human impacts on terrestrial water cycles could also be included to obtain more reliable simulations by comparison to the observations in highly anthropized basins. In particular, a new irrigation module based on the flooding irrigation method (Arboleda-Obando et al., 2024) and a new demand-based hydropower module (Baratgin et al., 2024) have recently been developed and validated by the ORCHIDEE project team at IPSL, and should now be mobilized to achieve more realistic simulations.

M5300010: Loire at Montjean-sur-Loire




Figure 9. The temporal trends of the observed and simulated annual Q (a) and ET (b) of the Loire River at the hydrometric station Montjean-sur-Loire (M5300010) for the 1959-2020, 1980-2020, and 2001-2015 periods. The trend magnitudes are marked in the plots in units of %/year and the symbol (*) indicates the significance of the trend (p value < 0.05).

H8110010: Seine at Vernon




Figure 10. The same as in Figure 9 but for the Seine River at the hydrometric station Vernon (H8110010).

485 *Code and data availability.* The ORCHIDEE codes and data used in this study can be obtained by contacting the corresponding author.

Author contributions. PH, AD, and LR designed the research. PH and LR performed the simulations. PH analysed the data and prepared a draft of the manuscript. JP and LB contributed to building the high-resolution river network. VB prepared the input data for the simulation. ES prepared the river discharge observations. All the authors contributed to interpreting results, discussing findings and improving the manuscript.

490 *Competing interests.* The authors declare that they have no conflict of interest.

Acknowledgements. This research was financed by the Explore2 project with support from the French Biodiversity Agency (OFB) and the French Ministry of Ecological Transition (MTECT). This research was also financed by the BLUEGEM project (ANR-21-SOIL-0001) founded by the Belmont Forum. The simulations analyzed in the paper were produced and stored at the IDRIS on the supercompute Jean Zay CSL, owing to the resources provided by GENCI under grant 2022-AD010113599.

495 **References**

- Andrew, J. T. and Sauquet, E.: Climate Change Impacts and Water Management Adaptation in Two Mediterranean–Climate Watersheds: Learning from the Durance and Sacramento Rivers, *Water*, 9, <https://doi.org/10.3390/w9020126>, 2017.
- Arboleda-Obando, P. F., Ducharne, A., Yin, Z., and Ciais, P.: Validation of a new global irrigation scheme in the land surface model ORCHIDEE v2.2, *Geoscientific Model Development*, 17, 2141–2164, <https://doi.org/10.5194/gmd-17-2141-2024>, 2024.
- 500 Bai, P., Liu, X., Zhang, Y., and Liu, C.: Incorporating vegetation dynamics noticeably improved performance of hydrological model under vegetation greening, *Science of The Total Environment*, 643, 610–622, <https://doi.org/10.1016/j.scitotenv.2018.06.233>, 2018.
- Baratgin, L., Polcher, J., Dumas, P., and Quirion, P.: Modeling hydropower operations at the scale of a power grid: a demand-based approach, *EGUsphere*, 2024, 1–52, <https://doi.org/10.5194/egusphere-2023-3106>, 2024.
- Best, M. J., Abramowitz, G., Johnson, H. R., Pitman, A. J., Balsamo, G., Boone, A., Cuntz, M., Decharme, B., Dirmeyer, P. A., Dong,
505 J., Ek, M., Guo, Z., Haverd, V., van den Hurk, B. J. J., Nearing, G. S., Pak, B., Peters-Lidard, C., Santanello, J. A., Stevens, L., and Vuichard, N.: The Plumbing of Land Surface Models: Benchmarking Model Performance, *Journal of Hydrometeorology*, 16, 1425 – 1442, <https://doi.org/10.1175/JHM-D-14-0158.1>, 2015.
- Beven, K.: A manifesto for the equifinality thesis, *Journal of Hydrology*, 320, 18–36, <https://doi.org/10.1016/j.jhydrol.2005.07.007>, the model parameter estimation experiment, 2006.
- 510 Bierkens, M. F. P., Bell, V. A., Burek, P., Chaney, N., Condon, L. E., David, C. H., de Roo, A., Döll, P., Drost, N., Famiglietti, J. S., Flörke, M., Gochis, D. J., Houser, P., Hut, R., Keune, J., Kollet, S., Maxwell, R. M., Reager, J. T., Samaniego, L., Sudicky, E., Sutanudjaja, E. H., van de Giesen, N., Winsemius, H., and Wood, E. F.: Hyper-resolution global hydrological modelling: what is next?, *Hydrological Processes*, 29, 310–320, <https://doi.org/10.1002/hyp.10391>, 2015.
- Birman, C., Karbou, F., Mahfouf, J.-F., Lafaysse, M., Durand, Y., Giraud, G., Mérindol, L., and Hermozo, L.: Precipitation Analysis over
515 the French Alps Using a Variational Approach and Study of Potential Added Value of Ground-Based Radar Observations, *Journal of Hydrometeorology*, 18, 1425 – 1451, <https://doi.org/10.1175/JHM-D-16-0144.1>, 2017.
- Boucher, O., Servonnat, J., Albright, A. L., Aumont, O., Balkanski, Y., Bastrikov, V., Bekki, S., Bonnet, R., Bony, S., Bopp, L., Braconnot, P., Brockmann, P., Cadule, P., Caubel, A., Cheruy, F., Codron, F., Cozic, A., Cugnet, D., D’Andrea, F., Davini, P., de Lavergne, C., Denvil, S., Deshayes, J., Devilliers, M., Ducharne, A., Dufresne, J.-L., Dupont, E., Éthé, C., Fairhead, L., Falletti, L., Flavoni, S., Foujols, M.-A.,
520 Gardoll, S., Gastineau, G., Ghattas, J., Grandpeix, J.-Y., Guenet, B., Guez, Lionel, E., Guilyardi, E., Guimberteau, M., Hauglustaine, D., Hourdin, F., Idelkadi, A., Joussaume, S., Kageyama, M., Khodri, M., Krinner, G., Lebas, N., Levvasseur, G., Lévy, C., Li, L., Lott, F., Lurton, T., Luysaert, S., Madec, G., Madeleine, J.-B., Maignan, F., Marchand, M., Marti, O., Mellul, L., Meurdesoif, Y., Mignot, J., Musat, I., Ottlé, C., Peylin, P., Planton, Y., Polcher, J., Rio, C., Rochetin, N., Rousset, C., Sepulchre, P., Sima, A., Swingedouw, D., Thiéblemont, R., Traore, A. K., Vancoppenolle, M., Vial, J., Vialard, J., Viovy, N., and Vuichard, N.: Presentation and Evaluation of the IPSL-CM6A-LR
525 Climate Model, *Journal of Advances in Modeling Earth Systems*, 12, e2019MS002 010, <https://doi.org/10.1029/2019MS002010>, 2020.
- Boé, J., Terray, L., Martin, E., and Habets, F.: Projected changes in components of the hydrological cycle in French river basins during the 21st century, *Water Resources Research*, 45, W08 426, <https://doi.org/10.1029/2008WR007437>, 2009.
- Brutsaert, W.: *Hydrology: An Introduction*, Cambridge University Press, <https://doi.org/10.1017/CBO9780511808470>, 2005.
- Cai, X., Yang, Z.-L., David, C. H., Niu, G.-Y., and Rodell, M.: Hydrological evaluation of the Noah-MP land surface model for the Mississippi
530 River Basin, *Journal of Geophysical Research: Atmospheres*, 119, 23–38, <https://doi.org/10.1002/2013JD020792>, 2014.

- Campoy, A., Ducharne, A., Cheruy, F., Hourdin, F., Polcher, J., and Dupont, J. C.: Response of land surface fluxes and precipitation to different soil bottom hydrological conditions in a general circulation model, *Journal of Geophysical Research: Atmospheres*, 118, 10725–10739, <https://doi.org/10.1002/jgrd.50627>, 2013.
- 535 Cheng, Y., Xia, W., Detto, M., and Shoemaker, C. A.: A Framework to Calibrate Ecosystem Demography Models Within Earth System Models Using Parallel Surrogate Global Optimization, *Water Resources Research*, 59, e2022WR032945, <https://doi.org/10.1029/2022WR032945>, 2023.
- Cheruy, F., Ducharne, A., Hourdin, F., Musat, I., Vignon, E., Gastineau, G., Bastrikov, V., Vuichard, N., Diallo, B., Dufresne, J.-L., Ghattas, J., Grandpeix, J.-Y., Idelkadi, A., Mellul, L., Maignan, F., Ménégoz, M., Ottlé, C., Peylin, P., Servonnat, J., Wang, F., and Zhao, Y.: Improved Near-Surface Continental Climate in IPSL-CM6A-LR by Combined Evolutions of Atmospheric and Land Surface Physics, *Journal of Advances in Modeling Earth Systems*, 12, e2019MS002005, <https://doi.org/10.1029/2019MS002005>, 2020.
- 540 Cho, K. and Kim, Y.: Improving streamflow prediction in the WRF-Hydro model with LSTM networks, *Journal of Hydrology*, 605, 127–297, <https://doi.org/10.1016/j.jhydrol.2021.127297>, 2022.
- Clark, M. P., Fan, Y., Lawrence, D. M., Adam, J. C., Bolster, D., Gochis, D. J., Hooper, R. P., Kumar, M., Leung, L. R., Mackay, D. S., Maxwell, R. M., Shen, C., Swenson, S. C., and Zeng, X.: Improving the representation of hydrologic processes in Earth System Models, *Water Resources Research*, 51, 5929–5956, <https://doi.org/10.1002/2015WR017096>, 2015.
- 545 Coe, M. T.: Modeling Terrestrial Hydrological Systems at the Continental Scale: Testing the Accuracy of an Atmospheric GCM, *Journal of Climate*, 13, 686–704, [https://doi.org/10.1175/1520-0442\(2000\)013<0686:MTHSAT>2.0.CO;2](https://doi.org/10.1175/1520-0442(2000)013<0686:MTHSAT>2.0.CO;2), 2000.
- Dantec-Nédélec, S., Ottlé, C., Wang, T., Guglielmo, F., Maignan, F., Delbart, N., Valdayskikh, V., Radchenko, T., Nekrasova, O., Zakharov, V., and Jouzel, J.: Testing the capability of ORCHIDEE land surface model to simulate Arctic ecosystems: Sensitivity analysis and site-level model calibration, *Journal of Advances in Modeling Earth Systems*, 9, 1212–1230, <https://doi.org/10.1002/2016MS000860>, 2017.
- 550 de Rosnay, P., Polcher, J., Bruen, M., and Laval, K.: Impact of a physically based soil water flow and soil-plant interaction representation for modeling large-scale land surface processes, *Journal of Geophysical Research: Atmospheres*, 107, ACL 3–1–ACL 3–19, <https://doi.org/10.1029/2001JD000634>, 2002.
- Decharme, B. and Douville, H.: Introduction of a sub-grid hydrology in the ISBA land surface model, *Climate dynamics*, 26, 65–78, <https://doi.org/10.1007/s00382-005-0059-7>, 2006.
- 555 Delaigue, O., Génot, B., Lebecherel, L., Brigode, P., and Bourgin, P.: Database of watershed-scale hydroclimatic observations in France, Université Paris-Saclay, INRAE, HYCAR Research Unit, Hydrology group, Antony. Available from: <https://webgr.inrae.fr/activites/base-de-donnees/>, 2020.
- d’Orgeval, T., Polcher, J., and de Rosnay, P.: Sensitivity of the West African hydrological cycle in ORCHIDEE to infiltration processes, *Hydrology and Earth System Sciences*, 12, 1387–1401, <https://doi.org/10.5194/hess-12-1387-2008>, 2008.
- 560 Dorigo, W., Wagner, W., Albergel, C., Albrecht, F., Balsamo, G., Brocca, L., Chung, D., Ertl, M., Forkel, M., Gruber, A., Haas, E., Hamer, P. D., Hirschi, M., Ikonen, J., de Jeu, R., Kidd, R., Lahoz, W., Liu, Y. Y., Miralles, D., Mistelbauer, T., Nicolai-Shaw, N., Parinussa, R., Pratola, C., Reimer, C., van der Schalie, R., Seneviratne, S. I., Smolander, T., and Lecomte, P.: ESA CCI Soil Moisture for improved Earth system understanding: State-of-the art and future directions, *Remote Sensing of Environment*, 203, 185–215, <https://doi.org/10.1016/j.rse.2017.07.001>, 2017.
- Ducharne, A., Golaz, C., Leblois, E., Laval, K., Polcher, J., Ledoux, E., and de Marsily, G.: Development of a high resolution runoff routing model, calibration and application to assess runoff from the LMD GCM, *Journal of Hydrology*, 280, 207–228, [https://doi.org/10.1016/S0022-1694\(03\)00230-0](https://doi.org/10.1016/S0022-1694(03)00230-0), 2003.

- Ducoudré, N. I., Laval, K., and Perrier, A.: SECHIBA, a New Set of Parameterizations of the Hydrologic Exchanges at the Land-Atmosphere Interface within the LMD Atmospheric General Circulation Model, *Journal of Climate*, 6, 248–273, [https://doi.org/10.1175/1520-0442\(1993\)006<0248:SANSOP>2.0.CO;2](https://doi.org/10.1175/1520-0442(1993)006<0248:SANSOP>2.0.CO;2), 1993.
- Duethmann, D., Blöschl, G., and Parajka, J.: Why does a conceptual hydrological model fail to correctly predict discharge changes in response to climate change?, *Hydrology and Earth System Sciences*, 24, 3493–3511, <https://doi.org/10.5194/hess-24-3493-2020>, 2020.
- Dufresne, J. L., Foujols, M. A., Denvil, S., Caubel, A., Marti, O., Aumont, O., Balkanski, Y., Bekki, S., Bellenger, H., Benshila, R., Bony, S., Bopp, L., Braconnot, P., Brockmann, P., Cadule, P., Cheruy, F., Codron, F., Cozic, A., Cugnet, D., de Noblet, N., Duvel, J. P., Ethé, C., Fairhead, L., Fichefet, T., Flavoni, S., Friedlingstein, P., Grandpeix, J. Y., Guez, L., Guilyardi, E., Hauglustaine, D., Hourdin, F., Idelkadi, A., Ghattas, J., Joussaume, S., Kageyama, M., Krinner, G., Labetoulle, S., Lahellec, A., Lefebvre, M. P., Lefevre, F., Levy, C., Li, Z. X., Lloyd, J., Lott, F., Madec, G., Mancip, M., Marchand, M., Masson, S., Meurdesoif, Y., Mignot, J., Musat, I., Parouty, S., Polcher, J., Rio, C., Schulz, M., Swingedouw, D., Szopa, S., Talandier, C., Terray, P., Viovy, N., and Vuichard, N.: Climate change projections using the IPSL-CM5 Earth System Model: from CMIP3 to CMIP5, *Climate Dynamics*, 40, 2123–2165, <https://doi.org/10.1007/s00382-012-1636-1>, 2013.
- Eilander, D., van Verseveld, W., Yamazaki, D., Weerts, A., Winsemius, H. C., and Ward, P. J.: A hydrography upscaling method for scale-invariant parametrization of distributed hydrological models, *Hydrology and Earth System Sciences*, 25, 5287–5313, <https://doi.org/10.5194/hess-25-5287-2021>, 2021.
- Fisher, R. A. and Koven, C. D.: Perspectives on the Future of Land Surface Models and the Challenges of Representing Complex Terrestrial Systems, *Journal of Advances in Modeling Earth Systems*, 12, e2018MS001453, <https://doi.org/10.1029/2018MS001453>, 2020.
- Flipo, N., Labadie, P., Lestel, L., Meybeck, M., and Garnier, J.: The Seine River Basin, Springer Cham, <https://doi.org/10.1007/978-3-030-54260-3>, 2020.
- Fowler, K., Knoben, W., Peel, M., Peterson, T., Ryu, D., Saft, M., Seo, K.-W., and Western, A.: Many commonly used rainfall-runoff models lack long, slow dynamics: Implications for runoff projections, *Water Resources Research*, 56, e2019WR025286, <https://doi.org/10.1029/2019WR025286>, 2020.
- François, B., Hingray, B., Hendrickx, F., and Creutin, J. D.: Seasonal patterns of water storage as signatures of the climatological equilibrium between resource and demand, *Hydrology and Earth System Sciences*, 18, 3787–3800, <https://doi.org/10.5194/hess-18-3787-2014>, 2014.
- García-Ruiz, J. M., López-Moreno, J. I., Vicente-Serrano, S. M., Lasanta-Martínez, T., and Beguería, S.: Mediterranean water resources in a global change scenario, *Earth-Science Reviews*, 105, 121–139, <https://doi.org/10.1016/j.earscirev.2011.01.006>, 2011.
- Gascoin, S., Ducharne, A., Ribstein, P., Carli, M., and Habets, F.: Adaptation of a catchment-based land surface model to the hydrogeological setting of the Somme River basin (France), *Journal of Hydrology*, 368, 105–116, <https://doi.org/10.1016/j.jhydrol.2009.01.039>, 2009.
- Gelati, E., Decharme, B., Calvet, J.-C., Minvielle, M., Polcher, J., Fairbairn, D., and Weedon, G. P.: Hydrological assessment of atmospheric forcing uncertainty in the Euro-Mediterranean area using a land surface model, *Hydrology and Earth System Sciences*, 22, 2091–2115, <https://doi.org/10.5194/hess-22-2091-2018>, 2018.
- Gou, J., Miao, C., Duan, Q., Tang, Q., Di, Z., Liao, W., Wu, J., and Zhou, R.: Sensitivity Analysis-Based Automatic Parameter Calibration of the VIC Model for Streamflow Simulations Over China, *Water Resources Research*, 56, e2019WR025968, <https://doi.org/10.1029/2019WR025968>, 2020.
- Greve, P., Burek, P., Guillaumot, L., van Meijgaard, E., Aalbers, E., Smilovic, M. M., Sperna-Weiland, F., Kahil, T., and Wada, Y.: Low flow sensitivity to water withdrawals in Central and Southwestern Europe under 2 K global warming, *Environmental Research Letters*, 18, 094020, <https://doi.org/10.1088/1748-9326/acec60>, 2023.

- Gudmundsson, L., Seneviratne, S., and Zhang, X.: Anthropogenic climate change detected in European renewable freshwater resources, *Nature Climate Change*, 7, 813–816, <https://doi.org/10.1038/nclimate3416>, 2017.
- Habets, F., Boone, A., Champeaux, J. L., Etchevers, P., Franchistéguy, L., Leblois, E., Ledoux, E., Le Moigne, P., Martin, E., Morel, S.,
610 Noilhan, J., Quintana Seguí, P., Rousset-Regimbeau, F., and Viennot, P.: The SAFRAN-ISBA-MODCOU hydrometeorological model applied over France, *Journal of Geophysical Research: Atmospheres*, 113, <https://doi.org/10.1029/2007JD008548>, 2008.
- Hall, D. K., Riggs, G. A., Salomonson, V. V., DiGirolamo, N. E., and Bayr, K. J.: MODIS snow-cover products, *Remote Sensing of Environment*, 83, 181–194, [https://doi.org/10.1016/S0034-4257\(02\)00095-0](https://doi.org/10.1016/S0034-4257(02)00095-0), 2002.
- Harper, K. L., Lamarche, C., Hartley, A., Peylin, P., Ottlé, C., Bastrikov, V., San Martín, R., Bohnenstengel, S. I., Kirches, G., Boettcher, M.,
615 Shevchuk, R., Brockmann, C., and Defourny, P.: A 29-year time series of annual 300 m resolution plant-functional-type maps for climate models, *Earth System Science Data*, 15, 1465–1499, <https://doi.org/10.5194/essd-15-1465-2023>, 2023.
- Hersbach, H., Bell, B., Berrisford, P., Hirahara, S., Horányi, A., Muñoz-Sabater, J., Nicolas, J., Peubey, C., Radu, R., Schepers, D., Simmons, A., Soci, C., Abdalla, S., Abellan, X., Balsamo, G., Bechtold, P., Biavati, G., Bidlot, J., Bonavita, M., De Chiara, G., Dahlgren, P., Dee, D., Diamantakis, M., Dragani, R., Flemming, J., Forbes, R., Fuentes, M., Geer, A., Haimberger, L., Healy, S., Hogan, R. J.,
620 Hólm, E., Janisková, M., Keeley, S., Laloyaux, P., Lopez, P., Lupu, C., Radnoti, G., de Rosnay, P., Rozum, I., Vamborg, F., Villaume, S., and Thépaut, J.-N.: The ERA5 global reanalysis, *Quarterly Journal of the Royal Meteorological Society*, 146, 1999–2049, <https://doi.org/10.1002/qj.3803>, 2020.
- Huang, P., Sauquet, E., Vidal, J.-P., and Riba, N. D.: Vulnerability of water resource management to climate change: Application to a Pyrenean valley, *Journal of Hydrology: Regional Studies*, 44, 101 241, <https://doi.org/10.1016/j.ejrh.2022.101241>, 2022.
- 625 Hurtt, G. C., Chini, L., Sahajpal, R., Frolking, S., Boudirsky, B. L., Calvin, K., Doelman, J. C., Fisk, J., Fujimori, S., Klein Goldewijk, K., Hasegawa, T., Havlik, P., Heinemann, A., Humpenöder, F., Jungclaus, J., Kaplan, J. O., Kennedy, J., Krisztin, T., Lawrence, D., Lawrence, P., Ma, L., Mertz, O., Pongratz, J., Popp, A., Poulter, B., Riahi, K., Shevliakova, E., Stehfest, E., Thornton, P., Tubiello, F. N., van Vuuren, D. P., and Zhang, X.: Harmonization of global land use change and management for the period 850–2100 (LUH2) for CMIP6, *Geoscientific Model Development*, 13, 5425–5464, <https://doi.org/10.5194/gmd-13-5425-2020>, 2020.
- 630 IPCC: Climate Change 2021 – The Physical Science Basis: Working Group I Contribution to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change, Cambridge University Press, <https://doi.org/10.1017/9781009157896>, 2023.
- Jacob, D., Petersen, J., Eggert, B., Alias, A., Christensen, O., Bouwer, L., Braun, A., Colette, A., Déqué, M., Georgievski, G., Georgopoulou, E., Gobiet, A., Menut, L., Nikulin, G., Haensler, A., Hempelmann, N., Jones, C., Keuler, K., Kovats, S., and Yiou, P.: EURO-CORDEX: New high-resolution climate change projections for European impact research, *Regional Environmental Change*, 14, 563–578,
635 <https://doi.org/10.1007/s10113-013-0499-2>, 2014.
- Janin, J.-L.: L'irrigation en France depuis 1988, *La Houille Blanche*, 82, 27–34, <https://doi.org/10.1051/lhb/1996083>, 1996.
- Jiang, L., Wu, H., Tao, J., Kimball, J. S., Alfieri, L., and Chen, X.: Satellite-Based Evapotranspiration in Hydrological Model Calibration, *Remote Sensing*, 12, <https://doi.org/10.3390/rs12030428>, 2020.
- Jiao, Y., Lei, H., Yang, D., Huang, M., Liu, D., and Yuan, X.: Impact of vegetation dynamics on hydrological processes in a semi-arid basin
640 by using a land surface-hydrology coupled model, *Journal of Hydrology*, 551, 116–131, <https://doi.org/10.1016/j.jhydrol.2017.05.060>, 2017.
- Jung, M., Koirala, S., Weber, U., Ichii, K., Gans, F., Camps-Valls, G., Papale, D., Schwalm, C., Tramontana, G., and Reichstein, M.: The FLUXCOM ensemble of global land-atmosphere energy fluxes, *Scientific Data*, 6, 74, <https://doi.org/10.1038/s41597-019-0076-8>, 2019.

- Kabir, T., Pokhrel, Y., and Felfelani, F.: On the Precipitation-Induced Uncertainties in Process-Based Hydrological Modeling in the Mekong River Basin, *Water Resources Research*, 58, e2021WR030828, <https://doi.org/10.1029/2021WR030828>, 2022.
- Kendall, M. G.: Rank correlation methods., Griffin, 1948.
- Kilic, D., Rivière, A., Gallois, N., Ducharne, A., Wang, S., Peylin, P., and Flipo, N.: Assessing water and energy fluxes in a regional hydrosystem: case study of the Seine basin, *Comptes Rendus. Géoscience*, pp. 1–21, <https://doi.org/10.5802/crgeos.165>, 2023.
- Kling, H., Fuchs, M., and Paulin, M.: Runoff conditions in the upper Danube basin under an ensemble of climate change scenarios, *Journal of Hydrology*, 424-425, 264–277, <https://doi.org/10.1016/j.jhydrol.2012.01.011>, 2012.
- Krinner, G., Viovy, N., de Noblet-Ducoudré, N., Ogée, J., Polcher, J., Friedlingstein, P., Ciais, P., Sitch, S., and Prentice, I. C.: A dynamic global vegetation model for studies of the coupled atmosphere-biosphere system, *Global Biogeochemical Cycles*, 19, <https://doi.org/10.1029/2003GB002199>, 2005.
- Le Moigne, P., Besson, F., Martin, E., Boé, J., Boone, A., Decharme, B., Etchevers, P., Faroux, S., Habets, F., Lafaysse, M., Leroux, D., and Rousset-Regimbeau, F.: The latest improvements with SURFEX v8.0 of the Safran–Isba–Modcou hydrometeorological model for France, *Geoscientific Model Development*, 13, 3925–3946, <https://doi.org/10.5194/gmd-13-3925-2020>, 2020.
- Ledoux, E., Girard, G., de Marsily, G., Villeneuve, J. P., and Deschenes, J.: Spatially Distributed Modeling: Conceptual Approach, *Coupling Surface Water And Groundwater*, pp. 435–454, Springer Netherlands, Dordrecht, https://doi.org/10.1007/978-94-009-2352-2_16, 1989.
- Leleu, I., Tonnelier, I., Puechberty, R., Gouin, P., Viquendi, I., Cobos, L., Foray, A., Baillon, M., and Ndima, P.-O.: La refonte du système d'information national pour la gestion et la mise à disposition des données hydrométriques, *La Houille Blanche*, pp. 25–32, <https://doi.org/10.1051/lhb/2014004>, 2014.
- Liu, H., Xin, X., Su, Z., Zeng, Y., Lian, T., Li, L., Yu, S., and Zhang, H.: Intercomparison and evaluation of ten global ET products at site and basin scales, *Journal of Hydrology*, 617, 128887, <https://doi.org/10.1016/j.jhydrol.2022.128887>, 2023.
- Loon, A. F. V., Rangecroft, S., Coxon, G., Werner, M., Wanders, N., Baldassarre, G. D., Tjrdeman, E., Bosman, M., Gleeson, T., Nauditt, A., Aghakouchak, A., Breña-Naranjo, J. A., Cenobio-Cruz, O., Costa, A. C., Fendekova, M., Jewitt, G., Kingston, D. G., Loft, J., Mager, S. M., Mallakpour, I., Masih, I., Maureira-Cortés, H., Toth, E., Oel, P. V., Ogtrop, F. V., Verbist, K., Vidal, J.-P., Wen, L., Yu, M., Yuan, X., Zhang, M., and Lanen, H. A. J. V.: Streamflow droughts aggravated by human activities despite management, *Environmental Research Letters*, 17, 044059, <https://doi.org/10.1088/1748-9326/ac5def>, 2022.
- López López, P., Sutanudjaja, E. H., Schellekens, J., Sterk, G., and Bierkens, M. F. P.: Calibration of a large-scale hydrological model using satellite-based soil moisture and evapotranspiration products, *Hydrology and Earth System Sciences*, 21, 3125–3144, <https://doi.org/10.5194/hess-21-3125-2017>, 2017.
- Lurton, T., Balkanski, Y., Bastrikov, V., Bekki, S., Bopp, L., Braconnot, P., Brockmann, P., Cadule, P., Contoux, C., Cozic, A., Cugnet, D., Dufresne, J.-L., Éthé, C., Foujols, M.-A., Ghattas, J., Hauglustaine, D., Hu, R.-M., Kageyama, M., Khodri, M., Lebas, N., Levavasseur, G., Marchand, M., Ottlé, C., Peylin, P., Sima, A., Szopa, S., Thiéblemont, R., Vuichard, N., and Boucher, O.: Implementation of the CMIP6 Forcing Data in the IPSL-CM6A-LR Model, *Journal of Advances in Modeling Earth Systems*, 12, e2019MS001940, <https://doi.org/10.1029/2019MS001940>, 2020.
- MacBean, N., Scott, R. L., Biederman, J. A., Ottlé, C., Vuichard, N., Ducharne, A., Kolb, T., Dore, S., Litvak, M., and Moore, D. J. P.: Testing water fluxes and storage from two hydrology configurations within the ORCHIDEE land surface model across US semi-arid sites, *Hydrology and Earth System Sciences*, 24, 5203–5230, <https://doi.org/10.5194/hess-24-5203-2020>, 2020.
- Mann, H. B.: Nonparametric tests against trend, *Econometrica: Journal of the econometric society*, pp. 245–259, 1945.

- Mardhel, V., Pinson, S., and Allier, D.: Description of an indirect method (IDPR) to determine spatial distribution of infiltration and runoff and its hydrogeological applications to the French territory, *Journal of Hydrology*, 592, 125–609, <https://doi.org/10.1016/j.jhydrol.2020.125609>, 2021.
- Martens, B., Miralles, D. G., Lievens, H., van der Schalie, R., de Jeu, R. A. M., Fernández-Prieto, D., Beck, H. E., Dorigo, W. A., and Verhoest, N. E. C.: GLEAM v3: satellite-based land evaporation and root-zone soil moisture, *Geoscientific Model Development*, 10, 1903–1925, <https://doi.org/10.5194/gmd-10-1903-2017>, 2017.
- McMillan, H. K.: A review of hydrologic signatures and their applications, *WIREs Water*, 8, e1499, <https://doi.org/10.1002/wat2.1499>, 2021.
- Milly, P. C. D., Betancourt, J., Falkenmark, M., Hirsch, R. M., Kundzewicz, Z. W., Lettenmaier, D. P., and Stouffer, R. J.: Stationarity Is Dead: Whither Water Management?, *Science*, 319, 573–574, <https://doi.org/10.1126/science.1151915>, 2008.
- Müller, J., Paudel, R., Shoemaker, C. A., Woodbury, J., Wang, Y., and Mahowald, N.: CH₄ parameter estimation in CLM4.5bgc using surrogate global optimization, *Geoscientific Model Development*, 8, 3285–3310, <https://doi.org/10.5194/gmd-8-3285-2015>, 2015.
- Nash, J. and Sutcliffe, J.: River flow forecasting through conceptual models part I — A discussion of principles, *Journal of Hydrology*, 10, 282–290, [https://doi.org/10.1016/0022-1694\(70\)90255-6](https://doi.org/10.1016/0022-1694(70)90255-6), 1970.
- Nguyen-Quang, T., Polcher, J., Ducharne, A., Arsouze, T., Zhou, X., Schneider, A., and Fita, L.: ORCHIDEE-ROUTING: revisiting the river routing scheme using a high-resolution hydrological database, *Geoscientific Model Development*, 11, 4965–4985, <https://doi.org/10.5194/gmd-11-4965-2018>, 2018.
- Oki, T. and Sud, Y. C.: Design of Total Runoff Integrating Pathways (TRIP)—A Global River Channel Network, *Earth Interactions*, 2, 1–37, [https://doi.org/10.1175/1087-3562\(1998\)002<0001:DOTRIP>2.3.CO;2](https://doi.org/10.1175/1087-3562(1998)002<0001:DOTRIP>2.3.CO;2), 1998.
- Oki, T., Nishimura, T., and Dirmeyer, P.: Assessment of Annual Runoff from Land Surface Models Using Total Runoff Integrating Pathways (TRIP), *Journal of the Meteorological Society of Japan. Ser. II*, 77, 235–255, https://doi.org/10.2151/jmsj1965.77.1B_235, 1999.
- Pokhrel, Y., Felfelani, F., Satoh, Y., Boulange, J., Burek, P., Gädeke, A., Gerten, D., Gosling, S., Grillakis, M., Gudmundsson, L., Hanasaki, N., Kim, H., Koutroulis, A., Liu, J., Papadimitriou, L., Schewe, J., Müller Schmied, H., Stacke, T., Telteu, C.-E., and Wada, Y.: Global terrestrial water storage and drought severity under climate change, *Nature Climate Change*, 11, 1–8, <https://doi.org/10.1038/s41558-020-00972-w>, 2021.
- Polcher, J., Schrapffer, A., Dupont, E., Rinchioso, L., Zhou, X., Boucher, O., Mouche, E., Ottlé, C., and Servonnat, J.: Hydrological modelling on atmospheric grids: using graphs of sub-grid elements to transport energy and water, *Geoscientific Model Development*, 16, 2583–2606, <https://doi.org/10.5194/gmd-16-2583-2023>, 2023.
- Prentice, I. C., Liang, X., Medlyn, B. E., and Wang, Y.-P.: Reliable, robust and realistic: the three R’s of next-generation land-surface modelling, *Atmospheric Chemistry and Physics*, 15, 5987–6005, <https://doi.org/10.5194/acp-15-5987-2015>, 2015.
- Priestley, C. H. B. and Taylor, R. J.: On the Assessment of Surface Heat Flux and Evaporation Using Large-Scale Parameters, *Monthly Weather Review*, 100, 81–92, [https://doi.org/10.1175/1520-0493\(1972\)100<0081:OTAOSH>2.3.CO;2](https://doi.org/10.1175/1520-0493(1972)100<0081:OTAOSH>2.3.CO;2), 1972.
- Quintana Seguí, P., Martin, E., Habets, F., and Noilhan, J.: Improvement, calibration and validation of a distributed hydrological model over France, *Hydrology and Earth System Sciences*, 13, 163–181, <https://doi.org/10.5194/hess-13-163-2009>, 2009.
- Rajib, A., Evenson, G. R., Golden, H. E., and Lane, C. R.: Hydrologic model predictability improves with spatially explicit calibration using remotely sensed evapotranspiration and biophysical parameters, *Journal of Hydrology*, 567, 668–683, <https://doi.org/10.1016/j.jhydrol.2018.10.024>, 2018a.
- Rajib, A., Merwade, V., and Yu, Z.: Rationale and Efficacy of Assimilating Remotely Sensed Potential Evapotranspiration for Reduced Uncertainty of Hydrologic Models, *Water Resources Research*, 54, 4615–4637, <https://doi.org/10.1029/2017WR021147>, 2018b.

- Raoult, N., Ottlé, C., Peylin, P., Bastrikov, V., and Maugis, P.: Evaluating and Optimizing Surface Soil Moisture Drydowns in the ORCHIDEE Land Surface Model at In Situ Locations, *Journal of Hydrometeorology*, 22, 1025–1043, <https://doi.org/10.1175/JHM-D-20-0115.1>, 2021.
- 720 Reynolds, C. A., Jackson, T. J., and Rawls, W. J.: Estimating soil water-holding capacities by linking the Food and Agriculture Organization Soil map of the world with global pedon databases and continuous pedotransfer functions, *Water Resources Research*, 36, 3653–3662, <https://doi.org/10.1029/2000WR900130>, 2000.
- Ruiz-Vásquez, M., O, S., Arduini, G., Boussetta, S., Brenning, A., Bastos, A., Koirala, S., Balsamo, G., Reichstein, M., and Orth, R.: Impact of Updating Vegetation Information on Land Surface Model Performance, *Journal of Geophysical Research: Atmospheres*, 128, e2023JD039076, <https://doi.org/10.1029/2023JD039076>, 2023.
- 725 Rumlmer, T., Wagner, A., Arnault, J., and Kunstmann, H.: Lateral terrestrial water fluxes in the LSM of WRF-Hydro: Benefits of a 2D groundwater representation, *Hydrological Processes*, 36, e14510, <https://doi.org/10.1002/hyp.14510>, 2022.
- Samaniego, L., Kumar, R., and Attinger, S.: Multiscale parameter regionalization of a grid-based hydrologic model at the mesoscale, *Water Resources Research*, 46, W05523, <https://doi.org/10.1029/2008WR007327>, 2010.
- 730 Santos, L., Thirel, G., and Perrin, C.: Technical note: Pitfalls in using log-transformed flows within the KGE criterion, *Hydrology and Earth System Sciences*, 22, 4583–4591, <https://doi.org/10.5194/hess-22-4583-2018>, 2018.
- Schaperow, J., Li, D., Margulis, S., and Lettenmaier, D.: A near-global, high resolution land surface parameter dataset for the variable infiltration capacity model, *Scientific Data*, 8, 216, <https://doi.org/10.1038/s41597-021-00999-4>, 2021.
- 735 Schneider, A., Jost, A., Coulon, C., Silvestre, M., Théry, S., and Ducharne, A.: Global-scale river network extraction based on high-resolution topography and constrained by lithology, climate, slope, and observed drainage density, *Geophysical Research Letters*, 44, 2773–2781, <https://doi.org/10.1002/2016GL071844>, 2017.
- Schrapffer, A., Sörensson, A., Polcher, J., and Fita, L.: Benefits of representing floodplains in a Land Surface Model: Pantanal simulated with ORCHIDEE CMIP6 version, *Climate Dynamics*, 55, 1303–1323, <https://doi.org/10.1007/s00382-020-05324-0>, 2020.
- 740 Sen, P. K.: Estimates of the Regression Coefficient Based on Kendall's Tau, *Journal of the American Statistical Association*, 63, 1379–1389, 1968.
- Song, J.-H., Her, Y., Park, J., and Kang, M.-S.: Exploring parsimonious daily rainfall-runoff model structure using the hyperbolic tangent function and Tank model, *Journal of Hydrology*, 574, 574–587, <https://doi.org/10.1016/j.jhydrol.2019.04.054>, 2019.
- Su, Z.: The Surface Energy Balance System (SEBS) for estimation of turbulent heat fluxes, *Hydrology and Earth System Sciences*, 6, 85–100, <https://doi.org/10.5194/hess-6-85-2002>, 2002.
- 745 Su, Z., Schmugge, T., Kustas, W. P., and Massman, W. J.: An Evaluation of Two Models for Estimation of the Roughness Height for Heat Transfer between the Land Surface and the Atmosphere, *Journal of Applied Meteorology*, 40, 1933–1951, [https://doi.org/10.1175/1520-0450\(2001\)040<1933:AEOTMF>2.0.CO;2](https://doi.org/10.1175/1520-0450(2001)040<1933:AEOTMF>2.0.CO;2), 2001.
- Sun, R., Hernández, F., Liang, X., and Yuan, H.: A Calibration Framework for High-Resolution Hydrological Models Using a Multiresolution and Heterogeneous Strategy, *Water Resources Research*, 56, e2019WR026541, <https://doi.org/10.1029/2019WR026541>, 2020.
- 750 Sutanudjaja, E. H., van Beek, L. P. H., de Jong, S. M., van Geer, F. C., and Bierkens, M. F. P.: Calibrating a large-extent high-resolution coupled groundwater-land surface model using soil moisture and discharge data, *Water Resources Research*, 50, 687–705, <https://doi.org/10.1002/2013WR013807>, 2014.
- Tafasca, S., Ducharne, A., and Valentin, C.: Weak sensitivity of the terrestrial water budget to global soil texture maps in the ORCHIDEE land surface model, *Hydrology and Earth System Sciences*, 24, 3753–3774, <https://doi.org/10.5194/hess-24-3753-2020>, 2020.
- 755

- Telteu, C.-E., Müller Schmied, H., Thiery, W., Leng, G., Burek, P., Liu, X., Boulange, J. E. S., Andersen, L. S., Grillakis, M., Gosling, S. N., Satoh, Y., Rakovec, O., Stacke, T., Chang, J., Wanders, N., Shah, H. L., Trautmann, T., Mao, G., Hanasaki, N., Koutroulis, A., Pokhrel, Y., Samaniego, L., Wada, Y., Mishra, V., Liu, J., Döll, P., Zhao, F., Gädeke, A., Rabin, S. S., and Herz, F.: Understanding each other's models: an introduction and a standard representation of 16 global water models to support intercomparison, improvement, and communication, *Geoscientific Model Development*, 14, 3843–3878, <https://doi.org/10.5194/gmd-14-3843-2021>, 2021.
- 760
- Ting, K. M.: Confusion Matrix, pp. 209–209, Springer US, Boston, MA, https://doi.org/10.1007/978-0-387-30164-8_157, 2010.
- Todorović, A., Grabs, T., and Teutschbein, C.: Advancing traditional strategies for testing hydrological model fitness in a changing climate, *Hydrological Sciences Journal*, 67, 1790–1811, <https://doi.org/10.1080/02626667.2022.2104646>, 2022.
- Troy, T. J., Wood, E. F., and Sheffield, J.: An efficient calibration method for continental-scale land surface modeling, *Water Resources Research*, 44, <https://doi.org/10.1029/2007WR006513>, 2008.
- 765
- van Kempen, G., van der Wiel, K., and Melsen, L. A.: The impact of hydrological model structure on the simulation of extreme runoff events, *Natural Hazards and Earth System Sciences*, 21, 961–976, <https://doi.org/10.5194/nhess-21-961-2021>, 2021.
- Vergnes, J.-P. and Decharme, B.: A simple groundwater scheme in the TRIP river routing model: global off-line evaluation against GRACE terrestrial water storage estimates and observed river discharges, *Hydrology and Earth System Sciences*, 16, 3889–3908, <https://doi.org/10.5194/hess-16-3889-2012>, 2012.
- 770
- Vicente-Serrano, S. M., Peña-Gallardo, M., Hannaford, J., Murphy, C., Lorenzo-Lacruz, J., Dominguez-Castro, F., López-Moreno, J. I., Beguería, S., Noguera, I., Harrigan, S., and Vidal, J.-P.: Climate, Irrigation, and Land Cover Change Explain Streamflow Trends in Countries Bordering the Northeast Atlantic, *Geophysical Research Letters*, 46, 10 821–10 833, <https://doi.org/10.1029/2019GL084084>, 2019.
- 775
- Vidal, J.-P., Martin, E., Franchistéguy, L., Baillon, M., and Soubeyroux, J.-M.: A 50-year high-resolution atmospheric reanalysis over France with the Safran system, *International Journal of Climatology*, 30, 1627–1644, <https://doi.org/10.1002/joc.2003>, 2010a.
- Vidal, J.-P., Martin, E., Franchistéguy, L., Habets, F., Soubeyroux, J.-M., Blanchard, M., and Baillon, M.: Multilevel and multiscale drought reanalysis over France with the Safran-Isba-Modcou hydrometeorological suite, *Hydrology and Earth System Sciences*, 14, 459–478, <https://doi.org/10.5194/hess-14-459-2010>, 2010b.
- 780
- Wang, T., Ottlé, C., Boone, A., Ciais, P., Brun, E., Morin, S., Krinner, G., Piao, S., and Peng, S.: Evaluation of an improved intermediate complexity snow scheme in the ORCHIDEE land surface model, *Journal of Geophysical Research: Atmospheres*, 118, 6064–6079, <https://doi.org/10.1002/jgrd.50395>, 2013.
- Yamazaki, D., Ikeshima, D., Sosa, J., Bates, P. D., Allen, G. H., and Pavelsky, T. M.: MERIT Hydro: A High-Resolution Global Hydrography Map Based on Latest Topography Dataset, *Water Resources Research*, 55, 5053–5073, <https://doi.org/10.1029/2019WR024873>, 2019.
- 785
- Yang, K., Zhu, L., Chen, Y., Zhao, L., Qin, J., Lu, H., Tang, W., Han, M., Ding, B., and Fang, N.: Land surface model calibration through microwave data assimilation for improving soil moisture simulations, *Journal of Hydrology*, 533, 266–276, <https://doi.org/10.1016/j.jhydrol.2015.12.018>, 2016.
- Yang, Y., Guan, K., Peng, B., Pan, M., Jiang, C., and Franz, T. E.: High-resolution spatially explicit land surface model calibration using field-scale satellite-based daily evapotranspiration product, *Journal of Hydrology*, 596, 125 730, <https://doi.org/10.1016/j.jhydrol.2020.125730>, 2021.
- 790
- Zeng, R. and Cai, X.: Hydrologic Observation, Model, and Theory Congruence on Evapotranspiration Variance: Diagnosis of Multiple Observations and Land Surface Models, *Water Resources Research*, 54, 9074–9095, <https://doi.org/10.1029/2018WR022723>, 2018.

Zhou, X., Polcher, J., and Dumas, P.: Representing Human Water Management in a Land Surface Model Using a Supply/Demand Approach, *Water Resources Research*, 57, e2020WR028133, <https://doi.org/10.1029/2020WR028133>, 2021.