

Evolution of low-karstified rock-blocks and their influence on reservoir leakage: a modelling perspective

Youjun Jiao^{1, 2, 3, 4}, Franci Gabrovšek^{3, 5}, Xusheng Wang¹, Qingchun Yu¹

¹Beijing Key Laboratory of Water Resources and Environmental Engineering, School of Water Resources and Environment, China University of Geosciences (Beijing), Beijing 100083, China

²Institute of Karst Geology, CAGS/ Key Laboratory of Karst Dynamics, MNR & GZAR/ International Research Centre on Karst under the Auspices of UNESCO, Guilin, Guangxi 541004, China

³Karst Research Institute ZRC SAZU, Titov trg 2, Postojna 6230, Slovenia

⁴Pingguo Guangxi, Karst Ecosystem, National Observation and Research Station, Pingguo, Guangxi 531406, China

⁵Faculty of Mathematics and Physics, University of Ljubljana, Jadranska ulica 19, Ljubljana 1000, Slovenia

Correspondence to: Qingchun Yu (yuqch@cugb.edu.cn) and Franci Gabrovšek (franci.gabrovsek@zrc-sazu.si)

Abstract. Hydraulic structures such as dams and reservoirs pose significant construction challenges in karst areas due to severe and costly leakage issues. In this study, we apply a numerical model to test the hypothesis that karst aquifers in water divide areas may contain intrinsically low-karstified rock-blocks (LKB), which form due to the specific evolution of unconfined aquifer with recharge distributed to the water table. We develop, test, and apply a model of flow, transport, and dissolution in a 2D fracture network with a fluctuating water table. The model's structure and boundary conditions are based on the conceptualization of the Luojiaao (China) interfluvial aquifer. First, we simulate the evolution of an unconfined network, representing the interfluvial, up to a stage resembling the present conditions at Luojiaao. We then analyse leakage through the evolved aquifer from a reservoir at different water levels and simulate further aquifer evolution under reservoir conditions. Our results demonstrate the formation of the LKB and highlight its role in mitigating leakage.

1 Introduction

Karst areas occupy approximately 14% of Earth's ice-free land surface. In these regions, the chemical erosion of rock by surface water and groundwater—known as karstification—produces distinctive surface and subsurface features. Karst aquifers are among the most productive freshwater resources, supplying drinking water to around 20% of the world's population—and more than 50% in some countries (Chen et al., 2017; Ford and Williams, 2007). These aquifers are characterized by networks of solution conduits formed within initially fractured and porous rock. The development of these

conduits, a process known as speleogenesis, is complex and spans nearly the entire period during which the rock is exposed to groundwater circulation (Dreybrodt, 1996; Yuan et al., 1993).

Karst aquifers can be conceptualized as hierarchically organized conduit systems embedded within a fractured porous matrix. These conduits serve as high-transmissivity flow pathways, channelling water from points of recharge to karst springs. Karstified rocks are also widespread in young orogenic belts, where the high-relief terrain provides favourable elevation differences that facilitate the construction of hydraulic structures such as dams and reservoirs (Milanović, 2000; Yuan et al., 1993; Shen et al., 1997).

However, the construction hydraulic structures in karst areas pose significant engineering challenges. The position, size, and connectivity of existing networks of solution conduits are extremely difficult to predict or detect. As a result, the extent of initial leakage from a reservoir is also hard to estimate (Milanović, 2000, 2018). Furthermore, the high hydraulic gradients induced by such structures can accelerate the formation of new conductive pathways, potentially leading to a rapid increase in leakage—sometimes reaching intolerable levels within the operational lifespan of the structure (Dreybrodt, 1996; Gabrovšek and Dreybrodt, 2001, 2010; Romanov et al., 2003, 2007).

Basic flow solutions in unconfined porous aquifers with constant recharge as shown in Figure 1a, suggest a relatively stagnant flow zone in water divide area (Rhoades and Sinacori, 1941; Tóth, 1962; Liang et al., 2010). Studies on porous aquifers have revealed a zone of low permeability in divide areas, characterized by slower flow velocities (Kang et al., 2003; Wang et al., 2011; Jiang et al., 2012; Nogues et al., 2013). This also applies to fractured aquifer and can have important implication for karstification, where low flow zone may also result in less karstified zone, as shown in Figure 1b. Such low-karstified rock-blocks (LKB) have been recognised in water divide regions of real karst aquifers and proven to be effective in mitigation of leakage from reservoirs in karst areas (Yuan et al., 1993; Milanović, 2000; Xu and Yan, 2004). The LKB means that there is a relatively low permeable region formed in the middle of karst aquifer during the natural karst evolution.

The concept is illustrated in Figure 1, showing a low karstified block formed in the water divide region during natural karstification (Figures 1a and 1b). As depicted in Figure 1c, this zone can effectively mitigate leakage from man-made reservoirs.




Figure 1. Simplified cross section of an unconfined aquifer in water divide region. (a) Low flow zone in the water divide area. (b) Karstification increases permeability and progressively lowers the water table over time, but leaves the water divide zone less karstified (LKB). (c) In case of reservoir construction, the LKB can effectively mitigate leakage across the aquifer. (Modified from Zhang et al., 2018).

Due to the intricate nature of karst leakage, there have been limited reports on quantitative modelling studies of this phenomenon (Milanović, 2000, 2018; Smerdon et al., 2005). Modelling karst aquifer leakage is a challenging endeavour, often deemed impractical despite its importance for engineering planning. In engineering construction, predictions of

reservoir leakage primarily rely on geological surveys and field experiments. For example, one study analysed extensive observational data and predicted that leakage would remain minimal (Yuan et al., 2002; Shen et al., 1997).

To model evolution of karst aquifers, it is essential to simulate flow, dissolution, and transport processes within soluble fractured media. When modelling an unconfined aquifer that includes a water divide, the problem involves a free surface, requiring the determination of the water table position at each time step of the model. Some studies have addressed this by treating discrete fractures as equivalent continuum media (Desai and Li, 1983). However, such models are unable to capture the processes of fracture dissolution and widening. Several studies have reported on modelling discrete fracture flow with free surfaces. For instance, Wang (1993) employed an initial flux method to locate the free surface within the fracture system, while Jing et al. (2001) used a discontinuous deformation analysis (DDA) method for modelling fracture flow. These intuitive methods often encounter numerical instability due to their lack of a solid mathematical foundation. The variational inequality method, which introduces the continuous Heaviside function in the finite element method, has proven effective in modelling the free surface in discrete fractures (Zheng et al., 2005; Jiang et al., 2013). But these models do not consider situations with recharge to the water table.

Several models have been used to simulate the evolution of unconfined karst aquifers with constant recharge at the water table (Clemens et al., 1999; Gabrovšek and Dreybrodt, 2001, 2010, 2021; Kaufmann, 2003; Dreybrodt et al., 2005). As demonstrated in these works, the evolution of unconfined karst aquifers is most pronounced near the water table. These models do not explicitly account for the details of flow and dissolution in the vadose zone—the region between the surface and the water table—but instead assume gravitational flow that reaches a specific level of chemical saturation with respect to calcite. Nevertheless, within the phreatic zone, water is typically least saturated with respect to calcite near the water table, and thus possesses the highest potential for dissolution (often referred as aggressivity) in this region. The numerical methods employed in these studies primarily focus on the evolution of relatively homogeneous fracture networks, rather than on the randomly distributed fractures typical of natural karst aquifers.

In this work, we introduce a numerical model to study the evolution of karst aquifer under distributed (rainfall) recharge. The algorithm is built upon an earlier study by Yu et al. (1999). We propose an intuitive method that uses iterative search for the water table and couples flow, transport and dissolution to simulate evolution of discrete fracture network. We

first simulate the natural evolution of the aquifer under rainfall recharge up to selected stage of maturity. Then, the obtained
85 aquifer is subjected to boundary conditions imposed by the construction of the reservoir. We analyse how the LKB has
evolved and assess its effectiveness in mitigating leakage from the reservoir.

2 Modelling evolution of unconfined discrete fracture network

Models of fracture networks' karstification necessitate the integration of flow, dissolution, and transport processes
within the system, while adhering to specified hydraulic and hydrochemical boundary conditions. In our research, we
90 simulate the evolution of a stochastic fracture network under constant recharge and fixed head boundary conditions. The
computational procedure is shown in flowchart of Figure 2 and outlined as follows:

- (1) Generate random fracture network and boundary conditions;
- (2) Locate the water table and compute the flow within the network;
- (3) Calculate dissolution and solute transport;
- 95 (4) Update fracture apertures: compute the changes in the width of each fracture within the specified time step;
- (5) Iterate or terminate: proceed to the next time step and repeat steps 2 to 4, or terminate the simulation as required.




Figure 2. The flowchart of the whole modelling process. At each time step, the new position of the water table is determined
through an iterative process. Subsequently, the coupled flow, dissolution, and transport equations are solved at both the
100 individual fracture scale and the fracture network scale. Based on these results, the fracture apertures are updated accordingly.

The modified fracture network then serves as the basis for calculations in the following time step.

2.1 Flow in fractures

2.1.1 Fracture network generation

The initial fracture network is created through Monte Carlo stochastic simulation, as described by Yu et al. (1999). Fracture parameters, including centre location, length, aperture, and direction, are randomly generated using Gaussian and lognormal distributions. Subsequently, the algorithm searches for fracture intersections (nodes) and excludes all dead end segments, which do not contribute to flow. In this work the fractures are uniform plan parallel planes, defined by length and aperture.

2.1.2 Flow in one fracture

When a fracture with length L_{ij} and aperture b_{ij} connects nodes i and j with hydraulic heads H_i and H_j , respectively, the flow rate q_{ij} within the fracture conforms to the cubic law for laminar flow, whereas for turbulent flow, the Lomize equation (Lomize, 1951) is used to relate the flow rate to the hydraulic gradient J_{ij} .

$$q_{ij} = \frac{g b_{ij}^3}{12 \nu} J, \quad Re < 2020 \quad (1)$$

$$q_{ij} = 4.7 \sqrt[7]{\frac{g^4}{\nu} b_{ij}^{12} J^4}, \quad Re > 2020 \quad (2)$$

$$J_{ij} = \frac{H_i - H_j}{L_{ij}} \quad (3)$$

where g is the gravitational acceleration, ν is the kinematic viscosity of water, and Re is Reynolds number. The transition from the laminar to the turbulent flow regime is here introduced at the point where turbulent frictional losses exceed those associated with laminar flow. The factor in Lomize equation (Eq. 2) is set so that transition occurs at a Reynolds number around 2020. This simplification omits the transitional flow zone, resulting in a smooth increase in flow rates as turbulence sets in (Su et al., 1994; Finenko and Konietzky, 2024). However, in simulations presented in this work, flow always remains laminar.

2.2 Solution for water table in random fractures under distributed uniform recharge conditions

Each evolution time step requires the calculation of flow, dissolution, solute transport, and the corresponding changes in fracture aperture. Accurate flow calculation depends on determining the position of the water table at each time step. This

is achieved through an iterative process, in which the water table position is updated until specific convergence criteria are met, as described in Section 2.2.2. The procedure is illustrated in Figure 3. At each iteration, the current approximation of the water table defines a set of boundary conditions (Figure 3a): prescribed recharge at water table nodes, seepage face
125 (boundary nodes, where hydraulic head equals the elevation), and constant-head conditions elsewhere. The flow solver (*confined flow solution*) is then invoked to compute flow rates and hydraulic heads at all nodes. Water table nodes are subsequently searched node by node within each layer (Figure 3b, *node-by-node iteration*) and layer-by-layer throughout the domain (Figure 3c, *layer-by-layer iteration*).




Figure 3. Conceptual presentation of flow calculation in the fracture network. (a) Boundary conditions for confined flow calculation performed at every iterative step. (b) Node-by-node iteration: testing wetting of a dry node across a layer. (c) Layer-by-layer iteration.

2.2.1 Confined flow solution

During each node-by-node iteration, an approximate water table is used to classify boundary nodes as having either a specified head, a prescribed recharge, or as part of the seepage face. At every node, a flow balance must be satisfied:

$$\sum q_{ij} + \sum q_w = 0 \quad (4)$$

Where the first part is the sum of flow from/to all inner (non-boundary) nodes (see Eqs. 1-2) and the second part is the sum of direct recharge q_w from the vadose zone, applied to the water table nodes.

Assuming that the equations are non-linear, we use the Newton–Raphson iteration to solve the system of equations, with convergence criteria as follows:

$$\Delta H_{\max} \leq H_{\text{tol}}, \text{ for } \Delta H_{\max} = \max (| \Delta \mathbf{H}_{\text{error}} |) \quad (5)$$

$$Q_{\text{erro}} \leq Q_{\text{tol}}, \text{ for } Q_{\text{erro}} = \sum q \quad (6)$$

where $\Delta \mathbf{H}_{\text{error}}$ is the water head error vector between the n and $n+1$ iterations. $\mathbf{H}$ is the water head vector. $\Delta H_{\max}$ is the maximum water head difference between two iterations and H_{tol} is the allowable error. Q_{erro} is the sum of water flow budget of all inner nodes, and Q_{tol} is the allowable error.

The difference in the water heads between two iterations and the water budget is checked to validate the flow results. When $\Delta H_{\max}$ is less than the allowable error H_{tol} and the water budget Q_{erro} is less than the allowable error Q_{tol} , the iteration converges. The C++ open source linear algebra package Armadillo (Sanderson and Curtin, 2016, 2019) was employed to perform matrix computation.

2.2.2 The node-by-node and layer-by-layer iterations: search for the water table

One of the challenges in modelling unconfined aquifers with distributed recharge lies in accurately identifying the water table. In the presence of dissolution and increasing permeability of fractured media, the water table changes in time also when recharge is constant. We use a robust “intuitive” algorithm for computing the position of a water table as shown in Figure 3. The algorithm employs a two-level iterative strategy: (1) layer-by-layer iterations and (2) node-by-node iterations within each layer. When the algorithm solving for the confined water head is included, the method effectively operates as a three-level iterative strategy, ensuring robustness and accuracy in resolving wetting and free surface dynamics. The algorithm is applied for all time-steps of a simulation.

155 **Step 0:** Initially, the water table is positioned at the lowest constant head boundary in the domain (Figure 3a). The nodes of the water table receive direct recharge from the vadose zone. The heads at all nodes in the phreatic part are calculated by above described confined flow solution.

Step 1: Dry nodes, directly connected to water table nodes are identified. For each pair, the difference between the hydraulic head of the nearest water table node H_i^{WT} and the elevation of the dry node z_j^D is calculated as $\Delta_{ij}=H_i^{WT}-z_j^D$. These
160 differences are then sorted into an ordered sequence.

Step 2: Following the sequence each dry node is changed to a water table node and the heads are recalculated by confined flow solver, assuming new boundary conditions with constant input to the new WT node (Figure 3b). If the head at the node is higher than its elevation, and no other wet node becomes dry, the transition of the node from dry to wet is kept. Otherwise, the node remains dry and the procedure continues with the next node in the sorted sequence.

165 **Step 3:** Repeat Steps 1 and 2 layer by layer until no dry node becomes wet (Figure 3c).

The numerical model was verified successfully against a MODFLOW model and an analytical model using the Dupuit assumption. Please see the Supplements for details.

2.3 Dissolution widening of fractures

The dissolution rates of limestone under both laminar and turbulent flow conditions have been the focus of extensive
170 research (Dreybrodt, 1990, 1996; Liu and Dreybrodt, 1997; Eisenlohr et al., 1999; Dreybrodt and Kaufmann, 2007). These rates are governed by a complex interplay of surface reactions, transport mechanisms, and CO₂ conversion processes (Dijk et al., 2002; Detwiler and Rajaram, 2007). In this study, we adopt the rate equations developed by Dreybrodt (1996):

$$F(c)=k_1\left(1-\frac{C}{C_{eq}}\right), (C<C_s) \quad (7)$$

$$F(c)=k_n\left(1-\frac{C}{C_{eq}}\right)^n, (C>0.9C_s, n>1) \quad (8)$$

Where k_1 and k_n are rate constants (in mol cm⁻² s⁻¹), C represents the concentration of Ca²⁺ ions (in mol L⁻¹), and C_{eq} denotes the equilibrium concentration in the H₂O-CO₂-CaCO₃ system. The C_{eq} is determined by the concentrations of
175 calcium and dissolved CO₂ in the solution at the water table. These concentrations result from complex flow and dissolution processes occurring from the surface down to the water table—including flow and reactions within the soil, epikarst, and

vadose zone—which are beyond the scope of this study. The reaction follows a linear rate law up to the switch concentration C_s , transitioning to a nonlinear rate law between C_s and C_{eq} . Here we assume that rates are entirely controlled by surface reaction, and ignore the concentration gradient perpendicular to flow. This approximation is valid for situations where the solutions are close to equilibrium (Gabrovšek, 2000), which is mostly the case in the presented scenarios (Yuan et al., 2002; Wan et al., 1999). The reaction order n and the switch concentration C_s are experimentally determined and influenced by the impurity content in the limestone (Eisenlohr et al., 1999). Experimental studies have reported reaction orders ranging from 3 to 11. For this study, we use $n = 4$, $C_s = 0.9C_{eq}$, $k_1 = 4 \times 10^{-11} \text{ mol} \cdot \text{cm}^{-2} \cdot \text{s}^{-1}$, and $k_4 = 4 \times 10^{-8} \text{ mol} \cdot \text{cm}^{-2} \cdot \text{s}^{-1}$ (Gabrovšek and Dreybrodt, 2000; Dreybrodt et al., 2005). Studies on the dissolution kinetics of calcium carbonate minerals under turbulent flow (Buhmann and Dreybrodt, 1985a, 1985b; Liu and Dreybrodt, 1997) indicate that the rate constant in turbulent conditions is an order of magnitude greater than that under laminar flow.

The change in concentration ΔC along an individual fracture can be determined by applying the principle of mass conservation within a water parcel passing along the fracture. This can be analytically calculated for a plane parallel fracture, as shown in the Supplements. The change in concentration along the fracture is converted to mass removed from the fracture walls and the change of aperture during time Δt :

$$\Delta b = \frac{\Delta C q M_{\text{CaCO}_3}}{\rho L} \Delta t \quad (9)$$


Where L is the fracture length, ρ is the density of calcite (2.5 g/cm^3), M_{CaCO_3} is the molar mass of calcite (100 g/mol), and q is the flow rate.

To calculate the change in concentration along a fracture, the calcium concentration at the input node must be known. This input concentration is determined as the flow-weighted average of all inflows to that node. To ensure that all required concentrations are available when needed, the computation proceeds in a cascading sequence, starting from nodes with the highest hydraulic heads and moving downstream (see the Supplements). A uniform widening rate is assumed along each fracture. Once the fracture apertures in the entire phreatic zone are updated to reflect dissolution widening within a time step, the evolution time step is completed.

3 Karstification of an unconfined interfluvial aquifer with uniform recharge

200 As an example of an aquifer, where the concept of LKB formation can be applied is Luojiang interfluvial aquifer, located between the two reaches of the Qingjiang river meander. Hubei Province, China (Figure 4a and b). On the western side of the interfluvial, the Geheyan Reservoir was constructed, which is one of three karst reservoirs along the river (Xu and Yan, 2004). The water level in the reservoir is above the original water divide, which was determined by boreholes (Figure 4c). However, the leakage and its trend could not be determined with field methods.

205 Previous studies (Yuan et al., 2002; Shen et al., 1997; Wan et al., 1999) revealed cave development near both riverbeds, with an absence of caves in the water divide region. Although we lack knowledge on the possible previous karstification stages at this particular site, we expect that the water divide in the interfluvial is a result of karstification under rainfall recharge, and that the LKB may play a crucial role in reservoir leakage.



210 **Figure 4.** Location and setting of the Geheyang Reservoir, situated on the upstream side of a bend in the Qingjiang River, Changyang County, Hubei Province, China. (a) The location of Geheyang Reservoir. (b) Simplified map of the reservoir area and Luojiaao interfluvial aquifer (marked by a dashed rectangle in figure a). (c) Cross-section through the Luojiaao interfluvial aquifer along the line AB in figure b. The dashed line shows position of the water table before the reservoir construction.

215 **3.1 Construction of conceptual and numerical model of an initial aquifer**

The conceptual model, translated into a numerical one, is based on a simplified interpretation of field mapping data. The modelled domain represents a two-dimensional cross-section of a fractured limestone aquifer, 2000 m in length and 500 m in height. The initial conductive structures are gently dipping bedding planes (8–10 °) and a set of near-vertical fractures with an average dip of 85 °, both generated randomly using the statistical parameters listed in Table 1. Their initial
220 apertures are uniformly distributed, with a mean value of 0.01 cm. After identifying fracture intersections (nodes) and removing all dead-end segments, the resulting fracture network consists of 4,073 intersection nodes and 7,401 fracture segments, with segment lengths ranging from 0.01 m to 143 m. The average segment length is 15.74 m.

Boundary conditions include a constant hydraulic head of 100 m applied to the left and right sides of the domain (from elevations –100 m to 100 m), and seepage boundaries between 100 m and 400 m elevation. A uniform infiltration rate of
225 200 mm/year is applied to the water table nodes.

Reconstructing hydrogeochemical boundary conditions at the water table is inherently challenging. Based on measurements of soil CO₂ and Ca²⁺ concentrations from three boreholes and two springs, we assume a closed-system equilibrium concentration (C_{eq}) of 2 mmol/L (Yuan et al., 2002; Wan et al., 1999). The saturation ratio of infiltrating water is assumed to be $C_{in} / C_{eq} = 0.92$. The total simulation time is set to 100,000 years, with model convergence evaluated at each
230 time step.

Table 1 Statistical parameters of the original fractures

group	parameter	distribution	mean	standard deviation	min	max
1	direction (°)	Gaussian	11	1	9	13
	length (m)	lognormal	240	5	220	260

	aperture (cm)	uniform	0.01	/	0.008	0.012
	direction (°)	Gaussian	85	2	82	88
2	length (m)	lognormal	240	5	220	260
	aperture (cm)	uniform	0.01	/	0.008	0.012

3.2 Model of karstification under distributed uniform recharge




Figure 5. The initial aquifer (a), and aquifer after 10 ka (thousand years) (b) and 20 ka (c) of evolution. The widths of
235 the lines present the aperture, colours the head and arrows the flow direction. To facilitate the discussion the aquifer is
divided into 3 primary vertical sections and each of them into 5 horizontal subsections, as shown in panels a and d.

The modelling results are shown in Figure 5. We observe the expected drop of water table due to increasing
transmissivity of the aquifer. The groundwater divide remained close to the middle of the domain, whilst the elevation of the
240 highest wet node, which represents the divide ridge, descended from 350 m to 230 m at 10 ka and to 185 m at 20 ka.

As expected, there is a fringe of high dissolution rates close to the water table. Below the water table, the fracture
widening is relatively slow. As the water table gradually decreases, the fringe of high dissolution rates migrates vertically
through the aquifer and increases the hydraulic conductivity.

3.3 Changes in fracture aperture and discharge during karstification




Figure 6. Evolution of fracture apertures under natural karstification at 0 ka (thousand years) (a), at 10 ka (b) and at 20 ka (c).




Figure 7. The box-whisker plot of fracture aperture under natural evolution for 20 thousand years in three primary

sections (see Figure 5).

The fracture aperture distributions at three evolution time steps are shown in Figure 6. To facilitate the discussion, we have divided the aquifer into 15 subsections along three vertical primary sections, as shown in Figure 5a. The variation of aperture statistics in three vertical sections is shown in Figure 7. The water table with dissolution fringe mainly descends through the upper section, which experience the evident change in aperture (Gabrovšek and Dreybrodt, 2001; Hubinger and Birk, 2011).




Figure 8. The relative change in the average aperture b/b_0 and the change in discharge rate q (flow out) in different subsections.

The changes of apertures and discharge rates in several representative subsections are shown in Figure 8. Generally, the change of apertures drops along vertical directions and is higher near the left and right boundary. In the lower section, the change of aperture is minimal (A13).

The discharge rate in each subsection was computed by checking the fractures that cross the boundary and flow into the subsection. The lateral aquifer width was assumed to be 100 m. The A13 subsection has the lowest discharge, which changes the least over time. The discharge in the A8 subsection changed more slowly than that in other parts of the

265 middle primary section. The A3 subsection, in the middle part of the upper primary section, exhibited a much greater leakage trend than did the lower parts. From the aperture and discharge analysis, we concluded that a low-karstified area exists mainly in the middle and lower primary sections.

3.4 Changes in conductivity K and formation of the LKB

270 To further elucidate the formation of an LKB, we calculated vertical and horizontal hydraulic conductivity in each subsection. To do this, we “cut out” a section at certain stage of evolution, and calculated confined flow rate for a given head difference along horizontal and vertical direction, respectively. Thus horizontal and vertical equivalent K values, and the changes and trends in the representative subsection were computed (Figure 9). Notably, the fractures below 50 m in the lower subsections (A11 to A15), remained unevolved. The horizontal K varied between 0.005 and 0.008 m/d in the different subsections, and the vertical K varied between 0.001 and 0.002 m/d.

275 The middle subsections A7, A8, and A9 experienced low level of karstification, in particular, subsection A8 (less than 0.01 m/d), which combined with the lower section forms an LKB, which could effectively prevent horizontal flow. In the A6 and A10 subsections, the K increased by more than one order of magnitude.

The upper primary section was also tested to determine whether it included a low permeable part. Note that here only phreatic karst process is considered, therefore most fractures in subsection A1 did not experience widening. The water table 280 descended through subsection A3, where the conductivity trends increased in both the horizontal and vertical directions compared with those in the other subsections. Although the upper primary area does not exhibit a low conductivity, its underlying low permeable rock-blocks have already been recognized as an LKB.











Figure 9. Changes and increasing trends of the equivalent conductivity K in the different subsections during 20 ka

285 natural evolution process.

4 The influence of LKB on reservoir leakage

To verify the relevance of LKB formation on reservoir leakage, as in the case of Luojiaao interfluvium, we now apply reservoir boundary conditions to an evolved aquifer. The borehole data revealed that the natural water divide level is 50 to 80 meters above the river, which roughly corresponds to the situation in our synthetic aquifer after 20 ka of evolution.

290 **4.1 Reservoir leakage with various reservoir levels**

First, we test the leakage through the aquifer at different reservoir water **by applying** constant head of 200 m, 250 m and 300 m, on the left boundary (presenting reservoir) of the aquifer which has evolved for 20 ka. The flow fields are shown in Figure 10. In case of 200 m, the groundwater divide still exists, although it is shifted towards the left boundary. However, the water still flows from the aquifer to the reservoir. When the water is raised to 250 m, as shown in Figure 10b, the groundwater divide moves almost to the left boundary, so that the flow to the reservoir is only local (upper left), however, deeper the flow is directed from the reservoir to the aquifer. At 300 m, as shown in Figure 10c, the flow direction is almost entirely from the reservoir to the aquifer.




Figure 10. Flow fields within the aquifer, which has evolved for 20,000 years under natural conditions, after the

300 application of reservoir boundary conditions on the left side at: (a) 200 m, (b) 250 m, and (c) 300 m.




Figure 11. Leakage as a function of reservoir level for aquifer after 20 ka, 30 ka and 40 ka of evolution. The lateral width is 100 m.

Figure 11 shows the reservoir leakage at different water levels through the aquifer at different stage of evolution, assuming the lateral width of the aquifer is 100 m. For the aquifer after 20 ka of evolution under rainfall recharge, no leakage is observed below 225 m, as the water divide is still present and high enough to drive water from the aquifer to the reservoir. For 30 ka and 40 ka “old aquifers”, leakage is present at all levels applied and increases linearly with the reservoir level. The actual water level of the Geheyan reservoir is 200 m, which is below the level, where significant leakage may be expected from the model.




Figure 12. Variation of hydraulic conductivity (K) in the karst aquifer before and after reservoir filling: horizontal (a) and vertical (c) distribution of hydraulic conductivity after 20 ka of natural evolution; horizontal (b) and vertical (d) distribution of K after one thousand years of reservoir conditions. The saturation ratio (C / C_{eq}) of reservoir water is 0.8.

315 If water in the river is aggressive to calcite, evolution of aquifer continues after the reservoir filling. We assume that the saturation ratio (C / C_{eq}) of reservoir water is 0.8. Figure 12 shows the distribution of hydraulic conductivities in an aquifer, which has evolved naturally for 20 ka and then under the influence of reservoir for one thousand years. The subsections A8 and A13 maintained the lowest conductivity also after reservoir filling. Based on the conductivity analysis of the middle and lower primary sections, we conclude that the developed LKB remained a continuous, low-permeability barrier throughout 1,000 years of reservoir filling conditions.

320




Figure 13. Reservoir leakage through karst aquifers over one thousand years (assuming that the aquifer lateral width is 100 m).

Figure 13 illustrates the increasing trend of reservoir leakage over a 1,000-year period of reservoir operation. Leakage rates were estimated assuming a lateral aquifer width of 100 m. At the 200 m reservoir level, no leakage occurs initially, resulting in no further evolution over time. For the 250 m and 300 m levels, leakage remains below 2 L/s over the entire 1,000-year span.


325

While the severity of leakage under these idealized conditions may appear acceptable during long-term reservoir operation, the final determination of a permissible water level must consider a broader range of factors. These include geological uncertainties, site-specific topographic features, and social safety requirements, all of which play critical roles in the decision-making process.

330

The fracture flow velocity distribution during the natural condition evolution process and under different water levels of the reservoir is shown in Figure 14. Areas with low flow velocity in the central part indicate low permeability and weak karstification. The high-velocity flow region forms an arch-shaped region along the permeable fringe, which has developed along the descending water table.

In the water divide region, the LKB forms, mitigating flow beneath the fringe. Under reservoir conditions, leakage becomes substantial only when the reservoir level rises well above the LKB, causing the water divide to shift towards the reservoir and initiating flow along the permeable arch.



340

Figure 14. Velocity distribution in the aquifer at different stages and conditions: (a) at the onset of karstification, (b) after 20 ka of natural evolution prior to reservoir impoundment, (c) after 20 ka of natural evolution and then with a reservoir level of 200 m, and (d) after 20 ka of natural evolution and with a reservoir level of 300 m.

5 Discussion and conclusions




Figure 15. Conceptualisation of the low-karstified rock-blocks (LKB) in the water divide region (shaded area between dotted lines b and c). The zone below line c exhibits minimal karstification. Line a indicates the naturally evolving water table prior to reservoir impoundment, with conduits and caves forming on both sides of this water level.

The concept of LKB, also demonstrated by our model, is summarized in Figure 15. The dotted line is the evolving water table under natural conditions. Below line c, the fractures have experienced almost no karstification. Between lines a and b, well-karstified zones have developed on both sides of the descending water table area. In contrast, the region between lines b and c exhibits only moderate fracture widening. This section—designated as the LKB—acts as a naturally low-permeability zone that helps mitigate potential leakage from the reservoir.

In a broader sense, karstification presents a form of nucleation, where flow-induced dissolution and changes in porosity are coupled through feedback mechanisms (Edery et al., 2021; Molins et al., 2014). In unconfined aquifers under constant recharge conditions, dissolution is most intense near the water table. This process creates a highly permeable fringe that effectively channels inflow toward both sides of the water divide. As this fringe migrates downward across the aquifer cross-section, it leaves behind a distinctive porosity imprint. Simultaneously, it inhibits deeper penetration of the inflowing solution, favouring the preferential development of horizontal fractures. Moreover, flow along the water table increases progressively from the water divide toward the discharge points. As a result the water divide zone is less karstified than the regions close to the output. Similar anisotropic, directional changes, including fingers or preferential flows, has also been observed through experimental studies and other numerical simulations (Rege and Fogler, 1989; Shavelzon and Edery, 2022; Singurindy and Berkowitz, 2003).

Reservoir leakage is highly sensitive to the relative elevation of the reservoir water level and the elevation of the low-permeability-block (LKB). Identifying the water table position within the aquifer prior to reservoir impoundment can help
365 locate the LKB and potentially reduce the need for costly engineering measures to prevent leakage (Zhou and Li, 1996).

The presented model simplifies the system by neglecting many of the complexities observed in natural settings. Karst
aquifers evolve in different climatological, hydrological and geological settings, and they often undergo multiple phases of
karstification over geological timescales, driven by varying hydrological and geochemical boundary conditions. In active
tectonic areas, the structure and boundary conditions may change during the karstification, which may continuously adapt to
370 the terrain uplift and/or valley entrenchment (Gabrovšek et al., 2014). Therefore, any modelling related to a specific site
must include all information on the environment in which an aquifer has evolved (Class et al., 2021; Hartmann et al., 2013).
The initial structure of an aquifer is typically far more intricate than assumed in the model, potentially including pre-existing
preferential flow paths, geochemical heterogeneity (e.g., interbedded layers of less soluble rock), and temporal variability in
recharge. Additionally, the model does not account for the development of the vadose zone, which plays a crucial role in
375 modifying the permeability of layers above the water table and influences the geochemical characteristics of the water at the
water table. These features could be systematically incorporated into the model to investigate their influence on aquifer
evolution.

Despite its limitations, the model effectively serves as a proof of concept, offering valuable insights for hydraulic
engineering in karst regions.

380 **Data Availability Statement**

All data used in this research are publicly available. The data and code used for simulating fracture phreatic water table
and karst evolution are available at <https://github.com/jiaoyj/Fracturetokarst2024>.

Author contribution

YJ contributed with writing of the original draft, methodology and modifying the code. FG contributed with
385 conceptualization, review and editing of the manuscript. XW contributed with conceptualization, review and editing of the
manuscript. QY contributed with the original code, conceptualization, methodology and review.

Competing interests. The authors declare that they have no conflict of interest.

Acknowledgments

This work was supported by the National Natural Sciences Foundation of China (Grant Nos. 42377061, 41772249,
390 41702279), Guangxi Key R&D Project (AB25069394), Guizhou Academician Workstation (KXJZ[2024]005), China
Geological Survey (DD20251205) and the China Scholarship Council. The authors are very grateful for the help of the Rock
Fracture Work Group. The work of Franci Gabrovšek was supported by the research program Karst Research (P6-0119(B)),
funded by the Slovenian Research and Innovation Agency (ARIS), and by the project ERC KARST (101071836), funded by
the European Research Council.

395 References

- Buhmann, D., and Dreybrodt, W.: The kinetics of calcite dissolution and precipitation in geologically relevant situations of
karst areas: 1. Open system, Chem. Geol., 48, 189-211, [https://doi.org/10.1016/0009-2541\(85\)90046-4](https://doi.org/10.1016/0009-2541(85)90046-4), 1985a.
- Buhmann, D., and Dreybrodt, W.: The kinetics of calcite dissolution and precipitation in geologically relevant situations of
karst areas: 2. Closed system, Chem. Geol., 53, 109-124, [https://doi.org/10.1016/0009-2541\(85\)90024-5](https://doi.org/10.1016/0009-2541(85)90024-5), 1985b.
- 400 Chen, Z., Auler, A. S., Bakalowicz, M., Drew, D., Griger, F., Hartmann, J., Jiang, G., Moosdorf, N., Richts, A., Stevanovic,
Z., Veni, G., and Goldscheider, N.: The World Karst Aquifer Mapping project: concept, mapping procedure and map of
Europe, Hydrogeol. J., 25, 771-785, <https://doi.org/10.1007/s10040-016-1519-3>, 2017.
- Class, H., Bärkle, P., Sauerborn, T., Trötschler, O., Strauch, B., and Zimmer, M.: On the role of density-driven dissolution of
CO₂ in phreatic karst systems, Water Resour. Res., 57, e2021WR030912, <https://doi.org/10.1029/2021WR030912>, 2021.
- 405 Clemens, T., Hückinghaus, D., Liedl, R., and Sauter, M.: Simulation of the development of karst aquifers: role of the
epikarst, Int. J. Earth Sci. (Geol. Rundsch.), 88, 157-162, <https://doi.org/10.1007/s005310050252>, 1999.
- Desai, C. S., and Li, G. C.: A residual flow procedure and application for free surface flow in porous media, Adv. Water
Resour., 6, 27-35, [https://doi.org/10.1016/0309-1708\(83\)90076-3](https://doi.org/10.1016/0309-1708(83)90076-3), 1983.

- Detwiler, L. R., and Rajaram, H.: Predicting dissolution patterns in variable aperture fractures: Evaluation of an enhanced depth-averaged computational model, *Water Resour. Res.*, 43, W04403, <https://doi.org/10.1029/2006WR005147>, 2007.
- Dijk, P. E., Berkowitz, B., and Yechieli, Y.: Measurement and analysis of dissolution patterns in rock fractures, *Water Resour. Res.*, 38, <https://doi.org/10.1029/2001WR000246>, 2002.
- Dreybrodt, W.: The role of dissolution kinetics in the development of karst aquifers in limestone: a model simulation of karst evolution, *J. Geol.*, 98, 639-655, <https://doi.org/10.1086/629431>, 1990.
- Dreybrodt, W.: Principles of early development of karst conduits under natural and man-made conditions revealed by mathematical analysis of numerical models, *Water Resour. Res.*, 32, 3085-3096, <https://doi.org/10.1029/96WR01970>, 1996.
- Dreybrodt, W., Gabrovšek, F., and Romanov, D.: Processes of speleogenesis: a modelling approach, Založba ZRC, 2005.
- Dreybrodt, W., and Kaufmann, G.: Physics and chemistry of dissolution on subaerially exposed soluble rocks by flowing water films, *Acta Carsologica*, 36, 137-154, 2007.
- Eisenlohr, L., Meteva, K., Gabrovšek, F., and Dreybrodt, W.: The inhibiting action of intrinsic impurities in natural calcium carbonate minerals to their dissolution kinetics in aqueous $\text{H}_2\text{O}-\text{CO}_2$ solutions, *Geochim. Cosmochim. Acta*, 63, 3007-3017, [https://doi.org/10.1016/S0016-7037\(99\)00157-X](https://doi.org/10.1016/S0016-7037(99)00157-X), 1999.
- Edery, Y., Stolar, M., Porta, G., and Guadagnini, A.: Feedback mechanisms between precipitation and dissolution reactions across randomly heterogeneous conductivity fields, *Hydrol. Earth Syst. Sci.*, 25, 5905–5915, [https://doi.org/10.5194/hess-25-](https://doi.org/10.5194/hess-25-5905-2021) 5905-2021, 2021.
- Finenko, M., and Konietzky, H.: Numerical simulation of turbulent fluid flow in rough rock fracture: 2D case, *Rock Mechanics and Rock Engineering*, 57, 451-479, <https://doi.org/10.1007/s00603-023-03551-5>, 2024.
- Ford, D., and Williams, P. D.: Karst hydrogeology and geomorphology, John Wiley & Sons, 2007.
- Gabrovšek, F.: Evolution of early karst aquifers: from simple principles to complex models, Založba ZRC, 2000.
- Gabrovšek, F., and Dreybrodt, W.: Role of mixing corrosion in calcite-aggressive $\text{H}_2\text{O}-\text{CO}_2-\text{CaCO}_3$ solutions in the early evolution of karst aquifers in limestone, *Water Resour. Res.*, 36, 1179-1188, <https://doi.org/10.1029/1999WR900337>, 2000.
- Gabrovšek, F., and Dreybrodt, W.: A model of the early evolution of karst aquifers in limestone in the dimensions of length and depth, *J. Hydrol.*, 240, 206-224, [https://doi.org/10.1016/S0022-1694\(00\)00323-1](https://doi.org/10.1016/S0022-1694(00)00323-1), 2001.
- Gabrovšek, F., and Dreybrodt, W.: Karstification in unconfined limestone aquifers by mixing of phreatic water with surface water from a local input: a model, *J. Hydrol.*, 386, 130-141, <https://doi.org/10.1016/j.jhydrol.2010.03.015>, 2010.
- Gabrovšek, F., Häselmann, P., and Audra, P.: 'Looping caves' versus 'water table caves': the role of base-level changes and recharge variations in cave development, *Geomorphology*, 204, 683-691, <https://doi.org/10.1016/j.geomorph.2013.09.016>, 2014.
- Gabrovšek, F., and Dreybrodt, W.: Early hypogenic carbonic acid speleogenesis in unconfined limestone aquifers by upwelling deep-seated waters with high CO_2 concentration: a modelling approach, *Hydrol. Earth Syst. Sci.*, 25, 2895-2913, <https://doi.org/10.5194/hess-25-2895-2021>, 2021.

- Harbaugh, A. W., Banta, E. R., Hill, M. C., and McDonald, M. G.: MODFLOW-2000, the US Geological Survey modular ground-water model: User guide to modularization concepts and the ground-water flow process, U.S. GEOLOGICAL SURVEY, Open-File Report 00-92, <https://doi.org/10.3133/ofr200092>, 2000.
- 445 Hartmann, A., Weiler, M., Wagener, T., Lange, J., Kralik, M., Humer, F., Mizyed, N., Rimmer, A., Barber á J. A., Andreo, B., Butscher, C., and Huggenberger, P.: Process-based karst modelling to relate hydrodynamic and hydrochemical characteristics to system properties, *Hydrol. Earth Syst. Sci.*, 17, 3305–3321, <https://doi.org/10.5194/hess-17-3305-2013>, 2013.
- Hubinger, B. and Birk, S.: Influence of initial heterogeneities and recharge limitations on the evolution of aperture
450 distributions in carbonate aquifers, *Hydrol. Earth Syst. Sci.*, 15, 3715–3729, <https://doi.org/10.5194/hess-15-3715-2011>, 2011.
- Jiang, Q., Yao, C., Ye, Z., and Zhou, C.: Seepage flow with free surface in fracture networks, *Water Resour. Res.*, 49, 176–186, <https://doi.org/10.1029/2012WR011991>, 2013.
- Jiang, X., Wan, L., Ge, S., Cao, G., Hou, G., and Hu, F.: A quantitative study on accumulation of age mass around
455 stagnation points in nested flow systems, *Water Resour. Res.*, 48, <https://doi.org/10.1029/2012WR012509>, 2012.
- Jing, L., Ma, Y., and Fang, Z.: Modelling of fluid flow and solid deformation for fractured rocks with discontinuous deformation analysis (DDA) method, *Int. J. Rock Mech. Min. Sci.*, 38, 343–355, [https://doi.org/10.1016/S1365-1609\(01\)00005-3](https://doi.org/10.1016/S1365-1609(01)00005-3), 2001.
- Kang, Q., Zhang, D., and Chen, S.: Simulation of dissolution and precipitation in porous media, *J. Geophys. Res.*, 108,
460 <https://doi.org/10.1029/2003JB002504>, 2003.
- Kaufmann, G.: Modelling unsaturated flow in an evolving karst aquifer, *J. Hydrol.*, 276, 53–70, [https://doi.org/10.1016/S0022-1694\(03\)00037-4](https://doi.org/10.1016/S0022-1694(03)00037-4), 2003.
- Liang, X., Liu, Y., Jin, M., Lu, X., and Zhang, R.: Direct observation of complex Tóhian groundwater flow systems in the laboratory, *Hydrol. Process.*, 24, 3568–3573, <https://doi.org/10.1002/hyp.7758>, 2010.
- 465 Liu, Z., and Dreybrodt, W.: Dissolution kinetics of calcium carbonate minerals in H₂O–CO₂ solutions in turbulent flow: The role of the diffusion boundary layer and the slow reaction $\text{H}_2\text{O} + \text{CO}_2 \rightarrow \text{H}^{++} \text{HCO}_3^-$, *Geochim. Cosmochim. Acta*, 61, 2879–2889, [https://doi.org/10.1016/S0016-7037\(97\)00143-9](https://doi.org/10.1016/S0016-7037(97)00143-9), 1997.
- Lomize, G. M.: Flow in fractured rocks, Gosenergoizdat, Moscow, 127–197, 1951.
- Milanović, P. T.: Geological Engineering in Karst: dams, reservoirs, grouting, groundwater protection, water tapping,
470 tunneling: with 190 figures, Zebra publishing ltd., Belgrade, 2000.
- Milanović, P. T.: Engineering karstology of dams and reservoirs, CRC Press, Boca Raton, <https://doi.org/10.1201/9780429453403>, 2018.
- Molins, S., Trebotich, D., Yang, L., Ajo-Franklin, J. B., Ligocki, T. J., Shen, C., and Steefel, C. I.: Pore-scale controls on calcite dissolution rates from flow-through laboratory and numerical experiments, *Environ. Sci. Technol.*, 48, 7453–7460,
475 <https://doi.org/10.1021/es5013438>, 2014.

- Nogues, J. P., Fitts, J. P., Celia, M. A., and Peters, C. A.: Permeability evolution due to dissolution and precipitation of carbonates using reactive transport modelling in pore networks, *Water Resour. Res.*, 49, 6006–6021, <https://doi.org/10.1002/wrcr.20486>, 2013.
- Rege, S. D., and Fogler, H. S.: Competition among flow, dissolution, and precipitation in porous media, *AIChE J.*, 35, 1177 – 1185, <https://doi.org/10.1002/aic.690350713>, 1989.
- Rhoades, R., and Sinacori, M. N.: Pattern of ground-water flow and solution, *The Journal of Geology*, 49, 785-794, 1941.
- Romanov, D., Gabrovšek, F., and Dreybrodt, W.: Dam sites in soluble rocks: a model of increasing leakage by dissolutional widening of fractures beneath a dam, *Engineering Geology*, 70, 17-35, [https://doi.org/10.1016/S0013-7952\(03\)00073-5](https://doi.org/10.1016/S0013-7952(03)00073-5), 2003.
- 485 Romanov, D., Gabrovsek, F., and Dreybrodt, W.: Leakage below dam sites in limestone terrains by enhanced karstification: a modelling approach, *Environmental Geology*, 51, 775-779, <https://doi.org/10.1007/s00254-006-0394-y>, 2007.
- Sanderson, C., and Curtin, R.: Armadillo: a template-based C++ library for linear algebra, *Journal of Open Source Software*, 1, 26, <https://doi.org/10.21105/joss.00026>, 2016.
- Sanderson, C., and Curtin, R.: Practical sparse matrices in C++ with hybrid storage and template-based expression
490 optimisation, *Mathematical and Computational Applications*, 24, 70, <https://doi.org/10.3390/mca24030070>, 2019.
- Shavelzon, E., and Edery, Y.: Modelling of Reactive Transport in Porous Rock: Influence of Peclet Number, *EGU22-8059*, <https://doi.org/10.5194/egusphere-egu22-8059>, 2022.
- Shen, J., Wan, J., Xu, S., Shi, B., and Zhang, T.: The effect of large reservoir impoundment on karst water environment in carbonate rock area- taking Geheyan reservoir as an example, *Carsologica Sinica*, 16, 397-402, (in Chinese),
495 <http://www.cnki.com.cn/Article/CJFDTotat-ZGYR704.013.htm>, 1997.
- Singurindy, O., and Berkowitz, B.: Evolution of hydraulic conductivity by precipitation and dissolution in carbonate rock, *Water Resour. Res.*, 39, W1016, <https://doi.org/10.1029/2001WR001055>, 2003.
- Smerdon, B. D., Mendoza, C. A., and McCann, A. M.: Quantitative investigations of the hydraulic connection between a large reservoir and a buried valley aquifer in southern Alberta, *Canadian Geotechnical Journal*, 42, 1461-1473,
500 <https://doi.org/10.1139/t05-065>, 2005.
- Su, B., Zhan, M., and Zhao, J.: The model test of the flow in smooth fracture and the study of its mechanism, *Journal of Hydraulic Engineering*, 5, 19-24, (in Chinese), 1994.
- Tóth, J.: A theory of groundwater motion in small drainage basins in central Alberta, Canada, *Journal of Geophysical Research*, 67, 4375-4388, <https://doi.org/10.1029/JZ067i011p04375>, 1962.
- 505 Wan, J., Chao, N., Shen, J., and Cai, J.: Study on the carbon cycle in a karst system at the Luojiaao interfluvium along the Qingjiang River of western Hubei, China, *Carsologica Sinica*, 18, 123-128, (in Chinese), <https://doi.org/10.3969/j.issn.1001-4810.1999.02.004>, 1999.
- Wang, E.: Seepage calculation method in fissure networks on vertical section, *Hydrogeology & Engineering Geology*, 20, 27-29, (in Chinese), <https://doi.org/10.16030.j.cnki.issn.1000-3665.1993.04.009>, 1993.

- 510 Wang, X., Jiang, X., Wan, L., Ge, S., and Li, H.: A new analytical solution of topography-driven flow in a drainage basin with depth-dependent anisotropy of conductivity, *Water Resour. Res.*, 47, W09603, <https://doi.org/10.1029/2011WR010507>, 2011.
- Xu, R., and Yan, F.: Karst geology and engineering treatment in the Geheyan Project on the Qingjiang River, China, *Engineering Geology*, 76, 155-164, <https://doi.org/10.1016/j.enggeo.2004.06.012>, 2004.
- 515 Yu, Q., Shen, J., Wan, J., and Ohnishi, Y.: Some investigation on early organization of Karst system, *Journal of China University of Geosciences*, 10, 314-321, http://en.cnki.com.cn/Article_en/CJFDTOTAL-ZDDY199904007.htm, 1999.
- Yuan, D., Zhu, D., Weng, J., Zhu, X., Han, X., Wang, X., Cai, G., Zhu, Y., Cui, G., and Deng, Z.: *Karst of China*, Geological Publishing House, Beijing, (in Chinese), 1993.
- Yuan, D., Liu, Z., Lin, Y., Shen, J., He, S., Xu, S., Yang, L., Li, B., Qin, J., Cai, W., Cao, J., Zhang, M., Jiang, Z., and Zhao, J.: *Karst dynamic system of China*, Geological Publishing House, Beijing, (in Chinese), 2002.
- 520 Zhang, R., Liang, X., Jin, M., Wan, L., and Yu, Q.: *Fundamentals of hydrogeology*, Geological Publishing House, Beijing, (in Chinese), 2018.
- Zheng, H., Liu, D. F., Lee, C. F., and Tham, L. G.: A new formulation of Signorini's type for seepage problems with free surfaces, *International Journal for Numerical Methods in Engineering*, 64, 1-16, <https://doi.org/10.1002/nme.1345>, 2005.
- 525 Zhou, Z., and Li, Y.: Seepage estimation of the rock-mass in divide area at Geheyan Water Conservancy Project in Qingjiang River, *Journal of Hohai University (Natural Sciences)*, 24, 101-104, (in Chinese), 1996.