

Comment on "Design study for an airborne N₂O lidar" by Kiemle et al. (2024)

Joel F. Campbell¹, Bing Lin¹, Zhaoyan Liu²

¹NASA Langley Research Center, Hampton, VA 23681

joel.f.campbell@nasa.gov

²NASA Ames Research Center, Moffett Field, CA 94035

In a recent publication (Kiemle et al., 2024) the following was stated:

“Another low-power option for IPDA is (modulated) continuous-wave (cw) laser operation instead of emitting pulsed signals (e.g., Campbell et al., 2020). For measurements with a precision requirement below 1 %, however, the length of the atmospheric column must be known to an accuracy of better than 3 m, which is only practicable with short laser pulses in combination with a sufficiently large detection bandwidth (Table 3; Ehret et al., 2008). Alternatively, a precision range finder had to be added, which annihilates the cost benefit of cw lidar.”

We reported doing those things with a CW lidar system in the referenced publication without the aid of an external range finder so this statement is incorrect. The CW technique was first used in radar many decades ago to do ranging, so there really is not an advantage or necessity to choose one technology over another if ranging is the only consideration. In fact, one of the main applications for CW lidar is ranging. The same physics applies to either technology. If a narrow pulse is required for target discrimination purposes, this can also be achieved with CW using a modulation with a wide bandwidth. Once the matched filter transform is performed, a narrow width synthetic pulse can be achieved. A 3 m resolution CW ranging lidar would require a modulation bandwidth of $\Delta f = \frac{c}{2\Delta r} = 50\text{MHz}$, where c is the light speed and Δr is the ranging resolution. This is not difficult especially if optical communication hardware is utilized. Another method would be to use frequency modulated CW (FMCW; Gao and Hui, 2012) or phase modulated CW (PMCW; Zhi et al., 2025) and heterodyne detection. In fact, FMCW lidar is used in the auto industry to detect near objects (Kim et al., 2020).

Regarding the point of a narrow pulse (or alternatively a narrow synthetic CW pulse) being required to do ranging down to 3 meters: If the field is cluttered by clouds or other features, we would say this statement is probably true depending on the situation, but in clear sky conditions where the ground is the only return, interpolation can be used. Interpolating lower resolution lidars is not a particularly controversial technique and has been used extensively in the past (Hu et al., 2007; Ai et al., 2011; Dobler et al., 2013; Lu et al., 2014; Campbell et al., 2014). If the field is cluttered by closely spaced scatterers, one return could interfere with another to distort the shape of the pulse and affect the range measurement. If the ground is the only return this is not likely to occur except through ground topography, which would also affect a pulse lidar. In some pulse

lidars where there is variability from pulse to pulse, interpolation can be more problematic depending on the system. However, CW does not suffer from this. Each modulation frame is generated from a preset waveform and clock and there is a very high degree of repeatability. Not only that, each synthetic pulse is generated from multiple sweeps in our processing, and the interpolation is a natural feature of the way that we do the matched filtering, using a type of circular Fourier interpolation by collapsing the Kronecker comb of the matched filter in the frequency domain, so the results of the modified matched filter produces an interpolated synthetic pulse with very good results (Campbell et al., 2014). As long as the signal is Nyquist sampled, the original continuous signal can be recovered to within the limits of noise. This is the basic tenet of the Nyquist-Shannon sampling theorem. Fourier interpolation (or at least our version of it designed for circular correlations) is the most natural and accurate interpolation method for this type of band limited signal.

The paper in question shows results from the multifunctional fiber laser lidar (MFLL), an instrument that was developed over many years by Harris Corporation (now L3Harris) in collaboration with NASA Langley Research Center. MFLL evolved from an instrument that used a single frequency modulation for each wavelength that were orthogonal to one another in its early development (Dobbs et al., 2008) to what it was on the Atmospheric Carbon and Transport – America (ACT America) flights where it used orthogonal swept frequency modulations (Dobler et al., 2013, Campbell et al., 2020). Although it is true ranging is more problematic with single frequency modulations, swept frequency modulation is a technique commonly used in many older CW radars to do ranging and that is what was being used by MFLL for the ACT America flights. The results show that the ranging is clearly less than 3 m, which meets and, actually, exceeds the science/instrumentation requirement. The authors have also experimented with PN code modulation on different instruments with good results (Campbell et al., 2014).

References

- Ai, Xiao; Nock, Richard; Rarity, John G.; and Dahnoun, Naim: High-resolution random-modulation cw lidar, *Appl. Opt.* 50, 4478-4488, <https://doi.org/10.1364/AO.50.004478>, 2011
- Campbell, Joel F.; Lin, Bing; Nehrir, Amin R.; Harrison, F. Wallace; and Obland, Michael D.: High-resolution CW lidar altimetry using repeating intensity-modulated waveforms and Fourier transform reordering, *Opt. Lett.* 39, 6078-6081, <https://doi.org/10.1364/OL.39.006078>, 2014
- Campbell, J. F.; Lin, B.; Dobler, J.; Pal, S.; Davis, K.; Obland, M. D.; Erxleben, W.; McGregor, D.; O'Dell, C.; Bell, E.; Weir, B.; Fan, T.-F.; Kooi, S.; Gordon, I.; Corbett, A.; and Kochanov, R.: Field evaluation of column CO₂ retrievals from intensity-modulated continuous-wave differential absorption lidar measurements during the ACT-America campaign, *Earth and Space Science*, 7, e2019EA000847, <https://doi.org/10.1029/2019EA000847>, 2020
- Dobbs, Michael; Dobler, Jeremy; Braun, Michael; McGregor, Doug; Overbeck, Jay; Moore III, Berrien; Browell, Edward; Zaccheo, T.S.: A Modulated CW Fiber Laser-Lidar Suite for the

ASCENDS Mission, Conference: 24th International Laser Radar Conference At: Boulder, CO, 2008

Dobler, J. T.; Harrison, F. W.; Browell, E. V.; Lin, B.; McGregor, D.; Kooi, S.; Choi, Y.; and Ismail, S.: Atmospheric CO₂ column measurements with an airborne intensity-modulated continuous wave 1.57 μm fiber laser lidar. *Applied Optics*, **52**(12), 2874–2892. <https://doi.org/10.1364/AO.52.002874>, 2013

Gao, S. and Hui, R.: Frequency-modulated continuous-wave lidar using I/Q modulator for simplified heterodyne detection, *Opt. Lett.* **37**, 2022–2024. <https://doi.org/10.1364/OL.37.002022>, (2012)

Hu, Y.; Powell, K.; Vaughan, M.; Teppe, C.; Weimer, C.; Beherenfeld, M.; Young, S.; Winker, D.; Hostetler, C.; Hunt, W.; Kuehn, R.; Flittner, D.; Cisewski, M.; Gibson, G.; Lin, B.; and MacDonnell, D.: Elevation information in tail (EIT) technique for lidar altimetry, *Optics Express* **15**, 14504–14515, <https://doi.org/10.1364/OE.15.014504>, 2007.

Kiemle, Christoph; Fix, Andreas; Fruck, Christian; Ehret, Gerhard; and Wirth, Martin: Design study for an airborne N₂O lidar, *AMT*, **17**, 6569–6578, <https://doi.org/10.5194/amt-17-6569-2024>, 2024

Kim, Chankyu; Jung, Yunho; and Lee, Seongjoo: FMCW LiDAR System to Reduce Hardware Complexity and Post-Processing Techniques to Improve Distance Resolution, *Sensors*, **20**(22), 6676; <https://doi.org/10.3390/s20226676>, 2020

Lu, X.; Hu, Y.; Trepte, C.; and Liu, Z.: A Super-Resolution Laser Altimetry Concept, in *IEEE Geoscience and Remote Sensing Letters*, vol. 11, no. 1, pp. 298–302, doi:10.1109/LGRS.2013.2256876, 2014

Zhi, Yanan; Wang, Jinkai; Sun, Yujiao; Huang, Sijing; Wang, Huanyan; Xu, Bijun; and Tian, Kehan: Differential pseudo-random phase-modulated continuous-wave coherent LiDAR, *Opt. Express* **33**, 13624–13646, <https://doi.org/10.1364/OE.549354>, 2025