

A systematic evaluation of 15 actual evapotranspiration formulations within conceptual hydrological models

Gabrielle Burns¹, Keirnan Fowler¹, Murray Peel¹, Clare Stephens²

¹Department of Infrastructure Engineering, The University of Melbourne, Parkville, VIC Australia

5 ²Hawkesbury Institute for the Environment, Western Sydney University, Richmond, NSW, Australia

Correspondence to: Gabrielle Burns (gabrielle.burns@unimelb.edu.au)

Abstract. Actual evapotranspiration (AET) is a major component of the water balance, yet it is rarely assessed for accuracy in conceptual rainfall-runoff models that are often calibrated to match streamflow only. Inaccurate representation of underlying AET processes may cause models to incorrectly simulate long-term changes in partitioning between AET and streamflow, even if this partitioning was relatively accurate during calibration. To investigate AET representation within conceptual hydrological models, we systematically tested 15 evapotranspiration (ET) equations that convert potential evapotranspiration (PET) and soil moisture to AET. The 15 equations represent common practice, having been sourced from a published comprehensive review of conceptual hydrological models. Each of these 15 formulations were trialled within three conceptual hydrological models (GR4J, Simhyd and Vic). Following multi-objective calibration, we evaluated performance across both streamflow and flux tower AET measurements at seven catchments from a range of Australian climates. A small number of AET equations outperformed the rest, with one equation standing out, which uses a non-linear relationship with soil moisture storage and can scale down AET such that it cannot equal PET even under high soil moisture conditions. This equation achieved a higher objective function value for both AET and streamflow and accurately captured evapotranspiration signatures. However, even this equation showed limitations in reproducing observed AET, suggesting persistent issues across commonly used formulations. These shortcomings may reflect missing vegetation-related dynamics and other simplifications. Our findings highlight the importance of ET equation selection in modelling AET and streamflow, and we recommend the identified equation as a promising option for future Australian studies. Further work is needed to test equations for consistency with known processes to improve the physical realism of conceptual hydrological models.

1 Introduction

25 Hydrological models play a critical role in understanding and replicating catchment behaviours, providing insights into the movement and storage of water within landscapes (Liu et al., 2017). These models are widely applied in water resource management, where they inform decision-making in contexts such as flood mitigation, drought planning, and adapting to the impacts of a shifting climate (Grigg & Hughes, 2018). Streamflow is often the main output of interest; however, internal state variables (e.g. soil moisture) and fluxes (e.g. AET, groundwater recharge) are also simulated. Hydrological models are

30 commonly calibrated to match observed streamflow data alone, often based on the assumption that streamflow is the integral
of the other catchment processes and accurate streamflow replication implies accuracy across all modelled fluxes. In reality,
models may exhibit poor replication of internal fluxes like actual evapotranspiration (AET) (Kelleher & Shaw, 2018) or
streamflow generation mechanisms, despite achieving acceptable streamflow, due to equifinality - where multiple
parameterisations or process representations yield similar outputs (Beven, 2006; Khatami et al., 2019). The wide range of
35 internal behaviours shown in flux maps by Khatami et al. (2019) illustrates this issue and raises concerns about how reliably
models capture underlying hydrological processes. In this study, we focus specifically on conceptual rainfall-runoff models,
although many of the challenges discussed apply more broadly across hydrological model types.

Increasing emphasis has been placed on the ability of models to operate under change, particularly climate change. Blöschl et
al. (2019) highlighted the need for hydrological models capable of adapting to changing conditions, including evolving
40 vegetation. For example, inaccurate representation of underlying processes may cause models to incorrectly simulate long-
term changes in water partitioning, despite being accurate during calibration. Furthermore, studies have found that model
performance decreases when multi-annual shifts in rainfall-runoff relationships occur, often driven by long-term changes in
climate forcing (Saft et al., 2016). These historical cases provide valuable analogues for understanding how models may
perform under future climate change.

45 A key component of these changing dynamics is evapotranspiration (AET), which represents a major pathway through which
vegetation influences catchment water balance. Vegetation may play a key role in driving this non-stationary catchment
behaviour, yet its effects are rarely represented explicitly in traditional conceptual model structures (Deb & Kiem, 2020;
Duethmann et al., 2020). Instead, vegetation influences are typically embedded implicitly within empirical AET formulations.
Neglecting these controls can exacerbate limitations in model performance under changing conditions. -

50 The hydrology community has identified these challenges as critical to advancing the field, suggesting current models need
improving (Fowler et al., 2020; Stephens et al., 2019; Vaze et al., 2010). Addressing these gaps requires a shift toward
harmonising conceptual models with process-based understanding to improve model adaptability under change. However, a
useful first step is evaluating the performance of existing empirical equations used within models to determine which best
capture key processes.

55 Conceptual hydrological models typically estimate AET using potential evapotranspiration (PET) as an upper limit, with
reductions based on water availability and model-specific assumptions. The specific choice of equations can influence how
accurately AET is represented, but explicit evaluation of AET accuracy remains uncommon (Kelleher & Shaw, 2018), and
few studies stray from the default AET equations of their chosen model. In recent years, studies have increasingly adopted
multi-objective calibration approaches, some incorporating AET alongside streamflow to enhance model performance.

60 Research demonstrates that integrating AET into calibration not only enhances the accuracy of AET estimates (Arciniega-
Esparza et al., 2022; Dembélé et al., 2020; Herman et al., 2018; Rientjes et al., 2013) but can also improve the simulation of
total water storage (Bai et al., 2018; Pool et al., 2024). Despite these advances, the characterisation of AET accuracy may be
limited to the consideration of aggregate measures of performance, which led Gardiya Weligamage et al. (2025a) to propose

the use of “signatures”, a concept borrowed from streamflow evaluation (e.g. McMillan, 2021), to separately characterise
65 different aspects of AET dynamics.

Few studies have systematically compared AET equation options in a controlled way. For example, previous research has investigated which AET products are best to use in calibration (Taia et al., 2023) and assessed the impact of using different PET forcing inputs (Bai et al., 2016), but the impact of the equations themselves has not been investigated. Studies examining the performance of modelled AET are often confined to assessing the default equations built into specific hydrological models
70 (Arciniega-Esparza et al., 2022; Dembélé et al., 2020; Guo et al., 2017; Herman et al., 2018; Rientjes et al., 2013). This approach makes it difficult to disentangle whether differences in performance are from the AET equation itself or from the surrounding model structure. By systematically evaluating AET equations in isolation, independent of broader model-specific assumptions, we can better understand their individual strengths and limitations. Additionally, many commonly used equations may already encode elements of process understanding that are not immediately apparent. Assessing their empirical
75 performance in a controlled framework could reveal implicit process representations, offering insights that inform both conceptual and process-based model development. This is particularly important given the continued reliance on conceptual models in many water resource applications.

The aim of this study is to evaluate the performance of different AET equations in conceptual hydrological models at the daily timestep, focusing on their ability to reproduce observed AET, while also considering the impact (if any) on streamflow
80 simulation. This study’s novelty lies in its systematic evaluation of different AET equations while holding other aspects of the model structure constant. In addition, novel aspects include the wide range of different AET equations tested, the use of multi-objective calibration incorporating flux tower derived AET data, and the use of AET signatures in model evaluation.

2 Methods

2.1 Overview of methodology

85 As noted above, a key limitation in previous studies is that comparisons of AET performance have been made between entire models, rather than isolating the contribution of individual AET equations. -Thus, it is impossible to tell whether differences in performance are due to the AET equation used within the model or the surrounding model structure.— To address this, we systematically substitute a range of AET equations into a fixed model structure, testing each in turn. To ensure the findings are not model-specific, this process is repeated across three commonly used conceptual hydrological models, treating each
90 model as a consistent “container” for testing the equations.

The AET equations are based on the study of Knoben et al. (2019), who conducted a systematic review of 47 existing conceptual rainfall runoff models, compiling them into the Modular Assessment of Rainfall-Runoff Models Toolbox (MARRMoT) framework. This framework’s structure isolates the unique equations used for a particular process such as AET—i.e. although there are 47 models, there are not 47 different AET equations because multiple models may use the same
95 AET equation. This unique MARRMoT list forms the basis of the AET equations tested here. In addition, MARRMoT is used

for the simulation experiment itself. It provides an effective framework for addressing these challenges because it is set up to ensure consistent model implementation, allowing for intercomparison and modification of model structures and internal components. By leveraging MARRMoT, the performance of various AET equations can be systematically investigated within consistent conceptual model structures, addressing the gaps identified above. By advancing the representation of AET, this study contributes to more robust and reliable hydrological modelling practices particularly under changing environmental conditions, where traditional model assumptions are increasingly challenged.

Specifically, (as indicated in Fig. 1), this study systematically evaluates 15 evapotranspiration (AET) equations by substituting them into the models, applied across seven catchments. Each model is individually calibrated ($15 \times 3 \times 7 = 315$ calibrations) using a multi-objective function that equally weights the match to both streamflow and flux tower-derived AET data. All simulations were performed at a daily time step, and a catchment water balance was applied to the flux tower derived AET, discussed in detail in section 2.4.




Figure 1: General methodology visualisation. By holding the model structure constant and only varying the AET equation, this approach isolates the influence of different AET equations on model performance.

We utilise flux tower data as our benchmark for evaluating actual evapotranspiration (AET) in hydrological models because it provides direct, high-temporal resolution observations of surface energy and water fluxes (Beringer et al., 2022). Compared to remotely sensed AET estimates, which offer broader spatial coverage, flux tower data avoids uncertainties related to satellite retrieval algorithms and coarse spatial and temporal resolution, including uncertainty around overpass timing, which may not align well with daily model time steps. Additionally, Gardiya Weligamage et al. (2025c) assessed the quality of remotely sensed AET across Australia and identified several limitations of remotely sensed AET, including seasonal inconsistencies and variability issues. The flux tower data used here is sourced from the TERN-OzFlux (Terrestrial Ecosystem Research Network) dataset, which is the Australia and New Zealand portion of the Fluxnet network of stations that measure carbon, water, and energy fluxes (Beringer et al., 2022).

Nonetheless, flux tower measurements are point-based, while hydrological models simulate catchment-averaged fluxes, leading to a scale mismatch that requires careful consideration. A recent study by Gardiya Weligamage et al., (2025c) paired 15 OzFlux sites with nearby catchments from the CAMELS-AUS dataset (Fowler et al., 2025) and evaluated simulations from several models. To further address this issue, we applied strict selection criteria, focusing only on flux tower–catchment pairs where we had reasonable confidence in representativeness. In addition to geographic proximity, we required close alignment in precipitation and temperature regimes, and placed particular emphasis on land cover similarity, given the importance of vegetation dynamics in controlling AET. Sites were excluded where vegetation type, structure, or density diverged markedly between the tower footprint and the broader catchment. This process aimed to reduce discrepancies between observed and modelled AET that could otherwise result from mismatched biophysical controls.

While we acknowledge the scale limitations of point-based flux data, supplementary analysis from Gardiya Weligamage et al. (2025c) suggests that even distant flux tower observations (up to hundreds of kilometres away) often provide more realistic AET estimates than co-located remotely sensed data. This highlights the value of flux tower measurements for hydrological model evaluation, particularly when accompanied by rigorous site selection.


2.2 Study area

The selected flux tower sites represent a range of climatic zones and vegetation types characteristic of the diverse Australian hydrological conditions, as outlined in Table 1, and shown in Fig. 2. Their selection ensures that the findings are applicable to broader Australian conditions.

Table 1: Details on catchments and flux tower sites. Note mean daily AET is from the flux tower information, and adjustment factors are described in section 2.4. Additional catchment and flux tower information can be found in the supplementary materials [table Table S1](#).

Flux tower site name	Flux tower site description	Flux tower site loc.	Nearby catchment code	Catchment size (km ²)	Mean daily P (mm/d)	Mean daily Q (mm/d)	Mean daily AET (mm/d)	Adjustment factors
Wombat Forest	Mixed Eucalyptus forest	-37.4, 144.1	407221	167.5	2.19	0.37	2.42	0.81
Whroo	Box woodland forest	-36.7, 145.0	405229	108.7	1.44	0.08	1.49	0.84
Tumbarumba	Alpine ash forest	-35.7, 148.2	401009	215.5	2.82	0.43	2.40	0.94
Robson Creek	Tropical rainforest	-17.1, 145.6	111007A	521.4	7.11	4.14	2.90	1.54
Litchfield	Burnt tropical savanna	-13.2, 130.8	G8150180	1044.2	3.90	1.38	3.13	0.85

Dry River	Open forest savanna	-15.3, 132.4	G8140011	4794.5	2.07	0.12	2.13	0.99
Gingin	Coastal heath Banksia woodland	-31.4, 115.7	617003	1404.1	1.81	0.06	2.42	0.63



140 **Figure 2: Map of Australia showing the seven flux tower sites and their associated catchments.**

2.3 Data

OzFlux eddy covariance evapotranspiration data were accessed from OzFlux towers through the Terrestrial Ecosystem Research Network (TERN) data portal (<https://portal.tern.org.au/>, 2024 Version 2, last accessed 07/03/2025) using level 6, quality controlled and gap filled daily time scales. The dates of the flux tower data availability differ between sites. The full data periods used in calibration are shown in [table-Table S1](#) of the Supplementary Materials, where any missing values were excluded from the analysis.

145 Remaining hydrometeorological data were sourced from the CAMELS-AUS dataset which covers the period from 01 January 1950 to 26 May 2022. Potential evapotranspiration data (specifically Morton’s Wet Environment Evaporation) are provided

in CAMELS and sourced from the Scientific Information for Land Owners, or SILO, database, published by the state of
150 Queensland (<https://www.longpaddock.qld.gov.au/silo/>, last accessed 15/01/2025). Precipitation data were provided in
CAMELS and sourced from the Australian Gridded Climate Data (AGCD) dataset of the Bureau of Meteorology
(<https://portal.ga.gov.au/>, last accessed 15/01/2025). Streamflow data were also obtained from this dataset, and any missing
values were excluded from the analysis.

2.4 Flux tower data adjustment

155 Building on the careful selection of representative tower-catchment pairs (Section 2.1), we further adjusted the flux tower AET
data to improve comparability with catchment-scale values. Since actual evapotranspiration at the catchment scale is not
directly measurable, we applied a long-term water balance approach to provide an independent estimate of long-term
catchment-average AET and adjust the flux tower data accordingly. This adjustment involved calculating a linear scaling factor
that was applied to the full flux tower AET time series, correcting the ~~long-long-term~~ average without altering the intra-annual
160 shape of the AET curve. This approach assumes that while the temporal dynamics of AET at the flux tower (e.g. seasonal
dynamics) are broadly representative of catchment-scale behaviour, the magnitude may differ due to spatial heterogeneity in
vegetation, soil properties, or microclimate.

To derive the scaling factor via catchment water balance, we assumed negligible long-term change in storage ($\Delta S \approx 0$). This is
a common assumption in hydrology, justified here by the fact that the water balance components: precipitation (P), streamflow
165 (Q), and AET, are aggregated over a multi-year period. As such, any difference in storage between the start and end of the
period is small relative to the cumulative fluxes and has minimal influence on the resulting estimate. The catchment water
balance therefore simplifies to:

$$\Delta S = P - Q - AET \rightarrow AET_{catchment} = P - Q, (1)$$

where P is long-term average precipitation and Q is long-term average streamflow, both measured over the same period as the
170 flux tower record. The corresponding long-term average AET from the flux tower, AET_{tower} , was calculated from the eddy
covariance measurements. A scaling factor f was then derived as:

$$f = \frac{AET_{catchment}}{AET_{tower}}, (2)$$

This factor was applied to the full flux tower time series:

$$AET_{adjusted}(t) = f \times AET_{tower}(t), (3)$$

175 This adjustment ensures that the flux tower data matches the long-term magnitude of AET estimated at the catchment scale,
while preserving its temporal variability. Combined with careful catchment selection, this was deemed the most practical
method available to reduce scale mismatch and increase confidence in data used for the model evaluation.

2.5 Models and equations

This experimental setup, introduced in Section 2.1, was applied across three model structures - GR4J, Simhyd, and VIC - which were selected from the 47 options in MARRMoT to represent a range of complexity and conceptual assumptions. GR4J is the most parsimonious model, with four parameters and two representative storages (Perrin et al., 2003). Simhyd represents an intermediate level of complexity, with seven parameters and three storages (Chiew et al., 2002). VIC is the most complex model chosen, comprising ten parameters and three storages (Liang et al., 1994). In Simhyd and VIC, AET is drawn from multiple storages, and the evaluation of AET simulations was always conducted on the sum of AET across these storages. However, this still leaves the question of which storage is subject to the experimental changes in equations. For the purposes of this study, the AET equation was substituted into only the primary soil moisture storage, which is assumed to contribute most to total evapotranspiration in these model structures. The remaining storages retained their original AET formulations. The decision to apply the equation changes only to the primary soil moisture storage was made a priori, recognising that the contribution of each storage may vary depending on parameter values. As stated, calibration and evaluation performance scores are based on the total modelled AET, regardless of the internal distribution across storages.

Additionally, extending alternative AET formulations to all storages would require introducing additional parameters for each storage, substantially increasing model dimensionality and calibration complexity. This would make it more difficult to reliably attribute differences in model performance to the AET formulation itself. Furthermore, maintaining a consistent implementation across different model structures is important for intercomparison. Applying different modifications across models would reduce comparability of results. Finally, some storages (e.g. interception) represent fundamentally different physical processes, and modifying their AET formulation would be inconsistent with their conceptual role. The chosen approach therefore represents a pragmatic compromise that allows differences in AET formulation to be isolated while maintaining model interpretability.

Across the 47 models in MARRMoT there are 23 unique AET equations, but the experiment did not test all 23 because some are incompatible with the three chosen models, ~~and also~~ and because we found some redundancy between the equations. For instance, some equations used different names for equivalent parameters, such as maximum storage represented as "Smax" in one equation and "S3 parameter" in another. When simplified, these equations were found to have the same functionality. Additionally, two equations were excluded because they were designed to operate on soil moisture storages defined in a "deficit" manner, which was not compatible with the three selected models. Following the process of simplifying equations to ensure compatibility with the chosen models and removing redundant parameters, 15 of the 23 equations remained. These equations retained their original naming according to the MARRMoT framework.

Table 2 provides an overview of the selected 15 equations, including their corresponding number within MARRMoT, the number of additional parameters required, descriptions as provided in MARRMoT, and simplified formulas. Additionally, the list of models that utilise each equation can be found in Table S2 of the Supplementary Material. The resulting 15 AET equations represent diverse approaches to modelling the conversion of potential evapotranspiration (PET) into actual

evapotranspiration (AET) as a function of soil moisture. This diversity of equations allows for a robust experiment that represents the diversity of current practice in conceptual modelling. These approaches fall into five major relationship types, which are summarised below:

- Linear relationships with soil moisture (AET equations `evap_1`, 7 and 11) assume a direct proportionality between soil moisture and evapotranspiration.
- Threshold-based relationships (6, 8, 16, 21, 22, and 23) impose thresholds (e.g., wilting points or storage thresholds) that control when and how PET translates into AET.
- Nonlinear relationships with soil moisture (4, 13, 19, and 20) include non-linear scaling factors to represent more complex vegetation or soil interactions.
- Multi-component representations (3, 20, 23) explicitly separate processes such as transpiration from vegetation and evaporation from bare soil.
- Evaporation-rate limitations (20 and 22) cap AET to a maximum rate or constrain it below certain thresholds

Table 2. Description of the 15 AET equations. `p1` and `p2` are additional parameters, whereby `[0-1]` indicates the parameter is set between 0-1, and `[mm]` indicates it is an unbound parameter with the value representing millimetres. ***The function `f(S,0.01)` refers to “Smooth_Storage_Threshold_Function”, `(S, 0.01)` refers to a logistic smoothing function implemented in MARRMoT, which gradually reduces fluxes as storage (S) approaches a lower threshold. This avoids abrupt cut-offs by applying a smooth, continuous transition, governed by a steepness parameter (here, 0.01, inherited from MARRMoT), allowing for more numerically stable and physically plausible flux behaviour when storage is low.

Equation no. evap_X (from MARR MoT)	Extra parameters	Description	Formula simplification	Features				
				Linear scaling	Quadratic scaling	Exponential scaling	Nonlinear scaling	Threshold based
7	0	Evaporation scaled by relative storage	Minimum of $(S / S_{max}) \times PET$ S	X	-	-	-	-
11	0	Evaporation quadratically related to current soil moisture	$(2 \times (S / S_{max}) - (S / S_{max}^2)) \times PET$	-	X	-	-	-
1	0	Evaporation at the potential rate	Minimum of S PET	X	-	-	-	-
16	1	Scaled evaporation if another store is below a threshold	Minimum of $p1[0-1] \times PET \times \text{SmoothStorageThresholdFunction}(f(S, 0.01))$ *** S	-	-	-	-	X

2	1	Evaporation at a scaled, plant-controlled rate	Minimum of • $p1[mm] \times S / S_{max}$ • PET • S	X	-	-	-	-
19	2	Non-linear scaled evaporation	Minimum of • S • PET • $p1[0-1] \times PET \times S / S_{max}^{p2[0-1]}$	-	-	-	X	-
21	2	Threshold-based evaporation with constant minimum rate	Minimum of • Maximum of ○ $p1[mm] \times p2[0-1]$ ○ PET $\times$ minimum of ▪ $S / p1[mm]$ ▪ 1 • S	-	-	-	-	X
23	2	Transpiration from vegetation at the potential rate if storage is above field capacity and scaled by relative storage if not, addition of evaporation from bare soil scaled by relative storage	Minimum of • PET / $S_{max} \times PET$ • PET $\times S / (p1[0-1] \times S_{max}) + S / S_{max} \times PET$ • S	X	-	-	-	X
4	2	Constrained, scaled evaporation if storage is above a wilting point	Minimum of • PET $\times p1[0-1] \times (S - p2[0-1] \times S_{max}) / (S_{max} - p2[0-1] \times S_{max})$ • S • 0	-	-	-	X	X
3	2	Evaporation based on scaled current water storage and wilting point	Minimum of • $S / (p1[0-1] \times S_{max} \times PET)$ • PET • S	X	-	-	-	-
6	2	Transpiration from vegetation at the potential rate if storage is above a wilting point and scaled by relative storage if not	Minimum of • PET $\times S / (p1[0-1] \times S_{max})$ • PET • S	X	-	-	-	-
8	2	Transpiration from vegetation, at potential rate if soil moisture is above the wilting point and linearly decreasing if not. Also scaled by relative storage across all stores	Minimum of • Minimum of ○ PET ○ $S / p1[mm] \times PET$ ○ S • 0	X	-	-	-	X
13	2	Exponentially scaled evaporation	Minimum of	-	-	X	X	-

			• $p1[0-1]^{p2[0-1]} \times PET$ • S						
20	2	Evaporation limited by a maximum evaporation rate and scaled below a wilting point	Minimum of • $p1 [mm] \times S \div (p2[0-1] \times S_{max})$ • PET • S	X	-	-	-	X	
22	2	Threshold-based evaporation rate	Minimum of • S • $(S \times p1[mm]) \div (p2[mm] - p1[mm]) \times PET$ • PET	X	-	-	-	X	

230 2.6 Calibration

The calibration approach was based on single objective optimisation to a composite objective function that equally weighted the performance of the model against streamflow data from CAMELS-AUS and AET data from the flux towers. For streamflow (Q), a Kling–Gupta Efficiency (KGE) (Gupta et al., 2009) derived objective function was used that incorporates separate penalties for bias in high- and low-flow regimes, as described in Trotter et al. (2023, Equation 1) (Eqn. 4). Specifically, the component of Eqn. 4 assessing low-flow performance is the KGE calculated on flow raised to the power of 0.2, the component focussed on high flows is the standard KGE, and the component focussed on bias is the final term in the equation. Please see Trotter et al. (2023) for more information. For AET, the KGE was applied to square-root-transformed data, following Gardiya Weligamage et al. (2025b) (Eqn. 5), where d is daily and m is monthly. This calibration approach ensured that both monthly and seasonal dynamics of AET were incorporated, alongside a commonly used method for streamflow. Both objective functions are similarly bounded KGE-based metrics and therefore exhibit comparable numerical ranges during calibration. As a result, equal weighting of the two objective functions leads to approximately equal contribution to the combined objective function value (OFV), which was computed as the mean of the streamflow and AET objective values (Eqn. 6).

$$OFV_{Streamflow} = \frac{1}{2} (KGE_Q + KGE_{Q^{0.2}}) - 5 \times \left| \ln \left(1 + \left(\frac{mean(Q_{simulated} - Q_{observed})}{mean(Q_{observed})} \right) \right) \right|^{2.5}, \quad (4)$$

$$OFV_{AET} = \frac{1}{2} (KGE_{daily-AET_d^{0.5}} + KGE_{monthly-AET_m^{0.5}}), \quad (5)$$

$$OFV = 0.5 * (OFV_{Streamflow} + OFV_{AET}), \quad (6)$$

Model calibration was performed using the Covariance Matrix Adaptation Evolution Strategy (CMA-ES) algorithm, a high performing algorithm commonly used in hydrology (Arsenault et al., 2014), as implemented in the default calibration framework of MARRMoT v2.1 (Trotter et al., 2022). This study focuses on identifying a single optimal parameter set for each configuration, rather than exploring the full parameter uncertainty space.

250 **2.7 Process and data analysis**

In order to systematically test the available AET equations, the 15 AET equations were individually substituted into each model. This was repeated for all seven catchments, resulting in 315 calibrations. AET equations were ranked to determine which performed best according to the objective function values described above.

255 In addition to traditional objective function values, we conducted a more comprehensive assessment of model performance by analysing results based on evapotranspiration signatures, as defined by Gardiya Weligamage et al. (2025b). These signatures, similar to commonly used streamflow signatures (e.g. (McMillan, 2021)), provide insights into whether the models can reproduce specific aspects of AET. The eight calculated AET signatures are: long-term median and inter-annual variability for annual dynamics; peak timing and lag-12 correlation for seasonal dynamics; water stress, variability, and synchronicity for monthly dynamics; and rainfall event responsiveness for daily dynamics.

260 Finally, we conducted split-sample testing to evaluate how well the updated models responded to previously unseen data. In this study, split-sample testing refers specifically to temporal split-sample validation, and does not assess spatial transferability or proxy-basin performance. Evaluating with data outside the calibration period ensured that the identified improvements in model performance were not an artifact of overfitting but instead reflected a more generalisable enhancement in AET representation. For brevity, this test was conducted only on the highest performing AET equation in calibration, as a final
265 robustness check, rather than as a systematic assessment of overfitting across all equations which would add substantial complexity.


The available AET data were divided in half, with calibration performed on the first half and evaluation on the second and repeated in reverse for a second calibration. The length of the calibration and evaluation periods varied between catchments, reflecting differences in the availability of flux tower observations (see Table [S7S6](#)). The relatively short duration of flux tower
270 records at some sites may limit the ability of the split-sample test to fully capture long-term model behaviour. This procedure was applied to all catchments and all three models, comparing the original model formulation with the version incorporating the best-performing evapotranspiration equation.

3 Results

3.1 Overview of results

275 Figure 3₇ provides an example of AET model outputs by showing a time series of simulated AET at one of the seven sites, Wombat Forest, using the Simhyd model. In this figure, Simhyd was recalibrated with each of the 15 AET equations independently, such that differences in simulated AET arise solely from the choice of equation, with all other model components held constant. The observed flux tower AET (catchment adjusted) is shown as a thick blue line, while the model outputs from the various AET equations are displayed in different colours. PET (grey) and rainfall (inverted, light blue) are
280 also shown to illustrate the key drivers of AET and help contextualise model behaviour.

This figure highlights the variation in simulated AET that arises solely from substituting the AET equation, demonstrating the sensitivity of e-model outputs to this component-of-the-model. Similar outcomes were observed across other catchments and model structures (21 figures total), with the remaining plots included in the supplementary materials (S4S3) for reference.



285 **Figure 3. Observed flux tower data, precipitation, and PET for Wombat Forest, Victoria, Australia. 15 calibrations showing simulated AET at the site (evap_1, evap_2, etc.) for the base model (Simhyd).**

As noted, each AET equation is optimised individually across streamflow and actual evapotranspiration (AET) objective function values (OFV), resulting in 315 calibrations (3 models $\times$ 7 catchments $\times$ 15 equations). Table 3 displays the summary of these results by ranking the combined OFVs to two decimal places for each model and catchment, with a rank of 1 indicating the best-performing equation. Equal ranks were assigned when the rounded values (to two decimal places) were equal. Full tables with raw OFV scores and rankings are included in the supplementary materials (S2S4). The summary shown here aggregates rankings across all catchments for each model and-also-and provides an overall ranking across all models.

AET equation evap_19 emerges as the overall top performer, achieving the highest average rank. AET equations 3, 8, and 21 also rank highly, though their performance varies more noticeably across model structures (e.g., Simhyd vs GR4J).

295 **Table 3. Summary of AET equation rankings (1 = best; 15 = worst) based on combined streamflow and actual evapotranspiration (AET) objective function values (OFVs). Rankings are averaged across all catchments for each model (GR4J, Simhyd, and VIC). The final column shows the overall ranking across all models. An asterisk is placed in each model’s column next to its “native” equation’s performance. See S4 for more details including the quantitative performance metrics corresponding to these rankings.**

AET equation	GR4J	Simhyd	VIC	All models
1	15	14	15	15

2	12	5*	12	12
3	5	3	8	4
4	11	5	3	5
6	5	8	11	7
7	10	12	2*	9
8	5	2	8	3
11	9*	11	5	11
13	8	10	6	9
16	7	9	9	11
<u>19</u>	<u>1</u>	<u>1</u>	<u>1</u>	<u>1</u>
20	13	13	13	13
21	2	6	4	2
22	14	15	14	14
23	5	8	11	7

To further explore the calibration results, Fig. 4 separates the combined objective function values into their two components: streamflow and AET performance. Each subplot represents a catchment, showing variations across all models and AET equations (15 points per model, 45 total). The most effective AET equations appear toward the top-right quadrant, indicating strong performance on both streamflow and AET objectives. The native (original) AET equation used in each model is marked with a black star, and AET equation evap_19 is highlighted in red for reference. These plots visually represent that while some models exhibit catchment-specific variations (e.g., GR4J's poor performance for Whroo), ~~it is noted~~ evap_19 consistently ranks among the best.





Figure 4. Trade-off plots of objective function values (OFVs) for streamflow (x-axis) and AET (y-axis), shown for each catchment. Each subplot displays all 45 calibrations (15 AET equations × 3 models), with AET equation evap_19 highlighted in red and native AET equations marked with black stars. Higher values indicate better model performance.

310 Despite some promising results, certain hydrological behaviours remain poorly represented. For instance, even the four best-performing AET equations (3, 8, 19, and 21) fail to perform adequately at specific sites. This is evident when comparing results at Tumbarumba and Litchfield (Fig. 5a and 5b, respectively). All models provide reasonable estimates of AET at Tumbarumba, and both Simhyd and VIC perform reasonably well at Litchfield. However, GR4J significantly overpredicts AET at Litchfield.



315 **Figure 5. Modelled AET vs. observed flux tower data, showing the four best performing AET equations across the three models at Tumbaramba (a) and Litchfield (b).**

To explore this discrepancy, GR4J was recalibrated for Litchfield using only AET, giving the model the best possible chance to match observed AET without the constraint of streamflow calibration. However, even under these conditions, GR4J still failed to replicate AET accurately at this site, indicating a possible structural limitation in the model. Results of this analysis
320 are shown in supplementary materials ([S3S5](#)), which includes the performance of all plausible equations under AET-only calibration. No improvement in AET performance was observed compared to the results shown in Fig. 5b.

3.2 Signatures

Beyond matching overall OFV scores, AET equations were also assessed using evapotranspiration signatures (Gardiya Weligamage et al., 2025b). Similar to hydrological signatures, these metrics break down AET behaviour into distinct
325 components, focusing on characteristics such as the mean, variability and periodicity of AET. Across all eight signature plots,

we observe broadly consistent patterns in terms of model performance, so only one representative scatterplot is shown here. An exception was the interannual variability signature (Fig. S246-2), which exhibited very similar patterns across all models and AET formulations. This may suggest that this signature is primarily driven by the precipitation forcing rather than differences in model structure or AET formulation. An alternative view, given this signature is not very well simulated, is that all models tested are subject to similar limitations in simulating this aspect of AET dynamics, regardless of choice of equation. Either way, it provides limited discriminatory power for evaluating AET equation performance in this framework.

Below we focus on a timing-based signature, namely monthly AET asynchronicity with PET (Fig. 6), while the remaining signatures are shown in the supplementary materials (S4S6). This signature captures the degree to which AET follows the seasonal cycle of PET, independent of magnitude, with greater asynchronicity suggesting a decoupling between the two. Including this signature helps evaluate whether equations reproduce not just how much evapotranspiration occurs, but when it occurs—a key aspect of improving process representation in conceptual models. For example, high asynchronicity might suggest that a model fails to capture stomatal regulation or delayed transpiration responses to atmospheric demand, processes that are critical under drought or seasonal stress.

The results indicate that while some equations clearly perform poorly, there are a few that consistently align well with the observed signatures, including across multiple metrics. These better-performing equations also generally agree with those identified through OFV-based testing. Notably, AET equation evap_19 is among the top performers across all signature comparisons.




Figure 6. Monthly asynchronicity of AET: observed vs. simulated, across all equations and models. AET equation evap_19 is highlighted with a red box. Remaining signature plots are in supplementary materials S4S6. This signature is purely based on the

asynchronicity between normalised PET and AET, calculated by quantifying the area between the normalised curves, and is indicative of seasonal water stress.

3.3 Split sample test of AET equation evap_19

350 As an evaluation of robustness, a split-sample test was conducted, comparing the original model formulations with those incorporating the best-performing evapotranspiration equation, AET equation evap_19 (Fig. 7). Each model was calibrated on one half of the data and evaluated on the other, with results reported separately for AET and streamflow (Q).

For the calibration period, (and as shown previously), models using evap_19 achieved higher AET objective function values (OFVs) across all catchments compared to the base equations (Fig. 7a). Streamflow performance also generally improved under evap_19 during this period (Fig. 7b). As for the evaluation period for AET, equation evap_19 consistently improved 355 performance, maintaining higher OFVs across most catchments, similar to the trend observed in calibration (Fig. 7c).

For streamflow, the evaluation period results were more variable. While some catchments showed improvements with evap_19, others performed similarly or worse than the original formulation (Fig. 7d). Notably, catchments that performed poorly under the original AET equation also tended to have low performance under evap_19.

It is important to acknowledge that the available flux tower data covers a relatively short timeframe, which may limit the 360 reliability of this test in fully capturing long-term model behaviour (see supplementary materials [SSS1](#)). This constraint could, in part, explain discrepancies in streamflow performance during evaluation. Despite this, the results provide evidence that integrating evap_19 enhances AET representation and, in many cases, improves model performance beyond AET.




Figure 7. Split-sample test results showing objective function values for AET and streamflow (Q). Each point represents a model–catchment combination calibrated on one half of the data and evaluated on the other. Panel figures are as follows: results during the calibration period for AET (a) and streamflow (b), and results during the evaluation period for AET (c) and streamflow (d). Note: Streamflow points with OFVs < −1 under the base equation are omitted.

3.4 Seasonal timing of AET

Overall, with an appropriate choice of equation, the models capture AET dynamics relatively well compared to the default options. However, a key feature that emerged upon closer examination of the time series (Fig. 5) was that modelled actual evapotranspiration (AET) appeared to peak earlier than observed flux tower data. This pattern is also apparent in most other catchments (see supplementary materials [S4S3](#)). To investigate this further, we expanded the analysis of the “monthly peak” signature. Specifically, we examined a 7-month window centred on the observed peak month (i.e., three months before, the

peak month itself, and three months after). Based on the time series patterns, it appeared that the models were overestimating AET before and during the peak while underestimating it afterward.

To test this, we quantified the proportion of AET occurring in the three months leading up to and including the peak, expressed as a percentage of the total AET over the 7-month period. This metric was then used to assess how well the models reproduced the observed AET distribution. The calculation was focused on the best-performing evaporation equation (evap_19), for the three hydrological models across the seven catchments under the multi-objective calibration to both streamflow and AET (Fig. 8.a).

To determine whether this timing mismatch was due to model structure, we repeated the analysis calibrating solely to AET to assess whether the models had the capacity to match the observed timing more accurately (Fig. 8.b). This approach was chosen to isolate the influence of streamflow constraints on seasonal AET behaviour.

Finally, we calibrated to streamflow alone to evaluate how much the AET timing deteriorated when AET was not explicitly considered in the calibration process (Fig. 8.c). The results of this analysis are presented in Fig. 8, which confirms the initial impression about early timing of simulated AET. Further, it shows that although the AET distribution improves when calibrating to AET alone, seasonal AET timing remains a clear limitation of the models, even when utilising equation evap_19. To assess whether this behaviour is sensitive to the choice of PET forcing, an additional analysis using an alternative PET formulation is presented in the Supplementary Material (S8), where the overall results were consistent with the original PET input results seen in Fig. 8.




Figure 8. Percentage of AET which occurs in the first half of the observed seasonal peak, for each catchment and model combination, utilising evapotranspiration equation `evap_19`. The models are calibrated to (a) streamflow and AET, (b) AET only, and (c) streamflow only. Note: The 7-month period is determined by identifying the peak month of observed AET (the most common peak month across the flux data time period—one of the AET signatures). The values shown represent the total AET accumulated in the first four months (including the peak month) as a percentage of the total AET over the full 7-month period. Catchments are ordered by increasing total AET over the 7-month period.

4 Discussion

400 4.1 Overview of findings

This study systematically tested 15 AET equations within three widely used conceptual rainfall-runoff models across seven catchments with nearby flux tower AET data. This responds to the call for evaluation of evapotranspiration in hydrological models in previous work (e.g. Kelleher & Shaw, 2018; Dembélé et al., 2020), by isolating equation performance from model structure. Our results show that, while absolute performance varied across catchments and models, a small subset of AET
405 equations, particularly equation `evap_19`, consistently ranked among the top performers relative to the others. Equations 3, 8, and 21 also performed well in some cases but exhibited more variability across models and sites.

While this study primarily focuses on AET equation performance rather than inter-model comparisons, some patterns emerged. For example, GR4J struggled to replicate AET at certain sites (e.g., Litchfield), even when recalibrated using AET-only optimisation. This suggests possible structural limitations in GR4J's partitioning of available water between AET and runoff,
410 highlighting the importance of model-specific considerations when selecting or modifying AET equations.

The main remaining issue across models was that AET often peaked earlier than observed in the flux tower data. While Equation `evap_19` consistently outperformed the others, it only partially addressed this problem—reducing but not eliminating the seasonal timing mismatch. Below, we first examine why equation `evap_19` provides superior simulations, before unpacking the broader implications, both for equation `evap_19` and the remaining challenges highlighted by this study.

415 4.2 Why is `evap_19` best?


To understand why `evap_19` provides improved simulations, we first need to examine how it differs from other formulations. The structure of the equation is:

$$AET = \min(S, PET, p_1 \times PET \times \left(\frac{S}{S_{max}}\right)^{p_2}), (7)$$

Two key features stand out: (i) its ability to restrict AET to below PET, even under high soil moisture conditions, via the p_1
420 parameter; and (ii) its concave, non-linear relationship between AET and relative soil moisture, shaped by the p_2 parameter. Both parameters are restricted between 0 and 1.

The p_1 parameter introduces a physically meaningful limitation, reflecting that vegetation or atmospheric conditions often prevent actual evapotranspiration from reaching its potential rate.

The p_2 parameter governs how AET responds to soil moisture: when $p_2 = 1$, the relationship is linear; when $p_2 < 1$, the
425 relationship becomes concave, meaning AET increases rapidly at low soil moisture levels but tapers off as soil moisture becomes abundant. This behaviour appears to better reflect vegetation function in these catchments, where plants actively transpire when water is limited but taper water use under wet conditions, aligning with the need for more physically grounded representations of vegetation-mediated water use (Deb & Kiem, 2020).



430 **Figure 9. Comparison of equation evap_19 with a typical evapotranspiration formulation (here the generic equation is represented as evap_19 where p_1 and p_2 equal 1). (a) p_1 parameter-driven behaviour: Time series of AET/PET over 15 days, illustrating how evap_19 constrains AET to remain below PET. (b) p_2 parameter-driven behaviour: Relationship between relative soil moisture (SM/S_{max}) and AET/PET, showing the stronger non-linear response of AET equation evap_19 to changes in soil moisture availability.**

The calibrated values of these parameters across the seven catchments and three models (see supplementary materials [S6S9](#)) show that p_1 values were generally well below 1.0, indicating that this PET-limiting feature was frequently required to match observed AET patterns. For instance, in VIC, p_1 ranged from 0.28 (Gingin) to 1.00 (Robson Creek), with similarly constrained values in GR4J and Simhyd. This suggests that the models often needed to invoke sub-PET limitations, which may reflect transport limitations on evapotranspiration, although further evidence is needed to confirm this. The p_2 values also varied between catchments, often falling below 0.5 (e.g., Wombat Forest, Tumbarumba), indicating the need for a concave soil moisture response. That is, AET increases quickly under dry to moderate conditions but becomes less sensitive as soil moisture approaches saturation. While some evapotranspiration equations assume AET will continue increasing proportionally with soil moisture, this behaviour appears inconsistent with the flux tower data and the known role of vegetation in regulating water loss.

Together, these features help explain why equation evap_19 outperformed alternatives: it avoids the assumption that AET always equals PET under moist conditions, reduces over-extraction of water, and better captures the dynamic relationship between soil moisture and evapotranspiration observed in flux tower data.

Conversely, the poorer-performing AET equations exhibited several recurring issues. Many lacked explicit constraints or responded too linearly to changes in soil moisture, resulting in rapid water depletion and elevated AET values that rarely match flux tower behaviour. Several formulations allowed AET to equal PET frequently—an outcome that overlooks the regulatory role of vegetation and other limiting processes.

However, despite evap_19's relative improvements, it does not fully resolve all issues. As shown in Fig. 8, it still overestimates AET in early-season periods. This suggests our conceptual models are lacking the knowledge that water availability does not lead to immediate transpiration. AET equation evap_19 mitigates this issue more effectively than the other tested equations, but the challenge remains.

455 4.3 Implications

Accurate AET representation is essential for reliable hydrological modelling, particularly when applied to future climate scenarios (Zhao et al., 2013). Incorrect AET modelling could propagate errors, leading to misleading projections of water availability, catchment response, and long-term water balance estimates. Ensuring that AET equations appropriately constrain AET to realistic values is therefore required to improve model robustness and predictive capacity.

460 The findings of this study highlight how assumptions embedded within many conceptual models, especially linear or overly simplified relationships between PET and soil moisture, can lead to systematic biases in AET simulations. These relationships are often taken for granted rather than being critically evaluated, despite their substantial influence on model behaviour. By drawing attention to this issue, we hope to encourage deeper scrutiny of the ways AET is represented within hydrological models, particularly in light of observed vegetation responses (Duethmann et al., 2020).

465 The strong performance of AET equation evap_19 could potentially be attributed to its origin of purpose, in the conceptual hydrological model LASCAM, which, during its creation, included thought on the inclusion of vegetation impacts (Sivapalan et al., 1996). This included the interaction of the deep-rooted eucalyptus trees found within Australia, ~~which leading~~ to the use of constraints on soil moisture availability and AET behaviour, which (as demonstrated here) are more realistic when evaluated against flux tower data. These insights suggest that existing models could benefit from replacing simplistic AET equations
470 with more process-informed alternatives or by developing new formulations inspired by evap_19.

The additional parameters introduced in equation evap_19 (p_1 and p_2) exhibit substantial variability across catchments (Table ~~S9S7~~), suggesting that location-specific calibration is necessary. These parameters represent unresolved controls on evapotranspiration, rather than strictly physical quantities. Their variability likely reflects differences in local evaporative regimes, vegetation characteristics, and climate conditions across catchments.

475 Therefore, an important direction for future research is to assess whether these parameters can be regionalised using mappable catchment attributes, such as aridity indices, vegetation functional types, or remotely sensed indicators of canopy dynamics. Additionally, incorporating spatially varying PET scaling approaches, such as crop coefficients or vegetation-adjusted PET, may help reduce the need for empirical suppression of AET under high moisture availability. These approaches would require more explicit representation of vegetation processes, which is beyond the scope of the current conceptual modelling framework
480 but represents a promising avenue for future work.

While AET equation evap_19 consistently improved model performance, its limitations offer insight into deeper ecohydrological processes that remain unaccounted for, such as the seasonal partitioning of AET. Although evap_19 better matches overall AET signatures, it does not fully capture the observed differences in AET between the beginning and end of

the season. Specifically, the catchments appear to be photosynthesising at a lower-than-expected rate (using less water and thus exhibiting lower AET) early in the season. This discrepancy likely arises because conceptual models, which lack explicit vegetation components, assume that water availability directly translates into immediate AET increases. In contrast, observed data suggest that the catchment does not use all available water at the start of the season, possibly due to physiological constraints on vegetation growth. If plants transpired at the rate the model predicts, they could experience excessive growth that would not be sustainable through the dry season. Similar findings have been reported in previous studies, such as Stephens et al. (2025), which found that catchments in intermediately wet regions (i.e. not arid or very wet) often exhibited lower-than-expected AET in wet periods. Lower-than-expected wet season transpiration was also demonstrated by Eamus et al. (2000) in savannah trees, suggesting that the vegetation's capacity to transport moisture may limit AET during the wet season.

The problems we found with seasonal timing of AET indicate that, even with improved AET parameterisation, conceptual models may still lack a critical physical mechanism governing seasonal water use. Future work should explore ways to incorporate such ecohydrological feedbacks into hydrological models, ensuring that the representation of AET accounts for vegetation constraints and long-term water availability strategies. Additionally, further studies should investigate whether this catchment behaviour is unique to Australian ecosystems or occurs more broadly. Australia's high interannual climate variability may encourage conservative water use strategies in vegetation that differ from those in more temperate or consistently wet climates (Norton et al., 2022). Exploring such geographic differences could help tailor model structures to better reflect regional vegetation–climate interactions.

An important source of uncertainty not explicitly explored in this study is the estimation of potential evapotranspiration (PET). Numerous studies have demonstrated that different PET formulations can produce different estimates of atmospheric evaporative demand, with implications for simulated evapotranspiration, soil moisture, and runoff (e.g. Oudin et al., 2005; Pimentel et al., 2023; Thakur et al., 2025). In the present analysis, PET formulation was held constant across all experiments in order to isolate the effects of AET formulation specifically. To understand the implications of PET formula choice for a key finding of this paper, we reproduced Fig. 8 with Mortons Point Potential PET (Fig. S6S30). As part of this additional analysis, all three models were re-calibrated across the seven catchments using the alternative PET forcing. While some catchment-specific differences in the magnitude of timing mismatch were observed, the overall patterns and conclusions remained unchanged. The timing bias in simulated AET persisted across PET formulations, indicating that the early seasonal peak identified in the original analysis is not a consequence of the choice of PET input.

Moving forward, systematic evaluations of internal flux equations in hydrological models should become standard practice, particularly when combined with multi-objective calibration approaches that leverage real-world data such as flux tower observations. Although we recognise limitations associated with flux tower coverage, using such data helps highlight where improvements to model structure, rather than parameterisation alone, may be needed. Additionally, further integration of empirically driven, process-based enhancements in hydrological models could help refine AET representation. These improvements would aid hydrologists in selecting AET equations that best match their specific modelling objectives, ultimately enhancing the reliability of hydrological simulations across diverse environmental conditions.

Our study's inclusion of many models, catchments, and AET equations provides a comprehensive assessment, but future work should explore individual model performance in greater detail. A logical next step would be to test AET equation `evap_19` within all 47 available hydrological models, using the same methodology applied here, to assess whether similar performance trends hold across a greater range of models. Additionally, this study did not evaluate AET equations in deficit-style hydrological models. Future research should extend this analysis to these alternative modelling frameworks to determine whether similar AET performance patterns emerge, particularly given evidence of more realistic AET dynamics in deficit models in water limited conditions (Fowler et al., 2021). Additionally, future research should consider testing these findings under spatial transferability and proxy-basins, explicitly targeting regionalisation or prediction in ungauged basins, an important avenue that lies beyond the intended scope of the present study.

It is also important to note that all results presented here are based on a single optimal parameter set for each model and catchment. Due to equifinality, there may exist a range of alternative parameter sets that produce similarly good performance but exhibit different trade-offs between streamflow and AET simulation, as well as different transferability properties (Khatami et al., 2019). For example, the strong performance of equation `evap_19` for AET, coupled with occasional reductions in streamflow performance, may in part reflect calibration trade-offs within a single optimal solution. A more comprehensive assessment of model behaviour could therefore be achieved by analysing ensembles of near-optimal parameter sets, which would allow uncertainty in parameter estimation and trade-offs between objectives to be more fully characterised. While this was beyond the scope of the present study, it represents an important direction for future work and should be considered when interpreting the robustness of the results.

Lastly, we note the limitation discussed above, namely that the best-performing AET formulation—which we recommend other researchers test and, if appropriate, adopt—does not entirely solve the issues regarding seasonal timing of AET in the catchments tested here. Continued exploration of equation-level performance in controlled testing frameworks, like the one used here, will help to identify process representations that bridge conceptual and process-based modelling—a critical direction for future model development (Knoben et al., 2019; McMillan, 2021).

Conclusion

This study conducted a systematic evaluation of 15 actual evapotranspiration (AET) equations within three conceptual hydrological models across diverse Australian catchments. By isolating AET formulations while holding other model components constant, this study was better able to identify variations in performance due to the AET equations themselves (as distinct from the surrounding model structure). AET equation `evap_19` consistently outperformed alternatives in both streamflow and AET objectives, as well as AET signature alignment. Its success appears linked to its non-linear soil moisture dependence and explicit limitation of AET below potential evapotranspiration, aligning better with observed flux tower data. Despite this improvement, persistent mismatches in seasonal AET timing, especially early-season overestimation, highlight limitations in current conceptual models. These results suggest that empirical equations alone may be insufficient to fully

550 capture vegetation-driven dynamics, especially under conditions of climatic or phenological change. While substituting AET equations such as AET equation `evap_19` can enhance performance, future work should aim to integrate ecohydrological mechanisms, such as plant water regulation and delayed transpiration responses, into model structures.

Overall, this research demonstrates the importance of critically assessing and selecting AET equations in conceptual modelling. Incorporating process-informed empirical equations and advancing the representation of vegetation dynamics will be essential

555 for improving the robustness of hydrological simulations by ensuring accurate water partitioning, particularly under changing environmental conditions.

Author contribution

GB: Conceptualisation, data curation, formal analysis, investigation, methodology, validation, visualisation, writing – original draft, review and editing.

560 KF: Conceptualisation, methodology, supervision, writing – review and edit

MP: Conceptualisation, methodology, supervision, writing – review and edit

CS: Conceptualisation, methodology, supervision, writing – review and edit

Competing interests

The authors declare that they have no conflict of interest.

565 **Acknowledgements**

This research was supported by an Australian Government Research Training Program Scholarship and an Ingenium Scholarship provided by the Faculty of Engineering Information and Technology, The University of Melbourne.

References

570 Arciniega-Esparza, S., Birkel, C., Chavarria-Palma, A., Arheimer, B., & Breña-Naranjo, J. A. (2022). Remote sensing-aided rainfall–runoff modeling in the tropics of Costa Rica. *Hydrology and Earth System Sciences*, 26(4), 975–999. <https://doi.org/10.5194/hess-26-975-2022>

Arsenault, R., Poulin, A., Côté, P., & Brissette, F. (2014). A Comparison of Stochastic Optimization Algorithms in Hydrological Model Calibration. *Journal of Hydrologic Engineering*, 19, 1374–1384. [https://doi.org/10.1061/\(ASCE\)HE.1943-5584.0000938](https://doi.org/10.1061/(ASCE)HE.1943-5584.0000938)

575 Bai, P., Liu, X., & Liu, C. (2018). Improving hydrological simulations by incorporating GRACE data for model calibration. *Journal of Hydrology*, 557, 291–304. <https://doi.org/10.1016/j.jhydrol.2017.12.025>

Bai, P., Liu, X., Yang, T., Li, F., Liang, K., Hu, S., & Liu, C. (2016). Assessment of the Influences of Different Potential Evapotranspiration Inputs on the Performance of Monthly Hydrological Models under Different Climatic Conditions. *Journal of Hydrometeorology*, 17(8), 2259–2274. <https://doi.org/10.1175/JHM-D-15-0202.1>

- 580 Beringer, J., Moore, C. E., Cleverly, J., Campbell, D. I., Cleugh, H., De Kauwe, M. G., Kirschbaum, M. U. F., Griebel, A., Grover, S., Huete, A., Hutley, L. B., Laubach, J., Van Niel, T., Arndt, S. K., Bennett, A. C., Cernusak, L. A., Eamus, D., Ewenz, C. M., Goodrich, J. P., ... Woodgate, W. (2022). Bridge to the future: Important lessons from 20 years of ecosystem observations made by the OzFlux network. *Global Change Biology*, 28(11), 3489–3514. <https://doi.org/10.1111/gcb.16141>
- 585 Beven, K. (2006). A manifesto for the equifinality thesis. *Journal of Hydrology, The Model Parameter Estimation Experiment*, 320(1), 18–36. <https://doi.org/10.1016/j.jhydrol.2005.07.007>
- Blöschl, G., Bierkens, M. F. P., Chambel, A., Cudennec, C., Destouni, G., Fiori, A., Kirchner, J. W., McDonnell, J. J., Savenije, H. H. G., Sivapalan, M., Stumpp, C., Toth, E., Volpi, E., Carr, G., Lupton, C., Salinas, J., Széles, B., Viglione, A., Aksoy, H., ... Zhang, Y. (2019). Twenty-three unsolved problems in hydrology (UPH) – a community perspective. *Hydrological Sciences Journal*, 64(10), 1141–1158. <https://doi.org/10.1080/02626667.2019.1620507>
- 590 Chiew, F. H. S., Peel, M. C., & Western, A. (2002). *Application and testing of the simple rainfall-runoff model SIMHYD*.
- Deb, P., & Kiem, A. S. (2020). Evaluation of rainfall–runoff model performance under non-stationary hydroclimatic conditions. *Hydrological Sciences Journal*, 65(10), 1667–1684. <https://doi.org/10.1080/02626667.2020.1754420>
- Dembélé, M., Ceperley, N., Zwart, S. J., Salvatore, E., Mariethoz, G., & Schaeffli, B. (2020). Potential of satellite and reanalysis evaporation datasets for hydrological modelling under various model calibration strategies. *Advances in Water Resources*, 143, 103667. <https://doi.org/10.1016/j.advwatres.2020.103667>
- 595 Duethmann, D., Blöschl, G., & Parajka, J. (2020). Why does a conceptual hydrological model fail to correctly predict discharge changes in response to climate change? *Hydrology and Earth System Sciences*, 24(7), 3493–3511. <https://doi.org/10.5194/hess-24-3493-2020>
- 600 Eamus, D., O’Grady, A. P., & Hutley, L. (2000). Dry season conditions determine wet season water use in the wet–tropical savannas of northern Australia. *Tree Physiology*, 20(18), 1219–1226. <https://doi.org/10.1093/treephys/20.18.1219>
- Fowler, K. J. A., Coxon, G., Freer, J. E., Knoben, W. J. M., Peel, M. C., Wagener, T., Western, A. W., Woods, R. A., & Zhang, L. (2021). Towards more realistic runoff projections by removing limits on simulated soil moisture deficit. *Journal of Hydrology*, 600, 126505. <https://doi.org/10.1016/j.jhydrol.2021.126505>
- 605 Fowler, K. J. A., Zhang, Z., & Hou, X. (2025). CAMELS-AUS v2: Updated hydrometeorological time series and landscape attributes for an enlarged set of catchments in Australia. *Earth System Science Data*, 17(8), 4079–4095. <https://doi.org/10.5194/essd-17-4079-2025>
- Fowler, K., Knoben, W., Peel, M., Peterson, T., Ryu, D., Saft, M., Seo, K.-W., & Western, A. (2020). Many Commonly Used Rainfall-Runoff Models Lack Long, Slow Dynamics: Implications for Runoff Projections. *Water Resources Research*, 56(5), e2019WR025286. <https://doi.org/10.1029/2019WR025286>
- 610 Gardiya Weligamage, H., Fowler, K., Saft, M., Peterson, T., Ryu, D., & Peel, M. (2025a). *Characterising evapotranspiration signatures for improved behavioural insights*. <https://doi.org/10.5194/hess-2024-373>
- Gardiya Weligamage, H., Fowler, K., Saft, M., Peterson, T., Ryu, D., & Peel, M. (2025b). Characterising evapotranspiration signatures for improved behavioural insights. *Hydrology and Earth System Sciences Discussions*, 1–23. <https://doi.org/10.5194/hess-2024-373>
- 615 Gardiya Weligamage, H., Fowler, K., Saft, M., Peterson, T., Ryu, D., & Peel, M. (2025c). Using evapotranspiration signatures to assess evapotranspiration realism in rainfall-runoff models. *EGUsphere*, 1–26. <https://doi.org/10.5194/egusphere-2025-3373>
- Grigg, A. H., & Hughes, J. D. (2018). Nonstationarity driven by multidecadal change in catchment groundwater storage: A test of modifications to a common rainfall-run-off model. *Hydrological Processes*, 32(24), 3675–3688. <https://doi.org/10.1002/hyp.13282>
- 620 Guo, D., Westra, S., & Maier, H. R. (2017). Impact of evapotranspiration process representation on runoff projections from conceptual rainfall-runoff models. *Water Resources Research*, 53(1), 435–454. <https://doi.org/10.1002/2016WR019627>
- 625 Gupta, H. V., Kling, H., Yilmaz, K. K., & Martinez, G. F. (2009). Decomposition of the mean squared error and NSE performance criteria: Implications for improving hydrological modelling. *Journal of Hydrology*, 377(1), 80–91. <https://doi.org/10.1016/j.jhydrol.2009.08.003>
- Herman, M. R., Nejadhashemi, A. P., Abouali, M., Hernandez-Suarez, J. S., Daneshvar, F., Zhang, Z., Anderson, M. C., Sadeghi, A. M., Hain, C. R., & Sharifi, A. (2018). Evaluating the role of evapotranspiration remote sensing data in

- 630 improving hydrological modeling predictability. *Journal of Hydrology*, 556, 39–49.
<https://doi.org/10.1016/j.jhydrol.2017.11.009>
- Kelleher, C. A., & Shaw, S. B. (2018). Is ET often oversimplified in hydrologic models? Using long records to elucidate unaccounted for controls on ET. *Journal of Hydrology*, 557, 160–172. <https://doi.org/10.1016/j.jhydrol.2017.12.018>
- 635 Khatami, S., Peel, M. C., Peterson, T. J., & Western, A. W. (2019). Equifinality and Flux Mapping: A New Approach to Model Evaluation and Process Representation Under Uncertainty. *Water Resources Research*, 55(11), 8922–8941.
<https://doi.org/10.1029/2018WR023750>
- Knoben, W. J. M., Freer, J. E., Fowler, K. J. A., Peel, M. C., & Woods, R. A. (2019). Modular Assessment of Rainfall–Runoff Models Toolbox (MARRMoT) v1.2: An open-source, extendable framework providing implementations of 46 conceptual hydrologic models as continuous state-space formulations. *Geoscientific Model Development*, 12(6), 2463–2480. <https://doi.org/10.5194/gmd-12-2463-2019>
- 640 Liang, X., Lettenmaier, D. P., Wood, E. F., & Burges, S. J. (1994). A simple hydrologically based model of land surface water and energy fluxes for general circulation models. *Journal of Geophysical Research: Atmospheres*, 99(D7), 14415–14428. <https://doi.org/10.1029/94JD00483>
- Liu, Z., Wang, Y., Xu, Z., & Duan, Q. (2017). Conceptual Hydrological Models. In Q. Duan, F. Pappenberger, J. Thielen, A. Wood, H. L. Cloke, & J. C. Schaake (Eds), *Handbook of Hydrometeorological Ensemble Forecasting* (pp. 1–23). Springer. https://doi.org/10.1007/978-3-642-40457-3_22-1
- 645 McMillan, H. K. (2021). A review of hydrologic signatures and their applications. *WIREs Water*, 8(1), e1499. <https://doi.org/10.1002/wat2.1499>
- Norton, A. J., Rayner, P. J., Wang, Y.-P., Parazoo, N. C., Baskaran, L., Briggs, P. R., Haverd, V., & Doughty, R. (2022). Hydrologic connectivity drives extremes and high variability in vegetation productivity across Australian arid and semi-arid ecosystems. *Remote Sensing of Environment*, 272, 112937. <https://doi.org/10.1016/j.rse.2022.112937>
- 650 Perrin, C., Michel, C., & Andréassian, V. (2003). Improvement of a parsimonious model for streamflow simulation. *Journal of Hydrology*, 279(1–4), 275–289. [https://doi.org/10.1016/S0022-1694\(03\)00225-7](https://doi.org/10.1016/S0022-1694(03)00225-7)
- Pool, S., Fowler, K., & Peel, M. (2024). Benefit of Multivariate Model Calibration for Different Climatic Regions. *Water Resources Research*, 60(4), e2023WR036364. <https://doi.org/10.1029/2023WR036364>
- 655 Rientjes, T. H. M., Muthuwatta, L. P., Bos, M. G., Booij, M. J., & Bhatti, H. A. (2013). Multi-variable calibration of a semi-distributed hydrological model using streamflow data and satellite-based evapotranspiration. *Journal of Hydrology*, 505, 276–290. <https://doi.org/10.1016/j.jhydrol.2013.10.006>
- Saft, M., Peel, M. C., Western, A. W., Perraud, J., & Zhang, L. (2016). Bias in streamflow projections due to climate-induced shifts in catchment response. *Geophysical Research Letters*, 43(4), 1574–1581. <https://doi.org/10.1002/2015GL067326>
- 660 Sivapalan, M., Ruprecht, J. K., & Viney, N. R. (1996). Water and salt balance modelling to predict the effects of land-use changes in forested catchments. 1. Small catchment water balance model. *Hydrological Processes*, 10(3), 393–411. [https://doi.org/10.1002/\(SICI\)1099-1085\(199603\)10:3%253C393::AID-HYP307%253E3.0.CO;2-%2523](https://doi.org/10.1002/(SICI)1099-1085(199603)10:3%253C393::AID-HYP307%253E3.0.CO;2-%2523)
- 665 Stephens, C. M., Marshall, L. A., & Johnson, F. M. (2019). Investigating strategies to improve hydrologic model performance in a changing climate. *Journal of Hydrology*, 579, 124219. <https://doi.org/10.1016/j.jhydrol.2019.124219>
- Stephens, C., Medlyn, B., Williams, L., Knauer, J., Inbar, A., Pendall, E., Arndt, S. K., Beringer, J., Ewenz, C. M., Hinko-Najera, N., Hutley, L. B., Isaac, P., Liddell, M., Meyer, W., Moore, C. E., Cranko Page, J., Silberstein, R., & Woodgate, W. (2025). The Response and Recovery of Carbon and Water Fluxes in Australian Ecosystems Exposed to Severe Drought. *Global Change Biology*, 31(7), e70361. <https://doi.org/10.1111/gcb.70361>
- 670 Taia, S., Scozzari, A., Erraioui, L., Kili, M., Mridekh, A., Haida, S., Chao, J., & El Mansouri, B. (2023). Comparing the ability of different remotely sensed evapotranspiration products in enhancing hydrological model performance and reducing prediction uncertainty. *Ecological Informatics*, 78, 102352. <https://doi.org/10.1016/j.ecoinf.2023.102352>
- Trotter, L., Knoben, W. J. M., Fowler, K. J. A., Saft, M., & Peel, M. C. (2022). Modular Assessment of Rainfall–Runoff Models Toolbox (MARRMoT) v2.1: An object-oriented implementation of 47 established hydrological models for improved speed and readability. *Geoscientific Model Development*, 15(16), 6359–6369. <https://doi.org/10.5194/gmd-15-6359-2022>
- 675

- 680 Trotter, L., Saft, M., Peel, M. C., & Fowler, K. J. A. (2023). Symptoms of Performance Degradation During Multi-Annual
Drought: A Large-Sample, Multi-Model Study. *Water Resources Research*, 59(2), e2021WR031845.
<https://doi.org/10.1029/2021WR031845>
- Vaze, J., Post, D. A., Chiew, F. H. S., Perraud, J.-M., Viney, N. R., & Teng, J. (2010). Climate non-stationarity – Validity of
calibrated rainfall–runoff models for use in climate change studies. *Journal of Hydrology*, 394(3–4), 447–457.
<https://doi.org/10.1016/j.jhydrol.2010.09.018>
- 685 Zhao, L., Xia, J., Xu, C., Wang, Z., Sobkowiak, L., & Long, C. (2013). Evapotranspiration estimation methods in hydrological
models. *Journal of Geographical Sciences*, 23(2), 359–369. <https://doi.org/10.1007/s11442-013-1015-9>