

Critical assessment of metrics and methods used to quantify temporal loading of rainfall events

Molly Asher^{1,2}, Mark A. Trigg¹, Cathryn E. Birch², Rasmus L.T. Henriksen³, Steven J. Böing^{3,4}, and Jonas W. Pedersen^{3,4}

¹School of Civil Engineering, University of Leeds, Leeds, UK

²Institute for Climate and Atmospheric Science, University of Leeds, Leeds, UK

³Weather research, Danish Meteorological Institute. Sankt Kjelds Plads 11, 2100 Copenhagen O, Denmark.

⁴DTU Sustain, Technical University of Denmark. Bygningstorvet Building 115, 2800 Kgs. Lyngby, Denmark

Correspondence: Molly Asher (gy17m2a@leeds.ac.uk)

Abstract. The distribution of rainfall intensity through time at a fixed spatial location, referred to here as event temporal loading, can significantly influence hydrological and geomorphological responses, including run-off generation, urban flood risk, and soil erosion. Numerous approaches have been developed to analyse rainfall event temporal loading, but these differ in how they characterise rainfall behaviour and in the aspects of storm structure they emphasise. Emerging research further suggests that climate change may alter rainfall temporal loading in complex and regionally dependent ways, underlining the importance of clear and consistent approaches to its quantification. In this study, we identify 48 metrics which have been previously applied to describe event temporal loading, and define a further five metrics representing aspects not fully captured in existing metrics. We calculate these metrics for 233,128 rainfall events recorded at Danish rain gauges. We use data-driven cluster analysis to reveal how the metrics relate, highlighting groups of metrics that describe similar properties, and others that are more distinct. Based on this, we conceptualise five aspects of temporal loading: mass timing, peak timing, magnitude concentration, temporal concentration, and intermittency. We demonstrate that some metrics are robust to changes in rainfall event temporal resolution and pre-processing, while others are highly sensitive. Drawing on these findings, we recommend one representative metric per aspect: the 4th quartile mass fraction (or D_{50} if a continuous measure is preferred) for mass timing; peak position ratio for peak timing; the Gini coefficient for magnitude concentration; temporal standard deviation for temporal concentration; and the wet-dry transition rate for intermittency. Together, these recommendations provide a practical framework for deliberate metric selection and more consistent cross-study comparison of rainfall temporal loading.

1 Introduction

Rainfall events vary not only in total volume and duration but also in how intensities fluctuate as storms develop. Storms typically progress through phases of initiation, intensification, and dissipation, reflecting the dynamic interplay of meteorological and cloud processes. These processes give rise to storms with complex space–time structure, so that rainfall evolution differs across both time and location. We use the term ‘event temporal loading’ to describe the internal variability of intensity over the course of a storm at a fixed location. This Eulerian perspective is conceptually straightforward and aligns with the conven-

tional representation of storms in hydrological modelling, such as the design storm approach, where temporal variations are condensed into a single site-based hyetograph. Event temporal loading is described in previous research under various names, including intensity profile (Dunkerley, 2021a), storm profile (Kottegoda and Kassim, 1991), rainfall temporal pattern (Wang, 2020), and intra-event rainfall variability (Todisco, 2014). While it is possible in principle to analyse temporal loading from a moving-storm, or Lagrangian, perspective, systematic methods for doing so have not yet been established.

Rainfall event temporal loading has been shown to influence hydrological and geomorphological responses across a wide range of environmental processes, however the direction and magnitude of its effects often vary between studies. For instance, flood modelling experiments have demonstrated that temporal loading alone can produce flood depth differences of up to 35% under identical rainfall volumes (Hettiarachchi et al., 2018). In landslide studies, early-peaking storms have been associated with greater infiltration and more severe slope instability (Fan et al., 2020). Soil erosion studies exemplify the diverging outcomes in temporal loading studies. Wang et al. (2016) reported greater soil loss from later-peaking storms, while Aquino et al. (2013) found early-peaking events to be more damaging. Such differences underscore that while temporal loading is clearly influential, its specific impacts depend on system characteristics, dominant processes, and methodological approaches.

Extreme rainfall events are expected to intensify in a warming climate at around 6–7% per degree Celsius, following the Clausius–Clapeyron (CC) relationship (Trenberth et al., 2003). Furthermore, for short-duration convective extremes, some studies suggest even greater rates of intensification, known as super-CC scaling (Fowler et al., 2021). This behaviour has been linked to dynamical storm changes under higher temperatures, including variations in storm speed, convective cell development, and feedbacks such as latent heat release (Lenderink and Van Meijgaard, 2009; Fowler et al., 2021). These dynamical storm processes have also been suggested to affect the temporal distribution of rainfall within storms. A growing body of work has begun to examine how event temporal loading may change in a warmer climate (Visser et al., 2023; Ghanghas et al., 2024; Asher et al., 2025a; Wasko and Sharma, 2015), but results to date show variable magnitudes and directions of change, pointing to possible regional dependencies in behaviour. Research in this area remains at an early stage and is developing actively.

Despite its demonstrated importance, rainfall event temporal loading is often simplified in impact modelling applications, particularly in design-oriented or regulatory contexts. This simplification is most commonly achieved using design storms, which are synthetic profiles used to standardise the representation of extreme events across specified return periods, and a longstanding component of engineering practice (Watt and Marsalek, 2013). Design storms combine an estimate of total rainfall with a prescribed hyetograph, which dictates how rainfall is distributed over the course of the storm. While total rainfall depths are typically derived from locally specific statistics, the same hyetograph shape is often applied universally. For example, symmetrical, centrally peaked intensity profiles are commonly used, such as the FEH design profiles in the UK (Centre for Ecology & Hydrology, 1999) and the Chicago design storm in the US and other countries (Keifer and Chu, 1957).

An alternative approach in impact modelling is continuous simulation, in which long-term rainfall time series are routed through models to generate extended sequences of runoff responses that are subsequently analysed to estimate flood magnitudes for given return periods (Boughton and Droop, 2003). This approach inherently accounts for antecedent wetness conditions and avoids many ad hoc assumptions about initial losses, but requires extensive data and substantially greater computational effort. Considerable research has examined the temporal and spatial resolution needed to capture storm dynamics relevant to urban

hydrology, with several studies suggesting that sub-hourly (often 1–5 minute) data are required to resolve the short, intense bursts that drive urban response (Einfalt et al., 2004; Schilling, 1991). Radar products and stochastic rainfall generators have
60 therefore been developed to provide such high-resolution inputs. Nonetheless, continuous simulation remains less commonly used in routine flood risk assessment and infrastructure design than event-based methods, which continue to be favoured for their simplicity, interpretability, and established role in practice (Boughton and Droop, 2003; Pathiraja et al., 2012; Formetta et al., 2018; Krvavica and Rubinić, 2020).

Robust, interpretable metrics are therefore essential to bridge the gap between observed rainfall behaviour and the simplified
65 forms commonly used in models. By quantifying key aspects of temporal loading, such metrics help preserve important features when rainfall events are simplified, improving the fidelity of hydrological representations. Furthermore, metrics can offer insight into why the influence of temporal loading varies across studies and contexts, by revealing which specific aspects of storm evolution are most relevant to particular hydrological responses. Flood response, for instance, may be especially sensitive to peak intensity and its timing, whereas soil erosion and landslide initiation may respond more strongly to rainfall
70 concentration or intermittency. Despite this, a wide variety of metrics have been proposed with little systematic evaluation of how they relate to one another, how sensitive they are to temporal resolution and data processing choices, or whether they are broadly suitable across different contexts. Terminology is also inconsistent, with metrics often targeting different characteristics, such as asymmetry, peakiness, or intermittency, but these distinctions are rarely made explicit. Applying metrics without regard to these differences risks misplaced emphasis or misinterpretation.

75 This study seeks to address gaps in knowledge on how temporal loading metrics perform under different data and processing conditions, and on how metrics relate to one another. The work addresses the following research questions:

- RQ1: What key properties of rainfall event temporal loading are commonly measured, and why?
- RQ2: Which metrics are strongly correlated, suggesting they may be redundant or are suitable for use in cross-comparison of studies?
- 80 – RQ3: How sensitive are these metrics to the temporal resolution of the rainfall data?
- RQ4: How does conversion of rainfall events to Dimensionless Mass Curves (DMCs) affect metric values?

The first research question is addressed through a structured literature review that identifies existing metrics used to quantify temporal loading, followed by a synthesis of their underlying assumptions, intended applications, and data requirements (Sect. 2). The remaining questions apply data from Danish rain gauges. The second question is tackled using cluster analysis to
85 explore similarities among metrics calculated from raw rainfall events at a 5-minute resolution (Sect. 4.1). The third and fourth questions are examined via comparative analyses of metrics calculated on rainfall events at varying temporal resolutions (Sect. 4.2) and after calculation of DMCs (Sect. 4.3). Through this empirical analysis, the study builds toward a practical framework for metric selection, identifying five distinct aspects of rainfall temporal loading and proposing a representative metric for each, with the aim of reducing inconsistency and improving comparability across future studies.

90 2 Literature review

The literature review is conducted according to the PRISMA (Preferred Reporting Items for Systematic Reviews and Meta-Analyses) framework. This is a standardised method of performing literature review which aims to minimise potential researcher bias. Further methodological details are provided in Appendix A. The main outcomes of the literature review are reported in the sections that follow.

95 2.1 Domains and purposes of reviewed literature

Research into rainfall temporal loading is conducted across domains where hydrological and geomorphological responses to rainfall are important, including flood and hydrological research, pollution modelling, and soil erosion and landslide studies. Across these contexts, research is generally motivated by similar questions. One common aim is to assess system sensitivity to rainfall temporal loading. Running models using rainfall events with fixed total volume and duration but varying temporal
100 distribution allows for impacts to be examined. Research of this nature has been performed in regards to: runoff generation in urban catchments (Cai et al., 2024; Asher et al., 2025b), the hydraulic performance of urban sewer systems (Li et al., 2021), modelling of soil erosion and sediment transport (Römkens et al., 2002; Liu et al., 2022; Dunkerley, 2021a; Rivera et al., 2012; Gao et al., 2024; Wang et al., 2016; Alavinia et al., 2019; Gholami et al., 2021; Aquino et al., 2013; Klamkowski et al., 2012), pollution wash-off (Fu et al., 2021), and rainfall-induced landslides (Fan et al., 2020).

105 A second common aim is to characterise the temporal loading of rainfall events. This includes research developing new or more nuanced metrics for describing internal rainfall variability (Todisco, 2014; Dunkerley, 2022), or research applying existing metrics in order to group and summarise events into representative hyetographs for specific locations (Wang, 2020; Amin et al., 2000; Dolšák et al., 2016; Vantas et al., 2019). This allows assessment of how well standard hyetographs reflect observed temporal patterns, and the improvement of design storms. A third aim of research on temporal loading is to improve
110 representation of the statistical characteristics of rainfall in stochastic rainfall generation and disaggregation (Wu et al., 2006; Nguyen and Chen, 2022). A final aim is to assess the impact of climate change on extreme rainfall characteristics (Visser et al., 2023; Hu et al., 2018; Asher et al., 2025a).

2.2 Rainfall data sources

The reviewed studies rely on two main sources of rainfall data: observational records and synthetically generated events. The
115 majority of studies use events extracted from observed rainfall time series, typically recorded by rain gauges (e.g., Zhang et al. (2023)), or radar (e.g., Urgilés et al. (2024)). Events are extracted from observational records at point locations based on assumptions about what constitutes the start and end of a rainfall event, such as minimum intensity thresholds or inter-event dry periods (Restrepo-Posada and Eagleson, 1982). Additionally, event boundaries and characteristics are inevitably shaped by the temporal resolution of the observational dataset, and so ‘observed’ rainfall events remain approximations shaped by the
120 resolution of the measurement system, rather than exact representations of storm behaviour.

Other studies use synthetic rainfall events. Stochastic rainfall generators produce events which reproduce the statistical properties of observed rainfall while allowing control over event magnitude and duration (Cai et al., 2024; Fan et al., 2020). These events are typically used within modelling frameworks to explore a broader range of rainfall scenarios. While this approach enables controlled investigation of temporal effects, it relies on assumptions about what constitutes a ‘representative’ event. This can influence interpretation and limit generalisation to real world rainfall. Idealised design storms are an additional form of synthetic events. These adopt simple geometric profiles, such as uniform rainfall (e.g., the rational method (Smith and Lee, 1984) or triangular hyetographs peaking early, centrally, or late in the event (e.g., Parsons and Stone, 2006). These profiles are used to systematically explore the influence of temporal loading, often forming the basis for physical experiments where pre-defined rainfall patterns are applied to laboratory set-ups simulating hillslopes or infiltration systems (Wang et al., 2023; de Lima et al., 2013; Parsons and Stone, 2006; Zhang et al., 1997). Idealised design storms are pivotal in a lot of the early work on understanding the influence of rainfall temporal loading, however, as temporal structure is prescribed rather than quantified using a metric they are not discussed further here.

2.3 Rainfall processing choices

Rainfall temporal loading metrics may be applied directly to a raw rainfall intensity series, which retains the original units and absolute values of the event, allowing metrics to reflect both timing and intensity. However, metrics are sometimes instead applied to dimensionless mass curves (DMCs). DMCs were originally developed to characterise within-storm temporal structure independently of event magnitude and duration, and have since been widely used in rainfall analysis and design storm construction (Koutsoyiannis and Foufoula-Georgiou, 1993). They are derived by double normalising a rainfall event, scaling cumulative rainfall and event duration between 0 and 100%, and expressing the event as a cumulative mass profile. To enable comparison across events with different durations and data resolutions, these dimensionless profiles are typically interpolated at regular fractions of storm duration (e.g. every 1% or 10%), producing standardised curves of fixed length (Pan et al., 2017).

The widespread use of DMCs in the literature reflects the need for a standardised representation of rainfall temporal structure that enables direct comparison across events with different durations, magnitudes and numbers of observations. However, the combined effects of double normalisation and interpolation also modify the internal structure of rainfall events, with implications for the behaviour and interpretation of temporal loading metrics. Metrics based on absolute values (e.g. peak intensity) lose their physical units when applied to DMCs, instead reflecting fractions of total rainfall per bin rather than mm/hr. This makes direct numerical comparison with raw equivalents meaningless, though the metrics remain defined and carry information about event shape. Metrics describing timing may become discretised, such that values are constrained to the interpolation intervals (e.g. time of peak occurring at 0, 10, 20%, etc. of event duration). As a result, conclusions drawn from metrics applied to raw rainfall and to DMCs may differ.

Despite this, studies do not always make explicit whether temporal metrics are calculated using raw rainfall series or DMCs, nor do they consistently discuss the implications of this choice. This lack of clarity complicates comparisons across studies and makes it difficult to determine whether reported differences in temporal structure reflect intrinsic storm behaviour or artefacts of data processing.

The wide range of metrics identified in the reviewed studies are listed in Table 1. Each metric is categorised as either a categorical or continuous metric. In cases where the same metric formulation is referred to by different names, we list both. In the remainder of the work, we refer to the metric only by the first name listed in Table 1.

Table 1: Overview of metrics based on literature review

Metric	Meaning	Type
<i>3rd/4th/5th with peak</i>	Finds the fraction of event with the peak rainfall	Categorical
<i>3rd/4th/5th with most</i>	Finds the fraction of event with the most rainfall	Categorical
<i>3rd with D_{50}</i>	Finds the third in which 50% of cumulative rainfall is reached (see D_{50} definition later in Table 1)	Categorical
<i>3rd with CoG</i>	Finds the third containing the centre of gravity of rainfall	Categorical
<i>Binary Shape Code</i>	Measures whether cumulative rainfall in each quartile exceeds that of a uniform distribution, and uses this to assign a 4-digit code	Categorical
<i>Crossing properties</i>	Measures the number of times the event DMC crosses the uniform DMC and whether the event has generally an increasing or decreasing intensity profile, assigns a number and a letter based on this	Categorical
<i>I30</i>	Identifies the max rainfall depth within any 30-minute period	Continuous
<i>Classical skewness [(C) skewness]</i>	Quantifies the asymmetry of the rainfall intensity value distribution. Positive values indicate many small intensities and a few large ones, while negative values indicate the reverse. Does not account for the temporal ordering of intensities. This is referred to as ‘Classical skewness’ to distinguish from ‘Temporal skewness’ which is introduced in Table 2	Continuous
<i>Classical kurtosis [(C) kurtosis]</i>	Quantifies the tailedness of the rainfall intensity value distribution. Positive values indicate a distribution with heavier tails and more extreme values relative to the variance, while negative values indicate lighter tails and fewer extremes. Does not account for the temporal ordering of intensities. This is referred to as ‘Classical kurtosis’ to distinguish from ‘Temporal kurtosis’ which is introduced in Table 2	Continuous

Metric	Meaning	Type
<i>Classical standard deviation [(C) std]</i>	Quantifies the dispersion of rainfall intensity values around the mean intensity. A higher value indicates greater variability in intensity magnitudes (i.e., larger deviations from the mean), while a lower value indicates more uniform intensities throughout the event. Does not account for the temporal ordering of intensities. This is referred to as ‘Classical std’ to distinguish from ‘Temporal std’ which is introduced in Table 2	Continuous
<i>Coefficient of variation (CV)</i>	Measures the variation of intensity values around the mean intensity by calculating the classical standard deviation divided by the mean	Continuous
<i>Peak-mean ratio or Rainfall intensity irregularity (n_i)</i>	Calculates the maximum intensity divided by mean intensity	Continuous
<i>Relative amplitude</i>	Calculates the range (maximum - minimum intensity) divided by the mean intensity	Continuous
<i>Time to peak</i>	Represents the time to peak in minutes	Continuous
<i>Peak position ratio or Coefficient peak rainfall intensity</i>	Calculates the time to peak divided by duration	Continuous
<i>Skew_p</i>	Measures the relative position of the peak within the rainfall duration, and is therefore anchored to the peak timing. Takes a value from -0.25 to 0.25. Negative values indicate front-loading, positive values indicate back-loading	Continuous
<i>T25 / T50 or D₅₀ / T75</i>	Calculates the proportion of event duration elapsed when a specified percentage (e.g., 25%, 50%, 75%) of total rainfall has occurred	Continuous
<i>m1</i>	Calculates the relative volume of rainfall before versus after the peak	Continuous
<i>m2</i>	Calculates the percentage of rainfall in the highest-intensity time step divided by rainfall in whole event	Continuous
<i>m3 / m4 / m5</i>	Calculates the percentage rainfall in first 33% / 30% / 50% of event duration	Continuous
<i>Event loading index</i>	Classifies the temporal variability (captured by the standardised temporal heterogeneity, STH) of a storm by comparing it against that of a symmetrised version constructed by mirroring the rising limb around the peak	Continuous
<i>Asymmetry of dependence</i>	Classifies the degree of reversibility in a timeseries using ranked-based statistics (copulas)	Continuous
<i>Precipitation Concentration Index (PCI)</i>	Compares sum of squared intensities to square of total rainfall. Higher values indicate more rainfall concentrated in fewer steps	Continuous

Metric	Meaning	Type
<i>Temporal Concentration Index (TCI)</i>	Measures how strongly rain is clustered in time around each time-step, selects value for the time step around which rainfall is most tightly clustered. Higher values indicate stronger temporal concentration	Continuous
<i>NRMSE_p</i>	Quantifies the concentration of rainfall near the peak by calculating the RMSE from the peak, normalised by the rainfall total. Values range from 0 (uniform distribution) to 1 (all rainfall in a single time step)	Continuous
<i>Gini coefficient</i>	Measures the inequality of the rainfall distribution. Higher values indicate greater concentration of rainfall in fewer intervals	Continuous
<i>Lorenz asymmetry coefficient</i>	Quantifies the skewness of the rainfall intensity distribution relative to the mean, distinguishing whether the concentration arises from a few extreme high-intensity bursts or from many moderately intense intervals, even if overall inequality is similar	Continuous
	The High Intensity Zone (HIZ) is defined as the period of the event of above-average intensity; The LIZ is the period of the event below average intensity	
<i>Mean intensity in HIZ</i>	Measures the average intensity in the HIZ	Continuous
<i>% time in LIZ / HIZ</i>	Measures the proportion of time in the LIZ and HIZ	Continuous
<i>% rain in HIZ</i>	Measures the proportion of rainfall in the HIZ. More rainfall in HIZ indicates a more concentrated event	Continuous
<i>Frac. in Q1 / Q2 / Q3 / Q4</i>	Measures the percentage of total rainfall in each quarter	Continuous
<i>Event dry ratio or Intermittency fraction</i>	Quantifies the proportion of event duration spent at 0 mm/hr	Continuous

2.4.1 Categorical metrics

- 160 Those metrics flagged as categorical in Table 1 assign rainfall events to discrete structural classes. Some complex schemes exist, such as the Binary Shape Code (Terranova and Iaquina, 2011) and Crossing Properties (Kottegoda and Kassim, 1991), both of which compare an event's DMC to a uniform reference profile. Most approaches, however, divide an event into equal fractions (e.g. thirds, quarters or fifths) and identify which fraction contains a defining feature such as the peak intensity or the largest rainfall volume.
- 165 While simple, the outcomes of these classification metrics depend heavily on implementation choices. For example, Horner and Jens (1942) introduced the original third-based classification scheme, defining events as advanced, intermediate, or delayed based on the timing of peak intensity. By contrast, Liang et al. (2023) also use thirds but classify events based on the location of rainfall mass, identifying the third with the highest total rainfall. Figure 1 illustrates how these conceptually similar approaches

can assign different structural labels to the same event. The *3rd with peak* metric classifies the event as centred, since maximum intensity occurs in the middle third, while both *3rd with most* and *3rd with D_{50}* identify it as front-loaded, since the majority of cumulative rainfall mass falls within the first third. This has direct implications for the comparability of studies using categorical metrics. A study using *3rd with peak* might report that most events are centred, while a study using *3rd with most* applied to the same dataset might report that most events are front-loaded. Without careful documentation of which metric was used and what it measures, such differences in reported event structure could be mistaken for genuine differences between study catchments or climates, when in fact they simply reflect differences in metric definition.

Additionally, by reducing a continuous temporal profile to a discrete label, categorical metrics inevitably mask within-class variability. Despite this, they offer a tractable way to group storms by type, reducing complex temporal profiles into interpretable structural classes. This is particularly valuable in design and modelling contexts where consistent, repeatable classification procedures are important.




Figure 1. Illustration of some categorical metrics for an example rainfall event: (a) the raw rainfall data, and classification of the event based on (b) *3rd with peak*, (c) *3rd with most*, (d) *3rd with D_{50}* (NB: these are not even thirds)

180 **2.4.2 Continuous metrics**

While categorical metrics reduce temporal structure to a discrete label, continuous metrics quantify it using numerical indices. They describe structural properties such as the prominence of intense bursts, the timing of rainfall mass, the degree of concentration into short intervals, and the presence of intermittency. Many continuous metrics aim to quantify similar conceptual properties, such as whether rainfall is early- or late-loaded, but differ in their mathematical construction and therefore in what they actually capture. The distinction between peak-based and mass-based definitions, already seen for the categorical metrics, reappears here. Some metrics define loading in relation to the timing of peak intensity (e.g. *peak position ratio*), while others use the timing of the bulk of rainfall mass (e.g. D_{50}). In the example event shown in Figure 2, these perspectives lead to similar interpretations, but this need not always be the case. An event with a short intense burst near the beginning but most of its rainfall occurring later would be classified as early-loaded by a peak-based metric and late-loaded by a mass-based one.

185

190 This tension between peak- and mass-based definitions, which run across both categorical and continuous metrics, reflect a broader point: rainfall temporal structure is multidimensional, and no single metric captures it fully. Metric choice therefore shapes interpretation, and different metrics can produce substantively different characterisations of the same event.




Figure 2. Illustration of several continuous metrics for an example rainfall event, including $m1$, $m2$, $m4$, $m5$ (Wartalska and Kotowski, 2020), $T25$, $T50$, $T75$ (Knighton and Walter, 2016), *centre of gravity* and *time to peak* (Jun et al., 2021; Knighton and Walter, 2016)

2.5 Summary of reviewed studies and metrics

A full overview of the reviewed studies is provided in Table B1 (Appendix B). These studies span diverse domains, data sources, processing approaches, and metric types, which reflects the breadth of contexts in which temporal loading is studied. Table C1 (Appendix C) summarises the distribution of these characteristics across studies. Despite this diversity, a small number of metrics dominate the literature. As shown in Figure C1 (Appendix C), most metrics appear in only one or two studies. Notable exceptions are the *4th with most* metric, which forms the basis of Huff quartiles (Huff, 1967), and the *3rd with peak* metric, which underlies the advanced, intermediate, and delayed classification of Horner and Jens (1942). Both have been widely adopted and represent the earliest formal attempts to categorise storm temporal structure. This uneven distribution of metric use, combined with the sensitivity of even the most widely adopted metrics to methodological choices, points to the need for more deliberate and consistent metric selection, which is addressed in the subsequent sections.

3 Methods

3.1 Rainfall data

This research uses rainfall events extracted from Danish rain gauge data at 1 minute resolution. Figure 3 shows the national Danish rain gauge network, which is maintained and operated by the Danish Meteorological Institute (DMI). The individual gauges in the network are mainly owned by DMI and the Danish water utilities organised through the ‘Water Pollution Committee of The Society of Danish Engineers’ (abbreviated ‘SVK’ in Danish for ‘Spildevandskomiteen’). DMI’s gauges are weighing rain gauges of the brands Geonor and OTT Pluvio². The measurement resolution of Geonor gauges are 0.1 mm, while the resolution of the Pluvio² gauges started at 0.1 and was updated during the time period focused on in this study to 0.01 mm. SVK’s gauges are tipping bucket gauges by Rimco with a measurement resolution of 0.2 mm. Both gauge types record data with a temporal resolution of one minute. Figure 3 (left) shows that all DMI’s gauges have been operational for less than 15 years, while there is a much larger spread in time series lengths for the SVK gauges with the oldest ones providing continuous time series from 1979 to the present. Figure 3 (right) shows the spatial locations of the gauges with DMI gauges being relatively evenly spread across the country, while SVK gauges cluster around the major cities.

Data quality control for all gauges in the network are performed manually by DMI’s climatology department (DMI, 2025). Data points ruled non-trustworthy by manual quality control are excluded from this study.

3.2 Rainfall event extraction and pre-processing

For each rain gauge, independent rainfall events are extracted over the full period of available data. The rainfall time series is first aggregated to 5-minute resolution. This resolution is deemed to best preserve temporal detail, while minimising noise due to the measurement resolution of the rain gauge data. This noise arises because both tipping-bucket gauges and weighing gauges record rainfall in discrete increments, when the buckets tip or when the accumulated weight flips a decimal, which leads to many small, artificial peaks in the 1-minute time series.




Figure 3. A stacked histogram of the length of the time series for rain gauges (left), and a map of Denmark showing the locations of each gauge, including indications of gauge ownership and time series length (right). Base map: © OpenStreetMap contributors 2025. Distributed under the Open Data Commons Open Database License (ODbL) v1.0.

To ensure event independence, we extract events using a minimum inter-event time (MIT) threshold (Restrepo-Posada and Eagleson, 1982; Molina-Sanchis et al., 2016). An ‘event’ thus constitutes any rainfall separated by at least 11 hours of rain-free conditions, following practice in several Danish hydrological studies (Gregersen et al., 2013; Thomassen et al., 2023). This approach ensures that each event begins and ends with non-zero rainfall. The choice of MIT has been shown to play an important role in determining both the number and properties of rainfall events identified (Dunkerley, 2008). In this study, event definition is treated as a fixed preprocessing choice rather than a variable of investigation, reflecting a deliberate scoping decision.

While the delineation of event boundaries can influence the timing and relative prominence of peak intensity, and hence derived temporal loading metrics, its effects have been examined in several previous studies, e.g. Dunkerley (2008, 2010, 2015); Wang et al. (2019); Freitas et al. (2020); Molina-Sanchis et al. (2016); Haile et al. (2011); Medina-Cobo et al. (2016); Meier et al. (2016). In contrast, this study focuses on methodological choices that have received less systematic attention, namely the selection and interpretation of temporal loading metrics and their sensitivity to rainfall representation and aggregation.

We define and analyse entire rainfall events, rather than only the most intense ‘burst’ periods, capturing the complete temporal evolution of each storm. Events with less than 4 mm of total rainfall are excluded to remove very light events unlikely to be hydrologically significant. This process produces a dataset of 233,128 rainfall events observed between 1979 and 2025.

Coarser-resolution versions of each event are also derived at 10-, 30-, and 60-minute resolutions. These are generated based on the start and end times of the 5-minute event, so for a given coarser resolution, the first timestamp equal to or before the 5-minute event start is taken as the new start, and the last timestamp equal to or later than the event end is taken as the new end. As a result, the duration of events at coarser resolutions may be equal or longer in the duration than their 5-minute counterparts.

3.3 Dimensionless mass curve generation

Dimensionless mass curves (DMCs) are generated from all 5-minute resolution rainfall events. A DMC represents the distribution of rainfall within an event, scaled such that both time and accumulated rainfall range from 0% to 100%. Each DMC is interpolated to have 10 equally spaced time points. Importantly, while DMCs are typically defined as cumulative profiles, in this analysis we derive a double normalised incremental representation by converting each interpolated DMC back into incremental rainfall. This version reflects rainfall intensity as a proportion of total event mass, distributed over relative time. All temporal loading metrics in this study are applied to these 10-point, double normalised incremental series rather than to cumulative curves. This preserves consistency with how metrics are typically applied to raw rainfall intensities, while enabling direct comparison across events in a dimensionless domain. We additionally apply all metrics to events that have been double normalised but retain their original number of time steps, isolating the effect of normalisation from that of aggregation to 10 points.

3.4 Metric computation and post-processing

Rainfall temporal loading metrics are implemented in Python based on the definitions provided in the original publications. The full codebase for rainfall event extraction and metric calculation is openly available at our GitHub repository (<https://github.com/masher92/MetricEvaluation/>), providing a consistent and reproducible framework for future applications of these metrics. In some cases, the literature lacks sufficient detail on the precise application of metrics (e.g., with respect to temporal resolution, handling of zero values, normalisation procedures). Where ambiguity exists, we make reasonable interpretations of the provided formulations. Two of the metrics identified in Table 1, the Binary Shape Code and the event’s Crossing Properties, are not straightforward numeric indicators and are thus deemed outwith the scope of this study.

In addition to the literature-identified metrics, we calculate a set of additional metrics on each event’s intensity profile. Firstly, we include the mean and maximum event intensity to aid interpretation of the clustering results. Although these do not describe temporal loading directly, they can help identify cases where other metrics primarily reflect overall magnitude rather than temporal structure. We then calculate several temporal moments, which describe the overall distribution of rainfall intensity through time. These provide a compact and physically interpretable summary of how rainfall mass is positioned, spread, and skewed within an event. Despite their general applicability as distributional descriptors, such metrics have not previously been applied in the context of rainfall temporal structure. Finally, we introduce an author-defined metric, termed the wet-dry transition rate, which quantifies the frequency of wet–dry transitions within an event. This was included to test an event-based representation of intermittency that aligns closely with the intuitive, dictionary definition of the term (i.e., alternation between wet and dry periods). While previous metrics have been proposed to quantify intermittency—for example, the intermittency fraction of Dunkerley (2015), which calculates the proportion of dry time-steps, and the burstiness and memory metrics of Schleiss and Smith (2016) and Dey (2023), which operate on interarrival times over long, multi-event time series—these approaches either measure dry fraction rather than alternation, or require long series to provide stable estimates.

The wet-dry transition rate provides a simple, interpretable, event-based alternative that is directly applicable at the scale of individual rainfall events.

Table 2: Overview of metrics defined by authors

Metric	Meaning	Type
<i>Centre of Gravity (CoG)</i>	Equivalent to the temporal mean. Calculates the rainfall-weighted mean time of the event by multiplying each time step by its rainfall intensity, summing these values, and dividing by the total rainfall. This is then normalised to fall between 0 and 1	Continuous
<i>Temporal kurtosis [(T) kurtosis]</i>	Quantifies how sharply the rain is clustered around the temporal mean	Continuous
<i>Temporal skewness [(T) skewness]</i>	Measures the asymmetry of rainfall in time around the temporal mean	Continuous
<i>Temporal standard deviation [(T) std]</i>	Measures the spread of rainfall in time around the temporal mean, indicating how temporally concentrated or dispersed the rainfall is over the event duration	Continuous
<i>Wet-dry transition rate</i>	Measures the normalised (by event length) frequency of switches between a wet and dry state	Continuous
<i>Max intensity</i>	Identifies the maximum rainfall intensity within the event	Continuous
<i>Mean intensity</i>	Identifies the mean rainfall intensity within the event	Continuous

3.5 Testing metric overlap and complementarity (RQ2)

To identify metrics which are strongly correlated we apply agglomerative hierarchical clustering based on pairwise metric similarity across all events at 5-minute resolution (Jain et al., 1999). Similarity between metrics is quantified using the absolute Spearman rank correlation coefficient, and clustering is performed using average linkage. While clustering directly on metric vectors using Euclidean distance was considered, this would have prioritised numerical proximity over functional similarity. This is problematic because some metrics which have very high negative correlation, and likely describe the same feature, are very distant in Euclidean space. Prior to clustering, each metric is assessed for skewness, and those with an absolute skewness ≤ 1 are retained in their original form. For variables with higher skewness, a logarithmic transformation ($\log_{1p}$) is applied if all values are positive, and otherwise, the Yeo-Johnson transformation (Yeo and Johnson, 2000), which supports zero and negative values, is used. After transformation, all variables are MinMax scaled to common [0,1] range. To inform the number of clusters, we compute silhouette scores for a range of candidate cluster numbers. Silhouette scores quantify how appropriate a cluster number is based on how well each metric fits within its assigned cluster, based upon its similarity to members of its own cluster compared with its dissimilarity to those in other neighbouring clusters (Rousseeuw, 1987). This analysis suggests twelve clusters to be the optimal number (Figure D1, Appendix D).

290 3.6 Testing sensitivity to temporal aggregation (RQ3)

To assess the sensitivity of each metric to temporal aggregation of rainfall data, we compare metric values computed on rainfall events derived from data aggregated at different temporal resolutions. We treat metrics computed on events from 5-minute rainfall data as the reference ('truth') and compare them to values obtained from coarser aggregations at 10-, 30-, and 60-minute intervals.

295 For each metric and resolution pair, we quantify both numerical and ranking sensitivity. These two complementary measures allow us to distinguish between metrics which exhibit substantial changes in raw values (numerical sensitivity), those which show shifts in the relative ordering of events (ranking sensitivity), and those which display both or neither aspect of sensitivity.

For continuous metrics, the numerical sensitivity is assessed using the symmetrical median absolute percentage error (sMAPE) (Makridakis and Hibon, 1995). sMAPE measures the the absolute percentage error between the metric values at 5 minute and
300 at coarser resolutions, and is calculated as:

$$\text{sMAPE} = \frac{100}{n} \sum_{i=1}^n \frac{|x_i - y_i|}{(|x_i| + |y_i|)/2} \quad (1)$$

where x_i and y_i are the original and transformed metric values for event i , respectively.

The ranking sensitivity is assessed using Spearman's rank correlation coefficient (ρ), which quantifies the degree to which the relative ordering of events changes due to temporal aggregation, and is calculated as:

$$305 \quad \rho = 1 - \frac{6 \sum_{i=1}^n d_i^2}{n(n^2 - 1)} \quad (2)$$

where n is the number of paired observations, $d_i = R(x_i) - R(y_i)$ is the difference between the ranks of the i^{th} pair of observations.

For categorical metrics, the % of events in a different category from 5 minute at each coarser resolution is used for numerical sensitivity, and Kendall's τ quantifies the ranking sensitivity (Kendall, 1938) by measuring the association between two ranked
310 variables. It is defined as:

$$\tau = \frac{P - Q}{\sqrt{(P + Q + T)(P + Q + U)}} \quad (3)$$

where P / Q are the number of concordant / discordant pairs, and T is the number of ties only in x , and U is the number of ties only in y . If a tie occurs in both x and y for the same pair, it is not counted in either T or U .

We also visually explore how each metric responds to aggregation by plotting distributions across resolutions (using his-
315 tograms for continuous metrics, and bar plots for categorical metrics).

We note that comparing continuous and categorical metrics introduces interpretive limitations. When calculating sMAPE scores and plotting metric distributions we opted to not transform or scale metrics. This was to preserve the physical interpretability of each metric, allowing percentage errors to reflect changes in real units (e.g., minutes or intensity proportions)

rather than abstracted or standardised values. However, although sMAPE expresses the average percentage difference between two representations (e.g., at different resolutions), the meaning of a given percentage depends on the nature and scale of the metric. For instance, a 70% sMAPE for a bounded percentile-based timing measure like D_{50} does not carry the same meaning as a 70% sMAPE for a scale-dependent metric such as standard deviation. This presents a trade-off, where preserving metric-specific meaning improves interpretability within each metric, but complicates comparative analysis across them. We recognise that we are operating within these constraints, but by interpreting sMAPE scores in conjunction with visual plots, rank correlations, and physical understanding of the metric’s behaviour, we can still make valuable assessments of metric behaviour at different resolutions and processing options.

3.7 Testing sensitivity to DMC construction (RQ4)

To evaluate the robustness of rainfall metrics to DMC conversion, we compare values calculated on raw 5-minute rainfall events and DMC-transformed rainfall time series. Note that, $I30$ cannot be calculated, as DMCs have no concept of 30-minutes. Likewise the *Frac. in Q1 / 2 / 3 / 4* can only be calculated on events with n timesteps divisible by 4, and so are not calculated either. Following the methods for temporal aggregation sensitivity testing (Sect. 3.6), we calculate numerical and ranking sensitivity of continuous metrics using sMAPE and Spearman’s ρ , and for categorical metrics using % differences in categorisation and Kendall’s τ . Metric value distributions are also compared using histograms for continuous metrics, and bar plots for categorical metrics.

4 Results and discussion: Quantitative metric analysis

4.1 Metric overlap and complementarity (RQ2)

The results of the hierarchical cluster analysis suggest that several well-defined groups of metrics exist. Within each cluster, metrics rank rainfall events similarly. On the dendrogram in Figure 4.(a), the shorter the horizontal distance between metrics or groups of metrics, the greater the similarity in rankings. Figure 4.(b) shows the matrix of Spearman’s rank correlation scores upon which the clustering is based. Negative correlations arise where metrics respond to the same underlying asymmetry but with reversed directionality — for instance, a front-loaded event will have a lower D_{50} (proportion of event elapsed when 50% of cumulative rainfall has fallen), but a higher $m3$ (proportion of rainfall in the first third).

The clusters that emerge from this analysis form the empirical basis for defining five distinct aspects of rainfall temporal loading, each capturing a different dimension of storm structure. As described in the following sections, four aspects map closely onto the clusters, while the fifth — intermittency — emerges from a combination of its isolated position in the dendrogram and its prominent treatment in the literature. Two clusters are treated as contributing to a single aspect, magnitude concentration, given their shared conceptual basis.

Cluster 1 is the largest, containing fifteen metrics all describing what we term mass timing — the time at which most rainfall falls during an event. The metrics span both categorical and continuous types, yet exhibit very high Spearman’s rank correlation

coefficients throughout. This suggests that coarser categorical metrics, such as *3rd with most*, rank events similarly to more detailed continuous alternatives such as the *centre of gravity*, despite their differences in construction.

The second cluster contains eight metrics describing a related but distinct aspect: peak timing, the time at which the peak rainfall intensity occurs. Correlation coefficients are again high despite the mixture of categorical and continuous metrics. While most metrics in this group explicitly quantify the timing of the peak time step, interestingly, the metric *m1*, representing the ratio of rainfall before versus after the peak, is also placed within this cluster. Although *m1* is seemingly focused on the balance of rainfall mass distribution rather than peak timing, its position within this cluster suggests that, in practice, it is strongly influenced by peak placement.




Figure 4. (a) Dendrogram visualising results of hierarchical cluster analysis of the pairwise similarity of metrics across all events. Similarity is quantified using the absolute value of Spearman's ρ , and clustering is performed using agglomerative hierarchical clustering with average linkage and 12 clusters. Clusters with more than one member are highlighted in colour and marked with a cluster number. (b) The full Spearman correlation matrix upon which clustering is based

Clusters 3 and 4 both relate to what we term magnitude concentration — the degree to which rainfall is unevenly distributed across timesteps in terms of intensity. Although they form distinct clusters, both describe the contrast between high- and low-intensity periods, and are treated here as related parts of the same underlying aspect.

Cluster 3 emphasises distributional imbalance — how unequally rainfall is shared across timesteps, rather than the size of peaks in absolute terms. *Peak–mean ratio*, *relative amplitude*, and the *coefficient of variation* form a subcluster reflecting mean-based contrasts between intense and weak timesteps. *classical skewness* and *classical kurtosis* characterise the shape of the intensity distribution. As negative kurtosis is rare in rainfall events (as this would involve lots of high intensity timesteps, accompanied by few low intensity), *classical skewness* and *classical kurtosis* generally co-vary, tending to be high in events where rainfall is concentrated into few timesteps. A further subcluster tightly links the *% time in LIZ* with its complement, *% time in HIZ*, reflecting their inverse relationship, with *Lorenz asymmetry* joining nearby as it also quantifies imbalance in the rainfall distribution between wetter and drier periods. In a separate branch, *event dry ratio*, *Gini coefficient*, and *% of rainfall in the HIZ* cluster together, collectively describing how rainfall volume concentrates into a few timesteps, with events scoring high on one metric tending to do so on the others as well.

Cluster 4 shifts emphasis towards the absolute strength of intense phases. Its first subcluster groups *maximum intensity* and *I30* (the maximum intensity in any 30-minute period), both capturing the magnitude of the single wettest short-duration period. The second subcluster links *mean intensity in the HIZ* (timesteps above the event’s mean intensity) with *classical standard deviation*, both reflecting how rainfall is distributed relative to the event mean. The third subcluster contains *m2* (percentage of total rainfall in the highest-intensity timestep), *PCI*, and *NRMSE_p*. These metrics explicitly compare rainfall in some timesteps with rainfall in other, directly quantifying how concentrated rainfall is within an event. They also share a potential sensitivity to event length, tending to return higher values when an intense burst is embedded in a short event than when it appears in a longer event with more low-intensity timesteps.

The fifth cluster groups *temporal kurtosis*, *temporal standard deviation*, and the *TCI*, defining a further distinct aspect: temporal concentration. Unlike magnitude-based concentration metrics, these only return high values when high-intensity timesteps are tightly grouped in time. Their very low correlation with metrics in other clusters indicates that this dimension of temporal loading is largely independent from the others. An event can have strongly concentrated intensity without that intensity being temporally clustered, and vice versa. This distinction is particularly relevant for applications such as flash-flood risk and soil erosion modelling, where closely clustered high-intensity periods can greatly amplify impacts compared to if high intensity timesteps were spread across an event.

The remaining seven clusters each contain only a single metric, reflecting a range of different situations. *Asymmetry of dependence* characterises how rainfall intensities evolve over time, identifying whether events intensify and decay at similar rates — a feature potentially relevant for understanding storm generation and event evolution. The *event loading index* measures the deviation in temporal variability between an observed event and its time-reversed mirror, capturing structural irregularities not represented by other metrics. Both describe properties that are conceptually interesting and may have value in specific applications, but they do not correspond cleanly to any of the four aspects identified above and are not sufficiently general to warrant inclusion as a core component of the framework. The fractional metrics, *fraction of rainfall in Q2*, *Q3*, and *Q4*, are isolated not because they are uniquely informative, but because individually they offer limited descriptive power, with their information more completely conveyed by mass timing metrics such as *D₅₀* or *4th with most*. *Mean intensity* was included as

395 a diagnostic to test whether any other metrics are implicitly driven by overall event magnitude rather than temporal structure; its isolation confirms this is not the case.

The wet-dry transition rate is also isolated in the cluster analysis, but unlike the metrics discussed above, we argue for this metric to form the basis of a fifth aspect of temporal loading: intermittency. Intermittency is frequently discussed in the literature, especially in the context of soil erosion (Dunkerley, 2015, 2023), and dry intervals within events have been shown
400 to influence infiltration capacity, such that more intermittent rainfall can be tolerated at higher intensities during wet intervals (Dunkerley, 2021b; Aryal et al., 2007). However, whether such processes are occurring depends on the actual arrangement of wet and dry periods within an event, not simply on the proportion of dry time. Despite this, intermittency has primarily been measured using the *event dry ratio* (referred to elsewhere as the *intermittency fraction*, which captures only the proportion of event time that is dry. This creates a conceptual inconsistency: while the literature emphasises the importance of the frequency
405 and sequencing of wet and dry periods, the metrics used typically reduce this to a single duration-based quantity. Two events can share the same dry-time proportion while differing markedly in how fragmented the rainfall is. An event with a single prolonged dry interval is qualitatively different from one in which the same total dry duration is distributed across many short alternating periods. The clustering results confirm this: the *event dry ratio* groups with measures of magnitude concentration, reflecting the fact that a high proportion of dry timesteps implies rainfall is compressed into fewer wet periods, irrespective of
410 how those periods are arranged in time. In contrast, the wet-dry transition rate remains isolated, suggesting that intermittency — when defined in terms of wet–dry alternation frequency — represents a genuinely distinct dimension of event structure not captured by commonly used metrics. Together with the four aspects identified through the cluster analysis, intermittency forms the basis of the conceptual framework developed in the remainder of this study.

4.2 Sensitivity to temporal aggregation (RQ3)

415 The sensitivity of each temporal loading metric to changes in rainfall temporal resolution is examined in Figure 5. Metrics located in the bottom-right corner exhibit high robustness (low numerical and ranking sensitivity), and those trending upwards and to the left show increasing sensitivity to aggregation. Figure 6 complements this by illustrating how full metric distributions shift across temporal resolutions. Results are discussed with reference to the five aspects of temporal loading identified in Section 4.1.

420 Mass timing metrics, including *temporal skewness*, *centre of gravity*, and percentile-based measures such as D_{50} and $T75$, are among the most robust to temporal aggregation. These metrics summarise the cumulative distribution of rainfall mass rather than individual intensity extremes, and their numerical values and event rankings remain tightly clustered across resolutions. Categorical metrics derived from these quantities, such as *3rd with D_{50}* and *3rd with CoG*, are correspondingly stable, though metrics classifying events by the fraction containing the bulk of rainfall show moderate sensitivity — substantially less,
425 however, than those defined by peak timing.

Peak timing metrics show considerably higher sensitivity. Continuous measures describing the position of the peak, such as *time to peak* and *peak position ratio*, and those anchored to peak timing including mI and $skew_p$, display high numerical and ranking instability under aggregation. Temporal aggregation not only smooths intensities but can displace the apparent




Figure 5. Sensitivity of metrics to temporal aggregation. For each metric (separate subplot), points represent comparisons between the metric calculated at coarser resolutions (10-, 30-, 60-minutes) and the reference 5-minute data. For (a). continuous metrics, the x-axis shows Spearman's rank correlation coefficient (ρ) and y-axis symmetrical mean absolute percentage error (sMAPE) relative to the 5-minute baseline. For (b). categorical metrics, the x-axis shows Kendall's tau, and y-axis shows the percent disagreement with 5-minute baseline.

430 timing of the peak, particularly where aggregated values are assigned to the end of time intervals, leading to systematic shifts at coarser resolutions. Distributions for these metrics broaden under aggregation and event rankings are frequently reordered. Categorical metrics based on peak position exhibit a similar pattern. Although this behaviour is conceptually expected, the magnitude and consistency of ranking instability across a large event sample cannot be inferred a priori and therefore warrants explicit quantification.

435 Within the magnitude concentration group, sensitivity varies depending on metric construction. Metrics explicitly dependent on peak intensity, including *peak–mean ratio*, *relative amplitude*, and *maximum intensity*, show strong numerical sensitivity, with values decreasing at coarser resolutions due to peak smoothing. Conversely, *m2*, defined as the percentage of rainfall in the peak timestep, increases with aggregation as longer intervals allow the highest-intensity step to capture a larger fraction of total rainfall. In both cases, ranking sensitivity remains comparatively low (Spearman’s $\rho > 0.8$), suggesting that relative event ordering is largely preserved even where absolute values shift. Such metrics may therefore remain useful for comparative 440 analyses across datasets of differing resolution, though absolute values should not be interpreted independently of it. *Classical skewness* and *classical kurtosis* show both high numerical and ranking sensitivity, reflecting their mathematical dependence on extreme values directly modified by aggregation. Metrics partitioning events into high- and low-intensity zones (HIZ/LIZ) exhibit more moderate responses, with limited numerical change but some ranking instability. *Event dry ratio* also shows moderate sensitivity. An event with a high dry ratio is likely to contain at least one substantial contiguous dry period, which 445 would need to be entirely absorbed by coarsening before the metric is meaningfully altered.

Temporal concentration metrics are among the most robust in the analysis. *Temporal kurtosis*, *temporal standard deviation*, and the *TCI* integrate information across the full event duration and are less dependent on the precise magnitude or location of individual peaks. Both numerical values and event rankings remain comparatively stable across resolutions, and distributions in Figure 6 show only minor shifts, indicating that broader patterns of temporal clustering are largely preserved under aggregation.

450 The intermittency metric exhibits both numerical and ranking sensitivity to aggregation, and we argue this reflects a fundamental incompatibility between the metric and coarsely aggregated data. At coarser resolutions, intermittent dry periods within events are obscured by aggregation, rendering intermittency effectively unmeasurable. Treating coarse-resolution estimates as meaningful risks drawing incorrect conclusions in applications that depend on accurate characterisation of within-event dry periods, including soil erosion modelling, where dry intervals influence infiltration recovery (Dunkerley, 2019, 2021b), and 455 detection of long-term changes in rainfall intensity. If intermittency increases over time but goes undetected due to coarse temporal aggregation, apparent stability in hourly or daily totals could mask a real increase in wet-period intensity (Schleiss, 2018).

Overall, while some responses to aggregation, particularly for peak-dependent metrics, are intuitive, the results demonstrate that the magnitude and ranking implications are highly metric-specific and cannot always be reliably anticipated without 460 explicit testing. These findings provide a practical reference for metric selection under data constraints. Where only coarse-resolution data are available, mass timing and temporal concentration metrics offer the most reliable characterisation, peak timing and magnitude concentration metrics should be interpreted with caution, and the intermittency metric should be considered unreliable.




Figure 6. Sensitivity of metric distributions to temporal aggregation. Each subplot shows how the distribution of a given metric changes when calculated on rainfall data at different temporal resolutions (5-, 10-, 30-, 60-minutes). For (a). continuous metrics, this is shown using overlaid histograms. For (b). categorical metrics, grouped bar charts display the relative frequency of each category across resolutions.

4.3 Sensitivity to DMC construction (RQ4)

465 Sensitivity to conversion of raw 5-minute rainfall into double-normalised, 10-step representations (DMCs) varies substantially across temporal loading metrics, as shown in Figure 7 and Figure 8. Results are discussed with reference to the five aspects of temporal loading identified in Section 4.1. The effects of DMC transformation reflect both de-dimensionalisation, with both time and intensity rescaled to a [0,1] domain, and also resolution coarsening through interpolation. Appendix E presents supplementary sensitivity analysis using double-normalised events that retain their original temporal resolution (i.e., without 470 interpolation to 10 time steps).

Mass timing metrics are among the most robust to DMC conversion. Percentile timing measures (T_{25} , D_{50} , T_{75}), moment-based metrics (*centre of gravity*, *temporal skewness*), and mass distribution indicators (m_3 , m_4 , m_5) all show limited numerical and ranking sensitivity, with value distributions remaining largely unchanged after conversion (Figure 8). These metrics reflect the shape and balance of the event over its duration rather than relying on specific peaks or absolute magnitudes, and are either 475 unitless by construction or meaningful when expressed as proportions of total event time or mass. Categorical metrics derived from these quantities, including *3rd with D_{50}* , *3rd with CoG*, and those recording the fraction with most rainfall (*3rd / 4th / 5th with most*), show corresponding stability.




Figure 7. Sensitivity of metrics to dimensionless mass curve representation. For each metric, points represent comparisons between the metric calculated with 5-minute raw data and with a 10-point, DMCs calculated on 5-minute data. For (a). continuous metrics, the x-axis shows Spearman's rank correlation coefficient (ρ) and y-axis the symmetrical mean absolute percentage error (sMAPE). For (b). categorical metrics, the x-axis shows Kendall's tau and the y-axis the percent disagreement between the pairs of metric values.




Figure 8. Sensitivity of metric distributions to calculation on DMCs. Each subplot shows how the distribution of a given metric changes when calculated on raw rainfall data at 5-minute temporal resolution and on a double-normalised version of the event, interpolated to ten data points. For (a). continuous metrics, distributions are shown using overlaid histograms. Note that gaps in some histograms arise from the discretisation of values when metrics are computed on DMCs—certain metric values are simply not possible, so some histogram bins remain empty. For (b). categorical metrics, grouped bar charts show the relative frequency of each category across resolutions.

Peak timing metrics show considerably higher sensitivity to DMC conversion. Metrics such as *peak position ratio*, *skew_p*, and *m1* are affected both by the interpolation-induced smoothing of sharp transitions and by discretisation arising from the 10-step representation, which constrains values to multiples of 10% and limits meaningful variation across events. The stepped histograms visible in Figure 8.(a) illustrate this clearly. As with temporal aggregation, peak displacement under interpolation can reorder event rankings, and this sensitivity is particularly pronounced for metrics anchored to the precise timing of peak intensity.

The effects of DMC conversion on magnitude concentration metrics are more varied. Metrics relying on relative contrasts between timesteps, such as *peak–mean ratio*, *relative amplitude* and *m2*, are affected by interpolation-induced smoothing in a manner similar to temporal aggregation. However, de-dimensionalisation introduces additional consequences not present under aggregation alone. Metrics that depend on absolute intensity contrasts, such as *classical standard deviation* and *coefficient of variation*, lose interpretability when all intensities are normalised to a [0,1] domain, as relative differences are compressed and the metric no longer reflects the original signal. *Mean intensity* becomes entirely uninformative, returning a fixed value of 0.1 in all cases (Figure 8.(a)). Metrics describing distributional imbalance in relative terms, such as the *Gini coefficient*, are more stable, as their construction is less dependent on physical units.

Temporal concentration metrics show moderate sensitivity to DMC conversion. The interpolation process smooths sharp transitions between timesteps, which can reduce the apparent clustering of high-intensity periods and affect metrics such as *temporal kurtosis* and *temporal standard deviation*. However, because these metrics integrate information across the full event rather than depending on individual peaks, they remain more stable than peak timing metrics, and broader patterns of temporal clustering are largely preserved.

The conclusions drawn above for the aggregation sensitivity of the intermittency metric apply equally to the DMC representation. Interpolation to ten time steps inevitably obscures within-event dry periods, and intermittency derived from DMC events should be treated with the same caution as coarse-resolution estimates. As with aggregation, treating DMC-based intermittency estimates as meaningful risks masking real variability in wet-dry switching behaviour, and we recommend that intermittency is excluded from any analysis based solely on DMC representations.

Overall, these findings reinforce the practical guidance offered by the temporal aggregation analysis. Mass timing and temporal concentration metrics are the most transferable across input representations, while peak timing and magnitude concentration metrics require particular caution when applied to DMC data, and intermittency metrics become meaningless. This distinction is especially relevant when DMCs are used to classify rainfall types or inform design storms, where metric interpretability in the dimensionless domain should be an explicit consideration in metric selection.

4.4 Recommendations

Based on the findings of the literature review and the data-driven clustering exercise, we recommend breaking event temporal loading into five components: (1) mass timing, (2) peak timing, (3) magnitude concentration, (4) temporal concentration, and (5) intermittency. Table 3 summarises each component, lists the metrics associated with it, and identifies a recommended metric for practical use. The recommended metrics are: the 4th with most rainfall and D50 (mass timing); the peak-position-

ratio (peak timing); Gini coefficient (magnitude concentration); Temporal standard deviation (temporal concentration); and the wet-dry transition rate (intermittency). Recommended metrics are selected on the basis of two criteria. Where a component showed high sensitivity to temporal aggregation or DMC construction, we recommend the metric that proved most robust across resolutions and representations. Where a component showed consistently low sensitivity, we prioritise comparability with existing literature and recommend the simplest and most widely used metric. An exception is mass timing, for which we recommend two metrics — one continuous and one categorical. D_{50} is recommended as the more precise and informative measure. However, the categorical *4th with most* metric is so widely used in the literature and performs sufficiently well in sensitivity testing that we also recommend its continued use, to maintain comparability with existing studies. The equation for each of the suggested metrics are detailed in Equations 4, 6, 7, 8, 9, and 12.

Conceptually, D_{50} is defined as the percentage of event duration at which 50% of the total event rainfall volume has accumulated. Given a precipitation rate, $r(t)$, and a precipitation accumulation over time, $P(t) = \int_0^t r(t)dt$, D_{50} is given by

$$D_{50} = \frac{t_{50}}{t_{end}} \quad (4)$$

where t_{end} is the total event duration, and t_{50} satisfies $P(t_{50}) = \frac{1}{2}P(t_{end})$.

4th with most is calculated by splitting a rainfall event into four segments of equal duration, and defining this set as $q = 1, 2, 3, 4$. If the total number of time steps is not divisible by four, then the time steps are rescaled accordingly and the precipitation is linearly interpolated to the new time steps. We then define the total sum of precipitation in each quartile as:

$$P_q = \sum_{i \in T_q} p_i, \quad q = 1, 2, 3, 4 \quad (5)$$

where T_q is the set of time steps in each segment, and p_i is the precipitation accumulation in the i 'th time step. Finally, *4th with most* becomes:

$$Q_{\max} = \arg \max_{q \in \{1, 2, 3, 4\}} P_q \quad (6)$$

The *Gini coefficient* is provided by

$$Gini = \frac{1}{2n^2\mu} \sum_{i=1}^n \sum_{j=1}^n |p_i - p_j| \quad (7)$$

where n is the total number of time steps in the event, and μ is the mean precipitation intensity.

The *peak position ratio* is given as the time step where the peak, t_{peak} , is located over the total duration of the event, t_{end} :

$$PeakPositionRatio = \frac{t_{peak}}{t_{end}} \quad (8)$$

The *temporal standard deviation* is defined as

$$\sigma_t = \frac{1}{t_{end}} \sqrt{\frac{\sum_{i=1}^n (t_i - t_{\mu})^2 p_i}{\sum_{i=1}^n p_i}} \quad (9)$$

where t_μ is the centre of gravity and t_i is the time accumulation during the event at time step i :

$$t_\mu = \frac{\sum_{i=1}^n t_i p_i}{\sum_{i=1}^n p_i} \quad (10)$$

$$t_i = (i + 1)\Delta t \quad (11)$$

545 The *wet-dry transition rate* is the proportion of event duration where a switch between wet and dry states occur:

$$\text{Wet} - \text{dry transition rate} = \frac{1}{n} \sum_{i=1}^{n-1} \mathbf{1}(s_i \neq s_{i+1}) \quad (12)$$

where $\mathbf{1}(\cdot)$ is an indicator function (1 = true, 0 = false), and $s_i = \mathbf{1}(p_i > 0)$ is a binary wet/dry indicator.

4.5 Study limitations

It is important to reflect on the representativeness of the rainfall data used in this study. Our analysis draws on the high-quality,
 550 dense network of gauges across Denmark, providing over 233,000 well-observed rainfall events. This scale of dataset allows for robust evaluation of metric behaviour under real storm conditions. However, Denmark's temperate maritime climate is not fully representative of the range of rainfall regimes globally. In particular, strongly convective extremes typical of tropical and subtropical climates are less frequent, and storm dynamics may differ from those in arid or mountainous regions. As such, while our findings on the behaviour, sensitivity, and clustering of metrics are expected to generalise across contexts,
 555 the specific distribution of rainfall events and the relative prevalence of different temporal loading structures may not. We therefore recommend that future work apply similar analyses in a wider set of climatic settings, both to test the robustness of our methodological conclusions and to build a more globally representative basis for metric selection.

This analysis also has limited ability to assess whether metric choice would materially alter substantive conclusions about rainfall characteristics in a given context. The cluster analysis shows that many metrics rank events in a similar order, but does
 560 not consider how those rankings are converted into interpretable outcomes. In practice, this often involves applying thresholds or grouping events—for example, classifying events as front- or back-loaded using D_{50} . Although different metrics may agree on which events are more or less front-loaded, they do not necessarily assign events to the same categories, particularly for events that sit near the classification boundaries. As a result, the same set of events could support different conclusions—for instance, one metric indicating a predominance of front-loaded events, while another suggests a more balanced distribution.

565 This issue extends to aggregated analyses. Differences in how events are classified can propagate into summary statistics, such as the proportion of front-loaded events or comparisons between catchments and climates. The key limitation is therefore not disagreement in relative ordering, but in how that ordering is translated into categorical or aggregated interpretations. Quantifying the extent to which this influences substantive conclusions was beyond the scope of this study, but represents an important direction for future work.

Table 3. Five recommended components of rainfall event temporal loading. Each component is described, the associated metrics listed, and a recommended metric identified. Listed metrics robust to temporal aggregation and DMC processing are highlighted in red

Component	Description	All metrics	Recommendation	Reasons
Mass timing	Describes when the majority of rainfall mass falls during the event.	<i>3rd / 4th / 5th with most, 3rd with D_{50}, 3rd with CoG, Centre of gravity, D_{50}, T25/75, m3, m4, m5, Event loading index, (t) skewness, Asymmetry of dependence, Frac. in Q1 / 2 / 3 / 4</i>	<i>4th with most (categorical) D_{50} (continuous)</i>	Many metrics are robust to both temporal aggregation and DMC construction. D_{50} is recommended as the most precise and informative continuous measure. The <i>4th with most</i> is additionally recommended due to its widespread use in the literature, supporting comparability with existing studies.
Peak timing	Describes when the peak intensity occurs during the event.	<i>3rd/ 4th / 5th with peak, 3rd ppr, time to peak, peak position ratio, Skew_p, m1</i>	<i>Peak position ratio</i>	No peak timing metrics are robust to temporal aggregation or DMC construction, so all should be used in cross-resolution comparison with care. <i>Peak position ratio</i> is recommended as the simplest and most widely applied option
Magnitude concentration	Describes the strength of intense phases, contrasts between high- and low-intensity periods, or overall statistical inequality. Not affected by whether timesteps concentrating rainfall are close together in time, or where in time they occur.	<i>Max intensity, I30, PCI, (c) skewness, (c) kurtosis, (c) std, CV, Mean intensity in HIZ, % time in LIZ / HIZ, % Rain in HIZ, Gini Coefficient, Lorenz Asymmetry Coefficient, NRMSE_p, Peak-mean ratio, Relative amplitude, m2, event dry ratio</i>	<i>Gini coefficient</i>	Most metrics in this category are sensitive to both temporal aggregation and DMC construction. The Gini coefficient is the only metric robust to both, and is therefore recommended despite being less commonly applied than alternatives such as peak-mean ratio.
Temporal concentration	Describes how narrowly rainfall is clustered around a point in time, regardless of when in time that cluster appears.	<i>TCl, (t) kurtosis, (t) std</i>	<i>(T) std</i>	All metrics in this category are robust to both temporal aggregation and DMC construction. <i>(t) standard deviation</i> is recommended over <i>TCl</i> as it is simpler to compute and interpret, and directly related to a well-established statistical concept, while capturing the same underlying property.
Intermittency	Describes how frequently conditions within a rainfall event switch between wet and dry conditions.	<i>Wet-dry transition rate</i>	<i>Wet-dry transition rate</i>	<i>Wet-dry transition rate</i> is sensitive to temporal aggregation because within-event dry periods are obscured at coarser resolutions. It is recommended only where high-resolution data are available, and results should not be compared across studies using different

570 5 Summary and conclusions

Rainfall event temporal loading, the distribution of rainfall intensity over time at a fixed location, plays an important role in driving hydrological and geomorphological responses such as run-off, urban flooding, and soil erosion. Yet despite its significance, a coherent, consistent approach to its quantification has previously been lacking. This study provides a comprehensive, interdisciplinary review of rainfall event temporal loading metrics, identifying 48 metrics previously applied across scientific domains and introducing five additional metrics to represent aspects not fully covered by existing approaches. Considerable inconsistency in terminology and framing was found across the literature, making it difficult to determine what different studies are measuring, what aspect of storm structure they intend to capture, or whether seemingly similar analyses are directly comparable. The five-component conceptual framework proposed here provides a structured way to distinguish between the key properties of temporal loading and clarify the purpose of different metrics.

580 All 53 metrics were calculated across 233,128 rainfall events from Danish rain gauge records, and cluster analysis revealed which metrics capture overlapping information and which describe distinct aspects of storm structure. This provided an empirical basis for the suggested five-component conceptual framework and metric recommendations.

Metrics were also evaluated under different data and processing conditions. Sensitivity to temporal resolution was found to vary substantially between metrics: those describing mass timing and temporal concentration are relatively stable under aggregation, whereas metrics related to peak timing and intermittency are highly sensitive. The behaviour of magnitude concentration metrics was more variable, and dependent upon their specific formulation. In addition, transforming events to dimensionless mass curves alters the interpretability of some metrics while leaving others largely unaffected. Given that rainfall data from gauges, radar, and reanalysis products are typically available at differing levels of temporal aggregation, these findings highlight that robustness to data representation is a key consideration. Metric selection should therefore be aligned not only with the aspect of storm structure of interest, but also with the characteristics and limitations of the available data.

590 Overall, this work provides a clearer understanding of what temporal loading metrics measure, how they relate to one another, and how they behave under different data conditions. It offers a foundation for more explicit, consistent, and reproducible characterisation of rainfall temporal loading, and supports clearer cross-study comparison going forward.

Code availability. Code is available at <https://github.com/masher92/MetricEvaluation/>

595 Appendix A: Literature review: search and selection strategy

The literature review follows the PRISMA (Preferred Reporting Items for Systematic Reviews and Meta-Analyses) framework (Moher et al., 2010). The PRISMA framework is a standardised method of performing literature review which aims to minimise potential researcher bias, and to promote transparency and reproducibility in the identification and selection of relevant studies. The framework includes four key stages: (1) identification, boolean queries used to identify potential studies, duplicated studies
600 removed; (2) screening, abstract level review to remove irrelevant studies; (3) eligibility, full-text review against pre-defined inclusion/exclusion criteria; and (4) inclusion, relevant studies included for review, and the total number of studies reported.

Boolean queries are search strings using AND, OR and NOT operators, and are constructed here by combining different terms used in the literature to describe event temporal loading, with different terms used to describe rainfall events. The full queries used to search the Scopus, Web of Science, and Google Scholar databases are outlined below:

- 605 – Scopus supports proximity operators (e.g., *W/n* requires two words to appear within *n* words of each other; *Pre/n* requires one word to precede the other within *n* words), a feature not available in the other databases. As such, for Scopus the search term was: [("rainfall event" OR "precipitation event" OR "rain storm" OR "rainstorm" OR "storm event" OR (("precipitation" OR "rain" OR "rainfall" OR "storm") PRE/3 "event")) OR (("precipitation varia*" OR "rainfall varia*") W/1 "intra-event")) W/5 ("rainfall profile" OR "temporal pattern" OR "temporal distribution" OR
610 "event loading" OR "temporal profile" OR "temporal loading" OR "intensity profile" OR (("precipitation pattern" OR "rainfall pattern") W/3 "temporal"))]
- For Web of Science and Google Scholar, it was: ("rainfall event" OR "precipitation event" OR "rain storm" OR "rainstorm" OR "storm event" OR ("precipitation" OR "rain" OR "rainfall" OR "storm") AND "event" OR ("precipitation varia*" OR "rainfall varia*") AND "intra-event") AND ("rainfall profile" OR "temporal pattern" OR "temporal distribution" OR "event loading" OR "temporal profile" OR "temporal loading" OR "intensity profile" OR ("precipitation
615 pattern" OR "rainfall pattern") AND "temporal")].

The searches were performed on the 15/02/2025 and returned 903 relevant records overall (including 181 on Scopus, 409 on Web of Science, and 313 on Google Scholar). 351 duplicated records were removed, leaving 552 studies for abstract level screening. After screening of abstracts, a further 390 studies were eliminated, leaving 162 papers for full review.

- 620 Studies were included if they met the following criteria: (a) use of search terms in the title, abstract, or keywords; (b) published in English; (c) focus on individual rainfall events with data at sub-daily temporal resolution; (d) application of a method or metric to quantify temporal loading. Exclusion criteria were: (a) not published in English; (b) inaccessible or behind paywalls (to the authors, not all included studies are open-access); (c) lack of use of sub-daily rainfall data; (d) combined spatial and temporal analysis (where the temporal loading could not be separated); (e) focus on rainfall trends over extended
625 periods (e.g., seasonal or monthly scales); (f) no application of a metric for quantifying within-event temporal variability.

After applying these criteria, a total of 59 studies remained. We note, however, that several additional studies met all criteria except the use of a metric to quantify temporal loading. These excluded studies fall into three main groups. The first concerns

the disaggregation of daily rainfall data (Pampaloni et al., 2021). The second includes stochastic event generation approaches (Cha et al., 2024; Efstratiadis et al., 2022; Kao and Govindaraju, 2008; Nguyen and Chen, 2022; Oriani et al., 2018; Pampaloni et al., 2021). The third involves applications of synthetic rainfall events with prescribed temporal patterns to investigate impacts on soil erosion (De Lima and Singh, 2002; de Lima et al., 2013; Frauenfeld and Truman, 2004; Gao et al., 2018; Parsons and Stone, 2006; Wang et al., 2023), landslides (Zhao et al., 2025), and herbicide runoff (Zhang et al., 1997). In these cases, event profiles are described using broad qualitative labels (e.g. linearly increasing, stepped increasing–decreasing, uniform) rather than being quantified with explicit metrics.

Table B1. Summary of reviewed papers

Authors	Metric type	Metric	Study purpose	Rainfall	Processing
Amin et al. (2000)	Classification	<i>4th with most</i>	Characterising typical profiles in an area	Real	DMC
Aquino et al. (2013)	Classification	<i>3rd with peak</i>	Impact of storm temporal pattern on soil erosion	Real	Raw
Asher et al. (2025b)	Classification	<i>5th with most</i>	Impact of storm temporal pattern on flood risk	Synthetic	DMC
Azli and Rao (2010)	Classification	<i>4th with most</i>	Characterising typical profiles in an area	Real	DMC
Back and Rodrigues (2021)	Classification	<i>4th with peak</i>	Characterising typical profiles in an area	Real	Unclear
Bezak et al. (2018)	Classification	<i>4th with most</i>	Impact of storm temporal pattern on hydraulic model outcomes	Synthetic	DMC
Brommer et al. (2013)	Continuous	<i>mean, (C) std, (C) skewness, (C) kurtosis</i>	Characterising typical profiles in an area	Real	Raw
Cai et al. (2024)	Continuous	<i>Peak position ratio, PCI</i>	Impact of storm temporal pattern on peak runoff generation	Synthetic	Raw
Chen et al. (2015)	Classification	<i>4th with most</i>	Characterising typical profiles in an area	Real	Unclear
de Assunção Montenegro et al. (2018)	Classification	<i>3rd with peak</i>	Impact of storm temporal pattern on soil moisture patterns	Real	Raw
de Andrade et al. (2020)	Classification, Continuous	<i>3rd with peak, I30</i>	Impact of storm temporal pattern on soil erosion	Real	Raw
Dolšek et al. (2016)	Classification	<i>4th with most, BSC</i>	Characterising typical profiles in an area	Real	DMC
Dunkerley (2015)	Continuous	<i>Intermittency fraction</i>	Developing methods for describing temporal profile	Real	Raw
Dunkerley (2021b)	Continuous	<i>Intermittency fraction</i>	Developing methods for describing temporal profile	Real	Raw
Fan et al. (2020)	Continuous	<i>(C) skewness, (C) kurtosis</i>	Impact of storm temporal pattern on landslides	Synthetic	Raw

Authors	Metric type	Metric	Study purpose	Rainfall	Processing
Fatone et al. (2021)	Classification	<i>3rd with peak</i>	Impact of storm temporal pattern on hydrograph outflow	Real	DMC
Fu et al. (2021)	Continuous	<i>Coefficient peak rainfall intensity, 3rd with ppr</i>	Impact of typhoon temporal pattern on pollution generation	Real	Raw
Gao et al. (2024)	Continuous	<i>Relative amplitude</i>	Impact of storm temporal pattern on soil erosion	Real	Raw
García-Bartual and Andrés-Doménech (2017)	Continuous	<i>(C) kurtosis, (C) standard deviation</i>	Characterising typical profiles in an area	Real	Raw
Garcia-Guzman and Aranda-Oliver (1993)	Classification	<i>4th with most</i>	Characterising typical profiles in an area	Real	DMC
Ghanghas et al. (2024)	Continuous	<i>Event Loading Index</i>	Impact of climate on temporal pattern	Real	Raw
He et al. (2022)	Continuous	<i>PCI</i>	Characterising typical profiles in an area	Synthetic	Raw
He et al. (2024)	Continuous	<i>(C) skewness, (C) kurtosis</i>	Impact of storm temporal pattern on slope instability	Synthetic	Raw
Horner and Jens (1942)	Classification	<i>3rd with peak</i>	Impact of storm temporal pattern on surface runoff	Real	Unclear
Hu et al. (2018)	Continuous	<i>Gini coefficient, Lorenz coefficient</i>	Changes to temporal inequality of daily precipitation over last 50 years	Synthetic	Raw
Huff (1967)	Classification	<i>4th with most</i>	Characterising typical profiles in an area	Real	DMC
Jeon et al. (2017)	Classification	<i>4th with most</i>	Impact of storm temporal pattern on water quality from storm runoff	Synthetic	DMC
Jun et al. (2021)	Classification Continuous	<i>4th with most, time to peak</i>	Characterising typical profiles in an area	Real	Unclear
Knighton and Walter (2016)	Continuous	<i>T25 / 50 / 75, time to peak</i>	Stochastic event generation	Real	DMC
Li et al. (2023)	Continuous	<i>Peak-mean ratio, peak position ratio</i>	Evaluating satellite precipitation products	Real	Raw
Liang et al. (2023)	Classification	<i>3rd with most</i>	Impact of storm temporal pattern on soil erosion	Synthetic	DMC

Li et al. (2021)	Classification	<i>4th with most</i>	Characterising typical profiles in an area; Impact of storm temporal pattern on sewer overflows	Real	Raw
Liu et al. (2022)	Continuous	<i>Relative amplitude, % rain HIZ, % time in HIZ / LIZ</i>	Impact of storm temporal pattern on runoff and soil loss	Real	Raw
Long et al. (2021)	Continuous	<i>TCI</i>	Impact of climate on temporal (and spatial) pattern	Real	Unclear
Loveridge et al. (2015)	Classification	<i>3rd with D50</i>	Characterising typical profiles in an area	Real	DMC
Lu and Qin (2020)	Classification	<i>4th with most</i>	Impact of storm temporal pattern on urban drainage	Synthetic	DMC
Müller et al. (2017)	Continuous	<i>Asymmetry of dependence</i>	Impact of storm temporal patterns on sewer flow simulations	Real	Raw
Nel (2007)	Classification	<i>4th with peak</i>	Characterising typical profiles in an area; Impact of storm temporal pattern on runoff and soil erosion	Real	DMC
Oh et al. (2024)	Continuous	<i>NRMSE_p and Skew_p</i>	Impact of storm temporal pattern on peak flood discharge	Real	Unclear
Pandey et al. (2025)	Continuous	<i>Intermittency fraction</i>	Impact of climate on temporal pattern	Real	Raw
Pinheiro et al. (2018)	Classification	<i>3rd with peak</i>	Characterising typical profiles in an area; Impact of storm temporal pattern on soil erosion	Real	DMC
Pohle et al. (2018)	Continuous	<i>Event dry ratio, Frac. in Q1 / Q2 / Q3 / Q4</i>	Stochastic event generation	Synthetic	Raw
Terranova and Iaquina (2011)	Classification	<i>BSC</i>	Characterising typical profiles in an area	Real	DMC
Tian et al. (2017)	Continuous	<i>CV</i>	Stochastic event generation	Synthetic	Raw
Todisco (2014)	Classification	<i>CV, Run number</i>	Developing methods for describing temporal profile; Impact of storm temporal pattern on soil erosion	Real	Raw
Tsubo et al. (2005)	Classification	<i>4th with peak</i>	Characterising typical profiles in an area	Real	DMC

Serna and Taipe (2019)	Classification	<i>3rd with peak</i>	Characterising typical profiles in an area	Real	DMC
Schiff (1943)	Classification	<i>3rd with peak</i>	Impact of storm temporal pattern on infiltration and runoff	Real	DMC
Varga et al. (2009)	Classification	<i>3rd with CoG</i>	Developing methods for describing temporal profile	Real	DMC
Vantas et al. (2019)	Classification	<i>4th with most</i>	Developing methods for describing temporal profile	Real	Raw
Villalobos Herrera et al. (2023)	Classification	<i>5th with most</i>	Characterising typical profiles in an area	Real	DMC
Visser et al. (2023)	Continuous	<i>D₅₀</i>	Impact of climate on temporal pattern	Real	DMC
Wang et al. (2016)	Classification	<i>3rd with peak</i>	Impact of storm temporal pattern on soil erosive loss	Real	DMC
Wang et al. (2018)	Classification	<i>3rd with ppr</i>	Impact of storm temporal pattern on soil water transport	Real	DMC
Yang et al. (2015)	Continuous	<i>Coefficient of variability</i>	Assessing performance of data assimilation on events with different temporal loading characteristics	Real	Raw
Yang et al. (2022)	Continuous	<i>Peak position ratio</i>	Characterising typical profiles in an area Regional patterns in temporal profile	Real	Raw
Yang et al. (2024)	Classification	<i>5th with peak</i>	Impact of storm temporal pattern on flash flooding	Real	Unclear
Yin et al. (2016)	Classification	<i>4th with peak</i>	Characterising typical profiles in an area	Real	DMC
Wartalska et al. (2020)	Continuous	<i>m1, m2, m3, m4, m5, peak position ratio</i>	Characterising typical profiles in an area	Real	DMC
Wartalska and Kotowski (2020)	Continuous	<i>m4, n_i</i>	Characterising typical profiles in an area; Impact of future climate on typical profiles.	Real	DMC
Williams-Sether (2004)	Classification	<i>4th with most</i>	Characterising typical profiles in an area	Real	DMC

Appendix C: Summary of reviewed literature and metrics




Figure C1. Distribution of metrics across the reviewed studies, showing both the number of studies in which each metric was applied and the countries from which these studies were drawn.

Table C1. Summary of studies by purpose, metric type, the type of rainfall events used in the study, and the processing stages applied. Note that some studies may be counted under more than one categorisation

Category	Subcategory	Detail	Number of studies
Study purpose	Characterise rainfall profiles in an area		23
	Impact of storm temporal profile on:	Flooding/hydrology	12
		Landslide	1
		Pollution	2
		Soil erosion	13
	Climatic study		6
	Stochastic event generation		3
	Evaluating satellite data		1
	Metric development		5
Metric type	Classification		35
	Continuous		28
Rainfall type	Real		49
	Synthetic		13
Rainfall processing	Raw rainfall events		26
	Dimensionless Mass Curves		28
	Unclear		7

Appendix D: Silhoutte score




Figure D1. Silhouette scores for different numbers of clusters

Appendix E: Repeat of experiments in Section 4.3 using double normalised events

Figures E1 and E2 present supplementary sensitivity analyses that isolate the contribution of de-dimensionalisation to the overall DMC sensitivity reported in Section 4.3, by evaluating sensitivity against double-normalised events that retain their original temporal resolution (i.e., without interpolation to 10 time steps).

For the majority of metrics, retaining the original temporal resolution substantially reduces sensitivity, with Spearman's ρ approaching 1 and sMAPE approaching zero. This confirms that interpolation to ten data points is the dominant driver of sensitivity to DMC construction for most metrics, and that double normalisation alone has limited effect on ranking or value distributions across events.

A notable exception is the cluster of metrics, including *maximum intensity*, *mean intensity*, *time to peak*, *standard deviation*, and *mean intensity within the HIZ*, which exhibit sMAPE values approaching 200. These metrics are defined in terms of absolute magnitudes, meaning that their values depend directly on the scale of the rainfall intensities. When applied to double normalised representations constrained to the range [0,1], this magnitude information is removed, and the resulting values are no longer directly comparable to those derived from the raw data. As a result, the difference between raw and normalised values is dominated by this scale mismatch, causing sMAPE to approach its upper bound. While variability is not eliminated under normalisation, it is substantially compressed relative to the raw values, which may span several orders of magnitude. This compression further inflates sMAPE, as differences are evaluated relative to a much smaller range. These results should therefore be interpreted as evidence of incompatibility between the metric definition and the normalised representation, rather than as an indication of genuine sensitivity.




Figure E1. Sensitivity of metrics to calculation on double normalised events. For each metric, points represent comparisons between the metric calculated with 5-minute raw data and with a double normalised version of the event calculated on 5-minute data. For (a). continuous metrics the x-axis shows Spearman's rank correlation coefficient (ρ) and y-axis the symmetrical mean absolute percentage error (sMAPE). For (b). categorical metrics, the x-axis shows Kendall's tau and the y-axis the percent disagreement between the pairs of metric values.




Figure E2. Sensitivity of metric distributions to calculation on double normalised events. Each subplot shows how the distribution of a given metric changes when calculated on raw rainfall data at 5-minute temporal resolution and on a double-normalised version of the event calculated on 5-minute data. For (a), continuous metrics, distributions are shown using overlaid histograms. For (b), categorical metrics, grouped bar charts show the relative frequency of each category across resolutions.

Appendix F: Summary of experimental results for selected metrics

Table F1: Summary of experimental results for investigated metrics

Metric	Classification	Robust to:	
		Temporal resolution	DMC transformation
<i>Frac. in Q1</i>	Mass timing	×	×
<i>m3 / m4 / m5</i>	Mass timing	✓	✓
<i>Temporal skewness [(T) skewness]</i>	Mass timing	✓	✓
<i>Centre of gravity (CoG)</i>	Mass timing	✓	✓
<i>T25 / T50 and D₅₀ / T75</i>	Mass timing	✓	✓
<i>m1</i>	Mass timing	×	×
<i>3rd with D₅₀</i>	Mass timing	✓	✓
<i>3rd with CoG</i>	Mass timing	✓	✓
<i>3rd/4th/5th with most</i>	Mass timing	✓	✓
<i>Time to peak</i>	Peak timing	×	×
<i>Skew_p</i>	Peak timing	×	×
<i>Peak position ratio / Coefficient-peak-rainfall-intensity</i>	Peak timing	×	×
<i>3rd with ppr</i>	Peak timing	×	×
<i>3rd/4th/5th with peak</i>	Peak timing	×	×
<i>I30</i>	Magnitude concentration	✓	×
<i>Max intensity</i>	Magnitude concentration	×	×
<i>Classical standard deviation [(C) std]</i>	Magnitude concentration	✓	×
<i>Classical kurtosis [(C) kurtosis]</i>	Magnitude concentration	×	×
<i>Classical skewness [(C) skewness]</i>	Magnitude concentration	×	×
<i>Coefficient of variation</i>	Magnitude concentration	✓	×
<i>Peak-mean ratio / Rainfall intensity irregularity (n_i)</i>	Magnitude concentration	×	×
<i>Relative amplitude</i>	Magnitude concentration	×	×
<i>Mean intensity in HIZ</i>	Magnitude concentration	✓	×
<i>% rain in HIZ</i>	Magnitude concentration	×	×
<i>% time in LIZ / HIZ</i>	Magnitude concentration	×	×
<i>NRMSE_p</i>	Magnitude concentration	×	×

Metric	Classification	Robust to:	
		Temporal resolution	DMC transformation
<i>m2</i>	Magnitude concentration	×	×
<i>Gini coefficient</i>	Magnitude concentration	✓	✓
<i>Lorenz asymmetry coefficient</i>	Magnitude concentration	×	×
<i>Precipitation Concentration Index (PCI)</i>	Magnitude concentration	×	×
<i>Event dry ratio</i>	Magnitude concentration	×	×
<i>Temporal Concentration Index (TCI)</i>	Temporal concentration	✓	✓
<i>Temporal kurtosis [(T) kurtosis]</i>	Temporal concentration	✓	✓
<i>Temporal standard deviation [(T) std]</i>	Temporal concentration	✓	✓
<i>Wet-dry transition rate</i>	Intermittency	×	×
<i>Event loading index</i>	Unclassified	×	×
<i>Asymmetry of dependence</i>	Unclassified	×	×
<i>Mean intensity</i>	Unclassified	✓	×
<i>Frac. in Q2 / Q3 / Q4</i>	Unclassified	×	×

Author contributions. Conceptualisation and methodology was by MA and JP, Funding acquisition and supervision by MT and CB. Data curation was by MA, JP and RH. Formal analysis was by MA and RH. Investigation and visualisation was by MA. The original manuscript was written by MA, with review and editing by JP, MT, CB and SB.

660 *Competing interests.* The authors declare that they have no conflict of interest.

Acknowledgements. We would like to thank the Water Pollution Committee of The Society of Danish Engineers for allowing us to use their data for this study.

We also extend thanks to Lawrence Jackson for his guidance on the statistical analysis of metrics performed in this study.

References

- Alavinia, M., Saleh, F. N., and Asadi, H.: Effects of rainfall patterns on runoff and rainfall-induced erosion, *International Journal of Sediment Research*, 34, 270–278, 2019.
- Amin, S., Sepaskhah, A. R., and Keshmiripour, B.: Rainfall intensity distribution patterns in climatological conditions of four stations in Fars province, Iran, *Iranian Journal of Science and Technology*, 24, 89–98, 2000.
- Aquino, R. F., Silva, M. L. N., Freitas, D. A. F. d., Curi, N., and Avanzi, J. C.: Soil losses from typic Cambisols and Red Latosol as related to three erosive rainfall patterns, *Revista Brasileira de Ciência do Solo*, 37, 213–220, 2013.
- Aryal, R., Furumai, H., Nakajima, F., and Jinadasa, H.: The role of inter-event time definition and recovery of initial/depression loss for the accuracy in quantitative simulations of highway runoff, *Urban Water Journal*, 4, 53–58, 2007.
- Asher, M., Pedersen, J. W., Böing, S., Birch, C., Trigg, M., and Kendon, E.: Extreme rainfall and temporal loading in Great Britain: Analysis of present and future trends using a convection-permitting climate model, *Journal of Hydrology: Regional Studies*, 62, 102750, <https://doi.org/10.1016/j.ejrh.2025.102750>, 2025a.
- Asher, M., Trigg, M., Böing, S., and Birch, C.: The Sensitivity of Urban Pluvial Flooding to the Temporal Distribution of Rainfall Within Design Storms, *Journal of Flood Risk Management*, 18, e70097, 2025b.
- Azli, M. and Rao, A. R.: Development of Huff curves for peninsular Malaysia, *Journal of Hydrology*, 388, 77–84, 2010.
- Back, A. J. and Rodrigues, M. L. G.: Characterization of temporal rainfall distribution in Florianópolis, Santa Catarina, Brazil, *Revista Brasileira de Climatologia*, 28, 201–219, 2021.
- Bezák, N., Šraj, M., Rusjan, S., and Mikoš, M.: Impact of the rainfall duration and temporal rainfall distribution defined using the Huff curves on the hydraulic flood modelling results, *Geosciences*, 8, 69, 2018.
- Boughton, W. and Droop, O.: Continuous simulation for design flood estimation—a review, *Environmental Modelling & Software*, 18, 309–318, 2003.
- Brommer, D. M., Cervený, R. S., and Balling Jr, R. C.: An analysis of intra-event precipitation variability for the United States (1980–2010), *Physical Geography*, 34, 456–470, 2013.
- Cai, Y., Yang, Y., Tan, Q., Dai, C., Zhu, Z., and Zhang, X.: Impacts of temporal/spatial rainfall heterogeneities on peak runoff distribution and intensities for an urban river basin of south China, *River*, 3, 24–37, 2024.
- Centre for Ecology & Hydrology: The Flood Estimation Handbook (five volumes). Volume 3: Statistical procedures for flood frequency estimation, Centre for Ecology & Hydrology, Wallingford, UK, 1999.
- Cha, H., Baik, J., Lee, J., Na, W., Bateni, S. M., and Jun, C.: Generation of rainfall scenarios based on rainfall transition probability to determine temporal distribution of independent rainstorms, *Stochastic Environmental Research and Risk Assessment*, pp. 1–19, 2024.
- Chen, Z., Yin, L., Chen, X., Wei, S., and Zhu, Z.: Research on the characteristics of urban rainstorm pattern in the humid area of Southern China: a case study of Guangzhou City., *International Journal of Climatology*, 35, 2015.
- de Andrade, A. F., Machado, R. L., Rezende, C. C., Ferreira, E. A., de Águas, M. A., Correchel, V., and de Carvalho, D. F.: Precipitation Patterns and Rainfall Erosivity Return Period Under Savanna Conditions in Formosa, Goiás, Brazil, *Journal of Agricultural Studies*, 8, 554–569, 2020.
- de Assunção Montenegro, A. A., dos Santos Souza, T. E. M., de Souza, E. R., and Montenegro, S. M. G. L.: Temporal dynamics of soil moisture and rainfall erosivity in a tropical volcanic archipelago, *Journal of Hydrology*, 563, 737–749, 2018.

- 700 De Lima, J. and Singh, V.: The influence of the pattern of moving rainstorms on overland flow, *Advances in Water Resources*, 25, 817–828, 2002.
- de Lima, J. L., Carvalho, S. C., and P de Lima, M. I.: Rainfall simulator experiments on the importance of when rainfall burst occurs during storm events on runoff and soil loss, *Zeitschrift fur Geomorphologie Supplement*, 57, 91–109, 2013.
- Dey, P.: On the Structure of the Intermittency of Rainfall, *Water Resources Management*, 37, 1461–1472, 2023.
- 705 DMI: Climate Data — DMI Open Data, https://opendatadocs.dmi.govcloud.dk/en/Data/Climate_Data, accessed: 2025-06-22, 2025.
- Dolšák, D., Bezak, N., and Šraj, M.: Temporal characteristics of rainfall events under three climate types in Slovenia, *Journal of Hydrology*, 541, 1395–1405, 2016.
- Dunkerley, D.: Identifying individual rain events from pluviograph records: a review with analysis of data from an Australian dryland site, *Hydrological Processes: An International Journal*, 22, 5024–5036, 2008.
- 710 Dunkerley, D.: Intra-event intermittency of rainfall: An analysis of the metrics of rain and no-rain periods, *Hydrological Processes*, 29, 3294–3305, 2015.
- Dunkerley, D.: The importance of incorporating rain intensity profiles in rainfall simulation studies of infiltration, runoff production, soil erosion, and related landsurface processes, *Journal of Hydrology*, 603, 126 834, 2021a.
- Dunkerley, D.: Intermittency of rainfall at sub-daily timescales: New quantitative indices based on the number, duration, and sequencing of interruptions to rainfall, *Atmospheric Research*, 253, 105 475, 2021b.
- 715 Dunkerley, D.: Huff quartile classification of rainfall intensity profiles ('storm patterns'): A modified approach employing an intensity threshold, *Catena*, 216, 106 371, 2022.
- Dunkerley, D.: Rainfall intensity and intermittency over timescales of minutes: Measurement using low sampling-rate acoustic recording, *Atmospheric Research*, 290, 106 814, 2023.
- 720 Dunkerley, D. L.: How do the rain rates of sub-event intervals such as the maximum 5-and 15-min rates (I5 or I30) relate to the properties of the enclosing rainfall event?, *Hydrological Processes*, 24, 2425–2439, 2010.
- Dunkerley, D. L.: Rainfall intensity bursts and the erosion of soils: An analysis highlighting the need for high temporal resolution rainfall data for research under current and future climates, *Earth Surface Dynamics*, 7, 345–360, 2019.
- Efstratiadis, A., Dimas, P., Pouliasis, G., Tsoukalas, I., Kossieris, P., Bellos, V., Sakki, G.-K., Makropoulos, C., and Michas, S.: Revisiting flood hazard assessment practices under a hybrid stochastic simulation framework, *Water*, 14, 457, 2022.
- 725 Einfalt, T., Arnbjerg-Nielsen, K., Golz, C., Jensen, N.-E., Quirmbach, M., Vaes, G., and Vieux, B.: Towards a roadmap for use of radar rainfall data in urban drainage, *Journal of Hydrology*, 299, 186–202, 2004.
- Fan, L., Lehmann, P., Zheng, C., and Or, D.: Rainfall intensity temporal patterns affect shallow landslide triggering and hazard evolution, *Geophysical Research Letters*, 47, e2019GL085 994, 2020.
- 730 Fatone, F., Szeląg, B., Kiczko, A., Majerek, D., Majewska, M., Drewnowski, J., and Łagód, G.: Advanced sensitivity analysis of the impact of the temporal distribution and intensity of rainfall on hydrograph parameters in urban catchments, *Hydrology and Earth System Sciences*, 25, 5493–5516, 2021.
- Formetta, G., Prosdocimi, I., Stewart, E., and Bell, V.: Estimating the index flood with continuous hydrological models: an application in Great Britain, *Hydrology Research*, 49, 123–133, 2018.
- 735 Fowler, H. J., Lenderink, G., Prein, A. F., Westra, S., Allan, R. P., Ban, N., Barbero, R., Berg, P., Blenkinsop, S., Do, H. X., et al.: Anthropogenic intensification of short-duration rainfall extremes, *Nature Reviews Earth & Environment*, 2, 107–122, 2021.

- Frauenfeld, B. and Truman, C.: Variable rainfall intensity effects on runoff and interrill erosion from two coastal plain ultisols in Georgia, *Soil Science*, 169, 143–154, 2004.
- Freitas, E. d. S., Coelho, V. H. R., Xuan, Y., de CD Melo, D., Gadelha, A. N., Santos, E. A., Galvão, C. d. O., Ramos Filho, G. M., Barbosa, L. R., Huffman, G. J., et al.: The performance of the IMERG satellite-based product in identifying sub-daily rainfall events and their properties, *Journal of Hydrology*, 589, 125–128, 2020.
- Fu, X., Liu, J., Mei, C., Luan, Q., Wang, H., Shao, W., Sun, P., and Huo, Y.: Effect of typhoon rainstorm patterns on the spatio-temporal distribution of non-point source pollution in a coastal urbanized watershed, *Journal of Cleaner Production*, 292, 126–128, 2021.
- Gao, G., Liang, Y., Liu, J., Dunkerley, D., and Fu, B.: A modified RUSLE model to simulate soil erosion under different ecological restoration types in the loess hilly area, *International Soil and Water Conservation Research*, 12, 258–266, 2024.
- Gao, J., Kirkby, M., and Holden, J.: The effect of interactions between rainfall patterns and land-cover change on flood peaks in upland peatlands, *Journal of Hydrology*, 567, 546–559, 2018.
- García-Bartual, R. and Andrés-Doménech, I.: A two-parameter design storm for Mediterranean convective rainfall, *Hydrology and Earth System Sciences*, 21, 2377–2387, 2017.
- Garcia-Guzman, A. and Aranda-Oliver, E.: A stochastic model of dimensionless hyetograph, *Water Resources Research*, 29, 2363–2370, 1993.
- Ghanghas, A., Sharma, A., and Merwade, V.: Unveiling the evolution of extreme rainfall storm structure across space and time in a warming climate, *Earth's Future*, 12, e2024EF004675, 2024.
- Gholami, L., Khaledi Darvishan, A., Spalevic, V., Cerdà, A., and Kavian, A.: Effect of storm pattern on soil erosion in damaged rangeland: Field rainfall simulation approach, *Journal of Mountain Science*, 18, 706–715, <https://doi.org/10.1007/s11629-020-6157-1>, 2021.
- Gregersen, I. B., Sørup, H. J. D., Madsen, H., Rosbjerg, D., Mikkelsen, P. S., and Arnbjerg-Nielsen, K.: Assessing future climatic changes of rainfall extremes at small spatio-temporal scales, *Climatic change*, 118, 783–797, 2013.
- Haile, A., Rientjes, T., Habib, E., Jetten, V., and Gebremichael, M.: Rain event properties at the source of the Blue Nile River, *Hydrology and Earth System Sciences*, 15, 1023–1034, 2011.
- He, S., Wang, Z., Wang, D., Liao, W., Wu, X., and Lai, C.: Spatiotemporal variability of event-based rainstorm: The perspective of rainfall pattern and concentration, *International Journal of Climatology*, 42, 6258–6276, 2022.
- He, Z., Huang, Y., Li, Y., and Li, X.: Probabilistic fragility assessment of slopes considering uncertainty associated with temporal patterns of rainfall intensity, *Computers and Geotechnics*, 173, 106–107, 2024.
- Hettiarachchi, S., Wasko, C., and Sharma, A.: Increase in flood risk resulting from climate change in a developed urban watershed—the role of storm temporal patterns, *Hydrology and Earth System Sciences*, 22, 2041–2056, 2018.
- Horner, W. and Jens, S.: Surface runoff determination from rainfall without using coefficients, *Transactions of the American Society of Civil Engineers*, 107, 1039–1075, 1942.
- Hu, S., Feng, F., Liu, W., and She, D.: Changes in temporal inequality and persistence of precipitation over China during the period 1961–2013, *Hydrology Research*, 49, 1283–1291, 2018.
- Huff, F. A.: Time distribution of rainfall in heavy storms, *Water resources research*, 3, 1007–1019, 1967.
- Jain, A. K., Murty, M. N., and Flynn, P. J.: Data clustering: a review, *ACM computing surveys (CSUR)*, 31, 264–323, 1999.
- Jeon, D. J., Ki, S. J., Baek, S.-S., Cha, Y., Cho, K. H., Yoon, K.-S., Shin, H. S., and Kim, J. H.: Assessing the efficiency of aggregate low impact development (LID) at a small urbanized sub-catchment under different storm scenarios, *Desalination and Water Treatment*, 86, 1–8, 2017.

- 775 Jun, C., Qin, X., Chen, M., and Seo, H.: Investigating event-based temporal patterns of design rainfall in a tropical region, *Hydrological Sciences Journal*, 66, 1986–1996, 2021.
- Kao, S.-C. and Govindaraju, R. S.: Trivariate statistical analysis of extreme rainfall events via the Plackett family of copulas, *Water Resources Research*, 44, 2008.
- Keifer, C. J. and Chu, H. H.: Synthetic storm pattern for drainage design, *Journal of the hydraulics division*, 83, 1332–1, 1957.
- 780 Kendall, M. G.: A new measure of rank correlation, *Biometrika*, 30, 81–93, 1938.
- Klamkowski, K., Treder, W., and Tryngiel-GaĆ, A.: The effect of rainfall intensity and floor management practices on changes in soil water status in an apple orchard, pp. 539–544, 2012.
- Knighton, J. O. and Walter, M. T.: Critical rainfall statistics for predicting watershed flood responses: rethinking the design storm concept, *Hydrological processes*, 30, 3788–3803, 2016.
- 785 Kottegoda, N. and Kassim, A.: Classification of storm profiles using crossing properties, *Journal of Hydrology*, 127, 37–53, 1991.
- Koutsoyiannis, D. and Foufoula-Georgiou, E.: A scaling model of a storm hyetograph, *Water Resources Research*, 29, 2345–2361, 1993.
- Krvavica, N. and RubiniĆ, J.: Evaluation of design storms and critical rainfall durations for flood prediction in partially urbanized catchments, *Water*, 12, 2044, 2020.
- Lenderink, G. and Van Meijgaard, E.: Unexpected rise in extreme precipitation caused by a shift in rain type?, *Nature Geoscience*, 2, 373–373, 790 2009.
- Li, R., Guilloteau, C., Kirstetter, P.-E., and Foufoula-Georgiou, E.: How well does the IMERG satellite precipitation product capture the timing of precipitation events?, *Journal of Hydrology*, 620, 129 563, 2023.
- Li, T., Lee, G., and Kim, G.: Case study of urban flood inundation—impact of temporal variability in rainfall events, *Water*, 13, 3438, 2021.
- Liang, Y., Gao, G., Liu, J., Dunkerley, D., and Fu, B.: Runoff and soil loss responses of restoration vegetation under natural rainfall patterns 795 in the Loess Plateau of China: The role of rainfall intensity fluctuation, *Catena*, 225, 107 013, 2023.
- Liu, J., Liang, Y., Gao, G., Dunkerley, D., and Fu, B.: Quantifying the effects of rainfall intensity fluctuation on runoff and soil loss: From indicators to models, *Journal of Hydrology*, 607, 127 494, 2022.
- Long, K., Wang, D., Wang, G., Zhu, J., Wang, S., and Xie, S.: Higher temperature enhances spatiotemporal concentration of rainfall, *Journal of Hydrometeorology*, 22, 3159–3169, 2021.
- 800 Loveridge, M., Babister, M., and Retallick, M.: Australian Rainfall and Runoff Revision Project 3: Temporal Patterns of Rainfall, Engineers Australia, Barton, 2015.
- Lu, W. and Qin, X.: Integrated framework for assessing climate change impact on extreme rainfall and the urban drainage system, *Hydrology Research*, 51, 77–89, 2020.
- Makridakis, S. and Hibon, M.: Evaluating accuracy (or error) measures, 1995.
- 805 Medina-Cobo, M., García-Marín, A., Estévez, J., and Ayuso-Muñoz, J.: The identification of an appropriate Minimum Inter-event Time (MIT) based on multifractal characterization of rainfall data series, *Hydrological Processes*, 30, 3507–3517, 2016.
- Meier, C. I., Moraga, J. S., Pranzini, G., and Molnar, P.: Describing the interannual variability of precipitation with the derived distribution approach: effects of record length and resolution, *Hydrology and Earth System Sciences*, 20, 4177–4190, 2016.
- Moher, D., Liberati, A., Tetzlaff, J., Altman, D. G., Group, P., et al.: Preferred reporting items for systematic reviews and meta-analyses: the 810 PRISMA statement, *International journal of surgery*, 8, 336–341, 2010.
- Molina-Sanchis, I., Lázaro, R., Arnau-Rosalén, E., and Calvo-Cases, A.: Rainfall timing and runoff: The influence of the criterion for rain event separation, *Journal of Hydrology and Hydromechanics*, 64, 226, 2016.

- Müller, T., Schütze, M., and Bárdossy, A.: Temporal asymmetry in precipitation time series and its influence on flow simulations in combined sewer systems, *Advances in Water Resources*, 107, 56–64, 2017.
- 815 Nel, W.: Intra-storm attributes of extreme storm events in the Drakensberg, South Africa, *Physical Geography*, 28, 158–169, 2007.
- Nguyen, D. T. and Chen, S.-T.: Generating continuous rainfall time series with high temporal resolution by using a stochastic rainfall generator with a copula and modified huff rainfall curves, *Water*, 14, 2123, 2022.
- Oh, B., Kim, J., and Hwang, S.: Influence of Rainfall Patterns on Rainfall–Runoff Processes: Indices for the Quantification of Temporal Distribution of Rainfall., *Water* (20734441), 16, 2024.
- 820 Oriani, F., Mehrotra, R., Mariethoz, G., Straubhaar, J., Sharma, A., and Renard, P.: Simulating rainfall time-series: how to account for statistical variability at multiple scales?, *Stochastic Environmental Research and Risk Assessment*, 32, 321–340, 2018.
- Pampaloni, M., Sordo-Ward, A., Bianucci, P., Gabriel-Martin, I., Caporali, E., and Garrote, L.: A stochastic procedure for temporal disaggregation of daily rainfall data in SuDS design, *Water*, 13, 403, 2021.
- Pan, C., Wang, X., Liu, L., Huang, H., and Wang, D.: Improvement to the huff curve for design storms and urban flooding simulations in Guangzhou, China, *Water*, 9, 411, 2017.
- 825 Pandey, R. S., Carrassi, A., Porcù, F., and Adirosi, E.: High resolution analysis of rainfall intermittency at mid-latitude using disdrometer decade-long data, Available at SSRN 5489686, 2025.
- Parsons, A. and Stone, P.: Effects of intra-storm variations in rainfall intensity on interrill runoff and erosion, *Catena*, 67, 68–78, 2006.
- Pathiraja, S., Westra, S., and Sharma, A.: Why continuous simulation? The role of antecedent moisture in design flood estimation, *Water Resources Research*, 48, 2012.
- 830 Pinheiro, A. G., Souza, T. E. d. S., Montenegro, S. M., Montenegro, A. A. d. A., and Guerra, S.: Rainfall pattern and erosion potential in the physiographic regions of the state of Pernambuco, Brazil, *Revista Brasileira de Engenharia Agrícola e Ambiental*, 22, 849–853, 2018.
- Pohle, I., Niebisch, M., Müller, H., Schümberg, S., Zha, T., Maurer, T., and Hinz, C.: Coupling Poisson rectangular pulse and multiplicative microcanonical random cascade models to generate sub-daily precipitation timeseries, *Journal of Hydrology*, 562, 50–70, 2018.
- 835 Restrepo-Posada, P. J. and Eagleson, P. S.: Identification of independent rainstorms, *Journal of Hydrology*, 55, 303–319, 1982.
- Rivera, D., Arumí, J. L., and Lillo-Saavedredra, M.: Spatio-Temporal Patterns in Soil Water Content Time Series: Influence of the Time Series Length and Precipitation Events, p. 1, 2012.
- Römkens, M. J., Helming, K., and Prasad, S.: Soil erosion under different rainfall intensities, surface roughness, and soil water regimes, *Catena*, 46, 103–123, 2002.
- 840 Rousseeuw, Peter, J.: A graphical aid to the interpretation and validation of cluster analysis, *Journal of Computational and Applied Mathematics*, 20, 53–65, 1987.
- Schiff, L.: Classes and pattern of rainfall with reference to surface-runoff, *Eos, Transactions American Geophysical Union*, 24, 438–452, 1943.
- Schilling, W.: Rainfall data for urban hydrology: what do we need?, *Atmospheric Research*, 27, 5–21, 1991.
- 845 Schleiss, M.: How intermittency affects the rate at which rainfall extremes respond to changes in temperature, *Earth System Dynamics*, 9, 955–968, 2018.
- Schleiss, M. and Smith, J. A.: Two simple metrics for quantifying rainfall intermittency: The burstiness and memory of interamount times, *Journal of Hydrometeorology*, 17, 421–436, 2016.
- Serna, J. R. V. and Taípe, C. L. R.: Determination of storm profiles in the Central Andes of Peru, in: E-proceedings of the 38th IAHR World Congress, 2019.
- 850

- Smith, A. A. and Lee, K.-B.: The rational method revisited, *Canadian Journal of Civil Engineering*, 11, 854–862, 1984.
- Terranova, O. and Iaquina, P.: Temporal properties of rainfall events in Calabria (southern Italy), *Natural hazards and earth system sciences*, 11, 751–757, 2011.
- Thomassen, E. D., Arnbjerg-Nielsen, K., Sørup, H. J. D., Langen, P. L., Olsson, J., Pedersen, R. A., and Christensen, O. B.: Spatial and temporal characteristics of extreme rainfall: Added benefits with sub-kilometre-resolution climate model simulations?, *Quarterly Journal of the Royal Meteorological Society*, 149, 1913–1931, 2023.
- Tian, J., Liu, J., Yan, D., Li, C., and Yu, F.: Numerical rainfall simulation with different spatial and temporal evenness by using a WRF multiphysics ensemble, *Natural Hazards and Earth System Sciences*, 17, 563–579, 2017.
- Todisco, F.: The internal structure of erosive and non-erosive storm events for interpretation of erosive processes and rainfall simulation, *Journal of Hydrology*, 519, 3651–3663, 2014.
- Trenberth, K. E., Dai, A., Rasmussen, R. M., and Parsons, D. B.: The changing character of precipitation, *Bulletin of the American Meteorological Society*, 84, 1205–1218, 2003.
- Tsubo, M., Walker, S., and Hensley, M.: Quantifying risk for water harvesting under semi-arid conditions: Part I. Rainfall intensity generation, *Agricultural Water Management*, 76, 77–93, 2005.
- Urgilés, G., Céleri, R., Bendix, J., and Orellana-Alvear, J.: Identification of spatio-temporal patterns in extreme rainfall events in the Tropical Andes: A clustering analysis approach, *Meteorological Applications*, 31, e70005, 2024.
- Vantas, K., Sidiropoulos, E., and Vafeiadis, M.: Optimal temporal distribution curves for the classification of heavy precipitation using hierarchical clustering on principal components., 2019.
- Varga, C., Ball, J. E., and Babister, M.: A hydroinformatic approach to development of design temporal patterns of rainfall, *IAHS-AISH Publication*, 2009.
- Villalobos Herrera, R., Blenkinsop, S., Guerreiro, S. B., Dale, M., Faulkner, D., and Fowler, H. J.: Towards new design rainfall profiles for the United Kingdom, *Journal of Flood Risk Management*, p. e12958, 2023.
- Visser, J. B., Wasko, C., Sharma, A., and Nathan, R.: Changing storm temporal patterns with increasing temperatures across Australia, *Journal of Climate*, 36, 6247–6259, 2023.
- Wang, F.: Temporal pattern analysis of local rainstorm events in China during the flood season based on time series clustering, *Water*, 12, 725, 2020.
- Wang, G., Sun, W., Xue, B., Kiem, A., et al.: Stratification response of soil water content during rainfall events under different rainfall patterns., *Hydrological processes*, 32, 2018.
- Wang, H., Chen, R., Leung, A. K., and Garg, A.: Hydrological responses to early-peak rainfall in unsaturated rooted soils, *Heliyon*, 9, 2023.
- Wang, W., Yin, S., Xie, Y., Liu, B., and Liu, Y.: Effects of four storm patterns on soil loss from five soils under natural rainfall, *Catena*, 141, 56–65, 2016.
- Wang, W., Yin, S., Xie, Y., and Nearing, M. A.: Minimum inter-event times for rainfall in the eastern monsoon region of China, *Transactions of the ASABE*, 62, 9–18, 2019.
- Wartalska, K. and Kotowski, A.: Model hyetographs of short-term rainfall for Wrocław in the perspective of 2050, *Atmosphere*, 11, 663, 2020.
- Wartalska, K., Kaźmierczak, B., Nowakowska, M., and Kotowski, A.: Analysis of hyetographs for drainage system modeling, *Water*, 12, 149, 2020.

- Wasko, C. and Sharma, A.: Steeper temporal distribution of rain intensity at higher temperatures within Australian storms, *Nature Geoscience*, 8, 527–529, 2015.
- 890 Watt, E. and Marsalek, J.: Critical review of the evolution of the design storm event concept, *Canadian Journal of Civil Engineering*, 40, 105–113, 2013.
- Williams-Sether, T.: Empirical, dimensionless, cumulative-rainfall hyetographs developed from 1959-86 storm data for selected small watersheds in Texas, 2004, US Geological Survey, 2004.
- Wu, S.-J., Yang, J.-C., and Tung, Y.-K.: Identification and stochastic generation of representative rainfall temporal patterns in Hong Kong territory, *Stochastic environmental research and risk assessment*, 20, 171–183, 2006.
- 895 Yang, J., Duan, K., Wu, J., Qin, X., Shi, P., Liu, H., Xie, X., Zhang, X., and Sun, J.: Effect of data assimilation using WRF-3DVAR for heavy rain prediction on the northeastern edge of the Tibetan Plateau, *Advances in Meteorology*, 2015, 294 589, 2015.
- Yang, J., Xiang, Y., Xu, X., and Sun, J.: Design hyetograph for short-duration rainstorm in Jiangsu, *Atmosphere*, 13, 899, 2022.
- Yang, P., Xu, Z., Yan, X., and Wang, X.: Establishing a rainfall dual-threshold for flash flood early warning considering rainfall patterns in mountainous catchment, China, *Natural Hazards*, 120, 6657–6684, 2024.
- 900 Yeo, I.-K. and Johnson, R. A.: A new family of power transformations to improve normality or symmetry, *Biometrika*, 87, 954–959, 2000.
- Yin, S.-q., Xie, Y., Nearing, M. A., Guo, W.-l., and Zhu, Z.-y.: Intra-storm temporal patterns of rainfall in China using Huff curves, *Transactions of the ASABE*, 59, 1619–1632, 2016.
- Zhang, X., Norton, L., and Hickman, M.: Rain pattern and soil moisture content effects on atrazine and metolachlor losses in runoff, Tech. rep., Wiley Online Library, 1997.
- 905 Zhang, Y., Liang, K., and Liu, C.: Time distribution pattern and spatial heterogeneity of hourly scale event-based extreme precipitation in China, *Journal of Hydrology*, 622, 129 712, 2023.
- Zhao, B., Marin, R. J., Luo, W., Yu, Z., and Yuan, L.: Rainfall thresholds for shallow landslides considering rainfall temporal patterns, *Bulletin of Engineering Geology and the Environment*, 84, 1–13, 2025.