



Next-generation Ionospheric Model for Operations - Validation and Demonstration for Space Weather and Research

Angeline G. Burrell¹, Sarah McDonald¹, Dustin Hickey¹, Meghan Burleigh¹, Eliana Nossa², Chris Metzler¹, Manbharat Dhadly¹, Jennifer L. Tate³, and Ellen J. Wagner¹

¹U.S. Naval Research Laboratory, Geospace Science and Technology Branch, Space Science Division, 4555 Overlook Ave. SW, Washington DC, USA

²The Aerospace Corporation, El Segundo CA, USA

³Computational Physics, Inc., Springfield VA, USA

Correspondence: Angeline G. Burrell
(angeline.g.burrell.civ@us.navy.mil)

Abstract. The Next-generation Ionospheric Model for Operations (NIMO) is an assimilative geospace model developed to address the space weather operational needs in the ionosphere. NIMO harnesses contributions from both near real-time data and state-of-the-art implementation of ionospheric theory to provide hindcasts, nowcasts, and forecasts for operational or research purposes. NIMO is currently configured to assimilate various types of electron density measurements through the Ionospheric Data Assimilation Four-Dimensional (IDA-4D) data assimilation schema. Information from the neutral atmosphere is provided by empirical models. The ionospheric chemistry and transport calculations are handled within NIMO using a version of SAMI3 is also a Model of the Ionosphere (SAMI3) designed to have a realistic geomagnetic field and work effectively on a parallel processing system. This article discusses how NIMO is configured, demonstrates potential use cases for the research community, and validates hindcast runs using a new suite of metrics designed to allow repeatable, quantitative, model-independent evaluations against publicly available observations that may be adopted by any ionospheric global circulation or regional space weather model.

1 Introduction

The Earth's ionosphere is the region of the atmosphere in which solar Extreme Ultraviolet (EUV) and X-ray radiation ionizes atoms and molecules, creating a plasma of electrons and ions that extends upwards from roughly 80 km until it merges with the inner magnetosphere. The ionosphere consists of three main altitude regions that form distinct density peaks; the D region lies primarily in the mesosphere (60 km – 90 km) and is the only region that includes negatively charged ions, the E region extends from 90 km to about 130 km, and the F region is the uppermost region that reaches to the inner magnetosphere and plasmasphere. The F region is characterized by the largest concentrations of electrons and ions, with a peak at roughly 250 km to 350 km in altitude that varies with solar cycle conditions, latitude, and day-to-day conditions. In the absence of solar irradiance, the D and E regions largely disappear, while the F region persists due to the influence of plasma transport processes (e.g., Schunk and Nagy, 2009, and references therein).



The ionosphere is of paramount importance for medium- and long-range High Frequency (HF) direct and Over-the-Horizon Radar (OTHR) communication. Such systems are able to propagate signals over very long distances by reflecting HF radio waves off of the bottomside ionosphere ($\sim 100\text{--}350$ km altitude). Knowledge of the ionosphere is also important for space-based assets that must communicate through this region. Historically, simple maps of the ionosphere or empirical models, such as the International Reference Ionosphere (IRI-2016) have been employed in operational environments. However, there is a desire to provide higher fidelity nowcasts and forecasts of ionospheric electron density that can capture the day-to-day variations of ionospheric weather and capture meso-scale features (e.g., Eccles, 2004). The Next-generation Ionospheric Model for Operations (NIMO) has been developed to address these challenges by providing real time global electron density specifications.

This article provides an overview of NIMO version 1.0 (v1.0), a demonstration of its capabilities, and a validation of its output when run in its hindcast mode. Section 2 provides an overview of the NIMO architecture and outputs, while Section 3 discusses the model configuration. This is followed up by a validation in Section 4, which evaluates the performance of this new model against the current community standard (IRI-2016) when compared to observational data. Finally, Section 5 summarizes the key aspects of NIMO and the findings of the validation.

2 NIMO Architecture

As shown in Figure 1, NIMO ingests ionospheric data sets and outputs specifications and forecasts of three-dimensional (3D) electron density profiles. Figure 2 shows an example of the NIMO specification as a function of geographic latitude and altitude at a given geographic longitude. Enhancements in the electron density at $\sim 15\text{--}20^\circ$ North and South of the magnetic equator, known as the Equatorial Ionization Anomaly (EIA), are a typical feature of the ionosphere; electron density in the mid-latitudes is generally lower. The global map of the peak electron density in the F region ($N_m F_2$) is shown in Figure 3 at 15:00 Universal Time (UT); here, the EIA is strongest during the daytime, and persists into the evening hours.

The design of NIMO is similar to that of numerical weather forecast systems in that it consists of a forecast model and Data Assimilation (DA) system that runs in real time to generate both analysis states and weather forecasts at a regular cadence. The NIMO forecasts, as well as the background ionospheric state for the DA system, are generated by SAMI3 (SAMI3 is also a Model of the Ionosphere), which is a physics-based model of the ionosphere developed at the Naval Research Laboratory (NRL) (Huba et al., 2000, 2008, 2019). The DA is performed by the Ionospheric Data Assimilation Four-Dimensional (IDA-4D) system. IDA-4D uses a mathematical formulation that closely follows the meteorological 3D Variational Assimilation (3DVar) methodology and is described in detail in Bust et al. (2004, 2007).

NIMO includes a data pre-processor that reads in the various data sets, performs checks to verify the data is usable, and generates a file with all the data that will be assimilated within a given time step. The code was designed to be easily extensible to new data sources as they become available in the future. NIMO ingests a number of different data observations of local and integrated electron density. Supported real-time data sets are listed in Table 1. In more recent versions of NIMO (1.2 and greater), the ability to ingest ultraviolet (UV) radiance from instruments such as DMSP SSUSI has been successfully added.




Figure 1. NIMO consists of a data assimilation system, IDA-4D, and a physics-based ionosphere model, SAMI3. NIMO ingests a number of different data sets that can be represented as an electron density. The output is a 3D representation of the ionospheric electron density over the entire globe.

Table 1. Data types that can be ingested into NIMO version 1.0.

Data Type	Description
Global Positioning System (GPS)	Slant TEC from global networks of GPS ground receivers (e.g., Madrigal GPS data sets)
Total Electron Content (TEC)	TEC satellite remote sensing of long slant path TEC
Global Navigation Satellite System (GNSS)	(e.g., COSMIC-2)
Radio Occultation (RO)	Electron densities measured at satellite locations
In situ electron density	Ionosonde frequency sweeps that have been converted into vertical electron density profiles
Ionosonde profiles	




Figure 2. NIMO specification of electron density as a function of latitude and altitude at a longitude of 90°E at 15:00 UT for 19 Jan 2014.

Because IDA-4D is a 3DVar system, all the data collected within a single iteration is assimilated at the same time. Due to the highly variable nature of the ionosphere, we have set this iteration step to be 15 min. Thus, every 15 min NIMO collects the available operational data sets for the current time period, ingests them into the data pre-processor, and performs the assimilation with IDA-4D using the SAMI3 background state from the previous time step. SAMI3 then runs forward 15 min to generate the background state for the next iteration. NIMO may be run in hindcast or real time mode, depending on the needs of the user. However, for the purposes of this study, only the hindcast mode is used.

3 Model Configuration

This section provides a summary of the model configuration and data sets used to perform the validation runs.




Figure 3. NIMO specification of global peak electron density in the F region at 15:00 UT for 19 Jan 2014.

3.1 SAMI3 and IDA-4D Configuration

For global runs, such as presented here, SAMI3 is configured to run with a low-resolution grid that has 160 points along each magnetic field line, 160 field lines at each magnetic longitude, and 90 magnetic longitude slices. This grid yields a 4° resolution in longitude and 1° resolution in latitude and extends from 70 km to greater than 20,000 km in altitude. The auroral model and high-latitude convection model are not used in these runs, as further testing is required for their integration. The NIMO thermosphere is specified by the Horizontal Wind Model (HWM14; Drob et al. (2015)) and the NRL Mass Spectrometer Incoherent Scatter (NRLMSIS-2.0, Emmert et al. (2021)). Solar and geomagnetic inputs are provided by the $F_{10.7}$, three-hour A_P , and the 81-day average of the $F_{10.7}$ ($F_{10.7a}$).

Within the NIMO validation runs, IDA-4D was configured with a global equal area grid with 300 km grid spacing in latitude and longitude, and altitudes ranging from 100 km to 1500 km. The Jan 2021 global run was performed with two different IDA-4D grids. These grids differed in the range of their topside altitudes, in operations the IDA-4D grid extended up to 10,000 km. Although not used in the standard validation runs, the newer IDA-4D grid led to a small improvement in the ionospheric specification.



75 3.2 Ingested Data Sets

Data sets ingested for the validation runs include GPS vertical TEC, Electron Density Profiles (EDPs) from ionosondes (McNamara, 2005), and space-based RO data. The RO data is obtained from the COSMIC and COSMIC-2 constellations, which is publicly available at the University of Colorado. NIMO processes the podTEC files. NIMO is also capable of ingesting commercial RO data (such as data sets provided by Spire and GeoOptics).

80 The data included in each of the different validation runs are shown in Table 2. The combination of ground- and space-based observations leads to reasonable global coverage, though there is less data to ingest at high latitudes and over the oceans.

Table 2. Data ingested for the validation runs tabulated in Table 3.

Run	Ingested Data Sets (✓ = Yes; × = No)			
	GPS	COSMIC	COSMIC-2	Ionosonde
Jan 2014	✓	✓	×	✓
Apr 2014	✓	✓	×	✓
Jul 2014	✓	✓	×	✓
Oct 2014	✓	✓	×	✓
Aug 2018	✓	✓	×	✓
Oct 2019	✓	✓	×	✓
Apr 2020	✓	×	✓	✓
Jan 2021	✓	×	✓	✓
Mar 2015	✓	×	✓	✓

4 Model Validation

The purpose of this validation is to evaluate the accuracy of the electron density against observations in different spatio-temporal regions, ionospheric layers, and under different solar and geomagnetic conditions for the global NIMO runs. A variety of different validation periods, shown in Table 3, were chosen to ensure representative seasonal and solar cycle coverage under quiet geomagnetic conditions. An additional run that includes a significant geomagnetic storm is also considered to allow evaluation during disturbed geomagnetic times, bringing the total of runs up to nine.

The validation process involves establishing meaningful comparison metrics from different observational or empirical data sets and evaluating the new model's performance against the International Reference Ionosphere (IRI-2016), a climatological model primarily based on ionosonde measurements (Bilitza, 2018). The IRI-2016 was run using a compiled executable with the default flags as of Sep 2021, which uses the Altadill et al. (2013) $h_m F_2$ model (AMTB-2013). It should be noted that since this time the default $h_m F_2$ model has been changed to the model created by Shubin (2015) (SHU-2015), which provides very different results. These differences are discussed in more detail in the $h_m F_2$ validation sections.



Table 3. Validation periods.

Start Time	Stop Time	F _{10.7} Range	Max. Kp	Interest
1 Jan 2021	31 Jan 2021	73 – 82	5-	Quiet
1 Apr 2020	30 Apr 2020	68 – 71	5-	⋮
1 Oct 2019	31 Oct 2019	64 – 71	5+	⋮
1 Aug 2018	31 Aug 2018	67 – 72	7+	⋮
15 Mar 2015	19 Mar 2015	109 – 117	8-	Storm
1 Oct 2014	31 Oct 2014	111 – 227	5	Active
1 Jul 2014	31 Jul 2014	86 – 201	3+	⋮
1 Apr 2014	31 Apr 2014	118 – 184	5	⋮
1 Jan 2014	31 Jan 2014	121 – 237	4+	⋮

IRI-2016 was run at a one hour temporal cadence with a $5^{\circ}\text{N} \times 4^{\circ}\text{E} \times 10 \text{ km}$ latitude $\times$ longitude $\times$ altitude grid. The altitude range was chosen to allow the Joint Altimetry Satellite Oceanography Network (JASON) TEC to be compared against modeled TEC calculated up to the altitude of 1300 km, similar to the nominal orbital altitude. Some of the validation methods interpolate between these times, while others simply calculate statistics at a lower cadence. The interpolation method showed little difference in results between a one hour resolution and a 15 min resolution, as IRI-2016 varies smoothly. The matching method was found to work well as long as enough paired data points were available to calculate the desired statistics.

Seven different observational data sets and one empirical model were used to calculate validations metrics for this study. Each data set has its own intricacies, which are discussed in Section 4.1. Finally, the different metrics used in this validation study are presented in Section 4.2.

4.1 Data Sources

This section provides an overview of the ground- and space-based observational data sets used to validate the electron density provided by NIMO.

4.1.1 Ionosondes

Ionosondes measure the time delay of vertically propagated Medium Frequency (MF) and HF radio waves, which reflect off of the bottomside of the ionosphere. The transmitter sweeps through a range of frequencies (generally from about 1-30 MHz) to obtain information about the electron density at multiple altitudes. To analyze ionosonde data, the frequency-altitude output must be scaled from delay as a function of frequency to electron density as a function of altitude. This can be done using an auto-scaler program or performed manually by an experienced analyst. The data for these validation studies was collected from the Lowell GIRO Data Center (LGDC), which collects data from ionosondes around the world. The majority of the data in this



study has been scaled using versions 4 or 5 of an autoscaler called Automatic Real-Time Ionogram Scaler with True height (ARTIST), although some of the outputs from LGDC indicate that the scaling method used is unknown (Galkin and Reinisch, 115 2008). The ARTIST outputs do not include errors in the measurements but they do include a confidence score that can be used to determine if the profile is usable.

Using hand-scaled ionograms is generally considered preferable to using autoscaled ionograms, since the results have been verified by a knowledgeable data processor. However, it can be very time consuming and the results are less repeatable. Themens et al. (2022) discusses the challenges and best practices for using ARTIST autoscaled parameters. They describe how to use 120 the autoscale scores and conclude that it varies depending on parameter and is not as simple as using a cutoff value. In Galkin et al. (2008) they discuss the f_oF_2 error for three sites by comparing the f_oF_2 to hand scaled ionosondes. They found that 95% of automatically determined f_oF_2 from ARTIST 5 fell within -0.3 to 0.4 MHz of the hand scaled profiles. The hand scaled profiles also have errors associated with them as discussed in Dandenault et al. (2020). They found differences in parameters due to different people doing the hand scaling and found that even the same person may not get the same result if they redo the 125 same ionogram scaling. In that study they found a standard deviation in f_oF_2 of 0.62 MHz. The error in f_oF_2 primarily comes from correctly determining the peak frequency but h_mF_2 has an added complication that the conversion from virtual height on the ionogram, to the actual height depends on the profile below it. This adds another source of error in both the autoscaled and hand scaled outputs. Due to these drawbacks, only auto-scaled ionosondes were used in this study. This means that it is likely that poorly-behaved ionosondes were included in the data ingestion and validation, despite efforts to ensure a clean data set.




Figure 4. Map of ionosonde locations used for validation.



130 Ionosondes are relatively inexpensive instruments to install and operate, making them a popular source for ionospheric
measurements across the globe. Figure 4 shows the locations of the sites used in this study. When specific ionosonde sites
are used for validation, they are identified by station name and location. Another complication for this validation effort is that
some of these ionosondes are also used in NIMO's data assimilation. Although the ingestion process does remove some of the
provided data to prevent the dominance of one data set on the assimilation, this information is not available post-processing.
135 Due to this complication, instances where ionosonde data is or is not assimilated are addressed on a case-by-case basis and the
regional statistics do not make a distinction between these two possible states.

4.1.2 Incoherent Scatter Radars

An Incoherent Scatter Radar (ISR) probes the ionosphere by sending powerful signals and measuring the weak backscatter of
the random motion of the ionospheric ions and electrons (Dougherty and Farley, 1960). The ISR provides the most accurate
140 measurement of ionospheric electrons (plasma) as a function of altitude for a single latitude and longitude. The ISR systems
need to be large and powerful (Farley, 2009), since the electron radar scattering cross-section is roughly $10^{-28} m^2$ and the
plasma clouds are more than 100 km away. There are only six ISR systems in the American sector, located in Alaska, Nunavut
(Canada), Massachusetts, Puerto Rico, and Peru. This study uses the available ISR data, which comes from the Millstone Hill
(MH), Arecibo Observatory (AO), and Jicamarca Radio Observatory (JRO) ISRs.

145 The MH ISR is part of the Haystack Observatory in Massachusetts. MH is a mid-latitude radar located at (42.6°N, 71.5°W).
This ISR transmits 2.5 MW of power using a 46 m steerable dish or a 68 m fixed zenith antenna. The data presented in this
document were acquired with the fixed zenith antenna and using alternating uncoded transmitting pulses, providing a changing
height resolution from 4.5 km at the E region to less than 60 km at an altitude of 400 km. The electron density profiles used in
this study were obtained from the MH data by calibrating the ion line amplitude (or ISR backscatter power).

150 The AO is located in Puerto Rico at (18.3°N, 66.7°W), and is considered a low-latitude site. It had the largest single dish ISR
until 2019, when it ceased operations. The ISR instrument consisted of two 430 MHz radar antennas that could be used together
or independently, in addition to other antennas that transmitted different frequencies used for radio astronomy, planetary, and
HF studies. The Arecibo ISR had the higher sensitivity among the ISRs, with range resolution of 150 m, time resolution of
the order of ms, and frequency resolution of 0.7 kHz. The data in this study uses the calibrated ion line to validate the NIMO
155 simulations.

The JRO is located in Peru at (11.9°S, 76.9°W), under the magnetic equator, with a magnetic dip angle around 1°. The JRO
ISR is an array of 18,432 crossed-dipole 50 MHz antennas, covering an area of 85,000 m², that transmits up to 4.5 MW of
power. The JRO ISR dual-polarization makes it possible to measure the Faraday rotation of the incoherent backscatter waves,
which allows an absolute estimate of electron density independent of any other instrumentation (Farley, 1969). The range
160 resolution of the data is set by the radar transmitted codes (Hysell, 2018). JRO uses alternate uncoded pulses that minimize the
clutter at F region heights and provide a height resolution of 15 km.



4.1.3 GPS TEC

TEC is measured by satellite-based transmitters paired with either ground- or space-based receivers that measure the time delay between signals at two different frequencies. The TEC provides a column integrated density measurement rather than vertically resolved electron density profiles, but the high accuracy and vast coverage of this data set make it, arguably, the most complete ionospheric specification data set currently available.

The TEC measured by distributed ground- and space-based receivers and transmitters onboard the GPS satellite constellation provide line-of-sight, or slant TEC (STEC), measurements of the density along the path between the transmitter and receiver. This path typically covers a range of latitude and longitudes, and so is frequently converted to vertical TEC (which projects the STEC vertically using assumptions about the ionospheric structure). The MIT Haystack Madrigal data base provides two TEC data products: the STEC and unbinned vertical TEC as well as vertical TEC binned at a resolution of 5 min, 1° latitude and 1° longitude (Rideout and Coster, 2006). The sources of uncertainties and biases in the TEC processing are reported in Rideout and Coster (2006), and the gridded vertical TEC files report data errors for each gridded value. These errors are typically on the order of a tenth of a TEC Unit (TECU) (where 1 TECU = 10^{16} electrons m^{-2}) over the validation region. Figure 5 shows the typical coverage of the vertical TEC data with the area used for validation marked by a green box.




Figure 5. Madrigal binned TEC coverage for 1 Apr 2014 where N_{TEC} is the number of observations at each location over the selected day. The green square marks the validation region.

As was the case with the ionosonde data, TEC was also ingested into the NIMO data assimilation. However, in this instance the assimilated STEC was obtained from an alternate source and used a different receiver bias calibration.



4.1.4 JASON TEC

The JASON satellites are part of a mission to supply scientific and commercial data about sea level rise, ocean temperatures and circulation, and climate change. The JASON-3 satellite launched in 2016 and is still operational, and so covers many of the validation periods shown in Table 3. The validation periods in 2014 are covered by JASON-2, which was operational between 20 Jun 2008 and 9 Oct 2019. These satellites include dual-frequency altimeters, operating at 13.575 GHz (K_u -band) and 5.3 GHz (C-band), to measure the height of the ocean surface to high accuracy. The JASON satellites fly in an orbit with a 66° inclination and a 10-day repeating reference orbit, advancing approximately 2° per day.

Corrections must be applied to these measurements due to the dispersive nature of the atmosphere that results in path delay of the radar signal. The ionospheric correction, or delay, is directly proportional to the electron content along the ray path and inversely proportional to the frequency (f) squared of the signal. The difference in delay between the altimeters' dual-frequency measurements can be used to calculate the TEC in the nadir (vertical) direction from the spacecraft at 1,340 km altitude to the surface over the oceans (Imel, 1994). TEC is calculated using the following formula:

$$TEC = -dR \times \frac{f^2}{40.3} \quad (1)$$

In Equation 1, TEC is the vertical TEC in the ionosphere measured in TECU, dR is the K_u -band ionospheric range correction in meters provided in the JASON-2 and JASON-3 Geophysical Data Records (GDRs) that are available at, for example, <https://www.ncei.noaa.gov/data/oceans/jason3/gdr/gdr/>. The sampling rate of the JASON-2 and JASON-3 instruments is 1 Hz. However, as recommended by Imel (1994) and the JASON-3 Handbook (Dumont et al., 2017), the ionospheric range correction should be smoothed over 100 km or more to reduce instrument noise. To calculate the JASON-2 and JASON-3 TEC used in this study, we have averaged the measurements over 18 s, which yields approximately $\sim 1^\circ$ bins. The $\frac{\sigma}{\sqrt{N}}$ precision is ~ 1 TECU. Because both JASON-2 and JASON-3 satellites are used in this validation study, we have been careful to take the bias between the instruments into account. During the tandem period (Feb - Oct 2016), JASON-3 was inserted into the same orbit as JASON-2 and trailing by one minute. An evaluation of the TEC measurements during this time period shows that the JASON-2 instrument has a +2.6 TECU bias with respect to the JASON-3 instrument. For this study, we have subtracted 2.6 TECU from the JASON-2 measurements to account for this bias.

While JASON-3 does not provide a dense set of measurements, it does provide a direct TEC measurement over bodies of water. Altimeter data, such as this, has been used extensively to validate TEC models and other measurement techniques (e.g., Burrell et al., 2008; Li et al., 2018).

4.1.5 CINDI

The Coupled Ion-Neutral Dynamics Investigation (CINDI) mission operated onboard the Communication/Navigation Outage Forecasting System (C/NOFS) satellite (de la Beaujardière and C/NOFS Science Definition Team, 2004) between 2 Aug 2008 and 26 Nov 2015. The C/NOFS satellite was launched into a low earth orbit with an inclination of 13° and an orbital period



of about 97 min. Initially, the satellite orbit had a perigee of 400 km and an apogee near 860 km. The mission was placed in safety mode (not providing any data) between 5 Jun 2013 and 22 Oct 2013, before becoming operational again (at this point the C/NOFS satellite had a perigee of 388 km and an apogee of 690 km). This orbit allowed the orbital plane to precess 24 h in local time over a period of 3 months.

Two instruments from the CINDI mission are used in the data validation efforts: the Retarding Potential Analyzer (RPA) and the Ion Drift Meter (IDM) (Heelis and Hanson, 1998). Together known as the Ion Velocity Meter (IVM), these instruments provided the 3D ion velocity, converted into magnetic coordinates using the International Geomagnetic Reference Field (IGRF) (Maus et al., 2005), as well as the ion density, temperature, and composition. The *pysat* data framework (Stoneback et al., 2018, 2021) includes cleaning routines for these instruments, ensuring a high quality of data when performing validations (Stoneback et al., 2011; Burrell, 2012). The orbital characteristics of the C/NOFS satellite allow CINDI observations to validate model runs in the topside, equatorial ionosphere.

4.1.6 DMSP SSIES

The Defense Meteorological Satellite Program (DMSP) Special Sensor for Ions, Electrons, and Scintillation (SSIES), an earlier incarnation of the CINDI IVM, was flown onboard four of the DMSP satellites (F15, F16, F17, and F18) as a part of their mission is to monitor the meteorological, oceanographic, and geospace environment (Hall, 2001). The first DMSP satellite was launched in 1962, and there are currently several satellites operational and in their desired orbits. These orbits are sun-synchronous, polar orbits with altitudes near 830 km. Each satellite crosses the equatorial plane at a different Solar Local Time (SLT), allowing DMSP to validate the topside ionospheric density at a range of latitudes and local times.

4.1.7 ICON IVM

The Ionospheric CONnection Explorer (ICON) IVM suite measured the in situ ionospheric drift (Heelis et al., 2017) using RPAs and IDMs at the front (A) and rear (B) of the spacecraft. For the periods used in this validation study, only IVM-A returned observations. The IVM measures the ion density, temperature, 3D drift, and composition. The ion density, which is the density for all species, may be directly compared to the model's electron density as there are only significant populations of singly-ionized species in the topside ionosphere.

4.2 Validation Metrics

This section describes the metrics that are used to evaluate the model. Here and elsewhere, the subscript *obs* is used to indicate observational data, while the subscript *mod* indicates modeled data. When two different models are being compared, subscripts will use the model names.

4.2.1 Difference Histograms

A standard way of visualizing the agreement between two data sets is to plot a histogram of the differences between the two data sets. If there is no systematic offset between the two data sets and any disagreement is randomly distributed, the histogram will have a classic Gaussian bell shape centered about zero. The offset of the peak, pronouncement of the tails, and symmetry of the distribution at the half-maximum point can all be easily assessed using a difference histogram. Figure 6 shows an example of two difference histograms.




Figure 6. Difference histograms for the two different Gaussian data sets (left) and a Gaussian and Poisson data set (right).

4.2.2 Bias or Mean Error

The Bias (B) or the Mean Error (ME) is a scale-dependent bias, measured by differencing the means of two data sets, as shown in Equation 2. As previously stated, the subscript *mod* refers to model data and the subscript *obs* refers to observational data. *X* acts as a placeholder for the different observations used in the validation efforts, and $\langle X \rangle$ denotes the mean of the enclosed data set. B and ME are the same statistic.

$$B = \langle X_{mod} \rangle - \langle X_{obs} \rangle \quad (2)$$



4.2.3 Root Mean Squared Error

250 The Root Mean Squared Error (RMSE) provides a measure of the magnitude of the difference between two data sets. It is defined as:

$$RMSE = \sqrt{\langle (X_{mod} - X_{obs})^2 \rangle}. \quad (3)$$

4.2.4 Mean Absolute Error

The Mean Absolute Error (MAE) is another way to measure the magnitude of the difference between two data sets. Described
 255 in Equation 4, it is simply the mean of the absolute value of the difference between the modeled and observed data sets.

$$MAE = \langle |X_{mod} - X_{obs}| \rangle \quad (4)$$

4.2.5 Median Absolute Error

The Median Absolute Error (Med. AE) is a more robust measure of the magnitude of the difference between two data sets. It is calculated in the same way the MAE is, but instead of taking the mean of the absolute value of the differences between the
 260 modeled and observational data sets, the median is calculated. This makes the result less susceptible to outliers, but it does not measure the distribution of differences between the data pairs.

4.2.6 Mean Absolute Percentage Error

The Mean Absolute Percentage Error (MAPE) is a way to measure the magnitude of the difference between two data sets. Described in equation 5, it is simply the mean of the absolute value of the difference between the modeled and observed data
 265 sets, expressed as a percentage.

$$MAPE = \left\langle \frac{|X_{mod} - X_{obs}|}{X_{obs}} \right\rangle \times 100\% \quad (5)$$

4.2.7 Pearson Correlation Coefficient

Correlation coefficients are a way to show how strongly two sets of data are related. The Pearson correlation coefficient (r_1) measures the strength of the linear correlation between two sets of data by determining the ratio between the covariance of
 270 two variables and the product of their standard deviation. Positive values indicate a strong association among the two sets, negative values indicate an anti-correlation, and values equal to zero indicate no relationship at all. The correlation of a set of



data with itself gives an r_1 of unity. The Pearson correlation coefficient equation between the modeled and observed data sets is calculated using:

$$r_1 = \frac{\sum_i^N (X_{mod_i} - \langle X_{mod} \rangle)(X_{obs_i} - \langle X_{obs} \rangle)}{\sqrt{\sum_i^N (X_{mod_i} - \langle X_{mod} \rangle)^2 \sum_i^N (X_{obs_i} - \langle X_{obs} \rangle)^2}}. \quad (6)$$

275 In the above equation, N is the number of samples and i is the index of an individual model-observation pairing.

Correlation and anti-correlation can be differentiated together from the absence of any correlation by using the square of the Pearson correlation coefficient (R^2). R^2 is simply the square of r_1 , and is useful for separating data sets that have a relationship from those that have no relationship at all.

4.2.8 Meta Analysis

280 Meta analysis is commonly performed to obtain a clear picture of a large number of statistics. This study uses meta analysis to clarify the comparative model performance of one particular statistic. More specifically, when evaluating the performance of one of the statistics presented above (S), the percentage of validation runs where NIMO outperforms IRI-2016 (P_S) can be determined using:

$$P_S = \frac{\sum_i^N c(i, NIMO, IRI - 2016)}{N} \times 100\%, \quad (7)$$

285 where:

$$c(i, NIMO, IRI - 2016) = \begin{cases} 1, & \text{if } S_{iNIMO} \text{ is better than } S_{iIRI-2016} \\ 0, & \text{otherwise.} \end{cases} \quad (8)$$

In the equations above N is the number of validation runs. The qualifier ‘better than’ is used instead of a numerical description because the numerical condition that indicates a ‘better’ value changes. For example, the RMSE is better when the value is lower, but the B is better when its absolute value is closer to zero.

290 4.3 Validation Results

4.3.1 Ionosondes

While ionosondes provide a wealth of data that can be used to validate several different aspects of the bottomside ionosphere, this study uses only the f_oF_2 and the h_mF_2 . This choice was made to ensure that the most reliable aspects of the auto-scaled ionosonde data were used in the validation process. Focusing on the critical frequency and height of the F_2 peak has the
295 additional advantage of validating the location and strength of a major ionospheric feature.



Figure 7 shows the observed and modeled f_oF_2 for a day at two of the ionosonde sites; the top panel shows data that was included in the data assimilation (Boulder, USA) and the bottom shows data that was not assimilated (Beijing, China). Ionosonde measurements are shown as red dots, the NIMO output is marked by a blue line and triangles and the orange line and squares shows the IRI-2016 output. NIMO shows significantly more variation than IRI-2016, as it is not a climatological model. Additionally, the top panel shows a solar quiet period, while the bottom panel shows a solar active period. This illustrates how NIMO is typically more successful than IRI-2016 at capturing the critical frequency (and therefore density) at the F_2 peak, whether or not data was assimilated at this location.




Figure 7. f_oF_2 for ionosonde station locations at Boulder, USA (top) and Beijing, China (bottom). The ionosonde observations are shown by red dots, while the NIMO results are plotted in blue lines and triangles and the IRI-2016 results are plotted in orange lines and squares.

However, it is more challenging to capture the correct h_mF_2 . Figure 8 shows the same time periods and stations as Figure 7, but for the h_mF_2 . This demonstrates that the IDA-4D data assimilation process is also blindly successful, meaning that the



305 model will attempt to drive the ionospheric state towards incorrect assimilated values and create unrealistic modeled output. This may not impact NIMO's ability to provide realistic column-integrated specifications of the electron density (e.g., VTEC), but is detrimental for its ability to specify the electron density at a particular altitude.




Figure 8. $h_m F_2$ for ionosonde station locations at Boulder, USA (top) and Beijing, China (bottom). The ionosonde observations are shown by red dots, while the NIMO results are plotted in blue lines and triangles and the IRI-2016 results are plotted in orange lines and squares.

The B, RMSE, and MAE (see Sections 4.2.2, 4.2.3, and 4.2.5) are used to compare ionosonde observations with NIMO and IRI-2016 outputs. The global results from all available ionosondes are shown in Tables A1 and A2 and plotted in Figures 9 and 10 for the desired validation periods. These statistics are calculated for all local times, daytime hours (06:00-18:00 SLT), and nighttime hours (18:00-06:00 SLT). Although these local times do contain some overlap of sunlit and non-sunlit locations (as solar zenith angle is not accounted for), they are each dominated by either day- or night-time processes. A subset of these runs was used to evaluate the $f_o F_2$ using only ionosondes not used in the data assimilation process (see Table 4).




Figure 9. Global f_oF_2 B (a), MAE (b), and RMSE (c) in different local time bins for all ionosonde locations.

Table 4. Global, solar active f_oF_2 for all local times from only non-ingested ionosonde locations.

Run	NIMO (MHz)			IRI-2016 (MHz)		
	B	MAE	RMSE	B	MAE	RMSE
Jan 2014	1.40	2.17	2.60	2.06	2.61	3.24
Apr 2014	3.65	3.85	5.14	1.93	2.82	3.70
Jul 2014	1.52	1.92	3.00	1.05	1.75	2.40
Oct 2014	0.702	1.26	1.89	-0.039	1.41	1.91

315 The B shows that both NIMO and IRI-2016 overestimate f_oF_2 , while NIMO is more likely to overestimate the h_mF_2 . In general, IRI-2016 tends to have a lower B than NIMO. Recall that a low bias may indicate a good performance or that a model is equally likely to overestimate as it is to underestimate for the chosen evaluation period. The interpretation that NIMO tends to overestimate the f_oF_2 and h_mF_2 , while IRI-2016 overestimates peaks and underestimates minima for these values is supported by the examples shown in Figures 7 and 8.




Figure 10. Global h_mF_2 B (a), MAE (b), and RMSE (c) in different local time bins for all ionosonde locations.

Examining the other f_oF_2 statistics further supports this interpretation. Calculating P_{MAE} for all validation runs and local
 320 time periods shows that NIMO outperforms IRI-2016 in 85.2% of the cases. Similarly, $P_{RMSE} = 74.1\%$. When considering
 the potential impact of removing the comparison with ionosondes used in the data assimilation, Table 4 shows that both NIMO
 and IRI-2016 have higher biases and errors for these four runs. However, the only time there is a change in relative performance
 between the two models is the Jul 2014 MAE, which is now lower for IRI-2016.

A challenge when using ionosondes for validation is that the errors from the ionosondes are not well defined, as previously
 325 discussed in Section 4.1.1. This impacts both the NIMO output, due to the ingested ionosondes, and the f_oF_2 and h_mF_2
 validation with the ionosondes. Since this NIMO validation uses many ionosonde sites over long periods of time, it is likely
 that poorly-behaved ionosondes are included in the analysis. This will increase the error in an unquantifiable manner, but the
 robustness of the f_oF_2 and h_mF_2 parameters allows one to consider the ionosonde f_oF_2 as significantly more reliable than the
 ionosonde h_mF_2 .



330 As expected due to the challenges with obtaining the $h_m F_2$, the validation against $h_m F_2$ is less consistent. IRI-2016 typically outperforms NIMO, with $P_{MAE} = 44.5\%$ and $P_{RMSE} = 25.9\%$. However, the difference between the MAE and RMSE values are usually less than 1 km, which is not significant.

The run where NIMO most consistently performs better than IRI-2016 is the Mar 2015 storm period. During the geomagnetic storm, NIMO more correctly estimates the increases in $f_o F_2$ and $h_m F_2$ during the daytime and the nighttime. The nighttime
335 differences between NIMO and IRI-2016 are more significant, though. This is unsurprising, as NIMO better equipped to handle the combination of drivers needed to correctly specify an individual geomagnetic storm than a climatological model such as IRI-2016.

4.3.2 Incoherent Scatter Radars

The observations from ISRs located at AO, JRO, and MH were available for five of the desired validation periods: two active
340 solar times, two quiet solar times, and the geomagnetic storm period. Following the lead of the ionosondes, the ISR data used for validation is currently limited to the $h_m F_2$ and $N_m F_2$. The $h_m F_2$ and $N_m F_2$ values for the ISR data are obtained by finding the maximum density and the corresponding altitude for each electron density profile at a given time.

Because NIMO captures both sub-hourly variations in the ionosphere and long-term climatological trends, it is useful to evaluate both the standard NIMO output and the trend of the NIMO output (which removes the short-term variations). The
345 NIMO trend was calculated for the model's $h_m F_2$ and $N_m F_2$ by taking a boxcar average of the standard NIMO outputs using a full window width of 2 h. The trend results were provided at a 15 min resolution, matching the NIMO output cadence. A similar analysis was performed for the ionosonde validations, but the trend statistics were extremely close to the standard model statistics, and so are not included here in the interest of brevity.

The bias and the r_1 coefficient are calculated to determine both the degree and presence of a correlation between the models
350 and the ISR observations. For the NIMO validation runs, the model trends for $h_m F_2$ and $N_m F_2$ are also examined to see whether NIMO captures the main features of the $h_m F_2$ and $N_m F_2$ in a manner comparable to IRI-2016. An example of the ISR data and model outputs is shown in Figure 11, which shows the observations (purple), NIMO results (blue), NIMO trends (green), and IRI-2016 results (yellow).

The results of the ISR $h_m F_2$ and $N_m F_2$ validation are shown in Figures 12 and 13 (and presented in Tables A3 and A4),
355 respectively. The results show that at all locations NIMO performs equally well or better than IRI-2016, when considering the standard model output and the NIMO trend. The NIMO trend usually performs slightly better than the standard NIMO output (except during the storm run), though the differences in the metrics are small. NIMO performs significantly better than IRI-2016 at times of higher ionospheric density (such as geomagnetic storm period), while the differences in the bias and r_1 are smaller during solar quiet times.

360 4.3.3 GPS CONUS TEC

This section examines the GPS VTEC from the Madrigal data base over a validation region within the Contiguous United States (CONUS), shown with the green box in Figure 5. This region was chosen for this validation because it is heavily instrumented.




Figure 11. h_mF_2 (a) and N_mF_2 (b) for the JRO ISR. The ISR observations are shown by purple lines, the NIMO results are plotted in blue, the NIMO trend is plotted in green, and the IRI-2016 results are plotted in yellow. Note how the purple JRO h_mF_2 generally lies in the middle of the NIMO h_mF_2 and shows similar local time variations to the NIMO N_mF_2 , while the IRI-2016 values consistently have local time variations not consistent with the observations.




Figure 12. $h_mF_2 r_1$ (a) and B (b) for the JRO (circles), MH (stars), and AO (triangles) ISRs. The NIMO results are plotted in navy blue, the NIMO trend is plotted in slate blue, and the IRI-2016 results are plotted in light blue.

To facilitate analysis, the Madrigal TEC is linearly interpolated onto the NIMO TEC grid, reducing the resolution to 1° in latitude and 4° in longitude. The Madrigal data time step closest to each NIMO output time is retained for comparisons.




Figure 13. $N_m F_2 r_1$ (a) and B (b) for the JRO (circles), MH (stars), and AO (triangles) ISRs. The NIMO results are plotted in navy blue, the NIMO trend is plotted in slate blue, and the IRI-2016 results are plotted in light blue.

365 The Madrigal TEC is also compared to IRI-2016 TEC outputs. The IRI-2016 TEC is also linearly interpolated onto the NIMO TEC grid increasing the resolution to 1° in latitude and 4° in longitude. The Madrigal data time step closest to each IRI-2016 output time is retained for these comparisons.

The results of the Madrigal vertical TEC validation, presented in Table A5 and Figure 14, show that NIMO typically outperforms IRI-2016, having a $P_B = 66.67\%$ and a $P_{RMSE} = 100\%$. Both NIMO and IRI-2016 agree with the data better during
 370 the solar quiet periods than the solar active or storm periods.

An example of the time evolution of these statistics is included in Figure 15, which shows one of the time periods where the IRI-2016 B outperforms the NIMO B . The top left panel shows the average TEC within CONUS over the duration of the Oct 2014 run for both NIMO and Madrigal TEC. NIMO tracks the daily variation well but overshoots the daily maxima by a little bit during the latter half of the month. The generally good agreement is supported by the resulting small B and RMSE in the
 375 top right panel.

By comparison, IRI-2016 and Madrigal average TEC are shown in the bottom left panel. IRI-2016 typically undershoots the TEC for the first half of the month but significantly overshoots the daily maxima during the second half of the month. This tendency to both overestimate and underestimate the TEC in IRI-2016 is captured by the B trending negative during the first half of the month and then positive during the second half of the month. However, these opposing biases average out when
 380 considering the period as a whole. This causes the small B for the entire run, shown in Table A5, and highlights why the B must be considered alongside other metrics when evaluating model performance.




Figure 14. CONUS TEC B (a) and RMSE (b) for all validation runs.

4.3.4 JASON TEC

The JASON-2 and JASON-3 altimeters provide direct measurements of the nadir TEC between the spacecraft (mean altitude of 1,340 km) and the Earth's surface. The measurements are only available over the oceans (Figure 16), but are a good complement to land-based GPS receiver measurements. With an inclination angle of 66° , each JASON satellite slowly precesses through all local times in ~ 2 months; thus each validation month covers roughly half of the local times, as illustrated in Figure 17 for Jan 2021. For more details on the JASON measurements, refer to Section 4.1.4 and references therein.

Overall, the validation shows that NIMO TEC, calculated up to 1,340 km in altitude, compares well with JASON TEC measurements and outperforms IRI-2016. The global statistics for each validation run are shown in Table A6 and by the filled circles in Figure 18. Seasonal and solar cycle variations in the RMSE are highlighted in Figure 19.

During the solar active months in 2014, the NIMO RMSE was lower than that of IRI-2016 by 37% and during solar quiet months the improvement is more than 40%. Both models show a seasonal change in performance during the solar active runs that is not present during the solar quiet runs, with the solstices having lower RMSE values than the equinoxes. Additional metrics used for this analysis include the B and R^2 (see Sections 4.2.2, 4.2.3, 4.2.7). The R^2 shows a higher correlation between the NIMO results and the data in all instances, while the B is typically lower in the NIMO results.

Breaking the data down into the four regions shown in Figure 16 permits the validation of low-latitudes (within 35° of the magnetic equator) and mid-latitudes (between 60° and 35° north and south of the magnetic equator) in two local time




Figure 15. Time evolution of the average TEC in CONUS for NIMO, IRI-2016, and Madrigal TEC (left column) and the resulting statistics (right column) during the Oct 2014 run.

regions that largely encompass day (06:00-18:00 SLT) and night (18:00-06:00 SLT) times, as was done for the ionosondes. The mid-latitude results are presented in Table A7 and shown in Figure 18 by squares and stars. To summarize across all of the validation runs, the mid-latitude daytime results show NIMO outperforming IRI-2016 with $P_{R^2} = 77.78\%$, $P_B = 88.89\%$ and $P_{RMSE} = 100\%$. The mid-latitude nighttime results also show better agreement between NIMO and the JASON observations, with $P_{R^2} = 100\%$, $P_B = 77.78\%$ and $P_{RMSE} = 77.78\%$. In the low-latitudes (presented in Table A8 and shown in Figure 18 by upward and downward facing triangles), all of the daytime and nighttime NIMO results correlate better with the JASON observations ($P_{R^2} = 100\%$). The P_{RMSE} also shows NIMO outperforming IRI-2016 in both local time groups, with values of 100% for the daytime and 88.89% for the nighttime. The B comparison is weaker, with NIMO outperforming IRI-2016 in the daytime ($P_B = 66.67\%$), but not at night ($P_B = 44.44\%$). However, this can be explained by examining the different TEC distributions. An example of the type of distribution where IRI-2016 outperforms NIMO is shown in Figure 20. The wider




Figure 16. JASON-2 data coverage in Jan 2014 as a function of latitude and longitude for the mid- and low-latitudes at daytime and nighttime. For this report, we define mid-latitudes as latitudes between 60° and 35° north and south of the magnetic equator. Low-latitudes include regions within 35° of the magnetic equator. Daytime passes include local times between 06:00 SLT and 18:00 SLT, and nighttime passes are between 18:00 SLT and 06:00 SLT.

typical deviation between the IRI-2016 and JASON observations has a tendency to balance out, as reflected in the performance of the R^2 and RMSE statistics.

410 4.3.5 Topside Plasma Density

The topside ionosphere, the O^+ dominated region above the F_2 peak, is dominated by plasma transport processes. In different latitudinal regions, the magnetic field structure leads to different types of interactions between the ionosphere, thermosphere, and magnetosphere. This validation uses in situ measurements of the plasma density from IVMs flown onboard the C/NOFS, DMSP, and ICON satellites. The data from the satellites are paired directly with the model output, reducing the number of
 415 samples available for the validation based on the model's 15 min cadence. This direct pairing was chosen to avoid introducing




Figure 17. JASON-2 data coverage in Jan 2014 as a function of SLT. The blue bars indicate nighttime measurements, defined as the SLT between 18:00 SLT – 06:00 SLT, and the red bars show the daytime measurements. Bars with diagonal lines show the portion of the measurements in the low-latitude region.

interpolation into the validation process and avoid considering structures with time-scales smaller than the model is capable of reproducing. For more details about these data sets, see Sections 4.1.5, 4.1.6, and 4.1.7.

The results of the topside ionosphere validations, presented in Tables A9 and A10, may be summarized for all satellites and regions with NIMO outperforming IRI-2016 in the error meta analysis, but not the bias, with $P_B = 27.9\%$, $P_{RMSE} = 74.4\%$,
 420 and $P_{Med.AE} = 62.8\%$.

A more detailed look at the topside error is presented in Figure 21, which presents the seasonal variations for each spacecraft used in the model validation for the solar active and solar quiet periods. The seasonal and solar cycle variations are similar to those seen by the JASON TEC in Figure 19. During the solar active year of 2014 NIMO and IRI-2016 perform better during solstices than equinoxes, with the best performance seen during Jul 2014. During the solar quiet years, no seasonal variation is
 425 present, and both IRI-2016 and NIMO have lower Med. AE values then they do during the solar active years.

The DMSP results were further broken down into different local time regions that were chosen to encompass times with similar physical processes, four of which contained sufficient data to be used for model validation. These four groups, and the reason behind their selection are: 02:00-06:00 SLT contains sunrise, 06:00-08:00 SLT contains the morning hours at northern mid-latitudes (for F18, the only spacecraft to use this bin), 12:00-17:00 SLT contains the afternoon density peak, and 17:00-
 430 20:00 SLT contains sunset. The summary of these results is shown in Figure 22. This figure shows that NIMO most consistently outperforms IRI-2016 during the 02:00 – 06:00 SLT period. During the other local time periods NIMO typically outperforms IRI-2016 during the solar active runs, but not during the solar quiet runs.




Figure 18. JASON TEC B (a), RMSE (b), and R^2 (c) for all validation runs, latitudes, and local times.

5 Conclusions

NIMO is a new operational, ionospheric model that brings together the expertise of the ab initio SAMI3 ionospheric model and IDA-4D data assimilation to provide hindcasts, nowcasts, and forecasts of the ionospheric electron density. NIMO v1.0 the first stable version of this model, later versions of which have been transitioned for use in an operational environment. The validation of NIMO v1.0 demonstrates the combined ability of data assimilation and physics-based modeling to provide realistic calculations of electron density over the entire terrestrial ionosphere.

NIMO was extensively validated against a variety of available ionospheric data sets, with the goal of benchmarking its performance near and away from locations of assimilated data in the F region. As all models need to be validated against independent data sets, special emphasis is placed on the JRO ISR, JASON TEC, CINDI, DMSP, and ICON observations. These data sets were not used in the data assimilation nor are they reliant on any potentially assimilated data (the AO and MH ISRs use ionosonde data to assist in the altitude calibration).

The ionosonde validation showed no consistent local time variations in the relative performance of the two models. It found that NIMO outperformed IRI-2016 when modeling the f_oF_2 , while IRI-2016 did slightly better at modeling the h_mF_2 . The only exception is times with geomagnetic storms, where NIMO outperformed IRI-2016.




Figure 19. JASON RMSE for NIMO (black circles) and IRI-2016 (red triangles) over solar active and quiet validation runs.




Figure 20. Difference histograms of the TEC between the models NIMO and IRI-2016 and JASON-2 in Jan 2014.




Figure 21. Med. AE of the different topside satellites (circles, squares, upward and downward triangles, and stars) compared to NIMO (navy blue) and IRI-2016 (light blue) over solar active (left, a) and quiet (right, b) validation runs. The shaded boxes mark the solstice seasons.

The ISR validation was able to examine portions of five of the nine desired validation periods at either AO, JRO, or MH (with some overlap in the time periods). At all times and locations, NIMO outperformed IRI-2016 and the NIMO climatological trend slightly outperformed the standard NIMO output. This shows that while NIMO does a good job representing the $N_m F_2$ and $h_m F_2$ at mid-, low-, and equatorial latitudes, the small-scale variations do not exactly match those seen in the observations.

The CONUS GPS TEC validation found that NIMO outperformed IRI-2016, with the RMSE reflecting NIMO's ability to capture day-to-day variations in the VTEC over each validation period. Both the B and RMSE showed that NIMO performed better in the CONUS region of interest at solar quiet times, with the solar active periods and the storm validation run having similarly worse RMSE values.

The JASON TEC validation focused on the model performance over the oceans, where the amount of data contributing to assimilation or the formation of an empirical model is low. It found that NIMO outperformed IRI-2016 globally in all the validation runs. This performance is upheld when looking at smaller latitudinal and local time regions.

The CINDI, DMSP, and ICON validation focused on the model performance in the topside ionosphere. It found that NIMO outperformed IRI-2016 during solar active periods, though both NIMO and IRI-2016 had smaller errors during solar quiet periods. The topside ionospheric validation showed seasonal variations in the Med. AE that were similar to those seen in the JASON TEC RMSE.

The results of this validation demonstrate that the current capabilities to specify the electron density using NIMO v1.0 are as good or better than climatology, as provided by IRI-2016. Particular improvement is seen over the oceans, where data assimilation and data-based climatologies are less able to provide constraints. Future versions of NIMO will include improvements to the data assimilation and physics-based processes, aiming to improve the regions that this validation revealed as weaknesses.




Figure 22. Percentage of runs for different SLT regions (differentiated by color) where NIMO outperforms IRI-2016 for DMSP F15-F18 considering P_B (a), P_{RMSE} (b), and $P_{Med.AE}$ (c).

Appendix A

Statistics from each of the different instrument comparisons discussed in Section 4.3 are presented here in a tabular form. By providing the values of the statistics for each data-model comparison, future validations can use these results in an apples-to-apples benchmarking.



Table A1. Global f_oF_2 statistics in different local time bins for all ionosonde locations.

Run	SLT (h)	NIMO (MHz)			IRI-2016 (MHz)		
		B	MAE	RMSE	B	MAE	RMSE
Jan 2014	00:00 - 24:00	0.775	1.22	1.82	1.40	1.79	2.40
⋮	06:00 - 18:00	0.823	1.29	1.87	1.53	1.90	2.56
⋮	18:00 - 06:00	0.733	1.16	1.78	1.25	1.67	2.23
Apr 2014	00:00 - 24:00	1.58	1.79	3.28	0.649	1.65	2.49
⋮	06:00 - 18:00	1.62	1.80	3.34	0.636	1.72	2.62
⋮	18:00 - 06:00	1.54	1.77	3.21	0.644	1.57	2.33
Jul 2014	00:00 - 24:00	0.586	0.798	1.58	0.322	0.989	1.46
⋮	06:00 - 18:00	0.725	0.891	1.69	0.402	1.06	1.57
⋮	18:00 - 06:00	0.46	0.721	1.5	0.228	0.921	1.36
Oct 2014	00:00 - 24:00	0.233	0.594	1.05	0.212	1.12	1.50
⋮	06:00 - 18:00	0.317	0.668	1.11	0.053	1.19	1.55
⋮	18:00 - 06:00	0.152	0.523	1.00	0.445	1.04	1.45
Jan 2021	00:00 - 24:00	0.065	0.497	0.697	-0.251	0.692	0.904
⋮	06:00 - 18:00	0.141	0.488	0.680	-0.007	0.630	0.833
⋮	18:00 - 06:00	-0.024	0.491	0.693	-0.531	0.766	0.983
Apr 2020	00:00 - 24:00	0.107	0.569	0.873	0.148	0.692	1.01
⋮	06:00 - 18:00	0.208	0.573	0.874	0.325	0.724	1.04
⋮	18:00 - 06:00	0.0001	0.563	0.873	-0.040	0.662	0.976
Oct 2019	00:00 - 24:00	0.246	0.656	0.925	0.157	0.702	0.959
⋮	06:00 - 18:00	0.378	0.651	0.935	0.340	0.715	0.964
⋮	18:00 - 06:00	0.096	0.659	0.908	-0.052	0.676	0.940
Aug 2018	00:00 - 24:00	0.351	0.615	0.924	0.213	0.622	0.937
⋮	06:00 - 18:00	0.419	0.597	0.883	0.332	0.660	0.925
⋮	18:00 - 06:00	0.273	0.632	0.966	0.095	0.585	0.953
Mar 2015	00:00 - 24:00	0.485	0.830	1.24	-0.403	1.08	1.48
⋮	06:00 - 18:00	0.687	0.944	1.33	-0.552	1.19	1.53
⋮	18:00 - 06:00	0.348	0.797	1.24	-0.370	1.03	1.52



Table A2. Global $h_m F_2$ statistics in different local time bins for all ionosonde locations.

Run	SLT (h)	NIMO (km)			IRI-2016 (km)		
		B	MAE	RMSE	B	MAE	RMSE
Jan 2014	00:00 - 24:00	13.4	25.2	38.7	3.08	24.2	34.8
⋮	06:00 - 18:00	9.35	19.0	28.6	4.60	20.3	29.2
⋮	18:00 - 06:00	17.2	31.3	46.9	1.11	28.0	39.6
Apr 2014	00:00 - 24:00	10.6	19.3	31.0	3.29	20.0	26.9
⋮	06:00 - 18:00	8.0	19.0	31.0	5.83	17.5	24.4
⋮	18:00 - 06:00	13.0	19.4	30.7	0.826	22.2	28.8
Jul 2014	00:00 - 24:00	22.3	35.7	71.3	14.9	36.7	69.1
⋮	06:00 - 18:00	18.9	36.6	72.0	16.6	38.5	71.0
⋮	18:00 - 06:00	26.4	35.6	72.2	14.2	36.0	68.8
Oct 2014	00:00 - 24:00	10.5	23.4	49.6	-31.0	25.1	47.5
⋮	06:00 - 18:00	5.46	18.8	38.4	0	17.5	33.6
⋮	18:00 - 06:00	16.0	28.6	59.8	-6.36	33.4	59.2
Jan 2021	00:00 - 24:00	8.45	25.0	34.4	-2.8	23.4	34.4
⋮	06:00 - 18:00	13.5	24.0	31.8	2.05	20.6	30.4
⋮	18:00 - 06:00	3.1	26.2	37.3	-8.21	26.9	38.7
Apr 2020	00:00 - 24:00	9.61	25.6	37.3	2.92	24.8	36.7
⋮	06:00 - 18:00	13.8	26.3	36.4	7.98	24.9	35.0
⋮	18:00 - 06:00	5.36	24.8	38.0	-2.43	24.6	38.2
Oct 2019	00:00 - 24:00	10.6	23.8	33.0	-0.968	21.5	31.4
⋮	06:00 - 18:00	13.2	23.6	31.4	3.12	19.2	27.5
⋮	18:00 - 06:00	7.84	24.0	34.6	-5.33	23.9	35.2
Aug 2018	00:00 - 24:00	17.3	28.3	39.6	6.22	25.3	36.0
⋮	06:00 - 18:00	21.9	30.9	41.2	14.8	27.2	36.6
⋮	18:00 - 06:00	12.5	25.8	38.2	-3.07	23.7	35.8
Mar 2015	00:00 - 24:00	11.4	27.4	43.0	-13.9	28.8	43.0
⋮	06:00 - 18:00	9.60	24.2	38.2	-5.65	24.7	36.4
⋮	18:00 - 06:00	13.4	32.9	50.8	-25.4	36.0	52.8



Table A3. NIMO trends and IRI-2016 correlation factor (r_1) with the ISR data for $h_m F_2$ at the ISR locations.

Validation run period	ISR	r_1			B (km)		
		NIMO	NIMO trend	IRI-2016	NIMO	NIMO trend	IRI-2016
Jan 2014	JRO	0.82	0.86	0.75	34.99	30.35	40.09
⋮	MH	0.9	0.93	0.91	21.45	21.20	15.49
Jul 2014	MH	0.86	0.86	0.78	19.00	18.80	23.30
Mar 2015	AO	0.91	0.92	0.71	13.41	13.36	45.47
⋮	MH	0.64	0.64	0.43	35.56	35.69	43.00
Aug 2018	AO	0.71	0.77	0.79	21.77	20.40	18.86
Jan 2021	JRO	0.55	0.70	0.44	27.03	19.03	25.04
⋮	MH	0.74	0.78	0.82	20.64	18.60	17.39

Table A4. NIMO trends and IRI-2016 correlation factor (r_1) with the ISR data for $N_m F_2$ at the ISR locations.

Validation run period	ISR	r_1			B (10^5 cm^{-3})		
		NIMO	NIMO trend	IRI-2016	NIMO	NIMO trend	IRI-2016
Jan 2014	JRO	0.90	0.92	0.89	2.17	2.02	2.68
⋮	MH	0.97	0.98	0.96	0.95	0.83	3.8
Jul 2014	MH	0.95	0.96	0.90	0.65	0.63	0.51
Mar 2015	AO	0.93	0.96	0.77	1.47	1.19	4.31
⋮	MH	0.86	0.85	0.82	2.07	2.05	1.32
Aug 2018	AO	0.87	0.89	0.73	0.84	0.81	1.21
Jan 2021	JRO	0.83	0.90	0.22	0.97	0.89	1.34
⋮	MH	0.95	0.96	0.96	0.81	0.80	0.40



Table A5. Vertical TEC statistics from CONUS during solar active conditions.

Validation Run	NIMO (TECU)		IRI-2016 (TECU)	
	B	RMSE	B	RMSE
Jan 2014	0.25	1.94	3.92	7.47
Apr 2014	1.46	3.23	-3.31	5.86
Jul 2014	-0.95	3.20	-2.51	4.62
Oct 2014	0.96	2.38	0.56	6.33
Mar 2015	1.37	2.69	-0.15	4.15
Aug 2018	-0.06	1.36	-0.29	1.59
Oct 2019	-0.26	1.09	-0.09	1.88
Apr 2020	-0.07	1.07	-0.82	1.41
Jan 2021	-0.95	1.52	-1.46	2.76

Table A6. Global TEC statistics from JASON-2 for all local times.

Validation Run	NIMO			IRI-2016		
	R ²	RMSE	B	R ²	RMSE	B
Jan 2014	0.88	5.46	1.74	0.55	10.16	0.14
Apr 2014	0.90	7.57	1.55	0.81	9.96	-1.44
Jul 2014	0.89	3.89	0.65	0.70	7.38	2.44
Oct 2014	0.82	8.52	2.73	0.60	12.03	0.02
Mar 2015	0.89	7.80	-0.54	0.78	11.43	-3.71
Aug 2018	0.82	2.25	0.97	0.80	3.73	2.25
Oct 2019	0.75	2.87	1.57	0.72	5.77	4.03
Apr 2020	0.87	1.81	-0.63	0.73	3.57	1.63
Jan 2021	0.91	1.95	0.65	0.77	4.22	2.30



Table A7. Mid-latitude TEC statistics from JASON-2 for day and night times.

Validation Run		NIMO			IRI-2016		
Date	SLT	R ²	RMSE	B	R ²	RMSE	B
Jan 2014	06:00 – 18:00	0.82	3.98	1.12	0.28	8.60	3.65
⋮	18:00 – 06:00	0.88	3.56	0.04	0.61	7.70	-4.08
Apr 2014	06:00 – 18:00	0.87	4.95	0.34	0.69	7.67	-0.81
⋮	18:00 – 06:00	0.87	2.61	-0.23	0.73	3.68	-0.75
Jul 2014	06:00 – 18:00	0.78	2.75	1.09	0.45	7.22	4.68
⋮	18:00 – 06:00	0.92	2.33	-0.76	0.88	3.05	-1.52
Oct 2014	06:00 – 18:00	0.63	7.91	3.06	0.32	9.66	0.41
⋮	18:00 – 06:00	0.86	4.41	1.25	0.57	5.71	0.30
Mar 2015	06:00 – 18:00	0.78	6.82	0.28	0.44	10.83	-2.06
⋮	18:00 – 06:00	0.35	3.03	0.36	0.29	2.80	-0.96
Aug 2018	06:00 – 18:00	0.43	1.94	1.12	0.44	2.44	1.87
⋮	18:00 – 06:00	0.27	1.46	0.64	0.15	1.66	0.91
Oct 2019	06:00 – 18:00	0.39	2.22	1.46	0.40	3.09	2.47
⋮	18:00 – 06:00	0.45	1.96	1.20	0.44	2.38	1.64
Apr 2020	06:00 – 18:00	0.58	1.65	-0.54	0.49	2.14	1.01
⋮	18:00 – 06:00	0.63	1.67	-1.05	0.59	1.45	-0.31
Jan 2021	06:00 – 18:00	0.73	1.86	0.58	0.36	3.73	2.54
⋮	18:00 – 06:00	0.73	2.07	0.91	0.56	2.60	1.00



Table A8. Low-latitude TEC statistics from JASON-2 for day and night times.

Validation Run		NIMO			IRI-2016		
Date	SLT	R ²	RMSE	B	R ²	RMSE	B
Jan 2014	06:00 – 18:00	0.82	8.46	3.88	0.36	14.71	2.75
⋮	18:00 – 06:00	0.87	5.54	2.45	0.64	9.29	1.69
Apr 2014	06:00 – 18:00	0.78	11.08	3.42	0.58	14.28	-2.89
⋮	18:00 – 06:00	0.74	9.38	3.45	0.50	11.94	-0.53
Jul 2014	06:00 – 18:00	0.83	5.55	1.11	0.50	10.26	4.20
⋮	18:00 – 06:00	0.89	4.00	0.82	0.80	6.64	1.95
Oct 2014	06:00 – 18:00	0.68	10.03	2.41	0.20	15.76	1.92
⋮	18:00 – 06:00	0.76	10.53	4.25	0.48	14.15	-1.58
Mar 2015	06:00 – 18:00	0.68	12.84	-5.83	0.30	19.61	-9.67
⋮	18:00 – 06:00	0.37	6.11	3.32	0.20	6.12	-2.42
Aug 2018	06:00 – 18:00	0.67	2.72	0.29	0.52	6.30	4.95
⋮	18:00 – 06:00	0.43	2.47	1.79	0.26	2.38	1.24
Oct 2019	06:00 – 18:00	0.75	3.13	1.24	0.65	8.63	7.51
⋮	18:00 – 06:00	0.58	3.76	2.53	0.53	6.51	4.79
Apr 2020	06:00 – 18:00	0.91	2.11	-1.03	0.67	5.66	4.13
⋮	18:00 – 06:00	0.86	1.91	-0.21	0.69	3.84	1.73
Jan 2021	06:00 – 18:00	0.88	2.24	0.24	0.56	6.75	5.09
⋮	18:00 – 06:00	0.80	1.82	1.05	0.43	3.24	1.58



Table A9: Global, topside ionosphere statistics from DMSP for SLT regions.

Run	Spacecraft #	SLT (h)	NIMO (10^3 cm^{-3})			IRI-2016 (10^3 cm^{-3})		
			B	RMSE	Med. AE	B	RMSE	Med. AE
Jan 2014	F16	02:00 – 06:00	-2.09	16.0	8.07	-0.172	18.0	10.2
⋮	⋮	12:00 – 17:00	-3.09	13.6	5.62	33.7	46.3	33.9
⋮	F17	02:00 – 06:00	-9.25	22.1	12.4	-9.48	25.6	11.8
⋮	⋮	17:00 – 20:00	-9.57	25.0	10.9	-8.54	36.3	19.8
⋮	F18	06:00 – 08:00	-15.8	25.2	17.8	-2.32	29.3	16.5
⋮	⋮	17:00 – 20:00	1.08	22.1	3.13	9.13	27.9	12.3
Apr 2014	F15	02:00 – 06:00	1.88	12.3	6.28	-1.07	15.3	7.93
⋮	⋮	12:00 – 17:00	-31.3	53.9	20.4	-28.3	72.5	18.3
⋮	F16	02:00 – 06:00	-2.06	9.26	5.46	-3.94	11.7	6.14
⋮	⋮	12:00 – 17:00	-15.3	34.0	16.3	-32.8	65.7	20.2
⋮	F17	02:00 – 06:00	-2.99	8.93	4.14	3.10	12.7	6.42
⋮	⋮	17:00 – 20:00	-6.3	30.6	12.2	-22.7	65.1	14.3
⋮	F18	06:00 – 08:00	-8.05	12.1	7.75	17.0	26.6	13.8
⋮	⋮	17:00 – 20:00	-4.62	36.8	13.1	-30.9	69.0	18.1
Jul 2014	F15	02:00 – 06:00	-1.16	10.8	4.96	-1.93	14.6	6.30
⋮	⋮	12:00 – 17:00	-14.8	22.6	11.8	4.12	22.5	11.8
⋮	F16	02:00 – 06:00	-2.21	8.28	4.14	-4.45	9.42	5.56
⋮	⋮	12:00 – 17:00	-17.3	24.4	13.5	-4.86	22.7	13.5
⋮	F17	02:00 – 06:00	-1.33	4.31	2.67	0.633	7.17	3.24
⋮	⋮	17:00 – 20:00	-10.1	17.8	6.66	3.58	18.3	9.26
⋮	F18	06:00 – 08:00	-3.47	7.09	2.97	10.8	18.7	6.07
⋮	⋮	17:00 – 20:00	-7.72	15.4	10.2	0.984	20.4	11.4
Oct 2014	F15	02:00 – 06:00	2.73	13.8	5.76	4.03	16.2	7.86
⋮	⋮	12:00 – 17:00	-26.4	49.8	17.1	-13.9	65.1	27.0
⋮	F16	02:00 – 06:00	-2.09	10.5	4.81	-2.29	15.0	7.28
⋮	⋮	12:00 – 17:00	-16.7	41.0	14.2	-19.8	75.0	21.8

Continued on next page



Table A9 – continued from previous page

Run	Spacecraft #	SLT (h)	NIMO (10^3 cm^{-3})			IRI-2016 (10^3 cm^{-3})		
			B	RMSE	Med. AE	B	RMSE	Med. AE
⋮	F17	02:00 – 06:00	-7.87	17.1	8.74	-4.77	23.0	10.1
⋮	⋮	17:00 – 20:00	-6.18	37.2	11.8	-14.8	60.5	18.3
⋮	F18	06:00 – 08:00	-9.75	18.7	11.1	17.8	35.8	20.7
⋮	⋮	17:00 – 20:00	7.91	42.8	9.44	2.74	46.3	17.2
Aug 2018	F15	02:00 – 06:00	-1.70	4.96	3.06	-5.14	6.86	4.38
⋮	⋮	12:00 – 17:00	-6.75	9.88	5.40	1.98	8.23	2.70
⋮	F16	02:00 – 06:00	-2.97	5.57	3.26	-6.39	8.68	6.00
⋮	⋮	12:00 – 17:00	-8.02	11.4	6.13	7.43	7.94	2.79
⋮	F17	02:00 – 06:00	-0.0268	2.44	1.33	-0.106	2.21	1.13
⋮	⋮	17:00 – 20:00	-6.57	8.91	6.23	-2.71	6.71	3.41
⋮	F18	06:00 – 08:00	-2.43	4.59	2.80	-2.21	3.43	1.76
⋮	⋮	17:00 – 20:00	-5.71	8.57	4.59	-0.451	5.63	3.09
Oct 2019	F15	02:00 – 06:00	-3.03	6.42	3.61	-7.27	9.77	7.37
⋮	⋮	12:00 – 17:00	-7.98	14.0	4.89	4.22	13.1	4.49
⋮	F16	02:00 – 06:00	-3.09	6.51	3.69	-7.01	9.41	7.31
⋮	⋮	12:00 – 17:00	-8.07	13.6	5.13	2.71	11.3	3.53
⋮	F17	02:00 – 06:00	-1.05	4.36	2.62	-0.701	2.88	1.93
⋮	⋮	17:00 – 20:00	-3.76	7.36	3.56	2.76	8.94	3.58
⋮	F18	06:00 – 08:00	0.606	2.43	1.33	-0.124	2.89	1.50
⋮	⋮	17:00 – 20:00	-7.03	11.8	6.07	3.97	11.1	4.19
Apr 2020	F15	02:00 – 06:00	-3.32	6.02	2.97	-7.59	9.76	7.42
⋮	⋮	12:00 – 17:00	-4.55	8.10	4.07	3.53	12.0	2.97
⋮	F16	02:00 – 06:00	-3.42	6.00	3.04	-7.33	9.75	6.83
⋮	⋮	12:00 – 17:00	-4.79	7.81	7.81	2.52	10.2	2.69
⋮	F17	02:00 – 06:00	-0.190	2.96	1.56	-0.285	2.89	1.83
⋮	⋮	17:00 – 20:00	-2.32	5.14	3.39	1.65	7.94	3.83
⋮	F18	06:00 – 08:00	-0.349	3.11	1.81	-1.66	2.58	1.64

Continued on next page



Table A9 – continued from previous page

Run	Spacecraft #	SLT (h)	NIMO (10^3 cm^{-3})			IRI-2016 (10^3 cm^{-3})		
			B	RMSE	Med. AE	B	RMSE	Med. AE
⋮	⋮	17:00 – 20:00	-1.47	5.59	2.63	1.23	5.18	2.04
Jan 2021	F15	02:00 – 06:00	-3.16	5.57	2.88	-6.32	8.23	6.23
⋮	⋮	12:00 – 17:00	-3.37	8.53	4.27	-1.43	7.36	3.42
⋮	F16	02:00 – 06:00	-3.69	6.19	3.23	-7.11	9.26	6.99
⋮	⋮	12:00 – 17:00	-3.48	8.26	4.07	-1.21	7.16	3.35
⋮	F17	02:00 – 06:00	-8.94	12.4	8.48	-6.10	10.2	5.38
⋮	⋮	17:00 – 20:00	-3.13	7.85	4.37	-2.82	7.55	4.82
⋮	F18	17:00 – 20:00	-9.44	11.0	9.38	-5.31	7.36	3.67

Table A10: Global, topside ionosphere statistics from CINDI, DMSP, and ICON for all local times

Validation Run	Spacecraft ID	NIMO (10^3 cm^{-3})			IRI-2016 (10^3 cm^{-3})		
		B	RMSE	Med. AE	B	RMSE	Med. AE
Jan 2014	CINDI	127	294	108	843	247	86.3
⋮	DMSP F15	-12.0	26.7	12.0	-7.93	29.0	17.4
⋮	DMSP F16	-6.65	19.8	8.47	7.32	28.7	14.3
⋮	DMSP F17	-6.72	20.1	7.67	-4.09	27.3	12.5
⋮	DMSP F18	-5.86	22.9	8.12	0.839	29.3	14.8
Apr 2014	CINDI	93.1	312	158	-87.7	389	231
⋮	DMSP F15	-13.9	37.3	20.7	-15.3	50.4	12.7
⋮	DMSP F16	9.66	23.7	14.9	-13.6	38.4	11.5
⋮	DMSP F17	-6.18	22.4	8.40	-12.8	44.4	12.5
⋮	DMSP F18	-6.32	22.7	9.85	-5.53	40.9	14.3
Jul 2014	CINDI	26.0	183	69.4	59.4	210	94.4
⋮	DMSP F15	-7.52	16.8	6.89	0.619	18.1	8.58
⋮	DMSP F16	-7.9	15.6	6.21	-2.97	16.1	8.36
⋮	DMSP F17	-7.11	14.0	5.58	-1.93	15.1	8.37

Continued on next page



Table A10 – continued from previous page

Validation Run	Spacecraft ID	NIMO (10^3 cm^{-3})			IRI-2016 (10^3 cm^{-3})		
		B	RMSE	Med. AE	B	RMSE	Med. AE
⋮	DMSP F18	-5.77	11.4	5.07	1.37	16.7	7.70
Oct 2014	CINDI	141	372	266	-53.6	381	206
⋮	DMSP F15	-11.8	35.2	11.1	-7.21	45.4	13.6
⋮	DMSP F16	-9.68	26.9	9.08	-11.0	46.1	11.9
⋮	DMSP F17	-6.45	25.6	8.77	-6.29	40.7	13.5
⋮	DMSP F18	-3.24	27.2	10.7	4.71	34.4	15.4
Mar 2015	CINDI	-32.1	422	192	-214	500	169
⋮	DMSP F15	-1.67	5.03	1.31	-1.70	7.32	0.981
⋮	DMSP F16	-1.55	4.00	1.04	-1.10	2.57	0.882
⋮	DMSP F17	-1.30	3.94	0.905	-1.26	4.78	0.582
⋮	DMSP F18	-1.11	2.75	1.00	-0.475	2.31	0.986
Aug 2018	DMSP F15	-3.90	7.51	3.59	-1.44	7.12	2.96
⋮	DMSP F16	-4.82	8.48	4.19	-2.86	7.71	3.09
⋮	DMSP F17	-4.03	6.91	3.75	-2.09	5.38	2.52
⋮	DMSP F18	-3.43	6.74	3.49	-1.66	4.88	2.26
Oct 2019	DMSP F15	-4.63	10.2	3.95	-1.37	10.7	4.77
⋮	DMSP F16	-4.67	9.86	4.07	-2.06	6.55	4.13
⋮	DMSP F17	-2.01	5.77	2.89	1.53	6.82	2.62
⋮	DMSP F18	-2.77	7.30	3.16	-0.352	7.26	2.49
Apr 2020	DMSP F15	-3.36	6.82	3.34	-1.72	10.2	6.86
⋮	DMSP F16	-3.37	6.59	3.30	-2.13	9.08	3.58
⋮	DMSP F17	-2.15	4.76	2.56	0.418	5.86	2.53
⋮	DMSP F18	-2.27	5.32	2.66	-1.25	7.47	2.87
⋮	ICON	-16.7	26.7	12.2	24.7	46.3	23.5
Jan 2021	DMSP F15	-3.96	7.89	3.77	-3.53	7.82	4.50
⋮	DMSP F16	-4.29	8.01	3.83	-4.35	8.07	5.05
⋮	DMSP F17	-3.40	7.62	3.34	-2.25	6.70	3.24

Continued on next page



Table A10 – continued from previous page

Validation Run	Spacecraft ID	NIMO (10^3 cm^{-3})			IRI-2016 (10^3 cm^{-3})		
		B	RMSE	Med. AE	B	RMSE	Med. AE
⋮	DMSP F18	-3.03	6.98	3.42	-2.67	7.05	3.72
⋮	ICON	-12.9	25.3	10.1	8.39	32.9	16.5

470 *Acknowledgements.* Radar observations and analysis at MH are supported by the National Science Foundation (NSF) Cooperative Agreement AGS-1952737 with the Massachusetts Institute of Technology. The AO was a NSF facility operated by a cooperative agreement with University of Central Florida. The JRO is a facility of the Instituto Geofísico del Perú operated with support from the NSF AGS-1732209 through Cornell University.

475 The Madrigal distributed database system is supported by NSF Cooperative Agreement AGS-1952737 with the Massachusetts Institute of Technology.

AGB, SM, CM, DH, MB, MD, EN, JLT, and EJW were supported by the Office of Naval Research.



References

- Altadill, D., Magdaleno, S., Torta, J., and Blanch, E.: Global empirical models of the density peak height and of the equivalent scale height for quiet conditions, *Advances in Space Research*, 52, 1756–1769, <https://doi.org/10.1016/j.asr.2012.11.018>, 2013.
- 480 Bilitza, D.: IRI the International Standard for the Ionosphere, *Adv. Radio Sci.*, 16, 1–11, <https://doi.org/10.5194/ars-16-1-2018>, 2018.
- Burrell, A. G.: Equatorial Topside Magnetic Field-Aligned Ion Drifts at Solar Minimum, Ph.D. thesis, University of Texas at Dallas, Richardson, TX, 2012.
- Burrell, A. G., Bonito, N. A., and Carrano, C. S.: Total electron content processing from GPS observations to facilitate ionospheric modeling, *GPS Solutions*, 13, 83–95, <https://doi.org/10.1007/s10291-008-0102-3>, 2008.
- 485 Bust, G. S., Garner, T. W., and Gaussiran, T. L.: Ionospheric Data Assimilation Three-Dimensional (IDA3D): A global, multisensor, electron density specification algorithm, *Journal of Geophysical Research: Space Physics*, 109, A11312, <https://doi.org/10.1029/2003JA010234>, 2004.
- Bust, G. S., Crowley, G., Garner, T. W., Gaussiran, T. L., Meggs, R. W., Mitchell, C. N., Spencer, P. S. J., Yin, P., and Zapfe, B.: Four-dimensional GPS imaging of space weather storms, *Space Weather*, 5, 02003, <https://doi.org/10.1029/2006SW000237>, 2007.
- 490 Dandenault, P. B., Dao, E., Kaeppler, S. R., and Miller, E. S.: An Estimation of Human-Error Contributions to Historical Ionospheric Data, *Earth and Space Science*, 7, e2020EA001123, <https://doi.org/10.1029/2020EA001123>, e2020EA001123 2020EA001123, 2020.
- de la Beaujardière, O. and C/NOFS Science Definition Team: C/NOFS: A mission to forecast scintillations, *Journal of Atmospheric and Solar-Terrestrial Physics*, 66, 1573–1591, <https://doi.org/10.1016/j.jastp.2004.07.030>, 2004.
- Dougherty, J. P. and Farley, D. T.: A theory of incoherent scattering of radio waves by a plasma, *Proc. R. Soc. London Ser. A*, A259, 79–99, 1960.
- 495 Drob, D., Emmert, J., Meriwether, J., Makela, J., Doornobs, E., Conde, M., Hernandez, G., Noto, J., Zawdie, K., McDoanld, S., Huba, J., and Klenzing, J.: An update to the Horizontal Wind Model (HWM): The quiet time thermosphere, *Earth and Space Science*, 2, 301–319, <https://doi.org/10.1002/2014EA000089>, 2015.
- Dumont, J., Rosmorduc, V., Carrere, L., Picot, N., Bronner, E., Couhert, A., Guillot, A., Desai, S., and Benekamp, H.: Jason-3 Products Handbook, CNES: SALP-MU-M-OP-16118-CN, Issue 1 rev 4, 2017.
- 500 Eccles, J. V.: Assimilation of global-scale and mesoscale electric fields from low-latitude satellites, *Radio Science*, 39, <https://doi.org/10.1029/2002RS002810>, 2004.
- Emmert, J. T., Drob, D. P., Picone, J. M., Siskind, D. E., Jones Jr., M., Mlynczak, M. G., Bernath, P. F., Chu, X., Doornbos, E., Funke, B., Goncharenko, L. P., Hervig, M. E., Schwartz, M. J., Sheese, P. E., Vargas, F., Williams, B. P., and Yuan, T.: NRLMSIS 2.0: A Whole-Atmosphere Empirical Model of Temperature and Neutral Species Densities, *Earth and Space Science*, 8, e2020EA001321, <https://doi.org/10.1029/2020EA001321>, 2021.
- 505 Farley, D.: Incoherent Scatter, Manuscript to be published, handled by D. Hysell, 2009.
- Farley, D. T.: Faraday rotation measurements using incoherent scatter, *Radio Sci.*, 4, 143–152, 1969.
- Galkin, I. and Reinisch, B.: The new ARTIST 5 for all digisondes, in: Ionosonde Network Advisory Group (INAG) Bulletin, International Radio Science Union: Ghent, Belgium, 69 edn., 2008.
- 510 Galkin, I. A., Khmyrov, G. M., Kozlov, A. V., Reinisch, B. W., Huang, X., and Paznukhov, V. V.: The ARTIST 5, in: AIP conference proceedings, vol. 974, pp. 150–159, American Institute of Physics, 2008.
- Hall, R. C.: A History of the Military Polar Orbiting Meteorological Satellite Program, Tech. rep., National Reconnaissance Office, 2001.



- Heelis, R. A. and Hanson, W. B.: Measurements of Thermal Ion Drift Velocity and Temperature using Planar Sensors, in: Measurement
515 Techniques in Space Plasmas: Particles, edited by Pfaff, R. F., Borovsky, E., and Young, T., pp. 61–71, AGU, Washington, D.C.,
<https://doi.org/10.1029/GM102>, 1998.
- Heelis, R. A., Stoneback, R. A., Purdue, M. D., Depew, M. D., Morgan, W. A., Mankey, M. W., Lippincott, C. R., Harmon, L. L.,
and Holt, B. J.: Ion Velocity Measurements for the Ionospheric Connections Explorer, Space Science Reviews, 212, 615–629,
<https://doi.org/10.1007/s11214-017-0383-3>, 2017.
- 520 Huba, J. D., Joyce, G., and Fedder, J. A.: Sami2 is Another Model of the Ionosphere (SAMI2): A new low-latitude ionosphere model, J.
Geophys. Res. Space Phys., 105, 23 035–23 053, <https://doi.org/10.1029/2000JA000035>, 2000.
- Huba, J. D., Joyce, G., and Krall, J.: Three-dimensional equatorial spread F modeling, Geophysical Research Letters, 35, L10 102,
<https://doi.org/10.1029/2008GL033509>, 2008.
- Huba, J. D., Krall, J., and Drob, D.: Global ionospheric metal ion transport with SAMI3, Geophysical Research Letters, 46, 7937–7944,
525 <https://doi.org/10.1029/2019GL083583>, 2019.
- Hysell, D.: Antennas and Radar for Environmental Scientists and Engineers, Cambridge University Press,
<https://doi.org/10.1017/9781108164122>, 2018.
- Imel, D. A.: Evaluation of the TOPEX/POSEIDON dual-frequency ionosphere correction, Journal of Geophysical Research, 99, 24 895,
<https://doi.org/10.1029/94jc01869>, 1994.
- 530 Li, M., Yuan, Y., Wang, N., Li, Z., and Huo, X.: Performance of various predicted GNSS global ionospheric maps relative to GPS and JASON
TEC data, GPS Solutions, 22, <https://doi.org/10.1007/s10291-018-0721-2>, 2018.
- Maus, S., Macmillan, S., Chernova, T., Choi, S., Dater, D., Golovkov, V., Lesur, V., Lowes, F., Lühr, H., Mai, W., McLean, S., Olsen, N.,
Rother, M., Sabaka, T., Thomson, A., and Zvereva, T. I.: The 10th generation international geomagnetic reference field, Physics of the
Earth and Planetary Interiors, 151, 320–322, <https://doi.org/10.1016/j.pepi.2005.03.006>, 2005.
- 535 McNamara, L.: Quality figures and error bars for autoscaled Digisonde vertical incidence ionograms, Radio Science, 41, RS4011,
<https://doi.org/10.1029/2005RS003440>, 2005.
- Rideout, W. and Coster, A. J.: Automated GPS processing for global total electron content data, GPS Solutions, 10, 219–228,
<https://doi.org/10.1007/s10291-006-0029-5>, 2006.
- Schunk, R. W. and Nagy, A. F.: Ionospheres: Physics, Plasma Physics, and Chemistry, Atmospheric and Space Science Series, Cambridge
540 University Press, New York, NY (USA), 2 edn., ISBN 9780521877060, <https://doi.org/10.1017/CBO9780511635342>, 2009.
- Shubin, V.: Global median model of the F2-layer peak height based on ionospheric radio-occultation and ground-based Digisonde observa-
tions, Advances in Space Research, 56, 916–928, <https://doi.org/10.1016/j.asr.2015.05.029>, 2015.
- Stoneback, R., Klenzing, J., Burrell, A. G., Pembroke, A., Spence, C., Depew, M., Smith, J. M., Fuller, R., Von Bose, V., Hargrave, N., Iyer,
G., and Leite, S.: pysat/pysat: v3.0.1, <https://doi.org/10.5281/zenodo.5142690>, 2021.
- 545 Stoneback, R. A., Heelis, R. A., Burrell, A. G., Coley, W. R., Fejer, B. G., and Pacheco Josán, E. E.: Observations of quiet time verti-
cal ion drift in the equatorial ionosphere during the solar minimum period of 2009, Journal of Geophysical Research, 116, A12 327,
<https://doi.org/10.1029/2011JA016712>, 2011.
- Stoneback, R. A., Burrell, A. G., Klenzing, J. H., and Depew, M. D.: PYSAT: Python Satellite Data Analysis Toolkit, Journal of Geophysical
Research: Space Physics, 123, <https://doi.org/10.1029/2018JA025297>, 2018.
- 550 Themens, D. R., Reid, B., and Elvidge, S.: ARTIST ionogram autoscaling confidence scores: Best practices, URSI Radio Sci. Lett, 4, 22–
0001, 2022.