

Modernizing GNSS Data Acquisition, Pre-Processing, and Distribution at Volcanological Observatories

Pierre Sakic¹, Patrice Boissier^{1,2}, Jean-Marie Saurel¹, Sébastien Deroussi^{1,3}, Arnaud Andrieu^{1,4}, Cyprien Griot^{1,2}, Alexis Bosson^{1,3}, Cyril Vidal^{1,4}, Constanza Pardo¹, Jean-Bernard de Chabalier¹, and OVPF, OVSG & OVSM Teams*

¹Université Paris Cité, Institut de physique du globe de Paris, CNRS, IGN, F-75005 Paris, France

²Observatoire volcanologique du Piton de la Fournaise, Institut de physique du globe de Paris, F-97418 La Plaine des Cafres, La Réunion, France.

³Observatoire volcanologique et sismologique de Guadeloupe, Institut de physique du globe de Paris, F-97113 Gourbeyre, France.

⁴Observatoire volcanologique et sismologique de la Martinique, Institut de physique du globe de Paris, F-97250 Saint-Pierre, Martinique, France.

*A full list of authors appears at the end of the paper.

Correspondence: Pierre Sakic (sakic@ipgp.fr)

Abstract. In recent years, the field of geodetic monitoring is undergoing a profound transformation driven by the transition from GPS-only positioning to a fully multi-GNSS environment. With Galileo, BeiDou, and modernized GPS & GLONASS constellations now operational, a wealth of new signals and frequencies provides enhanced opportunities for high-precision positioning and real-time monitoring. However, these advances present challenges: the integration of heterogeneous receivers across local and campaign-based networks, the continued reliance on outdated RINEX 2 workflows, and the discontinuation of the `teqc` utility in 2019 have all disrupted well proven, long-standing GNSS pre-processing pipelines. While the *International GNSS Service* (IGS) community has smoothly adopted RINEX 3/4 and alternative pre-processing tools, smaller research-oriented networks have often struggled to keep pace, leaving a gap between available technology and operational monitoring practices.

10 In this paper, we present two complementary tools designed to address these challenges in the context of volcanological and seismological observatories. The first, `rinexmod` (for *RINEX Modification*), is a lightweight utility for editing RINEX headers, renaming files, and enriching metadata. It replaces critical `teqc` functionalities while supporting modern RINEX 3/4 conventions, long-file naming schemes, and direct sitelog integration. The second, `autorino` (for *Assisted Unloading, Treatment and Organization of RINEX Observations*), implements a flexible multi-step workflow for automated acquisition of
15 raw GNSS data from heterogeneous receivers and conversion to a common standard RINEX format. By integrating official manufacturer converters, handling file splicing/splitting, and linking directly with `rinexmod`, it provides a unified pipeline capable of near real-time operation (down to 5-minute intervals). Together, these tools modernize GNSS workflows across networks that are both technically diverse and geographically remote, ensuring interoperability with IGS standards while preserving operational robustness in challenging field conditions.

20 We illustrate their deployment at the *Institut de physique du globe de Paris*'s volcanological observatories and monitoring networks in Guadeloupe, Martinique, La Réunion, and Mayotte, where they enable continuous monitoring of volcanic and tectonic processes. Beyond local applications, these tools contribute to bridging the gap between global GNSS standards and regional network realities, supporting the long-term sustainability of GNSS-based geo-hazard monitoring.

1 GNSS at the IPGP's Volcanological and Seismological Observatories

25 1.1 Introduction: deformation measurements for operational volcanological monitoring

The *Institut de physique du globe de Paris* (Paris' Institute of Earth Physics, IPGP) is responsible for the operational monitoring of France's four active volcanoes, all located overseas, as well as their regional seismicity, to properly issue upstream warnings to the local and national authorities. The observations of IPGP observatories are also used by Tsunami Service Providers in their respective area. For this matter, three *Observatoires volcanologiques et sismologiques* (Volcanological and Seismological
30 Observatories, OVS) and one monitoring network are located on four different overseas islands:

- the *Observatoire volcanologique du Piton de la Fournaise* (Piton de la Fournaise Volcanological Observatory, OVPF), which is responsible for *Piton de la Fournaise* in La Réunion in the Indian Ocean,
- the *Observatoire volcanologique et sismologique de Guadeloupe* (Guadeloupe Volcanological and Seismological Observatory, OVSG), responsible for *La Soufrière de Guadeloupe* in the Lesser Antilles,
- 35 – the *Observatoire volcanologique et sismologique de Martinique* (Martinique Volcanological and Seismological Observatory, OVSM), which is responsible for *Montagne Pelée* in Martinique, also in the Lesser Antilles,
- the OVPF is also responsible of the maintenance and daily monitoring operation of the *Réseau de surveillance volcanologique et sismologique de Mayotte* (Mayotte Volcanological and Seismological Monitoring Network, REVOSIMA), to monitor *Fani Maoré*, an underwater volcano off the coast of Mayotte and the associated active volcanic area, North of the
40 Mozambique Channel.

Secular surface deformation measurements are a key component of volcanic monitoring, offering essential insights into in-depth processes such as the inflation–deflation of magmatic reservoirs, magma ascent through the plumbing system, hydrothermal activity, and flank instability (Cayol et al., 2022). The value of GNSS for these purposes was quickly recognized by the volcanology community (Dzurisin, 2000; Poland et al., 2006).

45 At Piton de la Fournaise, GNSS observations have proven particularly effective. For instance, they revealed detailed magma ascent from deep reservoirs to shallow depths before the June 2014 eruption, followed by sustained deep-to-shallow magma transfer that fed multiple eruptions in 2015 (Peltier et al., 2016; Beauducel et al., 2020b).

In Mayotte, during the 2018 seismo-volcanic crisis, GNSS stations on the island captured the decimeter-scale deformation caused by the deflation of a deep reservoir, responsible for the formation of the previously unknown submarine volcano Fani
50 Maoré (Lemoine et al., 2020; Peltier et al., 2023).

In the Caribbean, GNSS-derived deformation is integrated with seismic, geochemical, and other observations to anticipate volcanic eruptions of Soufrière de Guadeloupe and Montagne Pelée, currently in a state of unrest (Fontaine et al., 2025; Moretti et al., 2020; Pantobe et al., in press). Beyond volcano's edifices, stations located throughout the islands of Martinique, Guadeloupe and Saint-Barthelemy also monitor seismic loading and release of the active faults associated to the Lesser Antilles subduction zone (Sakic et al., 2020; Van Rijnsingen et al., 2021, 2022).

Beyond the main volcanological and seismotectonic monitoring purposes for which the stations were installed, GNSS data from OVS have other applications, such as estimating the total water vapor content in the atmosphere (Bock et al., 2021) or detecting tsunami generation through observations of ionospheric perturbations (Ravanelli et al., 2021, 2024).

1.2 OVS's GNSS networks

Nowadays, the OVS's permanent GNSS stations are divided into five networks. Four of them correspond to the four main islands where volcanoes are monitored. These are:

- **GL**: OVSG's GNSS network in the Guadeloupe Archipelago, including La Désirade, Marie-Galante, and Les Saintes Islands, plus a station located in St Barthélemy (IPGP, 2021a, Figure 1).
- **MQ**: OVSM's GNSS network in Martinique (IPGP, 2021b, Figure 2),
- **PF**: OVPF's GNSS network in La Réunion (IPGP, 2021c, Figure 3),
- **QM**: IPGP's GNSS stations components of REVOSIMA in Mayotte and Grande Glorieuse (REVOSIMA et al., 2021, Figure 4).

A fifth supplementary network, **WI** (IPGP, 2008), comprises GNSS stations in the Antilles that also belong to GL and MQ, located outside the volcanically active areas, to monitor the subduction context. These networks have been named in the same manner as their seismological counterparts, following the FDSN's two-character convention (FDSN, 2025).

The first permanent GPS stations of the OVS in the Caribbean were HOUZ00GLP and SOUF00GLP, deployed in 2000 at the Observatory's main site on Houëlmont Hill and at the summit of La Soufrière, respectively. They were followed by FSDC00MTQ in Martinique in January 2003, installed at the historical *Morne des Cadets* Observatory. At Piton de la Fournaise, the long-term GNSS network was implemented in 2004, with the permanent equipment of repetition point BORG00REU (Staudacher and Peltier, 2016). Since then, the number of stations deployed has continued to increase, as illustrated in Figure 6. Consequently, the total number of archived RINEX files has increased quadratically, reaching more than 300 000 in 2025 (Figure 5). The first GLONASS-compatible receivers were deployed in 2008, and the first real multi-GNSS capabilities began in 2016 with the installation of the first Galileo-compatible receivers (Figure 7). The latest upgrade of the OVPF's PF network in 2024 enabled the deployment of latest-generation receivers that are fully multi-GNSS compatible, including BeiDou and QZSS.

Currently (mid-2025), the OVS directly operates 71 permanent stations: 27 belong to PF network, 25 to GL, 15 to MQ and 4 to QM. Depending on the sites and requirements, the three OVS also use GNSS data produced by scientific and institutional

partners, such as the *Institut national de l'information géographique et forestière* (IGN) or the Maïdo's *Observatoire de physique de l'atmosphère de La Réunion*; or commercial providers like *Exagone/Teria* (<https://www.reseau-teria.com>) or
85 *Précision Topo/Lél@* (<https://precision-topo.com>).

In parallel with continuous GNSS observations, repetition campaigns are conducted to spatially densify deformation measurements by surveying standardized sealed stainless steel rods. On the two Caribbean islands, these measurements are generally performed on an annual basis (de Chabalier et al., 2024). For the 2024 campaign, for instance, 17 points in Martinique and 40 points in Guadeloupe were surveyed for at least three days. At Piton de la Fournaise, 70 points are measured using 3 min rapid-static
90 surveys, routinely every six months or more frequently during ongoing eruptions (Staudacher and Peltier, 2016; Peltier et al., 2026).

The OVS operate a very diverse pool of instruments in terms of manufacturers and models, as illustrated in Table 1. In addition to the Trimble, Septentrio, and Leica equipments currently in use, OVS has also historically used Topcon and Ashtech equipments.

95 The means of data transmission are also varied: even though everything is now based on an IP protocol, data can be transmitted via direct Ethernet link (very low latency, very high bandwidth, very short range), WiFi links (low latency, high bandwidth, short range), 3G/4G cellular networks (variable latency, variable bandwidth, medium range, both highly dependent on the cellular network), terrestrial internet connections (low latency, variable bandwidth, long range, but dependent on infrastructure), or VSAT satellite links (high latency, very limited bandwidth, global range) (Anglade et al., 2015). Table 2
100 summarizes the different transmission means.

2 Evolutions in GNSS data

2.1 The RINEX format

With the advent of the space era, geodetic observations have been conducted on a global scale. Geodesists, who now collaborate from multiple institutions and universities scattered around the world, needed to share their observations. This gradually
105 became more widespread with the arrival of space-based positioning systems in the 1980s, primarily the United States of America's (USA) Global Positioning System (GPS). At the end of this decade, the geodetic community, particularly its scientific stakeholders, developed and adopted a common data exchange standard to ensure compatibility between different brands of receivers and processing software. This standard, the *Receiver Independent Exchange format* (RINEX) was created by the Astronomical Institute of the University of Bern to support the large-scale EUREF-89 campaign (Gurtner and Mader,
110 1990). This international collaboration was one of the largest at that time, as it involved more than 60 GPS receivers from four different manufacturers. Following this campaign, RINEX was recommended as an international data exchange format during a dedicated workshop on GPS Exchange Formats during the *Fifth International Geodetic Symposium on Satellite Systems* in March 1989, selected among three other formats (Gurtner, 1994).

The RINEX consists of an ASCII-based standard designed to store and exchange raw GPS data, such as pseudorange,
115 carrier-phase, Doppler, signal strength, navigation messages, and meteorological measurements. Its strength lies in the fact that

it is a plain-text, human-readable file format that is independent of the receiver brand, thus greatly facilitating the exchange and processing of stored data. In this sense, it meets almost all of the optimal qualities, except for the minimum file size criterion, which could certainly have been met by selecting a binary format, but which would have been at the expense of the first two requirements, portability and readability, set out by the 1989's Symposium workshop (Gurtner, 1994).

120 However, since the late 1980s and the EUREF-89 campaign, the satellite positioning environment has changed considerably. While Russia modernized the Soviet Union's GLONASS system in the 2000s (Dach et al., 2011), several new global navigation satellite systems have reached full operational capability over the last ten years. Among these, the European Union's Galileo constellation achieved full operational status in 2016 (ESA, 2016), followed by China's BeiDou system in 2018 (CSNO, 2018). Additionally, USA launched the first satellite of its next-generation GPS Block III series in 2018 (USAF, 2018),
125 marking a major milestone in the modernization of its Global Positioning System. The Indian NAVIC and Japanese QZSS regional systems reinforce coverage in the areas concerned since 2017 and 2018 respectively (Department of Space, 2017; National Space Policy Secretariat, 2018), and several Satellite-Based Augmentation Systems (SBAS) complete the picture by broadcasting signals compatible with GNSS. Thus, the navigation and geodesy community has gradually transitioned to a multi-GNSS environment.

130 As a result of these advances, the number of available satellite observations has increased substantially. While an average of six satellites were visible in the early 1990s (Dixon, 1991), a multi-GNSS station can now observe more than sixty. In addition to numerous supplementary satellites, the new systems also provide new frequencies (for instance, Galileo introduced the L5 frequency) which themselves come with several new signals, like the AltBOC (Galileo, 2021; Lestarquit et al., 2008).

To support these changes in scale, four versions of RINEX have been developed and published since the early years: (Janssen,
135 2024)

- The original version 1, which was presented and accepted in 1989 (see above).
- Version 2 was presented at the *Second International Symposium of Precise Positioning with the Global Positioning System* in 1990. It mainly added the possibility of including tracking data from different satellite systems (*i.e.* GLONASS, SBAS) with a dedicated one-letter code. Over time, it was upgraded through several sub-versions, culminating in the
140 release of version 2.11 in 2007 (Gurtner and Estey, 2007).
- Version 3 was released in 2007. It introduces substantial changes to fully support multi-GNSS without a theoretical limit on the number of satellites. It identifies the tracking modes of each observation by introducing three-character codes (instead of two for the RINEX 2). In this sense, version 3 revives a statement already made a decade earlier by Gurtner (1994): *It is important to define precisely the meanings of the observables in RINEX observation files so that they
145 can be properly interpreted by the processing software.* Version 3 also introduced a new standardized long file naming convention, intended to provide a more intuitive description of the dataset directly within the filename. The traditional 4-character station identifier was expanded to 9 characters, in particular to allow the inclusion of a country ISO code and thereby reduce ambiguities from stations sharing the same name worldwide. Over time, it was upgraded via several sub-versions, until version 3.05 (IGS/RTCM, 2020).

150 – Version 4 was released in 2021, mainly to support the modern multi-GNSS navigation messages. However, the RINEX observation files have not undergone any major changes compared to version 3, apart from a few additions to the header fields to enhance the metadata record possibilities. It has since been updated to version 4.02 in 2024 (IGS/RTCM, 2024).

As we have illustrated, the constant improvements of the multi-GNSS environment have rendered the legacy of RINEX 2 format, which has been in use since 1993, increasingly obsolete and insufficient for handling modern GNSS data requirements, 155 despite recurring enhancements up to version 2.11. However, many local GNSS networks struggle to integrate these advances due to heterogeneous receiver hardware and outdated workflows.

2.2 `teqc`'s end of life

Additionally, the year 2019 marked another significant turning point for the GNSS community: the end of development and support for `teqc` utility developed by UNAVCO (EarthScope since 2023) (Estey and Meertens, 1999). For decades, `teqc` 160 (for *translating, editing, and quality checking*) had been considered the “Swiss army knife” of GNSS data processing: an indispensable, multi-purpose, and reliable tool for three different but complementary needs in GNSS data pre-processing: editing (splitting and splicing), quality control, and raw-to-RINEX conversion (or translation in `teqc` vocabulary). Its universality and ease of use led to its widespread adoption throughout the GNSS community over more than two decades. However, `teqc` was fundamentally designed to read/write RINEX version 2 at low-level, preventing its transition to version 3/4. The need to 165 have access to often confidential information from manufacturers to translate raw data, and above all, the retirement of its main developer, ultimately led to the software's demise (UNAVCO, 2016).

With its discontinuation, no single tool has fully matched its wide range of functionality. Very efficient alternatives exist for data editing and quality control, like `GFZRNX` (Nischan, 2016), `Anubis` (Vaclavovic and Dousa, 2015) or `RINGO` (Kawamoto et al., 2023). But for conversion, users have increasingly had to rely on OEM-provided converters (see Table 3) to produce 170 RINEX files, particularly for new-generation receivers offering full multi-GNSS support. However, the final version of `teqc` remains central to many pre-processing workflows, but its legacy status has also slowed the migration to RINEX 3/4. As a result, RINEX 2 continues to be widely used, limiting access to modern GNSS capabilities.

The abandonment of `teqc` could be perceived as a step backwards. However, returning to the use of manufacturer converters validates more than ever the statement issued 35 years ago by Gurtner and Mader (1990): *The ideal case would be if the receiver 175 manufacturers themselves developed the necessary software to translate the raw data of their receivers into RINEX because probably nobody else knows their receiver better.*

3 Motivation for the present work

This evolution from RINEX 2 to RINEX 3/4 has been smoothly managed by the space geodesy community over the 2010s decade, for several reasons: operators of global GNSS station networks intended for terrestrial reference system definition and 180 for precise orbit determination are often homogeneous networks operating hardware from the same manufacturer, or even the same model. Moreover, most of these operators are federated within the *International GNSS Service* (IGS, Johnston et al.,

2017). This international scientific association is one of the main providers of standardization within the GNSS community, or at least for its geodetic applications (Noll et al., 2009). Its efficient organization allows for clearly defined agendas with milestones for the adoption of new standards by its members (IGS Central Bureau, 2021).

185 However, this transition remains much more challenging for operators of regional and/or campaign-based GNSS networks. Indeed, the IGS mainly brings together players in space geodesy in its global dimension, such as state space agencies or national mapping agencies. In contrast, the personnel operating local GNSS networks belong to universities and research institutes with a more local footprint and are less aware of IGS decisions and the new standards that result from them. Technically, the equipment used within these networks is also often very heterogeneous, both in terms of manufacturers and generations of
190 receivers.

This situation is not specific to the IGP's OVS, but is shared by many regional GNSS infrastructures worldwide, including those operated in tectonic, volcanological, or environmental monitoring contexts (e.g. Lee et al., 2025). Comparable challenges have been identified and addressed in other large-scale initiatives such as *EarthScope/ex-UNAVCO* in North America (Zawacki et al., 2025), homonym *GeoNet* in Japan (Tsuji et al., 2013, 2017) & New Zealand (Gentle et al., 2016; Hanson et al., 2024),
195 or regional reference networks coordinated within federative frameworks like *Geosciences Australia*'s one in Australia (Brown et al., 2020), or *EUREF* in Europe (Bruyninx et al., 2019; Kenyeres et al., 2019).

Nevertheless, the OVS constitute a good example of the lasting legacy of `teqc` and the RINEX 2 standard. Over the past two decades, the three OVS have implemented very different approaches to downloading and pre-processing their GNSS data, as well as implementing them using different tools, despite the staff belonging to the same organization. Despite attempts
200 to exchange methods and associated codes, geographical distance, time zone difference between the observatories and Paris and lack of dedicated human resources have led to this situation. This same geographical distance has also resulted in limited consideration of the new standards issued by the IGS, in particular by retaining infrastructure based on the RINEX 2 format, even though new multi-GNSS-compatible receivers were gradually being installed in the field.

As shown in Table 1, the wide variety of devices employed across the OVS introduces an additional layer of complexity,
205 resulting in some observatories using hardware from certain manufacturers while others do not. This diversity necessitates a versatile and flexible approach if we want a unified pre-processing workflow.

To overcome all these limitations, we have developed two new tools, presented hereafter: The first is `rinexmod`, a RINEX header editing utility that substitutes this specific `teqc` functionality. The second tool is `autorino`, which is designed as an integrated workflow for automated download and conversion of raw data from the main manufacturers' receivers based on their
210 respective official conversion utilities. Together, these tools aim to facilitate the transition toward modern RINEX standards for heterogeneous regional and national GNSS networks, and to provide polyvalent acquisition and pre-processing solutions for a wide range of scientific GNSS infrastructures.

4 `rinexmod`: RINEX header editing and file management

215 `rinexmod` (for *RINEX Modification*) is a command-line utility developed in Python 3 designed to batch modify the headers of GNSS data files in RINEX format and rename them according to standardized conventions. It replaces a key functionality of `teqc` while adding support for modern GNSS formats and direct metadata handling. This tool ensures compatibility with recent GNSS workflows and the highest quality of embedded metadata.

4.1 `rinexmod`'s main functionalities

4.1.1 State-of-the-art and legacy version handling

220 `rinexmod` natively supports the specifications of the latest RINEX 4 format and its close predecessor RINEX 3, as well as those of the older RINEX 2 format.

4.1.2 Flexible input processing

The program accepts multiple possible inputs, including individual RINEX files, batch file lists, and can browse directory structures if a folder is given as input. `rinexmod` directly integrates file management features, eliminating the need for 225 scriptable overlays, which are usually required for this type of metadata editing operation.

4.1.3 Multi-source metadata integration

Metadata can be sourced from standardized and widespread IGS sitelogs, but also from GAMIT's `station.info` files, which is also a *de facto* standard for recording GNSS data. The user can also manually specify custom values using keywords specified as arguments.

230 4.1.4 Metadata consistency and traceability

A security mechanism is implemented to verify that the external metadata and the content of the “a priori” header’s content before modification are consistent. An equivalence comparison is performed on the receiver’s model and serial number values, which in theory should always be identical, to detect any discrepancies. If this is the case, a warning message is issued. To ensure the traceability of metadata written by `rinexmod`, the sitelog’s timestamped name is written as a comment in the 235 RINEX header.

4.1.5 Compression management

`rinexmod` natively supports various compression formats for both input and output: `gzip`, recommended as IGS standard (Romero and Ruddick, 2020) or Unix `compress` for legacy purposes, with integrated RINEX-specific Hatanaka compression (Hatanaka, 2008) or not. Uncompressed input or output is also possible.

240 4.1.6 Filename management

`rinexmod` can manage RINEX output file names based on data content, *i.e.*, the definition of the start date, file period, and data frequency. Alternatively, these values can also be manually forced. `rinexmod` can manage the legacy short naming convention and the long name convention introduced by the RINEX 3 norm to name the modded output RINEXs. Regarding the long-naming convention, three filename modes are implemented to accommodate different operational requirements:

- 245 – *Basic mode*: a simple mode to apply a strict filename period (01H or 01D), being compatible with the IGS conventions.
e.g.: FNG000GLP_R_20242220000_01D_30S_MO.crx.gz
- *Flexible mode*: the filename period is tolerant and corresponds to the actual data content, but then can be odd (e.g. 07H, 14H...). The filename start time is rounded to the hour.
e.g.: FNG000GLP_R_20242221800_06H_30S_MO.crx.gz
- 250 – *Exact mode*: the filename start time is strictly the one of the first epoch in the RINEX. Useful for specific cases, such as splicing.
e.g.: FNG000GLP_R_20242221829_06H_30S_MO.crx.gz

4.2 `rinexmod`'s workflow

Figure 8 illustrates the `rinexmod` processing workflow for RINEX files. Raw RINEX datasets are ingested and converted
255 into `RinexFile` objects. In parallel, metadata are provided from external sources such as `sitelog(s)` or `GAMIT`'s `station.info` & `apriori` file, yielding `MetaData` objects. A metadata selection step then ensures that each `RinexFile` is correctly linked to the corresponding `MetaData` for the appropriate station and epoch. The `RinexFile` objects are then updated based on their associated `MetaData` and/or user-defined manual keywords. Finally, the processed `RinexFile` objects proceed to the export stage, where they are renamed and compressed, producing fully “modded” RINEX outputs compliant with the external
260 metadata.

5 `autorino`: GNSS data acquisition and Pre-processing

The `autorino` package (for *Assisted Unloading, Treatment & Organisation of RINex Observations*) is designed for automated download and conversion of GNSS raw data from the main manufacturers' receivers (Leica, Septentrio, Topcon, Trimble, and the brand-independent BINEX) based on their respective official conversion utilities. It is developed in Python 3, relying on
265 the `geodezyx` toolbox (Sakic et al., 2019, in review) for elementary operations. A special focus has been put on conversion to RINEX 3/4 to get rid of the outdated legacy RINEX 2 standard and near real-time capability (download frequency up to 5 min).

`autorino` aims to perform the following four tasks:

- download GNSS raw data from remote GNSS receivers.

- 270
- convert GNSS raw data to RINEX 3/4 format using official conversion utilities from the main GNSS manufacturers.
 - handle RINEX files (e.g., merging, splitting, splicing, etc.) using dedicated utilities.
 - edit metadata of RINEX files (e.g., modifying header metadata, renaming filenames, editing comments, etc.) based on the `rinexmod` tool described above.

5.1 Multi-step workflow

275 `autorino` operates through a structured workflow composed of multiple *steps*. These steps are typically executed sequentially but can also be run independently. Each step may be skipped temporarily or permanently, depending on the user’s requirements. By design, a log for each step is automatically written to a dedicated folder, allowing the operator to subsequently verify that the automated workflow has been executed correctly, or, *a contrario*, identify any warnings or errors. The steps currently implemented are described below and a standard workflow is represented in Figure 9.

280 5.1.1 Download step

The download step handles remote data acquisition with configurable connection parameters. It supports two file discovery modes:

- *Ask mode*: uses interactive FTP directory exploration to locate and retrieve the desired remote files.
 - *Guess mode*: generates predicted remote file paths and tests their existence in the receiver’s file tree. This mode is
- 285 primarily intended for HTTP downloads, where directory listings are not readily available.

Additional features include timeout controls, retry mechanisms, and preliminary network ping checks to enhance reliability. Local file validation and corruption detection are performed after retrieval to ensure data integrity.

5.1.2 Convert step

The convert step transforms manufacturer-specific raw GNSS files into standardized RINEX format. An automatic detection

290 mechanism selects the appropriate converter based on input file characteristics, while manual override is also possible. `autorino` functions as a unified interface for GNSS data conversion, integrating a suite of external tools and supporting most major receiver manufacturers (Table 3).

Template-based input/output directory rules ensure consistent file organization. After conversion, `rinexmod` is automatically invoked to update RINEX headers and filenames based on external metadata sources (e.g., `sitelogs`, site configuration files).

295 Since `autorino` assumes that header metadata may be unreliable, these values are always updated. For certain fields (receiver serial number, firmware version), discrepancies between the RINEX content and external metadata trigger warnings—indicating that the external metadata source should be corrected—though the header is still overwritten.

5.1.3 Splice step

The splice step merges multiple RINEX files across time boundaries to produce a single, continuous dataset. A gap-detection
300 algorithm ensures optimal continuity and completeness, which is particularly useful for Leica receivers that create fragmented
files after interruptions in data collection.

Splicing (and splitting) requires an external RINEX manipulation tool; `autorino` supports `GFZRNX` and `Converto`
(IGN-SGM). Following splicing, `rinexmod` is again executed to validate and update metadata.

5.1.4 Split step

The split step is the inverse of splicing: it divides continuous RINEX files into smaller, defined time segments. Like the splice
305 step, it relies on an external tool (`GFZRNX` or `Converto`), and it triggers an automatic `rinexmod` metadata update.

5.1.5 Modify step

The modify step provides a stand-alone RINEX header and filename update via `rinexmod`. This is useful for tasks such
as downgrading a long name to the legacy short name convention—sometimes necessary for software like GAMIT, which
310 supports RINEX 3/4 but not the long name convention. While not recommended in general, this option ensures compatibility
in legacy workflows.

5.2 Configuration files

`autorino` relies on configuration files structured in YAML format (YAML Language Development Team, 2021). They
encapsulate all necessary parameters to perform the desired workflow (*i.e.* a set of steps) operations. The details of a configuration
315 file are provided in the supplementary materials. The nature of YAML leads to configuration files being built in different
sections:

5.2.1 Environment section

It centralizes the definition of external tool paths required for RINEX conversion and manipulation, *i.e.* the GNSS converter
binaries. General environment settings like logging verbosity, default software preferences are specified here.

320 5.2.2 Station section

It is the most important in the configuration file since it defines all site-specific metadata and device parameters required for
automated GNSS data preprocessing. It contains several subsections:

- **Site:** It contains the full site name, its 9-character site ID, the DOMES number, and the station’s geocentric coordinates.

- 325 – **Device:** It specifies whether to extract device attributes from an external sitelog or use the values provided directly (if no sitelog is available for instance). It details the antenna type & serial number, antenna eccentricity, receiver type & serial number, and firmware version. These parameters are used to rewrite the RINEX header once the conversion is done.
- **Access:** It defines how the system connects to the station to retrieve raw data, including protocol (e.g., FTP), network address, authentication credentials. . . . The concept of “*datalink*” is also introduced. This is a free keyword that groups together all stations that communicate using the same technology (same VSAT link, same WiFi network, etc.). Any simultaneous downloads from the same datalink are temporarily blocked in order to limit them to one at a time, thereby saving bandwidth and avoiding download failures.
- 330 – **Sessions:** The configuration enables the definition of multiple, independently parameterized data processing sessions. Each session specifies temporal parameters to which the step’s actions must apply (epoch ranges and periods) and a hierarchical set of workflow steps detailed above.

335 5.2.3 Include section

It provides a mechanism to reference and load additional configuration files into the current one. This feature is useful for modularizing configuration and reusing common settings across different configuration files. Typically, for sites that are equipped with the same receiver models, use the same communication protocols or internal file tree structures. . . .

Thus, with the “include” philosophy, one can distinguish three kinds of configuration files:

- 340 – *main*: general settings regarding `autorino`’s environment (converters paths, etc.) and GNSS network definition: name, sitelog path, etc.
- *site-specific*: IP addresses, site name, and code, login & password, etc.
- *profile*: common settings for a group of sites (same manufacturer, same data structure, same data transfer protocol, etc.). A site can be part of several profiles.

345 5.3 Calling `autorino` for final user

For the user, `autorino` can be easily called up in the command line interface through three main programs:

`autorino_cfgfile_run` utility provides a command-line interface for orchestrating the automated processing of the `autorino` configuration files. It accepts parameters specifying a single configuration file as input or directories containing several. The user can customize epoch ranges, site and step selection or exclusion. Upon invocation, `autorino_cfgfile_run` 350 parses the provided configuration(s), filters sites and processing steps according to user input, and executes the specified workflow steps (e.g., download, convert, split, splice, modify) for each relevant site and epoch.

`autorino_convert_rnx` provides standardized conversion capabilities for heterogeneous GNSS raw data formats. It constitutes the command-line interface for the convert step described above. Users can supply GNSS raw files as listed in Table

3, with the tool performing automatic format detection and backend conversion using the appropriate manufacturer-specific
355 converter. The output RINEX destination can be customized, and the tool also offers the option to archive the raw files in a
properly structured archive too. In that sense, it can serve as an effective substitute for `teqc`'s translation functionalities, with
the added benefit of automated archiving.

`autorino_check_rnx` is an auxiliary tool designed to perform inventory and completeness checks on RINEX files
generated by `autorino`. It scans a directory over a specified date range and records which expected daily files are present
360 or missing. For the existing RINEX files, it compiles a summary of their completeness ratio (recorded/expected epochs) in a
comprehensive table. Optionally, if an output folder is specified, the tool can also save the tables, generate basic statistics, and
produce a quick visualization plot.

The synopses of these functions are provided in the supplementary materials.

5.4 Simple use case example

365 As an illustration, a basic download-and-convert workflow for station ENCG00REU can be initiated with the following command:

```
autorino_cfgfile_run -c $AUTORINO_CFG/sites/autorino -sp download,convert  
-si ENCG00REU -ds '2025-12-31' -de '10 days ago'
```

The main options used to control the workflow are:

- `-si`, which specifies the station name to be searched in the configuration directory provided via the `-c` option;
- 370 - `-sp`, which defines the desired processing steps (download and convert);
- `-ds` and `-de`, which define the start and end dates of the processing period. Dates may be specified either in absolute or
relative form.

The logs generated for the two steps executed by this example command are provided in the supplementary materials.

6 New GNSS data acquisition and distribution pipeline

375 The GNSS data acquisition, preprocessing, and distribution pipeline has been completely redesigned, with `autorino` and
`rinexmod` now forming its core components. The complete pipeline, illustrated in Figure 10, can be divided into four main
stages:

1. Direct acquisition and conversion of raw data at the three observatories.
2. Centralization of raw and RINEX data in Paris.
- 380 3. Distribution of data to external users via the IPGP Data Center.
4. Transversal integration of the Metadata

6.1 On-site observatories acquisition and conversion

autorino was deployed in the Antilles observatories in January 2025. Using the `autorino_cfgfile_run` command, the acquisition runs daily between 00:15 and 02:15 UTC on the acquisition servers of the respective observatories via `crontab`.
385 Separate `autorino` calls are executed independently for each datalink (see Section 5.2.2), ensuring that slowdowns, timeouts, or failures at individual stations do not affect the overall network acquisition. By default, acquisition requests cover the last 10 days, and steps are skipped if the desired output files already exist. Acquired and converted data are stored in the observatory archives, processed with *GipsyX* (Bertiger et al., 2020) to produce daily station positions (with both rapid and final latency), and analyzed with *WebObs* to monitor potential volcanic deformation (Beauducel et al., 2020a). A daily `autorino_check_rnx`
390 call at 06:00 local time checks the network health for the previous 21 days.

At the La Réunion observatory, `autorino` was deployed in May 2025, with its execution orchestrated via Apache `Airflow`, an automated workflow management system (Boissier et al., 2024). `Airflow` runs on a machine separate from the acquisition server where `autorino` is installed, and it triggers `autorino_cfgfile_run` through SSH commands. Each step of a workflow is executed independently, enabling fine-grained monitoring of its progress. A set of exit codes returned by
395 `autorino_cfgfile_run` allows `Airflow` to determine whether a step completed successfully or encountered warnings or errors. When errors are detected, `Airflow` can automatically retry the affected step after a configurable delay period, providing more flexible and robust handling of temporary issues.

In case of temporary transmission interruptions, local operators may manually relaunch `autorino` for specific stations and time span. When telemetry fails but a receiver still records, technical staff can offload data during maintenance visits and
400 reintegrate them into the pipeline using `autorino_convert_rnx`, which converts and integrates raw and RINEX data into the archives.

Table 4 summarizes performance statistics for raw data downloading over the period from 1 July to 31 December 2025 for the GL, MQ and PF networks. Detailed statistics by network and station are presented in the supplementary materials. The Day + 1 success ratio for all stations, although close to or above 80%, may initially appear relatively low, since an ideal value would
405 be near 100%. However, this metric refers exclusively to data availability on Day + 1. It therefore reflects more the harsh weather, power supply, and transmission conditions at several station sites rather than limitations of the acquisition process itself.

As mentioned above, `autorino` is designed with an automatic re-download mechanism that allows missing data to be recovered in subsequent days. Over the 10-day retry period, the success ratio increases to more than 90%. Only about 7% of
410 the data require manual forced download after this period, typically once transmission conditions have improved.

For the GL network, the very high mean and maximum download times observed over the period are mainly explained by data transmitted via VSAT links, whose transfer rates are often on the order of a few hundred bytes per second. Nevertheless, `autorino` successfully retrieves the data in the vast majority of cases.

Conversion steps proceed smoothly in almost all situations; the very rare failures are subsequently corrected through manual
415 intervention (e.g., re-downloading data or checking read/write access permissions).

6.2 Centralization and backup

A daily synchronization between the observatories' archives and the IPGP site in Paris ensures off-site backup of the data. As soon as data are available, a backup GNSS processing runs for all four networks, also analyzed using *WebObs* based on *GipsyX* position solution and more recently with *SPOTGINS* (Santamaría-Gómez et al., 2025) as an alternative solution. If
420 needed, raw data can also be reconverted in Paris. Synchronized data are then automatically transmitted daily to the IPGP Data Center (IPGP-DC) for archiving and dissemination. A 20-day latency between data recording and distribution has been decided, to allow operators to report changes in equipment in the metadata before data dissemination. Before distribution, a final `rinexmod` operation is run on the RINEX files to ensure that the latest metadata are included. Manual deliveries may also occur, for example, for annual distribution of certain partner network data, such as from *Exagone/Teria*.

425 6.3 Data distribution

The IPGP-DC develops and maintains the *VOLOBISIS* Information System (<http://volobisis.ipgp.fr/>), to archive and distribute the data acquired by the IPGP's OVS to the national and international scientific communities (Satriano et al., 2016).

For OVS's GNSS data dissemination, a *GLASS* node was established in 2022 to complete *VOLOBISIS* capabilities (Fernandes et al., 2022). This node is integrated within EPOS (European Plate Observing System) as part of IPGP's involvement in
430 the TCS-Volcanology framework (Cocco et al., 2022; Bailo et al., 2023). Integration into EPOS allows access to the Data Quality Monitoring Web Portal (<https://gnssquality-epos.oma.be>), enabling long-term GNSS data quality control (Bamahry et al., 2024).

The available datasets for the different networks are:

– In RINEX 3:

- 435 – GL (OVSG, Guadeloupe): from 1 Jan. 2011 (DOY 2011-001).
- MQ (OVSM, Martinique): from 1 Jan. 2017 (DOY 2017-001).
- PF (OVPF, La Réunion): from 1 Jan. 2019 (DOY 2019-001).
- QM (IPGP's component of the REVOSIMA, Mayotte) : from 1 Jan. 2022 (DOY 2022-001).

– In RINEX 2 prior to these dates.

440 These dates correspond to the installation of the first Galileo-compatible receivers for the PF, QM, and MQ networks, as well as a dedicated RAW-to-RINEX 3 re-conversion effort for the GL network. In both cases, a conversion was therefore carried out using the raw data to obtain RINEX 3.

6.4 Transversal metadata integration

To ensure up-to-date station metadata (e.g., hardware changes), the observatories rely directly on the *M3G* database of EPOS,
445 maintained by the Royal Observatory of Belgium (ORB, Fabian et al., 2021). *M3G* is a system to upload, validate, and

distribute GNSS station metadata such as IGS-style sitelogs. It offers a user-friendly web interface for recording station hardware modifications. On-site observatory operators can thus document changes immediately on the *M3G* website after on-site interventions.

On all acquisition servers at the observatories and in Paris, a local archive of sitelogs is maintained, in order to keep access to metadata even if the internet connection is lost. This archive is synchronized with *M3G* every hour, ensuring rapid updates when modifications occur. At every stage where `rinexmod` and/or `autorino` are executed, these locally mirrored sitelogs are used to update the headers of the corresponding RINEX files.

7 Implementation and availability

`rinexmod` and `autorino` are implemented in Python 3 and distributed as open-source packages under the *GNU General Public License* (GPLv3). They have been developed and tested on a *Linux* environment (Debian or Ubuntu-like). Both are available on the Python Package Index (PyPI) and can be installed with a single command:

```
pip install autorino
pip install rinexmod
```

Their source codes are available on freely accessible GitHub repositories:

- <https://github.com/IPGP/autorino>
- <https://github.com/IPGP/rinexmod>

The `autorino` package is fully documented and distributed with practical examples. Its documentation is accessible at: <https://ipgp.github.io/autorino>. More specifically, the installation procedure is described here: <https://ipgp.github.io/autorino/installation.html>.

As mentioned above, OVS's GNSS data are available under *Creative Commons Attribution 4.0* license (CC-BY-4.0) on a GLASS node through this VOLOBSIS portal's landing page: <http://volobsis.ipgp.fr/data/access-gnss-data>.

8 Conclusion

The shift to a multi-GNSS environment has redefined both the opportunities and the challenges of geodetic monitoring. For global networks coordinated under the IGS, the adoption of RINEX 3/4 and the phasing out of `teqc` were absorbed through coordinated strategies, standardized hardware, and centralized expertise. In contrast, regional and campaign-based networks—such as those operated by the IPGP's volcanological observatories—have faced persistent barriers linked to heterogeneous instrumentation, limited human resources, and geographically isolated operations. These barriers historically resulted in fragmented workflows, heavy reliance on legacy RINEX 2, and limited uptake of modern standards, thereby constraining the scientific and operational potential of the networks.

The `rinexmod` and `autorino` tools presented in this work provide practical, open, and sustainable solutions to these challenges. By replacing critical `teqc` functionalities while fully supporting RINEX 3/4 conventions, `rinexmod` ensures metadata consistency and compatibility with international standards. Meanwhile, `autorino` offers a versatile and modular workflow capable of automated raw data acquisition, manufacturer-based conversion, splicing/splitting, and systematic metadata
480 injection—enabling a unified pre-processing chain across diverse receivers and transmission infrastructures. The Python-based development and packaging facilitate their potential integration within containerized environments (e.g., Docker, Kubernetes), enabling potential cloud deployment. The design of both tools emphasizes interoperability, reproducibility, and near real-time capability, which are critical for observatories tasked with continuous volcanic and seismic hazard monitoring.

Operational deployment in La Réunion, Guadeloupe, Martinique, and Mayotte demonstrates that these tools effectively
485 bridge the gap between heterogeneous local infrastructures and the standardized practices required for multi-GNSS geodesy. They not only facilitate robust daily operations (including campaign surveys and near real-time monitoring), but also ensure long-term data quality and archival consistency, thereby enhancing the value of datasets for both hazard response and fundamental geoscience research.

Thus, these tools provide a foundation for scaling regional networks toward greater interoperability with international
490 initiatives such as the IGS or EPOS, while remaining adaptable to local operational constraints. By lowering the technical barriers associated with multi-GNSS adoption, they contribute to a more inclusive and sustainable geodetic ecosystem—one where small and regional networks can fully exploit the capabilities of modern GNSS to monitor Earth processes in near real time.

. See section 7.

495 . See section 7.

. PS, PB, JMS, and JBC defined the needs and requirements; PS, PB, JMS, and CP designed the new pipeline; PS and PB programmed and tested the software; PS, PB, SD, AA, and CP implemented it operationally; PB, CG, AB, CV, and CP set up the underlying IT infrastructure; PS wrote the article. All authors have read and approved the final manuscript.

. The authors declare that they have no competing financial or non-financial interests in relation to this work.

500 . The Volcanological and Seismological Observatories of the Institut de physique du globe de Paris supported this work. The authors acknowledge the technical and scientific staff of each observatory for the daily maintenance of the ground stations, the telecommunication means, and the IT infrastructure.

Mayotte’s REVOSIMA network is funded by the Ministry for Ecological Transition (MTE), the Ministry of Higher Education and Research (MESR), the Ministry of the Interior and Overseas (MIOM), with the support of the French Ministry for Armed Forces (MINARM).

505 The authors thank Giorgi Khazaradze Tsilosani and an anonymous referee for their valuable comments during the review process which helped to improve the manuscript. The authors acknowledge Félix Leger for the initial implementation of `rinexmod`, Arianna Boisseau for the new features she added in `rinexmod`’s code, and Martin Valgur & Roman Sermiagin for their collaborative improvements via `rinexmod`’s GitHub. The authors also thank Angela Schlesinger, Émilie Klein & Semih Ergintav for their feedback on using `autorino` & `rinexmod`, which enables continuous improvement of the software’s functionalities.

510 . Members of the *OVPF Team*:

François Beauducel, Christophe Brunet, Kevin Canjamalé, Philippe Catherine, Nicolas Desfete, Zacharie Duputel, Fabrice F. Fontaine, Luciano Garavaglia, Philippe Kowalski, Angèle Laurent, Frédéric Lauret, Diane Pacaud, Aline Peltier, Frédérick Pesqueira, Nicolas Villeneuve

Members of the *OVSF Team*:

Carole Berthod, Imen Defferrard, Élodie Chilin-Eusebe, Gaëtan “Thierry” Kitou, Christian Lambert, Julien Novar, Joanny Pierre, Ivan

515 Vlastelic

Members of the *OVSF Team*:

Jordane Corbeau, Jean-Gilles Gabriel, Frédéric Jadelus, Adélaïde “Jean-Marc” Lavenaire, Anne-Solenne Leygnac, David Melezan, Samantha Phemius, Jérôme Vergne

References

- 520 Anglade, A., Lemarchand, A., Saurel, J.-M., Clouard, V., Bouin, M.-P., De Chabaliér, J.-B., Tait, S., Brunet, C., Nercessian, A., Beauducel, F., Robertson, R., Lynch, L., Higgins, M., and Latchman, J.: Significant Technical Advances in Broadband Seismic Stations in the Lesser Antilles, *Advances in Geosciences*, 40, 43–50, <https://doi.org/10.5194/adgeo-40-43-2015>, 2015.
- Bailo, D., Paciello, R., Michalek, J., Cocco, M., Freda, C., Jeffery, K., and Atakan, K.: The EPOS Multi-Disciplinary Data Portal for Integrated Access to Solid Earth Science Datasets, *Scientific Data*, 10, 784, <https://doi.org/10.1038/s41597-023-02697-9>, 2023.
- 525 Bamahry, F., Legrand, J., Bruyninx, C., and Fabian, A.: EPOS-GNSS Data Quality Monitoring Web Portal, in: Together Again for Geodesy, edited by Freymueller, J. T. and Sánchez, L., vol. 157, pp. 401–409, Springer Nature Switzerland, Cham, https://doi.org/10.1007/1345_2024_264, 2024.
- Beauducel, F., Lafon, D., Béguin, X., Saurel, J.-M., Bosson, A., Mallarino, D., Boissier, P., Brunet, C., Lemarchand, A., Anténor-Habazac, C., Nercessian, A., and Fahmi, A. A.: WebObs: The Volcano Observatories Missing Link Between Research and Real-Time Monitoring, *Frontiers in Earth Science*, 8, 48, <https://doi.org/10.3389/feart.2020.00048>, 2020a.
- 530 Beauducel, F., Peltier, A., Villié, A., and Suryanto, W.: Mechanical Imaging of a Volcano Plumbing System From GNSS Unsupervised Modeling, *Geophysical Research Letters*, 47, e2020GL089419, <https://doi.org/10.1029/2020GL089419>, 2020b.
- Bertiger, W., Bar-Sever, Y., Dorsey, A., Haines, B., Harvey, N., Hemberger, D., Heflin, M., Lu, W., Miller, M., Moore, A. W., Murphy, D., Ries, P., Romans, L., Sibois, A., Sibthorpe, A., Szilagyi, B., Vallisneri, M., and Willis, P.: GipsyX/RTGx, a New Tool Set for Space
- 535 Geodetic Operations and Research, *Advances in Space Research*, 66, 469–489, <https://doi.org/10.1016/j.asr.2020.04.015>, 2020.
- Bock, O., Bosser, P., Flamant, C., Doerflinger, E., Jansen, F., Fages, R., Bony, S., and Schnitt, S.: Integrated Water Vapour Observations in the Caribbean Arc from a Network of Ground-Based GNSS Receivers during EUREC⁴ A, *Earth System Science Data*, 13, 2407–2436, <https://doi.org/10.5194/essd-13-2407-2021>, 2021.
- Boissier, P., Griot, C., and Pacaud, D.: Orchestration de Flux de Données Avec Apache Airflow à l’Observatoire Volcanologique Du Piton
- 540 de La Fournaise, in: JRES (Journées Réseaux de l’enseignement et de La Recherche) 2024, Renater, Rennes, France, 2024.
- Brown, N., Dawson, J., and Ruddick, R.: Positioning Australia for the Future, *Engineering*, 6, 857–859, <https://doi.org/10.1016/j.eng.2020.07.012>, 2020.
- Bruyninx, C., Legrand, J., Fabian, A., and Pottiaux, E.: GNSS Metadata and Data Validation in the EUREF Permanent Network, *GPS Solutions*, 23, 106, <https://doi.org/10.1007/s10291-019-0880-9>, 2019.
- 545 Cayol, V., Peltier, A., Froger, J.-L., and Beauducel, F.: Monitoring Volcano Deformation, in: Hazards and Monitoring of Volcanic Activity 2: Seismology, Deformation and Remote Sensing, edited by Lénat, J.-F., pp. –, Wiley-ISTE, London, 2022.
- Cocco, M., Freda, C., Atakan, K., Bailo, D., Saleh-Contell, K., Lange, O., and Michalek, J.: The EPOS Research Infrastructure: A Federated Approach to Integrate Solid Earth Science Data and Services, *Annals of Geophysics*, 65, DM208, <https://doi.org/10.4401/ag-8756>, 2022.
- CSNO: The BDS-3 Preliminary System Is Completed to Provide Global Services, Press Release, BeiDou Navigation Satellite System, 2018.
- 550 Dach, R., Schmid, R., Schmitz, M., Thaller, D., Schaer, S., Lutz, S., Steigenberger, P., Wübbena, G., and Beutler, G.: Improved Antenna Phase Center Models for GLONASS, *GPS Solutions*, 15, 49–65, <https://doi.org/10.1007/s10291-010-0169-5>, 2011.
- de Chabaliér, J.-B. et al.: PREST: Volcans, Séismes et Tsunamis Dans La Caraïbe, Technical Report, European Union Interreg Caraïbes Program, 2024.
- Department of Space: Desi Global Positioning System, Press Release, Press Information Bureau, Government of India, 2017.

- 555 Dixon, T. H.: An Introduction to the Global Positioning System and Some Geological Applications, *Reviews of Geophysics*, 29, 249–276, <https://doi.org/10.1029/91RG00152>, 1991.
- Dzurisin, D.: Volcano Geodesy: Challenges and Opportunities for the 21st Century, *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 358, 1547–1566, <https://doi.org/10.1098/rsta.2000.0603>, 2000.
- ESA: Galileo Begins Serving the Globe, Press Release, European Space Agency, 2016.
- 560 Estey, L. H. and Meertens, C. M.: TEQC: The Multi-Purpose Toolkit for GPS/GLONASS Data, *GPS Solutions*, 3, 42–49, <https://doi.org/10.1007/PL00012778>, 1999.
- Fabian, A., Bruyninx, C., Miglio, A., and Legrand, J.: M3G - Metadata Management and Distribution System for Multiple GNSS Networks, <https://doi.org/10.24414/ROB-GNSS-M3G>, 2021.
- FDSN: Network Codes, Tech. rep., International Federation of Digital Seismograph Networks (FDSN), 2025.
- 565 Fernandes, R., Bruyninx, C., Crocker, P., Menut, J.-L., Socquet, A., Vergnolle, M., Avallone, A., Bos, M., Bruni, S., Cardoso, R., Carvalho, L., Cotte, N., D'Agostino, N., Deprez, A., Andras, F., Geraldés, F., Janex, G., Kenyeres, A., Legrand, J., Ngo, K.-M., Lidberg, M., Liwosz, T., Manteigueiro, J., Miglio, A., Soehne, W., Holger, S., Toth, S., Dousa, J., Ganas, A., Kapetanidis, V., and Batti, G.: A New European Service to Share GNSS Data and Products, *Annals of Geophysics*, 65, DM317, <https://doi.org/10.4401/ag-8776>, 2022.
- Fontaine, F. R., Komorowski, J.-C., Corbeau, J., Burtin, A., De Chabalier, J.-B., Grandin, R., Saurel, J. M., Agrinier, P., Moune, S., Jadelus, F.,
- 570 Melezan, D., Gabriel, J.-G., Vidal, C., Zimmermann, B., Vatou, D., Koziol, J., Lavenaire, J. M., Moretti, R., Lemarchand, A., Labasque, T., Blard, P.-H., Tibari, B., Zimmermann, L., Aubaud, C., Vergne, J., Andrieu, A., Filliaert, A., Chilin-Eusebe, E., Wahlgren, S. Z., Inostroza, M., Métaixian, J.-P., Potier, A., Fernandez, I., Robert, V., Deroussi, S., Carazzo, G., Tait, S., Vlastelic, I., Jessop, D. E., Bonaimé, S., Le Friant, A., Chaussidon, M., Michaud-Dubuy, A., Retailleau, L., Di Muro, A., Allard, P., and Satriano, C.: Ongoing Multiparameter Unrest at the Montagne Pelée Volcano on Martinique from 2019 to 2024, *Scientific Reports*, 15, 23 189, <https://doi.org/10.1038/s41598-025-05641-6>, 2025.
- 575 Galileo, ICD.: European GNSS (Galileo) Open Service Signal-in-Space Interface Control Document, Issue 2.0, 2021.
- Gentle, P., Gledhill, K., and Blick, G.: The Development and Evolution of the GeoNet and PositionNZ GNSS Continuously Operating Network in New Zealand, *New Zealand Journal of Geology and Geophysics*, 59, 33–42, <https://doi.org/10.1080/00288306.2015.1127821>, 2016.
- Gurtner, W.: RINEX: The Receiver-Independent Exchange Format, *GPS world*, 5, 48–52, 1994.
- 580 Gurtner, W. and Estey, L.: RINEX: The Receiver Independent Exchange Format Version 2.11, Tech. Rep. 2.11, International GNSS Service (IGS) / UNAVCO, Astronomical Institute, University of Bern, 2007.
- Gurtner, W. and Mader, G.: The RINEX Format: Current Status, Future Developments, in: *Proceedings of the Second International Symposium of Precise Positioning with the Global Positioning System*, Pp. 977ff, Ottawa, 1990.
- Hanson, J. B., Sherburn, S., Behr, Y., Britten, K. M., Hughes, E. C., Jarvis, P. A., Lamb, O. D., Mazot, A., Fitzgerald, R. H., Scott, B. J.,
- 585 Fournier, N., Volcano Monitoring Group, and GeoNet team: Twenty Years of Volcano Data at GeoNet—Collection, Custodianship, and Evolution of Open Data on New Zealand's Volcanoes, *Bulletin of Volcanology*, 86, 81, <https://doi.org/10.1007/s00445-024-01769-x>, 2024.
- Hatanaka, Y.: A Compression Format and Tools for GNSS Observation Data, *Bulletin of the Geographical Survey Institute*, 55, 2008.
- IGS Central Bureau: International GNSS Service (IGS) 2021+ Strategic Plan, 2021.
- IGS/RTCM: RINEX Version 3.05, Tech. Rep. 3.05, International GNSS Service / RTCM - SC104, 2020.
- 590 IGS/RTCM: RINEX Version 4.02, Tech. Rep. 4.02, International GNSS Service / RTCM, 2024.
- IPGP: GNSS, Seismic Broadband and Strong Motion Permanent Networks in West Indies, <https://doi.org/10.18715/ANTILLES.WI>, 2008.

- IPGP: Data collection of the seismological and volcanological observatory of Guadeloupe, <https://doi.org/10.18715/GUADELOUPE.OVSG>, 2021a.
- IPGP: Data collection of the seismological and volcanological observatory of Martinique, <https://doi.org/10.18715/MARTINIQUE.OVSM>, 595 2021b.
- IPGP: Data collection of the volcanological observatory of Piton de la Fournaise, <https://doi.org/10.18715/REUNION.OVPF>, 2021c.
- Janssen, V.: Understanding the RINEX Format, in: Proceedings of Association of Public Authority Surveyors Conference (APAS2024), pp. 3–18, 2024.
- Johnston, G., Riddell, A., and Hausler, G.: The International GNSS Service, in: Springer Handbook of Global Navigation Satellite Systems, 600 pp. 967–982, Springer International Publishing, Cham, https://doi.org/10.1007/978-3-319-42928-1_33, 2017.
- Kawamoto, S., Takamatsu, N., and Abe, S.: RINGO: A RINEX Pre-Processing Software for Multi-GNSS Data, Earth, Planets and Space, 75, 54, <https://doi.org/10.1186/s40623-023-01811-w>, 2023.
- Kenyeres, A., Bellet, J. G., Bruyninx, C., Caporali, A., De Doncker, F., Droscak, B., Duret, A., Franke, P., Georgiev, I., Bingley, R., Huisman, L., Jivall, L., Khoda, O., Kollo, K., Kurt, A. I., Lahtinen, S., Legrand, J., Magyar, B., Mesmaker, D., Morozova, K., Nágl, J., Özdemir, 605 S., Papanikolaou, X., Parseliunas, E., Stangl, G., Ryczywolski, M., Tangen, O. B., Valdes, M., Zurutuza, J., and Weber, M.: Regional Integration of Long-Term National Dense GNSS Network Solutions, GPS Solutions, 23, 122, <https://doi.org/10.1007/s10291-019-0902-7>, 2019.
- Lee, S.-J., Yun, H.-S., Yoon, H.-M., and Lee, S.-H.: Evaluating GNSS Infrastructure Readiness for IGS Contribution: The Case of King Sejong Station, Antarctica, Scientific Reports, 15, 44 064, <https://doi.org/10.1038/s41598-025-26151-5>, 2025.
- 610 Lemoine, A., Briole, P., Bertil, D., Roullé, A., Foumelis, M., Thinon, I., Raucoules, D., de Michele, M., Valtý, P., and Hoste Colomer, R.: The 2018–2019 Seismo-Volcanic Crisis East of Mayotte, Comoros Islands: Seismicity and Ground Deformation Markers of an Exceptional Submarine Eruption, Geophysical Journal International, 223, 22–44, <https://doi.org/10.1093/gji/ggaa273>, 2020.
- Lestarquit, L., Artaud, G., and Issler, J.-L.: AltBOC for Dummies or Everything You Always Wanted to Know about AltBOC, in: Proceedings of the 21st International Technical Meeting of the Satellite Division of the Institute of Navigation (ION GNSS 2008), pp. 961–970, 2008.
- 615 Moretti, R., Komorowski, J.-C., Ucciani, G., Moune, S., Jessop, D., De Chabaliér, J.-B., Beauducel, F., Bonifacie, M., Burtin, A., Vallée, M., Deroussi, S., Robert, V., Gibert, D., Didier, T., Kitou, T., Feuillet, N., Allard, P., Tamburello, G., Shreve, T., Saurel, J.-M., Lemarchand, A., Rosas-Carbajal, M., Agrinier, P., Le Friant, A., and Chaussidon, M.: The 2018 Unrest Phase at La Soufrière of Guadeloupe (French West Indies) Andesitic Volcano: Scrutiny of a Failed but Prodromal Phreatic Eruption, Journal of Volcanology and Geothermal Research, 393, 106 769, <https://doi.org/10.1016/j.jvolgeores.2020.106769>, 2020.
- 620 National Space Policy Secretariat: Start of QZSS Services, Announcement, Cabinet Office, Government of Japan, 2018.
- Nischan, T.: GFZRNX - RINEX GNSS Data Conversion and Manipulation Toolbox, GFZ Data Services, <https://doi.org/10.5880/GFZ.1.1.2016.002>, 2016.
- Noll, C., Bock, Y., Habrich, H., and Moore, A.: Development of Data Infrastructure to Support Scientific Analysis for the International GNSS Service, Journal of Geodesy, 83, 309–325, <https://doi.org/10.1007/s00190-008-0245-6>, 2009.
- 625 Pantobe, L., Chanard, K., Burtin, A., Sakic, P., and Komorowski, J.-C.: Integrating GNSS and Hydrological Data to Understand Seasonal Microseismicity at La Soufrière de Guadeloupe, Journal of Geophysical Research, in press.
- Peltier, A., Beauducel, F., Villeneuve, N., Ferrazzini, V., Di Muro, A., Aiuppa, A., Derrien, A., Jourde, K., and Taisne, B.: Deep Fluid Transfer Evidenced by Surface Deformation during the 2014–2015 Unrest at Piton de La Fournaise Volcano, Journal of Volcanology and Geothermal Research, 321, 140–148, <https://doi.org/10.1016/j.jvolgeores.2016.04.031>, 2016.

- 630 Peltier, A., Saur, S., Ballu, V., Beauducel, F., Briole, P., Chanard, K., Dausse, D., De Chabalier, J.-B., Grandin, R., Rouffiac, P., Tranchant, Y.-T., De Berc, M. B., Besançon, S., Boissier, P., Broucke, C., Brunet, C., Canjamalé, K., Carme, E., Catherine, P., Colombain, A., Crawford, W., Daniel, R., Dectot, G., Desfete, N., Doubre, C., Dumouch, T., Griot, C., Grunberg, M., Jund, H., Kowalski, P., Lauret, F., Lebreton, J., Pesqueira, F., Tronel, F., Valty, P., and Van Der Woerd, J.: Ground Deformation Monitoring of the Eruption Offshore Mayotte, *Comptes Rendus. Géoscience*, 354, 171–193, <https://doi.org/10.5802/crgeos.176>, 2023.
- 635 Peltier, A., Villeneuve, N., Boissier, P., Brunet, C., Canjamalé, K., Catherine, P., Chevrel, M. O., Derrien, A., Di Muro, A., Desfete, N., Duputel, Z., J. Fontaine, F., Frangieh, M., Garavaglia, L., Griot, C., Journeau, C., Kowalski, P., Laborde, C., Lauret, F., Pesqueira, F., Richter, N., Smittarello, D., and Vaitilingom, A.: Ten Years of GNSS Field Campaigns Covering a Full Eruptive Cycle at Piton de La Fournaise (2014–2023), *Bulletin of Volcanology*, 88, 19, <https://doi.org/10.1007/s00445-026-01944-2>, 2026.
- Poland, M., Hamburger, M., and Newman, A.: The Changing Shapes of Active Volcanoes: History, Evolution, and Future Challenges for
640 Volcano Geodesy, *Journal of Volcanology and Geothermal Research*, 150, 1–13, <https://doi.org/10.1016/j.jvolgeores.2005.11.005>, 2006.
- Ravanelli, M., Occhipinti, G., Savastano, G., Komjathy, A., Shume, E. B., and Crespi, M.: GNSS Total Variometric Approach: First Demonstration of a Tool for Real-Time Tsunami Genesis Estimation, *Scientific Reports*, 11, 3114, <https://doi.org/10.1038/s41598-021-82532-6>, 2021.
- Ravanelli, M., Astafyeva, E., Sakic, P., Baucry, R., and Crespi, M.: An Insight into ALTRUIST: How to Use GNSS Variometry for Natural
645 Hazards Detecting and Monitoring, in: EGU General Assembly Conference Abstracts, p. 12315, 2024.
- REVOSIMA, Institut de physique du globe de Paris (IPGP), Bureau de recherches géologiques et minières (BRGM), Institut français de recherche pour l'exploitation de la mer (IFREMER), and Centre national de la recherche scientifique (CNRS): Data collection of the Mayotte volcanological and seismological monitoring network (REVOSIMA), <https://doi.org/10.18715/MAYOTTE.REVOSIMA>, 2021.
- Romero, N. and Ruddick, R.: RINEX 2.11: Compression Method Clarification Addendum, Technical Report, IGS RINEX Working Group,
650 ESA/ESOC Navigation Support Office; Geoscience Australia, Canberra, Australia, 2020.
- Sakic, P., Mansur, G., Kitpracha, C., and Ballu, V.: The geodeZYX Toolbox: A Versatile Python 3 Toolbox for Geodetic-Oriented Purposes, <https://doi.org/10.5880/GFZ.1.1.2019.002>, 2019.
- Sakic, P., Männel, B., Bradke, M., Ballu, V., de Chabalier, J.-B., and Lemarchand, A.: Estimation of Lesser Antilles Vertical Velocity Fields Using a GNSS-PPP Software Comparison, in: International Association of Geodesy Symposia, Springer, Berlin, Heidelberg,
655 https://doi.org/10.1007/1345_2020_101, 2020.
- Sakic, P., Nahmani, S., and Mansur, G. B.: Geodezyx: A Versatile Python Toolbox for Geodetic Data Manipulation with GNSS Processing Pedagogical Features, in: Geodesy for a Changing Environment - Proceedings of the 2025 IAG Scientific Assembly, in review.
- Santamaría-Gómez, A., Boy, J.-P., Feriol, F., Gravelle, M., Loyer, S., Nahmani, S., Nicolas, J., García Pallero, J. L., Panetier, A., Pollet, A., Sakic, P., and Wöppelmann, G.: Monitoring the Earth's Deformation with the SPOTGINS Series, *Earth System Science Data*, 17,
660 5833–5840, <https://doi.org/10.5194/essd-17-5833-2025>, 2025.
- Satriano, C., Lemarchand, A., Saurel, J.M.M., Pardo, C., Vincent, D., de Chabalier, J.B., Beauducel, F., Shapiro, N., and Cyril, G.: VOLOBSIS: An Infrastructure for Open Access to Seismic and GNSS Data from the Volcanological and Seismological French Observatories, in: AGU Fall Meeting Abstracts, vol. 2016, pp. IN21C–1747, 2016.
- Staudacher, T. and Peltier, A.: Ground Deformation at Piton de La Fournaise, a Review from 20 Years of GNSS Monitoring, in: Active
665 Volcanoes of the Southwest Indian Ocean: Piton de La Fournaise and Karthala, edited by Bachelery, P., Lenat, J.-F., Di Muro, A., and Michon, L., pp. 251–269, Springer Berlin Heidelberg, Berlin, Heidelberg, https://doi.org/10.1007/978-3-642-31395-0_15, 2016.

- Tsuji, H., Miyagawa, K., Yamaguchi, K., Yahagi, T., Oshima, K., Yamao, H., and Furuya, T.: Modernization of GEONET from GPS to GNSS, Bulletin of the Geospatial Information Authority of Japan, 2013.
- 670 Tsuji, H., Hatanaka, Y., Hiyama, Y., Yamaguchi, K., Furuya, T., Kawamoto, S., and Fukuzaki, Y.: Twenty-Year Successful Operation of GEONET, Bulletin of the Geospatial Information Authority of Japan, 2017.
- UNAVCO: Geodetic Data Services Plan for GNSS Modernization: Data Formats and Preprocessing Tools, Technical Report, UNAVCO Geodetic Data Services Advisory Committees Review, 2016.
- USAF: First GPS III Satellite Successfully Launched, Press Release, Los Angeles Air Force Base, 2018.
- Vaclavovic, P. and Dousa, J.: G-Nut/Anubis: Open-Source Tool for Multi-GNSS Data Monitoring with a Multipath Detection for New
675 Signals, Frequencies and Constellations, in: IAG 150 Years, edited by Rizos, C. and Willis, P., vol. 143, pp. 775–782, Springer International Publishing, Cham, https://doi.org/10.1007/1345_2015_97, 2015.
- Van Rijnsingen, E. M., Calais, E., Jolivet, R., De Chabalier, J.-B., Jara, J., Symithe, S., Robertson, R., and Ryan, G. A.: Inferring Interseismic Coupling Along the Lesser Antilles Arc: A Bayesian Approach, *Journal of Geophysical Research: Solid Earth*, 126, e2020JB020677, <https://doi.org/10.1029/2020JB020677>, 2021.
- 680 Van Rijnsingen, E. M., Calais, E., Jolivet, R., de Chabalier, J.-B., Robertson, R., Ryan, G. A., and Symithe, S.: Ongoing Tectonic Subsidence in the Lesser Antilles Subduction Zone, *Geophysical Journal International*, 231, 319–326, <https://doi.org/10.1093/gji/ggac192>, 2022.
- YAML Language Development Team: YAML Ain't Markup Language (YAML™) Version 1.2, 2021.
- Zawacki, E. E., Charlevoix, D. J., Meertens, C. M., Freymueller, J. T., and Van Dam, T.: A History of UNAVCO: Four Decades of Advancing Geodesy, *Perspectives of Earth and Space Scientists*, 6, e2025CN000276, <https://doi.org/10.1029/2025CN000276>, 2025.

685 **List of Figures**

	1	Map of the GL GNSS Network, managed by the OVSG at the Guadeloupe Archipelago island. a) Guadeloupe archipelago view & b) Soufrière de Guadeloupe volcano’s vicinity. For the sake of readability, the first four characters only of the station codes are represented. SBL000BLM located in St Bartélémy is not represented.	25
690	2	Map of the MQ GNSS Network, managed by the OVSM at Martinique island. a) Martinique Island view & b) Montagne Pelée volcano’s vicinity. For the sake of readability, the first four characters only of the station codes are represented.	26
	3	Maps of the PF GNSS Network, managed by the OVPF at La Réunion. a) South-East of La Réunion Island view & b) Piton de la Fournaise volcano’s vicinity (Enclos Fouqué caldera). For the sake of readability, the first four characters only of the station codes are represented.	27
695	4	Map of the QM GNSS Network, the IPGP’s component of the REVOSIMA. For the sake of readability, the first four characters only of the station codes are represented. GLOR00ATF located in Grande Glorieuse is not represented.	28
	5	Cumulative sum of daily RINEX files produced by the OVS distributed among their four networks, from 2000 to mid-2025.	29
700	6	Cumulative sum over time of the number of GNSS stations installed among the OVS’s four networks, from 2000 to mid-2025.	30
	7	Proportion over time of the different GNSS systems recorded by OVS’s GNSS receivers, from 2000 to mid-2025.	31
	8	Standard workflow for <code>rinexmod</code>	32
	9	Standard workflow for <code>autorino</code>	33
705	10	General pipeline for the acquisition, integration and distribution of GNSS Data for the IPGP’s OVS	34






Figure 1. Map of the GL GNSS Network, managed by the OVSG at the Guadeloupe Archipelago island. **a)** Guadeloupe archipelago view & **b)** Soufrière de Guadeloupe volcano's vicinity. For the sake of readability, the first four characters only of the station codes are represented. SBL000BLM located in St Bartélémy is not represented.



(a)

Figure 2. Map of the MQ GNSS Network, managed by the OVSM at Martinique island. **a)** Martinique Island view & **b)** Montagne Pelée volcano's vicinity. For the sake of readability, the first four characters only of the station codes are represented.




Figure 3. Maps of the PF GNSS Network, managed by the OVPF at La Réunion. **a)** South-East of La Réunion Island view & **b)** Piton de la Fournaise volcano's vicinity (Enclos Fouqué caldera). For the sake of readability, the first four characters only of the station codes are represented.




Figure 4. Map of the QM GNSS Network, the IPGP's component of the REVOSIMA. For the sake of readability, the first four characters only of the station codes are represented. GLOR00ATF located in Grande Glorieuse is not represented.




Figure 5. Cumulative sum of daily RINEX files produced by the OVS distributed among their four networks, from 2000 to mid-2025.




Figure 6. Cumulative sum over time of the number of GNSS stations installed among the OVS's four networks, from 2000 to mid-2025.




Figure 7. Proportion over time of the different GNSS systems recorded by OVS's GNSS receivers, from 2000 to mid-2025.




Figure 8. Standard workflow for rinexmod




Figure 9. Standard workflow for *autorino*




Figure 10. General pipeline for the acquisition, integration and distribution of GNSS Data for the IPGP's OVS

List of Tables

	1	GNSS receivers manufacturers and models currently operated by the OVS	36
	2	Data transmission means for GNSS data retrieval operated by the OVS	37
	3	Raw file types, with associated manufacturers and converters supported by <code>autorino</code>	38
710	4	Download statistics for GL, MQ and PF network between 1 July and 31 December 2025. $D+n$ stands for <i>Day</i> + n i.e. the n -th day after the corresponding recorded data. <i>After</i> $D+10$ metrics reflect manually-forced data download	39

<i># of receivers</i>	PF	GL	MQ	QM	total per model
TRIMBLE NETR9	3	15	4	4	26
TRIMBLE ALLOY	4	1	4	0	9
SEPTENTRIO POLARX5	20	0	0	0	20
LEICA GR25	0	6	4	0	10
LEICA GR50	0	3	3	0	6
total per network	27	25	15	4	71

Table 1. GNSS receivers manufacturers and models currently operated by the OVS

<i># of transmission</i>	PF	GL	MQ	QM	total per transmission
Direct Ethernet	0	1	1	0	2
Internet	1	0	0	4	5
WiFi	14	16	8	0	38
Cellular	12	1	2	0	15
VSAT	0	7	4	0	11
total per network	27	25	15	4	71

Table 2. Data transmission means for GNSS data retrieval operated by the OVS

Manufacturer	Converter	File type	Linux compatibility
Leica	mdb2rinex	.mdb	Linux binary
Septentrio	sbf2rin	.sbf	Linux binary
Topcon	tps2rin	.tps	Windows executable via Linux Wine emulation
Trimble (official)	t0xConvert	.T0n	Linux binary
Trimble (docker)	trm2rinex	.T0n	Windows executable via Wine in an Ubuntu-based Docker container
Universal (BINEX)	convbin (RTKLIB-explorer)	.bnx	Linux binary
Universal (legacy)	teqc	—	Linux binary

Table 3. Raw file types, with associated manufacturers and converters supported by `autorino`.

	GL	MQ	PF
total # of files fetched	4046	2254	4555
# of files fetched at D+1	3280	1727	3861
# of files fetched at D+2	174	120	142
# of files fetched b/w D+3 and D+10	319	396	173
# of files fetched after D+10	273	11	379
success ratio at D+1	81.07%	76.62%	84.76%
success ratio at D+2	85.37%	81.94%	87.88%
success ratio at D+10	93.25%	99.51%	91.68%
remaining ratio after D+10	6.75%	0.49%	8.32%
download mean time	1768.54s	417.77s	116.29s
download median time	22.93s	8.97s	53.51s
download min. time	0.94s	0.12s	2.22s
download max. time	38190.07s	5220.14s	1171.08s

Table 4. Download statistics for GL, MQ and PF network between 1 July and 31 December 2025. $D+n$ stands for *Day + n* i.e. the n -th day after the corresponding recorded data. *After D+10* metrics reflect manually-forced data download