

Field-validated imaging of decadal and seasonal changes in permafrost bedrock using quantitative electrical resistivity tomography (Zugspitze, Germany/Austria)

Riccardo Scandroglio¹, Samuel Weber^{2,3}, Jonas K. Limbrock⁴, and Michael Krautblatter¹

¹Technical University of Munich, Chair of Landslide Research, Munich, Germany

²Climate Change, Extremes and Natural Hazards in Alpine Regions Research Center CERC, Switzerland

³WSL Institute for Snow and Avalanche Research SLF, Davos, Switzerland

⁴University of Bonn, Institute of Geosciences, Geophysics Section, Bonn, Germany

Correspondence: Riccardo Scandroglio (r.scandroglio@tum.de)

Abstract. Ongoing permafrost degradation in alpine regions requires monitoring methods that accurately decipher spatial and temporal dynamics. Electrical resistivity tomography (ERT) is widely applied in bedrock permafrost, yet its outputs are often interpreted only qualitatively. Quantitative evaluation of ERT results, however, is crucial for improving process understanding and enhancing predictions of permafrost-related slope instability. In this study, we present a 17-year monitoring of permafrost rock slopes on Mount Zugspitze (Germany/Austria) with monthly ERT campaigns. ERT data are combined with rock temperatures at four depths to establish field-based temperature–resistivity calibrations and to validate existing laboratory-derived relations. Both approaches agree well in the freezing range; however, field calibrations tend to yield higher resistivities at subzero temperatures and reveal substantial spatial heterogeneity. Incorporating reciprocal measurements refines the existing error model, increases image resolution, and improves the identification of subsurface features. Over ~~ten~~10 years, the measured rock temperature increased by 1°C, accompanied by a 25% decrease in resistivity. The permanently frozen surface decreased by 40%, with degradation ~~rated~~rates up to $-4.2 \text{ k}\Omega\text{m}^{-1}$. Extrapolating these trends would result in the loss of 65% of permafrost within a decade. Thermal forcing controls the degradation; however, the observed conditions and projected increases in heatwaves suggest that newly unfrozen and connected fracture networks will enhance advective heat ~~transfer~~. ~~This~~transport. This heat shortcut is expected to accelerate permafrost warming and thawing, thereby increasing the risk of slope instability. With these results, we demonstrate that ERT monitoring can yield high-quality quantitative insights into long-term permafrost evolution and effectively track bedrock permafrost degradation across both decadal and seasonal timescales.

1 Introduction

In the last few decades, air temperatures have reached unprecedented record values during repeated summer heatwaves, with consequences also underground. Warming of frozen ground is well documented at all latitudes and altitudes worldwide (Biskaborn et al., 2019; Smith et al., 2022; Gruber et al., 2017; Masiokas et al., 2020; Aalto et al., 2018) with European mountain permafrost warming about 0.4°C in the last 20 years (Etzelmüller et al., 2020; Noetzli et al., 2024). This degradation is projected to continue in ~~the future in~~ response to climate change, but its magnitude and timing are uncertain, as the thermal response appears to be site-specific (Smith et al., 2022). In fact, it depends on material, topography, surface characteristics, slope histories, permafrost type (warm vs. cold), and, most specifically, ice content (Magnin et al., 2017; Haberkorn et al., 2021; Deline et al., 2021). Ice-poor bedrock permafrost, close to 0°C, has recently experienced the strongest warming (Magnin et al., 2023). ~~However~~If ice is present, permafrost degradation ~~near the freezing point~~ appears to be non-linear, due to latent heat effects (Hauck and Hilbich, 2024). Degrading permafrost has demonstrably ~~led to~~ increased slope instability (Krautblatter et al., 2013; Mamot et al., 2021), as ~~evidenced by recent events such as~~ shown by recent rockfalls, rock glacier acceleration, debris flows, and other cascading phenomena (Huggel et al., 2012; Phillips et al., 2017; Walter et al., 2020; Deline et al., 2021). Therefore, it needs to be closely monitored.

Geophysics can support these investigations with deep and spatially extensive insights (Vonder Muehll et al., 2001). Electrical Resistivity Tomography (ERT) clearly detects permafrost due to the large resistivity contrasts between frozen and unfrozen conditions (Tsytovlch and Sumgin, 1937; Muller, 1947; Parkhomenko, 1967). Focusing on mountain environments, ERT was introduced in the early 2000s (Vonder Muehll et al., 2000; Hauck, 2001). It quickly evolved into 2D surveys (Hauck and Vonder Muehll, 2003; Kneisel, 2004; Marescot et al., 2003) with Krautblatter and Hauck (2007) first applying it to ~~solid~~ bedrock permafrost, followed by 3D surveys (e.g., Rödder and Kneisel, 2012; Duvillard et al., 2018; Scandroglio et al., 2021), and cross-borehole measurements (Phillips et al., 2023; Bast et al., 2024). Repetition of measurements, i.e., time-lapse ERT, proved its capability to monitor permafrost changes (Hilbich et al., 2008; Krautblatter et al., 2010; Pogliotti et al.; Scandroglio et al., 2021). Fundamental for reproducibility is a robust ~~set-up~~ setup (Kneisel et al., 2014), but only recently have standard procedures been suggested (Herring et al., 2023). The majority of time-lapse studies are composed of one single measurement per year at the end of summer for permafrost detection (e.g., Kellerer-Pirklbauer and Eulenstein, 2023; Pavoni et al., 2023; Cathala et al., 2024) and the repetition of surveys accounts only for 20% of the studies (Herring et al., 2023). Most of these were single repetitions (e.g., Magnin et al., 2015; Buckel et al., 2023), some monitoring occurred at irregular time intervals (Scandroglio et al., 2021; Etzelmüller et al., 2023; Noetzli and Pellet, 2024), and only a few sites were regularly monitored (Mollaret et al., 2019; Morard et al., 2024). Although knowledge of the minimum permafrost extension at the end of summer is sufficient for most sites, hazardous locations require a higher temporal resolution to interpret site-specific, complex hydrothermal dynamics at depth (Krautblatter et al., 2010; Kneisel et al., 2014; Offer et al., 2025). This enables the evaluation of rock instabilities (Keuschnig et al., 2015; Etzelmüller et al., 2022; Cathala et al., 2024) to inform the development of effective geotechnical solutions and appropriate risk-reduction strategies (Bommer et al., 2009; Deline et al., 2021). ~~Autonomous~~ Automated time-lapse ERT can provide high temporal resolution (Kneisel et al., 2014; Doetsch et al., 2015). However, the analyses published

so far are limited to 2 years or have significant gaps due to frequent technical failures (Hilbich et al., 2011; Supper et al., 2014; Keuschnig et al., 2017). Therefore, ~~autonomous-automated~~ ERT has rarely been used to examine long-term trends in permafrost change (Herring et al., 2023). The only known work presenting continuous decadal data ~~with a~~ at monthly resolution is by Mollaret et al. (2019) at the Schilthorn (CH).

Quantification of permafrost changes ~~is~~ can be obtained by calculating the average resistivity of the whole model (Hilbich et al., 2008) or only of the area of interest (Kneisel et al., 2014). Quantitatively translating resistivity values into temperatures is a non-trivial task, as many factors influence the measurements (Krautblatter et al., 2010). Laboratory calibration of bedrock samples was first introduced by Krautblatter et al. (2010) and subsequently employed in several studies to enhance the interpretation of geophysical data in permafrost environments (e.g., Magnin et al., 2015; Etzelmüller et al., 2022; Scandroglio et al., 2021), although without quantitative field validation. ERT validation is possible with borehole data (Vonder Muehll et al., 2000; Lewkowicz et al., 2011; Doetsch et al., 2015; Mollaret et al., 2019; Farzamian et al., 2020) to constrain the interpretation of the results. ~~Notably, while~~ While many studies report both borehole temperature data and ERT measurements, a direct comparison and validation between the two is ~~often lacking. Further, no known studies rare in the literature. Only in recent studies, shallow borehole data have been used to calibrate automated ERT datasets: e.g., in arctic sediments (Cimpoiasu et al., 2024, 2025)~~ . Further, to our knowledge, no study has validated laboratory-based calibrations in the field.

Here, we present the first field-validated long-term temperature-resistivity monitoring over more than 10 years in bedrock permafrost. This database originates from a high-alpine location (Mount Zugspitze, Germany/Austria, 2,800~~m above sea level~~)~~and~~ m asl). It is unique due to its monthly resolution, the location of the electrodes in the permafrost core rather than on the surface, and the high-quality results achieved through manual measurements. Results are compared with those of Krautblatter et al. (2010) to validate the methods and investigate the effects of climate change.

This study aims to answer the following questions:

1. How reliable is laboratory calibration, and is it consistent with field calibration and observations?
2. Do enhanced error models improve the reconnaissance of thermal processes in bedrock?
3. What long-term trends and seasonal signals of permafrost degradation can be effectively captured with monthly resolution?
4. At the Zugspitze, can we quantify permafrost extent, its degradation over a decade, and anticipate its future development?

2 Material and Methods

2.1 Field site

Measurements took place in the Kammstollen, a private tunnel ~~under~~ beneath the E-W oriented ridge of ~~Mount Zugspitze~~ (2962 Zugspitze (2,962 m asl, Fig. 1a-b), located at the German-Austrian border. This mountain is part of the Northern Calcareous Alps, and its summit is composed of 600–800 m more or less uniform layers of Triassic Wetterstein back-reef fine-grained limestones, that are partly dolomitised in the vicinity of the summit (Miller, 1962). Brecciated Upper Triassic carbonate rocks, mainly massive limestones of the Wetterstein Formation (Miller, 1962). The thick-bedded, locally dolomitized

rocks commonly exhibit fracturing and karstification due to dissolution, which are frequent and well documented on the nearby Plateau (Wrobel, 1980; Wetzel, 2004). Minor dolomite and occasional marl intercalations reflect depositional variability, while brecciated zones up to 1 m ~~thick~~ thickness are present in the summit area (Ulrich and King, 1993), ~~a relevant fault zone can be found in~~. A prominent fault zone extends from the investigation area up to the summit (Hornung and Haas, 2017), ~~and karst dissolution on the Plateau is frequent and well documented (Wrobel, 1980; Wetzel, 2004)~~ but overall, the steep summit cliffs consist of comparatively pure, competent carbonate rocks. The study area is accessible ~~all-year-round~~ year-round thanks to the infrastructure and logistical support of the research station, Scheefernerhaus (UFS), which is directly connected to the tunnel.

Long-term meteorological records on the summit by the German Meteorological Service (DWD) ~~exist~~ are available since 1900 ~~on the summit~~ (Fig. 1c). Air temperature increased drastically in the last 30 years, with mean temperatures in the last decade (2013–2022) reaching -3.3°C , which is 1.5°C warmer than the reference period 1961–1990. Additionally, the years 2011, 2020, 2022, and 2024 were the warmest years ~~ever recorded~~ on record. Mean annual precipitation is more than 2,500 mm of which 80% is snowfall, but the steep north walls remain snow-free for most of the winter. The hydrological behavior of clefts at this location has been thoroughly measured for many years and interpreted by Scandroglio et al. (2025).

2.2 State of the cryosphere at the Zugspitze

The ~~first~~ earliest records of permafrost ~~presence~~ on the Zugspitze ~~are linked~~ date to the construction of its infrastructure (AEG, 1931; Körner and Ulrich, 1965; Ulrich and King, 1993). In recent years, 3D modeling has confirmed the possible presence of permafrost on the shaded and steep north side of the SW-NE ridge, which includes the site of this study, ~~starting from approximately 2350 m above sea level~~ beginning at approximately 2,350 m asl, but suggests a rather warm permafrost (Noetzli et al., 2006). ~~On the basis of~~ Based on this modeling, one N-S borehole was drilled in 2007 by the Bavarian Environmental Agency (LfU) about 30 m under the summit to document permafrost presence and evolution under the summit cable car, at a distance of 700 m from our field site (Galleman et al., 2017, 2021; Wagner et al., 2023). These measurements support the modeling, showing average core temperatures between -1.2 and -0.7°C , with a warming trend of 0.4 K in the last ten years. Modeling by Galleman et al. (2017) forecasts the disappearance of this lens by 2070.

Krautblatter et al. (2010) conducted the first ERT monitoring in the tunnel in 2007, setting the basis for this study. The tunnel ~~is composed of~~ comprises a main tunnel (MT) and a side tunnel (ST). Ice accumulated ~~on the whole~~ across the entire ground of the side tunnel and in ~~some~~ parts of the main tunnel, reaching a depth of up to 50 cm in some locations. Recently Mamot et al. (2018, 2021) conducted intense geophysical measurements and mechanical modeling to monitor an ice-controlled instability on the ridge 400 m from the tunnel. This location showed strongly degrading permafrost due to the thermal influence of the southern slope on a thin ridge. Other geophysical measurements in the area utilized passive seismic methods to document permafrost degradation (Lindner et al., 2021) and relative gravimetry to detect mass changes associated with hydrology (Voigt et al., 2021). Finally, Mayer et al. (2021) documented the dramatic recession of the three glaciers at the Zugspitze, which have been ~~decreasing in size~~ shrinking since the 1980s and could completely disappear within the next decade.




Figure 1. Study site overview. a) Zugspitze summit, with the DWD meteorological station and the LfU borehole. In red, the main tunnel, going from the research station (UFS) at 2650 m asl (south) to the exit in the north slope at 2800 m asl. ©OpenStreetMap contributors-2023. Open Data Commons Open Database License v1. b) Zoom of the monitoring site showing the main and the side tunnel, the ERT electrodes, the temperature loggers, and the two temperature transects (A-A' and B-B'). In the background, one exemplary tomogram from Krautblatter et al. (2010) shows the permafrost lens. A red line shows the approximate location of the fault zone. c) Mean annual air temperature (MAAT) at the DWD station. The thick red line shows the 30-year backward moving mean, while the black lines show the average for the selected period. d) Data-The upper graph shows data availability for temperature logger-upper loggers. For abbreviations, consult table 1. The lower graph)and-shows ERT data availability, with the percentage indicating the number of quadrupoles collected during fieldwork (lower graph100% corresponds to 1310 quadrupoles).

2.3 Monitoring setup

~~Bedrock electrical resistivity (ρ): Following a feasibility study conducted in 2007 and 2008 (Krautblatter et al., 2010), monthly monitoring commenced in 2014. The setup was~~ The setup of our study is based on the feasibility study ~~and conducted in 2007 and 2008 by Krautblatter et al. (2010) and~~ remained constant to obtain comparable measurements. Monthly monitoring of electrical resistivity (ρ) commenced in 2014 and continues to this day. Measures were undertaken along 6 transects, with electrode distances of 4.6 m and 1.5 m, using Wenner and Schlumberger arrays. ~~Problematic electrodes with poor coupling, or ice cover,~~ for a total of 1310 quadrupoles. The monitoring settings are presented in the supplementary material (Fig. S1), and a detailed description of the procedures is provided in Krautblatter et al. (2010). Resistivity data were primarily collected using an ABEM Terrameter LS, with alternating use of an ABEM SAS 1000 and SAS 300C before 2018. Contact resistance ~~was improved by spraying the electrodes with saltwater shortly before the measurements, after our tests showed it did not affect the results. Electrodes that still had too high contact resistivity, mostly close to the active layer because of ice on or around the electrodes, were eventually excluded from the measurement. Problematic electrodes with rust or poor coupling have been consistently replaced. The monitoring settings are presented in the supplementary material~~ final number of measured quadrupoles reached on average 90% of the total, but was constantly above this average in the last 5 years (Fig. S1)-1d). Data were collected using a stacking of 2, increased to 4 in case of a measurement error above 1%. Between 2017 and 2018, data availability and quality were limited due to repeated cable failures; therefore, 14 measurements from this period have been excluded from this analysis.

~~Rock~~ Hourly monitoring of rock temperature (T) ~~: Hourly monitoring~~ follows Krautblatter et al. (2010) with updates and extensions as listed ~~hereafter and~~ in Table 1 ~~and hereafter. i) The old loggers.~~ Old loggers of Type UTL-1 were ~~substituted with new loggers~~ Type Geoprecision with replaced with new Geoprecision loggers, offering higher accuracy and reliability. ~~ii) New loggers were installed along the main tunnel at a depth of 40 cm depth for rock and air temperature (MT and AT).~~ ~~iii) One logger has been installed outside to measure rock surface temperature (RST) at 15 cm depth. The ST, AT, and RST loggers (Geoprecision) were calibrated at 0 °C by the manufacturer using a high-precision water triple-point cell, reaching a temperature stability of ± 0.005 °C. This process ensures high accuracy and reproducibility in calibrating the measurement system. The iButton loggers (MT) were calibrated in an ice bath on multiple occasions throughout the study to account for drift effects. The~~ analysis presented here focuses on the period after 2018, where complete data have been recorded. Data availability for temperature loggers is presented in Fig. 1d.

Table 1. List of all temperature loggers. MT = Main Tunnel, ST = Side Tunnel

Transect	Name	Nr.	Type (Precision)	Location	Distance <u>Spacing</u>	Time	Note
A-A'	ST	4	Geoprecision M-Log 5W (± 0.1 °C)	Side tunnel (ST), rock	5 m	2019-2024	substitute UTL
B-B'	MT	20	iButton DS1922L (± 0.5 °C)	Main tunnel (MT), rock	4.6 m	2020-2024	new
B-B'	AT	3	Geoprecision M-Log 5W (± 0.1 °C)	Main tunnel (MT), air	46 m	2020-2024	new
-	RST	1	Geoprecision M-Log 5W (± 0.1 °C)	outside, rock	-	2022-2024	new

2.4 Data analysis

~~We linearly interpolated single~~ To analyze temperature dynamics, we linearly interpolated the four temperature measurements along the ~~tunnel-side tunnel (transect A-A')~~ from 2019 to 2023, ~~as if they belonged to a unique "virtual" borehole.~~ Values from the side-tunnel (Transect A-A') were used for the field calibration together with values of ρ extracted from raw data, as normally done in laboratory calibrations. For validation, we analyzed the probability density function (pdf) of the apparent resistivity treating them as a borehole (Fig. ??), prior to inversion (Fig. 2 and 3).

Successively, T - ρ field calibration (Fig. 4, 5, and S6) was conducted by combining these temperature values with single apparent resistivity values from the closest quadrupole to each temperature logger (within a 0.3 m radius). Logger ST-5, located at a depth of 5 m ~~from below~~ the surface, was excluded from the calibration because ~~only summer resistivity measurements could be taken~~ resistivity measurements at this location were only available during summer, resulting in an insufficient amount of data dataset for robust analysis. To validate the results, we analyzed the probability density function of the apparent resistivity before inversion (Fig. 6).

Resistivity data were primarily collected using an ABEM Terrameter LS, with alternating use of an ABEM SAS-1000 and SAS-300C prior to 2018. Each measuring database was automatically After field work, each database was imported into MATLAB to obtain the complete information. Winter measurements from December to June produced, on average, 4 negative resistivity measurements, which were excluded, while summer measurements showed none. Data were filtered using the ~~variance of~~ coefficient of variability (CV , or $VAR(\%)$ according to ABEM) of the resistance, i.e., the standard deviation divided by the mean, as computed by the measuring instrument, to remove systematic errors. The threshold for the CV was set to 1%, resulting in an average exclusion of 6 data points, mostly concentrated in the winter months.

For the ERT inversion, we utilized an updated version of the software *CRTomo* (Kemna et al., 2000), ~~which features significantly shorter computing times.~~ This inversion algorithm fits a model $f(\mathbf{m})_i$ to the data d_i based on an adequate data error description ϵ_i , instead of just minimizing the data misfit as commonly done. Data fit is achieved when the data misfit ϵ_{RMS} (root mean square) value is close to one, which indicates that the model reproduces the data within the expected error margins on average, as shown in equation 1 (Kemna et al., 2000)

$$\epsilon_{\text{RMS}} = \sqrt{\frac{1}{N} \sum_i^N \left| \frac{d_i - f(\mathbf{m})_i}{\epsilon_i} \right|^2}. \quad (1)$$

Following Krauthblatter et al. (2010), we performed independent inversions without applying a time-lapse approach. Because time-lapse inversion can significantly influence results (Scandroglio et al., 2021), we aimed to minimize temporal constraints, such as those introduced by prior or initial inversions, that may bias the results. We argue that this approach enhances the robustness of our results, as consistent trends emerge without temporal regularization.

Further on, the error model for the inversion was updated with new measurements. Image quality is highly dependent on the error estimates ~~for in~~ the inversion: an overestimation smooths the picture, reducing the image, reducing resolution, while an underestimation leads to artifacts (Binley et al., 1995; LaBrecque et al., 1996; Slater et al., 2000; Lesparre et al., 2017; Tso

175 et al., 2017). The random error (e) can be quantified using the difference between normal (R_N) and reciprocal (R_R) resistivity measurements, although this is only a measure of precision and not accuracy (LaBrecque et al., 1996) and does not represent the total experimental error. The error ~~is~~ can be modeled as a linear function of the mean resistance R (Eq. 2), depending on an absolute (a) and a relative (b) term ~~+~~

$$|R_N - R_R| = e = a + bR. \quad (2)$$

180 To solve this, Slater et al. (2000) expresses R as a function of e , removes obvious outliers ($e > 10\% R$), and obtains a and b from the envelope of all remaining measurements. Koestel et al. (2008) instead rejected only values of $e > 100\% R$ and then divided the measurements into logarithmically equally sized bins. The standard deviations of the reciprocal errors in each bin were least-square fitted with the linear error model (Eq. 2). Lesparre et al. (2017) adapted the approach of Slater et al. (2000) to fit the discrepancies between readings acquired at different times, proposing data error estimates for time-lapse measurements.

185 ~~To accurately analyze temporal changes, it is first necessary to correctly classify the~~ After updating the used error estimates, we computed a new inversion for all measurements, including those from 2007 published in Krautblatter et al. (2010), and analyzed temporal changes by classifying different areas of the tomogram, such as the active layer and ~~the~~ permafrost core. Some authors manually define an area of interest (Kneisel et al., 2014), while others choose an automated algorithm (~~Watlet et al., 2023~~) (Delforge et al., 2021; Watlet et al., 2023). Here, the inversion results were clustered using the MATLAB k -means algorithm.

190 The function analyzed all tomograms from 2014 to 2023 and computed ~~for each cell of the grid the~~, for each grid cell, the squared Euclidean distance ~~from cluster centroids, which is the mean of the cluster~~ to the cluster centroids (the cluster means). Cells were then categorized into the nearest centroid. The number of clusters k is defined by the user, and assignment is mutually exclusive. ~~The clustering is not unique, since multiple solutions are possible. This approach converges to a local minimum, though lower minima may exist. In practice, the global minimum is approximated by running multiple replicates with random~~

195 starting points. We used five cluster classes, based on the elbow method (Cimpoiasu et al., 2025), which evaluates the sum of squared distances between samples and their nearest cluster center as a function of the number of clusters. The optimal number is identified at the elbow of the resulting curve.

3 Results

3.1 Characterization of thermal regime from temperature measurements

200 The temperature distribution in the tunnels indicates permafrost presence in transect A-A' (Fig. 2). Due to repeated measurement gaps ~~prior to~~ before 2019, it is not possible to determine longer temperature trends. Over the last five years, the increase in active layer thickness (ALT) from 8.5 m to 10 m, combined with the overall rise in annual maximum temperatures, indicates ~~degradation of permafrost~~ permafrost degradation. The 10 m logger has now reached 0°C and maintained this level for more than 2 months in summer 2023. It is likely to overcome this threshold in the next few years. No permafrost is recorded in

205 transect B-B' (Fig. S2 ~~in the~~, supplementary material), ~~only while~~ seasonally frozen rock is recorded between electrodes E30




Figure 2. Temperature profile in the side tunnel. The location of the transect is visible in Fig. 1b (profile A-A').

and E39. All loggers in the [main](#) tunnel recorded their maximum [temperature](#) in 2023, with a more pronounced increase in the area to the right of the side tunnel, specifically electrodes E32 to E41.

Outside the tunnel, the mean annual rock surface temperature (~~MARST~~) of the steep bedrock facing north is -1.7°C (-1.7°C (RST-Logger, Fig. ~~??e3c~~)).

210 [Ice on the ground of the main tunnel decreased between 2019 and 2023, especially in the area of the permafrost lens between electrodes E31 and ~~f in the supplementary material~~. The correlation coefficient between the E38 \(Fig. S5\). This decrease aligns with the temperature increases recorded by the loggers in the main tunnel. As documented by Scandroglio et al. \(2025\), large quantities of water from snowmelt are recorded in June and July in the northern part of the main tunnel \(electrodes E1 to E20, \$x = 200\$ to \$275\$ m\). In the side tunnel, water accumulation on the ground is also common, but only at the end of summer](#)

215 [and between the ST-5 and the north face. This water results from melting surface ice on the tunnel walls and from ice-filled fractures within the tunnel.](#)

[The correlation between rock temperature inside the tunnel and ~~the~~ air temperature outside ~~ranges from~~ is clear \(Fig. 3d\), with correlation coefficients between 0.77 for the ~~side tunnel logger ST-5 to logger at 5 m depth and~~ 0.4 for the ~~ST-15 and ST-20 loggers \(Fig. ??a\). As the logger depth increases logger at 20 m depth. As expected, with increasing depth,~~ the time lag](#)

220 [also grows, reaching up to 75 days ~~, which represents the duration needed at 10-15 meters. This represents the time required for the thermal signal to propagate to the permafrost core in within~~ the bedrock. The correlation between air temperatures inside](#)




Figure 3. Temperature loggers and their correlation with external air temperature. a) Photo of the new ST-loggers and the old UTL-loggers. All sensors are located at a depth of 40 cm. The old loggers were replaced in 2019, with a one-year overlapping period. b) Photos of the MT-loggers, also at a depth of 40 cm. c) Photo of the RST logger on the north face, close to Electrode E30, at 10 cm depth. d) Correlation between ST-loggers and external air temperature from the DWD station. e) Correlation between AT-loggers and external air temperature.

and outside the tunnel is strong at electrode 30 ($x = 143$ m), near one of the tunnel exits, but becomes absent at for deeper loggers (Fig. ??b3e), indicating the influence of additional processes at greater depths (e.g., solar radiation or snow cover from the south side slope).

225 A comparison of ST-Loggers with the LfU-borehole (Galle mann et al., 2017), which is installed on the summit under the
cable car (Galle mann et al., 2017), ca. 150-200 m higher than our site, shows that ST-5 and ST-10 are quite similar to the
LfU-borehole measurements in summer, while. At the same time, winter temperatures are much lower in the LfU-borehole
(Fig. S3 and S4 in the SM). The site tunnel logger ST-5 has temperatures similar to those of the borehole logger at a depth of
40 m. Deeper loggers (ST-15 and ST-20) are not reaching temperatures as low as in the LfU-borehole, even if the thickness of
230 the ridge is comparable at the two locations.

Monthly visual mapping of ice and water presence in the main tunnel (Fig. S5 of supplementary materials) shows that ice extension on the ground reduced between 2019 and 2023, especially between electrodes E31 and E38, which is the area of the permafrost lens. This fits well with the temperature increase recorded by the MT-loggers. Water presence in the southern side of the tunnel/ridge is well documented from April to October by Scandroglio et al. (2025). Large quantities of water from snowmelt are also recorded in June and July in the northern part of the tunnel (electrodes E1 to E20, $x = 200\text{--}275\text{ m}$). Water accumulation on the ground is common at the end of summer in the side tunnel, especially between the ST-5 and the north face. This water results from the melting of surface ice on the tunnel walls and ice-filled fractures within the tunnel.

Field calibration of the $T-\rho$ relation

3.2 Field calibration of the $T-\rho$ relation

The newly collected thermal information, together with the ERT measurements, allows us to validate the temperature-resistivity ($T-\rho$) laboratory calibration by Krautblatter et al. (2010), which was often used to interpret ERT field measurements so far (e.g., Magnin et al., 2015; Etzelmüller et al., 2022; Scandroglio et al., 2021). Figure ?? 4 shows that, despite big differences in resistivity ranges, temperatures and resistivities have there is a high correlation between temperature and resistivity.




Figure 4. Temperature versus resistivity. Rock temperatures from the ST loggers in blue, and air temperatures from the DWD station in dotted green. In red, single quadrupole apparent resistivity variations are interpolated in time from the monthly ERT measurements, prior to inversion, with reverse axis direction for simplifying comparison. Other periods are available in Fig. S6 of the supplementary materials.

The differences in resistivity range Resistivity varies from 30 to 120 kΩm for ST-10, from 15 to 25 kΩm for ST-15, and from 40 to 130 kΩm for ST-20. These differences lead to a strong spreading of data when plotting all the values together (Fig. ??a);




Figure 5. T - ρ field calibration. a) All values from 2021 to 2024. b) Calibration for ST-10, using only the values from the new T-loggers, from 2019. In red is the interpolating line, in green is the lab calibration from Krautblatter et al. (2010). c) Calibration lines for all loggers. In black, the average of logger ST-5, ST-10, and ST-20.

but 5a). Still, when analyzing each temperature logger separately, the correlation appears clear (Fig. 225b and Fig. S7b-e). This suggests that the relation between resistivity and temperature can not be assumed to be unique for this transect. Logger ST-5 presents records only a few values below 0°C: in-during the cold months, a thick ice cover in the tunnel limits the-electrode connection, while-electrode contact, whereas in the warm months, positive temperatures are measured. Therefore, ST-5 will be excluded from our analysis. The other loggers present-show a good linear fit: the best is at ST-10 ($R^2 = 0.84$), while-whereas at ST-20, the fit is poor ($R^2 = 0.41$). Resistivities decrease with-over time, possibly due to a-decrease-in-reduced ice content; therefore, a-yearly-analysis-could-deliver-an-annual-analysis-could-yield a better fit. Generally, most of-the-recorded data are

close to the freezing point, which should be taken into consideration. Supercooling effects and similar phenomena from the calibration are not detectable in the field calibration due to the absence of freeze-thaw cycles in the permafrost core.

255 The freezing point at 29 kΩm agrees with values from the laboratory, but in the field, resistivity increases at much stronger rates than laboratory experiments can reproduce. Field calibration results for ST-10 and ST-20 can be resumed in the "average" Equation 3.

$$\rho = (-106 \pm 49) T + 29 \quad (3)$$

260 ST-15 shows much lower resistivity values than the other locations and behaves similarly to the laboratory calibration. This could depend on the degree of fracturing at this location.

Field validation of the $T-\rho$ relation

3.3 Field validation of the $T-\rho$ relation

To explain the big discrepancies in the field calibration, we analyze the rock that composes the tunnel. While the majority is made of compact rock (material A in Fig. ??6), short parts of the tunnel are highly fractured due to the fault zone (material B in Fig. ??6). As suggested by Scandroglio et al. (2021), we compare the probability density function (PDF) of the apparent resistivity of all the ~~ERT measurements computed measurements~~ in the permafrost area (~~in the~~ side tunnel). The ERT transect on the right (Fig. ??6d) presents only one peak, while on the left (Fig. ??6c) two peaks are ~~present~~ visible. Supposing that each peak relates to a different rock type, this indicates the presence of two materials in the left area, as confirmed by field mapping (Fig. ??6a). ~~Material A has an average apparent resistivity of 50 kΩm, while material B presents average values of 15 kΩm~~ The probability density curves for material A on the right side of the tunnel clearly show variations with time towards lower values. At the same time, smaller changes are recorded on the left for material A and no changes for material B. A combination of both materials would likely produce results similar to material B, as current follows the easiest path of lower resistivity; however, this should be further investigated. ~~PDF-curves for material A on the right side of the tunnel clearly show variations with time towards lower values, while smaller changes are recorded on the left for material A and no changes for material B.~~

275 3.4 Error model updating

During previous research at this site, Krautblatter et al. (2010) ~~analysed~~ analyzed 3000 reciprocal measurements according to Koestel et al. (2008) and obtained values of $a = 48 \Omega$ and ~~$b = 0.08$~~ $b = 8\%$. We recorded reciprocal measurements for four months in summer and autumn to validate these results and analyzed them using three methods, as described in ~~Slater et al. (2000); Koestel et al. (2008)~~ Slater et al. (2000), Koestel et al. (2008), and Lesparre et al. (2017). All methods suggest that the previous absolute error (a) was strongly conservative. The newly computed value of a approaches zero (~~$a = 0.25 \Omega$~~ $a = 0.22 \Omega$), as Fig. ??-7 shows. The value of b by Krautblatter et al. (2010) appears to be correctly estimated: we obtained $b = 7.5\%$ according to Slater et al. (2000), ~~but could assume or~~ lower values (~~$b = 4\%$~~ $b = 4\%$) according to Koestel et al. (2008) and Lesparre et al. (2017). For




Figure 6. Comparison of ERT raw data for the two resistivity transects in the permafrost area. a) Photos from the tunnel. Material A, at electrode E36, is pure bedrock. Material B, at electrode E49, is mostly fine-grained material. A mix of materials A and B with fractures of variable width is also possible. b) Areas of interest of the ERT transects in the side tunnel: violet for the left and yellow for the right transect. c-d) Probability density functions of apparent resistivity of the whole transect for the warmest months. [FigureData in subplot c\) shows show](#) two peaks, indicating the presence of two main signatures, while [Fig.data in subplot d\) presents shows](#) only [onea single peak](#). The year 2023 recorded the lowest apparent resistivities in both cases.




Figure 7. Error model differences. a) ~~Error~~ The new error model according to Slater et al. (2000), where each dot represents a normal and a reciprocal measurement. b) Relative differences between inversions with the old and the new error model for 2022. Resistivity values in $\log_{10}(\rho)$. Numbers express the overall change as a percentage. c) Zoom: subsection of b outlined in black. Comparison of the permafrost extension in July. The upper figure is obtained using the old error model, and the middle figure is obtained using the new model. The and the lower image is a zoom of b) figure shows the differences.

the following analysis, we will use the error estimation from Slater et al. (2000), as lower values of b can lead to overfitting in the tomograms.

285 In Figure ??7b, we present the inversion differences between the error model chosen for this study and the model previously used in Krautblatter et al. (2010), applied to the inversion of the ERT monitoring data from 2022. Using the updated error model, resistivities in the permafrost core ($x = 65$ to 115 m) are higher in both winter and summer. The maximum differences occur from May to July, especially on the right side of the side tunnel (an increase of $> 10\%$), while the smallest differences ~~are occur~~ between January and April. An exception is represented by the area between $y = 0$ and -10 m right of the side
290 tunnel (Fig. ??7c), which is very close to the rock surface. Here, resistivities are generally lower, with peaks during the warm months: this better represents the ~~active-layer~~ active-layer dynamics measured with temperature loggers. ~~Strong~~ Considerable differences are also evident in the area corresponding to the fault zone crossing the permafrost body. The inversion with the updated error model reports lower resistivities along the fault axis; however, ~~it appears that~~ these values do not extend to the main tunnel, as field observations would suggest. The area between $x = 150$ and 200 m shows higher ~~resistivities~~ resistivity,
295 but only in the winter months. The tunnel in this area is covered by concrete (indicating a more fractured bedrock), and it is seasonally covered by ice on the ground and ~~on the walls. Furthermore, smaller differences are present at the~~ walls. The tunnel surface ($y < -25$ m) ~~here, frozen patches can be~~ shows smaller differences: frozen patches are found at different x -positions, but the most evident is at $x = 135$ m, which corresponds to one ~~exit in the tunnel~~ tunnel exit where snow normally accumulates in winter. Lower resistivities are produced by the inversion at $x > 225$ m from January to July, with new values reaching -10% .

300 3.5 Characterization of thermal regime from resistivity

Long-term signal

Figure ??a-8 shows all ERT inversion results from 2007 to 2023 using the updated error model. This allows the detection of features, listed hereafter, that are confirmed by field observation (Fig. ??a and Fig. S10 of the supplementary materials). a) S10).

- 305 a. The active layer is visible from 2014 on, at the right side of the tunnel next to the permafrost core ($x = 100$ and 150 m). This feature follows the structure of the external slope and reaches minimum values from July to September. b) ~~c)~~
- b. From December to April, a temporary frozen part appears at the center of the image ($x = 150$ to 200 m). This is an area of the tunnel with reduced rock thickness and a steep bedrock slope outside. c) ~~d)~~
- 310 c. The constantly unfrozen part between 200 and 250 m fits with a less steep debris-covered area outside the tunnel, which is snow-covered in winter. d) ~~e)~~
- d. Some frozen patches can be found along the tunnel ($y = -25$ m, lower border of each image) ~~here, frozen patches can be~~ while they are present all year long in 2014 and 2016, these features strongly reduced decrease, up to disappearing, from 2018 onward. e) ~~f)~~




Figure 8. ERT inversion results. Tomograms from 2007 to 2023. On the left, the month of each tomogram. The color bar shown is valid for all tomograms. Bottom right: reference tomogram with measures can be found in the following figure.

e. The fault zone crossing the permafrost is evident in all tomograms. This area exhibits lower ~~resistivities compared to~~ resistivity than the surrounding area, ~~without a~~ with no clear thermal explanation. ~~f)~~

315 f. The constantly lower values at the beginning of the tunnel represent the area with the biggest distance to the north slope.

In addition to these features, measurement errors are also evident, thanks to the new error model, for example, in November 2020. For all inversions based on the new error model, RMS values range from 0.97 to 1, and the number of iterations ranges from 3 to 12, with an average of 6. Details are shown in Figure S9b. As expected, the smaller b-value of the updated (or new) error model leads to smaller data misfits and, consequently, to less smooth, slightly more detailed inversion results.

320 Long-term trends clearly present a reduction of the frozen areas, as confirmed by Fig. ~~??9~~b. While frozen areas increased ~~contradictorily between 2007 and 2014~~ from 31% to 40% of the total area between 2007 and 2014, they drastically ~~reduced~~ decreased from 2014 to 2020 ~~down~~ to 25%. This corresponds to a 40% reduction compared to 2014. The last four years present little variation in the minimum frozen area. These trends are also visible in the winter months, but are less pronounced.




Figure 9. ~~a) Reference tomogram with measures and highlighted features, same color bar as the previous image. b)~~ Long-term development of the frozen areas, from 2007 to 2023.

Image clustering of the tomograms with *K*-means

325 The ~~best-fit between~~ best fit between the measurements and the previously analyzed features is obtained ~~for a clustering~~ with $k = 5$, as confirmed by the elbow method. The results are presented in Figure ~~??10~~. Class 1 shows the highest ρ values, which correspond to constantly frozen rock. This class has been remarkably consistent over the last 10 years and represents the core of the permafrost. Classes 2 and 3 include cells that are, respectively, mostly frozen and partially frozen, representing rapidly degrading permafrost and the active layer. Both classes are experiencing the strongest decrease in ρ (-4200 and $-2330 \Omega\text{m}^{-1}$,
 330 Fig. ~~??10~~b). Class 4 comprehends mostly unfrozen cells with a slightly decreasing 10-year trend and represents feature c) of Figure ~~??8~~. Class 5 encompasses the unfrozen area at the beginning of the tunnel, which has exhibited slightly increasing




Figure 10. *k*-means clustering. a) Classified tomogram. b) Mean resistivities for each class on a logarithmic scale. On the left, the areas covered by each class are listed, and on the right, the corresponding gradients are shown. c) Violin plot of all resistivity values included in one class.

values over the past decade but has undergone constant development recently. The distribution of values in Figure ??10c shows all values and not only the mean. In particular, values in class 2 are mostly frozen, while those in class 3 are half frozen and half unfrozen.

335 Quantification of changes in permafrost extent

Knowing the grid size, we can estimate the size of the permanently frozen area. It covers circa 2,000 m², of which 700 m² is in class 1 (35%) and 1,300 m² is in class 2 (65%). The external morphology suggests a vertical extension of the lens of 20-30 m, which would result in 40,000-60,000 m³ of frozen rock. The remaining temporarily frozen and unfrozen areas (classes 3, 4, and 5) cover 5,700 m², about 75% of the tomogram. Given the strong decreasing rates of in the outer layer (class 2), up to 39000-39,000 m³ of permafrost are very likely to suffer irreversible thermal degradation, potentially leading to its disappearance. By linear extrapolation of the gradient computed in Fig. ??10b, we expect this process to happen within the following decade. This assumption significantly simplifies the complex physical processes, which that are not necessarily linear and therefore should be considered with some degree of uncertainty. Still, given the actual development of climate change, the trend is unquestionable.

345 Quantification of seasonal variations

~~For detecting~~ To detect seasonal trends, we ~~utilized~~ used the mean ρ value ~~of the whole across the entire~~ ERT tomogram. The maximum values are recorded in April or May, the minimum around September (± 1 month), as shown in Fig. ??11a. In the summer months, there is a clear shift in time towards lower values of ρ , while this is less evident in the winters, which present a higher variability. Resistivities in 2023 (dark red) indicate a prolonged winter with low values, a drastic drop in resistivities from June to July, and a long summer season with extremely low values from July to October. Comparing ten years of records reveals three distinct phases. The first is a gradual increase in resistivity from October to March/April; ~~then there-~~ There is a sudden decrease between May and July, and finally, a stable phase with little variation in resistivity from August to October.

Seasonal averages in Fig. ??11b show that the resistivity decrease in the last ten years is more pronounced in the spring and summer months, reaching more than 0.9 k Ω m per year. Winter values are decreasing ~~at a rate of~~ less than one-third of the rate. While winter and spring values ~~have strong variations~~ vary widely from year to year, summer averages follow a clear linear trend.

Figures ??11c shows that the tomogram's mean ρ is strongly correlated with the mean monthly air temperature with an hysteresis pattern. Resistivity ~~reacts~~ responds to temperature changes with about a two-month delay ~~to temperature changes~~, producing an elliptical path. The change in time (described by colors) shows the evolution over the last 10 years towards warmer air temperatures ($+2^{\circ}\text{C}$ in summer), which led to lower resistivity (-8 k Ω m). 2023 recorded the lowest value both for ρ and MAAT: 4.8°C and 19 k Ω m.

4 Discussion

We present 15 years of monthly ERT profiles and investigate permafrost dynamics in steep bedrock applying a newly developed temperature-resistivity (~~$T-\rho$~~ $T-\rho$) field calibration, and an updated error model, compared to the first studies by Krautblatter et al. (2010). Newly available data, improvements in methods, and updated analyses have significantly enhanced the quantification of both short-term permafrost dynamics and long-term degradation.

4.1 Linking temperature and electrical resistivity: comparison between laboratory and field observations

Precise knowledge of the ~~$T-\rho$~~ $T-\rho$ correlation is crucial for a correct interpretation of the thermal state of the permafrost core derived from resistivities. Many laboratory calibrations are nowadays available for different sites and materials (examples in Herring et al., 2023; Limbrock et al., 2025), but most studies do not validate them quantitatively in the field (e.g. Magnin et al., 2015; Duvillard et al., 2021). ~~Only Mollaret et al. (2019) conducted field calibration before, but without comparing it with laboratory values. Offer et al. (2025) compared laboratory $T-\rho$ relations with field values, but without real calibration.~~ Information at permafrost core ~~depth~~ depths is often missing, as ~~no known few~~ studies have compared field and laboratory measurements.

~~Our new field calibration,~~ Mollaret et al. (2019) previously conducted field calibration but did not compare it with laboratory values. Offer et al. (2025, 2026) reported lower resistivity values in field measurements compared with laboratory ~~calibration~~




Figure 11. Seasonal changes of mean resistivity. Average value of the entire ERT tomogram, from 2014 to 2023. a) Seasonal variation for all years. b) Average values of 3 months, with trendline and gradient: February, March, and April in blue, May, June, and July in red, and August, September, and October in yellow. c) Comparison of the tomogram mean resistivity with the mean monthly air temperature, measured at the DWD station on the summit, both values as a 3-month moving mean.

by Krautblatter et al. (2013), presents similar values for calibrations, attributing this discrepancy to water pressure effects. To date, no field calibration procedures have been proposed.

Krautblatter (2009) demonstrates that resistivity behaves differently above and below the freezing point, a finding that we also observed at the ST-5m logger (see Fig. S7b). They could also show that the ρ -T gradient below the freezing point ($29.8 \pm 10.6 \text{ \% } ^\circ\text{C}^{-1}$) is, on average, ten times higher than that above the freezing point ($2.9 \pm 0.3 \text{ \% } ^\circ\text{C}^{-1}$). Our new field calibration yields similar values at the freezing point, but higher resistivity gradients at low temperatures. Similar results are obtained when comparing field calibration by Mollaret et al. (2019) with laboratory measurements from the literature (Hauck, 2001). In this case, the field results also exceeded the values obtained in the laboratory. Knowing that laboratory tests are typically conducted by Hauck (2001), or for laboratory measurements consistent for different types of rocks Limbrock et al. (2025)

Assuming that laboratory measurements are typically performed on intact rock samples, we can hypothesize that laboratory it can be inferred that such results provide a valid approximation for a saturated matrix, reasonable approximation of a saturated rock matrix. Laboratory calibrations are typically performed on fully saturated samples, whereas field conditions often involve partial saturation, which can result in higher resistivity. In this case, the conditions we observe at the Zugspitze are always nearly fully saturated (>90%), except for the outer 8-10 cm of the rock surface (Sass, 2005). In the specific setup where we measure from inside the gallery, meters to decameters from the rock wall, surface variations do not play an important role (compared to measurements with electrodes on the surface). The higher resistivity values obtained-observed in the field can be explained-by are likely attributable to the presence of ice in-within frozen discontinuities. However, the extraction of rock samples inevitably removes them from their in situ stress conditions, which may induce minor fracturing or the opening of pre-existing fractures, thereby potentially reducing the measured resistivity of the specimen.

Additionally, Krautblatter et al. (2010) recorded supercooling effects just after the equilibrium freezing point (-0.5°C) during initial freezing in laboratory tests. Although these effects are not directly apparent in our dataset, an increase in the standard deviation of resistivity measurements is observed near the freezing point in the ST-5m logger data (see Fig. S7b), which may be linked to similar processes. It is important to note that such effects were only observed in the laboratory during the initial freezing phase and for very short periods, conditions that cannot be replicated with our setup.

Both field and laboratory calibrations at our site agree on the freezing point around 29 k Ω m; however, the interpretation of laboratory measurements above this point should be taken with caution. In fact, it is impossible to accurately reproduce the steadily variable alternation of bedrock, fractures, ice/water, and voids available in nature-with found in nature in a sample; however, this composition strongly influences ERT results. This is evident in the high variability of the calibration results presented here, despite our temperature loggers being located just 5m apart-from-each-other m apart. For this reason, caution should be used-when-extrapolating-these-results-for-exercised when extrapolating the T- ρ relation to other locations, even at within the same site. We suggest that field calibrations are totally valid only for the measured spot. Further limitations are a reduced temperature range in nature and the lack of freeze-thaw cycles when measuring permafrost. Recent studies confirm the presence of hysteresis effects in field measurements and demonstrate their importance in the energy balance of permafrost (Limbrock et al., 2025; Luo et al., 2024; Tomašková and Ingeman-Nielsen, 2024).

Our measurements recorded resistivities greater than 200 k Ω m, values that exceed the laboratory calibration range. ~~These values have been explained by Krautblatter et al. (2010)~~ Krautblatter et al. (2010) has explained these values in terms of ice presence, but not numerically proven. Our results indicate that laboratory calibration should be validated in the field and, if
415 necessary, refined ~~according to the~~ based on field data.

4.2 Influence of the error model on long-term ~~, quantitative~~ ERT measurements

The chosen procedure, the ~~criteria for outlier filtering~~ filtering criteria for outliers, and the ~~placement of bins~~ bin placement can affect the quantification of the error to varying degrees (Koestel et al., 2008; Tso et al., 2017). Different arrays generate ~~different types of errors~~ distinct error types, corresponding to ~~distinct~~ different error models. Further complexity arises when
420 multiple measurements are combined into a single dataset, as in this case. In addition, the reciprocal error may vary over time during long-term monitoring due to changing external conditions, such as seasonal fluctuations in water state or long-term variations in underground water content. Given these factors, the best inversion would theoretically require one error model ~~for each array and each~~ per array and per epoch, which would be ~~extremely~~ time-consuming during data acquisition. As a consequence, the use of reciprocal errors is very rare in field applications (Herring et al., 2023). When reciprocal
425 measurements are conducted, most studies use a uniform error level for all configurations and time steps to reduce the degrees of freedom (~~Koestel et al., 2008; Lesparre et al., 2017; Tso et al., 2017~~) (Lesparre et al., 2017; Tso et al., 2017), thereby ensuring consistency among ~~ERT images results~~ at different times (Krautblatter et al., 2010; Maierhofer et al., 2024), while other authors use a time-varying error model (Koestel et al., 2008). With the new computation of the error model suggested here, i.e., the drastic reduction of the absolute term a , we possibly introduce some artifacts in the inversion results. Still, the significant
430 advantage ~~gained~~ is a substantial increase in resolution, ~~which enables~~ enabling us to investigate permafrost degradation ~~with~~ in much greater detail ~~-(see features in Fig. 8)~~.

As shown in Figure S9a, the updated error model has little impact on the RMS error, which remains within the same range (0.99–1), as expected, since this is the value minimized by the inversion algorithm. However, the number of iterations increases from 3–4 to 6, which was also foreseeable, since smaller errors require a more precise fit of the model to the data to achieve
435 the same RMS values and therefore more iterations. Inspection of the RMS formulation (Eq. 1) shows that, if ϵ_{RMS} remains approximately constant, smaller values of the error ϵ_i result in a reduced data misfit (i.e., $d_i - f(\mathbf{m})_i$). In our case, with the newly computed values of a (Fig. 7), we observe smaller errors for $R < 10^4 \Omega$, leading to stronger data weighting. This, in turn, allows for closer model adjustment, potentially improving the fit, though it also increases the risk of overfitting and introduces model artifacts, while reducing smoothing and enabling the resolution of finer-scale features.

440 4.3 Permafrost degradation according to ERT

New temperature calibrations and error models enable us to accurately interpret the inverted resistivities, particularly in the permafrost core. Results confirm the presence of warm permafrost ~~close to~~ near the melting point, and its degradation is ~~well~~ readily quantifiable. Still, complex inter-annual behavior due to latent heat effects during thawing, seasonal water infiltration, and variable snow cover makes the processes highly non-linear (Hauck and Hilbich, 2024) and therefore difficult to interpret.

445 The degree of fracturing also seems to contribute to this non-linearity. A survey of fractured zones was already presented in Krautblatter et al. (2010), but the effects of the fault zone were neglected. Here, thanks to the new field calibration, differences are distinctly highlighted. Clustering, as suggested by Delforge et al. (2021) and Watlet et al. (2023), also provided powerful insights in this direction. Thanks to simple algorithms, large amounts of data are used to detect similar patterns, yielding an objective, data-driven analysis. This allows for a more robust interpretation of results than the "user-defined areas of interest",
450 which are mostly rectangular, as previously used in the literature (Kneisel et al., 2014).

Despite this complexity at high temporal and spatial resolution, when looking at slope scale over one decade, it is evident that ERT values strongly correlate with rock and air temperatures, as shown in Figure ??12b. Mean resistivity of the tomograms decreases from 37 k Ω m in 2018 to 28 k Ω m in 2023 (−25%). The decrease is stronger from 2018 to 2021, ~~while~~ whereas in the last 3 years ~~it appears to be~~ it is less pronounced. Meanwhile, air temperatures have steadily increased since 2012, rising
455 from −4.2°C to −3.2°C.

This supports the theory that external thermal forcing and conductivity are the primary processes promoting permafrost degradation here. Contradicting trends, such as the increase in frozen areas between 2007 and 2014, as shown in Figure ??9, can also be explained by thermal forcing (e.g., an increase in rising air temperatures). In fact, the hydrological year 2006/2007 recorded extreme temperatures, 1°C warmer than the 30-year average. On the contrary, from 2007 to 2014, temperatures were
460 mostly below the 30-year average (Fig. ??12b, inlet). Therefore, 2007 can be considered an anomaly, and the measurements ~~in~~ from that year are not representative of the ~~decade~~ 2000-2010 decade.

Analyzing the resistivity ratio between active layer and permafrost ρ_{PL}/ρ_{AL} as suggested by Hauck and Hilbich (2024), we compare clustering class 1 with class 2 and class 1 with class 3 and focus on the maximum values of each year (Fig. ??12a). Although ~~showing different variations~~ they varied, both ratios increased over the last 10 years. The ratio class 1/class 2 closely
465 follows the trends of mean annual air temperature (MAAT): it decreased in 2018 and in 2021 after mild years, while it increased in all other years. In 9 out of the last 10 years, MAAT was above the long-term average of −3.8°C, with records reaching −2.6°C in 2019/2020 and 2022/2023. Excluding the possibility that the permafrost core has increased its resistivity (ρ_{PL}), this trend can be explained only by a decrease in resistivity in the active layer (ρ_{AL}), to a stronger degree than the decrease in the core, as confirmed by Figure ??10b. Compared with Figure ??9, it is remarkable that, although the number of frozen cells has
470 not decreased since 2021, the ratio ρ_{PL}/ρ_{AL} increased in 2022 and 2023. This ~~means that even if frozen areas do not diminish, resistivities reduce, indicating that non-linearly degrading confirms that non-linear degradation~~ processes are occurring in the active layer ~~and that sudden degradation might~~ may occur in the next few years. On the contrary, it seems that class 1/class 3 ~~stabilized in~~ have stabilized over the last four years, possibly indicating that degradation has already reached a stable level in these areas.

475 The resistivity ratio between the active layer and the permafrost in our data falls within the same range as reported by Hauck and Hilbich (2024). However, while they observed a long-term decrease in this ratio, our results show a contradictory overall increase. This suggests that, at our site, the degradation of the active layer has not yet significantly impacted the permafrost core. Notably, our unconventional measurement setup—conducting measurements from the inside out rather than from the surface may influence this interpretation. In typical surface-based ERT surveys, accuracy decreases with depth due to the limited




Figure 12. External thermal forcing drives resistivity changes in the active layer. a) Resistivity ~~ratio~~ratio: class 1/class 2 in dark blue, class 1/class 3 in light blue. The red lines unite the minimum values for each year. Lower bars: mean annual air temperatures (MAAT) of hydrological years from 2014 to 2024. b) The increase in overall mean resistivity (in red) is well explained by the increase in air temperature (in black). c) Inlet: MAAT of hydrological years from 2001 to 2014. The following abbreviations are used: MMAT (monthly mean air temperature), mm10y - moving mean 10 years, mm12m - moving mean 12 months, mm36m - moving mean 36 months.

480 number of data points, resulting in higher confidence near the surface and lower confidence at greater depths. ~~In contrast, our configuration yields the opposite: reduced accuracy in the shallow active layer and~~ The configuration used here yields improved

accuracy ~~in the deeper permafrost core~~ along the main tunnel (deep bedrock) and along the side tunnel (permafrost core), but provides lower resolution for the rest of the outside bedrock slope.

4.4 Lessons learned from over a decade of monitoring

485 After more than a decade of monitoring, we share key lessons learned from challenges like equipment malfunctions and data inconsistencies to improve future monitoring efforts and contribute to the scientific community. Long-term monitoring requires strict consistency in measurement parameters and procedures to ensure data comparability over time. However, when changes in software, hardware, or operational protocols are necessary or beneficial, it is advisable to implement an overlap period during which both the old and new setups are operated simultaneously. This overlap should be sufficiently long to capture variability
490 across different environmental conditions, including both warm and cold periods.

Instruments deployed in humid environments are particularly susceptible to corrosion, which can compromise data quality and equipment longevity. Regular inspection and maintenance are therefore essential and require the continuous replacement of faulty or degraded electrodes. All components of the monitoring system, including cables, measurement units, and data loggers, should be routinely tested to promptly detect and address failures. Immediate, on-site verification of collected data
495 — especially at remote locations — is strongly recommended to identify potential issues early. Quality control procedures — such as threshold checks, outlier detection, and trend analysis — in the data workflow can help identify inconsistencies early. Establishing clear criteria for data validation and flagging enhances the overall reliability of the dataset. In this context, optimizing and automating data analysis procedures can significantly enhance efficiency and reliability.

Comprehensive documentation, regular calibration (with redundancy where possible), and robust data management —
500 including automated logging, standardized formats, and secure backups—are essential to ensure the accuracy, reproducibility, and long-term usability of monitoring data. We also encourage the publication of data in open-access repositories and active participation in collaborative initiatives such as the IPA Action Group IDGSP.

4.5 Future development of permafrost degradation and slope stability

At this site, permafrost degradation is mainly driven by thermal forcing, as shown in Figure ??12a. Future heat waves are
505 projected to increase in magnitude and frequency (Lin et al., 2022). As a result, this trend is expected to persist in the coming decades, particularly for the active layer (cluster classes 2 and 3), although the permafrost core (class 1) will ~~also ultimately be impacted~~ ultimately be affected as well. The fault crossing the tomogram, clearly visible thanks to the newly developed error model, may further accelerate degradation due to its high permeability. In fact, when unfrozen, it could allow large volumes of water to infiltrate, as demonstrated by Scandroglio et al. (2025), in Scandroglio et al. (2025), thereby introducing advective
510 heat transport processes that compound the thermal degradation. Consequently, atmospheric forcing is expected to play a significant role in the dynamics of permafrost degradation; however, its influence remains difficult to quantify. Increasing the measurement frequency from April to July could provide valuable insights into the delayed thermal response of deep rock layers.

On steep slopes, the increase in rock temperatures is also linked to irreversible ice losses (Hauck and Hilbich, 2024).
515 Although this is not expected to ~~strongly~~ influence the hydrological cycle in alpine environments strongly, it has strong stability consequences for slope stability (Krautblatter et al., 2013). This might also be true for the analyzed area, where the fractured zones might be a source of new instabilities, ~~also considering given~~ the almost vertical ~~dipping dip~~ of this fracture area.

The current setup was not fully automated and, consequently, it does not enable real-time monitoring. The potential of automated ERT has been assessed in Keuschnig et al. (2017). The calibration and error estimates in this paper contribute to a
520 more robust implementation of ERT in monitoring and early warning systems for critical infrastructure, e.g., mountain huts and cable car stations, where less-calibrated approaches are currently being tested. Fixed and automated ERT monitoring systems have been implemented on steep permafrost slopes (e.g., studies by Abdulsamad et al. (2026); Offer et al. (2026)). In principle, such systems allow continuous resistivity measurements and could provide near-real-time insights into permafrost conditions. However, to our knowledge, these approaches have not yet reached a level of maturity that enables reliable operational use for
525 early warning purposes. Achieving this would require developing robust automated workflows for both data acquisition and processing and establishing clearly defined early-warning criteria. Potential criteria could include thresholds for active-layer thickness or for resistivity values approaching the thawing point. It is important to remember that ERT-derived information alone is insufficient for early warning applications. It must be complemented by detailed geological characterization, including surface fracture mapping and, ideally, subsurface information obtained from boreholes (Offer et al., 2026) or tunnels to identify
530 critical discontinuities and preferential ways for water flow. Furthermore, reliable quantitative interpretation of resistivity data requires field calibration over at least one complete freeze-thaw cycle and across multiple depths, as demonstrated in this study.

5 Conclusions

This study compiles 109 ERT measurements collected over 17 years at monthly frequency from the Kammstollen Tunnel, 2,800
535 m ~~above sea level asl~~ on Mount Zugspitze (Germany/Austria). Developing a field calibration ~~for the temperature-electrical resistivity of the temperature-resistivity~~ relation, improving the ~~error model of the inversion~~inversion error model, and automatically clustering the results ~~, advances~~ advance the understanding and quantification of permafrost degradation in steep rock slopes.

- ERT field-based calibration with rock temperatures over ~~a five-year period~~ five years validates laboratory-based calibrations, which have become a standard approach in the literature. While both methods show good agreement ~~on~~ at the freezing
540 point, field data reveal significantly higher resistivity values at ~~sub-zero~~ subzero temperatures and highly variable results. This highlights the need for ~~cautious interpretation of~~ caution when interpreting tomograms based solely on laboratory calibration.
- A correct estimation of measurement errors is essential for a correct inversion and interpretation of ERT data. Regular validation and update of the error model over time can significantly enhance the detection of thermal processes in long-
545 term monitoring.

- Mean resistivity of the tomogram shows a decrease of 25% in the last 10 years, with more enhanced degradation in the summer months, where the overall decrease rates reach $-0.9 \text{ k}\Omega\text{my}^{-1}$.
 - Frozen cells decreased by almost 40% in the same period, and the active layer suffered the strongest losses, with rates between -4.2 and $-2.3 \text{ k}\Omega\text{my}^{-1}$.
 - 550 – The strong meteorological variability between years requires at least monthly monitoring in the summer and autumn months to precisely assess long-term degradation. Monitoring the spring and winter months is crucial for a comprehensive understanding of the processes and an accurate evaluation of the yearly trends.
 - The extent of the permafrost lens in 2023 can be estimated in $2,000 \text{ m}^2$ (Class 1 and 2) - up to $60,000 \text{ m}^3$. The actual degradation rates indicate that approximately $1,300 \text{ m}^2$ (class 2) - up to $39,000 \text{ m}^3$ - will become unfrozen within the
555 next decade. Still, degradation is not always linear, and this estimation does not account for thermal advection caused by infiltrating water (Scandroglio et al., 2025), which could entirely enhance this phenomenon.
 - The proposed resistivity-temperature monitoring allows a quantitative investigation of changes in the thermal regime of permafrost. Compared to previous studies, the results confirm the presence of the permafrost core, but indicate differences in its spatial extent, providing a more accurate representation of its dynamics.
 - 560 These innovations enhance the ability to detect and predict permafrost degradation and the consequent bedrock instabilities with greater spatial and temporal precision. These findings help decision-makers assess the increasing risks ~~that rising temperatures~~ pose posed by rising temperatures to both society and infrastructure.
- . All data analyses and visualizations for this study have been conducted in MATLAB. Resistivity and temperature data are available at the following link: (will be provided before publication).
- 565 . RS designed the study, performed the field measurements, and conducted the data interpretation. JL supported the inversion of ERT data, and SW supported the development of the manuscript and data interpretation. MK designed, financed, and supervised the study. RS prepared and revised the manuscript with final approval from all authors. SW and JL improved the draft.
- . The authors declare that they have no conflict of interest.
- . ~~We extend our special thanks~~ Special thanks go to the Environmental Research Station Schneefernerhaus and ~~the~~ Bayerische Zugspitzbahn
570 Bergbahn AG for their logistical and financial support. We also ~~thank our~~ express our gratitude to all colleagues from the ~~Chair~~ Chairs of Landslide Research and ~~the Chair of~~ Engineering Geology for their continuous assistance and ~~collaboration. Special thanks~~ productive

exchanges. Massive thanks go to all the students who ~~helped-assisted~~ in the field and provided ~~constructive-ideas, especially-valuable~~ ideas, particularly Paul Schmid, Verena Soll, Saskia Brose, Frederik Reese, Leon Wassmann, Jonas Brixle, and Andrea Schmid. We also acknowledge the researchers who collected data prior to 2019, especially Saskia Eppinger, Tanja Schröder, and Philipp Mamot, as well as the Bavarian Environmental Agency (LfU), for the borehole data.

This research has been supported by the AlpSenseRely project, funded by the Bavarian State Ministry of the Environment and Consumer Protection (grant no. TUS01UFS-76976), and by the HydroPF project, funded by the TUM International Graduate School of Science and Engineering (IGSSE).

References

- 580 Aalto, J., Karjalainen, O., Hjort, J., and Luoto, M.: Statistical Forecasting of Current and Future Circum-Arctic Ground Temperatures and Active Layer Thickness, *Geophysical Research Letters*, 45, 4889–4898, <https://doi.org/10.1029/2018GL078007>, 2018.
- Abdulsamad, F., Bock, J., Magnin, F., Malet, E., Revil, A., Ben-Asher, M., Richard, J., Duvillard, P.-A., Karaoulis, M., Condom, T., Ravanel, L., and Deline, P.: Rockwall permafrost dynamics evidenced by repeated and Automated Electrical Resistivity Tomography at Aiguille du Midi (3842 m a.s.l., French Alps), *The Cryosphere*, 20, 2181–2207, <https://doi.org/10.5194/TC-20-2181-2026>, 2026.
- 585 AEG: Die Bayerische Zugspitzbahn, Tech. rep., Berlin, 1931.
- Bast, A., Kenner, R., and Phillips, M.: Short-term cooling, drying, and deceleration of an ice-rich rock glacier, *The Cryosphere*, 18, 3141–3158, <https://doi.org/10.5194/TC-18-3141-2024>, 2024.
- Binley, A., Ramirez, A., and Daily, W.: Regularized image reconstruction of noisy electrical resistance tomography data, in: *Proceedings of the 4h Workshop of the European Concerted Action on Process Tomography*, edited by Beck, M., pp. 401–401, 1995.
- 590 Biskaborn, B. K., Smith, S. L., Noetzli, J., Matthes, H., Vieira, G., Streletskiy, D. A., Schoeneich, P., Romanovsky, V. E., Lewkowicz, A. G., Abramov, A., Allard, M., Boike, J., Cable, W. L., Christiansen, H. H., Delaloye, R., Diekmann, B., Drozdov, D., Etzel Müller, B., Grosse, G., Guglielmin, M., Ingeman-Nielsen, T., Isaksen, K., Ishikawa, M., Johansson, M., Johannsson, H., Joo, A., Kaverin, D., Kholodov, A., Konstantinov, P., Kröger, T., Lambiel, C., Lanckman, J.-P., Luo, D., Malkova, G., Meiklejohn, I., Moskalenko, N., Oliva, M., Phillips, M., Ramos, M., Sannel, A. B. K., Sergeev, D., Seybold, C., Skryabin, P., Vasiliev, A., Wu, Q., Yoshikawa, K., Zheleznyak, M., and Lantuit, H.: Permafrost is warming at a global scale, *Nature Communications*, 10, 264, <https://doi.org/10.1038/s41467-018-08240-4>, 2019.
- 595 Bommer, C., Phillips, M., Keusen, H.-R., Teyssere, P., Forschungsanstalt für Wald, E., and Wsl, L.: *Bauen im Permafrost Ein Leitfaden für die Praxis*, 2009.
- Buckel, J., Mudler, J., Gardeweg, R., Hauck, C., Hilbich, C., Frauenfelder, R., Kneisel, C., Buchelt, S., Blöthe, J. H., Hördt, A., and Bücken, M.: Identifying mountain permafrost degradation by repeating historical electrical resistivity tomography (ERT) measurements, *The Cryosphere*, 17, 2919–2940, <https://doi.org/10.5194/tc-17-2919-2023>, 2023.
- 600 Cathala, M., Bock, J., Magnin, F., Ravanel, L., Ben Asher, M., Astrade, L., Bodin, X., Chambon, G., Deline, P., Faug, T., Genuite, K., Jaillet, S., Josnin, J.-Y., Revil, A., and Richard, J.: Predisposing, triggering and runout processes at a permafrost-affected rock avalanche site in the French Alps (Étache, June 2020), *Earth Surface Processes and Landforms*, <https://doi.org/10.1002/esp.5881>, 2024.
- Cimpoiasu, M. O., Kuras, O., Harrison, H., Wilkinson, P. B., Meldrum, P., Chambers, J. E., Liljestrand, D., Oroza, C., Schmidt, S. K., Sommers, P., Irons, T. P., and Bradley, J. A.: Characterization of a Deglaciated Sediment Chronosequence in the High Arctic Using Near-Surface Geoelectrical Monitoring Methods, *Permafrost and Periglacial Processes*, 35, 157–171, <https://doi.org/10.1002/PPP.2220;SUBPAGE:STRING:FULL>, 2024.
- 605 Cimpoiasu, M. O., Kuras, O., Harrison, H., Wilkinson, P. B., Meldrum, P., Chambers, J. E., Liljestrand, D., Oroza, C., Schmidt, S. K., Sommers, P., Vimercati, L., Irons, T. P., Lyu, Z., Solon, A., and Bradley, J. A.: High-resolution 4D electrical resistivity tomography and below-ground point sensor monitoring of High Arctic deglaciated sediments capture zero-curtain effects, freeze–thaw transitions, and mid-winter thawing, *Cryosphere*, 19, 401–421, <https://doi.org/10.5194/TC-19-401-2025>, 2025.
- Delforge, D., Watlet, A., Kaufmann, O., Camp, M. V., and Vanclooster, M.: Time-series clustering approaches for subsurface zonation and hydrofacies detection using a real time-lapse electrical resistivity dataset, *Journal of Applied Geophysics*, 184, 104203, <https://doi.org/10.1016/J.JAPPGEO.2020.104203>, 2021.

- 615 Deline, P., Gruber, S., Amann, F., Bodin, X., Delaloye, R., Failletaz, J., Fischer, L., Geertsema, M., Giardino, M., Hasler, A., Kirkbride, M.,
Krautblatter, M., Magnin, F., McColl, S., Ravel, L., Schoeneich, P., and Weber, S.: Ice loss from glaciers and permafrost and related slope
instability in high-mountain regions, *Snow and Ice-Related Hazards, Risks, and Disasters*, pp. 501–540, <https://doi.org/10.1016/B978-0-12-817129-5.00015-9>, 2021.
- Doetsch, J., Ingeman-Nielsen, T., Christiansen, A., Fiandaca, G., Auker, E., and Elberling, B.: Direct current (DC) resistivity and induced
620 polarization (IP) monitoring of active layer dynamics at high temporal resolution, *Cold Regions Science and Technology*, 119, 16–28,
<https://doi.org/10.1016/j.coldregions.2015.07.002>, 2015.
- Duvillard, P. A., Revil, A., Qi, Y., Soueid Ahmed, A., Coperey, A., and Ravel, L.: Three-Dimensional Electrical Conductivity
and Induced Polarization Tomography of a Rock Glacier, *Journal of Geophysical Research: Solid Earth*, 123, 9528–9554,
<https://doi.org/10.1029/2018JB015965>, 2018.
- 625 Duvillard, P. A., Magnin, F., Revil, A., Legay, A., Ravel, L., Abdulsamad, F., and Coperey, A.: Temperature distribution in a permafrost-
affected rock ridge from conductivity and induced polarization tomography, *Geophysical Journal International*, 225, 1207–1221,
<https://doi.org/10.1093/gji/ggaa597>, 2021.
- Etzelmüller, B., Guglielmin, M., Hauck, C., Hilbich, C., Hoelzle, M., Isaksen, K., Noetzli, J., Oliva, M., and Ramos, M.: Twenty
years of European mountain permafrost dynamics-the PACE legacy, *Environmental Research Letters*, 15, <https://doi.org/10.1088/1748-9326/ABAE9D>, 2020.
- 630 Etzelmüller, B., Czekirka, J., Magnin, F., Duvillard, P.-A. A., Ravel, L., Malet, E., Aspaas, A., Kristensen, L., Skrede, I.,
Majala, G. D., Jacobs, B., Leinauer, J., Hauck, C., Hilbich, C., Böhme, M., Hermanns, R., Eriksen, H. O. Ø., Lauknes, T. R.,
Krautblatter, M., and Westermann, S.: Permafrost in monitored unstable rock slopes in Norway – new insights from temperature
and surface velocity measurements, geophysical surveying, and ground temperature modelling, *Earth Surface Dynamics*, 10, 97–129,
635 <https://doi.org/10.5194/esurf-10-97-2022>, 2022.
- Etzelmüller, B., Isaksen, K., Czekirka, J., Westermann, S., Hilbich, C., and Hauck, C.: Rapid warming and degradation of mountain
permafrost in Norway and Iceland, *The Cryosphere*, 17, 5477–5497, <https://doi.org/10.5194/tc-17-5477-2023>, 2023.
- Farzamian, M., Vieira, G., Monteiro Santos, F. A., Yaghoobi Tabar, B., Hauck, C., Paz, M. C., Bernardo, I., Ramos, M., and de Pablo,
M. A.: Detailed detection of active layer freeze–thaw dynamics using quasi-continuous electrical resistivity tomography (Deception Island,
640 Antarctica), *The Cryosphere*, 14, 1105–1120, <https://doi.org/10.5194/tc-14-1105-2020>, 2020.
- Galleman, T., Haas, U., Teipel, U., von Poschinger, A., Wagner, B., Mahr, M., and Bäte, F.: Permafrost-Messstation am Zugspitzgipfel:
Ergebnisse und Modellberechnungen, Tech. rep., 2017.
- Galleman, T., Wagner, B., Foltyn, M., Mahr, M., and Jerz, H.: Permafrost und Böden im Bereich der Zugspitze, *Geologica Bavarica*, 120,
2021.
- 645 Gruber, S., Fleiner, R., Guegan, E., Panday, P., Schmid, M. O., Stumm, D., Wester, P., Zhang, Y., and Zhao, L.: Review article: Inferring
permafrost and permafrost thaw in the mountains of the Hindu Kush Himalaya region, *Cryosphere*, 11, 81–99, <https://doi.org/10.5194/TC-11-81-2017>, 2017.
- Haberkorn, A., Kenner, R., Noetzli, J., and Phillips, M.: Changes in Ground Temperature and Dynamics in Mountain Permafrost in the Swiss
Alps, *Frontiers in Earth Science*, 9, 1–21, <https://doi.org/10.3389/feart.2021.626686>, 2021.
- 650 Hauck, C.: Geophysical methods for detecting permafrost in high mountains, Ph.D. thesis, Technischen Hochschule Zurich, 2001.
- Hauck, C. and Hilbich, C.: Preconditioning of mountain permafrost towards degradation detected by electrical resistivity, *Environmental
Research Letters*, 19, 064 010, <https://doi.org/10.1088/1748-9326/ad3c55>, 2024.

- Hauck, C. and Vonder Muehll, D.: Inversion and interpretation of two-dimensional geoelectrical measurements for detecting permafrost in mountainous regions, *Permafrost and Periglacial Processes*, 14, 305–318, <https://doi.org/10.1002/ppp.462>, 2003.
- 655 Herring, T., Lewkowicz, A., Hauck, C., Hilbich, C., Mollaret, C., Oldenborger, G., Uhlemann, S., Farzamian, M., Calmels, F., and Scandroglio, R.: Best practices for using electrical resistivity tomography to investigate permafrost, *Permafrost and Periglacial Processes*, 34, 494–512, <https://doi.org/10.1002/ppp.2207>, 2023.
- Hilbich, C., Hauck, C., Hoelzle, M., Scherler, M., Schudel, L., Völksch, I., Vonder Muehll, D., and Mäusbacher, R.: Monitoring mountain permafrost evolution using electrical resistivity tomography: A 7-year study of seasonal, annual, and long-term variations at Schilthorn, Swiss Alps, *Journal of Geophysical Research*, 113, F01S90, <https://doi.org/10.1029/2007JF000799>, 2008.
- 660 Hilbich, C., Fuss, C., and Hauck, C.: Automated Time-lapse ERT for Improved Process Analysis and Monitoring of Frozen Ground, *Permafrost and Periglacial Processes*, 22, 306–319, <https://doi.org/10.1002/ppp.732>, 2011.
- Hornung, T. and Haas, U.: Erläuterungen zu den Blättern 8531/8631 Zugspitze & 8531/8632 Garmisch-Partenkirchen, Tech. rep., Bayrisches Landesamt für Umwelt, Augsburg, 2017.
- 665 Huggel, C., Clague, J. J., and Korup, O.: Is climate change responsible for changing landslide activity in high mountains?, *Earth Surface Processes and Landforms*, 37, 77–91, <https://doi.org/10.1002/ESP.2223>, 2012.
- Kellerer-Pirklbauer, A. and Eulenstein, J.: The summer heatwave in 2022 and its role in changing permafrost and periglacial conditions at a historic mountain pass in the Eastern Alps (Hochtor, Hohe Tauern Range, Austria), *Permafrost and Periglacial Processes*, 34, 547–565, <https://doi.org/10.1002/PPP.2205>, 2023.
- 670 Kemna, A., Binley, A., Ramirez, A., and Daily, W.: Complex resistivity tomography for environmental applications, *Chemical Engineering Journal*, 77, 11–18, [https://doi.org/10.1016/S1385-8947\(99\)00135-7](https://doi.org/10.1016/S1385-8947(99)00135-7), 2000.
- Keuschnig, M., Hartmeyer, I., Höfer-Öllinger, G., Schober, A., Krautblatter, M., and Schrott, L.: Permafrost-Related mass Movements: Implications from a Rock Slide at the Kitzsteinhorn, Austria, *Engineering Geology for Society and Territory - Volume 1: Climate Change and Engineering Geology*, pp. 255–259, https://doi.org/10.1007/978-3-319-09300-0_48/FIGURES/5, 2015.
- 675 Keuschnig, M., Krautblatter, M., Hartmeyer, I., Fuss, C., and Schrott, L.: Automated Electrical Resistivity Tomography Testing for Early Warning in Unstable Permafrost Rock Walls Around Alpine Infrastructure, *Permafrost and Periglacial Processes*, 28, 158–171, <https://doi.org/10.1002/ppp.1916>, 2017.
- Kneisel, C.: New insights into mountain permafrost occurrence and characteristics in glacier forefields at high altitude through the application of 2D resistivity imaging, *Permafrost and Periglacial Processes*, 15, 221–227, <https://doi.org/10.1002/PPP.495>, 2004.
- 680 Kneisel, C., Rödder, T., and Schwindt, D.: Frozen ground dynamics resolved by multi-year and yearround electrical resistivity monitoring at three alpine sites in the Swiss Alps, *Near Surface Geophysics*, 12, 117–132, <https://doi.org/10.3997/1873-0604.2013067>, 2014.
- Koestel, J., Kemna, A., Javaux, M., Binley, A., and Vereecken, H.: Quantitative imaging of solute transport in an unsaturated and undisturbed soil monolith with 3-D ERT and TDR, *Water Resources Research*, 44, 1–17, <https://doi.org/10.1029/2007WR006755>, 2008.
- Körner, H. and Ulrich, R.: Geologische und felsmechanische Untersuchungen für die Gipfelstation der Seilbahn Eibsee - Zugspitze, in: *Geologica Bavarica* 55, pp. 404–421, 1965.
- 685 Krautblatter, M.: Detection and quantification of permafrost change in alpine rock walls and implications for rock instability, Ph.D. thesis, Universität Bonn, 2009.
- Krautblatter, M. and Hauck, C.: Electrical resistivity tomography monitoring of permafrost in solid rock walls, *Journal of Geophysical Research: Earth Surface*, 112, 1–14, <https://doi.org/10.1029/2006JF000546>, 2007.

- 690 Krautblatter, M., Verleysdonk, S., Flores-Orozco, A., and Kemna, A.: Temperature-calibrated imaging of seasonal changes in permafrost rock walls by quantitative electrical resistivity tomography (Zugspitze, German/Austrian Alps), *Journal of Geophysical Research: Earth Surface*, 115, 1–15, <https://doi.org/10.1029/2008JF001209>, 2010.
- Krautblatter, M., Funk, D., and Günzel, F. K.: Why permafrost rocks become unstable: a rock-ice-mechanical model in time and space, *Earth Surface Processes and Landforms*, 38, 876–887, <https://doi.org/10.1002/esp.3374>, 2013.
- 695 LaBrecque, D. J., Miletto, M., Daily, W., Ramirez, A., and Owen, E.: The effects of noise on Occam’s inversion of resistivity tomography data, *Geophysics*, 61, 538–548, <https://doi.org/10.1190/1.1443980>, 1996.
- Lesparre, N., Nguyen, F., Kemna, A., Robert, T., Hermans, T., Daoudi, M., and Flores-Orozco, A.: A new approach for time-lapse data weighting in electrical resistivity tomography, *GEOPHYSICS*, 82, E325–E333, <https://doi.org/10.1190/geo2017-0024.1>, 2017.
- Lewkowicz, A. G., Etzelmüller, B., and Smith, S. L.: Characteristics of Discontinuous Permafrost based on Ground Temperature Measurements and Electrical Resistivity Tomography, Southern Yukon, Canada, *Permafrost and Periglacial Processes*, 22, 320–342, <https://doi.org/10.1002/PPP.703>, 2011.
- 700 Limbrock, J. K., Weigand, M., and Kemna, A.: Temperature Dependence of the Low-Frequency Electrical Properties of Partially Frozen Rocks, *Journal of Geophysical Research: Solid Earth*, 130, e2024JB030870, <https://doi.org/10.1029/2024JB030870>, 2025.
- Lin, C., Kjellström, E., Wilcke, R. A. I., and Chen, D.: Present and future European heat wave magnitudes: climatologies, trends, and their associated uncertainties in GCM-RCM model chains, *Earth System Dynamics*, 13, 1197–1214, [https://doi.org/10.5194/ESD-13-1197-](https://doi.org/10.5194/ESD-13-1197-2022)
- 705 2022, 2022.
- Lindner, F., Wassermann, J., and Igel, H.: Seasonal Freeze-Thaw Cycles and Permafrost Degradation on Mt. Zugspitze (German/Austrian Alps) Revealed by Single-Station Seismic Monitoring, *Geophysical Research Letters*, 48, 1–11, <https://doi.org/10.1029/2021GL094659>, 2021.
- 710 Luo, H., Jougnot, D., Jost, A., Limbrock, J. K., Wang, S., Thanh, L. D., and Kemna, A.: Bayesian inference of hysteretic behavior of unfrozen water content and electrical conductivity in saturated frozen rocks, *Journal of Hydrology*, 645, 132–146, <https://doi.org/10.1016/J.JHYDROL.2024.132146>, 2024.
- Magnin, F., Deline, P., Ravanel, L., Noetzi, J., and Pogliotti, P.: Thermal characteristics of permafrost in the steep alpine rock walls of the Aiguille du Midi (Mont Blanc Massif, 3842 m a.s.l.), *Cryosphere*, 9, 109–121, <https://doi.org/10.5194/tc-9-109-2015>, 2015.
- 715 Magnin, F., Westermann, S., Pogliotti, P., Ravanel, L., Deline, P., and Malet, E.: Snow control on active layer thickness in steep alpine rock walls (Aiguille du Midi, 3842 m a.s.l., Mont Blanc massif), *CATENA*, 149, 648–662, <https://doi.org/10.1016/J.CATENA.2016.06.006>, 2017.
- Magnin, F., Ravanel, L., Bodin, X., Deline, P., Malet, E., Krysiński, J. M., and Schoeneich, P.: Main results of permafrost monitoring in the French Alps through the PermaFrance network over the period 2010–2022, *Permafrost and Periglacial Processes*, <https://doi.org/10.1002/PPP.2209>, 2023.
- 720 Maierhofer, T., Orozco, A. F., Roser, N., Limbrock, J. K., Hilbich, C., Moser, C., Kemna, A., Drigo, E., Cella, U. M. D., and Hauck, C.: Spectral induced polarization imaging to monitor seasonal and annual dynamics of frozen ground at a mountain permafrost site in the Italian Alps, *Cryosphere*, 18, 3383–3414, <https://doi.org/10.5194/TC-18-3383-2024>, 2024.
- Mamot, P., Weber, S., Schröder, T., and Krautblatter, M.: A temperature-and stress-controlled failure criterion for ice-filled permafrost rock joints, *The Cryosphere*, 12, 3333–3353, <https://doi.org/10.5194/tc-12-3333-2018>, 2018.
- 725 Mamot, P., Weber, S., Eppinger, S., and Krautblatter, M.: A temperature-dependent mechanical model to assess the stability of degrading permafrost rock slopes, *Earth Surface Dynamics*, 9, 1125–1151, <https://doi.org/10.5194/esurf-9-1125-2021>, 2021.

- Marescot, L., Loke, M. H., Chapellier, D., Delaloye, R., Lambiel, C., and Reynard, E.: Assessing reliability of 2D resistivity imaging in mountain permafrost studies using the depth of investigation index method, *Near Surface Geophysics*, 1, 57–67, <https://doi.org/10.3997/1873-0604.2002007>, 2003.
- Masiokas, M. H., Rabatel, A., Rivera, A., Ruiz, L., Pitte, P., Ceballos, J. L., Barcaza, G., Soruco, A., Bown, F., Berthier, E., Dussailant, I., and MacDonell, S.: A Review of the Current State and Recent Changes of the Andean Cryosphere, *Frontiers in Earth Science*, 8, 503 838, <https://doi.org/10.3389/feart.2020.00099>, 2020.
- Mayer, C., Weber, M., Wendt, A., and Hagg, W.: Die bayerischen Gletscher, die verbliebenen Eisreserven Deutschlands, *Polarforschung*, 89, 1–7, <https://doi.org/10.5194/POLF-89-1-2021>, 2021.
- Miller, H.: Zur Geologie des westlichen Wetterstein- und Mieminger Gebirges., Phdthesis, LMU München, 1962.
- Mollaret, C., Hilbich, C., Pellet, C., Flores-Orozco, A., Delaloye, R., and Hauck, C.: Mountain permafrost degradation documented through a network of permanent electrical resistivity tomography sites, *The Cryosphere*, 13, 2557–2578, <https://doi.org/10.5194/tc-13-2557-2019>, 2019.
- Morard, S., Hilbich, C., Mollaret, C., Pellet, C., and Hauck, C.: 20-year permafrost evolution documented through petrophysical joint inversion, thermal and soil moisture data, *Environmental Research Letters*, <https://doi.org/10.1088/1748-9326/AD5571>, 2024.
- Muller, S. W.: Permafrost, or permanently frozen ground and related engineering problems, <https://catalog.hathitrust.org/Record/001514161https://hdl.handle.net/2027/mdp.39015006088929https://hdl.handle.net/2027/wu.89078556354https://babel.hathitrust.org/cgi/pt?id=mdp.39015006088929&seq=7>, 1947.
- Noetzli, J. and Pellet, C. e.: PERMOS Swiss Permafrost Bulletin 2023., Tech. Rep. September 2022, <https://doi.org/10.13093/permos-bull-24>, 2024.
- Noetzli, J., Gruber, S., and Haeberli, W.: 3D-Modellierung der thermischen Bedingungen im Bereich des Gipfelgrates der Zugspitze, Tech. rep., Bavarian State Ministry of the Environment. Glaciology and Geomorphodynamics Group, Department of Geography, University of Zurich, 2006.
- Noetzli, J., Isaksen, K., Barnett, J., Christiansen, H. H., Delaloye, R., Etzelmueller, B., Farinotti, D., Gallemann, T., Guglielmin, M., Hauck, C., Hilbich, C., Hoelzle, M., Lambiel, C., Magnin, F., Oliva, M., Paro, L., Pogliotti, P., Riedl, C., Schoeneich, P., Valt, M., Vieli, A., and Phillips, M.: Enhanced warming of European mountain permafrost in the early 21st century, *Nature Communications* 2024 15:1, 15, 1–15, <https://doi.org/10.1038/s41467-024-54831-9>, 2024.
- Offer, M., Weber, S., Krautblatter, M., Hartmeyer, I., and Keuschnig, M.: Pressurised water flow in fractured permafrost rocks revealed by borehole temperature, electrical resistivity tomography, and piezometric pressure, *The Cryosphere*, 19, 485–506, <https://doi.org/10.5194/tc-19-485-2025>, 2025.
- Offer, M., Hartmeyer, I., Weber, S., Keuschnig, M., and Krautblatter, M.: Seasonal thermo-hydro-mechanical dynamics of permafrost rockwalls revealed by automated electrical resistivity monitoring, *EGUsphere* (preprint), pp. 1–32, <https://doi.org/10.5194/EGUSPHERE-2025-6091>, 2026.
- Parkhomenko, E. I.: *Electrical Properties of Rocks*, Springer US, Boston, MA, <https://doi.org/10.1007/978-1-4615-8609-8>, 1967.
- Pavoni, M., Boaga, J., Wagner, F. M., Bast, A., and Phillips, M.: Characterization of rock glaciers environments combining structurally-coupled and petrophysically-coupled joint inversions of electrical resistivity and seismic refraction datasets, *Journal of Applied Geophysics*, 215, 105 097, <https://doi.org/10.1016/J.JAPPGEO.2023.105097>, 2023.

- Phillips, M., Wolter, A., Lüthi, R., Amann, F., Kenner, R., and Bühler, Y.: Rock slope failure in a recently deglaciated permafrost rock wall at Piz Kesch (Eastern Swiss Alps), February 2014, *Earth Surface Processes and Landforms*, 42, 426–438, <https://doi.org/10.1002/esp.3992>, 2017.
- Phillips, M., Buchli, C., Weber, S., Boaga, J., Pavoni, M., and Bast, A.: Brief communication: Combining borehole temperature, borehole piezometer and cross-borehole electrical resistivity tomography measurements to investigate seasonal changes in ice-rich mountain permafrost, *The Cryosphere*, 17, 753–760, <https://doi.org/10.5194/tc-17-753-2023>, 2023.
- Pogliotti, P., Guglielmin, M., Cremonese, E., Morra Di Cella, U., Filippa, G., Pellet, C., and Hauck, C.: Warming permafrost and active layer variability at Cime Bianche, Western European Alps, <https://doi.org/10.5194/tc-9-647-2015>.
- Rödder, T. and Kneisel, C.: Permafrost mapping using quasi-3D resistivity imaging, Murtèl, Swiss Alps, *Near Surface Geophysics*, 10, 117–127, <https://doi.org/10.3997/1873-0604.2011029>, 2012.
- Sass, O.: Rock moisture measurements: Techniques, results, and implications for weathering, *Earth Surface Processes and Landforms*, 30, 359–374, <https://doi.org/10.1002/esp.1214>, 2005.
- Scandroglio, R., Draebing, D., Offer, M., and Krautblatter, M.: 4D quantification of alpine permafrost degradation in steep rock walls using a laboratory-calibrated electrical resistivity tomography approach, *Near Surface Geophysics*, 19, 241–260, <https://doi.org/10.1002/nsg.12149>, 2021.
- Scandroglio, R., Weber, S., Rehm, T., and Krautblatter, M.: Decadal in situ hydrological observations and empirical modeling of pressure head in a high-alpine, fractured calcareous rock slope, *Earth Surface Dynamics*, 13, 295–314, <https://doi.org/10.5194/ESURF-13-295-2025>, 2025.
- Slater, L., Binley, A., Daily, W., and Johnson, R.: Cross-hole electrical imaging of a controlled saline tracer injection, *Journal of Applied Geophysics*, 44, 85–102, [https://doi.org/10.1016/S0926-9851\(00\)00002-1](https://doi.org/10.1016/S0926-9851(00)00002-1), 2000.
- Smith, S. L., O'Neill, H. B., Isaksen, K., Noetzli, J., and Romanovsky, V. E.: The changing thermal state of permafrost, *Nature Reviews Earth & Environment* 2022, 3, 10–23, <https://doi.org/10.1038/s43017-021-00240-1>, 2022.
- Supper, R., Ottowitz, D., Jochum, B., Römer, A., Pfeiler, S., Kauer, S., Keuschnig, M., and Ita, A.: Geoelectrical monitoring of frozen ground and permafrost in alpine areas: Field studies and considerations towards an improved measuring technology, *Near Surface Geophysics*, 12, 93–115, <https://doi.org/10.3997/1873-0604.2013057>, 2014.
- Tomaškovičová, S. and Ingeman-Nielsen, T.: Quantification of freeze–thaw hysteresis of unfrozen water content and electrical resistivity from time lapse measurements in the active layer and permafrost, *Permafrost and Periglacial Processes*, 35, 79–97, <https://doi.org/https://doi.org/10.1002/ppp.2201>, 2024.
- Tso, C. H. M., Kuras, O., Wilkinson, P. B., Uhlemann, S., Chambers, J. E., Meldrum, P. I., Graham, J., Sherlock, E. F., and Binley, A.: Improved characterisation and modelling of measurement errors in electrical resistivity tomography (ERT) surveys, *Journal of Applied Geophysics*, 146, 103–119, <https://doi.org/10.1016/J.JAPPGEO.2017.09.009>, 2017.
- Tsytovlch, N. A. and Sumgin, M. I.: Principles of Mechanics of Frozen Ground - Osnovaniia mekhaniki merzlykh gruntov, vol. 13, Translated from the Russian by E. A. Golomshtok, Moscow-Leningrad, izdatepatv edn., 1937.
- Ulrich, R. and King, L.: Influence of mountain permafrost on construction in the Zugspitze mountains, Bavarian alps, Germany, in: International conference; 6th, Permafrost; 1993; Beijing, pp. 625–630, South China University of Technology Press, <https://www.tib.eu/en/search/id/BLCP%3ACN015187124/Influence-of-Mountain-Permafrost-on-Construction/>, 1993.

- 800 Voigt, C., Schulz, K., Koch, F., Wetzel, K., Timmen, L., Rehm, T., Pflug, H., Stolarczuk, N., Förste, C., and Flechtner, F.: Technical note: Introduction of a superconducting gravimeter as novel hydrological sensor for the Alpine research catchment Zugspitze, *Hydrology and Earth System Sciences*, 25, 5047–5064, <https://doi.org/10.5194/HESS-25-5047-2021>, 2021.
- Vonder Muehll, D., Hauck, C., and Lehmann, F.: Verification of geophysical models in Alpine permafrost using borehole information, *Annals of Glaciology*, 31, 300–306, <https://doi.org/10.3189/172756400781820057>, 2000.
- 805 Vonder Muehll, D., Hauck, C., Gubler, H., McDonald, R., and Russill, N.: New geophysical methods of investigating the nature and distribution of mountain permafrost with special reference to radiometry techniques, *Permafrost and Periglacial Processes*, 12, 27–38, <https://doi.org/10.1002/PPP.382>, 2001.
- Wagner, B., Galleman, T., Foltyn, M., Joneck, M., and Mahr, M.: Permafrost Analysis for the Alpine Monitoring Station at Zugspitze (Bavaria, Germany): Measurements, Modeling and Climate Impacts, *Research Square (Preprint)*, <https://doi.org/10.21203/RS.3.RS-3142479/V1>, 2023.
- 810 Walter, F., Amann, F., Kos, A., Kenner, R., Phillips, M., de Preux, A., Huss, M., Tognacca, C., Clinton, J., Diehl, T., and Bonanomi, Y.: Direct observations of a three million cubic meter rock-slope collapse with almost immediate initiation of ensuing debris flows, *Geomorphology*, 351, 106933, <https://doi.org/10.1016/j.geomorph.2019.106933>, 2020.
- Watlet, A., Thirugnanam, H., Singh, B., Kumar M., N., Brahmanandan, D., Inauen, C., Swift, R., Meldrum, P., Uhlemann, S., Wilkinson, P.,
815 Chambers, J., and Ramesh, M. V.: 4D electrical resistivity to monitor unstable slopes in mountainous tropical regions: an example from Munnar, India, *Landslides* 2023, pp. 1–14, <https://doi.org/10.1007/S10346-023-02029-3>, 2023.
- Wetzel, K.: On the hydrology of the Partnach area in the Wetterstein mountains (Bavarian Alps), *Erdkunde*, 58, 172–186, 2004.
- Wrobel, J.: Bericht über den Markierungsversuch auf dem Zugspitzplatt im Sommer 1980, *Tech. rep.*, Bayerisches Geologisches Landesamt, Munich, 1980.

ERT settings
for TERRAMETER LS

NEW TASK

	Hauptstollen	Seitenstollen
spread	2X21S	2X21S
protocol	WEN32SX	WEN32SX ScNachWe
min. el. spacing X	4.6	1.53
min. el. spacing Y	1	1
min. el. spacing Z	1	1

RECEIVER SETTINGS

measure mode	RES
min. stacks	2
max. stacks	4
error limit	1 %
delay time	0.2 s
acq. time	0.2 s
full Wave Form	Yes
power line frequency	50 Hz

TRANSMITTER SETTINGS

min. current	0.5 mA
max. current	50 mA
max. power	250 W
max. output volt	600 V
electrode test	Focus One
bad electrode	600 kΩm
fail electrode	600 kΩm
electrode test current	1 mA

Figure S1. ERT settings.




Figure S2. Temperature profiles B-B' in the side tunnel. The location of the transect is visible in Fig. 1b.

Extra-analysis of tunnel temperatures. a) Correlation between rock temperatures and the external air temperature, measured at the DWD station. b) Correlation between AT loggers and the DWD air temperature. c) In blue is presented the 2-week moving mean of RST (image d), in red is the mean annual rock surface temperature. d) Photo of the new ST-loggers and the old UTL-loggers. All sensors are located at a depth of 40 cm. The old loggers were replaced in 2019, with a one-year overlapping period. e) Photos of the MT-loggers. All sensors are located at a depth of 40 cm. f) Photo of the RST logger installed on the north face, close to Electrode E30, at 10 cm depth.




Figure S3. Comparison of tunnel temperatures with those from the LfU borehole under the summit station. a) Location of the tunnel loggers. Please note that the numbering starts from the north wall ($X_{north} = 0m$). b)-c) Location of the LfU borehole (modified from Gallemann et al. (2017)). Please note that here the numbering starts from the south wall ($X_{north} = 43.7m$). d)-f) Comparison of the TUM RST logger and the LfU-43m logger. e)-g)-h) Comparison of TUM ST-5/ST-10 logger and LfU-41m/39m logger.




Figure S4. Comparison of tunnel temperatures with those from the LfU borehole under the summit station, second part. a)-b) Comparison of ST-10 TUM-logger and LfU-9/41m logger. c) Comparison of TUM ST-15 logger and multiple LfU loggers. d) Comparison of TUM ST-20 logger and multiple LfU loggers.




Figure S5. Mapping of surface ice in the tunnel. Upper graph: Surface coverage of the tunnel. Lower graph: Percentage of the ground covered by ice.




Figure S6. Comparison of temperatures and their closest apparent resistivities.




Figure S7. Field calibration. a) Apparent resistivity measured at the closest point to the respective ST-Logger. b-e) Correlation between ST-loggers and apparent resistivity. Only measurements from 2019 are included in the interpolation because new temperature loggers have a higher resolution. In red: resulting interpolation line with respective equation and R^2 value. In green, line after the calibration of Krautblatter et al. (2010).




Figure S8. Other Error models. Upper Figure: Normal vs reciprocal measurements. Middle Figure: Error modeling according to Koestel et al. (2008). Lower Figure: Error modeling after Lasparre et al. (2017).




Figure S9. Inversion statistics: RMS and iterations number. a) Comparison of the old in brown and new error model in green. b) Variation of RMS and iterations number for all the measurements, computed with the new error model.



Figure S10. Upper image: External view of the area outside the tunnel. The letters represent the features shown in Figure [??9a](#). Lower [imageimages](#): Internal view of [the side tunnel \(left\) at Logger ST-15 and main tunnel \(right\) in the temporary frozen area \(b\)](#).