Reservoir-Induced Seismicity in China: Systematic Characterization and Implications for Hazard Assessment

Jiashan Zhang[1], Changsheng Jiang[1, 2, 3, *], Fengling Yin[1, 2, 3], Yiming Zhu[1], Hongyu Zhai[1, 3], Jinmeng Bi[4], Yan Zhang[1]

[1)] Institute of Geophysics, China Earthquake Administration, No. 5 South Minzu University Road, Haidian District, Beijing 100081, China

[2)] Beijing Baijiatuan Earth Sciences National Observation and Research Station, Beijing 100095, China

[3)] Key Laboratory of Earthquake Source Physics, China Earthquake Administration, Beijing 100081, China

[4)] Tianjin Earthquake Agency, No. 19 Youyi Road, Hexi District, Tianjin 300201, China

Correspondence: Changsheng Jiang (jiangcs@cea-igp.ac.cn)

Abstract: Reservoir-Induced Seismicity (RIS) poses a significant geological risk for large-scale hydropower projects. However, its nationwide characteristics remain poorly understood in China, the country with the world's largest hydropower capacity. This study integrates a high-resolution national reservoir dataset (CRD) with a unified earthquake catalog since 1970 to establish a screening-eligible sample of 1,435 large/medium-sized reservoirs (impounded between 1971 and 2015) in China. Based on spatiotemporal clustering criteria, we systematically identified 88 induced-type reservoirs — that is, reservoirs exhibiting spatiotemporally clustered seismicity significantly associated with impoundment. Analysis of this dataset reveals

fundamental characteristics of RIS in China: Spatially, induced-type reservoirs are selectively concentrated in tectonically active regions like the eastern margin of the Tibetan Plateau, showing significant coupling with active faults and historical seismicity. In the near field, 95% of RIS events occur within 24.8 km of the reservoir shoreline. Temporally, the time lag between impoundment and peak seismicity, together with the distance-dependent occurrence rate, follows patterns governed primarily by pore pressure diffusion, leading to the development of a W-score model for probabilistic RIS identification. In terms of sequence characteristics, RIS exhibits statistically distinct parameters of their frequency-magnitude distribution (*e.g.*, lower α-value, higher *b*-value) compared to natural earthquakes, revealing a unique physical process of activating near-critical faults via pore pressure diffusion. The spatial evolution of the *b*-value further confirms an effective permeability boundary of pore water penetration at approximately 30-40 km, far exceeding the current Chinese national standard (10 km). Correlation analysis shows that static reservoir parameters (*e.g.*, reservoir capacity, dam height, and reservoir major axis length) are statistically intercorrelated; thus, only one parameter should be selected for hazard analysis. Reservoir capacity greater than 3.2×10^8 m^3 or reservoir major axis length exceeding 15.9 km could serve as quantitative thresholds for preliminary risk screening during the planning stage. However, correlation matrix analysis reveals only weak correlations between all static/dynamic parameters and the maximum magnitude (M_{max}), highlighting the urgent need for physics-based mechanistic models. This study provides the first national-scale systematic characterization of RIS in China, a quantitative identification tool (W-score),

and key engineering thresholds for RIS risk assessment in China, pointing towards future directions beyond traditional empirical models.

Keywords: Reservoir-induced seismicity, earthquake sequence parameters, pore pressure diffusion, seismic hazard

1 Introduction

Reservoir-Induced Seismicity (RIS), a typical example of human engineering activities altering the local crustal stress field and triggering seismic events, holds significant engineering and scientific value (Gupta, 2002). From an engineering perspective, even low-magnitude RIS can cause damaging shaking and social impact in steep terrain due to its shallow source characteristics, potentially triggering secondary disasters like rockfalls (Julian and Foulger, 2010). Scientifically, RIS provides a unique natural laboratory for understanding the critical role of fluids in fault instability (Talwani, 1997). The physical mechanisms linking reservoir impoundment to triggered seismicity are broadly categorized into two end-member processes (Talwani, 1997; Simpson *et al*., 1988). Elastic loading by the water column causes near-instantaneous crustal flexure and stress changes, typically affecting the near field within hours to weeks. In contrast, pore-pressure diffusion involves infiltration of reservoir water along fractures and faults, elevating pore pressure and reducing effective normal stress on pre-existing planes of weakness; this mechanism can operate over several tens of kilometres and produces a characteristic delayed response from months to years. The interplay between these processes, modulated by local fault permeability and crustal stress state, governs the

characteristic spatiotemporal signatures of RIS—namely, the distance-dependent decay of seismicity rates and the post-impoundment time lag analysed in the present study. While over 200 RIS cases have been reported globally, systematic, national-scale studies remain relatively scarce, with only a few countries like Canada, France, and Brazil having conducted comprehensive analyses based on their own data (Lamontagne *et al*., 2018; Grasso *et al*., 2018; Barros *et al*., 2018). These studies reveal that RIS occurrence is not random but strongly controlled by the regional tectonic setting. For instance, RIS in Canada is concentrated within the ancient, stable Canadian Shield, associated with the reactivation of fragile faults from paleo-rifts, with a typically limited affected distance (<5 km, Lamontagne *et al*., 2018). In France, RIS primarily occurs in active tectonic zones like the Western Alpine Arc and the Pyrenees, and its spatial distribution can be normalized using the reservoir major axis length as a characteristic scale (Grasso *et al*., 2018). Research in Brazil further indicates that RIS probability is significantly higher in regions of strong natural tectonic seismicity (Peak Ground Acceleration, PGA > 0.1g; i.e., PGA with 10% probability of exceedance in 50 years, or approximately a 475-year return period), suggesting that a critically stressed crust is a key prerequisite (Barros *et al*., 2018). Beyond spatial distributions, these global case studies have also established empirical understanding regarding the spatiotemporal evolution of induced sequences. For example, all RIS events in Canada are concentrated within 5 km of the reservoir shoreline, related to the permeability of faults near the reservoir and the localized effect of pore pressure diffusion (Lamontagne *et al*., 2018). In France, the spatial distribution of RIS can be normalized using the

reservoir major axis length as a characteristic scale, with the earthquake occurrence rate within 1~3 times the reservoir major axis being 4.5 times higher than in the far-field (10 times the reservoir major axis), confirming the localized nature of tectonic stress perturbation (Grasso *et al*., 2018). Regarding the time lag between RIS occurrence and the initial impoundment, previous studies found that RIS in Canada is predominantly characterized by a delayed response, where the Time Lag is negatively correlated with fault permeability (Lamontagne *et al*., 2018). In France, 62% of RIS events occur within 2 years after impoundment, corresponding to a rapid response to elastic loading, consistent with Simpson *et al*. (1988) Type I model (Grasso *et al*., 2018). These regional systematic studies have greatly enhanced our understanding of RIS patterns, but their conclusions are derived from specific, mostly moderately to low-active tectonic settings. Consequently, a key scientific question is whether these patterns apply to the world's most active tectonic domains. Addressing this question remains urgent.

As the country with the largest global hydropower capacity, China has accumulated valuable insights into RIS through case studies over the long term. The early case of the Xinfengjiang Reservoir in Guangdong Province, South China, is a globally recognized typical RIS event (Talwani, 1997; Gupta, 2002). Recent studies further revealed renewed intensification of seismicity northwest of the reservoir area after 2012, interpreted as the reactivation of a pre-existing NW-SE trending fault due to increased pore pressure from reservoir water infiltration (Dong *et al*., 2022). Research on the Three Gorges Reservoir in central China (Hubei Province and Chongqing Municipality) uncovered complex spatiotemporal patterns of its seismicity, which can be divided into

near-field (0~12 km) and far-field (32~70 km) areas, possibly controlled by different mechanisms (Li and Luo, 2022). In the lower reaches of the Jinsha River, impoundment of cascade reservoirs like Xiluodu and Xiangjiaba (Sichuan-Yunnan border region, China) was shown to alter the local stress field through the dual mechanisms of "elastic loading and pore pressure diffusion," and was highly correlated in time and space with a series of earthquakes with surface-wave magnitude M_S>4.5 (Miao *et al*., 2025; Zhang *et al*., 2021). These case studies not only confirm the presence of RIS in China but also preliminarily highlight the critical role of pore pressure diffusion in specific Chinese geological environments (*e.g*., areas with high-permeability faults and karst), where its influence range may far exceed traditional understanding (Miao *et al*., 2025).

Despite significant progress in case studies, the systematic patterns of RIS at the national scale in China remain unclear. Due to the lack of a unified, high-precision coupled dataset of national reservoirs and earthquakes, fundamental scientific questions persist: To what extent is the spatial distribution of RIS controlled by macro-tectonic patterns? What are the common characteristics of its spatiotemporal evolution? Do sequence behaviors exhibit nationwide statistical fingerprints? What are the quantitative influences of static or dynamic reservoir parameters on seismic activity? This knowledge gap directly hampers the precision of engineering practice. China's current risk assessment standards (GB/T 21075-2007) largely rely on early international experience and static models (Simpson *et al*., 1988; Gupta, 2002). Whether their core parameters (*e.g*., the 10 km influence range) are universally applicable in China's complex and diverse geological environments, especially in the southwestern region

with widely developed high-permeability faults, has become a critical issue requiring urgent verification.

Addressing the above questions, this study makes the first attempt at a comprehensive, multi-dimensional characterization of RIS across China. We integrated the high-resolution China Reservoir Dataset (CRD) with a unified national earthquake catalog spanning over fifty years to construct a screening sample (i.e., the initial pool of candidate reservoirs subjected to the induced-seismicity screening) of 1,435 large/medium-sized reservoirs (first impounded between 1971/01/01 and 2015/03/27). Using unified spatiotemporal clustering criteria, we systematically identified 88 induced-type reservoirs (i.e., reservoirs exhibiting spatiotemporally clustered seismicity significantly associated with impoundment; see Section 3 for detailed screening criteria). Based on this, to date, the most complete national-scale RIS dataset, this paper systematically examines the spatial distribution pattern of RIS in China and its coupling with the regional tectonic background, the spatiotemporal evolution and sequence characteristics of induced seismicity, the statistical differences between RIS and natural earthquake sequences, and the quantitative correlations between reservoir attributes and the RIS maximum magnitude (defined as the largest magnitude within the identified induced sequence for a given reservoir). The results of this study will provide insights into the macroscopic patterns of RIS in the world's most active tectonic domain and contribute to the development of more physics-based risk assessment methods.

2 Data Sources and Screening Sample Construction

This study utilizes seismic data from the National Unified Official Earthquake Catalog provided by the China Earthquake Networks Center (CENC, http://10.5.160.18/console/exit.action, last accessed on April 15, 2025). The catalog spans from January 1, 1970, to March 27, 2025, and contains basic parameters for all earthquakes recorded by the national and regional seismic networks within China's territory. Compiled and processed centrally by the CENC, this catalog integrates observation reports from provincial and national centers to produce a unified earthquake catalog and report (Dai *et al*., 2019). The seismic monitoring capability, represented by the minimum completeness magnitude (M_C), of the China Seismograph Network has evolved significantly since 1970. For eastern China, where reservoirs are densely distributed, the M_C was approximately local magnitud (M_L) 3.0~3.5 in the 1970s, improved to M_L 2.0~2.5 during 1980~2001, and after the nationwide digital upgrade of the network around 2009, the M_C reached or even fell below M_L 2.0 in most regions (Mignan *et al*., 2013; Wang *et al*., 2017). This macroscopic evolution of monitoring capability and the actual recorded data were considered during the identification of induced seismicity sequences for individual reservoirs. While dedicated seismic networks at individual reservoir sites often provide more complete data with lower M_C, accessing such data uniformly across China is challenging. Therefore, this study utilizes the *National Unified Official Earthquake Catalog*, which offers the significant advantages of relatively consistent spatial coverage across China and a long-term record spanning over 50 years.

The spatial distribution and fundamental attributes of reservoirs are primarily sourced

178 from the China Reservoir Dataset (CRD; Song *et al*., 2022). The CRD is a
179 comprehensive dataset constructed based on the interpretation of high-resolution
180 satellite imagery, providing vector boundaries and key attributes—including name,
181 geographic location, reservoir capacity, reservoir surface area, and administrative
182 region—for 97,435 reservoirs across China. Compared to mainstream international
183 databases (*e.g*., GeoDAR, GOODD and GRanD), the CRD offers significant
184 advantages in terms of reservoir coverage, spatial resolution, and attribute
185 completeness within China (Song *et al*., 2022). Specifically, the CRD catalogs 97,435
186 vectorized reservoir polygons—approximately one to two orders of magnitude more
187 than the Chinese subsets of GRanD (~900), GeoDAR (~4,900), and GOODD
188 (~9,200)—and achieves near-complete coverage of small reservoirs (<1 km^2, and
189 especially <0.1 km^2) that are largely absent from global products. Its boundaries are
190 mapped from high-resolution satellite imagery (including 10 m Sentinel-2 data for
191 narrow valley reservoirs), and it compiles essential engineering attributes such as
192 storage capacity and surface area indispensable for reservoir-induced seismicity
193 characterization.
194 Critical parameters for identifying RIS, such as the initial impoundment time, dam
195 height, and reservoir capacity, were obtained through the integration of multi-source,
196 heterogeneous data. We systematically collected publicly available academic literature,
197 sources like the *Encyclopedia of Chinese Rivers and Lakes*, local gazetteers,
198 government reports, and news archives. The CRD contains 4,854 medium and large
199 reservoirs (reservoir capacity ≥ 0.1×10^8 m^3), for which, we performed rigorous cross-

validation and data fusion. Due to limitations in data availability, the precision of the obtained initial impoundment times varies. For times precise only to the month, the last day of that month was taken as the initial impoundment time; for times precise only to the year, January 1 of the following year was used. This dataset is nearly complete for large reservoirs (reservoir capacity $\geq 1\times10^8$ m^3) nationwide, comprising 746 reservoirs, accounting for 84.29% of the corresponding large reservoirs in the CRD. For medium reservoirs, 2,111 were compiled, representing 53.39% of the corresponding medium reservoirs in the CRD. Among the 1,997 reservoirs with incomplete records, 1,433 (71.76%) have a reservoir capacity below 0.3×10^8 m^3. As this study requires comparing seismic activity for at least one year before initial impoundment and examining seismicity for at least ten years after impoundment, only those 1,435 reservoirs with initial impoundment dates between January 1, 1971, and March 27, 2015, were selected as the target group for identifying induced seismicity. The spatial distribution of the full 4,854-reservoir set, the 1,435-reservoir screening sample, and the excluded reservoirs is presented in *Supplementary Material* S1 and Figure S1; the close similarity in their geographic patterns confirms that the screening process does not introduce spatial bias into the characterization of induced-type reservoirs.

3 Methods

3.1 Identification Criteria for Induced Seismicity

As this study focuses on the overall statistical characteristics of RIS, we did not employ quantitative probabilistic methods like the spatiotemporal Epidemic-Type Aftershock Sequence (ETAS) model (Zhuang *et al*., 2002) or the nearest neighbor distance (NND)

method (Zaliapin *et al.*, 2008) for cluster identification. Instead, we adopted an approach similar to Bi and Jiang (2019), manually selecting the natural boundaries of spatiotemporal earthquake clusters. To facilitate reproducibility, this manual selection followed a standardized three-step protocol applied to each of the 1,435 reservoirs: (1) Temporal distinguishability — a sharp, sustained post-impoundment increase in cumulative seismicity, assessed at M_C = M_L 2.0, 2.5, and 3.0, was required, clearly separable from pre-impoundment background trends; reservoirs showing only a continuation of background activity, or increases attributable to regional tectonic episodes, were rejected. (2) Spatial separability — induced clusters must exhibit compact, shoreline-proximal aggregation (dominant distance peak typically at 0~10 km) with geometries consistent with local fault reactivation by pore-pressure diffusion, whereas diffuse alignments along major regional active faults with strong background activity were classified as natural tectonic clustering and excluded. (3) Spatiotemporal congruence — the temporal and spatial anomalies must coincide in the same near-reservoir volume, preventing misclassification of distant post-impoundment tectonic swarms.

3.2 Normalization and Spatiotemporal Coupling (W-score) Method

Based on the identified induced seismicity sequences from the 88 reservoirs, this study uses a completeness magnitude of M_L2.5 and a sequence duration of 10 years after initial impoundment to investigate the distance-from-shoreline distribution and time lag distribution characteristics of RIS. Since the occurrence rate varies significantly among different RIS sequences, we normalized the frequency for each sequence to extract

common patterns. Specifically, the earthquake frequency in each distance or time bin was divided by the total number of earthquakes in the respective RIS sequence, so that the sum of normalized frequencies (relative frequencies) for all bins equals 1, intuitively reflecting the proportion of earthquakes in each bin. The statistical distributions from all RIS sequences were then stacked and normalized again.

To quantitatively characterize the spatiotemporal coupling features of RIS, this study adopted the W-score method from Ghofrani and Atkinson (2020). In constructing this national-scale model, we adopt a first-order assumption of spatiotemporal uniformity: the characteristic distance decay and post-impoundment time lag are treated as statistically uniform across all tectonic provinces and reservoir geologies. This simplification is necessary to obtain a robust, generalizable baseline from the nationwide ensemble, but it inherently neglects regional variations in crustal permeability, stress regime, and lithology. Based on the spatial and temporal evolution characteristics described above, we constructed a power-law decay distribution function for the distance from the shoreline (d) and a hybrid power-law and linear distribution function for the time lag (t). Empirical functions were obtained by fitting the actual data as follows:

$$f(d)=0.118e^{-0.121d} \quad (1)$$

$$f(t)= -0.107e^{-5.686t}-0.003t+0.039 \quad (2)$$

Assuming equal weight for the empirical function of distance (d) and the empirical function of time lag (t), the comprehensive W-score formula was established as follows:

$$W= \frac{\{f(d)+f(t)\}}{2} \quad (3)$$

3.3 Sequence Parameter Calculation (*b*-value, *p*-value, *α*-value)

For the *b*-value calculation, we followed the approach of Yin and Jiang (2024), using the continuous distribution function given by Ogata and Katsura (1993) to describe the magnitude-frequency distribution (FMD), hereafter referred to as the OK1993 model:

$$\lambda(\beta|m)=e^{-\beta m}\frac{1}{\sqrt{2\pi\sigma^2}}\int_{-\infty}^{M}e^{\frac{(x-\mu)^2}{2\sigma^2}}dx, \quad (4)$$

where λ is the expected number of earthquakes, m is the magnitude, σ is the standard deviation of the normal distribution describing the detection capability, x is the integration variable, and μ is the magnitude at which the detection probability is 0.5. M is the maximum magnitude in the earthquake catalog used for calculation, and the power-law exponent β is related to the traditional Gutenberg-Richter (G-R) relation *b*-value by $\beta=b\cdot log10$. Specifically, the value of β was obtained by fitting the log-likelihood function of the OK1993 model using the maximum likelihood method, and the *b*-value was subsequently estimated.

We used the time-dependent Epidemic-Type Aftershock Sequence (ETAS) model to calculate the parameters *p*-value and *α*-value. The conditional intensity function of the ETAS model can be expressed as (Ogata, 1988):

$$\lambda(t^*)=\mu+K\sum_{t_i<t^*}\frac{e^{\alpha(M_i-M_0)}}{(t^*-t_i+c)^p}, M_i>M_0 \quad (5)$$

In the above equation, t^* is the time after the mainshock, M_0 is the cutoff magnitude (typically set equal to the completeness magnitude M_C); M_i and t_i are the magnitude and occurrence time of the *i*-th event, respectively, $\lambda(t^*)$ is the conditional intensity function, μ is the background seismicity rate of the source region, c is the time after the mainshock when the aftershock frequency peaks, and the constant K represents the

productivity of aftershocks. The p-value for natural tectonic earthquakes is typically around 1.0, and the α-value is generally greater than 1.0 but is usually less than 1.0 for swarm-like sequences (Ogata, 2001). Limited by an insufficient number of earthquakes ($N < 40$) in some RIS sequences —where 40 events is an empirical threshold widely used in earthquake sequence parameter fitting to ensure stability (*e.g.* Bi *et al.*, 2022)— or large uncertainties in the sequence parameters (determined as the standard errors derived from the maximum likelihood estimation, δb, δp, $\delta \alpha$ > parameter/10), we successfully calculated the corresponding parameters for 38 RIS sequences.

3.4 Correlation Analysis Methods

To comprehensively analyze the potential correlations with M_{max}, we employed both the Pearson correlation coefficient (r) (Pearson, 1895), suitable for linear correlation analysis, and the Spearman correlation coefficient (ρ) (Spearman, 1904), suitable for non-linear monotonic correlation analysis. The Pearson correlation coefficient is a statistic based on linear relationships, measuring the strength of linear correlation by calculating the standardized covariance. Its value ranges from [-1, 1], with positive values indicating a positive correlation and negative values a negative correlation (Pearson, 1895). Its mathematical expression is:

$$r=\frac{\sum (x_i-\bar{x})(y_i-\bar{y})}{\sqrt{\sum (x_i-\bar{x})^2 \sum (y_i-\bar{y})^2}} \quad (6)$$

The Spearman correlation coefficient is a non-parametric rank-based coefficient used to capture non-linear monotonic relationships, particularly suitable for non-normally distributed data or data containing outliers (Spearman, 1904). Its mathematical expression is:

$$\rho = 1 - \frac{6\sum d_i^2}{n(n^2-1)} \quad (7)$$

In the above equations, x represents the logarithmically transformed inducing factor, y represents the maximum magnitude, and d_i is the difference in ranks. Using these two methods in combination allows for the identification of both linear trends and non-linear monotonic relationships, with significance testing ($P < 0.05$ considered significant) ensuring robust conclusions.

4 Results

4.1 Spatial Distribution of Induced-Type Reservoirs

By applying the identification criteria described above, we operationally examined seismic events within 50 km of the reservoir shoreline and screened them against these criteria to select RIS sequences. Figure 1 shows an example of RIS identification for the Jinping-I Reservoir. Located on the main stream of the Yalong River in Yanyuan and Muli counties, Liangshan Prefecture, Sichuan Province, China, this reservoir is a key component of the Jinping-I Hydropower Station. It has a total reservoir capacity of 7.76 billion cubic meters, serves annual regulation functions, and provides comprehensive benefits including power generation, flood control, and sediment retention. Initial impoundment began at 09:26 on November 30, 2012. Within the following year, significant earthquake clustering occurred around the reservoir (Figure 1a). Notably, two distinct seismic clusters emerged near the central part and the western end (tail) of the reservoir, close to the shoreline, with a maximum magnitude of M_S 4.3 (surface-wave magnitude; determined from 20-second surface-wave amplitudes). These two clusters, delineated by purple dashed polygons in Figure 1a, were manually

selected as candidate induced sequences. Analyzing the distance-from-shoreline distribution for earthquakes within these clusters, selected using the minimum magnitude of magnitudes (M_C, used as the lower-bound cut-off) of M_L 2.0, 2.5, and 3.0, revealed similar characteristics: events were primarily concentrated within 0~12 km of the shoreline, with a peak distribution at 4~5 km (Figure 1b). Similarly, examining the temporal evolution of the cumulative frequency for these candidate sequences (using different M_C thresholds) and comparing it with the cumulative frequency of background seismicity (unselected events within 50 km) and all earthquakes in the area, shows a distinct increase in the candidate sequences starting around 250 days after impoundment. This increase clearly distinguishes them from the background seismicity, the total seismicity, and the pre-impoundment background activity (Figure 1c). This consistency satisfies the three identification criteria proposed herein. Therefore, the Jinping-I Reservoir is classified as an induced-type reservoir, and the selected sequences are identified as RIS sequences. As the spatiotemporal patterns remain consistent across different M_C values, indicating the stability of the identification results, we used the sequences filtered with $M_C = M_L2.5$—considering the completeness of the catalog in the reservoir area—as the dataset for subsequent analysis. Applying the above RIS identification methodology to the 1,435 large/medium reservoirs in the study period, we identified 88 induced-type reservoirs, comprising 56 large reservoirs and 32 medium reservoirs. Their spatial distribution is shown in Figure 2a, and basic information is listed in Table 1.




Figure 1. Example of identified reservoir-induced seismicity sequences at the Jinping-I Reservoir. (a) Reservoir boundary and spatial distribution of seismicity. Gray dots represent background seismicity recorded from 1970 to the initial impoundment; red dots represent earthquakes after the initial impoundment; purple dashed lines outline the spatiotemporal clusters of induced sequences; black curves denote active faults since the Late Pleistocene; gradient green areas indicate zones within 10, 20, 30, 40, and 50 km from the reservoir shoreline. Note that gray dots represent cumulative seismicity over ~42 years (1970~2012), whereas red dots represent cumulative seismicity over only 10 years (2012~2022); therefore, spatial densities are not directly comparable. The inset shows the location of the study area. (b) Normalized frequency distribution of induced earthquakes as a function of distance from the reservoir shoreline (for the 0~20 km range, with 1 km bins). Subplots (from top to bottom) show results for M_C of M_L 2.0, 2.5, and 3.0, respectively. (c) Temporal comparison of cumulative earthquake frequency (from one year before to ten years after the initial impoundment). "Inside" denotes earthquakes located within the

manually delineated induced-seismicity clusters (outlined by the purple dashed polygons in Fig. 1(a), "outside" denotes background seismicity within 50 km of the reservoir shoreline but outside those cluster boundaries, and "all" denotes all earthquakes within the 50 km buffer. Note that all curves are normalized to their respective maximum values. Consequently, the initial slope of the outside curve during the pre-impoundment baseline reflects the normalization of a small number of background events rather than an abrupt increase in seismicity. The green vertical dashed line marks the time of initial impoundment. Subplots (from top to bottom) correspond to (M_C) of M_L 2.0, 2.5, and 3.0, respectively.




Figure 2. Spatial distribution characteristics of reservoir-induced seismicity in China. (a) Spatial distribution of large/medium-sized reservoirs and reservoirs with induced seismicity. Blue polygons represent large/medium-sized reservoirs (capacity ≥ 0.1×10^8 m^3) with complete

parameters (*e.g.*, impoundment time, dam height); red polygons represent reservoirs with induced seismicity, identified based on spatiotemporal clustering. The green oblique box schematically outlines the approximate extent of the Sichuan-Yunnan rhombic block, highlighting the tectonic region where reservoir-induced earthquakes are predominantly concentrated. (b) Spatial density of reservoirs with induced seismicity (units: number per square degree). (c) Spatial distribution of the proportion of reservoirs with induced seismicity among all large/medium-sized reservoirs. (d) Density distribution of M≥4.0 earthquakes in China (units: number per square degree) and mapped active faults (brown lines, Xu *et al*., 2016). This threshold is chosen to illustrate the long-term regional tectonic setting and active fault framework, distinct from the M_C=M_L2.5 catalog used for RIS sequence analysis.

Table 1. Inventory of 88 identified induced-reservoirs in China with reservoir properties and parameters of the largest induced earthquake (M_{max}).

No.	Reservoir Name	Initial Impoundment Date	Reservoir Capacity (10^8 m^3)	Reservoir Area (km^2)	Dam Height (m)	Major Axis (km)	Capacity /Area (m)	M_{max} Distance (km)	Time Lag (days)	Peak Lag (days)	M_{max} Event Details			
											Date	Mag.	Lat. (°N)	Lon . (°E)
1	Dali	1975/08/30	0.117	1.36	62.00	1.85	8.60	17.20	17918	470	2024/09/18	4.8	31.97	117.50
2	Yinpan	2011/04/30	3.200	11.24	80.00	11.02	109.00	6.27	2400	3376	2017/11/23	5.0	29.39	107.99
3	Shuikou	1993/03/31	23.400	100.27	101.00	66.90	23.30	0.27	5455	9724	2008/03/06	4.2	26.37	118.67
4	Admiralty	2010/05/30	1.060	3.16	97.50	5.86	33.50	1.11	1193	642	2013/09/04	4.8	25.64	118.75
5	Haidianxia	2005/12/13	0.298	3.19	46.00	11.71	9.30	0.93	1402	4200	2009/10/15	3.9	35.02	103.79
6	Jiudianxia	2007/12/01	10.040	24.06	136.00	29.47	41.70	0.65	508	2647	2009/04/22	3.4	34.82	103.81
7	Jiefangcun	1971/08/30	0.606	6.09	16.00	3.86	10.00	9.25	14244	14248	2010/08/29	2.8	39.91	98.95
8	Xiaoxia	2004/09/30	0.480	18.40	50.70	46.66	2.60	4.11	5951	50	2021/01/14	4.0	36.06	104.07
9	Chaijiaxia	2007/07/30	0.166	3.17	33.00	7.70	5.20	5.06	5436	14200	2022/06/16	3.7	36.21	103.47
10	Daxia	1996/11/30	0.900	6.18	70.00	23.20	14.60	13.86	8812	3938	2021/01/14	4.0	36.06	104.07
11	Bikou	1976/01/01	5.210	13.94	101.80	23.31	37.40	12.31	11872	11873	2008/07/03	4.0	32.70	105.00
12	Zhaizhaizi	1989/10/30	0.120	1.39	25.00	1.35	8.60	2.66	5937	2185	2006/01/30	3.0	38.43	100.95

No.	Reservoir Name	Initial Impoundment Date	Reservoir Capacity (10^8 m^3)	Reservoir Area (km^2)	Dam Height (m)	Major Axis (km)	Capacity /Area (m)	M_{max} Distance (km)	Time Lag (days)	Peak Lag (days)	M_{max} Event Details			
											Date	Mag.	Lat. (°N)	Lon . (°E)
13	Longshou II	2002/04/30	0.177	1.99	146.50	5.50	8.90	12.64	525	752	2003/10/06	4.2	38.82	100.02
14	Shuangshusi	1975/05/30	0.111	1.30	58.50	3.73	8.50	10.83	10376	10376	2003/10/25	6.1	38.35	100.93
15	Jinjiang	1973/07/01	4.180	20.18	63.20	12.23	20.70	19.81	18389	2357	2023/11/04	4.9	22.09	112.24
16	Fengzishan	1977/01/01	0.149	1.69	93.00	3.18	8.80	13.56	17109	17109	2023/11/04	4.9	22.09	112.24
17	Yangjiang Nuclear	2005/06/30	0.118	1.37	101.00	3.20	8.60	0.06	1835	1835	2010/07/09	3.9	21.74	112.30
18	Jintan	2008/01/01	2.490	7.57	123.30	8.07	32.90	6.62	3205	3203	2016/10/10	2.8	24.52	113.10
19	Hengxi	1978/07/30	0.312	3.33	82.00	4.71	9.40	6.21	15495	15469	2020/12/31	3.4	25.03	113.16
20	Dahua	1982/05/01	9.640	13.01	78.50	33.50	74.10	5.72	3938	233	1993/02/10	4.9	23.63	107.88
21	Yantan	1992/03/01	33.500	126.86	110.00	110.58	26.40	5.96	11168	5609	2022/09/28	4.3	24.34	107.46
22	Longtan	2006/09/30	273.000	372.08	216.50	178.12	73.40	0.00	6348	194	2024/02/15	4.3	25.20	106.73
23	Letan	2006/01/07	9.500	32.66	80.00	49.67	29.10	4.63	4223	6188	2017/07/31	4.2	23.93	108.60
24	Jinjitan	2009/04/05	2.309	5.75	42.70	21.35	40.20	15.90	2659	7959	2016/07/16	3.4	23.43	107.49
25	Guangzhao	2007/12/30	32.450	47.83	200.50	33.00	67.90	8.74	279	717	2008/10/04	4.0	26.00	105.35
26	Huanghuazhai	2010/10/18	1.630	3.95	110.00	13.65	41.30	30.24	5001	5001	2024/06/27	4.1	25.44	106.55
27	Shannipo	2014/11/26	0.850	3.28	119.40	13.55	25.90	4.77	3528	1015	2024/07/24	4.5	26.27	104.74
28	Sanbanxi	2006/01/01	40.940	80.18	185.50	54.63	51.10	0.45	3375	3985	2015/03/30	5.5	26.58	108.84
29	Tianshengqiao II	1992/12/30	0.121	1.40	178.00	13.60	8.60	2.86	2783	1535	2000/08/13	3.9	24.92	105.12
30	Tianshengqiao I	1998/08/01	108.000	174.65	178.00	84.64	61.80	0.75	67	3998	1998/10/06	4.0	24.65	104.85
31	Dongqing	2009/08/20	9.550	23.37	150.00	27.96	40.90	1.97	411	573	2010/10/04	4.3	25.51	105.75
32	Shatuo	2013/04/20	9.100	23.78	116.50	62.45	38.30	0.00	2357	5024	2019/10/02	4.7	28.42	108.38
33	Goupitan	2008/11/29	64.510	87.53	232.50	72.56	73.70	0.91	4570	5455	2021/06/04	3.6	27.42	107.48
34	Dalong	2006/09/30	4.680	14.34	65.50	17.20	32.60	4.16	4708	13163	2019/08/20	4.0	18.52	109.40
35	Baicaoping	1974/01/01	0.465	2.07	42.00	2.77	22.50	5.30	14399	14388	2013/06/03	3.2	37.63	114.27
36	Pingwang	1977/12/30	0.304	3.24	23.50	3.56	9.40	5.83	2086	952	1983/09/15	4.1	37.52	114.27
37	Xiaolangdi	1999/09/30	126.500	235.35	154.00	70.89	53.70	0.00	1347	605	2003/06/08	3.6	35.08	111.93
38	Gaoguan	1973/12/30	2.120	13.13	45.60	9.58	16.10	23.85	11990	11990	2006/10/27	4.2	31.48	113.08
39	Xiaka River	1980/01/01	0.259	1.53	28.50	4.13	16.90	2.23	10714	10714	2009/05/01	3.2	31.46	112.24
40	Longyu Lake	1975/04/30	0.248	2.70	16.00	5.59	9.20	9.53	12421	12421	2009/05/01	3.2	31.46	112.24

No.	Reservoir Name	Initial Impoundment Date	Reservoir Capacity (10^8 m^3)	Reservoir Area (km^2)	Dam Height (m)	Major Axis (km)	Capacity /Area (m)	M_{max} Distance (km)	Time Lag (days)	Peak Lag (days)	M_{max} Event Details			
											Date	Mag.	Lat. (°N)	Lon . (°E)
41	Geheyan	1993/04/10	34.000	73.12	151.00	77.95	46.50	7.69	51	910	1993/05/30	3.3	30.32	110.97
42	Xuanmiaoguan	2005/04/30	0.129	1.48	65.50	4.13	8.70	2.42	6626	548	2023/06/21	3.3	31.30	111.31
43	Tianfumiao	1978/01/12	0.625	2.40	62.30	7.00	26.00	5.17	16596	7670	2023/06/21	3.3	31.30	111.31
44	Three Gorges	2003/06/01	393.000	894.20	181.00	450.21	44.00	5.25	3852	5907	2013/12/16	5.1	31.10	110.45
45	Mengquan	1981/01/01	0.511	5.56	43.00	5.68	9.20	4.42	9362	11436	2006/08/19	3.6	29.37	111.33
46	Dongjiang	1986/07/31	92.700	168.88	157.00	40.50	54.90	28.56	10936	5014	2016/07/08	4.1	25.90	113.05
47	Wanmipo	2003/11/30	3.780	10.01	64.50	15.27	37.80	10.55	4631	355	2016/08/03	3.3	28.72	109.37
48	Yihe Nuoer	1987/10/30	1.664	15.33	4.70	7.16	10.90	18.31	6945	17918	2006/11/03	4.2	43.55	119.68
49	Shankouyan	2012/06/21	1.050	3.90	99.10	6.54	26.90	11.91	1842	4591	2017/07/06	2.9	27.60	113.91
50	Baishan	1982/11/16	62.200	139.88	149.50	81.33	44.50	8.31	9760	3698	2009/08/05	4.2	42.27	127.19
51	Biliuhe	1983/08/26	9.340	56.86	53.30	21.53	16.40	0.00	5281	1101	1998/02/08	4.2	39.92	122.48
52	Shenwo	1972/11/30	7.910	37.18	50.30	18.16	21.30	2.31	753	5217	1974/12/22	5.2	41.20	123.60
53	Bando	2010/10/23	0.150	1.46	78.72	7.20	10.30	0.20	2185	3622	2016/10/16	2.9	35.30	100.27
54	Modo	2009/12/30	1.186	5.00	73.00	8.08	23.70	11.69	2482	27	2016/10/16	2.9	35.30	100.27
55	Xiaogangou	1991/11/30	0.110	0.77	55.00	4.68	14.30	10.22	10554	1440	2020/10/21	3.0	35.92	94.84
56	Hot Spring	1993/08/30	2.550	43.99	17.50	15.56	5.80	0.00	4595	752	2006/03/30	3.5	35.73	95.37
57	Dangka	2015/01/15	0.154	1.74	32.60	5.73	8.90	2.53	2689	5436	2022/05/26	4.1	32.56	96.61
58	Jiangkou	1992/05/12	2.770	22.97	50.70	33.09	12.10	6.33	7616	466	2013/03/18	3.3	31.61	107.76
59	Yangjiaba	1999/06/30	0.144	1.64	53.40	4.54	8.80	9.77	7795	7726	2020/10/31	4.0	32.10	105.17
60	Gongzui	1979/01/01	3.570	17.37	85.60	27.63	20.60	7.92	13163	1420	2015/01/14	5.0	29.30	103.20
61	Jinping I	2012/11/30	77.600	85.88	305.00	70.67	90.40	0.70	1486	1320	2016/12/25	4.3	27.89	101.38
62	Busey	2010/09/28	0.694	6.90	140.80	11.35	10.10	7.74	641	2783	2012/06/30	3.9	28.13	101.18
63	Guandi	2011/10/30	7.597	18.39	168.00	40.18	41.30	13.11	233	408	2012/06/19	3.3	28.24	101.72
64	Guanyinyan	2010/07/01	22.500	45.38	159.00	71.64	49.60	17.38	3837	9618	2021/01/01	3.5	26.21	101.24
65	Ertan	1985/04/30	58.000	98.65	240.00	90.26	58.80	6.55	3985	744	1996/03/28	3.7	27.35	101.88
66	Qiaoqi	2006/12/05	2.120	4.15	123.00	4.24	51.10	5.49	1187	3863	2010/03/05	3.5	30.78	102.75
67	Xiangjiaba	2012/10/10	51.630	99.57	161.00	85.55	51.90	23.10	676	4867	2014/08/17	5.2	28.12	103.51
68	Mangcuo Lake	1980/01/01	2.700	21.77	30.00	8.11	12.40	3.68	14227	2014	2018/12/13	4.9	29.60	98.84
69	Awoduo	2005/10/10	0.147	1.67	53.20	2.49	8.80	2.69	5225	2689	2020/01/30	4.5	28.66	91.97
70	Sujiahekou	2010/04/05	2.230	5.67	131.49	13.54	39.30	8.23	3663	3663	2020/04/15	3.7	25.26	98.30

No.	Reservoir Name	Initial Impoundment Date	Reservoir Capacity (10^8 m^3)	Reservoir Area (km^2)	Dam Height (m)	Major Axis (km)	Capacity /Area (m)	M_{max} Distance (km)	Time Lag (days)	Peak Lag (days)	M_{max} Event Details			
											Date	Mag.	Lat. (°N)	Lon . (°E)
71	Xiaowan	2008/12/16	150.000	196.66	292.00	124.62	76.30	11.87	2510	3683	2015/10/30	5.0	25.04	99.44
72	Qinghai Lake	2011/05/17	0.654	6.53	6.70	5.09	10.00	4.78	927	6945	2013/11/28	4.7	25.40	100.58
73	Gongguoqiao	2011/09/21	3.160	13.28	105.00	35.06	23.80	4.88	2068	927	2017/05/20	4.1	25.66	99.34
74	Longjiang	2010/03/01	12.170	32.59	110.00	35.46	37.30	0.11	5255	2274	2024/07/19	4.5	24.30	98.10
75	Liyuan	2014/11/10	7.270	16.14	155.00	44.49	45.00	5.98	353	7586	2015/10/29	4.8	27.55	100.30
76	Madushan	2010/12/01	5.510	21.53	105.50	50.16	25.60	0.00	2151	1572	2016/10/21	3.0	23.20	102.91
77	Yunpeng	2006/12/03	1.407	13.16	104.00	38.28	10.70	7.82	3897	18389	2017/08/04	3.9	24.20	103.65
78	Rudila	2013/04/30	17.183	64.32	140.00	55.29	26.70	2.21	2274	676	2019/07/21	4.9	26.15	100.55
79	Ahai	2011/12/11	8.280	24.09	138.00	54.27	34.40	3.84	1382	645	2015/09/22	3.7	27.69	100.29
80	Nuozhadu	2013/10/17	237.000	299.76	261.50	117.15	79.10	1.69	3995	6348	2024/09/23	4.0	23.37	100.06
81	Ma'anshan	1984/01/01	0.134	1.53	16.60	2.28	8.80	20.47	14399	9814	2023/06/03	2.9	22.86	104.58
82	Leidatan	2006/02/03	0.940	6.04	84.00	24.26	15.60	2.47	4200	256	2017/08/04	3.9	24.20	103.65
83	Xiluodu	2013/05/04	126.700	127.99	285.50	137.88	99.00	2.25	470	14227	2014/08/17	5.2	28.12	103.51
84	Jiaokou	1973/05/01	1.200	4.59	66.00	6.00	26.10	2.06	7799	13283	1994/09/07	4.7	29.82	121.25
85	Lubu	1983/11/30	0.263	1.69	34.00	2.56	15.60	14.80	3934	9419	1994/09/07	4.7	29.82	121.25
86	Lishimen	1978/03/30	1.990	7.47	74.30	8.77	26.60	4.28	14200	4708	2017/02/13	4.0	29.09	120.68
87	Shanxi	2001/01/01	18.240	40.79	132.00	25.76	44.70	0.00	1865	3852	2006/02/09	4.6	27.68	120.00
88	Lanxiqiao	1984/07/30	0.140	1.07	78.00	3.08	13.10	5.26	4958	4958	1998/02/24	3.6	27.58	119.13

Based on the 88 identified induced-type reservoirs, we systematically analyzed their spatial distribution characteristics. The results indicate a pronounced regional clustering of induced-type reservoirs in China, predominantly concentrated in the tectonically most active southwestern region, especially central Sichuan-Yunnan rhombic block and southwestern Yunnan, with only sporadic occurrences in southeastern coastal and northeastern regions (Figure 2a). This spatial pattern is highly consistent when viewed in terms of the density (number per unit area) of induced-type reservoirs (Figure 2b) and their proportion relative to all large/medium reservoirs within a region (Figure 2c).

The southwestern region is not only the core area of China's hydropower resources and the most densely populated area for large/giant reservoirs but also has the highest identified proportion of induced-type reservoirs, highlighting the elevated risk of induced seismicity for large reservoirs in specific tectonic environments. Visual spatial overlay comparison with the regional tectonic background (active faults since the Late Pleistocene) and the spatial distribution of moderate-to-strong seismicity ($M \geq 4.0$ earthquakes since 1970, Figure 2d) reveals a clear spatial consistency between the distribution of induced-type reservoirs and areas of active tectonics and seismicity. Therefore, compared to the overall distribution of large/medium reservoirs nationwide, the spatial distribution of induced-type reservoirs is highly selective and primarily controlled by regional tectonic activity. In particular, the strong crustal deformation, high tectonic stress accumulation, and widely developed active fault systems along the eastern margin of the Tibetan Plateau provide favorable mechanical conditions and pathways for reservoir water infiltration, fault weakening, and earthquake triggering. In contrast, the relatively stable tectonic eastern plains, despite having numerous reservoirs, show a significantly lower incidence of induced seismicity. This marked spatial correlation reveals the non-uniformity of reservoir-induced seismic hazard at the regional scale, an important aspect to be considered in the planning and siting of future major water conservancy and hydropower projects, regional seismic hazard assessments, and the development of operational risk monitoring strategies.

4.2 Spatiotemporal Characteristics of Induced Seismicity Sequences

The composite distance-from-shoreline and time lag distributions for the identified RIS

sequences are shown in Figures 3a and 3b, respectively. The results show that RIS sequences are closely distributed around the reservoir area. The cumulative frequency of earthquakes along the distance from the shoreline reaches 95% at 24.8 km and 99% at 38.2 km. This indicates that the maximum distance of RIS sequences can approach 40 km, suggesting that the influence range stipulated within 10 km of the reservoir area in the current Chinese national standard GB 21075-2007 (*Reservoir-Induced Seismic Hazard Assessment*) is overly conservative and may underestimate the spatial extent required for risk prevention and control. More importantly, Figure 3a shows that the earthquake occurrence rate of RIS sequences follows a significant power-law decay with increasing distance from the reservoir shoreline.




Figure 3. Spatiotemporal patterns of reservoir-induced seismicity and construction of the W-score

437 table. (a) Empirical distribution of normalized earthquake frequency versus distance from the
438 reservoir shoreline, with the blue curve showing the fit of a power-law function. (b) Empirical
439 distribution of normalized earthquake frequency versus time lag since initial impoundment, with
440 the red curve showing the fit of an exponential-linear hybrid model. (c) W-score table constructed
441 based on the joint distribution of reservoir distance and time lag. The color fill indicates the
442 probability of induced seismicity; black contour lines mark the boundaries for probabilities of 0.2,
443 0.3, 0.5, and 0.9. (d) Example application of the W-score table, using the Jinping-I Reservoir and
444 induced seismicity identification results for a completeness magnitude M_C = M_L2.5. Circles
445 represent manually identified induced earthquakes, squares represent background earthquakes, and
446 the color fill indicates the probability of induced seismicity.
447
448 Figure 3c shows the two-dimensional W-score results described by equation (3). The
449 W-score at any location in the figure represents the probability of any earthquake event
450 being induced, thus enabling a quantitative assessment of the probability of RIS. Figure
451 3d shows an example application of the W-score to the RIS sequence at the Jinping-I
452 Reservoir (Figure 1). It can be seen that the RIS sequence is significantly clustered in
453 high W-value regions (0.6 < W < 1.0), while background natural tectonic earthquakes
454 are mainly distributed in low W-value regions (W < 0.4). This W-score table provides
455 a new quantitative analysis tool for identifying RIS in China. While the Jinping-I
456 Reservoir is presented here as a representative illustration, the W-score model has been
457 further validated for four additional reservoirs (Xiluodu and Xiangjiaba in southwestern
458 China, Guangzhao in Guizhou Province, and Shuikou in Fujian Province) spanning

contrasting tectonic regimes, reservoir geometries, and storage capacities (*Supplementary Material* S2). Notably, these reservoirs differ in induced-seismicity intensity by over an order of magnitude, yet exhibit consistent W-score segregation—induced events consistently occupy high-W regions ($0.6 < W < 1.0$) independent of absolute event counts. This consistency arises because the W-score is formulated from normalized dimensionless parameters, ensuring applicability across reservoirs with varying seismicity rates and confirming that no single high-activity reservoir dominates the statistical signature.

4.3 Parameter Characteristics of Induced Seismicity Sequences

The statistical parameters of reservoir-induced seismicity sequences contain key information about their triggering mechanisms and evolution processes. For example, the *b*-value in the magnitude-frequency relationship describes the differential stress level (Jiang *et al*., 2021; Yin and Jiang, 2024; Chang *et al*., 2025); the *p*-value in the Omori-Utsu formula describes the decay rate of a sequence (Trivedi, 2015; Utsu, 1999); and the α-value in the Epidemic-Type Aftershock Sequence (ETAS) model describes the ability of an earthquake to generate secondary events (Ogata, 1988; Bi and Jiang, 2019). To systematically reveal the characteristics and physical implications of RIS sequences in China, this study calculated the α-value, *b*-value, and *p*-value for each of the identified induced seismicity sequences from reservoirs impounded between January 1, 1971, and March 27, 2015, and compared these sequence parameters with parameters of natural earthquake sequences. Additionally, we compared the *b*-value of each RIS sequence with the *b*-value of the background seismicity in the respective

reservoir areas.

The statistical distributions of the calculated α-values, b-values, and p-values are shown in Figures 4a~c. The median α-value is 0.89, the median b-value is 1.16, and the median p-value is 1.11. To compare with the statistical characteristics of natural earthquake sequence parameters, we collected 66 cases from previous studies that also used the time-dependent ETAS model for fitting and provided the resulting parameters (Jiang *et al*., 2013a, 2013b, 2014; Guo, 2015; Bi and Jiang, 2019; Mesimeri *et al*., 2019; Xue *et al*., 2021). These cases are mainly from China (51 cases) and partially from other regions globally (15 cases). All provide calculated p-values and α-values, and some provide b-value results (31 cases). The median α-value for these natural sequences is 1.88, the median b-value is 0.83, and the median p-value is 1.10. The corresponding parameter values are listed in Table 2. Direct comparison of the statistical distributions of α-value, b-value, and p-value shows that the α-values of RIS sequences are generally smaller than those of natural sequences, the b-value distribution is more scattered and generally higher, and the p-values are relatively similar. We used the Kolmogorov-Smirnov test (significance level P=0.05) to examine whether the respective parameter combinations of RIS sequences and natural sequences come from the same distribution. The results show significant differences for b-value and α-value (significance level $P <$ 0.05), while the difference for p-value is not statistically significant (significance level $P = 0.461 >> 0.05$). Furthermore, to avoid potential intrinsic correlations among these parameters (*e.g.*, Wang, 1994; Jiang *et al*., 2015) affecting the distinguishability between RIS and natural sequence characteristics, we examined the pairwise

503 distribution relationships among the three sequence parameters. As shown by the
504 sample density contour plots in Figures 4d~f, the distribution of RIS sequence
505 parameters can be clearly distinguished from that of natural earthquake sequence
506 parameters in the combined distributions of *b*-value vs. α-value, *b*-value vs. *p*-value,
507 and *p*-value vs. α-value. Therefore, it can be concluded that RIS sequences and natural
508 earthquake sequences have distinct characteristics in their statistical parameters, mainly
509 manifested as: RIS sequences typically have higher *b*-values (indicating lower effective
510 stress/higher proportion of small earthquakes) and significantly lower α-values
511 (indicating weaker ability of small-magnitude events to trigger secondary earthquakes).
512 Therefore, RIS sequences and natural earthquake sequences exhibit distinct statistical
513 characteristics in their frequency-magnitude distributions and triggering abilities.
514 To further investigate the differences between RIS sequences and the background
515 seismicity around the reservoir areas, this study compared the *b*-value of the induced
516 sequence with the *b*-values of background seismicity at different distances from the
517 reservoir shoreline (Figure 5). We employed two spatial strategies: The first was a non-
518 overlapping concentric zoning strategy, dividing the area around the reservoir into
519 discrete concentric zones of 0~10 km, 10~20 km, 20~30 km, 30~40 km, and 40~50 km.
520 The *b*-value of background seismicity in each zone was calculated independently and
521 compared with the RIS sequence *b*-value using the Kolmogorov-Smirnov (KS) test
522 (significance level P=0.05). The results show that the *P* for all zones are greater than
523 0.05, indicating no significant difference was identified. The second was a cumulative
524 zoning strategy, gradually expanding the study area in 10 km increments (0~10 km →

0~50 km). The *b*-value of background seismicity within the cumulative range was calculated. The KS test results show that the *P* decreases initially with increasing cumulative distance, becomes significantly lower than 0.05 at 30 km and 40 km, indicating a significant difference between the background seismicity *b*-value beyond this distance and the RIS sequence *b*-value. The *P* increases again after 40 km, possibly because beyond the effective range of reservoir water penetration, the background seismicity is controlled by the tectonic environment, and the *b*-value stabilizes. These results suggest that a distance of 30 km to 40 km from the shoreline may be a critical physical boundary, which can be defined as the effective spatial scale of reservoir water penetration. The first strategy failed to identify a difference, primarily due to insufficient sample size of far-field earthquakes and the smoothing effect of spatial continuity.




Figure 4. Parameter characteristics of the reservoir-induced seismicity sequences. (a) Statistical distribution of the α-value from the ETAS model for the induced sequences. (b) Statistical

distribution of the *p*-value from the ETAS model. (c) Statistical distribution of the *b*-value estimated using the OK1993 model. (d) Scatter plot of *α*-value versus *b*-value. (e) Scatter plot of *p*-value versus *b*-value. (f) Scatter plot of *α*-value versus *p*-value. In panels (d) to (f), the blue contours represent the bivariate kernel density estimate (KDE) for parameters of natural tectonic seismicity sequences from previous studies, and the red contours represent the KDE for parameters of the induced seismicity sequences from this study.




Figure 5. Statistical characteristics of the Kolmogorov-Smirnov (KS) test comparing the *b*-values of induced sequences and background seismicity. (a) Zonal KS test results: *b*-values of background seismicity within concentric distance zones (0~10, 10~20, 20~30, 30~40, 40~50 km from the reservoir shoreline) are compared against the *b*-value of the induced sequence. The KS statistic (*D*) and significance level (*P*) are plotted against distance. (b) Cumulative zonal KS test results: based on *b*-values of background seismicity within cumulative distance ranges (0~10, 0~20, 0~30, 0~40, 0~50 km). The red horizontal dashed lines in both panels indicate the statistical significance threshold (*P* = 0.05).

Table 2. Statistical parameters (*α*-value, *p*-value and *b*-value) of natural tectonic earthquake

559 sequences.

No.	α-value	p-value	b-value	Location of Earthquake Sequence	Reference
1	2.2611	0.9312	0.9889	North China, China	Bi and Jiang (2019)
2	1.9171	1.0576	1.0124	North China, China	Bi and Jiang (2019)
3	1.3486	0.7801	0.7797	North China, China	Bi and Jiang (2019)
4	1.5605	1.1545	0.9087	North China, China	Bi and Jiang (2019)
5	2.0487	0.9736	0.5000	North China, China	Bi and Jiang (2019)
6	1.2415	0.7789	0.8300	North China, China	Bi and Jiang (2019)
7	1.6860	1.1985	0.8069	North China, China	Bi and Jiang (2019)
8	1.5212	1.1230	0.7338	North China, China	Bi and Jiang (2019)
9	1.7802	0.8583	0.8823	North China, China	Bi and Jiang (2019)
10	1.5136	0.7757	1.0592	North China, China	Bi and Jiang (2019)
11	2.3568	1.0973	0.5758	North China, China	Bi and Jiang (2019)
12	1.6481	0.9321	0.7192	North China, China	Bi and Jiang (2019)
13	2.0762	1.1156	1.0906	North China, China	Bi and Jiang (2019)
14	2.0091	1.0333	0.9240	North China, China	Bi and Jiang (2019)
15	1.6155	0.9355	0.7081	North China, China	Bi and Jiang (2019)
16	1.2621	0.8847	0.7795	North China, China	Bi and Jiang (2019)
17	1.8200	2.0250	1.0700	Western Corinth Gulf, Greece	Mesimeri *et al*. (2019)
18	0.7890	2.1360	0.7000	Western Corinth Gulf, Greece	Mesimeri *et al*. (2019)
19	0.9710	1.5610	0.9200	Western Corinth Gulf, Greece	Mesimeri *et al*. (2019)
20	1.3580	1.4570	0.9000	Western Corinth Gulf, Greece	Mesimeri *et al*. (2019)

No.	α-value	p-value	b-value	Location of Earthquake Sequence	Reference
21	1.8900	1.2200	0.7200	Lushan, Sichuan, China	Jiang *et al*. (2013b)
22	1.7200	1.1485	/	Min County - Zhang County, Gansu, China	Jiang *et al*. (2013a)
23	1.6820	0.6692	/	Yutian, Xinjiang, China	Jiang *et al*. (2014)
24	1.8347	1.5569	0.7821	Kuril Islands, Russia	Xue *et al*. (2021)
25	1.9296	1.7326	0.8220	Kuril Islands, Russia	Xue *et al*. (2021)
26	2.2996	1.4557	1.1394	Kuril Islands, Russia	Xue *et al*. (2021)
27	2.1400	1.3663	0.7491	Off the coast of Honshu, Japan	Xue *et al*. (2021)
28	1.3439	1.2878	1.2818	Off the coast of Honshu, Japan	Xue *et al*. (2021)
29	1.5563	0.9113	0.7625	Santa Cruz Islands, Solomon Islands	Xue *et al*. (2021)
30	1.4872	1.7976	0.9349	Santa Cruz Islands, Solomon Islands	Xue *et al*. (2021)
31	2.0001	1.6973	0.8132	Off the coast of northern, Chile	Xue *et al*. (2021)
32	2.0970	1.4571	0.8833	Off the coast of northern, Chile	Xue *et al*. (2021)
33	1.0832	1.5272	0.9723	Off the coast of northern, Chile	Xue *et al*. (2021)
34	1.5193	0.6645	/	Ludian, Yunnan, China	Guo (2015)
35	1.6165	0.9586	/	Muli, Sichuan, China	Guo (2015)
36	1.9082	0.9281	/	Northeast of Mengzi, Yunnan, China	Guo (2015)
37	1.4829	0.8193	/	Northwest of Yingjiang, Yunnan, China	Guo (2015)
38	2.1897	1.0510	/	Northwest of Garzê, Sichuan, China	Guo (2015)
39	1.1823	1.1546	/	Jianchuan, Yunnan, China	Guo (2015)
40	1.8641	1.1987	/	North of Menyuan, Qinghai, China	Guo (2015)
41	4.1992	1.0944	/	Southwest of Zhongba, Tibet, China	Guo (2015)


No.	α-value	p-value	b-value	Location of Earthquake Sequence	Reference
42	1.2166	1.1223	/	Gonghe, Qinghai, China	Guo (2015)
43	2.3933	1.0757	/	Shidian, Yunnan, China	Guo (2015)
44	2.7122	1.0713	/	Dayao, Yunnan, China	Guo (2015)
45	3.9338	1.0077	/	Minle and Shandan, Gansu, China	Guo (2015)
46	5.2438	1.2607	/	Baoshan, Yunnan, China	Guo (2015)
47	2.2892	0.8905	/	Barkam, Sichuan, China	Guo (2015)
48	1.0478	1.0135	/	Baoshan, Yunnan, China	Guo (2015)
49	2.0710	1.2727	/	Huize, Sichuan, China	Guo (2015)
50	2.3146	1.0056	/	Myanmar	Guo (2015)
51	2.6223	1.2559	/	Yangbi, Yunnan, China	Guo (2015)
52	2.5879	1.1229	/	Wenchuan, Sichuan, China	Guo (2015)
53	1.4512	0.9181	/	Yingjiang, Yunnan, China	Guo (2015)
54	5.5711	1.4384	/	Eryuan, Yunnan, China	Guo (2015)
55	1.6950	0.9745	/	Yingjiang, Yunnan, China	Guo (2015)
56	2.3327	1.1857	/	Tengchong, Yunnan, China	Guo (2015)
57	2.2742	2.4711	/	Jinta, Gansu, China	Guo (2015)
58	2.5679	1.4200	/	Ninglang, Yunnan, China	Guo (2015)
59	1.2109	0.9480	/	Yiliang, Yunnan, China	Guo (2015)
60	2.8933	1.2979	/	Baiyu, Sichuan, China	Guo (2015)
61	1.5728	1.0687	/	Eryuan, Yunnan, China	Guo (2015)
62	2.0009	1.1667	/	Lushan, Sichuan, China	Guo (2015)

No.	α-value	*p*-value	*b*-value	Location of Earthquake Sequence	Reference
63	0.7704	1.1339	/	Changning, Sichuan, China	Guo (2015)
64	3.7824	1.0544	/	Min County, Gansu, China	Guo (2015)
65	2.3201	1.0142	/	Li County, Sichuan, China	Guo (2015)
66	2.1599	0.9962	/	Zuogong, Tibet, China	Guo (2015)

4.4 Correlation Analysis of Inducing Factors

To further elucidate the potential factors influencing the intensity of RIS sequence activity, we analyzed the correlation between the maximum magnitude (M_{max}) of the RIS sequences and two categories of parameters, totaling eight specific factors. The first category comprises static reservoir attributes: reservoir capacity (10^8 m^3), dam height (m), reservoir surface area (km^2), reservoir major axis length (km), and mean water depth, the latter calculated as reservoir capacity / reservoir area. The second category describes the dynamic response of RIS: the distance from the reservoir shoreline of the M_{max} event (M_{max} distance, km), the time lag of the M_{max} event since initial impoundment (time lag, days), and the time lag between initial impoundment and the peak seismicity rate (peak lag, days). Peak lag is operationally defined by binning the post-impoundment earthquake catalog into 0.25-year (3-month) intervals, computing the event frequency for each bin, and taking the elapsed time from the initial impoundment date to the bin with the maximum frequency. It is important to note that since dynamic response parameters cannot be defined for non-induced reservoirs, this analysis is based solely on the sample of 88 induced-type reservoirs.

The results of the correlation analysis between the eight potential inducing factors and M_{max} are shown in Figure 6. The results indicate that the five static reservoir attribute parameters exhibit weak positive correlations with M_{max}. The Pearson correlation coefficient (r) values range from 0.20 to 0.28, and the Spearman correlation coefficient (ρ) values range from 0.21 to 0.32. For each parameter, at least one of the r or ρ values has a significance level less than 0.05. In contrast, the three dynamic attribute parameters show no correlation with M_{max}, with r or ρ values close to zero, and the corresponding significance levels all exceed 0.05. These results suggest that relying on any single static or dynamic reservoir attribute parameter is insufficient for reliably predicting the maximum magnitude (M_{max}) of RIS.



589 **Figure 6**. Correlation analysis between the maximum magnitude (M_{max}) of induced seismicity and
590 potential inducing factors. (a) Reservoir capacity (10^8 m^3). (b) Dam height (m). (c) Reservoir surface
591 area (km^2). (d) Mean water depth (Capacity / Area, m). (e) Reservoir major axis length (km). (f)
592 Distance from the reservoir shoreline of the M_{max} event (M_{max} distance, km). (g) Time lag of the
593 M_{max} event since initial impoundment (time lag, days). (h) Time lag of the peak seismicity rate since
594 initial impoundment (peak lag, days). The Pearson correlation coefficient (r), Spearman correlation
595 coefficient (ρ), and the corresponding significance level (P) are indicated textually in each subplot.
596
597 Although the static and dynamic reservoir parameters show only weak or no correlation
598 with the intensity (M_{max}) of the RIS sequences, whether these parameters can be used
599 for preliminary screening of induced seismic risk prior to reservoir construction
600 remains a valuable question. We address this from two perspectives. First, we examine
601 whether thresholds exist for the five static parameters that show weak but statistically
602 significant correlations, which could indicate high RIS risk. For this purpose, we binned
603 the values of the five static reservoir attribute parameters and examined the proportion
604 of induced-type reservoirs within each bin. The results are shown in Figure 7. Reservoir
605 capacity and reservoir major axis show clear threshold indicative value for the
606 occurrence probability of induced-type reservoirs: As shown in Figure 7b, when the
607 reservoir capacity exceeds 3.2×10^8 m^3 ($10^{0.5}\times10^8$ m^3), the proportion of induced-type
608 reservoirs approaches 15%, which is already significant. In capacity bins above this
609 threshold, the proportion of induced-type reservoirs generally shows a positive
610 correlation with capacity. Figure 7c shows that the reservoir major axis exhibits a

similar characteristic; when it exceeds 15.9 km ($10^{1.2}$ km), the proportion of induced-type reservoirs exceeds 11%. In length bins above this threshold, the proportion shows a positive correlation with length. The existence of such clear thresholds in the proportion of induced-type reservoirs for these two static parameters can provide a basis for preliminary screening during project planning. Specifically, sites meeting or exceeding these threshold conditions warrant specialized RIS hazard assessment.




Figure 7. Proportion characteristics of induced-type reservoirs under the influence of single factors.

620 (a) Proportion across different bins of dam height (m). (b) Proportion across different bins of
621 reservoir capacity (10^8 m^3). (c) Proportion across different bins of reservoir major axis length (km).
622 (d) Proportion across different bins of mean water depth (Capacity / Area, m). (e) Proportion across
623 different bins of reservoir surface area (km^2). In each subplot, the purple filled area represents the
624 proportion of induced-type reservoirs for the respective bin, and the gray filled area represents the
625 proportion of non-induced-type reservoirs.
626
627 Furthermore, to examine the independence or intercorrelation among the attribute
628 parameters, we calculated the Pearson correlation coefficient matrix (Figure 8) and the
629 Spearman correlation coefficient matrix (Figure 9) for all eight parameters. The results
630 show that the five static reservoir attribute parameters are relatively highly correlated
631 among themselves. The pairwise Pearson correlation coefficients (r) range from 0.39
632 to 0.95, and the Spearman correlation coefficients (ρ) range from 0.59 to 0.95. All are
633 positive correlations and statistically significant at the $P < 0.01$ level. This reflects the
634 statistical redundancy among geometric parameters in hydropower project design and
635 highlights the need to focus on parameter independence when used in seismic hazard
636 analysis. The three dynamic reservoir attribute parameters show relatively weaker
637 correlations among themselves. The pairwise Pearson correlation coefficients (r) range
638 from 0.23 to 0.38, and the Spearman correlation coefficients (ρ) range from 0.22 to 0.33,
639 also all positive. Notably, the correlations between static and dynamic attribute
640 parameters are all negative. This implies that larger reservoir dimensions tend to be
641 associated with the M_{max} event occurring closer to the reservoir shoreline (smaller M_{max}

distance) and within a shorter time lag after initial impoundment, and the peak seismicity rate also tends to be reached sooner after impoundment (smaller peak lag).




Figure 8. Pearson correlation matrix among inducing factors. The lower triangle of the matrix visualizes the correlation coefficients using ellipses: flatter ellipses indicate stronger correlations; a 45° tilt indicates a positive correlation, and a -45° tilt indicates a negative correlation; asterisks indicate the statistical significance level (* P<0.05, ** P<0.01). The upper triangle displays the Pearson correlation coefficient (*r*) numerically, with colors transitioning from blue (strong negative correlation) through green (weak correlation) to yellow (strong positive correlation). The inducing factors are: Reservoir capacity (10^8 m^3), dam height (m), reservoir area (km^2), Capacity / Area (m), reservoir major axis (km), M_{max} distance (km), time lag (days), peak lag (days).




Figure 9. Spearman correlation matrix among inducing factors. In the lower triangle of the matrix, ellipses visualize the rank correlation coefficients: flatter ellipses indicate stronger correlations; a 45° tilt indicates a positive correlation, and a -45° tilt indicates a negative correlation; asterisks indicate the statistical significance level (* P<0.05, ** P<0.01). The upper triangle displays the Spearman correlation coefficient (ρ) numerically, with colors transitioning from blue (strong negative correlation) through green (weak correlation) to yellow (strong positive correlation). The inducing factors are the same as in Figure 8.

5 Discussion

This study finds that induced-type reservoirs in China exhibit a high degree of spatial selectivity, with the vast majority concentrated in the strong tectonic activity zone along the eastern margin of the Tibetan Plateau, showing clear spatial consistency with active faults since the Late Pleistocene and historical moderate-to-strong ($M \geq 4.0$) seismicity. This finding resonates with conclusions from several regional systematic studies worldwide, collectively highlighting the critical controlling role of the regional tectonic background on the occurrence of RIS. In Canada, RIS is concentrated within the relatively stable Canadian Shield, and its limited triggering range (<5 km) is attributed to the reactivation of fragile faults associated with paleo-rifts under reservoir water infiltration (Lamontagne *et al*., 2018). In France, RIS preferentially occurs in active tectonic zones (*e.g*., Alps, Pyrenees), and its spatial influence range can be effectively explained using the reservoir major axis (Deng *et al*., 2010; Grasso *et al*., 2018). Studies in Brazil also indicate that the probability of RIS is twice as high in areas of high natural seismicity compared to aseismic regions, further supporting the view that a critically stressed crust is an important prerequisite for RIS occurrence (Barros *et al*., 2018). The high concentration of RIS along the eastern margin of the Tibetan Plateau revealed in this study reinforces the global understanding that "high tectonic stress accumulation and developed fault systems are prerequisite geological conditions for RIS occurrence" (*e.g*., Barros *et al*., 2018; Grasso *et al*., 2018; Lamontagne *et al*., 2018). Compared to the Canadian and French cases, RIS in China exhibits a broader spatial influence range (95% of events within 24.8 km, 99% within 38.2 km of the shoreline). This difference may stem from the more complex intraplate tectonic setting in China, characterized by

687 intense crustal deformation and widely developed deep-seated strike-slip faults. These
688 pre-existing fault networks provide preferred pathways for fluid migration. Although
689 systematic quantitative comparisons of fault permeability between China and other
690 regions remain scarce, the observed long-distance diffusion of pore pressure (up to 30-
691 40 km) indicates that the hydraulic properties of these active faults meet or exceed the
692 threshold of seismogenic permeability (Talwani *et al*., 2007; Miao *et al*., 2025),
693 facilitating far-reaching pore pressure perturbations. Conventional understanding
694 suggests that the occurrence mechanisms of RIS are closely related to the regional
695 tectonic setting, and their spatial distribution contains key information about the
696 triggering mechanisms. Understanding the spatial distribution patterns of induced-type
697 reservoirs and their relationship with geological structures and regional seismicity is
698 fundamental for revealing RIS triggering mechanisms and assessing regional RIS
699 hazard. Furthermore, the observed RIS influence range far exceeds the 10 km specified
700 in the current Chinese national standard (GB 21075-2007), strongly suggesting that this
701 parameter should be revised in future risk assessments to prevent potential spatial
702 underestimation of risk.
703 The sequence parameter analysis in this study provides statistical evidence for
704 distinguishing RIS from natural tectonic earthquakes. We found that Chinese RIS
705 sequences exhibit significantly higher b-values and lower α-values. A high b-value
706 typically indicates lower effective stress in the source region or more fractured media,
707 which aligns well with the physical mechanism of pore pressure diffusion reducing the
708 effective normal stress on faults, thereby activating a large number of small-scale faults

709 that are in a critical state (Talwani, 1997; Rajendran and Talwani, 1992). A low α-value
710 suggests a weaker ability of small-magnitude events to trigger secondary sequences,
711 revealing a fundamental difference in the energy release pattern between the RIS
712 triggering process and natural mainshock-aftershock sequences. These differences may
713 reveal the fundamental distinctions between the triggering mechanism (dominated by
714 pore pressure diffusion) and evolution process (rapid decay, weaker triggering ability
715 of large earthquakes) of RIS compared to natural earthquakes. These characteristics are
716 consistent with findings from studies of the Xiluodu-Xiangjiaba reservoirs on the lower
717 Jinsha River in China (Miao *et al*., 2025) and are inherently linked to the observation
718 in French RIS sequences of a large difference between the magnitude of the second-
719 largest aftershock and the mainshock (Grasso *et al*., 2018). However, studies on a few
720 cases in Brazil found no significant difference between the *b*-value of RIS sequences
721 and the local natural earthquake *b*-value (Barros *et al*., 2018), which differs from the
722 traditional view that RIS has higher *b*-values (Gupta *et al*., 1972). Such regional
723 differences suggest that the sequence characteristics of RIS may be influenced by local
724 geological conditions, rock mechanical properties, and subtle differences in triggering
725 mechanisms, necessitating consideration of regional applicability when using statistical
726 parameters for discrimination. Furthermore, the spatial evolution analysis of the *b*-
727 value in this study statistically validates an effective boundary for reservoir water
728 penetration at 30~40 km. This not only supports the physical mechanism of RIS but
729 also provides a referential spatial constraint for defining monitoring and assessment
730 ranges in risk evaluation.

Regarding the triggering mechanism, the spatiotemporal evolution characteristics of RIS in China are most consistent with pore pressure diffusion as the primary process, though elastic loading may contribute in the near field. The peak in seismic activity 1~2 years after impoundment, and the significant power-law decay of the occurrence rate with distance from the reservoir shoreline (M_{max} distance), are typical manifestations of the pore pressure diffusion process (Talwani, 1997; Cheng *et al*., 2012; Grasso *et al*., 2018). This characteristic highly aligns with theoretical models of fault activation by fluid infiltration and diffusion (Talwani, 1997), consistent with pore pressure diffusion as a contributing mechanism. This is because the pore pressure increase caused by reservoir impoundment diffuses through pre-existing fractures, faults, and pores in the rock mass. The combined effect of the diffusion front and the nonlinear dependence of triggering probability on pressure changes — where small pore pressure increments below a critical threshold may produce negligible triggering, but the probability rises rapidly once the threshold is approached (Talwani, 1997) — typically results in a power-law decay of the probability or occurrence rate of triggered seismicity with distance.

This is very similar to the case of the Song Tranh 2 reservoir in Vietnam, where seismicity was triggered shortly after impoundment (rapid response) but the increase persisted after water level drop due to the delayed effect of pore pressure diffusion, clearly identified as a typical case of "rapid and delayed triggering" (Gahalaut *et al*., 2016). Similarly, in the cascade reservoirs on the lower Jinsha River in China, detailed 3D finite element simulations show the combined action of "elastic loading and pore

753 pressure diffusion" dual mechanisms, with pore pressure diffusion dominating the
754 contribution to Coulomb stress changes (Miao *et al*., 2025). In terms of temporal
755 response type, different regions globally show some variation: RIS in France is
756 predominantly rapid response (Type I), with 62% of events occurring within 2 years of
757 impoundment (Grasso *et al*., 2018); whereas RIS in Canada and Brazil more often
758 exhibits delayed response characteristics (Lamontagne *et al*., 2018; Barros *et al*., 2018).
759 The observed peak 1~2 years after initial impoundment in Chinese RIS is similar in
760 timescale to the rapid response mode in France, but the decay after the peak may be
761 slower due to the higher regional tectonic stress background and more active faulting.
762 This delayed response and gradual increase are typical manifestations of the time
763 required for pore pressure diffusion. Reservoir water infiltrates downward and outward
764 through pores, fractures, and pre-existing fault networks in the rock, causing pore
765 pressure perturbations to propagate at a rate controlled by the hydraulic diffusivity.
766 Significant increase in seismicity occurs only when the pore pressure front reaches and
767 sufficiently increases the effective pore pressure in deep potential fault zones to meet
768 the critical failure condition. The decay after the peak reflects stress release from the
769 most easily triggered fault ruptures in areas reached early by the pressure front. As the
770 diffusion distance increases, the pressure perturbation gradient decreases, and the
771 efficiency of infiltration paths reduces, making it more difficult to trigger new
772 earthquakes. Additionally, for special scenarios like cascade reservoirs, the
773 superposition effect of stress perturbations caused by the impoundment and operation
774 of adjacent reservoirs can significantly elevate the peak pore pressure, far exceeding

775 the perturbation amplitude of a single reservoir (Zhang *et al*., 2021), increasing the
776 complexity of RIS risk assessment. These comparisons indicate that although pore
777 pressure diffusion is a common thread in many RIS cases, its specific temporal
778 manifestation (rapid or delayed) and spatial extent are modulated by the combined
779 effects of regional fault permeability, hydraulic diffusivity, reservoir operation patterns,
780 and the initial tectonic stress level.

781 A principal limitation of this study is the first-order assumption of uniform
782 spatiotemporal behavior across China's diverse tectonic settings. The W-score and the
783 derived engineering thresholds are based on ensemble averages over 1,435 reservoirs
784 spanning the Tibetan Plateau margin, the South China Block, and the North China
785 Craton, among other provinces with vastly different crustal structures, stress states, and
786 permeability distributions. Consequently, the model may underestimate RIS potential
787 in high-permeability, extensional regimes where pore-pressure diffusion is rapid, or
788 overestimate it in stable cratonic interiors. Future work should develop region-specific
789 variants of the W-score framework by partitioning the dataset according to tectonic
790 province, reservoir volume, or local geological setting.

791 The correlation analysis in this study leads to an enlightening conclusion for the
792 paradigm of RIS risk assessment: although a reservoir capacity greater than 3.2×10^8 m^3
793 or a reservoir major axis exceeding 15.9 km can serve as practical thresholds for
794 preliminary risk screening during the planning stage, all static or dynamic reservoir
795 attribute parameters show only weak or no correlation with the maximum magnitude
796 (M_{max}). This finding is highly consistent with observations worldwide (Klose, 2013).

797 The physical mechanism underlying this is that Mmax is primarily controlled by the
798 pre-existing stress state and rupture scale of local faults (Talwani, 1997), rather than by
799 the properties of the reservoir itself. The static reservoir parameters mainly modulate
800 the timing of earthquake triggering through the process of pore pressure diffusion. For
801 example, the study in Brazil explicitly states that no clear trend is observed between the
802 maximum magnitude and dam height, reservoir capacity, or reservoir area (Barros *et*
803 *al*., 2018), and Gupta (2002) compilation of 117 global RIS cases also supports this
804 general rule. This statistically confirms that M_{max} is primarily controlled by inherent
805 geological factors such as the size of local faults, their pre-existing stress state, and rock
806 strength (Talwani, 1997), while static or dynamic reservoir parameters mainly influence
807 the probability and timing of earthquake triggering by modulating the pore pressure
808 diffusion process, rather than directly controlling the final rupture scale. Consequently,
809 traditional empirical models that over-rely on static reservoir parameters for predicting
810 M_{max} have clear limitations. Based on this, the future framework for RIS risk assessment
811 should gradually shift beyond static empirical models towards models that integrate
812 multi-source information and physical processes. The W-score model developed in this
813 study, which couples the observed power-law decay of RIS with M_{max} distance and its
814 time lag since initial impoundment, provides a new quantitative tool for the
815 probabilistic identification of RIS events. This direction aligns with the probabilistic
816 identification framework combining reservoir length, volume, and tectonic background
817 proposed earlier by Grasso *et al*. (2018), and the "pore pressure-fault activity" coupling
818 indicator suggested by Miao *et al*. (2025) for cascade reservoirs, representing a

common trend in development. For engineering practice in China, we recommend significantly expanding the monitoring and assessment range from the current 10 km to the 30~40 km permeability boundary identified in this study within the current standards. A dual-threshold screening process based on tectonic activity and reservoir geometric parameters (*e.g.*, reservoir capacity or reservoir major axis) should be introduced during the planning stage of reservoir construction. In the long term, it is essential to develop coupled multi-physics models that integrate geological structure, in-situ stress field, fault permeability, and hydrogeological conditions to achieve more accurate risk prediction and management.

6 Conclusions

Addressing the insufficient systematic understanding of Reservoir-Induced Seismicity (RIS) patterns in China, this study integrated a high-resolution national reservoir dataset (CRD) with a unified earthquake catalog spanning over fifty years to establish the first national-scale screening sample covering 1,435 large/medium-sized reservoirs, from which 88 induced-type reservoirs were identified. Through systematic analysis of their spatial distribution, spatiotemporal evolution, sequence parameters, and inducing factors, this study reveals a series of fundamental characteristics and physical mechanisms of RIS in China and offers new insights for risk assessment applications. The main conclusions are as follows:

1. RIS spatial distribution is dominated by the regional tectonic background, exhibiting significant selectivity. Induced-type reservoirs are not uniformly distributed but are highly concentrated in strong tectonic activity zones such as the Sichuan-

841 Yunnan rhombic block along the eastern margin of the Tibetan Plateau. Their spatial
842 pattern shows a high degree of coupling with Late Pleistocene active faults and
843 historical moderate-to-strong (M≥4.0) seismicity. This clearly indicates that high
844 tectonic stress accumulation and developed fault systems are prerequisite geological
845 conditions for RIS occurrence. In contrast, the tectonically stable eastern region, despite
846 having a high density of reservoirs, shows a significantly lower probability of induction.
847 This pattern provides a reference basis for the macro-siting of major hydropower
848 projects.

849 2. RIS spatiotemporal evolution is most consistent with pore pressure diffusion as
850 the primary process, with potential near-field contributions from elastic loading. RIS
851 events exhibit a significant power-law decay with increasing distance from the reservoir
852 shoreline (M_{max} distance), with 95% and 99% of events concentrated within 24.8 km
853 and 38.2 km, respectively. Temporally, seismic activity peaks 1~2 years after
854 impoundment, showing a typical delayed response. The W-score model established
855 based on these characteristics provides a quantitative screening framework for the
856 spatiotemporal coupling effect, providing a new tool for the probabilistic identification
857 of RIS events. The effective boundary of reservoir water penetration determined in this
858 study (30~40 km) far exceeds the 10 km zone suggested in the current national standard
859 (GB 21075-2007). It is recommended to revise this parameter in future risk assessments
860 to prevent potential underestimation of the spatial risk.

861 3. RIS sequence parameters possess statistical fingerprints distinct from natural
862 earthquakes, revealing a unique triggering and evolution physical process. Compared

to natural earthquake sequences, RIS sequences exhibit significantly lower α-values (weaker ability to trigger secondary events) and higher b-values. This reveals that RIS primarily activates critically stressed faults through pore pressure diffusion, leading to unique sequence behavior characterized by a high proportion of small earthquakes and a weaker ability of large earthquakes to trigger secondary sequences. Furthermore, a significant difference emerges between the b-value of RIS sequences and the b-value of background seismicity at a distance of 30~40 km from the shoreline, statistically validating this distance as the critical physical boundary for reservoir water penetration.

4. Correlation analysis reveals the fundamental limitations of using static or dynamic reservoir attribute parameters to predict the maximum magnitude, providing crucial evidence for risk assessment. The study finds that a reservoir capacity exceeding 3.2×10^8 m^3 or a reservoir major axis exceeding 15.9 km can serve as practical thresholds for preliminary risk screening during the planning stage. However, in-depth correlation matrix analysis shows that both static reservoir attributes (*e.g.*, reservoir capacity, dam height, reservoir area, Capacity / Area, reservoir major axis) and dynamic response parameters (M_{max} distance, time lag, peak lag) have only weak correlations with the RIS maximum magnitude (M_{max}). This finding statistically confirms that M_{max} is primarily controlled by geological factors such as local fault development scale, pre-existing stress state, and rock strength, while reservoir parameters mainly influence the probability of earthquake triggering by modulating the pore pressure diffusion process. Therefore, future risk assessment should gradually shift from experience-based models reliant on reservoir scale towards physics-based mechanistic models that integrate

geological structure, in-situ stress field, and hydrogeological conditions.

Data availability. The seismic data used in this study were obtained from the *National Unified Official Earthquake Catalog* provided by the China Earthquake Networks Center (last accessed on April 15, 2025, via http://10.5.160.18/console/exit.action). This catalog contains earthquake parameters for events across China from January 1, 1970, to March 27, 2025. This earthquake catalog is proprietary and cannot be released to the public. The spatial distribution and fundamental attributes of reservoirs were primarily sourced from the published China Reservoir Dataset (CRD, Song *et al*., 2022). Critical reservoir parameters, such as the initial impoundment time and dam height, were compiled and integrated by the authors from publicly available sources, including the *Encyclopedia of Chinese Rivers and Lakes*, local gazetteers, government reports, and news archives. This integrated reservoir attributes dataset is proprietary to this study and may be available from the corresponding author upon reasonable request. The computer codes used for calculating sequence parameters (α-value, b-value, and p-value) and the W-score model in this study are available from the corresponding author upon reasonable request.

Author Contributions. CJ and JZha conceived and designed the study. JZha, CJ, and YZu performed the data analysis and developed the W-score model. FY and HZhai compiled and curated the reservoir and earthquake datasets. JB contributed to the tectonic analysis and active fault mapping. YZan assisted with figure preparation and manuscript editing. CJ wrote the manuscript with contributions from all co-authors. All authors discussed the results and commented on the manuscript.

Competing Interests. The authors acknowledge there are no conflicts of interest recorded.

Acknowledgments. Data support was provided by the National Earth System Science Data Center, National Science & Technology Infrastructure of China (http://www.geodata.cn). We are grateful to Senior Engineer Xiaojing Ma of the Guangdong Earthquake Agency and Dr. Xinxin Yin of the Gansu Earthquake Agency

for their valuable assistance in providing reservoir attribute information. We also extend our sincere appreciation for their support. We sincerely thank Dr. Abhineet Gupta and Dr. Jürgen Mey for their thorough and constructive review comments, which significantly improved the clarity, structure, and rigor of this manuscript.

Financial support. This work was supported by the Special Fund of the Institute of Geophysics, China Earthquake Administration and the program of the China Seismic Experimental Site (Grant No. DQJB24Z04).

References

Barros, L. V., Assumpção, M., Ribotta, L. C., Ferreira, V. M., De Carvalho, J. M., Bowen, B. M. D., and Albuquerque, D. F.: Reservoir-Triggered Seismicity in Brazil: Statistical Characteristics in a Midplate Environment, Bulletin of the Seismological Society of America, 108, 3046–3061, https://doi.org/10.1785/0120170364, 2018.

Bi, J. M., Jiang, C. S.,: Distribution characteristics of earthquake sequence parameters in North China, Chinese Journal of Geophysics, 62, 4300–4312, https://doi.org/10.6038/cjg2019M0453, 2019. (in Chinese)

Bi, J. M., Jiang, C. S., Lai, G. J., and Song, C.: Effectiveness evaluation and constraints of early aftershock probability forecasting for strong earthquakes in continental China, Chinese Journal of Geophysics, 65, 2532–2545, https://doi.org/10.6038/cjg2022P0411, 2022. (in Chinese)

Chang, Y., Wang, R., Han, P., Wang, J., Miao, M., Zeng, Z., Wu, W., Jiang, C., Meng, L., Shi, H., and Hattori, K.: b-Value Evaluation and Applications to Seismic Hazard Assessment, Entropy, 27, 958, https://doi.org/10.3390/e27090958, 2025.

Cheng, H., Zhang, H., Zhu, B., Sun, Y., Zheng, L., Yang, S., and Shi, Y.: Finite element investigation of the poroelastic effect on the Xinfengjiang Reservoir-triggered earthquake, Sci. China Earth Sci., 55, 1942–1952, https://doi.org/10.1007/s11430-012-4470-8, 2012.

Dai, G. H., Miao, C., and Zhai, L.: Unified earthquake cataloging of China seismographic network, Earthquake Research in China, 35(1): 192-203, 2019. (in Chinese)

Deng, K., Zhou, S., Wang, R., Robinson, R., Zhao, C., and Cheng, W.: Evidence that the 2008 M_w 7.9 Wenchuan Earthquake Could Not Have Been Induced by the Zipingpu Reservoir, Bulletin

943 of the Seismological Society of America, 100, 2805–2814,
944 https://doi.org/10.1785/0120090222, 2010.
945 Dong, S., Li, L., Zhao, L., Shen, X., Wang, W., Huang, H., Peng, B., Xu, X., and Gao, R.: Seismic
946 Evidence for Fluid-Driven Pore Pressure Increase and Its Links With Induced Seismicity in the
947 Xinfengjiang Reservoir, South China, JGR Solid Earth, 127, e2021JB023548,
948 https://doi.org/10.1029/2021JB023548, 2022.
949 Gahalaut, K., Tuan, T. A., and Purnachandra Rao, N.: Rapid and Delayed Earthquake Triggering by
950 the Song Tranh 2 Reservoir, Vietnam, Bulletin of the Seismological Society of America, 106,
951 2389–2394, https://doi.org/10.1785/0120160106, 2016.
952 GB/T 21075-2007. Reservoir-induced earthquake hazard assessment. Beijing: Standards Press of
953 China, 2007.
954 Ghofrani, H. and Atkinson, G. M.: Activation Rate of Seismicity for Hydraulic Fracture Wells in
955 the Western Canada Sedimentary Basin, Bulletin of the Seismological Society of America, 110,
956 2252–2271, https://doi.org/10.1785/0120200002, 2020.
957 Grasso, J. -R., Karimov, A., Amorese, D., Sue, C., and Voisin, C.: Patterns of Reservoir-Triggered
958 Seismicity in a Low-Seismicity Region of France, Bulletin of the Seismological Society of
959 America, 108, 2967–2982, https://doi.org/10.1785/0120180172, 2018.
960 Guo, L. J., 2015. A study on the statistical features of earthquake sequence parameters of the North-
961 South Seismic Belt (Master's thesis). Institute of Geophysics, China Earthquake
962 Administration.
963 Gupta, H. K., Rastogi, B. K., and Narain, H.: Common features of the reservoir-associated seismic
964 activities, Bulletin of the Seismological Society of America, 62, 481–492,
965 https://doi.org/10.1785/BSSA0620020481, 1972.
966 Gupta, H. K.: A review of recent studies of triggered earthquakes by artificial water reservoirs with
967 special emphasis on earthquakes in Koyna, India, Earth-Science Reviews, 58, 279–310,
968 https://doi.org/10.1016/S0012-8252(02)00063-6, 2002.
969 Jiang, C. S., Han, L. B., Guo, L. J.,: Parameter characteristics in the early period of three earthquake
970 sequences in the Yutian, Xin Jiang since 2008, Acta Seismologica Sinica, 36, 165–174,
971 https://doi.org/10.3969/j.issn.0253-3782.2014.02.002, 2014. (in Chinese)
972 Jiang, C. S., Wu, Z. L., Han, L. B., Guo, L. J.,: Effect of cutoff magnitude M_c of earthquake

973 catalogues on the early estimation of earthquake sequence parameters with implication for the
974 probabilistic forecast of aftershocks: The 2013 Minxian-Zhangxian, Gansu, M_S6.6 earthquake
975 sequence, Chinese Journal of Geophysics, 56, 4048–4057,
976 https://doi.org/10.6038/cjg20131210, 2013b. (in Chinese)
977 Jiang, C. S., Wu, Z. L., Yin, F. L., Guo, L. J., Bi, J. M., Wang, Y. W.,: Stability of early-estimation
978 sequence parameters for continuous forecast of the aftershock rate: A case study of the 2014
979 Ludian, Yunnan M_S6.5 earthquake, Chinese Journal of Geophysics, 58, 4163–4173,
980 https://doi.org/10.6038/cjg20151123, 2015. (in Chinese)
981 Jiang, C. S., Zhuang, J. C., Long, F., Han, L. B., Guo, L. J.,: Statistical analysis of ETAS parameters
982 in the early stage of the 2013 Lushan M_S7.0 earthquake sequence, Acta Seismologica Sinica,
983 35, 661–669, https://doi.org/10.3969/j.issn.0253-3782.2013.05.005, 2013a. (in Chinese)
984 Jiang, C., Jiang, C. S., Yin, F. L., Zhang, Y. B., Bi, J. M., Long, F., Si, Z. Y., Yin, X. X.,: A new
985 method for calculating b-value of time sequence based on data-driven (TbDD): A case study
986 of the 2021 Yangbi M_S6.4 earthquake sequence in Yunnan, Chinese Journal of Geophysics, 64,
987 3126–3134, https://doi.org/10.6038/cjg2021P0385, 2021. (in Chinese)
988 Julian, B. R. and Foulger, G. R.: Time-dependent seismic tomography: Time-dependent seismic
989 tomography, Geophysical Journal International, 182, 1327–1338,
990 https://doi.org/10.1111/j.1365-246X.2010.04668.x, 2010.
991 Klose, C. D.: Mechanical and statistical evidence of the causality of human-made mass shifts on the
992 Earth's upper crust and the occurrence of earthquakes, Journal of Seismology, 17, 109–135,
993 https://doi.org/10.1007/s10950-012-9321-8, 2013.
994 Lamontagne, M., Rogers, G., Cassidy, J., Tournier, J., and Lawrence, M. S.: A Review of Reservoir
995 Monitoring and Reservoir-Triggered Seismicity in Canada, Bulletin of the Seismological
996 Society of America, 108, 3062–3079, https://doi.org/10.1785/0120180009, 2018.
997 Li, L. and Luo, G.: What causes the spatiotemporal patterns of seismicity in the Three Gorges
998 Reservoir area, central China?, Earth and Planetary Science Letters, 592, 117618,
999 https://doi.org/10.1016/j.epsl.2022.117618, 2022.
1000 Mesimeri, M., Karakostas, V., Papadimitriou, E., and Tsaklidis, G.: Characteristics of earthquake
1001 clusters: Application to western Corinth Gulf (Greece), Tectonophysics, 767, 228160,
1002 https://doi.org/10.1016/j.tecto.2019.228160, 2019.

Miao, M., Han, P., Yao, M., Wang, R., Zhao, C., Zhao, C., Lu, R., Du, Z., and Chen, X.: Spatial-Temporal Pore Pressure and Stress Evolution Associated With the Impoundment of Two Contiguous Reservoirs in Jinsha River, China and Regional Seismicity, JGR Solid Earth, 130, e2025JB031220, https://doi.org/10.1029/2025JB031220, 2025.

Mignan, A., Jiang, C., Zechar, J. D., Wiemer, S., Wu, Z., and Huang, Z.: Completeness of the Mainland China Earthquake Catalog and Implications for the Setup of the China Earthquake Forecast Testing Center, Bulletin of the Seismological Society of America, 103, 845–859, https://doi.org/10.1785/0120120052, 2013.

Ogata, Y. and Katsura, K.: Analysis of temporal and spatial heterogeneity of magnitude frequency distribution inferred from earthquake catalogues, Geophysical Journal International, 113, 727–738, https://doi.org/10.1111/j.1365-246X.1993.tb04663.x, 1993.

Ogata, Y.: Increased probability of large earthquakes near aftershock regions with relative quiescence, J. Geophys. Res., 106, 8729–8744, https://doi.org/10.1029/2000JB900400, 2001.

Ogata, Y.: Statistical Models for Earthquake Occurrences and Residual Analysis for Point Processes, Journal of the American Statistical Association, 83, 9–27, https://doi.org/10.1080/01621459.1988.10478560, 1988.

Pearson, K.: VII. Note on regression and inheritance in the case of two parents, Proceedings of the Royal Society of London, 58, 240–242, https://doi.org/10.1098/rspl.1895.0041, 1895.

Rajendran, K. and Talwani, P.: The role of elastic, undrained, and drained responses in triggering earthquakes at Monticello Reservoir, South Carolina, Bulletin of the Seismological Society of America, 82, 1867–1888, https://doi.org/10.1785/BSSA0820041867, 1992.

Simpson, D. W., Leith, W. S., and Scholz, C. H.: Two types of reservoir-induced seismicity, Bulletin of the Seismological Society of America, 78, 2025–2040, https://doi.org/10.1785/BSSA0780062025, 1988.

Song, C., Fan, C., Zhu, J., Wang, J., Sheng, Y., Liu, K., Chen, T., Zhan, P., Luo, S., Yuan, C., and Ke, L.: A comprehensive geospatial database of nearly 100 000 reservoirs in China, Earth Syst. Sci. Data, 14, 4017–4034, https://doi.org/10.5194/essd-14-4017-2022, 2022.

Spearman, C.: The Proof and Measurement of Association between Two Things, The American Journal of Psychology, 15, 72, https://doi.org/10.2307/1412159, 1904.

Talwani, P., Chen, L., and Gahalaut, K.: Seismogenic permeability, k_s, JGR Solid Earth, 112,

2006JB004665, https://doi.org/10.1029/2006JB004665, 2007.

Talwani, P.: On the Nature of Reservoir-induced Seismicity, Pure Appl. Geophys., 150, 473–492, https://doi.org/10.1007/s000240050089, 1997.

Trivedi, P. C.: Application of Omori's Decay Law to the 2001 Bhuj Aftershock Sequence for Kachchh Region of Western India, OJER, 04, 94–101, https://doi.org/10.4236/ojer.2015.43009, 2015.

Utsu, T.: Representation and Analysis of the Earthquake Size Distribution: A Historical Review and Some New Approaches, Pure Appl. Geophys., 155, 509–535, https://doi.org/10.1007/s000240050276, 1999.

Wang, J.-H.: On the correlation of observed Gutenberg-Richter's b value and Omori's p value for aftershocks, Bulletin of the Seismological Society of America, 84, 2008–2011, https://doi.org/10.1785/BSSA0840062008, 1994.

Wang, Y. W., Jiang, C. S., Liu, F., Bi, J. M.,: Assessment of earthquake monitoring capability and score of seismic station detection capability in China Seismic Network (2008-2015)., Chinese Journal of Geophysics, 60, 2767–2778, https://doi.org/10.6038/cjg20170722, 2017. (in Chinese)

Xu, X., Han, Z., Yang, X., Zhang, S., Yu, G., Zhou, B., Li, F., Ma, B., Chen, G., and Ran, Y.: Seismotectonic Map in China and its Adjacent Regions (1:4 000 000), Seismological Press, https://doi.org/10.12031/activefault.china.250.2016.db, 2016. (in Chinese)

Xue, Y., Xie, M. Y., Liu, J., Zhuang J. C.,: Study on foreshock sequences of the global great shallow-focus earthquakes with $M_W \geqslant 8.0$, Seismology and Geology, 43, 1233–1249, https://doi.org/10.3969/j.issn.0253-4967.2021.05.012, 2021. (in Chinese)

Yin, F. and Jiang, C.: Enhanced *b* -value time-series calculation method using data-driven approach, Geophysical Journal International, 236, 78–87, https://doi.org/10.1093/gji/ggad419, 2024.

Zaliapin, I., Gabrielov, A., Keilis-Borok, V., and Wong, H.: Clustering Analysis of Seismicity and Aftershock Identification, Phys. Rev. Lett., 101, 018501, https://doi.org/10.1103/PhysRevLett.101.018501, 2008.

Zhang, M., Ge, S., Yang, Q., and Ma, X.: Impoundment-Associated Hydro-Mechanical Changes and Regional Seismicity Near the Xiluodu Reservoir, Southwestern China, JGR Solid Earth, 126, e2020JB021590, https://doi.org/10.1029/2020JB021590, 2021.

1063 Zhuang, J., Ogata, Y., and Vere-Jones, D.: Stochastic Declustering of Space-Time Earthquake
1064 Occurrences, Journal of the American Statistical Association, 97, 369–380,
1065 https://doi.org/10.1198/016214502760046925, 2002.
1066