# Intercomparison of nighttime aerosol optical depth retrievals from both reflectance-based and city light-based methods using VIIRS DNB data

Aanan H. Schlief[1], Jared W. Marquis[1], Jianglong Zhang[1*], Jeffrey S. Reid[2], and Steve Miller[3]

[1]Department of Atmospheric Sciences, University of North Dakota, Grand Forks, ND 58202, USA
[2]Marine Meteorology Division, US Naval Research Laboratory, Monterey, CA 93943, USA
[3]Cooperative Institute for Research in the Atmosphere, Colorado State University, Fort Collins, CO 80521, USA

*Correspondence to*: Jianglong Zhang (jianglong.zhang@und.edu) & Aanan Schlief (aanan.schlief@und.edu)

**Abstract.**

Using observations from the Visible Infrared Imaging Radiometer Suite (VIIRS) Day/Night Band (DNB), two different nighttime aerosol optical depth (AOD) retrieval methods were evaluated and inter-compared. The first approach is a lunar reflectance-based retrieval method, using reflected moonlight in a manner similar to daytime retrievals. The second approach utilizes changes in light patterns over regions with artificial light sources due to the upward diffusion of light by aerosol particles. Both retrieval methods were implemented over Dakar and Dakar Belair, Senegal for 2017, 2018, and 2019. Retrievals from both approaches were evaluated against ground-based solar and lunar AErosol RObotic NETwork (AERONET) data, as well as daytime AOD retrievals from the Moderate Resolution Imaging Spectroradiometer (MODIS). Additionally, impacts of using the Miller and Turner (MT) lunar model for estimating Top-Of-Atmosphere (TOA) lunar spectral flux for AOD retrievals were also studied. Findings suggest that while both retrieval methods show skill in retrieving nighttime AOD by qualitatively identifying over-ocean aerosol plume locations and quantitatively comparing with solar and lunar retrieved AERONET data, cloud contamination and variations in lunar properties are factors that need to be carefully quantified in future studies for accurate nighttime aerosol retrievals using VIIRS DNB data. This study suggests that there are sampling issues from both approaches, but the combined use of both retrieval methods can increase the sampling rate for nighttime aerosol retrievals by more than 50%.

## 1 Introduction

In passive-based aerosol optical depth (AOD) retrievals, aerosol properties are typically derived during daytime hours from observed top-of-atmosphere reflected solar light (Remer et al., 2005). The lack of solar illumination during the nighttime makes the retrieval of nighttime aerosol properties using more traditional sensors such as from the Moderate Resolution Imaging Spectroradiometer (MODIS) and Multi-angle Imaging SpectroRadiometer (MISR) impossible (e.g. Zhang et al.,

2025). However, included within the Visible Infrared Imaging Radiometer Suite (VIIRS) sensor on-board Suomi-NPP, and the Joint Polar Satellite System (JPSS) series is a calibrated high gain Day/Night Band (DNB) channel that is able to sense reflected visible light levels up to 10 million times weaker than reflected sunlight (Miller et al., 2013). Using observations from VIIRS DNB, pioneering nighttime aerosol retrieval efforts have been attempted using either 1) reflected moonlight rather than sunlight (e.g. Zhou et al., 2021); 2) direct light emission brightness from artificial light sources (e.g. Zhang et al., 2008; Johnson et al., 2013); or 3) contrast reduction (variance) over artificial light sources (e.g. McHardy et al., 2015; Zhang et al., 2025).

Related to the more traditional passive retrieval approach, reflected moonlight, which contains information about surface and atmospheric properties (e.g., aerosols), can be applied for retrieving nighttime aerosol properties using a daytime-like approach. In fact, if reflectance is used, which is the measured Top-Of-Atmosphere (TOA) upward radiance from VIIRS DNB normalized by TOA downward lunar flux, single channel daytime AOD retrieval methods may be applicable to nighttime aerosol retrievals. Since reflectance is normalized by TOA downward flux, the observed reflectance from VIIRS DNB shall be similar given the same surface and atmospheric conditions, as well as the same viewing geometries regardless of TOA downward flux magnitude from solar light or moonlight. For example, Zhou et al., (2021) attempted nighttime aerosol retrievals using reflected lunar light over dark surfaces over rural areas in the United States. The study went on to note that the VIIRS DNB lunar reflectance-based retrieval algorithm can be used as a method to provide diurnal aerosol retrievals with the ability to track nighttime aerosols (Zhou et al., 2021).

The lunar reflectance method requires the presence of reflected moonlight, which can't be applicable to nights that lack moonlight such as new moon nights (e.g. Zhang et al., 2025). The broad DNB spectral range (0.5-0.9 μm) is significantly wider than most, requiring for some accounting of aerosol and surface optical properties, especially over land where vegetated albedo increases significantly in the red to near infrared. It is also very challenging to apply the reflected moonlight-based aerosol retrieval method over both vegetated and bright surfaces, where the TOA reflected moonlight is less-sensitive/insensitive to changes in the underneath aerosol layers.

As an alternative to the traditional aerosol retrieval method, using nighttime observations from the Defense Meteorological Satellite Program (DMSP) Operational Linescan System (OLS), Zhang et al., (2008) proposed a method of

retrieving AOD using observations over regions with the distribution of artificial light contrasts. The initial hypothesis of the study was that for aerosol polluted cloud free nights, radiance values over artificial light sources, as measured by the DNB, can be much reduced in comparison with aerosol free and cloud free nights, depending on AOD. McHardy et al., (2015) proposed a revised method for deriving nighttime AODs using variances in radiances (that is reduced sharpness) within an artificial light source known as the *variance method*. The advantage of the variance method (versus that of the direct light emission method) is that only the VIIRS DNB radiance distribution over artificial light sources is needed. This excludes the need for observations from artificial light free regions as required by direct light emissions methods (e.g. Johnson et al., 2013). Thus, only the variance method is discussed hereafter. This variance method has the additional benefit that the impact of moonlight on AOD retrievals is much reduced. Following similar methods proposed in McHardy et al., (2015), Zhang et al., (2019; 2025) extended the study on a much larger spatial and temporal domain demonstrating the possibility of conducting nighttime AOD retrievals using VIIRS DNB data on both local and global scales. While the findings in Zhang et al., (2019; 2025) were encouraging for the development of an operational nighttime AOD product, misclassification of high aerosol loading as cloud as well as differences in surface reflectance due to snow still provide complications.

In fact, both the reflected moonlight-based and artificial light-based variance methods are ultimately complimentary given differences in lower boundary conditions and the availability of lunar and artificial light sources. It is a natural desire to combine both methods for maximum data coverage in space and time. Yet, each method has its strengths and weaknesses that need to be studied before retrievals from both methods can be properly integrated. It is worth noting that although pioneer efforts have been conducted for attempting nighttime AOD retrievals based on either reflected moonlight or attenuated artificial lights, there has yet to be a pairwise comparison of AOD retrievals from both methods. In this study, using VIIRS DNB observations over the Atlantic Ocean near Dakar and Dakar Belair, Senegal, AOD retrievals from both methods were attempted and inter-compared for three years of data: 2017, 2018, and 2019. The Dakar and Dakar Belair, Senegal region was selected as this region is frequently polluted by dust aerosols originating from North Africa. Limitations and caveats of each method, including data sampling rates and major uncertainty sources, were explored in this study. Also, the impact of lunar reflectance models on AOD retrievals, including the use of Miller and Turner (MT) model (Miller and Turner, 2009) which estimate TOA downwelling spectral lunar fluxes needed to approximate VIIRS DNB reflectance, were also studied. In addition, we explored

the feasibility of applying a single channel daytime solar reflectance-based method, designed for daytime AOD retrievals using measured TOA reflected solar light (in unit of reflectance), for lunar AOD retrievals using reflected moonlight (in the unit of reflectance) by replacing TOA downwelling solar spectral irradiance with lunar spectral irradiance.

## 2 Datasets and Models

VIIRS DNB data were used for retrieving nighttime aerosol optical depth. MODIS and ground-based AErosol RObotic NETwork (AERONET) data were used for evaluating/validating VIIRS nighttime AOD retrievals for the years 2017-2019. Details of each dataset are listed below.

### 2.1 VIIRS DNB Data

The VIIRS sensor onboard the Suomi National Polar-Orbiting Partnership (NPP) satellite includes a Day/Night Band that is capable of providing passive-based observations of low light scenes at nighttime. The VIIRS DNB is a panchromatic sensor observing at a wavelength range of 0.5-0.9 μm centered at 0.7 μm (Miller et al., 2013; Zhang et al., 2019). The spatial resolution is ~750 meters across the swath width of approximately 3060 km. The VIIRS data for this study were obtained from the NOAA Comprehensive Large Array-Data Stewardship System (NOAA CLASS; https://www.avl.class.noaa.gov/saa/products/, last access: Apr 16, 2026).

Both VIIRS Environmental Data Records (EDR) and VIIRS Sensor Data Records (SDR) datasets were used in this study. The VIIRS SDR dataset contains VIIRS DNB Geographical Sensor data record (GDNBO) and VIIRS DNB radiance sensor data (SVDNB) providing DNB radiance and geolocation data at a spatial resolution of ~750 meters. Furthermore, the VIIRS EDR dataset includes VIIRS DNB cloud cover (VCCLO) and VIIRS cloud-aggregated environmental ellipsoid geolocation (GCLDO) layers data, provided at a gridded spatial resolution of 6 km, were used for cloud screening. Since the VIIRS SVDNB radiance data and cloud products (VCCLO and GCLDO) are available at different spatial resolutions, VIIRS cloud products were resampled to the spatial resolution of the VIIRS SVDNB data before being used to cloud screen the VIIRS DNB radiance data (e.g., Zhang et al., 2019; 2025). To further assist cloud screening, a cloud mask from the VIIRS Black Marble dataset were also used. The spatial resolution of VIIRS Black Marble data is at a resolution of 15 arc seconds (~500 m resolution; Román et al., 2018). The nearest VIIRS Black Marble cloud mask data for a given pixel is also used for assisting

detection of the presence of clouds. The NASA Black Marble data were downloaded from the NASA Level-1 and Atmosphere Archive & Distribution System (LAADS) Distributed Active Archive Center (https://ladsweb.modaps.eosdis.nasa.gov/; last accessed July 29, 2026).

For illustration purposes, VIIRS Moderate Resolution Band 16 (SVM16) and VIIRS Moderate Bands SDR Geolocation (GMODO) data were used to show InfraRed brightness temperature of the study scenes for selected case studies. The SVM16 data is a longwave thermal infrared band spanning the wavelength range of 11.54 – 12.49 μm at a spatial resolution of 750 meters. The dataset was downloaded from NOAA CLASS (last accessed July 28, 2026).

### 2.2 Aqua MODIS Data

The Aqua MODIS daytime aerosol retrievals were used for cross-comparison of nighttime aerosol retrievals from VIIRS in this study. The MODIS instrument includes a total of 36 spectral channels ranging from visible to thermal-infrared spectrum, providing retrievals of atmospheric properties including aerosol optical depth over land and oceans (Remer et al., 2005; 2013). The Collection 6.1 Aqua MODIS Dark Target (DT) data (DOI: 10.5067/MODIS/MYD04_L2.061), which were used in this study, include AOD retrievals at 7 different wavelengths (0.47, 0.55, 0.66, 0.86, 1.24, 1.63, 2.11 μm) over global oceans and 3 wavelengths over land (0.47, 0.55, 0.66 μm), with a spatial resolution at nadir of 10 km (Levy et al., 2013). Since the reflectance-based VIIRS DNB AOD retrievals developed in this study are available at the 0.55 μm wavelength, Effective Optical Depth Average Ocean data from MODIS were used for intercomparison with nighttime reflectance-based VIIRS AOD retrievals. The MODIS data used in this study were obtained from the NASA LADDS Distributed Active Archive Center (https://ladsweb.modaps.eosdis.nasa.gov/; last access: Apr 16, 2026).

### 2.3 AERONET Data

The cloud screened, quality assured Version 3, Level 2.0 nighttime and daytime AERONET data from the Dakar, Senegal (14.4° N, 17.0° W) and the Dakar Belair, Senegal (14.7° N, 17.4° W) stations were used to evaluate the VIIRS retrieved AOD data. Through directly measuring attenuated moonlight or daytime sky radiance, AERONET AOD data are available at several wavelengths from 340 nm to 1020 nm (Holben et al., 1998; Giles et al., 2019, Schafer et al., 2026). AOD retrievals at

0.675 μm and 0.5 μm from both the daytime and nighttime AERONET AOD products were used to assess the performance of the VIIRS retrieved AODs from the two different retrieval methods. The AERONET datasets used in this study were obtained from the AERONET website (aeronet.gsfc.nasa.gov; last access: Apr 16, 2026). In addition, both daytime and nighttime averages of AERONET AOD data were also downloaded from the AERONET website to investigate the difference in day and night AERONET data over the study region.

### 2.4 Radiative Models

VIIRS DNB data include calibrated TOA upwelling radiances, that is a strong function of moon phase and linked to parameters such as moon fraction and lunar zenith angle. To port daytime AOD retrieval methods for nighttime events, an estimation of TOA downwelling moon flux for a given observing condition is needed. For this study, we used the empirical-based MT lunar model (Miller and Turner, 2009), that estimates TOA downwelling fluxes based on spectral moon albedo, earth-moon-sun geometries, moon phase and the earth and sun distance at a 1 nm resolution for the spectral range of 0.2-2.8 μm (Miller and Turner 2009). The reported uncertainty of the MT lunar model is 7-17% (Miller and Turner, 2009) due to factors including sensitivity to high lunar phase angles (opposition effect) and libration effects (Zeng et al., 2018). By applying the VIIRS DNB sensor response function, VIIRS DNB reflectance can be derived using the MT model, and by using measured VIIRS DNB radiances as inputs (Miller and Turner, 2009).

To perform AOD retrievals, the Santa Barbarra Distort Radiative Transfer (SBDART) model (Ricchiazzi et al., 1998) was used to simulate VIIRS DNB received TOA reflectances over ocean scenes. The inputs for the radiative transfer model include surface properties, viewing geometries and atmospheric and aerosol conditions. Here we used ocean properties included in the SBDART model. The viewing geometries are from satellite ephemeris data. A standard atmospheric profile (Ricchiazzi et al., 1998) is assumed in which the mean vertical distribution of atmospheric properties (e.g., temperature) represents that of annual mid-latitude conditions. For consistency in dust aerosol optical properties, we applied MODIS Collection 6 (C6) Dark-Target (DT) over-ocean algorithm values of aerosol physical properties including refractive index, effective radius, and radii standard deviation values obtained for 7 wavelengths individually that range from 0.47-2.11 μm. (e.g., Figure 1). The five wavelengths of the DT aerosol parameters used are from the 0.47, 0.55, 0.65, 0.86, and 1.24

wavelengths. Using this information, for coarse mode aerosols, T-Matrix (Mishchenko et al., 1996) calculations were performed by the research team to estimate dust optical properties including phase function, single scattering albedo, extinction cross section, and scattering cross section, assuming spherical dust. Note that the shape assumption implemented in this study is different from what is done by the MODIS team (assuming spheroids instead). This means the retrieval is assuming purely coarse mode spherical dust aerosols. This assumption may introduce larger error when AOD is low (minimal dust) and may have a better performance for high AOD cases. Next, SBDART is designed and run for daytime simulations using optical properties such as single scattering albedo, extinction cross section, and Legrendre polynomial coefficients as provided by the T-matrix calculations at each of the seven wavelengths respectively. SBDART radiative transfer simulations were performed using discrete wavelengths from 0.49 – 0.90 µm in 0.005 µm intervals covering the spectral response range of the VIIRS DNB using the wavelength dependent optical properties from the T-matrix as explained. After which, the simulated monochromatic radiances from SBDART were weighted (or spectrally averaged) by the VIIRS DNB spectral response function to produce a single-band integrated reflectance. To perform nighttime simulations, the spectral TOA downwelling solar spectral irradiances were replaced by the spectral TOA downwelling lunar spectral irradiances with detailed discussed in Section 3.1.1.





**Figure 1.** Dust aerosol properties as a function of wavelength used in this study. This dust aerosol optical property data is obtained from the aerosol optical model 8 used in constructing the MODIS Dark Target products

## 3 Methodology

The VIIRS DNB nighttime observations, MODIS daytime observations, AERONET nighttime Lunar Provisional and daytime quality assured AERONET data were acquired for the 2017-2019 calendar years over the Dakar and Dakar Belair, Senegal region. Both the city light retrieval method and the lunar reflectance-based retrieval method were applied to VIIRS DNB data for aerosol retrievals as described below. Co-located MODIS and AERONET data were used for evaluating/validating VIIRS retrieved AOD values from this study.

### 3.1 Lunar Reflectance-Based Retrieval Method

#### 3.1.1 Retrieval Approach

As it is challenging to perform passive-based aerosol retrievals over bright surfaces such as desert regions using the reflectance-based method, only over-ocean, nighttime, assumed-dust, aerosol retrievals were applied using the lunar reflectance-based method. Open ocean surfaces offer a favourable target for the reflectance-based approach as it is relatively dark with comparatively homogeneous surface properties in comparison with land and the higher albedos of vegetated surfaces. Thus, over ocean aerosol retrievals are considered more reliable. Hence, we used the ocean surface reflectance model included in the SBDART model (Ricchiazzi et al., 1998) and changes in ocean optical properties (e.g. suspended sediments) are not considered. Additionally, while water vapor impacts the growth of hygroscopic aerosols, the influence of water vapor on AOD retrievals is considered marginal for wide spectral bands such as the DNB at the visible spectrum (e.g. Knapp et al., 2002). However, for narrower bands used in multispectral retrievals (e.g. VIIRS/MODIS), one needs to account for variations in water vapor absorption. The lunar reflectance-based method is almost identical to the reflectance method implemented for daytime aerosol retrievals (e.g. MODIS) but for a single channel. Different from the daytime solar-based reflectance method, reflected moonlight, instead of reflected sunlight, is used for estimating TOA reflectance for the nighttime AOD retrieval process. To perform the retrieval, the VIIRS DNB measured reflectance values are inter-compared with precomputed reflectance values from a look-up-table (LUT) for different atmospheric and aerosol conditions. The LUT values were computed using SBDART model (Ricchiazzi et al., 1998) with details listed in Section 2. The LUT includes precomputed reflectance based on aerosol properties, varying viewing geometries (lunar zenith angle, sensor zenith angle, relative azimuth angle), as well as surface

conditions using SBDART runs. In this study, to construct the LUTs, SBDART simulations were performed for over-ocean dust cases for 18 AOD, 9 lunar zenith angle, 7 sensor zenith angle and 12 relative zenith angle ranges.

As SBDART is designed with solar spectral irradiance models for radiative transfer in the visible spectrum, to create an AOD look-up-table for nighttime retrievals, a lunar spectral irradiance model is needed. This was created by normalizing the 5s solar model included within SBDART using the mean sun-moon-earth distance and the lunar albedo from the MT model at full moon. To simulate VIIRS DNB radiance, the VIIRS DNB sensor spectral response function was also used to determine upwelling and downwelling TOA radiance. TOA reflectance is derived by dividing the upwelling radiance multiplied by π by the downwelling lunar flux. Note that this approach does not directly account for the variations in sun-moon-earth distance and lunar phase. Yet, both affect TOA downwelling flux, and should be accounted for indirectly by using TOA reflectance (π×TOA upwelling radiance / TOA downwelling flux) as both the TOA upwelling radiance (part of the numerator) and the TOA downwelling flux (the denominator term) terms shall be scaled by the above-mentioned variations.

### 3.1.2 Quality Check for the Lunar Reflectance-Based Retrieval Method

Several quality check processes were implemented for removing less-ideal retrieving conditions, including lunar fractional illumination, glint angle, and data count checks. The lunar fractional illumination was used as a determination for the fullness of the moon on a range of 0 (new moon) – 1 (full moon) and is constant regardless of location on Earth. Still, nights with less sufficient moonlight need to be excluded for reliable nighttime aerosol retrievals. For example, for lunar fractional illumination changes from 1 to 0.5, the VIIRS DNB received radiance values can be decreased by ~90% (Cao et al., 2019); significantly reducing the signal-to-noise ratio for reliable aerosol retrievals. Thus, for this study, only VIIRS DNB data with lunar fractional illumination values larger than 0.5 are used for AOD retrievals. For fractional illuminations below 0.5, sensor noise is comparable to the incoming reflected lunar irradiance resulting in “noisy” pixels with large reflectance values (see discussions related to Figure 7). Note that for lunar fractional illumination ranges from 0.85 to 1.0 (e.g. Figure 6), which is preferred for lunar reflectance-based nighttime aerosol retrievals, sufficient TOA incoming moonlight accounts for 7-9 days per month (or 84-108 days per year).

Equivalent to daytime aerosol retrievals, where regions with sun glint are excluded due to strong glint reflectance, regions with lunar (moon) glint are excluded for nighttime aerosol retrievals. Lunar glint regions are computed using a

geometric calculation from Remer et al., (2005). Similar to daytime aerosol retrievals, VIIRS DNB data with lunar glint angles of less than 40° are excluded by this study (e.g. Remer et al., 2005). Moon glint regions are associated with higher-than-normal TOA upwelling radiance/reflectance as observed from VIIRS, which can introduce high uncertainties in VIIRS DNB based nighttime aerosol retrievals and thus need to be removed in the retrieval process.

### 3.1.3 Cloud Screening for the Lunar Reflectance-Based Retrieval Method

Cloud contamination is a persistent problem in daytime aerosol retrievals (e.g., Reid et al., 2022) and is even more problematic for nighttime aerosol retrievals using VIIRS DNB data. This is because unlike daytime retrievals that can utilize the high-resolution, visible and near IR channel-based cloud mask, only VIIRS DNB and VIIRS mid/thermal IR channels can be used to detect clouds at nighttime. Since VIIRS DNB nighttime cloud detection is limited to a single channel, thick atmospheric aerosol plumes could be misidentified as cloud using fixed cloud detection thresholds. Furthermore, nighttime cloud observations are challenged when detecting small, low, and thin clouds, especially at lower lunar fractional illumination values. Thus, various cloud screening steps were applied. Naturally, cloud fraction as reported from the nighttime VIIRS cloud products (e.g., Kopp et al., 2014) was used to screen potential cloud contaminated data points. To further excluding cloud contaminated data, a spatial coherence test for the VIIRS DNB data was also implemented.

The concept behind the spatial coherence test assumes that cloud contaminated regions have larger spatial variance than clear and aerosol polluted regions. Note that a similar concept was also applied for cloud–clearing daytime MODIS aerosol retrievals (Martins et al., 2002). In this method, retrievals were conducted at a 10 x 10-pixel domain. Both the standard deviation of a 10×10-pixel area and the averaged cloud fraction of the 10 x 10-pixel domain (based on the VIIRS cloud products) were computed. A set of cloud fraction thresholds (0.2-0.8) and a set of standard deviation thresholds (0.01-0.02) were used for cloud screening and the sensitivity of the thresholds chosen are mentioned in Section 3. Also, if the count of pixels within a 10 x 10 aggregated granule is than 25 (e.g., missing pixels) no retrieval is conducted.





**Figure 2.** a) Lunar reflectance from 27 Oct 2018, b) cloud mask for the same data as a) using a standard deviation threshold of 0.01 and cloud fraction threshold of 0.6, c) glint mask, d) AOD (0.55 μm) retrievals for the same image as a), with the use of the standard deviation threshold of 0.01 and cloud fraction threshold of 0.2 for cloud masking, e) similar to d) but with the use of a standard deviation threshold of 0.01 and cloud fraction threshold of 0.6 for cloud masking, f) similar to d) but with the use of a standard deviation threshold of 0.02 and cloud fraction threshold of 0.8 for cloud masking

Figure 2 shows an example of nighttime AOD retrievals for a case from 27 October 2018 illustrating the use of varying cloud screening thresholds. While cloud contamination is clearly visible using a cloud fraction threshold of 0.8 and a

standard deviation threshold of 0.2 (Figure 2f), the use of a very stringent cloud fraction threshold of 0.2 and a standard deviation threshold of 0.01 exclude some valid AOD retrievals (Figure 2d). To maintain sufficient retrievals while suppressing cloud contamination, an optimal section of thresholds for cloud screening is needed, which is discussed in detail in Section 4.

### 3.2 City Light-Based Retrieval Method (variance-based)

For the city light-based aerosol retrieval process (Zhang et al., 2008; Johnson et al., 2013; McHardy et al., 2015; Zhang et al., 2019; 2025), the VIIRS-observed cloud-free radiance over an artificial light source can be described using Equation 1:

$$I_{sat} = I_s e^{-\tau/\mu} + I_s T(\mu) + I_p \quad (1)$$

where $I_{sat}$ is the radiance received by the VIIRS instrument. $I_s e^{-\tau/\mu}$ is the direct upwelling surface light emission where $\mu$ is the cosine of the viewing angle. $\tau$ is the total column optical depth and $I_s$ is the surface upward irradiance for cloud-free sky. $I_s T(\mu)$ is the upwelling surface light emission through diffuse transmittance with $T(\mu)$ being the diffuse transmittance, and $I_p$ is the path irradiance source. Equation 1 shows that the observed radiance includes both direct and diffused radiation from the atmosphere, Earth's surface, and artificial light sources.

The optical depth of an atmosphere column can thus be derived, based on Eq. 2 (derived from Eq. 3; Johnson et al., 2013; McHardy et al., 2015; Zhang et al., 2019; 2025)

$$\tau = \mu \ln \frac{\Delta I_a}{k \Delta I_{sat} (1 - \bar{r} r_s)} \quad (2)$$

where $\tau$ is the nighttime column integrated aerosol optical depth, $k$ is a correction factor for the diffuse transmittance, derived from the 6S radiative transfer model for a standard atmosphere (Vermote et al., 1997; Johnson et al., 2013), $\Delta I_{sat}$ is the variance in TOA radiance for an artificial light source for cloud-free conditions over an artificial light source, $\Delta I_a$ is the variance in TOA radiance for an artificial light source for aerosol and cloud-free conditions, and the $\bar{r} r_s$ term is the reflected surface upward radiance by the aerosol layer and is treated as negligible in this study. $\tau$ is a summation of optical depth from aerosols, as well as Rayleigh scattering and absorption optical depth for gas species (Zhang et al., 2019).

Similar to the previous method, quality check and cloud screening steps were applied. First, missing or out-of-range data pixels were removed, along with pixels that have poor calibration quality or exhibited saturation. This process is adopted from Zhang et al., (2019) and requires a threshold-based screening of the solar zenith angle for a given pixel. For each pixel, a solar zenith angle greater than 102° must be observed to eliminate solar and twilight contamination. Following cloud screening and the previous quality assurance steps, artificial light source pixels were identified through a threshold-based method (Johnson et al., 2013; Zhang et al., 2019). For a pixel to be determined as an artificial light source pixel, the radiance of a pixel must be greater than 1.5 times the mean granule cloud-free background radiances. Various cloud screening methods, following Zhang et al., (2019) were also implemented.

The artificial light based AOD retrieval variance method was applied to data over the Dakar and Dakar Belair, Senegal region for the years of 2017, 2018 and 2019. Retrieved VIIRS AOD (0.7 μm) from the city light method were intercompared with both daytime and nighttime AEROENT retrievals and the AOD retrievals from the previously mentioned lunar reflectance based nighttime aerosol retrieval method (0.675 μm).

### 3.3 AERONET AOD Co-location Technique

As described earlier, the AERONET AOD data used in this study are nighttime Level 2.0 Lunar data and daytime Level 2.0 data taken from the 0.675 μm and 0.5 μm wavelengths retrieved at the Dakar, Senegal (14.4° N, 17.0° W) and the Dakar Belair, Senegal (14.7° N, 17.4° W) stations for the calendar years of 2017, 2018, and 2019. The city light-based AOD retrievals are available at 0.7 μm, so AERONET AOD data at 0.675 μm were used for inter-comparison purposes. The lunar reflectance-based AOD retrievals are available at 0.55 μm thus, to inter-compare VIIRS and AERONET AODs, the AERONET data from both 0.5 μm and 0.675 μm were used and interpolated to estimate AERONET AOD retrievals at 0.55 μm following a method as described in Shi et al., (2011).

The AERONET co-location technique used in this study is based upon the co-location techniques introduced in previous studies (Zhang et al., 2019). To be specific, only VIIRS and lunar AERONET data pairs that have a temporal difference within +/- 30 minutes and a spatial difference within 1° (Latitude/Longitude; Euclidean distance) were used. To compare with daytime AERONET data, the temporal and spatial windows are set to +/- 24 hours for a given nighttime VIIRS AOD retrieval and 1° (Latitude/Longitude; Euclidean distance) respectively. Additionally, for daytime AERONET AOD

comparisons with city light-based and lunar reflectance-based retrieved AOD, the AERONET AOD retrieved from the same day and the previous day (+/- 24 hours) are compared and if the difference in daytime AERONET AODs is within 0.2, a comparison with the city light-based or lunar reflectance-based AOD is attempted. All data points from an individual AERONET station within the temporal constraints are averaged to represent the co-located AERONET AOD for a single co-located VIIRS data point. For the lunar reflectance method, VIIRS AOD pixels within 1° (Latitude/Longitude; Euclidean distance) of the Dakar or Dakar Belair AERONET stations respectively are spatially averaged to represent a single VIIRS data point.

### 3.4 MODIS AOD Co-location Technique

The aforementioned MODIS AOD data were also used to evaluate the performance of the lunar reflectance-based VIIRS AOD retrievals. Although only daytime AOD retrievals are available from MODIS, different from AERONET data which are only available at sporadic locations, MODIS data can be used for cross-evaluating VIIRS AOD retrievals over a large spatial domain. For this effort, MODIS DT AOD data were used to inter-compare with the reflectance-based VIIRS DNB AOD retrievals, which are available at 0.55 μm. To co-locate the MODIS and VIIRS data spatially, both MODIS and VIIRS AOD data were averaged into 0.5° x 0.5° (Latitude/Longitude) aggregates first, then comparisons were conducted at the 0.5° x 0.5° (Latitude/Longitude) grid level. To co-locate the MODIS and VIIRS data temporally, the MODIS AOD retrievals from the same day as the VIIRS AOD retrievals were averaged to represent the AOD for the given bin. We also compared daytime average AERONET AOD data with the same days average MODIS AOD data that were within 1° (Latitude/Longitude) Euclidean distance from the Dakar and Dakar Belair AERONET stations over the study period.

### 3.5 Comparison of Lunar Reflectance-Based and City Light-Based Retrieval Methods

One of the goals in this study is to intercompare the lunar reflectance-based and the retrieved city light-based AOD over the Dakar and Dakar Belair, Senegal region. For the city light-based method, retrievals were performed at a spatial resolution of 25×25 $km^2$ (Zhang et al., 2025). Given the center point of 14.7231° N, -17.4604° S, artificial lights from Dakar and Dakar Belair, Senegal spanned across a total of 12-13 25×25 $km^2$ domains with detectable artificial lights depending on the year. Only two 25×25 $km^2$ domains have stable artificial light sources that passed QA (Zhang et al., 2025) and data volume

check (> 40 artificial light pixels). Retrievals from the two 25×25 $km^2$ domains were averaged to represent the city light-based AOD retrieval for a given night. For the two domains that passed QA checks, there are a total of 29 nights of which AOD retrievals are available from both domains and a mean difference of -0.02 and a correlation of 0.78 are found between AODs retrieved from the two domains. For the reflectance-based method, all available retrievals within a 1° x 1° (latitude/longitude) bounding box from the Dakar and Dakar Belair AERONET stations were averaged to represent the lunar reflectance-based AOD retrieval for the night. AOD retrievals from the two different methods were further inter-compared over Dakar /Dakar Belair to determine the frequency and performance of the moonlight and city light-based retrieval methods. For this, time series analysis was also conducted using AERONET and VIIRS DNB AOD data at 0.675 μm from Dakar and Dakar Beliar, Senegal for 2017, 2018, and 2019. Since the VIIRS DNB lunar reflectance-based retrieved AODs are completed at 0.55 μm, an averaged ratio between the Lunar AERONET AODs at 0.55 μm and 0.675 μm, was precomputed. This ratio is used to scale the VIIRS DNB lunar reflectance retrieved AODs from 0.55 μm to 0.675 μm for inter-comparison with the other AOD data used in this study.

## 4 Results

In this section, nighttime aerosol retrievals from both the lunar reflectance method and city light methods were generated using VIIRS DNB data near the Dakar and Dakar Belair, Senegal region for 2017, 2018, and 2019. Inter-comparisons with nighttime/daytime AERONET and daytime MODIS AOD retrievals were performed. Issues and limitations for each method were also explored.

### 4.1 Comparison of Nighttime City Light and Lunar Reflectance-Based AOD Retrievals

As the first step, we attempt to intercompare AOD retrievals from the reflectance based and the city light based AOD retrievals with a time series of solar and lunar AERONET measurements as shown in Figure 3a, where the lunar reflectance-based AOD retrievals were conducted using a standard deviation threshold of 0.01 and a cloud fraction threshold of 0.2. Detailed comparisons between AOD retrievals from both methods and AERONET and MODIS AOD data under difference observing conditions can also be found in later sections (e.g., Sections 4.2, 4.3 and 4.4). As suggested from Figure 3a, while AOD retrievals from both methods share some degree of consistency with AERONET AODs, underestimations and

overestimates are observable, including some significant outliers. In addition, there are only few nights that AOD retrievals from both methods are available, raising a sampling issue for both methods.





**Figure 3.** a) Time series of days/nights with AERONET daytime AOD (0.675 µm), AERONET nighttime AOD (0.675 µm), VIIRS lunar reflectance-based retrieved AOD (0.675 µm) and VIIRS city light-based retrieved AOD (0.7 µm) from Dakar and Dakar Belair, Senegal for 2017-2019. Co-located comparisons of b) daytime AERONET AOD and c) nighttime AERONET AOD and VIIRS DNB lunar reflectance-based AOD (0.55 µm) retrievals with a standard deviation threshold of 0.01 and cloud fraction threshold of 0.2. Also included are co-located comparisons of city light retrieved AOD with d) daytime and e) nighttime AERONET AOD from Dakar and Dakar Belair, Senegal for 2017-2019.

For example, for 2017 to 2019, 882 days are observed by daytime AERONET AOD, 328 nights are observed by nighttime AERONET AOD, yet only 110 nights have completed retrievals of AOD via the city light-based retrieval method, and 123 nights have completed retrievals of AOD via the lunar reflectance-based retrieval method. It is not surprising that the nighttime lunar AERONET AOD and the lunar reflectance-based AOD retrieval method have some of the fewest numbers of retrievals since both require moonlight to provide adequate lighting conditions for the retrieval of AOD. Furthermore, the lunar reflectance-based AOD retrieval method features several quality assurance steps that implement the VIIRS cloud product and contain screenings for lunar glint regions that further exclude additional nights from the study. The AERONET and city light retrieved AODs do contain cloud screening steps but not the moon-glint screening step as these retrievals took place on land surfaces. Moreover, ideal lunar reflectance-based AOD retrievals require nights with the lunar fractional illumination to be over 85%, which limits retrievals to 7-9 nights per month or 84-108 nights per year. The city light-based method, on the other hand, could be implemented regardless of moon status. Yet the stringent QA and cloud clearing steps (Zhang et al., 2025) also limited the number of retrievals available from the city light-based method.

Regardless of limitations as mentioned above, both the reflected moonlight as well as the city light-based methods have some merit in retrieving nighttime AOD by using observations from the VIIRS DNB. Future studies are needed to further explore the pros and cons of both methods and for developing a suitable method for future operational based applications. There are eleven nights with retrievals from both methods, with four nights in 2017, five nights occurring in 2018, and two nights in 2019 with a correlation of 0.08 and a mean difference of 0.26 in terms of AOD. In total 75, 72, and 75 nights occur with retrievals from any one of the retrievals for 2017, 2018, and 2019 respectively, indicating that the combined use of the two methods may double the data sampling rates for nighttime AODs using VIIRS DNB data.

### 4.2 VIIRS DNB AOD Lunar Reflectance-Based AOD Retrieval Comparisons with Co-located AERONET AOD Retrievals

VIIRS DNB AOD retrievals from the lunar reflectance-based nighttime AOD (0.55 μm) retrieval method from varying cloud screening thresholds were inter-compared with Level 2.0 daytime AERONET AOD and Level 2.0 Lunar AERONET AOD data from Dakar and Dakar Belair, Senegal as shown in Table 1. An example of these comparisons is shown

in Figure 3b-c using VIIRS AOD retrievals with a standard deviation threshold of 0.01 and cloud fraction threshold of 0.2. Figure 3b implies that the assumption that nighttime is similar to daytime is prone to error, as larger RMS (0.36) and absolute (0.22) errors are found between nighttime VIIRS AOD and daytime AERONET AOD (Figure 3b). The scatter plot of VIIRS DNB and lunar AERONET AOD for 2017-2019 is shown in Figure 3c, for which a slope of 0.9, an RMS error of 0.30 and an absolute error of 0.19 are found, indicating the feasibility of using lunar reflectance for aerosol retrievals.

The comparison study was conducted as a function of cloud screening thresholds as mentioned in Section 2 to evaluate the impact of and to select the best combination of cloud screening thresholds for AOD retrievals as shown in Table 1. Table 1 shows the comparison of nighttime AERONET AOD (0.55 μm) and VIIRS DNB lunar reflectance-based retrieved AOD (0.55 μm) as functions of the standard deviation threshold of 0.01-0.02 and the cloud fraction threshold of 0.2-0.8 for using data from 2017-2019. The number of valid co-located pairs decreased from 134 to 130 for cloud fraction threshold of 0.8 to 0.2 for a fixed standard deviation threshold of 0.02 with a decrease in Root-Mean-Square-Error (RMSE) from 0.36 to 0.33. The use of a more stringent standard deviation threshold of 0.01 and cloud fraction threshold of 0.2 lowered RMSE to 0.3, yet reducing data pairs to 78. Clearly, better performance is expected with more stringent cloud screening at the cost of data loss. Within this dataset, the lowest $r^2$ is found using a standard deviation threshold of 0.01 and cloud fraction threshold of 0.2. However, the data volume is quite small to generalize this conclusion.

In addition, the MT (2009) model was used to estimate TOA downwelling lunar flux for this study. In the MT (2009) model, different correcting factors were applied to the waxing and waning conditions. Waxing conditions refer to moon phase moving from New Moon to Full Moon (illuminated portion of the Moon is growing) while waning conditions describe moon phase moving from Full Moon to New Moon (illuminated portion of the Moon is shrinking). Thus, the comparison of VIIRS and AERONET AOD data was also conducted for both the waxing (filled circles) and waning (filled squares) conditions as shown in Figure 3 (e.g., Figs. 3b and 3c). As shown in Figure 3, slight differences are found for nighttime AOD retrievals using the lunar reflectance-based method for both waxing and waning phases. For 2017-2019, 41 co-located pairs were found under waning lunar conditions with a correlation of 0.73, RMSE of 0.24, absolute error of 0.165, and a slope of 1.05. Conversely, waxing lunar conditions produced 36 co-located pairs with correlation of 0.57, RMSE of 0.23, and a slope of 0.74.

In addition to lunar conditions, we also wanted to determine the frequency of AOD retrievals completed above/below a fractional illumination of 0.85. The fractional illumination of 0.85 is a 'critical' threshold as we noticed considerable deviations in terms of reflectance due to waxing or waning lunar phase. Five co-located nighttime AOD retrievals were found with a lunar fractional illumination value of less than 0.85. Seventy-two co-located retrievals using a standard deviation of 0.01 and cloud fraction threshold of 0.2 were completed with lunar fractional illumination values greater than 0.85. VIIRS DNB AOD retrievals completed with a lunar illumination greater than 0.85 for 2017-2019 have a RMS error of 0.23, absolute error of 0.16, and a correlation of 0.67.

| Standard Deviation Threshold | Cloud Fraction Threshold | Data Count | RMSE \| $r^2$ Value |
|---|---|---|---|
| Solar AERONET AOD | | | |
| 0.01 | 0.2 | 61 | 0.36 \| 0.48 |
| | 0.4 | 66 | 0.38 \| 0.51 |
| | 0.6 | 68 | 0.48 \| 0.37 |
| | 0.8 | 74 | 0.53 \| 0.42 |
| 0.02 | 0.2 | 114 | 0.42 \| 0.37 |
| | 0.4 | 118 | 0.43 \| 0.39 |
| | 0.6 | 124 | 0.53 \| 0.27 |
| | 0.8 | 134 | 0.63 \| 0.26 |
| Lunar AERONET AOD | | | |
| 0.01 | 0.2 | 78 | 0.30 \| 0.32 |
| | 0.4 | 82 | 0.29 \| 0.38 |
| | 0.6 | 82 | 0.29 \| 0.46 |
| | 0.8 | 85 | 0.29 \| 0.51 |
| 0.02 | 0.2 | 130 | 0.33 \| 0.35 |
| | 0.4 | 131 | 0.33 \| 0.39 |
| | 0.6 | 136 | 0.34 \| 0.38 |
| | 0.8 | 134 | 0.36 \| 0.40 |
| MODIS AOD | | | |
| 0.01 | 0.2 | 47,021 | 0.25 \| 0.37 |
| | 0.4 | 48,163 | 0.25 \| 0.36 |
| | 0.6 | 49,120 | 0.26 \| 0.36 |
| | 0.8 | 50,158 | 0.26 \| 0.35 |
| 0.02 | 0.2 | 77,590 | 0.31 \| 0.30 |
| | 0.4 | 80,821 | 0.32 \| 0.30 |
| | 0.6 | 81,712 | 0.33 \| 0.29 |
| | 0.8 | 84,847 | 0.36 \| 0.27 |

**Table 1.** Co-located statistical comparisons of daytime (solar) AERONET AOD (0.55 μm), nighttime (lunar) AERONET AOD (0.55 μm), MODIS AOD (0.55 μm) and VIIRS DNB lunar reflectance-based AOD (0.55 μm) retrievals for the study period of 2017 - 2019

### 4.3 Verification of Nighttime City Light AOD Retrievals

As previously mentioned, to verify the AOD retrieved using the city light-based method, AERONET retrieved AODs from the Dakar and Dakar Belair, Senegal stations were co-located and compared. In total, 110 nights of VIIRS DNB city light retrieved AODs are compared against the same day's daytime AERONET AOD and nighttime AERONET retrieved AOD during the study period. Figures 3d and 3e illustrate the comparison of AODs retrieved using the city light AOD retrieval method at 0.7 μm with daytime and nighttime retrieved AODs at 0.675 μm from the AERONET station located in Dakar and Dakar Belair, Senegal for 2017, 2018, and 2019.

Figure 3d and 3e shows the comparison of the city light retrieved AODs and the attributing co-located AERONET AODs for both nighttime and daytime observations for 2017-2019, respectively. Figure 3d and 3e show that the VIIRS DNB city light-based AOD retrievals agreed reasonably well with AERONET AOD values from the stations within the Dakar, Senegal region. The RMS error is on the order of 0.17, absolute error is on the order of 0.14, and the correlation is on the order of 0.80 for daytime comparisons. For the nighttime comparison the RMS error is 0.16, absolute error is 0.11, and correlation is 0.72. Both of which are smaller than VIIRS DNB AOD retrievals from the lunar reflectance-based method. For example, as discussed in the previous section, the RMS and absolute errors are 0.30 and 0.19 (based on the co-located nighttime AOD data), respectively for AOD retrievals (0.55 μm) using the reflected moonlight-based method with a standard deviation threshold of 0.01 and a cloud fraction threshold of 0.2. Thus, it seems, through comparisons with nighttime AERONET data, the city light retrieved AODs performed better than the lunar reflectance-based retrieved AODs.

It is also evident that a low bias exists for the AOD retrievals using the city light method, which is consistent with the findings of the previous Zhang et al., (2019) study. This low bias could be attributed to several factors. First, thick aerosol plumes are present over the Dakar and Dakar Belair, Senegal region for much of the year and thus, the derived cloud- and aerosol-free standard deviation of artificial light sources may not always be representative of an aerosol-free case (Zhang et al., 2019). Additionally, high aerosol loading cases are often misrepresented by the VIIRS cloud product and are thus screened out of the retrieval process.

Additionally, as mentioned earlier, the comparisons to daytime and nighttime AERONET AODs could not be considered 'ground truth' as AERONET has its own issues of representing aerosol optical depth. However, the AODs retrieved from the city light retrieval method do show skill for retrieving aerosol optical depth over artificial light sources.

435

**4.4 VIIRS DNB AOD Lunar Reflectance-Based AOD Retrieval Comparisons with Co-located MODIS AOD Retrievals**

Besides using daytime and nighttime AERONET AOD data, the performance of nighttime VIIRS AOD retrievals from the lunar reflectance-based method were also cross evaluated with daytime MODIS AOD retrievals. Note that there are non-trivial differences between day and nighttime AODs due to the differences in emission, transport, as well as atmospheric 440 conditions. Still, it is to be expected some correlations exist between nighttime AOD values and daytime AOD values for the adjacent day.

As a qualitative comparison given the day and nighttime AOD differences (for illustration only), Figure 4 shows an example of gridded VIIRS and MODIS AOD data from 1 June 2018 and 3 May 2018 for a qualitative comparison. Figure 4e-f shows the gridded MODIS AOD data and Figure 4g-h shows the gridded VIIRS AOD data. As shown in Figure 4a, a dust 445 plume is visible along the western coast of Africa leading to elevated AOD values on 1 June in comparison to the weaker dust plume shown in Figure 4b from 3 May. In both cases, differing dust plumes are found during daytime using MODIS AOD, likely due to diurnal variations in AOD.





**Figure 4.** VIIRS DNB Reflectance, VIIRS M16 Brightness Temperature, MODIS AOD, and VIIRS DNB AOD with a standard deviation threshold of 0.01 and cloud fraction threshold of 0.2 for two dates. Panels (a), c), e), g)) show 01 Jun 2018 while panels (b), d), f), h)) show 03 May 2018.

The comparisons of MODIS (daytime) and VIIRS DNB (nighttime) AOD as functions of cloud screen thresholds are

also included in Table 1. Approximately 1000 times more pairs of MODIS and VIIRS retrievals are available in comparison with the lunar AERONET and VIIRS study and the more stringent the cloud threshold, the lower the RMSE and absolute errors and higher the correlation. The best cloud screen thresholds are found to be the standard deviation value of 0.01 and cloud fraction of 0.2 with a ~45% data loss comparing with the most relaxed cloud screen thresholds (standard deviation value of 0.02 and cloud fraction of 0.8).

Despite the difference in AOD values between day and night, the comparisons between daytime MODIS AOD and nighttime retrieved VIIRS DNB AOD do show some degree of consistency with a correlation within a range of 0.52-0.61. This suggests that the lunar reflectance-based VIIRS DNB AOD retrieval could be used to retrieve dust aerosols over an over-ocean surface, but cloud contamination, lunar phase, and lunar glint are the main uncertainty sources for lunar reflectance-based AOD retrievals. This exercise also suggests that the use of daytime-like LUTs of reflectance is applicable for nighttime AOD retrievals, as long as the downward moon fluxes instead of downward solar fluxes are used in the reflectance calculations.

### 4.5 Verification of AERONET AOD Retrievals and Co-located MODIS AOD Retrievals

Since both daytime AERONET and daytime MODIS DT AOD data were used to intercompare with nighttime aerosol retrievals from this study, it is necessary to investigate how representative daytime AERONET/MODIS AOD retrievals are to the given nighttime retrievals (same day) for the study region. Figure 5a shows the comparison of averaged daytime and nighttime AERONET AOD measurements from the Dakar and Dakar Belair, Senegal stations from 2017-2019. Each data point in Figure 5a represents a pair of averaged daytime AERONET AOD and nighttime AERONET AOD for the same day.





**Figure 5.** Co-located comparisons of a) daytime and nighttime AERONET AOD (0.675 µm), b) nighttime AERONET AOD and MODIS AOD (0.55 µm) retrievals and c) daytime AERONET AOD and MODIS AOD (0.55 µm) retrievals

A correlation of 0.83 and a RMS error of 0.14 are found between the averaged daytime and nighttime AEORNET AODs for the two stations for 2017, 2018, and 2019 indicating that daytime AERONET AOD data has some skill in estimating nighttime AERONET AOD values.

Figure 5b shows the co-located comparison of nighttime AERONET AOD and MODIS AOD over the Dakar and Dakar Belair for 2017-2019. This diurnal comparison shows a correlation of 0.72 and a RMS error of 0.25. Figure 5c shows a similar comparison except for daytime AERONET AOD data with a total of 643 data points, a correlation of 0.90 and an RMS error of 0.16. A considerable outlier can be observed in Figure 5c occurring on 21 June 2018 where a significant plume of Saharan dust leads to a MODIS AOD of 3.42 and an AERONET AOD of 2.26. Figure 5 indicates that both daytime AERONET and MODIS AOD retrievals can be used to assist evaluation of the retrieved nighttime VIIRS DNB AODs.

**4.6 A Study of the Impact of Lunar Model on Data Selection and Cloud Screening**

To convert from VIIRS DNB radiance to reflectance, a lunar model, which estimates TOA downward moon flux under different moon status was used. Thus, the application of using the MT lunar model for this study is explored. For this analysis, a lunar zenith angle threshold of 80° and a satellite zenith angle of 60° was used to screen out potentially unreliable pixels for the lunar reflectance retrieval. Figure 6a shows the cloud-cleared, over-ocean granule average reflectance as a function of lunar fractional illumination (fraction of the moon surface illuminated, with 0 representing new moon and 1 representing full moon) for the MT lunar reflectance model. If aerosol parameters are assumed to not be a function of lunar illumination, reflectance should not see a dependence upon fractional lunar illumination. However, granule mean reflectance increases sharply at fractional lunar illuminations below 0.85 during the waxing phase of the lunar cycle to a physical reflectance above 1.0. Mean reflectance retrieved during the waning phase of the lunar cycle increase above 1 below a lunar fractional illumination threshold of 0.55. Dependencies on the lunar cycle, waxing or waning, can cause differences in mean granule reflectance, primarily due to lunar zenith angle and partially due to the zenith angle of the sensor. Between the two lunar phases, fewer granules are retrieved during the waxing phase of the lunar cycle than that of the waning phase. Ultimately, high spatial variations produced by VIIRS DNB depending on viewing and lunar geometries limit the effectiveness of the lunar reflectance-based AOD retrieval method. Visual inspection of granule reflectance shows increased spatial variation due to decreased signal-to-noise ratios when incident lunar light is limited (e.g., Figure 7).





**Figure 6.** Granule mean reflectance versus lunar phase (fractional illumination) using the MT lunar model for 2017-2019 over the study region (a), and retrieval performance as a function of lunar phase for nighttime (b) and daytime (c) city light and lunar reflectance retrieved AODs.

This exercise highlights limitations in the currently used MT lunar model. It is for this reason, for over ocean nighttime AOD retrievals using VIIRS DNB data, the preferred lunar fractional illumination range is from 0.85 to 1. It is worth noting that the city light-based method derived AOD values are based on the contrast within a given artificial light source and thus is negligibly impacted by uncertainties in lunar models and can be applied to nights with near-zero lunar phase angles. Still, Figure 6a indicates the need for careful qualification of lunar models for nighttime related applications that rely on using moonlight.

In addition to reflectance, we also investigated the performance of the city-light and lunar reflectance-based AODs as a function of lunar fractional illumination for both nighttime (Figure 6b) and daytime (Figure 6c) co-located AODs. To complete this analysis the difference between co-located VIIRS and AERONET AODs from both retrieval methods was determined. In both Figures 6b and 6c, no apparent retrieval bias is found as a function of lunar fractional illumination for both methods. Still, retrievals from the reflectance-based method are only observable at high lunar fractional illumination value range (e.g. lunar fractional illumination > 0.5). In comparison, retrievals from the city light-based method can be found at near 0 in terms of lunar fractional illumination (Figure 6c), indicating a potential benefit of using the city light-based method for nights without moonlight.





**Figure 7.** Four scenes over Dakar with differing lunar fractional illumination. a) VIIRS DNB image for 27 Oct 2018 with a lunar fractional illumination of 0.93, b) VIIRS DNB image for 26 Feb 2018 with a lunar fractional illumination of 0.79, c) VIIRS DNB image for 09 Mar 2018 with a lunar fractional illumination of 0.53 and d) VIIRS DNB image for 01 Dec 2018 with a lunar fractional illumination of 0.38

## 5 Conclusion

Using three years (2017, 2018, & 2019) of VIIRS DNB data and AERONET AOD data over the Dakar and Dakar Belair, Senegal region, nighttime AOD retrievals were performed using both the city light and the lunar reflectance methods. Limitations and issues for both retrieval methods were explored. AOD retrievals from both methods were also inter-compared. This study found that:

1). Both the lunar reflectance-based and city light-based methods have some skills in retrieving nighttime AODs. Validated against ground-based lunar AERONET data, the correlation, RMS error and absolute errors are 0.57, 0.30 and 0.19 for 78 co-located AOD retrievals using the lunar reflectance-based retrieval method for 2017-2019 data (standard deviation threshold of 0.1 and cloud fraction threshold of 0.2; 0.55 μm). Additionally, the correlation, RMS error and absolute errors are 0.72, 0.16, and 0.11 for 34 co-located AOD retrievals using the city light-based method (0.7 μm) for 2017 -2019.

2) This study confirms that if reflectance values from VIIRS DNB data can be obtained, a LUT for reflectance-based daytime AOD retrieval using the VIIRS DNB can be applied to nighttime by normalizing by the lunar albedo integrated over the VIIRS DNB spectral response. For example, retrieval methods developed for using daytime VIIRS DNB data (or a given sensor that is sensible to both day and night lights, capable of observing earth-atmospheric system using single channel, multiple, or hyperspectral channels) can be adapted for AOD retrievals using nighttime VIIRS DNB reflectance data (or reflectance data from the given sensor) with the use of the reflectance-based method.

3) AOD retrievals using the lunar reflectance-based methods are often limited by cloud contamination, moon glint and lunar phase. Since only nights with sufficient moonlight could be used in the retrieval process, 7-9 nights per month or 84-108 nights per year are qualified under this requirement. This limits the application of the lunar reflectance-based AOD retrieval method. In comparison, the city light-based method can be applied at nights with or without moon light. Still, only a very limited number of AOD retrievals (36 in 2017, 36 in 2018, and 38 in 2019) from the city light-based methods were derived. As many nights were excluded due to cloud screening and QA steps.

4) There are still noticeable uncertainties in lunar models that can affect nighttime AOD retrievals using the reflectance-based method, especially for nights with lunar phase angle less than 0.85. Additional refinements in lunar models may be needed in future studies.

5). This study highlights the limitation of both nighttime retrievals and demonstrates hopes for nighttime AOD retrievals using VIIRS DNB data. Perhaps combined retrievals from both methods could provide better data coverage, which deserves further exploration in a future study.

## Code and data availability

The Aqua MODIS and the VIIRS Black Marble data used in this study were obtained from the NASA Level-1 and Atmosphere Archive & Distribution System Distributed Active Archive Center (https://ladsweb.modaps.eosdis.nasa.gov/). The AERONET Level 2 nighttime and daytime datasets used in this study were obtained from the AERONET website (aeronet.gsfc.nasa.gov). The VIIRS data for this study were obtained from the NOAA Comprehensive Large Array-Data Stewardship System (NOAA CLASS; https://www.avl.class.noaa.gov/saa/products/). The SBDART Radiative Transfer model (Ricchiazzi et al., 1998; https://github.com/paulricchiazzi/SBDART) and T-Matrix model (Mishchenko et al., 1996; https://doi.org/10.1016/S0022-4073(98)00008-9 ) are publicly available software.

## Author contributions

Authors J. Zhang and J. W. Marquis designed the study. Author A. Schlief conducted data and image processing for the entire project. Author J. S. Reid provided key ideas and conducted extensive review/revisions of the study. Steve Miller provided the nighttime lunar model necessary to complete the study.

## Competing interests

The authors declare that they have no conflict of interest.


## Acknowledgements

The authors would like to thank the AERONET team for the AERONET data.

## Financial support

This project was/is supported by NASA grants 80NSSC20K1748 and 80NSSC24K1180.

**References**


Cao, C., Bai, Y., Wang, W. and Choi, T.: Radiometric Inter-Consistency of VIIRS DNB on Suomi NPP and NOAA-20 from Observations of Reflected Lunar Lights over Deep Convective Clouds, *Remote Sensing*, **11**, 934, https://doi.org/10.3390/rs11080934, 2019.

Giles, D. M., Sinyuk, A., Sorokin, M. G., Schafer, J. S., Smirnov, A., Slutsker, I., Eck, T. F., Holben, B. N., Lewis, J. R., Campbell, J. R., Welton, E. J., Korkin, S. V. and Lyapustin, A. I.: Advancements in the Aerosol Robotic Network (AERONET) Version 3 database – automated near-real-time quality control algorithm with improved cloud screening for Sun photometer aerosol optical depth (AOD) measurements, *Atmos. Meas. Tech.,* **12**, 169–209, https://doi.org/10.5194/amt-12-169-2019, 2019.

Holben, B. N., Eck, T. F., Slutsker, I., Tanre, D., Buis, J. P., Setzer, A., Vermote, E., Reagan, J. A., Kaufman, Y. J., Nakajima, T., Lavenu, F., Jankowiak, I. and Smirnov, A.: AERONET – A federated instrument network and data archive for aerosol characterization, *Remote Sens. Environ.,* **66**, 1–16, https://doi.org/10.1016/S0034-4257(98)00031-5, 1998.

Jackson, J. M., Liu, H., Laszlo, I., Kondragunta, S., Remer, L. A., Huang, J. and Huang, H.-C.: Suomi-NPP VIIRS aerosol algorithms and data products, *Journal of Geophysical Research: Atmospheres*, **118**, 12673–12689, https://doi.org/10.1002/2013JD020449, 2013.

Johnson, R. S., Zhang, J., Hyer, E. J., Miller, S. D. and Reid, J. S.: Preliminary investigations toward nighttime aerosol optical depth retrievals from the VIIRS Day/Night Band, *Atmos. Meas. Tech.*, **6**, 1245–1255, https://doi.org/10.5194/amt-6-1245-2013, 2013.

Knapp, K. R., Vonder Haar, T. H. and Kaufman, Y. J.: Aerosol optical depth retrieval from GOES-8: Uncertainty study and retrieval validation over South America, *Journal of Geophysical Research*, **107**, 4055, https://doi.org/10.1029/2001JD000505, 2002.

Kopp, T. J., Thomas, W., Heidinger, A. K., Botambekov, D., Frey, R. A., Hutchinson, K. D., Iisager, B. D., Brueske, K. and Reed, B.: The VIIRS Cloud Mask: Progress in the first year of S-NPP toward a common cloud detection scheme, *Journal of Geophysical Research*: *Atmospheres*, **119**, 2441–2456, https://doi.org/10.1002/2013JD020458, 2014.

Levy, R. C., Mattoo, S., Munchak, L. A., Remer, L. A., Sayer, A. M., Patadia, F. and Hsu, N. C.: The Collection 6 MODIS aerosol products over land and ocean, *Atmos. Meas. Tech.*, **6**, 2989–3034, https://doi.org/10.5194/amt-6-2989-2013, 2013.

Martins, J. V., Tanre, D., Remer, L., Kaufman, Y., Mattoo, S. and Levy, R.: MODIS Cloud screening for remote sensing of aerosols over oceans using spatial variability, *Geophys. Res. Lett.*, **29**, MOD4-1-MOD4-4, https://doi.org/10.1029/2001GL013252, 2002.

McHardy, T. M., Zhang, J., Reid, J. S., Miller, S. D., Hyer, E. J. and Kuehn, R. E.: An improved method for retrieving nighttime aerosol optical thickness from the VIIRS Day/Night Band, *Atmos. Meas. Tech.*, **8**, 4773–4783, https://doi.org/10.5194/amt-8-4773-2015, 2015.

Miller, S. D. and Turner, R. E.: A Dynamic Lunar Spectral Irradiance Data Set for NPOESS/VIIRS Day/Night Band Nighttime Environmental Applications, *IEEE Transactions on Geoscience and Remote Sensing*, **47**, 2316–2329, https://doi.org/10.1109/TGRS.2009.2012696, 2009.

Miller, S. D., Straka III, W., Mills, S. P., Elvidge, C. D., Lee, T. F., Solbrig, J., Walther, A., Heidinger, A. K. and Weiss, S. C.: Illuminating the Capabilities of the Suomi National Polar-Orbiting Partnership (NPP) Visible Infrared Imaging Radiometer Suite (VIIRS) Day/Night Band, *Remote Sensing*, **5**, 6717–6766, https://doi.org/10.3390/rs5126717, 2013.

Mischenko, M. I., Travis, L. D., and Mackowski, D. W.: T-Matrix Computations of Light Scattering by Nonspherical Particles: A Review, *Journal of Quantitative Spectroscopy and Radiative Transfer*, **55**, 535-575, https://doi.org/10.1016/0022-4073(96)00002-7, 1996.

Reid, J. S., Gumber, A., Zhang, J., Holz, R. E., Rubin, J. I., Xian, P., Smirnov, A., Eck, T. F., O'Neill, N. T., Levy, R. C., Reid, E. A., Colarco, P. R., Benedetti, A. and Tanaka, T.: A Coupled Evaluation of Operational MODIS and Model Aerosol Products for Maritime Environments Using Sun Photometry: Evaluation of the Fine and Coarse Mode, *Remote Sensing,* **14**, 2978, https://doi.org/10.3390/rs14132978, 2022.

Remer, L. A., Kaufman, Y. J., Tanre, D., Mattoo, S., Chu, D. A., Martins, J. V., Li, R.-R., Ichoku, C., Levy, R. C., Kleidman, R. G., Eck, T. F., Vermote, E. and Holben, B. N.: The MODIS Aerosol Algorithm, Products, and Validation, *Journal of the Atmospheric Sciences*, **62**, 947–973, https://doi.org/10.1175/JAS3385.1, 2005.

Remer, L. A., Mattoo, S., Levy, R. C. and Munchak, L. A.: MODIS 3 km aerosol product: algorithm and global perspective, *Atmos. Meas. Tech*., **6**, 1829–1844, https://doi.org/10.5194/amt-6-1829-2013, 2013.

Ricchiazzi, P., Yang, S., Gautier, C. and Sowle, D.: SBDART: A Research and Teaching Software Tool for Plane-Parallel Radiative Transfer in the Earth's Atmosphere, *Bulletin of the American Meteorological Society*, **79**, 2101–2114, https://doi.org/10.1175/1520-0477(1998)0792.0.CO;2, 1998.

Román, R., González, R., Toledano, C., Barreto, Á., Pérez-Ramírez, D., Benavent-Oltra, J. A., Olmo, F. J., Cachorro, V. E., Alados-Arboledas, L. and de Frutos, Á. M.: Correction of a lunar-irradiance model for aerosol optical depth retrieval and comparison with a star photometer, *Atmos. Meas. Tech*., **13**, 6293–6310, https://doi.org/10.5194/amt-13-6293-2020, 2020.

Schafer, J., Eck, T. F., Slutsker, I., Gupta, P., Sorokin, M., Sinyuk, A. and Smirnov, A.: An Assessment of Lunar Photometry in AERONET, EGUsphere [preprint], https://doi.org/10.5194/egusphere-2026-1506, 2026.

Shi, Y., Zhang, J., Reid, J. S., Holben, B., Hyer, E. J. and Curtis, C.: An analysis of the collection 5 MODIS over-ocean aerosol optical depth product for its implication in aerosol assimilation, *Atmos. Chem. Phys*., **11**, 557–565, https://doi.org/10.5194/acp-11-557-2011, 2011.

Vermote, E. F., Tanre, D., Deuze, J. L., Herman, M. and Morcette, J.-J.: Second Simulation of the Satellite Signal in the Solar Spectrum, 6S: an overview, *IEEE Transactions on Geoscience and Remote Sensing*, **35**, 675–686, https://doi.org/10.1109/36.581987, 1997.

Zeng, X., Shao, X., Qiu, S., Ma, L., Gao, C., and Li, C.: Stability Monitoring of the VIIRS Day/Night Band over Dome C with a Lunar Irradiance Model and BRDF Correction, *Remote Sens.*, **10**, 189, https://doi.org/10.3390/rs10020189, 2018.

Zhang, J., Reid, J. S., Miller, S. D. and Turk, F. J.: Strategy for studying nocturnal aerosol optical depth using artificial lights, *Int. J. Remote Sens*., **29**, 4599–4613, https://doi.org/10.1080/01431160802020528, 2008.

Zhang, J., Reid, J. S., Sorenson, B. T., Miller, S. D., Román, M. O., Wang, Z., Spurr, R. J. D., Jaker, S., Eck, T. F. and Rubin, J. I.: Towards gridded nighttime aerosol optical thickness retrievals using VIIRS day–night band observations over regions with artificial light sources, *Atmos. Meas. Tech*., **18**, 1787–1810, https://doi.org/10.5194/amt-18-1787-2025, 2025.

Zhang, J., Jaker, S. L., Reid, J. S., Miller, S. D., Solbrig, J. and Toth, T. D.: Characterization and application of artificial light sources for nighttime aerosol optical depth retrievals using the Visible Infrared Imager Radiometer Suite Day/Night Band, *Atmos. Meas. Tech*., **12**, 3209–3222, https://doi.org/10.5194/amt-12-3209-2019, 2019.

Zhou, M., Wang, J., Chen, X., Xu, X., Colarco, P., Miller, S. D., Reid, J. S., Kondragunta, S., Giles, D. M. and Holben, B.: Nighttime Smoke Aerosol Optical Depth over U.S. Rural Areas: First Retrieval from VIIRS Moonlight Observations, *Remote Sensing of Environment*, **267**, 112717, https://doi.org/10.1016/j.rse.2021.112717, 2021.