# A Self-Supervised and Distillation-Guided Framework for Robust Cloud-Layer Identification in Multi-Channel Raman Lidar Networks

Weijie Zou[1], Zhenping Yin[1], Tingxin Sun[2], Zhichao Bu[3], Yaru Dai[3], Haofei Wang[4], Longlong Wang[2], Yun He[5,6], Shuangliang Li[1,7], Jiarui Cheng[1], Xuan Wang[1], Siwei Li[1,7], Detlef Müller[1]

[1] School of Remote Sensing and Information Engineering, Wuhan University, Wuhan, China
[2] Hangzhou Institute of Advanced Studies, Zhejiang Normal University, Hangzhou, China
[3] Meteorological Observation Center, China Meteorological Administration, Beijing, China
[4] National Satellite Meteorological Center, China Meteorological Administration, Beijing, China
[5] State Observatory for Atmospheric Remote Sensing, Wuhan, China
[6] School of Earth and Space Science and Technology, Wuhan University, Wuhan, China
[7] Hubei Luojia Laboratory, Wuhan University, Wuhan, China

*Correspondence to*: Zhenping Yin (zp.yin@whu.edu.cn) and Detlef Müller (dgmueller@whu.edu.cn)

**Abstract.** Cloud-layer identification is a key prerequisite for automated ground-based lidar processing, but remains challenging in Raman lidar networks because of incomplete near-range overlap, weak high-level cloud echoes, day–night signal-to-noise ratio (SNR) contrasts, energy fluctuations, and aerosol–cloud ambiguity. Leveraging the China Aerosol Raman Lidar Network (CARLNET), we propose a multi-channel cloud-layer identification framework that operates on 355/532/1064 nm elastic signals and 355/532 nm volume depolarization ratios, reducing dependence on absolute calibration and retrieved optical products. The framework combines an anisotropic encoder–decoder architecture with a three-stage training strategy, including self-supervised pretraining, traditional-algorithm-guided probabilistic distillation, and fine-tuning with limited expert refinement. Strict cross-site and cross-time evaluation on held-out sites shows that, without using any test-site observations during pretraining or test-site annotations during fine-tuning, the framework achieves an F1 score of 0.937. Compared with direct supervised training, the pretrained model yields comparable cloud-base accuracy (MAE: 59.1 versus 55.3 m) while reducing the detectable cloud-top MAE from 94.0 to 82.2 m. It also substantially outperforms the conventional VDE baseline in both cloud-base and cloud-top estimation.~~Strict cross-site and cross-time evaluation on held-out sites shows that, without using any test-site labels, the framework achieves an F1 score of 0.9371 and reduces the mean absolute errors of cloud-base and cloud-top heights to 113 m and 213 m, respectively, outperforming training without pretraining by approximately 50 m and 70 m and the conventional VDE baseline for cloud-top height by about 400 m. A labeled-data-size ablation further shows improved label efficiency, with near-plateau performance reached at about 40 labeled days. Consistency checks against co-located radiosonde moist-layer indications support the realism of identified high-level weak-echo clouds and the robustness of cross-site deployment.~~ Independent evaluation based on a total of 47 matched lidar–radiosonde cases aggregated across the three held-out sites yields a structural consistency rate of 38.3% with

radiosonde-derived moist layers, compared with 34.0% for VDE, providing an independent structural-consistency assessment across the two observing systems. These results demonstrate a cloud-layer identification technique that is transferable across held-out CARLNET sites and reduces dependence on absolute calibration, supporting network-scale Raman lidar processing.~~These results demonstrate a transferable and calibration-decoupled cloud-layer identification technique for network-scale Raman lidar processing.~~

## 1 Introduction

Ground-based lidar systems provide vertically resolved observations of atmospheric aerosols and clouds with high spatial resolution and continuous temporal sampling, making them important instruments for automated atmospheric profiling and long-term network observations (Campbell et al., 2002; Illingworth et al., 2007; Baars et al., 2016; Yin et al., 2020; He et al., 2024; Jing et al., 2025). Multi-wavelength Raman–polarization lidars further provide complementary information from elastic backscatter, Raman signals, and depolarization measurements, which can support ~~aerosol/cloud~~aerosol-cloud discrimination, optical retrieval, and cloud-structure characterization (Sassen, 1991; Zhao et al., 2012; Thorsen et al., 2015; Alizadeh-Choobari and Gharaylou, 2017; Baars et al., 2017). However, the information content of lidar observations is strongly ~~height-dependent~~height-dependent. In the near range, incomplete overlap and the instrument blind zone can make low-level clouds and~~or~~ cloud bases difficult to detect reliably. At higher altitudes, weak backscatter signals, solar background, and increasing molecular-noise contributions~~molecular-noise dominance~~ make optically thin clouds, especially high-level cirrus, vulnerable to missed detections and uncertain boundary placement. These characteristics make robust cloud-layer identification a necessary but non-trivial step in automated lidar processing.

Cloud-layer identification is not merely a binary classification problem. In an operational lidar processing chain, cloud masks and cloud boundaries provide essential constraints for quality control, reference-layer selection, absolute calibration, attenuation correction, and subsequent ~~aerosol/cloud~~aerosol-cloud optical retrievals (Klett, 1981; Fernald, 1984; Wang and Sassen, 2001; Illingworth et al., 2007; Thorsen et al., 2015; Baars et al., 2016, 2017; Yin et al., 2020). If low clouds are missed or poorly characterized in the near-overlap region, the valid retrieval range and attenuation conditions may be misinterpreted. If thin high clouds or subtle multilayer structures remain undetected, the reference region used for calibration may be contaminated, introducing systematic biases into ~~causing systematic biases in~~ calibrated backscatter and extinction products. Conversely, aerosol layers or noise fluctuations misclassified as clouds can unnecessarily interrupt retrievals and reduce data availability. Therefore, a practical cloud-layer identification method should provide stable boundary delineation across both low-level and high-level cloud conditions, while maintaining robustness to noise, attenuation, and aerosol–cloud ambiguity.

These requirements become more demanding for multi-channel lidar networks. Compared with single-site observations, network operations involve stronger heterogeneity in instrument configuration, laser energy, receiver response, maintenance status, background light, aerosol environment, and data completeness. Such factors can alter signal-to-noise ratio (SNR),

relative channel scaling, and the apparent contrast among~~between~~ clouds, aerosols, and clear air (Illingworth et al., 2007; Baars et al., 2016; Yin et al., 2020). As a result, methods that perform well ~~work well~~ at one site or under one observing condition may not transfer directly to other sites without retuning. A network-scale cloud-layer identification algorithm should therefore operate on observables available before fine-grained optical inversion, reduce dependence on absolute calibration, and maintain consistent behavior under cross-site and cross-time changes~~shifts~~.

High, optically thin cirrus clouds are a representative example of these challenges. Cirrus predominantly occur in the upper troposphere and usually have low optical thickness, yet they exert a strong influence on the Earth–atmosphere radiative budget and high-cloud feedback (Hartmann et al., 1992; Pruppacher and Klett, 1997). Their occurrence and vertical structure also show pronounced diurnal, seasonal, and regional variability (Rossow and Schiffer, 1999; Sassen et al., 2008; Noel et al., 2018; Wang et al., 2022; Cordeiro et al., 2025). From the perspective of lidar cloud-layer identification, cirrus are challenging because their weak echoes, diffuse upper boundaries, and frequent occurrence in multilayer scenes require high sensitivity and stable boundary delineation. ~~From the perspective of lidar cloud-layer identification, cirrus are difficult not only because they are radiatively important, but also because their weak echoes, diffuse cloud tops, and frequent multilayer occurrence require high sensitivity and stable boundary preservation.~~ Therefore, cirrus and other weak high-altitude layers provide useful test cases for evaluating whether an identification method can preserve tenuous cloud structures under realistic operational perturbations.

A large body of prior work has developed rule-based and signal-processing approaches for lidar cloud-layer identification (Pal et al., 1992; Wang et al., 2018). Conventional thresholding methods are physically intuitive and computationally efficient, but their decisions are often coupled to signal amplitude, calibration constants, overlap conditions, and atmospheric background. These limitations become particularly important for low-level clouds in the near-range overlap region and for scenes in which strong or humidified aerosol layers coexist with clouds, because aerosol-enhanced echoes can approach the intensity of weak cloud returns and make cloud-aerosol separation ambiguous. Gradient- or change-point-based methods can capture layer transitions to some extent, but they remain sensitive to noise, attenuation, and short-term energy variability. The Value Distribution Equalization (VDE) method, inspired by image histogram equalization, enhances the contrast of elastic lidar echo distributions and identifies cloud and aerosol layers based on the equalized signal structure (Zhao et al., 2014). Nevertheless, because such methods primarily rely on single-channel or empirically transformed signal characteristics, they may still underestimate cloud tops, miss weak high-level clouds, produce unstable boundaries in multilayer scenes, or generate false detections under strong aerosol loading and low-SNR conditions.

Recent advances in machine learning and deep learning have opened new possibilities for lidar cloud-layer identification (Cromwell and Flynn, 2019; Chisari et al., 2024, 2025). However, several limitations remain for operational deployment. First, many existing studies treat lidar time–height observations as generic two-dimensional images, without explicitly considering the physical asymmetry between the temporal and vertical dimensions (Cromwell and Flynn, 2019; Wijnands et al., 2024). Second, some approaches use retrieved backscatter or extinction coefficients as model inputs (Vainiger et al., 2022). Because these retrieved quantities themselves depend on calibration assumptions, reference-layer selection, and

inversion settings, using them as inputs may introduce an implicit coupling between cloud detection and downstream optical retrieval. Third, many models are trained and validated on limited sites, single regions, or within-site random splits, so the training and testing distributions remain highly similar in both site and instrument domains (Cromwell and Flynn, 2019; Fu et al., 2025). Consequently, their true cross-site transferability and deployment~~t~~ robustness ~~risk~~ under network-scale operations are difficult to assess objectively.

At network scale, the central task is therefore to infer stable cloud-layer structures from multi-channel time–height observations under cross-site variations~~shifts~~ in instrument response and background conditions, while avoiding site-specific tuning and reducing reliance on dense manual annotations. To address this need, we propose a self-supervised and distillation-guided cloud-layer identification framework for multi-channel Raman lidar observations. Here, self-supervised learning is used to learn transferable structural representations from unlabeled lidar observations, while knowledge distillation introduces probabilistic guidance from a conventional cloud-detection method as weak supervision. The method operates directly on non-absolutely calibrated elastic signals at 355, 532, and 1064 nm, together with volume depolarization ratios at 355 and 532 nm. Retrieved optical products are not used as direct model inputs, but only as auxiliary information for expert annotation and physical interpretation. This design aims to decouple cloud-layer identification from fine-grained optical inversion and to improve robustness in automated processing chains.

The proposed framework combines a lidar-specific anisotropic encoder–decoder network with a three-stage training strategy. The network applies vertical downsampling while preserving the temporal dimension to account for the different physical roles of height and time. Training proceeds through self-supervised reconstruction pretraining, VDE-guided probabilistic distillation, and supervised fine-tuning with limited expert-refined labels. This design aims to improve annotation efficiency, reduce aerosol-induced false positives, and enhance robustness to SNR variations, energy fluctuations, and cross-site differences.~~The network explicitly accounts for the asymmetric physical meanings of the time and height axes: vertical downsampling enlarges the receptive field for multilayer structure extraction, whereas the temporal dimension is preserved to maintain short-term continuity. Training is conducted in three stages: self-supervised reconstruction pretraining to learn transferable time–height and cross-channel representations, VDE-guided probabilistic distillation to introduce physically motivated weak supervision, and fine-tuning with limited expert-refined labels to improve boundary placement. This strategy is designed to improve label efficiency, suppress aerosol-induced false positives, and enhance robustness to SNR changes, energy fluctuations, and cross-site observation shifts.~~

The methodological contribution of this study lies in the lidar-network-specific integration of self-supervised representation learning, empirical VDE-based probabilistic guidance, and limited expert supervision into a unified workflow for cross-site Raman lidar observations.

We evaluate the framework using observations from the China Aerosol Raman Lidar Network (CARLNET) under strict cross-site and cross-time settings (Shao et al., 2025). Three environmentally distinct sites are used as independent test sites. The evaluation includes pixel-level segmentation metrics, cloud-boundary errors, qualitative analyses under complex echo

设置了格式: 英语(美国)

conditions, and independent consistency checks with co-located radiosonde observations. These experiments assess the model in terms of detection accuracy, boundary stability, multilayer preservation, and applicability to lidar-network processing.~~We evaluate the framework using observations from the China Aerosol Raman Lidar Network (CARLNET) under strict cross-site and cross-time settings (Shao et al., 2025). Three sites representing different environmental backgrounds are held out from both pretraining and supervised training, and continuous observations from these sites are used for independent testing. The evaluation includes pixel-level segmentation metrics, operation-relevant cloud-base and cloud-top height errors, qualitative analyses under complex echo conditions, and independent consistency checks with co-located radiosonde observations. Through these experiments, we assess whether the proposed method improves not only binary cloud detection accuracy, but also boundary stability, multilayer preservation, and operational applicability for lidar-network processing.~~

~~The remainder of this paper is organized as follows. Section 2 describes the CARLNET observations, lidar input channels, auxiliary optical products, manual annotation protocol, radiosonde reference data, and VDE-derived distillation labels. Section 3 presents the proposed anisotropic encoder-decoder framework and the three-stage training strategy. Section 4 reports the cross-site and cross-time validation results, including label-efficiency experiments, cloud-base/cloud-top evaluation, qualitative case studies, and radiosonde-based consistency analyses. Section 5 summarizes the main conclusions, discusses limitations, and outlines future directions for operational deployment and cross-network evaluation.~~

## 2 Lidar observations and dataset

### 2.1 Ground-based lidar network and site selection

The data used in this study were collected from the China Aerosol Raman Lidar Network (CARLNET), an operational ground-based lidar network operated by the China Meteorological Administration. During the study period, CARLNET included 49 deployed multi-wavelength Raman-polarization lidar systems, of which 47 sites provided observations that satisfied the data-quality and completeness requirements of this study. These sites span different climatic and environmental regimes across China, including arid inland regions, monsoon-influenced regions, high-elevation areas, and humid coastal regions (Shao et al., 2025). ~~CARLNET consists of 47 multi-wavelength Raman-polarization lidar sites distributed across different climatic and environmental regimes in China, including arid inland regions, monsoon-influenced regions, high-elevation areas, and humid coastal regions (Shao et al., 2025).~~ As a regional dense-observation network, CARLNET is intended to provide vertically resolved aerosol and cloud observations for regional atmospheric monitoring and to support model evaluation and satellite-based remote-sensing applications. Its spatial coverage also provides diverse observing conditions in terms of aerosol loading, humidity background, solar radiation, cloud occurrence, and instrument operating state, making the dataset suitable for evaluating the robustness and transferability of cloud-layer identification methods under realistic network operations.~~This spatial coverage provides diverse observing conditions in terms of aerosol loading,~~

~~humidity background, solar radiation, cloud occurrence, and instrument operating state, making the dataset suitable for evaluating the robustness and transferability of cloud-layer identification methods under realistic network operations.~~

In this study, the CARLNET observations are used primarily for method development and cross-site validation rather than for climatological statistics. Observations from 2024 are used as the main data source for self-supervised representation learning, VDE-guided probabilistic distillation, and sampling of expert-refined labels. This design allows the model to learn from a wide range of operational conditions, including day–night background differences, signal-to-noise ratio variations, laser-energy fluctuations, aerosol–cloud coexistence, and intermittent data-quality changes. All data used for model training and validation are processed under the same preprocessing protocol described below.

To assess cross-site and cross-time generalization, three sites with contrasting environmental backgrounds are selected as independent test sites: CMA station ID 51628 (Aksu), located in a temperate continental arid region; 53845 (Yan'an), located in a temperate monsoon-influenced region; and 58847 (Fuzhou), located in a subtropical humid coastal region. These sites differ substantially in aerosol environment, moisture conditions, background radiation, and cloud characteristics, and therefore provide a high-contrast benchmark for network-scale deployment. The three sites are excluded from both the self-supervised/distillation stages and the supervised fine-tuning stage. Unless otherwise specified, evaluation uses continuous observations from these held-out sites in January 2025. A continuous fixed-period test set was chosen to provide an event-independent operational evaluation while preserving natural variations in cloud conditions, aerosol background, daytime–nighttime SNR, and instrument status. Using the same period at all three sites also enables a consistent cross-site comparison.

~~To rigorously assess cross-site and cross-time generalization, three sites with contrasting environmental backgrounds are selected as independent test sites: 51628 (Aksu), located in a temperate continental arid region; 53845 (Yan'an), located in a temperate monsoon-influenced region; and 58847 (Fuzhou), located in a subtropical humid coastal region. These sites differ substantially in aerosol environment, moisture conditions, background radiation, and cloud characteristics, and therefore provide a high-contrast benchmark for network-scale deployment. Importantly, these three sites are excluded from both the self-supervised/distillation stages and the supervised fine-tuning stage. Unless otherwise specified, all model evaluations are conducted using continuous observations from these held-out sites in January 2025, ensuring that the test data are independent of the training data in both site and time.~~

The remaining 44 sites are used as training and validation sources. This split is designed to evaluate whether the proposed framework can learn transferable cloud-layer representations from heterogeneous network observations and apply them to unseen sites without site-specific retuning. Fig.~~Figure~~ 1 shows the spatial distribution of the CARLNET sites and the train–test split used in this study.





**Figure 1. Spatial distribution of CARLNET sites and the schematic train–test split used in this study. Blue circles denote training/validation sites (n = 44), and red triangles denote the three independent test sites (n = 3): 51628 (Aksu), 53845 (Yan'an), and 58847 (Fuzhou). The background shows topographic elevation (km).**

### 2.2 Lidar instrumentation and observation configuration

Ground-based lidar systems deployed in CARLNET mainly come from two vendors. Despite vendor differences, all systems are designed and integrated under unified operational technical specifications, and each site performs routine maintenance and periodic calibration following operational protocols.

The lidar used in this study is a three-wavelength polarization Raman lidar system emitting at 355 nm (pulse energy ≥ 0.6 mJ), 532 nm (≥ 1.5 mJ), and 1064 nm (≥ 1.0 mJ), with a repetition rate of 1000 Hz. The eight receiving channels comprise the parallel- and cross-polarized elastic channels at 355 nm, the 387 nm nitrogen Raman channel, the 407 nm water-vapor Raman channel, the parallel- and cross-polarized elastic channels at 532 nm, the 607 nm nitrogen Raman channel, and the total elastic channel at 1064 nm.~~And it has eight receiving channels, 355 nm parallel and vertical channels, 386 nm and 407 Raman channels, 532 nm parallel and vertical channels, and 1064 nm elastic channel.~~ Each channel incorporates a ~~photon counting~~photon-counting digitizer to convert received photons into digital signals~~convert backscatter light into photon counts~~. The system has a vertical resolution of 15 m, with a complete overlap height starting from approximately 500 m. For operational processing, raw observations are resampled to a 5 min temporal resolution to balance temporal continuity, signal stability, and computational efficiency for automated cloud-layer identification. Routine maintenance and periodic


calibration are conducted according to unified CARLNET operational protocols, including polarization-gain calibration. Further details are provided by Shao et al. (2025).~~Details about the lidar network and lidar instrument specifications can be found in Shao et al. (2025).~~

Since cloud-layer identification is a prerequisite for subsequent instrument calibration and optical retrieval, we mainly use non-absolutely-calibrated observables as model input features, including total elastic signals at 355, 532, and 1064 nm, together with linear volume depolarization ratios (VDR) at 355 and 532 nm.~~including the elastic signals from the 355-nm elastic channel, 532-nm parallel channel, and 1064-nm parallel channel, together with linear Volume Depolarization Ratio (VDR) at 355 and 532 nm. The elastic-channel signals are preprocessed with trigger-delay correction, background subtraction, and range correction.~~

The volume depolarization ratio is defined as

$$\mathrm{VDR} = \mathrm{PGR} \times \frac{P_\mathrm{s}}{P_\mathrm{p}}, \tag{1}$$

where $P_\mathrm{s}$ and $P_\mathrm{p}$ denote the elastic echo signals measured in the cross-polarized and co-polarized channels, respectively, and PGR is the polarization gain ratio provided by each site after calibration.







**Figure 2.** Example of multi-wavelength lidar observations, retrieved optical properties, and cloud-layer identification at Site 52203 on 24 December 2024 (12:00–24:00 UTC). Panels (a–c) show the range-corrected elastic signals at 355, 532, and 1064 nm (displayed in logarithmic scale). Panels (d–e) show the volume depolarization ratio (VDR) at 355 and 532 nm. Panels (f–h) present the retrieved particle backscatter coefficients (\(\beta_p\)) at 355, 532, and 1064 nm, and panels (i–j) present the retrieved particle extinction coefficients (\(\alpha_p\)) at 355 and 532 nm. Panels (k–l) show the retrieved particle depolarization ratio (PDR) at 355 and 532 nm. These retrieved optical products provide auxiliary physical information for aerosol–cloud discrimination and expert annotation. Panel (m) shows the manually refined cloud/aerosol/clear-sky mask, and panel (n) shows the discretized cloud probability derived from the VDE method, which is used as the distillation reference. ~~Example of multi-wavelength lidar observations, retrieved optical properties, and cloud-layer identification at Site 52203 on 24 December 2024 (12:00–24:00 UTC). Panels (a–c) show elastic backscatter signals at 355, 532, and 1064 nm elastic channel (range-squared corrected and displayed in logarithmic scale). Panels (d–e) show the volume depolarization ratio (VDR) at 355 and 532 nm. Panels (f–h) show retrieved aerosol/cloud backscatter coefficients β at 355, 532, and 1064 nm elastic channel. Panels (i–j) show retrieved extinction coefficients α at 355 and 532 nm. Panels (k–l) show retrieved particle depolarization ratio (PDR) at 355 and 532 nm. These retrieved optical products provide auxiliary physical constraints to enhance cloud–aerosol discrimination. Panel (m) shows the manually refined cloud/aerosol/clear-sky mask, and panel (n) shows the discretized cloud decision produced by the conventional VDE method, used for comparison and as a distillation reference. As illustrated in (n), VDE captures the major cloud structures but tends to yield persistently elevated cloud-probability levels in the lower–middle troposphere under strong aerosol loading, reflecting intrinsic limitations of empirical-threshold-driven cloud/non-cloud decisions.~~

### 2.3 Auxiliary optical products for annotation and physical interpretation

Although the proposed model is designed to operate directly on observation-level elastic and polarization quantities, expert annotation of cloud, aerosol, and clear-sky regions benefits from additional physical information. Elastic echo intensity alone can be ambiguous: strong aerosol layers may produce echoes comparable to weak clouds, low-level liquid or mixed-phase clouds may cause strong attenuation above the cloud, and high-level optically thin clouds may only appear as weak and diffuse structures. Therefore, in addition to the model input channels, we generate auxiliary optical products to support manual interpretation and to provide a physically consistent context for evaluating cloud–aerosol discrimination.

The auxiliary products include multi-wavelength particle backscatter coefficients ($\beta$), particle extinction coefficients ($\alpha$), and particle depolarization ratio (PDR). When the Raman channels have sufficient signal-to-noise ratios, particle backscatter and extinction coefficients are retrieved using Raman lidar methods (Ansmann et al., 1990). Raman extinction is derived from the Raman signal profile without assuming a lidar ratio, whereas Raman backscatter is obtained from the elastic-to-Raman signal ratio using molecular normalization. PDR is derived from the polarization measurements together with the corresponding molecular and particle backscatter separation. However, Raman-based retrievals can become unstable under low-SNR conditions, particularly during daytime observations. When reliable Raman retrievals are unavailable, the Fernald method is applied to estimate particle backscatter and extinction using an assumed lidar ratio (Fernald, 1984). For the Fernald retrieval, a clear-sky reference region is manually selected, typically within 6–10 km, where molecular scattering dominates and cloud contamination is absent. The resulting elastic-signal-based estimates remain sensitive to the assumed lidar ratio and reference-region selection (Klett, 1981; Fernald, 1984) and are therefore used only as auxiliary information for expert interpretation rather than as deterministic annotation criteria.

It is important to emphasize that these retrieved optical products are not used as input channels during any training or inference stage of the deep learning model. They are used only for expert annotation, sample inspection, qualitative analysis, and physical interpretation. This separation ensures that cloud-layer identification can be performed before fine-grained optical inversion in the automated processing chain, rather than depending on inversion products that themselves require cloud screening, reference-layer selection, and calibration assumptions.

~~The auxiliary products include multi-wavelength backscatter coefficients $\beta$, extinction coefficients $\alpha$, and particle depolarization ratio (PDR). When Raman signals have sufficient signal-to-noise ratio, these products are retrieved using Raman lidar methods (Ansmann et al., 1990). However, Raman signals can have low SNR, especially during daytime, which may lead to large fluctuations in retrieved extinction coefficients. To extend the temporal availability of optical references, when Raman retrieval is unavailable or unstable, the Fernald method is used to retrieve backscatter coefficients and to estimate extinction coefficients under an assumed lidar ratio (Fernald, 1984). This Fernald-based estimate is hypothesis-driven and generally less reliable than Raman retrieval, but it provides useful auxiliary information for interpreting cloud structure, attenuation behavior, and aerosol–cloud transitions.~~

带格式的: 无项目符号或编号

~~It is important to emphasize that these retrieved optical products are not used as input channels in any training or inference stage of the deep learning model. They are used only for expert annotation, sample inspection, qualitative analysis, and physical interpretation. This separation is essential for the purpose of this study: the cloud-layer identification model should operate before fine-grained optical inversion in the automated processing chain, rather than depend on inversion products that themselves require cloud screening, reference-layer selection, and calibration assumptions.~~

Fig.~~Figure~~ 2 illustrates the complementary roles of observation-level inputs and auxiliary optical products under a typical cloud–~~–~~aerosol coexistence case. Elastic signals indicate scattering structures but may be ambiguous under strong aerosol loading or weak-cloud conditions. VDR and PDR provide information on particle nonsphericity and are particularly useful for identifying ice clouds and dust-like aerosol layers. Retrieved β and α further help characterize optical thickness, attenuation, and wavelength dependence. Together, these quantities provide a multi-physics background for expert annotation and for interpreting model behavior, while the actual model inputs remain limited to elastic signals and VDR.

Although polarization measurements require gain-ratio calibration, VDR is generally less affected by absolute energy fluctuations than elastic intensity. Together with multi-wavelength observations, the proposed multi-channel representation reduces sensitivity to instrument-specific amplitude variations and improves robustness under heterogeneous operational conditions.

### 2.4 Manual annotation and label construction

Manual annotations are produced based on a joint interpretation of multi-channel lidar observations and retrieved optical products. We stress that cloud–~~–~~aerosol discrimination is not purely an "intensity saliency" problem: strong aerosol layers can in some cases yield echo intensities comparable to thin clouds, while strong attenuation in low-level water clouds or mixed-phase clouds can suppress returns above the cloud, making cloud boundaries and multilayer structures more difficult to identify (Mylonaki et al., 2021; Floutsi et al., 2023). This motivates the use of multi-channel information and representation learning strategies to improve robustness.~~This is one motivation for incorporating multi-channel information and a pretraining strategy to enhance robustness.~~

During annotation, auxiliary optical products are used as supporting physical references rather than deterministic criteria. The final labels are not generated by thresholding retrieved optical quantities, but by joint interpretation of multi-channel elastic signals, polarization information, temporal continuity, and auxiliary retrieval products. Therefore, uncertainties associated with individual retrieval methods, including Fernald-based estimates under low Raman signal-to-noise conditions, are mitigated through multi-source interpretation.

During annotation, clouds, aerosols, and clear sky are distinguished mainly according to the following criteria:~~During annotation, clouds, aerosols, and clear sky are distinguished mainly according to the following criteria~~Manual annotation is ~~independently performed by two experts with experience in lidar operations and research, followed by two rounds of cross-checking and sampled re-inspection to ensure consistency.~~

~~:~~

i. ~~(i)~~ High-level cirrus: clear layered structures in elastic signals, with typically higher VDR and PDR (e.g., >0.1) (Voudouri et al., 2020). For example, the cirrus layer in Fig. 2m at 6–8 km exhibits both enhanced backscatter and elevated particle depolarization.

ii. ~~(ii)~~ Low-level water clouds / mixed-phase clouds: often accompanied by pronounced signal attenuation and high backscatter levels; retrieved backscatter coefficients can approach or exceed 0.01 $km^{-1}sr^{-1}$ ~~$km^{-1}sr^{-1}$~~, with weak wavelength dependence (Kalesse-Los et al., 2022). ~~For example, the cirrus layer in Figure 2m at 6–8 km exhibits both enhanced backscatter and elevated particle depolarization.~~

iii. ~~(iii)~~ Strong aerosol layers (humid haze/urban pollution): typically characterized by lower depolarization ratios (e.g., ~~Figure~~ Fig. 2d ~~–~~e at 0~~–~~2 km), evident spectral differences (color ratio deviating from 1), stronger wavelength dependence, and often larger lidar ratios (Floutsi et al., 2023).

iv. ~~(iv)~~ Dust aerosols: usually show higher depolarization ratios but relatively lower backscatter coefficients. Their polarization signatures can partially resemble high-level cirrus, which may cause confusion if relying on volume depolarization ratio alone. Compared with cirrus, dust layers often exhibit stronger spatial coherence and more stable layered structures, with slower temporal variation in layer altitude; these properties provide auxiliary cues (Mona et al., 2012).

Manual annotation was performed by multiple experts with experience in lidar operations and research. Approximately 10% of the annotated samples were independently re-examined by multiple experts for consistency assessment, and discrepancies were resolved through expert discussion and consensus. For a representative subset of 15 site-days, the pixel-wise agreement between expert annotations reached an IoU of 95.8%, indicating high consistency of the manual labels. ~~Manual annotation is independently performed by two experts with experience in lidar operations and research, followed by two rounds of cross-checking and sampled re-inspection to ensure consistency.~~

The dataset covers year-long observations from 47 sites in 2024, totaling approximately 15,000 site-days, with substantial spatial coverage and temporal continuity. Training data are obtained via sampling: approximately 150 site-days are sampled from 2024 observations of training sites, excluding the independent test sites. Test data consist of continuous observations from the three independent test sites in January 2025, totaling about 88 days, for strict cross-site and cross-time evaluation.

### 2.5 Radiosonde observations and cloud identification

To provide independent observational validation of cloud-layer identification results, we incorporate co-located radiosonde measurements. Radiosondes are launched daily at 00:00 and 12:00 UTC. The radiosonde station is within 100 m of the lidar site and is thus considered co-located. The radiosonde provides profiles of temperature, relative humidity, and pressure from

带格式的: 列表段落, 缩进: 悬挂缩进: 0.5 字符, 左 1.5 字符, 首行缩进: -0.5 字符, 编号 + 级别: 1 + 编号样式: i, ii, iii, … + 起始编号: 1 + 对齐方式: 右侧 + 对齐位置: 2.54 厘米 + 缩进位置: 3.28 厘米

the surface up to about 16 km, with an average ascent rate of approximately 400 m/min. The radiosonde measurements are recorded at a temporal resolution of 1 s. The corresponding vertical sampling distance depends on the instantaneous ascent velocity of the radiosonde and therefore varies with height.

**Table 1. Relative-humidity thresholds used for radiosonde-based cloud identification following Zhang et al. (2016).**

| Altitude (km)~~Altitude / km~~ | RH | | |
|---|---|---|---|
| | Min-RH (%) | Max-RH (%) | Inter-RH (%) |
| 0 – 2 | 90% – 92% | 93% – 95% | 82% – 84% |
| 2 – 6 | 88 – % – 90% | 90% – 93% | 78% – 80% |
| 6 – 12 | 80% – 88% | 80% – 90% | 70% – 78% |
| > 12 | 75% | 80% | 70% |

We apply an altitude-dependent relative-humidity thresholding method to identify humidity-defined moist layers associated with cloud structures.~~We apply a relative-humidity thresholding method to identify radiosonde cloud boundaries.~~ Specifically, following the altitude-dependent RH threshold scheme proposed by Zhang et al. (2016), different minimum, maximum, and intermediate RH thresholds are used for different altitude ranges (Table 1). Based on this scheme, we adjust the order of moist-layer identification and merging steps to avoid prematurely discarding thin layers before merging. The processing steps include:

(i) remove moist layers with base height < 120 m and cloud geometrical thickness (CGT) < 400 m;

(ii) identify moist layers using the altitude-dependent minimum RH threshold;

(iii) merge adjacent moist layers when their separation is < 300 m;

(iv) remove moist layers with CGT < 30 m.

Radiosondes may drift horizontally by up to approximately 30 km during ascent and therefore cannot be regarded as instantaneous single-column observations. Consequently, radiosonde-derived moist layers are used only as an independent consistency reference rather than as direct supervision or absolute ground truth~~It should be noted that radiosondes drift horizontally during ascent due to winds, which can be as large as 30 km. Therefore, the observations cannot be mapped to an instantaneous single-column profile at a specific time. .Therefore, radiosonde-based cloud identification is used only as an independent trend-level reference for external consistency checks of lidar-based cloud-layer identification, rather than as direct supervision.~~

带格式的: 行距: 单倍行距
格式化表格
带格式的: 行距: 单倍行距
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
带格式的: 行距: 单倍行距
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
带格式的: 行距: 单倍行距
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
带格式的: 行距: 单倍行距

### 2.6 VDE-based cloud-layer identification product

To improve model generalization across sites and observing conditions, we introduce a conventional cloud-layer identification approach based on elastic lidar echoes—the VDE algorithm (Zhao et al., 2014)—to construct the teacher labels required for the distillation stage. This can be viewed as a single-source, experience-based information stream.

VDE is a physics-informed, rule-based method for cloud–aerosol discrimination, originally developed for cloud-layer identification from single-channel elastic lidar observations. It operates directly on elastic echoes without range-squared correction. Rather than applying a fixed intensity threshold, VDE performs a histogram equalization-like transformation on the vertical distribution of echo intensity, enhancing structural differences and highlighting potential feature layers, as shown in Figure Fig. 2n.

Based on the equalized signal, VDE analyzes salient layers and combines (i) local peak characteristics and (ii) height-dependent attenuation behavior to distinguish clouds from aerosols. Typically, clouds manifest as prominent intensity peaks accompanied by rapid signal decay, especially for optically thick water clouds or low-level clouds. In contrast, aerosol layers tend to show smoother intensity variations and often lack the combined signature of strong peaks and sharp attenuation.

Accordingly, VDE classifies salient layers in each vertical profile: layers with distinct peaks and rapid attenuation are treated as positive samples (cloud), whereas layers with smooth variations and lacking pronounced attenuation are treated as negative samples (aerosol or clear sky). This procedure provides an empirical discrimination mechanism with clear physical intuition.

Building on the conventional binary VDE output, Zou et al. (2024) further extended the decision from hard classification to a discretized cloud-probability representation, where different probability levels are assigned according to peak saliency and attenuation characteristics. This representation partially preserves the uncertainty of cloud/non-cloud decisions and provides a suitable form of weak supervisory information.~~Building on the conventional binary VDE output, Zou et al. (2024) further extended the decision from hard classification to a discretized cloud-probability representation, where different probability levels are assigned based on peak saliency and attenuation strength, thereby partially preserving uncertainty in cloud/non-cloud decisions.~~

As shown in Fig. 2n, VDE identifies the major cloud structures but may produce elevated cloud-probability levels in the lower-middle troposphere under strong aerosol loading, reflecting the limitations of empirical cloud–aerosol discrimination under complex conditions. In this study, the VDE-derived cloud-probability product is not used as the final cloud-layer identification result; instead, it is used only as weak supervision during the distillation stage. Specifically, VDE is independently applied to the total elastic signals at 355, 532, and 1064 nm, and the cloud-probability outputs from the three wavelengths are averaged to generate the final soft supervisory target. This target provides physically informed guidance for the deep learning model after self-supervised pretraining, encouraging consistency with traditional lidar-based decision logic.

~~As shown in Figure 2n, VDE identifies the main cloud structures but tends to generate persistently elevated cloud-probability levels in the lower–middle troposphere under strong aerosol loading, revealing inherent limitations of empirical-threshold-~~

~~driven cloud–aerosol discrimination. In this study, the VDE-derived cloud-probability product is not used as the final cloud-layer identification result; instead, it is used only as weak supervision for distillation during training. Specifically, we run VDE independently on the elastic channels at 355, 532, and 1064 nm elastic channel, and then average the cloud-probability outputs across the three channels to form the final distillation soft label. This soft label guides the deep model—after self-supervised pretraining—to learn structural representations consistent with traditional physics-informed decision logic.~~

We emphasize that VDE is used only during the distillation stage. It is not used in final inference or performance evaluation. Its role is to provide an auxiliary constraint rooted in physical experience, rather than to replace manual annotations or the deep learning model itself.

## 3 Methodology

This section presents the proposed cloud-layer identification method and its training strategy. Motivated by (i) the continuous structural patterns of ground-based lidar observations in the time–height domain and (ii) the pronounced observation shifts across sites and instruments, we model multi-channel lidar measurements as a multi-channel 2D time–height array. We then develop an anisotropic encoder–decoder network together with a three-stage training framework to enable stable identification of cloud-layer structures and to improve cross-site generalization. The overall pipeline is illustrated in ~~Figure~~ Fig. 3. Using multi-channel time–height observations as input, the model is trained under a unified architecture in three consecutive phases: self-supervised reconstruction pretraining, distillation with VDE teacher signals, and fine-tuning with manually refined labels.

This section focuses on problem formulation, network design, and the stage-wise training strategy. Implementation details, hyperparameter settings, and additional experiments are deferred to the Appendix to ensure reproducibility.








**Figure 3. Schematic of the cloud-layer identification network based on multi-channel lidar observations and the three-stage training framework.** The three dimensions of [5,10,1056] and other vectors correspond to observation channels, temporal profiles, and resampled vertical bins, respectively.

### 3.1 Problem formulation and input representation

Ground-based lidar actively probes the atmosphere in a time–height profiling manner, featuring high vertical resolution and



带格式的: 居中

strong temporal continuity. Unlike conventional 2D remote-sensing imagery, the time and height axes are physically asymmetric: the height dimension corresponds to the true vertical atmospheric structure, whereas the time dimension reflects the temporal evolution of atmospheric processes. Therefore, simply treating lidar measurements as an isotropic 2D image and modeling them uniformly is insufficient to capture the underlying physical characteristics.

In this study, multi-wavelength total elastic signals at 355, 532, and 1064 nm and VDR at 355 and 532 nm are stacked along the channel dimension to form a multi-channel time–height input tensor.~~In this study, multi-wavelength elastic signals (355, 532, and 1064 nm elastic channel) and VDR at 355 and 532 nm are stacked along the channel dimension to form a multi-channel time–height input tensor.~~ The model outputs a corresponding binary cloud-layer mask, which marks echo regions associated with cloud processes.

Along the time dimension, the model does not make decisions from a single profile in isolation.~~ Instead, it uses a finite number of adjacent profiles as a joint input.~~ Instead, each sample consists of 10 consecutive lidar profiles with a temporal resolution of 5 min, corresponding to a 50-min local observation window, which is comparable to the timescale of many cloud-layer structural variations while remaining robust to operational interruptions and missing observations.~~Specifically, each sample consists of 10 consecutive lidar profiles with a temporal resolution of 5 min. This design aims to incorporate local temporal continuity while avoiding the non-stationarity introduced by overly long temporal windows.~~

The resulting cloud-layer masks are further converted into operation-relevant geometric products, including cloud-base and cloud-top heights, for the validation analyses in Sect. 4.

### 3.2 Anisotropic encoder–decoder network architecture

To account for the intrinsic physical asymmetry between the temporal and vertical dimensions of ground-based lidar observations, we design an anisotropic encoder–decoder network based on a U-Net architecture (Fig. 3). In this framework, the encoder extracts hierarchical representations from the time–height input, while the decoder progressively restores spatial resolution to generate pixel-level cloud-layer masks. Unlike conventional image segmentation networks that treat two spatial dimensions equivalently, the proposed architecture explicitly distinguishes temporal continuity from vertical atmospheric structure~~To explicitly reflect the asymmetric physical meaning of time and height in ground-based lidar observations, we design an anisotropic encoder–decoder architecture (Figure 3) to fuse multi-channel measurements and extract dominant spatiotemporal features for cloud-layer identification. Different from approaches that treat the time–height signal as an isotropic 2D image, our network explicitly differentiates modeling along the two dimensions~~.

Before entering the network, vertical resampling is applied to adapt the representation scale to the altitude-dependent characteristics of lidar observations. The original lidar profiles contain 2048 vertical range gates with a vertical resolution of 15 m. The vertical dimension is divided into three regions: the lower atmosphere (range gate <800, approximately 0–12 km), the middle atmosphere (800 ≤ range gate <1600, approximately 12–24 km), and the upper observation range (range gate ≥1600, approximately 24–30 km). The lower region retains relatively fine vertical sampling to preserve sharp cloud

boundaries and aerosol–cloud transition structures, whereas stronger resampling is applied to the middle and upper regions with factors of 4 and 8, respectively, to reduce redundant vertical information and enlarge the effective representation scale for weaker high-altitude structures. After vertical resampling, the input tensor is transformed from the original [5,10,2048] representation to the network input size of [5,10,1056], where the three dimensions correspond to observation channels, temporal profiles, and resampled vertical bins, respectively.

The anisotropic feature extraction is further achieved through direction-specific convolutional operations. Kernel sizes are defined as temporal dimension × vertical dimension. Temporal continuity features are extracted using 3×1, which integrate information along the time axis while preserving vertical resolution. In contrast, vertical atmospheric structures are modeled using height-oriented kernels. Specifically, the stem layer and the final decoder stage employ 1×3 kernels to preserve fine vertical details during feature transformation, whereas the remaining encoder layers, bottleneck layer, and decoder layers use 1×5 kernels to increase the vertical receptive field and capture multilayer cloud structures. This factorized anisotropic convolution design enables the network to emphasize vertically coherent atmospheric structures while maintaining local temporal continuity.

No pooling is applied along the temporal dimension throughout the network. The temporal dimension is therefore preserved during feature extraction, allowing the model to utilize short-term continuity information from the 10 consecutive lidar profiles without relying on long temporal sequences. This design improves robustness under operational conditions where missing observations, precipitation interference, strong background radiation, or instrument-state variations may interrupt continuous lidar measurements.

Between the encoder and decoder, skip connections perform joint fusion across scales and channels, transferring multi-scale wavelength- and polarization-dependent features from the encoder to the decoder for recovering fine-grained cloud boundaries (Ronneberger et al., 2015). In addition, gated skip connections are introduced (Oktay et al., 2018; Jiang et al., 2021) to adaptively regulate the transferred features, thereby controlling the contribution of multi-scale and multi-channel information under varying signal-to-noise ratios (SNRs) and cloud–aerosol ambiguity conditions. Specifically, the three gated skip connections employ 1×5 height-oriented kernels to selectively weight vertical feature information passed from the encoder to the decoder. This mechanism enables the network to retain informative atmospheric structures while reducing the influence of less reliable features under weak-signal conditions or complex aerosol–cloud coexistence scenarios.

This design preserves the multi-scale representation capability of the U-Net architecture while explicitly supporting multi-channel feature fusion tailored for network-scale lidar observations. By integrating vertical structural information, local temporal continuity, and adaptive feature selection, the proposed architecture is designed to improve the robustness of cloud-layer identification under heterogeneous operational lidar conditions.

~~Along the height dimension, the network performs progressive downsampling and feature compression to enlarge the vertical receptive field and enhance representation of multilayer cloud structures and weak signals at high altitudes. Along the time dimension, no downsampling is applied; instead, only limited-scale convolutions are used to extract local temporal-~~

~~consistency features, reducing reliance on long uninterrupted time series. This design helps preserve the continuity of cloud-layer structures while decreasing sensitivity to the completeness of temporal observations.~~

~~In the time dimension, the model takes 10 consecutive lidar profiles as a joint input to provide local temporal context for cloud-layer identification. The objective is to capture stable structural patterns on short time scales rather than to explicitly model the full temporal dynamics of cloud evolution. On the one hand, cloud-layer structures often remain coherent within minutes; on the other hand, operational interruptions caused by precipitation, strong background light, or instrument-state changes are common, and a short temporal window improves effective sample utilization and practical applicability.~~

~~Between the encoder and decoder, skip connections perform joint fusion across scales and channels, propagating wavelength-/polarization-specific cues from the encoder to the decoder for recovering fine-grained cloud boundaries (Ronneberger et al., 2015; Oktay et al., 2018). In addition, we introduce gated skip connections (Jiang et al., 2021) to adaptively weight the transferred features, thereby regulating the contribution of multi-scale and multi-channel information under varying SNR and cloud–aerosol ambiguity. This design preserves the multi-scale representation strength of U-Net while explicitly supporting multi-channel feature fusion tailored for network-scale lidar operations, where high vertical resolution, local temporal continuity, and cross-site observation shifts must be handled simultaneously.~~

### 3.3 Three-stage training strategy

To improve stability and generalization under limited manual annotations, we adopt a three-stage training strategy (Fig. 3). The first two stages constitute a label-efficient representation learning phase, whereas the final stage performs supervised adaptation using expert-refined annotations. In this study, the term “pretraining” refers to the first two stages, including self-supervised representation learning (Stage 1) and VDE-guided probabilistic distillation (Stage 2). Together, these two stages constitute a physics-guided pretraining phase before supervised fine-tuning with expert annotations (Stage 3).

Stage 1 employs a self-supervised reconstruction task based on channel-wise and profile-wise masking, guiding the model to learn spatiotemporally coherent structures and cross-channel consistency from lidar echoes without requiring manual cloud labels (Vincent et al., 2008; He et al., 2021).

Stage 2 performs VDE-guided probabilistic distillation to further regularize the cloud/non-cloud decision boundary learned from the self-supervised representation. Specifically, discretized cloud-probability levels generated by the conventional VDE algorithm (Zhao et al., 2014; Zou et al., 2024) are used as probabilistic supervisory information rather than absolute ground truth labels, and the segmentation head is optimized on top of the Stage-1 representation. Compared with binary decisions, probability-based guidance provides an uncertainty-aware signal that stabilizes learning under ambiguous conditions, including weak echoes, strong background noise, and aerosol–cloud overlap. In addition, aerosol-labeled regions are explicitly included as non-cloud constraints to penalize aerosol-induced false positives and prevent overly permissive cloud decisions. Overall, Stage 2 introduces physically informed guidance while limiting dependence on dense manual annotations. Because the VDE-derived probabilities are used as weak supervision during Stage 2, systematic errors in the empirical teacher, such as elevated cloud probabilities under strong aerosol loading, may be partially inherited by the student model.

The use of soft probabilistic targets, multi-wavelength averaging, explicit aerosol-suppression constraints, and subsequent fine-tuning with expert annotations is intended to reduce this influence, but cannot eliminate it ~~completely~~. VDE-guided distillation therefore represents a trade-off between improved label efficiency and the potential inheritance of empirical-rule limitations.

Stage 3 fine-tunes the model using a small set of manually refined cloud-layer masks. This stage further improves boundary delineation accuracy and cross-site generalization while preserving the stable structural representations learned in the previous stages.~~To improve stability and generalization under limited manual annotations, we adopt a three-stage training strategy (Figure 3).~~

~~Stage 1 employs a self-supervised reconstruction task based on channel-wise and profile-wise masking, guiding the model to learn spatiotemporally coherent structures and cross-channel consistency from lidar echoes without any manual labels (Vincent et al., 2008; He et al., 2021).~~

~~Stage 2 performs VDE-guided probabilistic distillation to regularize the cloud/non-cloud decision boundary learned in Stage 1. Specifically, we use discretized cloud-probability levels produced by the conventional VDE algorithm (Zhao et al., 2014; Zou et al., 2024) as soft targets, and optimize the segmentation head on top of the self-supervised representation. Compared with hard labels, these probability levels provide an uncertainty-aware training signal that stabilizes learning in ambiguous conditions, such as weak echoes, strong background noise, and aerosol–cloud overlap. In addition, we explicitly include aerosol-labeled regions as negative constraints to penalize aerosol-induced false positives and prevent the model from drifting toward overly permissive cloud decisions. Overall, Stage 2 improves transferability by injecting a robust, label-efficient regularization signal while limiting dependence on dense manual annotations.~~

~~Stage 3 fine-tunes the model using a small set of manually refined cloud-layer masks. This stage further improves boundary delineation accuracy and cross-site generalization while preserving the stable structural representations learned in the previous stages~~.

It should be noted that the multi-vendor and multi-site observation configurations in CARLNET inevitably introduce instrument-parameter differences and energy fluctuations in real operations. Rather than treating this heterogeneity as noise to be avoided, we leverage it as a realistic condition for evaluating robustness under varying instrument settings. By incorporating cross-site and cross-time data in the self-supervised and distillation stages, the model is encouraged to learn structural representations that are insensitive to instrument-dependent signal variations~~scale variations~~ and operational fluctuations, thereby improving generalization to unseen sites and different instrument conditions.

### 3.4 Data augmentation and robustness design

In real-world operations, ground-based lidar observations are inevitably affected by non-ideal factors, including cross-vendor instrument differences, laser energy fluctuations, background-noise variations, and signal perturbations under complex

设置了格式: 英语(美国)

environmental conditions. These factors frequently occur in operational network-scale observations~~These factors are pervasive at network scale~~ and constitute major sources that limit the cross-site generalization of deep learning models.

In this study, raw lidar signals are resampled to a 5 min temporal resolution in operational processing to balance temporal continuity, signal stability, and computational efficiency for automated cloud-layer identification.

However, the effective time resolution may still differ across sites due to observing conditions, quality control, or missing data. To address this, we introduce a set of lidar-oriented data augmentation strategies during training. Through explicit sampling and perturbation mechanisms, these augmentations cover variations in time scales and observing conditions, thereby improving robustness to time-resolution shifts.

The adopted augmentations operate primarily at the input-observation level, aiming to emulate realistic conditions such as energy-scale variations, noise perturbations, local temporal gaps, and incomplete channel information (Xie et al., 2020). The selected perturbation ranges are determined based on typical variability in operational lidar measurements, including laser-energy fluctuations, photon-counting noise characteristics, and signal-quality variations. These operations encourage the model to focus on structural patterns in the time–height domain rather than relying on specific signal amplitudes or fixed temporal completeness patterns, thereby reducing sensitivity to observation-condition differences.~~These operations encourage the model to focus on structural patterns in the time–height domain, rather than depending on specific amplitude scales or fixed sampling intervals, thus reducing sensitivity to configuration differences.~~

These augmentation strategies are applied across the three training stages and play important roles during the representation learning and VDE-guided distillation stages. The former facilitates the learning of stable time–height structural representations, whereas the latter further reduces uncertainty in cloud/non-cloud discrimination under noisy and variable observation conditions with physically informed guidance.~~These augmentation strategies are applied in different forms across the three training stages, and play particularly important roles in self-supervised pretraining and VDE-based distillation: the former facilitates learning stable time–height structural representations, whereas the latter further suppresses identification uncertainty induced by noise and scale changes under a physically motivated constraint.~~

All augmentations are applied only during training and are not used during inference or evaluation. Moreover, the augmentation operations are designed to remain physically plausible for lidar observations and do not introduce additional label information. The augmentation types, parameter ranges, and stage-wise usage are summarized in the Appendix.~~We emphasize that all data augmentations are used only during training and are not applied during inference or evaluation. Moreover, all augmentations are designed to be physically plausible for lidar observations and do not introduce any additional prior label information. For reproducibility, the augmentation types, parameter ranges, and stage-wise usage will be reported in the Appendix.~~

Once trained and validated, the model can be applied with the same preprocessing and inference protocol to generate consistent cloud-layer masks, cloud-base heights, and cloud-top heights for automated CARLNET processing. These

products provide a basis for downstream calibration, quality control, and future long-term cloud-structure analyses, but the present study focuses on method validation and cross-site transferability.

## 4 Experiments and validation

This section evaluates the proposed framework as an automated cloud-layer identification technique for network-scale Raman lidar processing. The validation is designed to test whether the method can maintain stable performance under cross-site differences in instrument response, background conditions, aerosol environment, and cloud structure. We assess the framework progressively in terms of ~~label efficiency~~annotation efficiency, pixel-level identification accuracy, operation-relevant geometric products including cloud-base and cloud-top heights, and external consistency with independent radiosonde observations.

Unless otherwise specified, all evaluations are conducted using continuous observations from three held-out CARLNET sites (51628, 53845, and 58847) in January 2025. These sites are excluded from both the pretraining phase (including Stage 1 self-supervised representation learning and Stage 2 VDE-guided probabilistic distillation) and the supervised fine-tuning stage. Any experiment introducing a small amount of test-site annotations is treated separately as a test-site adaptation experiment and is not included in the main validation protocol. The VDE method is used as the conventional physics-based baseline throughout this section.~~These sites are excluded from both pretraining and supervised training, thereby ensuring a strict cross-site and cross-time evaluation setting. Any experiment that introduces a small amount of labeled data from the test sites is explicitly treated as an adaptation ablation rather than as part of the main validation protocol. The VDE method is used as the rule-based baseline throughout this section.~~

The results reported in Figs. 4–6 and Tables 2–3 were obtained from a single training run using the fixed experimental configuration described in Appendix A. They are therefore interpreted as deterministic performance estimates for the specified data split rather than as statistical estimates of variability across model initializations.

### 4.1 Data-size test-site adaptation experiment~~ablation study~~

~~To evaluate how different training strategies behave under limited manual annotations, we design an ablation study with respect to the amount of labeled training data. The x-axis indicates the number of consecutive observation days used for training, and the y-axis reports the F1 score on the independent test set. The definition and computation of the F1 score are provided in Appendix A. The test set is fixed to continuous observations in January 2025 from the three test sites, ensuring that training and testing are independent in both site and time.~~

To evaluate the performance of different training strategies under limited manual annotations, we conducted a test-site adaptation experiment using varying amounts of labeled training data. Fig. 4 compares four strategies: direct supervised training, Stage 1 only (self-supervised representation learning), Stage 2 only (VDE-guided probabilistic distillation), and

Stage 1 + Stage 2 (physics-guided pretraining). The x-axis indicates the number of consecutive observation days used for training, while the y-axis reports the F1 score evaluated on the fixed independent test set. The definition and computation of the F1 score are provided in Appendix A. The test set comprises continuous observations collected in January 2025 from the three test sites, ensuring independence between the training and test data in both time and site.

As shown in Fig. 4, under the small-sample setting of 10 labeled training days, both Stage 1 and Stage 2 improve performance relative to direct supervised training, while the complete Stage 1 + Stage 2 strategy provides the largest gain. Specifically, the F1 score increases from approximately 0.75 for direct supervised training to approximately 0.91 with the complete physics-guided pretraining strategy, indicating a substantial reduction in segmentation error. As the amount of labeled training data increases, all four strategies show improved performance but diminishing marginal gains, with their F1 scores approaching a plateau at approximately 40 labeled days.

This experiment demonstrates that the combination of self-supervised representation learning and VDE-guided probabilistic distillation improves annotation efficiency by enabling competitive performance with fewer manually annotated observations. Considering the trade-off between annotation effort and marginal performance improvement, approximately 40 training days are selected for subsequent experiments. While F1 score provides an overall assessment of pixel-level cloud-layer identification capability, the practical advantages of improved representation learning are further reflected in cloud-boundary localization and robustness under complex observation conditions. Therefore, the impact of different training strategies on operationally relevant cloud-base and cloud-top height estimation is evaluated in Sect. 4.2.2, while qualitative analyses under challenging cloud–aerosol conditions are presented in Sect. 4.2.3.~~We compare four strategies: No Pretrain, Stage 1 self-supervised pretraining only, Stage 2 distillation pretraining only, and joint Stage 1+2 pretraining. Figure 4 summarizes the performance under different training data scales. The results show that under small-sample conditions (10 training days), pretraining yields a clear performance boost, and the joint pretraining strategy provides the most pronounced gain over training from scratch. As the training data scale increases, all methods improve but exhibit diminishing marginal returns, approaching a stable plateau at around 40 days.~~

~~This experiment indicates that self-supervised and distillation pretraining significantly improves data utilization efficiency, enabling better learning performance with fewer manual annotations and encouraging the model to learn structural representations that are more robust to cross-site differences and operational perturbations at an earlier stage. Considering the trade-off between plateau performance and training cost, the subsequent experiments adopt a training scale of approximately 40 consecutive days.~~





**Figure 4. Comparison of cloud-layer identification performance (F1 score) under different training-data scales. The black box highlights the F1 scores of different strategies under the 10-day small-sample setting.** The red dashed line denotes the selected 40-day training scale, beyond which additional annotations provide limited marginal improvement. ~~The red dashed line denotes the selected training-data scale where marginal gains become limited.~~

Overall, the results suggest that pretraining not only reduces reliance on large-scale manual annotations for cloud-layer identification, but also reduces reliance on extensive manual annotations for cross-site deployment. ~~provides a more controllable training cost for cross-site deployment.~~

### 4.2 Cross-site overall performance

#### 4.2.1 Overall performance and clarification of test-site usage

Table 2 reports the overall performance under different training strategies and different usages of the test-site data. Metrics include intersection over union (IoU), F1 score, precision, and recall. All results are computed over the full test set. Early stopping was applied using the validation criterion described in Appendix A5. ~~We apply an early-stopping strategy to mitigate overfitting: training is terminated when the validation performance does not improve for a number of consecutive epochs.~~

In Table 2, "Test-site observations used in pretraining" indicates whether observations without expert annotations from the three held-out test sites were included in Stage 1 and Stage 2, whereas "Test-site annotations used in fine-tuning" indicates whether a limited amount of manually annotated data from each test site was introduced during Stage 3. Specifically, the test-site adaptation setting uses 2 annotated days per site sampled from 2024, which are temporally independent of the January 2025 test period. The configuration excluding both test-site observations from pretraining and test-site annotations from fine-tuning represents the primary strict cross-site and cross-time evaluation. ~~In Table 2, "Test sites used in pretraining"~~

带格式的: 居中

设置了格式: 英语(美国)

设置了格式: 字体: Times New Roman

设置了格式: 字体: Times New Roman

~~indicates whether the test-site data are included during pretraining, and "Test-site labels used in training" indicates whether a small amount of labeled data is additionally introduced in the training stage for each of the three test sites (2 days per site, sampled from 2024 and independent of the test month). This setting is designed to emulate a practical scenario where a newly deployed site provides only limited annotations for adaptation. "Pretrain (no test sites) + train (no test sites)" corresponds to the strictest configuration: the test sites are used neither in pretraining nor in training, reflecting the zero-prior generalization capability for truly unseen network sites.~~

As shown in Table 2, pretraining (Stage 1 and Stage 2) yields stable gains in cross-site evaluation. Under the strict setting where no test-site observations are introduced during either pretraining or fine-tuning, the complete physics-guided pretrained model achieves F1 = 0.937, higher than 0.928 obtained by direct supervised training~~Under the setting where no labeled data from test sites is introduced during training, simulating newly added operational sites, the pretrained model achieves F1 = 0.9371, higher than 0.9281 obtained without pretraining~~. Measured by inconsistency (1 − F1), pretraining reduces it from 0.072~~19~~ to 0.063~~29~~, corresponding to a 12.5 % relative reduction. Because the results are obtained under a fixed dataset split and training configuration, the F1 difference should be interpreted as a modest deterministic performance gain rather than formal evidence of statistical significance. Its practical relevance is further evaluated using cloud-boundary errors and qualitative cases in the following sections. Notably, introducing a small amount of test-site annotations during fine-tuning does not further improve performance substantially ~~introducing a small amount of labeled data from the test sites during training does not further improve performance substantially~~ (F1 = 0.935~~47~~), suggesting that the major benefit primarily comes from transferable structural representations acquired during pretraining rather than from supervised fitting to specific test sites.

Compared with the proposed physics-guided pretrained model, the conventional VDE baseline exhibits lower consistency with manual annotations, particularly under complex cloud structures and strong aerosol backgrounds~~Compared with the deep learning models, VDE performs markedly worse under network-scale observations, particularly in IoU and F1 score, highlighting the limitation of rule-based methods under complex cloud structures and strong aerosol backgrounds~~.

**Table 2. Cloud-layer identification performance under different training strategies and different usages of test-site data.**

| Strategy | Pretraining | Test-site observations used in pretraining | Test-site annotations used in fine-tuning | IoU | F1 score | Precision | Recall |
|---|---|---|---|---|---|---|---|
| Direct supervised training | No | — | No | 0.865 | 0.928 | 0.909 | 0.947 |
| Direct supervised training | No | — | Yes | 0.867 | 0.929 | 0.927 | 0.931 |

设置了格式: 字体: 非加粗
带格式的: 行距: 单倍行距
带格式的: 居中, 行距: 单倍行距
格式化表格
设置了格式: 字体: 非加粗
设置了格式: 字体: 非加粗
带格式的: 行距: 单倍行距
带格式的: 居中, 行距: 单倍行距
带格式的: 行距: 单倍行距
带格式的: 居中, 行距: 单倍行距
格式化表格

| Strategy | Pretraining | Test-site observations used in pretraining | Test-site annotations used in fine-tuning | IoU | F1 score | Precision | Recall |
|---|---|---|---|---|---|---|---|
| Pretraining + Fine-tuning | Yes | No | No | 0.881 | 0.937 | 0.925 | 0.949 |
| Pretraining + Fine-tuning | Yes | No | Yes | 0.877 | 0.935 | 0.924 | 0.945 |
| VDE | — | — | — | 0.540 | 0.702 | 0.639 | 0.778 |

| ~~Strategy~~ | ~~Pretrain~~ | ~~Test Sites (Pretrain)~~ | ~~Test Sites (Training)~~ | ~~IoU~~ | ~~F1 Score~~ | ~~Precision~~ | ~~Recall~~ |
|---|---|---|---|---|---|---|---|
| ~~No Pretrain (No Test Sites)~~ | ~~✗~~ | - | ~~✗~~ | ~~0.866~~ | ~~0.928~~ | ~~0.910~~ | ~~0.947~~ |
| ~~No Pretrain (With Test Sites)~~ | ~~✗~~ | - | ~~✓~~ | ~~0.868~~ | ~~0.929~~ | ~~0.927~~ | ~~0.931~~ |
| ~~Pretrain (No Test Sites) + Train (No Test Sites)~~ | ~~✓~~ | ~~✗~~ | ~~✗~~ | ~~0.882~~ | ~~0.937~~ | ~~0.926~~ | ~~0.949~~ |
| ~~Pretrain (No Test Sites) + Train (With Test Sites)~~ | ~~✓~~ | ~~✗~~ | ~~✓~~ | ~~0.878~~ | ~~0.935~~ | ~~0.924~~ | ~~0.945~~ |
| ~~VDE~~ | ~~-~~ | ~~-~~ | ~~-~~ | ~~0.295~~ | ~~0.404~~ | ~~0.429~~ | ~~0.539~~ |

Overall, the results indicate that pretraining provides consistent improvements ~~under strict cross-site and cross-time settings,~~ and the strictest configuration performs no worse than configurations that include test-site information, supporting that the performance gain does not originate from site-specific fitting. This suggests that pretraining primarily enhances the model's general representation of cloud-layer structures, offering a more reliable foundation for operational scaling.

#### 4.2.2 Operation-relevant evaluation: cloud-base and detectable cloud-top heights~~cloud-top heights~~

The operational value of a cloud-layer mask is not only reflected by pixel-level classification accuracy, but also by its capability to characterize cloud geometrical structures, particularly the accurate estimation of cloud-base and cloud-top



设置了格式: 字体: 非加粗
带格式的: 行距: 单倍行距
带格式的: 居中, 行距: 单倍行距
格式化表格
设置了格式: 字体: 非加粗
设置了格式: 字体: 非加粗
带格式的: 行距: 单倍行距
带格式的: 居中, 行距: 单倍行距
带格式的: 行距: 单倍行距
带格式的: 居中, 行距: 单倍行距
带格式的: 行距: 单倍行距
带格式的: 居中, 行距: 单倍行距
设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
带格式的: 正文
设置了格式: 字体: Times New Roman
设置了格式: 字体: Times New Roman
设置了格式: 字体: Times New Roman

heights. To evaluate the practical relevance of different methods, predicted cloud-layer masks are converted into geometric cloud products and compared with manually refined annotations.

To derive layer-wise geometric errors, cloud layers are extracted from each vertical profile as vertically contiguous cloud-positive regions. The lowest and highest cloud-positive range bins of each layer are defined as the cloud-base height and detectable cloud-top height, respectively. Predicted and reference layers are then matched using a global one-to-one assignment implemented with the Hungarian algorithm (linear-sum assignment). The matching cost is constructed to prioritize physically overlapping layer pairs. For pairs with vertical overlap, the vertical intersection over union (IoU), defined as the ratio of the overlapping thickness to the total union thickness, is used as the primary matching criterion, while the absolute difference in layer-center height is used as a secondary criterion. For non-overlapping layers, matching is permitted only when the minimum vertical separation between the two layers does not exceed 300 m; pairs separated by more than 300 m are treated as invalid candidates.

Each predicted or reference layer can therefore be assigned to at most one corresponding layer. Unmatched reference layers are counted as missed detections, whereas cloud-base and cloud-top errors are calculated only for successfully matched layer pairs. This procedure prevents multiple predicted layers from being assigned to the same reference layer and allows small boundary discontinuities of up to 300 m without treating physically adjacent layers as completely unrelated detections.

Because ground-based lidar signals may be strongly or completely attenuated by optically thick clouds, the reported cloud-top height refers to the highest cloud boundary supported by a detectable lidar return, rather than necessarily the physical upper boundary of the cloud. Reliable cloud-top estimation therefore requires sufficient residual signal and signal-to-noise ratio near the upper cloud boundary. When complete attenuation prevents observation of the physical cloud top, the corresponding reference boundary is defined by the highest detectable cloud-positive bin in the manually refined mask. Cloud layers that are completely obscured and produce no detectable lidar return cannot be included in the boundary-error evaluation.

Fig. 5 presents the correspondence between estimated cloud boundaries and manually refined annotations, while Table 3 summarizes the detection rate and quantitative errors of cloud-base and cloud-top heights. For cloud-base estimation, the pretrained model achieves an MAE of 59.1 m, which is comparable to the direct supervised model (55.3 m) and substantially better than the VDE baseline (123.6 m). The corresponding cloud-base bias is −12.8 m, which is smaller than the original 15 m vertical sampling interval of the lidar and is therefore negligible at the native instrumental resolution. This indicates that all deep learning models can effectively capture relatively strong cloud-base signatures once sufficient structural information is learned.

The advantage of pretraining is more evident for cloud-top estimation. The pretrained model achieves a cloud-top MAE of 82.2 m, reducing the error by approximately 12.6-% compared with direct supervised training (94.0 m) and by approximately 67–% compared with VDE (250.7 m). This improvement suggests that the proposed pretraining strategy enhances the preservation of weak and optically thin cloud boundaries, where accurate cloud-top identification is more challenging due to signal attenuation, low signal-to-noise ratio, and multilayer cloud structures.

Beyond geometric errors, Table 3 also reports the cloud detection rate. The pretrained and direct supervised models exhibit nearly identical detection rates (93.9-% and 94.1-%, respectively), indicating that the improvement from pretraining does not originate from simply detecting more cloud layers. Instead, the main benefit lies in more accurate delineation of cloud boundaries and vertical structures. In contrast, VDE shows a lower detection rate (86.0-%) and substantially larger geometric errors, demonstrating its limitations under complex network-scale observations.


The larger cloud-top errors of VDE can be attributed to the empirical threshold-based discrimination strategy. As shown in Fig. 5c and 5f, VDE exhibits stronger deviations from the manually refined boundaries, particularly for cloud-top estimation. The attenuation-based decision criteria may suppress weak cloud signals near cloud boundaries, leading to underestimated cloud-top heights and missing thin or weak-echo cloud structures.


~~The operational value of a cloud layer mask is not only reflected by pixel-level classification accuracy, but also by its capability to characterize cloud geometrical structure—most importantly, the stable estimation of cloud base height and cloud top height. To assess method differences from an application oriented perspective, we convert predicted cloud layer masks into cloud base and cloud top height products and compare them with manually refined annotations.~~

~~Figure 5 shows the correspondence between estimates from different methods and the manual ground truth (GT), and Table 3 summarizes quantitative statistics including the detection rate and the errors of cloud base/cloud top heights. For cloud base estimation, the pretrained model achieves a mean absolute error (MAE) of 113 m, reducing the MAE by roughly 50 m compared with the no pretrain model (162 m). For cloud top estimation, the pretrained model yields an MAE of 213 m, improving by about 70 m over the no pretrain model (283 m). Relative to VDE, the improvement is particularly pronounced for cloud top height: the cloud top MAE decreases from 622 m to 213 m, i.e., by nearly 400 m.~~

~~Beyond geometric errors, Table 3 also reports the detection rate, defined as the fraction of samples in which a cloud process is detected. The pretrained and no pretrain models show nearly identical detection rates (94.81 % vs. 94.85 %), indicating comparable overall capability in detecting cloud processes; importantly, pretraining does not improve performance simply by detecting more clouds. In contrast, VDE exhibits a lower detection rate (64.07 %), reflecting a higher tendency to miss weak-echo clouds or complex layered structures at network scale.~~

~~A plausible explanation for VDE's lower detection rate can be inferred from Figure 5c and f. VDE tends to overestimate cloud base height while underestimating cloud top height, which can narrow or even eliminate marginal cloud layers in the derived vertical extent. The cloud top underestimation is consistent with its boundary determination strategy, whereas the elevated cloud base is likely related to the smoothing/denoising steps that suppress weak echoes near cloud boundaries. Moreover, VDE shows more abnormal outliers in the geometric errors, suggesting reduced robustness under low SNR conditions and complex multilayer scenes at network scale, thereby increasing the chance of missing clouds altogether. To further substantiate these interpretations with an independent reference, Sect. 4 introduces radiosonde observations for an objective evaluation~~.


(a) Pretrained - Cloud Base
N = 11840
MAE = 59.1 m
Bias = -12.8 m
RMSE = 164.5 m
R = 0.998
Pretrained Cloud Base (km)
GT Cloud Base (km)
(b) Direct supervised training - Cloud Base
N = 11869
MAE = 55.3 m
Bias = -13.1 m
RMSE = 159.0 m
R = 0.998
Direct supervised training Cloud Base (km)
GT Cloud Base (km)
(c) VDE - Cloud Base
N = 10851
MAE = 123.6 m
Bias = 66.3 m
RMSE = 302.9 m
R = 0.994
VDE Cloud Base (km)
GT Cloud Base (km)
(d) Pretrained - Cloud Top
N = 11840
MAE = 82.2 m
Bias = -2.8 m
RMSE = 229.0 m
R = 0.997
Pretrained Cloud Top (km)
GT Cloud Top (km)
(e) Direct supervised training - Cloud Top
N = 11869
MAE = 94.0 m
Bias = -18.9 m
RMSE = 276.5 m
R = 0.996
Direct supervised training Cloud Top (km)
GT Cloud Top (km)
(f) VDE - Cloud Top
N = 10851
MAE = 250.7 m
Bias = -96.4 m
RMSE = 528.6 m
R = 0.986
VDE Cloud Top (km)
GT Cloud Top (km)


(a) Pretrained - Cloud Base
MAE = 113.0 m
Bias = -10.9 m
RMSE = 409.3 m
R = 0.989
Pretrained Cloud Base (km)
GT Cloud Base (km)
(b) No-Pretrain - Cloud Base
MAE = 163.4 m
Bias = -47.6 m
RMSE = 644.1 m
R = 0.972
No-Pretrain Cloud Base (km)
GT Cloud Base (km)
(c) VDE - Cloud Base
N = 7909
MAE = 406.9 m
Bias = 51.4 m
RMSE = 1094.4 m
R = 0.895
VDE Cloud Base (km)
GT Cloud Base (km)
(d) Pretrained - Cloud Top
N = 11742
MAE = 212.0 m
Bias = 12.6 m
RMSE = 647.3 m
R = 0.978
Pretrained Cloud Top (km)
GT Cloud Top (km)
(e) No-Pretrain - Cloud Top
N = 11743
MAE = 284.6 m
Bias = -72.6 m
RMSE = 910.2 m
R = 0.957
No-Pretrain Cloud Top (km)
GT Cloud Top (km)
(f) VDE - Cloud Top
N = 7909
MAE = 621.0 m
Bias = -253.1 m
RMSE = 1378.2 m
R = 0.896
VDE Cloud Top (km)
GT Cloud Top (km)

带格式的: 居中

**Figure 5.** Comparison of estimated cloud-base and detectable cloud-top heights with manually refined annotations. Panels (a–c) show cloud-base comparisons, and panels (d–f) show detectable cloud-top comparisons. Panels (a, d), (b, e), and (c, f) correspond to the pretrained model, direct supervised model, and VDE method, respectively. GT denotes the manually refined reference, N is the number of successfully matched cloud layers, MAE is the mean absolute error, bias is the mean signed error defined as prediction minus reference, RMSE is the root-mean-square error, and R is the Pearson correlation coefficient. The dashed diagonal line indicates perfect 1:1 agreement.~~Cloud-base and cloud-top height estimates compared with the manual ground truth (GT). Panels (a–c): cloud base; panels (d–f): cloud top.~~

Taken together, these results demonstrate that the advantage of the proposed pretraining strategy is primarily reflected in improved cloud-boundary localization rather than a simple increase in cloud occurrence detection. The improved cloud-top estimation indicates stronger capability in preserving vertically extended and weak cloud structures, which is important for operational lidar cloud processing, quality control, and cloud-structure characterization.~~Taken together, the results suggest that the advantage of pretraining mainly lies in more accurate delineation of cloud boundaries and geometrical structure, rather than in the binary decision of "cloud present or not." The reduced cloud-top error and bias indicate stronger structure preservation under weak echoes, multilayer conditions, and attenuation, which directly benefits lidar calibration, quality control, and cloud-structure characterization in operational applications.~~

**Table 3. Quantitative comparison of detection rate and cloud-base/cloud-top height errors across methods. MAE denotes mean absolute error.**

| Method | Detection Rate (%) | Base MAE (m) | Base Bias (m) | Top MAE (m) | Top Bias (m) |
|---|---|---|---|---|---|
| Stage 1 + Stage 2 pretraining~~Pretrained~~ | 93.9~~94.8~~ | 59.1~~113.3~~ | -12.8~~-10.0~~ | 82.2~~212.8~~ | -2.8~~13.4~~ |
| Direct supervised training~~No-Pretrain~~ | 94.1~~94.9~~ | 55.3~~162.4~~ | -13.1~~-46.9~~ | 94.0~~283.1~~ | -18.9~~-70.9~~ |
| VDE | 86.0~~64.1~~ | 123.6~~40 7.4~~ | +66.35~~6.5~~ | 250.7~~621.6~~ | -96.4~~-245.2~~ |

### 4.2.3 Qualitative examples under complex conditions

To further illustrate the role of physics-guided pretraining in improving structural stability, Fig. 6 presents qualitative comparisons between the Stage 1 + Stage 2 pretrained model and the direct supervised model under complex lidar observation conditions. The examples focus on challenging scenarios including weak-echo clouds, aerosol–cloud coexistence, signal fluctuations, and multilayer structures. Compared with direct supervised training, the pretrained model produces cloud-layer masks that better agree with manually refined annotations in terms of boundary continuity, weak-layer

设置了格式: 字体: (中文) +中文正文 (宋体), (中文) 简体中文(中国大陆)
带格式的: 正文
带格式的: 居中, 右侧: 0 厘米, 行距: 单倍行距
带格式的: 右侧: 0 厘米, 行距: 单倍行距
格式化表格
带格式的: 右侧: 0 厘米, 行距: 单倍行距
带格式的: 右侧: 0 厘米, 行距: 单倍行距
带格式的: 右侧: 0 厘米, 行距: 单倍行距
设置了格式
带格式的: 标题 3
设置了格式: 字体: Times New Roman
设置了格式: 字体: Times New Roman
设置了格式: 字体: Times New Roman
设置了格式: 字体: 非倾斜

preservation, and temporal consistency.~~To further illustrate the role of pretraining in structural stability, Figure 6 provides qualitative examples comparing the pretrained and no-pretrain models under complex echo conditions. The pretrained model produces cloud-layer masks that are closer to manual annotations in terms of weak-echo cloud layers, multilayer structures, and boundary continuity, and also shows better temporal coherence. By contrast, the no-pretrain model more often produces layer breaks, misses, or localized false alarms over strong aerosol layers.~~

~~Specifically, Figure 6a shows a case at Fuzhou (58847). During 10:00–18:00 UTC, a weak aerosol layer exists above the boundary layer. The no-pretrain model persistently misclassifies this weakly scattering layer as cloud (black box), resulting in a non-physical continuous cloud coverage over a long period. The pretrained model suppresses such aerosol-induced false alarms more effectively and yields more coherent mask boundaries. Figure 6b shows a case at Aksu (51628). Around 12:00 UTC, a short-term energy fluctuation occurs; the no-pretrain model misclassifies locally enhanced noise as cloud, as marked by the black box, forming isolated "pseudo-cloud" fragments that are inconsistent with surrounding structures. In comparison, the pretrained model maintains a more stable decision without corresponding false alarms.~~ Fig. 6a shows an example from Fuzhou (58847), where a weak aerosol layer exists above the boundary layer during 10:00–18:00 UTC. Under this aerosol background, the direct supervised model tends to misclassify weak scattering structures as cloud, resulting in unrealistic continuous cloud regions (black box). In contrast, the pretrained model suppresses aerosol-induced false detections more effectively and maintains more physically consistent cloud boundaries. This example demonstrates the benefit of learning transferable structural representations for distinguishing cloud signals from aerosol-related echoes.

Together, these examples demonstrate that the advantage of physics-guided pretraining is not limited to improvements in average segmentation metrics, but is reflected in more stable structural interpretation under challenging observation conditions. Combined with the detection-rate analysis and geometric evaluation, the results suggest that the proposed framework improves the representation of complex cloud structures, particularly under weak echoes, aerosol–cloud coexistence, and variable operational conditions.~~These examples support that pretraining improves structural stability rather than providing incidental metric gains: it produces more continuous boundaries, more reliable multilayer preservation, and stronger suppression under strong aerosol backgrounds. Together with the detection-rate statistics, the advantage of deep learning at network scale is mainly attributed to more complete depiction of complex cloud structures, rather than merely identifying "strong-echo clouds."~~





**Figure 6. Qualitative comparison of cloud-layer masks produced by pretrained and direct supervised ~~no pretrain~~ models under complex echo conditions. The background shows the 1064 nm elastic channel (10:00–18:00 UTC; 0–6 km). ~~T~~The black solid contour denotes the pretrained model, whereas the black dotted contour denotes the direct supervised model. Red boxes highlight representative regions with substantial differences.~~he blue dashed contour denotes the pretrained model, and the green dashed**

~~contour denotes the no-pretrain model. Black boxes highlight representative regions with substantial differences.~~ **Panel a shows Fuzhou (58847, 2025-01-~~28~~13), and panel b shows Aksu (51628, 2025-01-~~28~~13).**

### 4.3 Independent validation with radiosonde observations

The radiosonde-based evaluation includes 47 valid lidar–radiosonde comparison cases from all three independent test sites. The quantitative statistics reported in Table 4 are calculated by aggregating the matched cases from Aksu, Yan'an, and Fuzhou. Fig. 7 and Fig. 8 present representative examples from Aksu to illustrate the comparison procedure and typical differences among the proposed model, VDE, manual annotations, and radiosonde-derived moist layers.~~To further assess cloud-layer identification results using an independent observing system, we incorporate co-located radiosonde data and compare the deep learning method (DL) with the conventional VDE approach.~~

Considering the temporal and spatial mismatch between lidar observations and radiosonde profiles, we aggregate lidar-derived cloud-layer masks within ±1 h around each radiosonde launch time and compare the resulting cloud structures with radiosonde-identified moist layers. This temporal aggregation is adopted to account for the time-evolving nature of cloud systems and the fact that radiosondes sample the atmosphere along a drifting ascent trajectory rather than an instantaneous vertical column.~~Given the time-accumulating nature of radiosonde observations, we take the union of lidar-based cloud-layer masks within ±1 h around each radiosonde launch time and match it with radiosonde-identified cloud layers to reduce spatiotemporal mismatch. Figures 7 and 8 show the results for Aksu (51628) and Fuzhou (58847) in January 2025.~~

For Aksu (Fig. 7), the proposed model and VDE show generally consistent temporal and vertical evolution of major cloud processes, while both exhibit systematic differences from radiosonde-derived moist layers in cloud boundaries. These differences mainly arise from the distinct observing principles: lidar provides high-resolution backscatter observations and is sensitive to weak scattering structures, whereas radiosonde-based cloud identification relies on altitude-dependent humidity thresholds and samples the atmosphere along a drifting ascent trajectory.~~For Aksu (Figure 7), DL and VDE are generally consistent in the temporal and vertical evolution of major cloud processes, while both often yield lower cloud bases and higher cloud tops compared with radiosondes. This systematic discrepancy mainly arises from differences in observing principles: lidar provides higher vertical resolution and sensitivity to weak echoes, whereas radiosonde moist-layer identification depends strongly on thresholding and the vertically accumulated ascent process.~~ On this basis, the proposed model~~DL~~ tends to better preserve the continuity of high-level weak-echo structures (Fig.~~Figure~~ 7b), with fewer apparent temporal discontinuities than VDE~~with fewer temporal breaks and fewer missed thin-cirrus segments than VDE~~, which helps mitigate cloud-top underestimation for tenuous upper-level layers. For low-level clouds, both methods capture the major structures reasonably well, with relatively smaller differences compared with upper-level weak clouds (Fig. 7c). ~~DL also provides more stable identification for low-level clouds, showing better agreement with radiosondes (Figure 7c).~~

Fig. 8a and Fig. 8b provide zoom-in comparisons of representative periods under radiosonde constraints. In these cases, the proposed model generally maintains closer vertical continuity with the radiosonde-derived cloud layers, while VDE exhibits larger deviations or intermittent discontinuities in weak-signal regions. These differences are particularly evident for cloud boundaries with relatively weak backscatter signals, where empirical threshold-based methods are more susceptible to local signal fluctuations. The consistency observed in these examples supports the quantitative comparison in Table 4 and indicates that the proposed model provides more stable structural representation under challenging lidar observation conditions.~~For Fuzhou (Figure 8), high-level cirrus coexists with persistent low-level clouds, creating a challenging scene in which weak upper-level echoes can be intermittently obscured or fragmented. DL maintains a more continuous representation of high-level cirrus over extended periods (Figure 8b), showing better consistency with the radiosonde moist-layer intervals and exhibiting fewer intermittent gaps and missed segments than VDE at these altitudes. This improvement is particularly relevant for thin, weak-echo cirrus layers, for which rule-based methods are more prone to discontinuous detection. For low-level clouds (Figure 8c), both DL and VDE capture the main structures reasonably well, and the differences are comparatively limited.~~


Beyond these qualitative comparisons, we further quantify the consistency between lidar-derived cloud layers and radiosonde-identified moist layers as shown in Table 4. Because radiosonde-based identification is affected by humidity thresholds, ascent sampling, and spatial drift, these statistics are interpreted as structural consistency indicators rather than strict accuracy measurements. The proposed model achieves a structural consistency rate of 38.3%, higher than VDE (34.0%) and expert annotation (27.7%). These differences should not be interpreted as absolute accuracy differences, because radiosonde-derived moist layers and lidar-observed cloud layers represent different atmospheric properties and are affected by different sampling characteristics. Instead, the structural consistency rate reflects the agreement between the two observing systems.

~~Based on the above trend-level comparison, we further quantify how well multilayer structures identified by radiosondes are preserved in the DL and VDE results, as a complementary assessment of multilayer completeness. Among 20 events in which radiosondes indicate a second cloud layer, DL identifies 17 (85.0 %), whereas VDE identifies 15 (75.0 %). For 85 first-layer cloud events, the identification ratios are similar (DL: 67/85, 78.8 %; VDE: 66/85, 77.6 %). This suggests that for the second layer, which is more likely to correspond to high-level or weak-echo structures, DL shows higher structural consistency than VDE, whereas for first-layer clouds dominated by strong echoes at low levels, the difference is limited. We stress that this statistic is used only to characterize structure preservation under radiosonde constraints and should not be interpreted as an absolute accuracy metric.~~

In summary, independent radiosonde-based comparisons indicate that the proposed model (DL) and VDE are broadly consistent in the temporal evolution of major cloud processes. Under the systematic offsets expected from differing observing principles, the proposed model ~~DL e~~shows improved consistency~~xhibits clearer advantages~~ for high-level, weak-echo layers, typical of thin cirrus, and for multilayer scenes, by preserving layer continuity and reducing intermittent misses

relative to VDE. This behavior aligns with the reduced cloud-top errors and the qualitative examples under complex echoes, and supports the interpretation that pretraining mainly improves structural stability and physically consistent cloud-layer representation ~~physical plausibility~~, rather than simply increasing cloud detections or yielding isolated metric gains.

We note that radiosonde-based cloud identification is derived from altitude-dependent relative-humidity thresholds and is therefore subject to uncertainties associated with threshold selection, moist-layer merging criteria, and horizontal drift during ascent. Consequently, radiosonde observations are not treated as a strict quantitative ground truth for lidar cloud-layer identification. Instead, they provide an independent atmospheric reference for evaluating the consistency of identified cloud-layer structures, including layer altitude, continuity, and multilayer occurrence.~~We note that radiosonde-based cloud identification here is derived from altitude-dependent relative-humidity thresholds and is inherently uncertain due to the threshold scheme, moist-layer merging choices, and horizontal drift during ascent. Therefore, radiosonde results are used as an independent structural reference to assess consistency in layer altitude and multilayer occurrence at the trend level, rather than as a strict quantitative ground truth.~~








**Figure 7. Consistency analysis of cloud-layer identification at Aksu (51628, January 2025) under radiosonde constraints. Panel a shows the radiosonde moist-layer cloud structure; panel b shows the manually refined labels; panel c shows the difference map between the proposed model and the VDE method ~~difference map between the deep learning (DL) algorithm and the VDE method~~ (green: both; ~~blu~~red: DL only; yellow~~orange~~: VDE only). Radiosonde-derived moist layers are used only as an independent structural-consistency reference and not as ground-truth cloud boundaries.**

**Table 4. Consistency of lidar-derived cloud layers with radiosonde-identified moist layers based on 47 valid comparison cases from the three independent test sites.**

| Lidar cloud product | Matched cases | Structural consistency rate (%) | Cloud-base MAE (m) | Detectable cloud-top MAE (m) |
|---|---|---|---|---|
| Expert annotation | 13/47 | 27.7 | 144.7 | 173.6 |
| Proposed model | 18/47 | 38.3 | 127.8 | 155.8 |
| VDE | 16/47 | 34.0 | 148.5 | 190.3 |




带格式的: 居中
带格式的: 题注
设置了格式: 字体: 加粗, 字体颜色: 自定义颜色(RGB(35,31,32))
带格式的: 正文文本, 段落间距段前: 0.6 磅, 不使用中文规则控制首尾字符, 不允许标点溢出
格式化表格
设置了格式: 字体: 加粗, 字体颜色: 自定义颜色(RGB(35,31,32))
带格式的: 正文文本, 居中, 段落间距段前: 0.6 磅, 不使用中文规则控制首尾字符, 不允许标点溢出
设置了格式: 字体: 加粗, 字体颜色: 自定义颜色(RGB(35,31,32))
设置了格式: 字体: 加粗, 字体颜色: 自定义颜色(RGB(35,31,32))
设置了格式: 字体: 加粗, 字体颜色: 自定义颜色(RGB(35,31,32))
设置了格式: 字体: 加粗, 字体颜色: 自定义颜色(RGB(35,31,32))
设置了格式: 字体颜色: 自定义颜色(RGB(35,31,32))
带格式的: 正文文本, 段落间距段前: 0.6 磅, 不使用中文规则控制首尾字符, 不允许标点溢出
带格式的: 正文文本, 居中, 段落间距段前: 0.6 磅, 不使用中文规则控制首尾字符, 不允许标点溢出
设置了格式: 字体: 加粗, 字体颜色: 自定义颜色(RGB(35,31,32))
设置了格式: 字体颜色: 自定义颜色(RGB(35,31,32))
带格式的: 正文文本, 段落间距段前: 0.6 磅, 不使用中文规则控制首尾字符, 不允许标点溢出
带格式的: 正文文本, 居中, 段落间距段前: 0.6 磅, 不使用中文规则控制首尾字符, 不允许标点溢出
设置了格式: 字体: 加粗, 字体颜色: 自定义颜色(RGB(35,31,32))
设置了格式: 字体颜色: 自定义颜色(RGB(35,31,32))
带格式的: 正文文本, 段落间距段前: 0.6 磅, 不使用中文规则控制首尾字符, 不允许标点溢出
带格式的: 正文文本, 居中, 段落间距段前: 0.6 磅, 不使用中文规则控制首尾字符, 不允许标点溢出
带格式的: 正文




带格式的: 居中

**Figure 8. Zoom-in examples of lidar-derived cloud-layer identification under radiosonde constraints. The 1064 nm elastic signal is shown as the background, with overlays of the proposed model, VDE-derived cloud layers, and radiosonde-identified moist layers. The black solid line denotes the proposed model, the black dotted line denotes the VDE result, and the gray dashed line denotes the radiosonde-derived cloud layer~~; panels d and e show zoom-in examples over representative periods, with the 1064 nm elastic channel as the background and overlays of the DL/VDE products and radiosonde constraints~~.**




~~Figure 8. Same as Figure 7, but for Fuzhou (58847, January 2025).~~

## 5 Conclusion and Discussion

This study developed and validated a multi-channel cloud-layer identification framework with reduced dependence on absolute calibration~~a calibration-decoupled, multi-channel cloud-layer identification framework~~ for automated Raman lidar network processing. The framework operates directly on observation-level elastic signals at 355, 532, and 1064 nm and volume depolarization ratios at 355 and 532 nm, without relying on fine-grained optical retrieval products as model inputs. By combining a lidar-specific anisotropic encoder–decoder architecture with self-supervised pretraining, VDE-guided probabilistic distillation, and supervised fine-tuning with limited expert-refined labels~~fine-tuning with limited expert-refined labels~~, the proposed method is designed to improve cloud-boundary stability, multilayer preservation, and cross-site transferability under realistic operational perturbations.

The framework was evaluated under a strict cross-site and cross-time setting using continuous observations from three held-out CARLNET sites that were excluded from both pretraining and supervised training. The results show that physics-guided pretraining improves pixel-level cloud-layer identification evaluation, while reducing dependence on extensive manual annotations.~~The results show that pretraining improves pixel-level cloud-layer identification without introducing any labeled data from the test sites.~~ Compared with training from scratch, the F1 score increases from 0.928~~1~~ to 0.937~~1~~, corresponding to a 12.5–% relative reduction in inconsistency (1 − F1). The labeled-data-size adaptation experiment ~~ablation~~ further demonstrates improved ~~label efficiency~~annotation efficiency, with the model approaching a performance plateau using a limited number of manually refined training days. These results indicate that the main benefit of pretraining is not site-specific fitting, but the acquisition of transferable time–height and cross-channel representations.

~~From an operational perspective, the improvement is more evident in geometry-related products.~~ From an operational perspective, the improvement is more evident in geometry-related products. Compared with direct supervised training, the pretrained model achieves comparable cloud-base height estimation while reducing cloud-top height error by approximately 12.6%.~~Compared with training from scratch, the pretrained model reduces the mean absolute error of cloud-base height by approximately 50 m and that of cloud-top height by approximately 70 m.~~ Relative to the conventional VDE baseline, the reduction in cloud-top error is particularly pronounced, with cloud-top MAE decreasing from 250.7 m to 82.2 m.~~Relative to the conventional VDE baseline, the reduction in cloud-top error is particularly pronounced, with cloud-top MAE decreasing from 622 m to 213 m.~~ The detection rates of the pretrained and direct supervised models remain nearly identical (93.9-% vs. 94.1–%), indicating that the performance gain mainly arises from improved cloud-boundary localization and multilayer structure preservation rather than from simply increasing cloud detections. Qualitative cases further show that the pretrained framework suppresses aerosol-induced false detections and reduces spurious responses associated with short-term signal fluctuations.~~The detection rates of the pretrained and no-pretrain models remain nearly identical, indicating that the performance gain mainly arises from more accurate boundary delineation and multilayer structure preservation rather than from simply detecting more cloud pixels. Qualitative cases further show that the pretrained framework suppresses non-physical cloud detections over strong aerosol layers and reduces false alarms caused by short-term energy fluctuations.~~

Independent radiosonde-based comparisons provide an additional consistency check from a different observing system. Although lidar and radiosonde cloud indications are not expected to match exactly because of differences in observing principles, humidity-threshold uncertainty, and balloon drift, the proposed framework shows higher structural consistency with radiosonde-identified moist layers than both expert annotation and VDE. Specifically, the proposed model achieves a structural consistency rate of 38.3-%, compared with 34.0-% for VDE and 27.7-% for expert annotation. This result should not be interpreted as an absolute accuracy comparison, but rather as evidence that the proposed framework provides a more consistent representation of atmospheric layer structures under independent observational constraints.~~Independent radiosonde-based comparisons provide an additional consistency check from a different observing system. Although lidar and radiosonde cloud indications are not expected to match exactly because of differences in observing principles, humidity-threshold uncertainty, and balloon drift, the proposed framework shows better preservation of second-layer structures than VDE under radiosonde constraints. This advantage is particularly relevant for high-level weak echoes and multilayer scenes, where rule-based methods are more prone to intermittent misses and cloud-top underestimation. For first-layer clouds dominated by stronger low-level echoes, the difference between the proposed method and VDE is smaller, suggesting that the primary practical value of the proposed framework lies in improving structural completeness under weak-signal and multilayer conditions.~~

This advantage is particularly relevant for high-level weak echoes and multilayer scenes, where empirical methods may experience larger uncertainty in maintaining layer continuity. For first-layer clouds dominated by stronger low-level echoes,

the difference between the proposed method and VDE is smaller, suggesting that the primary practical value of the proposed framework lies in improving structural completeness under weak-signal and multilayer conditions.

Several limitations should be noted. First, the present framework focuses on cloud-layer identification and does not explicitly separate precipitation from cloud layers. Scenes affected by precipitation, virga, or strongly attenuating hydrometeors may require additional physical constraints or task-specific labels. Second, although the model is designed to reduce dependence on absolute calibration, its inputs remain affected by near-range overlap, daytime background radiation, signal saturation, and severe attenuation by optically thick low clouds. These factors may still limit the observability of certain cloud regions, especially near the blind zone and above persistent low clouds. In particular, the model cannot recover a physical cloud top when the lidar signal is fully attenuated below that boundary. Third, the model uses a short temporal context window and is not designed to depend on long temporal averaging; however, its behavior under highly irregular sampling, sparse observations, and prolonged data gaps still requires further systematic evaluation. Fourth, although the current validation uses strict held-out sites within CARLNET, broader tests on external lidar networks are needed to assess cross-instrument and cross-platform generalizability. In addition, the current evaluation focuses on deterministic model performance under a fixed experimental setting. Although consistent improvements are observed across pixel-level metrics, geometric products, qualitative cases, and radiosonde-based consistency analyses, future work should further quantify uncertainty arising from model initialization and training variability through repeated experiments and confidence estimation.

Future work will focus on improving inference-time robustness and engineering readiness under challenging operational conditions, including strong daytime background, frequent low-cloud attenuation, irregular sampling, and data gaps. The framework will also be extended to external ground-based lidar networks and compared with spaceborne lidar observations to further evaluate cross-platform consistency. In addition, the resulting cloud-layer products can provide a unified basis for downstream calibration, quality control, ~~aerosol/cloud~~aerosol-cloud optical retrieval, and future long-term cloud-structure analyses. The training and inference framework, together with pretrained models, will be made available where possible to support reproducible evaluation and broader deployment.

## Appendix A

This appendix summarizes the training protocol of the proposed cloud-layer identification framework, including preprocessing, augmentation, model configuration, optimization, and evaluation settings. Unless explicitly stated, the same preprocessing and augmentation pipeline is applied across all stages to ensure consistent learning signals and to facilitate reproducibility.

### *A1. Preprocessing of multi-channel time–height observations*

We distinguish input vertical resampling from architectural anisotropy. Vertical resampling is performed before network input to reduce computational cost, whereas the network architecture applies downsampling only along the height axis. ~~We distinguish preprocessing vertical compression (for computational efficiency) from architectural anisotropy, where downsampling is applied only along the height axis inside the network.~~

Each input channel is normalized independently for each time–height sample. For channel $c$, the median and median absolute deviation (MAD) are calculated over all temporal and vertical pixels. The normalized signal is defined as

$$m_c = \mathrm{median}_{t,z}\left(x_{c,t,z}\right),$$
$$\mathrm{MAD}_c = \mathrm{median}_{t,z}\left|x_{c,t,z} - m_c\right|, \quad (1)$$
$$\tilde{x}_{c,t,z} = \frac{x_{c,t,z} - m_c}{1.4826\mathrm{MAD}_c + \varepsilon}.$$

The factor 1.4826 converts the MAD to a robust estimate of the standard deviation under a Gaussian distribution, while $\varepsilon = 10^{-6}$ prevents numerical instability when the MAD is close to zero. ~~All lidar channels are first normalized using a robust median absolute deviation (MAD) scheme to mitigate cross-site amplitude shifts and outlier contamination.~~

For the photon-counting elastic channels (1064 nm elastic channel, 355 nm and 532 nm parallel channels), we further apply range-squared correction followed by logarithmic compression in order to reduce dynamic range while preserving structural contrast, i.e.,

$$x \leftarrow \log(1 + x \cdot R^2), \quad (2)$$

where R denotes range. In contrast, the polarization-derived channels, i.e., VDR355 and VDR532, are kept in their native form and are not subject to range-squared correction, since they already represent a physically normalized ratio quantity.

To reduce computational cost while preserving the vertical structures relevant to cloud-layer identification, vertical resampling is performed before the observations are fed into the network. Starting from the original 2048 range gates with a vertical resolution of 15 m, the near-range region (< 800 range gates) is retained at the original resolution, while progressively coarser sampling is applied to higher-altitude regions. Specifically, the 800–1600 range-gate region is compressed using a pooling factor of 4, and the region above 1600 range gates is compressed using a pooling factor of 8. This preprocessing step converts the original 2048 vertical bins into the resampled input representation shown in Fig. 3 ([5, 10, 1056]). The same vertical resampling procedure is applied during all training stages and inference ~~To reduce computational cost while preserving the near-surface and boundary-layer structures relevant to operational usage, we compress the vertical axis using a height-dependent strategy that retains full resolution in the lower troposphere and progressively coarsens the upper levels. Specifically, the 0–12 km range is kept at the original resolution, 12–24 km is downsampled by a factor of 4, and 24–30 km is downsampled by a factor of 8. Starting from 2048 range bins with 15-m spacing, corresponding to approximately 30 km, this compression yields an effective vertical dimension of approximately 512 bins. The same vertical compression is used in all training stages and during inference~~.

The vertical resampling strategy prioritizes preserving lower-atmospheric structures where cloud boundaries and aerosol–cloud interactions are most frequently observed, while progressively reducing redundancy at higher altitudes where the original fine resolution produces ~~large~~high computational costs.

***A2. Data augmentation for operational robustness***

Operational lidar observations are affected by instrument-to-instrument differences, laser energy fluctuations, background noise variability, and occasional data irregularities. To encourage the model to learn structural cues rather than relying on absolute amplitude scales or specific sampling patterns, we adopt a strong but physically plausible augmentation policy throughout training. Concretely, we apply (i) random height cropping with probability 0.3 using a crop ratio sampled from [0.7, 0.9], (ii) additive Gaussian noise with probability 0.3 and standard deviation 0.05, (iii) multiplicative signal scaling with probability 0.3 using a factor sampled from [0.9, 1.1], and (iv) spatial dropout with probability 0.2 that randomly zeroes 10 % of pixels. These perturbations are applied only to the input observations and do not introduce any additional label information.

All perturbations are applied after channel-wise normalization. Therefore, the Gaussian-noise standard deviation of 0.05 is expressed on the normalized signal scale and corresponds to 5% of the robust unit scale. The multiplicative scaling range of 0.9–1.1 represents signal-amplitude variations of up to ±10%. A cropping ratio of 0.7–0.9 means that 70%–90% of the original vertical extent is retained, after which the cropped input is zero-padded to restore the original input size. Spatial dropout removes 10% of input pixels when activated, simulating localized missing or corrupted observations. These parameter ranges were selected empirically using training-site observations and validation performance to approximate realistic operational variability without generating physically implausible lidar structures. No held-out test-site data were used for parameter selection.

***A3. Unified model configuration***

A single unified anisotropic encoder–decoder network is used across all experiments. The input is a five-channel time–height tensor comprising the 1064 nm elastic channel, the 355 nm parallel-polarized elastic channel, the 532 nm parallel-polarized elastic channel, and the volume depolarization ratios at 355 nm and 532 nm. The segmentation head outputs a one-channel cloud-layer mask (cloud vs. non-cloud). The model uses a base width of 48 channels with dropout rate 0.1 and a vertical convolution kernel size $k_z = 5$. The overall parameter count is approximately 4.28~~8.5~~M. A reconstruction head is enabled only in Stage 1 (see below) to reconstruct all five channels; it is removed in Stage 2 and Stage 3 when training focuses on cloud-layer identification.

***A4. Stage-wise objectives***

Training follows the three-stage strategy described in the main text.

**Stage 1 (self-supervised representation learning).** The model is pretrained without manual annotations using a multi-task reconstruction objective designed to capture spatiotemporal continuity and cross-channel consistency in time–height echoes. The objective combines: (i) a full-channel reconstruction loss $L_{\text{recon}}$ implemented as MSE over all channels, (ii) a channel-masking prediction loss $L_{\text{ch}}$ where 1–2 channels are randomly masked and reconstructed, and (iii) a temporal-frame prediction loss $L_t$ where one time frame is masked and predicted from its neighbors. This stage encourages a transferable representation that is less sensitive to site-specific scaling and short-term perturbations.

The overall Stage-1 objective is defined as

$$\mathcal{L}_{\text{Stage1}} = \lambda_{\text{recon}}\mathcal{L}_{\text{recon}} + \lambda_{\text{ch}}\mathcal{L}_{\text{ch}} + \lambda_t\mathcal{L}_t. \quad (3)$$

During channel masking, one or two of the five input channels are randomly masked, corresponding to a masking ratio of 20%–40%. During temporal prediction, one of the ten input profiles is masked, corresponding to a temporal masking ratio of 10%. The loss weights are set to $\lambda_{\text{recon}} = 1$, $\lambda_{\text{ch}} = 0.5$ ~~*and* $\lambda_t = 0.5$ throughout~~ and $\lambda_t = 0.5$ throughout Stage 1.

**Stage 2 (VDE-guided probabilistic distillation~~weakly supervised distillation~~).** Starting from the Stage-1 initialization, we inject physical heuristics via distillation using discretized VDE-derived cloud probability as a teacher signal. We employ a weighted BCE-with-logits loss with a positive class weight pos_weight = 19.0 (reflecting an average cloud fraction of approximately 5%). Two additional terms are introduced to improve robustness under operational artifacts. Regions with a low teacher cloud score $\leq$ 0.4 receive an aerosol-suppression penalty with a weight of 3.0 to reduce aerosol-induced false positives. Predictions within the first 30 range bins (approximately 0–450 m and within the approximate 500 m incomplete-overlap region) receive a blind-zone penalty with a weight of 15.0 to discourage non-physical cloud detections. The overall Stage-2 objective is defined as

~~Two additional terms are incorporated to stabilize training under operational artifacts: regions with low teacher cloud score ($\leq$0.4) receive an aerosol-suppression penalty (weight 3.0) to reduce aerosol-induced false positives; and the near-range blind zone (the first 30 range bins, approximately 450 m) is strongly penalized (weight 15.0) to discourage non-physical cloud predictions in the blind region.~~

$$\mathcal{L}_{\text{Stage2}} = \mathcal{L}_{\text{BCE}} + 3\mathcal{L}_{\text{aero}} + 15\mathcal{L}_{\text{blind}} \quad (4)$$

where

$$\mathcal{L}_{\text{BCE}} = -\frac{1}{N}\sum_{i=1}^{N}\left[w_+ y_i \log\,\sigma(z_i) + (1-y_i)\log\,(1-\sigma(z_i))\right], \quad (5)$$

where $N$ denotes the total number of pixels, $z_i$ is the raw model logit for pixel i, $\sigma(\cdot)$ denotes the sigmoid function, $y_i \in [0,1]$ is the VDE-derived soft target, and $w_+ = 19.0$ is the positive-class weight. BCE-with-logits applies binary cross-entropy directly to the raw logits, with the sigmoid transformation incorporated internally for improved numerical stability. The positive-class weight was determined from the approximately 5% cloud-pixel fraction in the training data, corresponding to a negative-to-positive ratio of approximately (1-0.05)/0.05=19. The aerosol-suppression and blind-zone weights of 3.0 and 15.0, respectively, were empirically selected using the validation subset from the training sites to balance

设置了格式: 字体: 加粗

设置了格式: 字体: 加粗

aerosol-related false positives and non-physical predictions within the near-range blind zone. The held-out test sites were not used for hyperparameter selection, and all weights were fixed for the subsequent experiments.

**Stage 3 (supervised fine-tuning with manual annotations~~fine-tuning with manual labels~~).** Finally, the model is fine-tuned using a limited amount of manually refined cloud-layer annotations. Stage 3 uses the same weighted BCE-with-logits formulation with~~Finally, the model is fine-tuned using a limited amount of expert manual annotations with a standard BCE-with-logits loss and~~ $w_+$ ~~pos_weight~~ $= 19.0$~~.~~, but the soft VDE targets are replaced by binary expert annotations. This stage refines cloud-boundary placement while preserving the robust structural representations learned in Stages 1 and 2.~~This stage refines cloud boundary placement while preserving the robust structural representation learned in Stages 1–2.~~

设置了格式: 字体: 加粗

***A5. Optimization schedule and freezing strategy***

All stages are optimized using AdamW (Loshchilov and Hutter, 2019). Stage 1 uses a learning rate of $5 \times 10^{-5}$ with weight decay $1 \times 10^{-4}$, batch size 8, and 20 epochs. Stage 2 is trained in two consecutive phases to reduce overfitting to weak supervision: Phase 2A runs for 15 epochs with learning rate $5 \times 10^{-5}$ and weight decay 1×10–4 while freezing the first two encoder blocks; Phase 2B runs for 15 epochs with learning rate $2 \times 10^{-5}$ and weight decay $1 \times 10^{-5}$ while freezing the entire encoder (decoder-only adaptation). Stage 3 fine-tuning runs for 40 epochs using learning rate $1 \times 10^{-5}$, weight decay $5 \times 10^{-4}$, batch size 4, and a cosine annealing schedule with $\eta_{min} = 10^{-6}$ while freezing the encoder and bottleneck to focus adaptation on the decoder and prediction head. The cosine annealing schedule gradually decreases the learning rate from its initial value to ($\eta_{min}$) following a cosine curve, allowing relatively larger parameter updates during early fine-tuning and promoting more stable convergence during the later epochs.

Early stopping is applied based on validation performance to mitigate overfitting. Early stopping was based on the validation F1 score. Training was terminated if the validation F1 score did not improve by more than $10^{-4}$ for 5 consecutive epochs. The model checkpoint with the highest validation F1 score was retained for subsequent evaluation. This criterion was applied during all stages.

***A6. Sampling window, inference aggregation, and thresholds***

Each training sample consists of a local temporal context of 10 consecutive profiles (5-min resolution), which is sufficient to exploit short-term continuity without requiring long uninterrupted sequences. During training, a stride of 10 is used to reduce strong overlap among adjacent samples and improve computational efficiency. During inference, a stride of 1 is adopted to generate continuous cloud masks without temporal gaps~~During training we use a non-overlapping stride of 10 to avoid excessive redundancy. During inference, we use a stride of 1 and aggregate overlapping predictions by averaging to obtain smoother and more temporally consistent cloud-layer masks~~.

During Stage 2, the discretized VDE probabilities are retained as soft targets and are not binarized before calculating the BCE-with-logits loss. No probability threshold is therefore applied to the teacher targets during optimization. A threshold of 0.5 is used only to convert model probabilities into binary masks when monitoring validation metrics during training. After

Stage 3, the final operational threshold of 0.65 is selected using the held-out validation subset to balance missed detections and false positives. This threshold is fixed before evaluation and is applied consistently to all three independent test sites. The teacher-score threshold of 0.4 used for the aerosol-suppression term is a separate training constraint and is unrelated to the 0.5 validation threshold or the 0.65 final inference threshold. ~~A probability threshold of 0.5 is used during training. For final evaluation after Stage 3, a slightly more conservative threshold of 0.65 is used to reduce false positives in operational conditions.~~

***A7. Evaluation metrics and dataset split***

Cloud-layer identification is evaluated using pixel-wise intersection-over-union (IoU), F1 score, precision, recall, and accuracy. Let TP, FP, TN, and FN denote the number of true positives, false positives, true negatives, and false negatives, respectively, computed from the binary cloud-layer mask over the evaluation set. The metrics are defined as:

$$\text{Precision} = \frac{\text{TP}}{\text{TP+FP}}, \quad (6)$$

$$\text{Recall} = \frac{\text{TP}}{\text{TP+FN}}, \quad (7)$$

$$\text{F1} = \frac{2\,\text{Precision}\cdot\text{Recall}}{\text{Precision+Recall}} = \frac{2\text{TP}}{2\text{TP+FP+FN}}, \quad (8)$$

$$\text{IoU} = \frac{\text{TP}}{\text{TP+FP+FN}}, \quad (9)$$

$$\text{Accuracy} = \frac{\text{TP+TN}}{\text{TP+TN+FP+FN}}, \quad (10)$$

Within the 44 development sites, the training–validation split was performed at the site-day level, with approximately 80% of the site-days assigned to training and 20% assigned to validation. All 10-profile samples constructed from the same site on the same day were assigned exclusively to either the training or validation subset, thereby preventing highly overlapping temporal samples from being shared between the two subsets. The independent test set comprised continuous observations from the three held-out sites (51628, 53845, and 58847) in January 2025 and was excluded from model training, hyperparameter selection, threshold selection, and early stopping.

~~Unless otherwise stated, TP/FP/TN/FN are accumulated over all pixels of the entire test set (i.e., micro-averaging). The dataset is split into training (approximately 80%), validation (approximately 20%), and an independent test set composed of the three held-out sites (51628, 53845, 58847). The held-out sites are excluded from both pretraining and supervised training to ensure a strict cross-site and cross-time evaluation, as described in the main text.~~ All metrics range from 0 to 1, with values closer to 1 indicating better performance. Precision measures the reliability of predicted cloud pixels, whereas recall measures the proportion of reference cloud pixels successfully detected. The F1 score is their harmonic mean and therefore summarizes the balance between false detections and missed clouds. IoU provides a stricter measure of the spatial overlap between the predicted and reference cloud masks.

设置了格式: 英语(英国)

带格式的: 段落间距段前: 0 磅, 段后: 0 磅

设置了格式: 英语(英国)

***A8. Special constraints and practical considerations***

Two practical constraints are explicitly handled. First, the near-range blind zone is discouraged during training (Stage 2) to prevent non-physical detections. Second, in scenes dominated by aerosols, the distillation objective introduces an aerosol suppression term based on low teacher cloud-score regions to reduce false positives. For rare all-negative cases (no cloud pixels in the reference mask), metrics are computed with a consistent convention to avoid undefined precision/recall.

**Code and data availability**

The training and inference code, pretrained model weights, and transferable application examples will be made publicly available upon publication. The data and scripts required to reproduce the main figures and tables will be made available to reviewers during the review process upon reasonable request. The full CARLNET observational data used in this study are subject to institutional data-management policies. These data will be released in subsequent data products together with the planned cloud-statistics and optical-parameter-retrieval datasets, where permitted by the relevant data-sharing policy.

~~**Supplement link**~~

~~No supplement is available for this manuscript.~~

~~**Team list**~~

~~Not applicable. This manuscript was not authored by a consortium or named research team.~~

**Author contributions**

WZ and ZY conceived the study and designed the research framework. WZ developed the cloud-layer identification model, implemented the training and inference workflow, performed the experiments, analysed the results, and prepared the initial manuscript draft. ZY supervised the study, contributed to the lidar-processing methodology and experimental design, and revised the manuscript. TS contributed to data processing, model implementation, and experimental analysis. ZB and YD contributed to CARLNET data resources, instrument-operation information, and interpretation of operational lidar observations. HW contributed to cloud and aerosol remote-sensing interpretation and validation discussion. LW contributed to lidar-methodology discussion and interpretation of Raman–polarization lidar observations. YH contributed to radiosonde-related analysis and cloud-structure interpretation. ShL and JC contributed to data organization, annotation support, and experimental checking. XW and SiL contributed to project supervision, resources, and scientific discussion. DM contributed

to conceptualization, lidar-remote-sensing interpretation, supervision, and manuscript revision. All authors reviewed and approved the final manuscript.

**Competing interests**

The authors declare that they have no conflict of interest.

**Disclaimer**

Copernicus Publications remains neutral with regard to jurisdictional claims made in the text, published maps, institutional affiliations, or any other geographical representation in this paper. While Copernicus Publications makes every effort to include appropriate place names, the final responsibility lies with the authors. Views expressed in the text are those of the authors and do not necessarily reflect the views of the publisher.

**Acknowledgements**

The authors thank the China Meteorological Administration and the CARLNET operation teams for maintaining the ground-based Raman lidar observations used in this study. The authors also acknowledge the support from the School of Remote Sensing and Information Engineering, Wuhan University, and the collaborating institutions involved in lidar operation, data processing, and scientific discussion. The radiosonde observations used for independent consistency checks are also gratefully acknowledged.

**Financial support**

This work was supported by the National Key Research and Development Program of China (grant no. 2023YFC3007802), the National Natural Science Foundation of China (grant nos. 42575141, 42475147, 42575138, and 62275202), and the Fundamental Research Funds for the Central Universities (grant no. 20251504004).

**Review statement**

The review statement will be added by Copernicus Publications listing the handling editor as well as all contributing referees according to their status anonymous or identified.

**References**


Alizadeh-Choobari, O. and Gharaylou, M.: Aerosol impacts on radiative and microphysical properties of clouds and precipitation formation, Atmos. Res., 185, 53–64, https://doi.org/10.1016/j.atmosres.2016.10.021, 2017.

Ansmann, A., Riebesell, M., and Weitkamp, C.: Measurement of atmospheric aerosol extinction profiles with a Raman lidar, Opt. Lett., 15, 746–748, https://doi.org/10.1364/OL.15.000746, 1990.

Baars, H., et al.: An overview of the first decade of PollyNET: An emerging network of automated Raman-polarization lidars for continuous aerosol profiling, Atmos. Chem. Phys., 16, 5111–5137, https://doi.org/10.5194/acp-16-5111-2016, 2016.

Baars, H., et al.: Target categorization of aerosol and clouds by continuous multiwavelength-polarization lidar measurements, Atmos. Meas. Tech., 10, 3175–3201, https://doi.org/10.5194/amt-10-3175-2017, 2017.

Campbell, J. R., et al.: Full-time, eye-safe cloud and aerosol lidar observation at Atmospheric Radiation Measurement Program sites: Instruments and data processing, J. Atmos. Ocean. Technol., 19, 431–442, https://doi.org/10.1175/1520-0426(2002)019<0431:FTESCA>2.0.CO;2, 2002.

Chisari, A. B., et al.: On the cloud detection from backscattered images generated from a lidar-based ceilometer: Current state and opportunities, in: Proc. IEEE Int. Conf. Image Process. (ICIP), 144–150, https://doi.org/10.1109/ICIP51287.2024.10647352, 2024.

Chisari, A. B., et al.: Benchmarking computer vision architectures for cloud detection from lidar ceilometer backscatter data, Vis. Comput., 41, 9441–9458, https://doi.org/10.1007/s00371-025-03960-3, 2025.

Clothiaux, E. E., et al.: An automated algorithm for detection of hydrometeor returns in micropulse lidar data, J. Atmos. Ocean. Technol., 15, 1035–1042, https://doi.org/10.1175/1520-0426(1998)015<1035:AAAFDO>2.0.CO;2, 1998.

Cordeiro, L. P., Gouveia, D. A., and Barbosa, H. M. J.: Diurnal cycle and seasonality of cirrus clouds over the Amazon from a seven-year ground-based lidar record, J. Geophys. Res. Atmos., 130, e2025JD044592, https://doi.org/10.1029/2025JD044592, 2025.

Cromwell, E. and Flynn, D.: Lidar cloud detection with fully convolutional networks, in: Proc. IEEE Winter Conf. Appl. Comput. Vis. (WACV), 619–627, https://doi.org/10.1109/WACV.2019.00071, 2019.

Fang, J., et al.: Seasonal variation and vertical characteristic of cirrus clouds at a midlatitude monsoon site from Ka-band cloud radar observation, Atmos. Res., 322, 108118, https://doi.org/10.1016/j.atmosres.2025.108118, 2025.

Fernald, F. G.: Analysis of atmospheric lidar observations: Some comments, Appl. Opt., 23, 652–653, https://doi.org/10.1364/AO.23.000652, 1984.

Floutsi, A. A., et al.: DeLiAn – a growing collection of depolarization ratio, lidar ratio and Ångström exponent for different aerosol types and mixtures from ground-based lidar observations, Atmos. Meas. Tech., 16, 2353–2379, https://doi.org/10.5194/amt-16-2353-2023, 2023.

Fu, C., Yang, Z., and Ji, C.: Aerosol identification based on Attention-UNet neural network, Chin. J. Lasers, 52, 1010001, https://doi.org/10.3788/CJL241202, 2025.

Hartmann, D. L., Ockert-Bell, M. E., and Michelsen, M. L.: The effect of cloud type on Earth's energy balance: Global analysis, J. Climate, 5, 1281–1304, https://doi.org/10.1175/1520-0442(1992)005<1281:TEOCTO>2.0.CO;2, 1992.

He, K., et al.: Masked autoencoders are scalable vision learners, arXiv [preprint], https://doi.org/10.48550/arXiv.2111.06377, 2021.

He, Y., Jing, D., Yin, Z., Ohneiser, K., and Yi, F.: Long-term (2010–2021) lidar observations of stratospheric aerosols in Wuhan, China, Atmos. Chem. Phys., 24, 11431–11450, https://doi.org/10.5194/acp-24-11431-2024, 2024.

Illingworth, A. J., et al.: Continuous evaluation of cloud profiles in seven operational models using ground-based observations, Bull. Amer. Meteor. Soc., 88, 883–898, https://doi.org/10.1175/BAMS-88-6-883, 2007.

Jiang, Y., Yao, H., Tao, S., and Liang, J.: Gated skip-connection network with adaptive upsampling for retinal vessel segmentation, Sensors, 21, 6177, https://doi.org/10.3390/s21186177, 2021.

Jing, D., et al.: Evolution of tropospheric aerosols over central China during 2010–2024 as observed by lidar, Atmos. Chem. Phys., 25, 17047–17067, https://doi.org/10.5194/acp-25-17047-2025, 2025.

Kalesse-Los, H., et al.: Evaluating cloud liquid detection against Cloudnet using cloud radar Doppler spectra and neural networks, Atmos. Meas. Tech., 15, 279–295, https://doi.org/10.5194/amt-15-279-2022, 2022.

Kanamitsu, M.: Description of the NMC Global Data Assimilation and Forecast System, Weather Forecast., 4, 335–342, https://doi.org/10.1175/1520-0434(1989)004<0335:DOTNGD>2.0.CO;2, 1989.

Klett, J. D.: Stable analytical inversion solution for processing lidar returns, Appl. Opt., 20, 211–220, https://doi.org/10.1364/AO.20.000211, 1981.

Loshchilov, I. and Hutter, F.: Decoupled weight decay regularization, in: Proc. Int. Conf. Learn. Represent. (ICLR), https://doi.org/10.48550/arXiv.1711.05101, 2019.

Mona, L., et al.: Lidar measurements for desert dust characterization: An overview, Adv. Meteorol., 2012, 356265, https://doi.org/10.1155/2012/356265, 2012.

Mylonaki, M., et al.: Aerosol type classification analysis using EARLINET multiwavelength and depolarization lidar observations, Atmos. Chem. Phys., 21, 2211–2227, https://doi.org/10.5194/acp-21-2211-2021, 2021.

Noel, V., et al.: The diurnal cycle of cloud profiles over land and ocean between 51°S and 51°N, seen by the CATS spaceborne lidar from the International Space Station, Atmos. Chem. Phys., 18, 9457–9473, https://doi.org/10.5194/acp-18-9457-2018, 2018.

Oktay, O., et al.: Attention U-Net: Learning where to look for the pancreas, arXiv [preprint], https://doi.org/10.48550/arXiv.1804.03999, 2018.

Pal, S. R., Steinbrecht, W., and Carswell, A. I.: Automated method for lidar determination of cloud-base height and vertical extent, Appl. Opt., 31, 1488–1494, https://doi.org/10.1364/AO.31.001488, 1992.

Peng, D., et al.: In situ balloon-borne observations of the vertical structure of relative humidity in Asian summer monsoon cirrus clouds, Geophys. Res. Lett., 53, e2025GL118090, https://doi.org/10.1029/2025GL118090, 2026.

Pruppacher, H. R. and Klett, J. D.: Microphysics of Clouds and Precipitation, 2nd rev. and enl. ed., Kluwer Academic Publishers, Dordrecht, the Netherlands, 954 pp., 1997.

Ronneberger, O., Fischer, P., and Brox, T.: U-Net: Convolutional networks for biomedical image segmentation, arXiv [preprint], https://doi.org/10.48550/arXiv.1505.04597, 2015.

Rossow, W. B. and Schiffer, R. A.: Advances in understanding clouds from ISCCP, Bull. Amer. Meteor. Soc., 80, 2261–2288, https://doi.org/10.1175/1520-0477(1999)080<2261:AIUCFI>2.0.CO;2, 1999.

Sassen, K.: The polarization lidar technique for cloud research: A review and current assessment, Bull. Amer. Meteor. Soc., 72, 1848–1866, https://doi.org/10.1175/1520-0477(1991)072<1848:TPLTFC>2.0.CO;2, 1991.

Sassen, K., Wang, Z., and Liu, D.: Global distribution of cirrus clouds from CloudSat/Cloud–Aerosol Lidar and Infrared Pathfinder Satellite Observations (CALIPSO) measurements, J. Geophys. Res. Atmos., 113, D00A12, https://doi.org/10.1029/2008JD009972, 2008.

Shao, N., et al.: China Aerosol Raman Lidar Network (CARLNET)—Part I: Water vapor Raman channel calibration and quality control, Remote Sens., 17, 414, https://doi.org/10.3390/rs17030414, 2025.

Thorsen, T. J., et al.: Macrophysical properties of tropical cirrus clouds from the CALIPSO satellite and from ground-based micropulse and Raman lidars, J. Geophys. Res. Atmos., 118, 9209–9220, https://doi.org/10.1002/jgrd.50691, 2013.

Thorsen, T. J., et al.: Automated retrieval of cloud and aerosol properties from the ARM Raman lidar. Part I: Feature detection, J. Atmos. Ocean. Technol., 32, 1977–1998, https://doi.org/10.1175/JTECH-D-14-00150.1, 2015.

Vainiger, A., et al.: Supervised learning calibration of an atmospheric lidar, in: Proc. IEEE Int. Geosci. Remote Sens. Symp. (IGARSS), 7317–7320, https://doi.org/10.1109/IGARSS46834.2022.9883078, 2022.

Vincent, P., et al.: Extracting and composing robust features with denoising autoencoders, in: Proc. Int. Conf. Mach. Learn. (ICML), 1096–1103, https://doi.org/10.1145/1390156.1390294, 2008.

Voudouri, K. A., et al.: Variability in cirrus cloud properties using a PollyXT Raman lidar, Atmos. Chem. Phys., 20, 4427–4444, https://doi.org/10.5194/acp-20-4427-2020, 2020.

Wang, M., Su, J., Peng, N., Xu, Y., and Ge, J.: Diurnal cycle of cirrus cloud and its associated radiative effects at the SACOL site, Atmos. Res., 265, 105887, https://doi.org/10.1016/j.atmosres.2021.105887, 2022.

Wang, Y., et al.: Improved retrieval of cloud base heights from ceilometer using a non-standard instrument method, Atmos. Res., 202, 148–155, https://doi.org/10.1016/j.atmosres.2017.11.021, 2018.

Wang, Z. and Sassen, K.: Cloud type and macrophysical property retrieval using multiple remote sensors, J. Appl. Meteorol. Climatol., 40, 1665–1682, https://doi.org/10.1175/1520-0450(2001)040<1665:CTAMPR>2.0.CO;2, 2001.

Wijnands, J. S., et al.: Deep-Pathfinder: A boundary layer height detection algorithm based on image segmentation, Atmos. Meas. Tech., 17, 3029–3045, https://doi.org/10.5194/amt-17-3029-2024, 2024.

Xie, Q., et al.: Self-training with noisy student improves ImageNet classification, in: Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 10684–10695, https://doi.org/10.1109/CVPR42600.2020.01070, 2020.

Yin, Z., Baars, H., Seifert, P., and Engelmann, R.: Automatic lidar calibration and processing program for multiwavelength Raman polarization lidar, EPJ Web Conf., 237, 08007, https://doi.org/10.1051/epjconf/202023708007, 2020.

Zhang, J., et al.: Cloud properties under different synoptic circulations: Comparison of radiosonde and ground-based active remote sensing measurements, Atmosphere, 7, 154, https://doi.org/10.3390/atmos7120154, 2016.

Zhao, C., et al.: Toward understanding of differences in current cloud retrievals of ARM ground-based measurements, J. Geophys. Res. Atmos., 117, D10206, https://doi.org/10.1029/2011JD016792, 2012.

Zhao, C., et al.: A new cloud and aerosol layer detection method based on micropulse lidar measurements, J. Geophys. Res. Atmos., 119, 6788–6802, https://doi.org/10.1002/2014JD021760, 2014.

Zhou, Q., et al.: Cloud-base and cloud-top heights determined from a ground-based cloud radar in Beijing, China, Atmos. Environ., 201, 381–390, https://doi.org/10.1016/j.atmosenv.2019.01.012, 2019.

Zou, W., et al.: Robust lidar–radar composite cloud boundary detection method with rainfall pixels removal, IEEE Trans. Geosci. Remote Sens., 62, 1–16, https://doi.org/10.1109/TGRS.2024.3476127, 2024.